

UNCLASSIFIED

296C-4

USCG-D-56-79

NIL

1 + 3

المجلة

(18) 21SCG, CGR/DC

Technical Report Documentation Page

1. Report No. (19) 19CG-D-56-79, 23/79		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle (6) COMPUTER SIMULATION OF GREAT LAKES-ST. LAWRENCE SEAWAY ICEBREAKER REQUIREMENTS		(11)		5. Report Date Jan 1980	
6. Author(s) (10) Thomas V. Kotras James J. Peter		(14)		7. Performing Organization Code 296C-4 RDC-23/79	
8. Performing Organization Name and Address ARCTEC, Incorporated 9104 Red Branch Road Columbia, Maryland 21045		(15)		9. Performing Organization Report No. DOT-CG-81-78-1953	
10. Sponsoring Agency Name and Address Department of Transportation U.S. Coast Guard R&D Center Avery Point Groton, CT 06340		(9)		11. Type of Report and Period Covered Final Report Oct 1978 - Jan 1980	
12. Supplementary Notes		(12) 195		13. Sponsoring Agency Code U.S. Coast Guard R&D Center	
14. Abstract This report describes a computer simulation developed as a planning tool to aid in establishing future icebreaker requirements for the Great Lakes-St. Lawrence Seaway as a function of projected cargo tonnage, trade routes, winter severity, vessel ice-transiting capabilities, vessel operating restrictions, and alternate icebreaking plans and operating concepts (direct assistance, convoying, and channel ice clearing). The simulation allows the user to determine benefits in terms of reduced commercial transit time, reduced shipping cost and increased fleet tonnage capacity; to assess the impact of user charges on shipping costs; and to investigate alternate fleet mixes of icebreakers and icebreaking tugs and their assigned areas of operation. The simulation has the following two operating modes: (1) a fixed fleet of icebreakers; and (2) maximum response time where the required icebreaker fleet is determined internally. In addition to describing the simulation, this report also presents validation of the simulation based on U.S. Coast Guard records for the 1975-76 winter navigation season, and the results, conclusions, and recommendations of ten (10) production runs performed to examine the effect on icebreaker requirements of: (1) 20% increase in cargo over the year 2000 projections; (2) convoys; (3) winter severity; (4) imposed vessel restrictions; (5) channel ice clearing; and (6) prohibiting ice-breaking tugs from convoying. Based on these runs, a preliminary icebreaker fleet for the Great Lakes was generated to handle the projected cargo in the year 2000.					
15. Key Words COMPUTER SIMULATION ICEBREAKER REQUIREMENTS GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION			16. Distribution Statement Document is available to the U.S. Public through the National Technical Information Service, Springfield, VA 22161		
17. Security Classif. (of this report) Unclassified		18. Security Classif. (of this page) Unclassified		19. No. of Pages 195	
20. Price Jm					

407822


METRIC CONVERSION FACTORS

Approximate Conversions to Metric Measures

Symbol	When You Know	Multiply by	To Find	Symbol
LENGTH				
in	inches	2.5	centimeters	cm
ft	feet	30	centimeters	cm
yd	yards	0.9	meters	m
mi	miles	1.6	kilometers	km
AREA				
sq in	square inches	6.5	square centimeters	cm ²
sq ft	square feet	0.09	square meters	m ²
sq yd	square yards	0.8	square meters	m ²
sq mi	square miles	2.6	square kilometers	km ²
acres	acres	0.4	hectares	ha
MASS (weight)				
oz	ounces	28	grams	g
lb	pounds	0.45	kilograms	kg
	short tons (2000 lb)	0.9	tonnes	t
VOLUME				
teaspoon	teaspoons	5	milliliters	ml
fluid ounce	fluid ounces	30	milliliters	ml
cup	cups	0.24	liters	l
quart	quarts	0.95	liters	l
gallon	gallons	3.8	liters	l
cu ft	cubic feet	0.03	cubic meters	m ³
cu yd	cubic yards	0.76	cubic meters	m ³
TEMPERATURE (exact)				
°F	Fahrenheit temperature	5/9 (after subtracting 32)	Celsius temperature	°C


Approximate Conversions from Metric Measures

Symbol	When You Know	Multiply by	To Find	Symbol
LENGTH				
mm	millimeters	0.04	inches	in
cm	centimeters	0.4	inches	in
m	meters	3.3	feet	ft
km	kilometers	1.1	miles	mi
		0.6	miles	mi
AREA				
cm ²	square centimeters	0.16	square inches	in ²
m ²	square meters	1.2	square yards	yd ²
ha	hectares (10,000 m ²)	0.4	square miles	mi ²
		2.5	acres	acres
MASS (weight)				
g	grams	0.035	ounces	oz
kg	kilograms	2.2	pounds	lb
t	tonnes (1000 kg)	1.1	short tons	lb
VOLUME				
ml	milliliters	0.03	fluid ounces	fl oz
l	liters	2.1	pints	pt
		1.06	quarts	qt
		0.26	gallons	gal
m ³	cubic meters	36	cubic feet	ft ³
		1.3	cubic yards	yd ³
TEMPERATURE (exact)				
°C	Celsius temperature	9/5 (then add 32)	Fahrenheit temperature	°F



Copyright © 1994 by The McGraw-Hill Companies, Inc. All rights reserved. Printed in the United States of America. This book is a reprint of the 1994 edition. ISBN 0-07-000000-0.

THE GREAT LAKES - ST. LAWRENCE SEAWAY SYSTEM



Accession For	
HTIS C.A.M.I	☒
DAG TAB	☐
Unannounced	☐
Justification	
By	
Date/Initial/	
Number of Pages	
Number of/or	
First Initial	
A	

TABLE OF CONTENTS

	Page
1. SUMMARY OF GREAT LAKES-ST. LAWRENCE SEAWAY ICEBREAKER REQUIREMENTS STUDY	1-1
2. INTRODUCTION	2-1
2.1 Objectives	2-1
2.2 Background	2-2
2.3 Method of Approach	2-5
3. DESCRIPTION OF GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION	3-1
3.1 Overview	3-1
3.2 Ice Growth Model	3-3
3.3 Ship Speed Generating Model	3-11
3.4 Ship Processing Model	3-21
3.5 Freight Rate/Report Generating Model	3-28
4. REACH SELECTION	4-1
5. ICEBREAKER AND SHIP CLASS SELECTION	5-1
6. RESULTS OF SIMULATION RUNS	6-1
6.1 Overview	6-1
6.2 Validation	6-3
6.3 Summary of Production Run Results	6-22
6.4 Discussion of Production Run Results	6-38
7. CONCLUSIONS	7-1
8. RECOMMENDATIONS	8-1
9. REFERENCES	9-1

LIST OF FIGURES

Figure	Page
2.1 Conceptual Block Diagram for Total Program	2-3
3.1 Conceptual Block Diagram for GL-SLS Navigation Simulation	3-2
3.2 Broken and Refrozen Ice in a Ship Track	3-7
3.3 Thrust-Velocity Relation	3-15

LIST OF FIGURES (Continued)

Figure		Page
3.4	Typical Thrust and Resistance Characteristics	3-18
3.5	Required Turn Width vs Channel Turn Radius and Turn Width vs Preventive Icebreaking Transits	3-20
4.1	Reaches Comprising the GL-SLS Navigation System	4-2
4.2	Reaches Comprising the GL-SLS Navigation System	4-3
5.1	Speed of Advance vs Unconsolidated Brash Ice Thickness (0 inches Refrozen Brash Ice)	5-8
5.2	Speed of Advance vs Unconsolidated Brash Ice Thickness (5 inches Refrozen Brash Ice)	5-9
5.3	Speed of Advance vs Unconsolidated Brash Ice Thickness (10 inches Refrozen Brash Ice)	5-10
5.4	Speed of Advance vs Unconsolidated Brash Ice Thickness (15 inches Refrozen Brash Ice)	5-11
5.5	Speed of Advance vs Unconsolidated Brash Ice Thickness (20 inches Refrozen Brash Ice)	5-12
6.1	Round Trip Time From Two Harbors to Gary for Class 5 Laker Vessel	6-19
6.2	Round Trip Time From Two Harbors to Gary for Class 8 Inland Vessel	6-20
6.3	Round Trip Time From Two Harbors to Gary for Class 10 Laker Vessel	6-21

LIST OF TABLES

Table		Page
1.1	Production Runs for Simulation of GL-SLS Icebreaker Requirements	1-4
1.2	Comparison of Simulation Generated Icebreaker Fleet with Coast Guard Estimated Fleet for Normal Winter	1-6
1.3	Comparison of Simulation Generated Icebreaker Fleet with Coast Guard Estimated Fleet for Severe Winter	1-7
3.1	Calendar Dates of Simulation Periods	3-4
4.1	List of Port Reaches	4-5
4.2	List of Channel and Lock Reaches	4-6
4.3	Freezing Degree Day Coefficients (α) and Brash Ice Porosity (β) for Each Reach	4-9
5.1	Laker Bulk Vessel Characteristics	5-2
5.2	Ocean-Going Bulk Vessel Characteristics	5-3
5.3	Ocean-Going General Cargo Characteristics	5-4
5.4	Icebreaker Characteristics	5-5
6.1	Occurrences of Lakers Becoming Stuck for Severe Winter and Heavy Traffic	6-4
6.2	Occurrences of Lakers Becoming Stuck for Severe Winter and Moderate Traffic	6-5
6.3	Occurrences of Lakers Becoming Stuck for Normal Winter and Heavy Traffic	6-6

LIST OF TABLES (Continued)

Table		Page
6.4	Occurrences of Lakers Becoming Stuck for Normal Winter and Moderate Traffic	6-7
6.5	1975-76 Validation Icebreaker Assignments	6-11
6.6	Laker Routes and Tonnages for 1975-76 Validation	6-12
6.7	Summary of 1975-76 Validation Run	6-14
6.8	Summary of 1975-76 Validation Run (MRT Mode)	6-16
6.9	Icebreaker Fleet Generated by 1975-76 Validation Run (MRT Mode)	6-18
6.10a	Production Runs for Simulation of GL-SLS Icebreaker Requirements	6-23
6.10b	USCG Estimated Fleet for Year 2000	6-24
6.11	Major Laker Trade Routes Projected for Year 2000	6-25
6.12	Simulation Salty Trade Routes Projected for Year 2000	6-28
6.13	Effect of Increased Cargo Tonnage on System	6-29
6.14	Effect of Increased Maximum Response Time on Icebreaker Requirements	6-30
6.15	Effect of Convoying on Icebreaker Requirements	6-31
6.16	Comparison of Maximum Response Time Mode with Fixed Icebreaker Fleet for a Normal Winter	6-32
6.17	Effect of Winter Severity on Icebreaker Requirements	6-33
6.18	Effect of Prohibiting Class C Icebreakers from Convoying	6-34
6.19	Effect of Increased Low SHP/Length Restriction on Icebreaking Requirements	6-35
6.20	Effect of Channel Clearing on Icebreaker Requirements	6-36
6.21	Comparison of Maximum Response Time Mode with Fixed Icebreaker Fleet for a Severe Winter	6-37
6.22a	Summary of Input Conditions for Run No. 1	6-39
6.22b	USCG Estimated Fleet for Normal Winter for Run No. 1	6-40
6.22c	Results of Run No. 1 for Taconite Task Command	6-41
6.22d	Results of Run No. 1 for Oil Can Task Command	6-42
6.22e	Results of Run No. 1 for Coal Shovel Task Command	6-43
6.22f	Results of Run No. 1 for Seaway Task Command	6-44
6.22g	Extended Season Tonnage by Route for Run No. 1	6-45
6.23a	Summary of Input Conditions for Run No. 2	6-46
6.23b	Predicted Icebreaker Fleet by Home Port and Period for Run No. 2	6-47
6.23c	Results of Run No. 2 for Taconite Task Command	6-48
6.23d	Results of Run No. 2 for Oil Can Task Command	6-49
6.23e	Results of Run No. 2 for Coal Shovel Task Command	6-50
6.23f	Results of Run No. 2 for Seaway Task Command	6-51
6.23g	Extended Season Tonnage by Route for Run No. 2	6-52
6.24a	Summary of Input Conditions for Run No. 3	6-53
6.24b	Predicted Icebreaker Fleet by Home Port and Period for Run No. 3	6-54
6.24c	Results of Run No. 3 for Taconite Task Command	6-55
6.24d	Results of Run No. 3 for Oil Can Task Command	6-56
6.24e	Results of Run No. 3 for Coal Shovel Task Command	6-57
6.24f	Results of Run No. 3 for Seaway Task Command	6-58
6.24g	Extended Season Tonnage By Route for Run No. 3	6-59

LIST OF TABLES (Continued)

Table		Page
6.25a	Summary of Input Conditions for Run No. 4	5-60
6.25b	USCG Estimated Fleet for Normal Winter for Run No. 4	6-61
6.25c	Results of Run No. 4 for Taconite Task Command	6-62
6.25d	Results of Run No. 4 for Oil Can Task Command	6-63
6.25e	Results of Run No. 4 for Coal Shovel Task Command	6-64
6.25f	Results of Run No. 4 for Seaway Task Command	6-65
6.25g	Extended Season Tonnage by Route for Run No. 4	6-66
6.26a	Summary of Input Conditions for Run No. 5	6-67
6.26b	Predicted Icebreaker Fleet by Home Port and Period for Run No. 5	6-68
6.26c	Results of Run No. 5 for Taconite Task Command	6-69
6.26d	Results of Run No. 5 for Oil Can Task Command	6-70
6.26e	Results of Run No. 5 for Coal Shovel Task Command	6-71
6.26f	Results of Run No. 5 for Seaway Task Command	6-72
6.26g	Extended Season Tonnage by Route for Run No. 6	6-73
6.27a	Summary of Input Conditions for Run No. 6	6-74
6.27b	Predicted Icebreaker Fleet by Home Port and Period for Run No. 6	6-75
6.27c	Results of Run No. 6 for Taconite Task Command	6-76
6.27d	Results of Run No. 6 for Oil Can Task Command	6-77
6.27e	Results of Run No. 6 for Coal Shovel Task Command	6-78
6.27f	Results of Run No. 6 for Seaway Task Command	6-79
6.27g	Extended Season Tonnage by Route for Run No. 6	6-80
6.28a	Summary of Input Conditions for Run No. 7	6-81
6.28b	Predicted Icebreaker Fleet by Home Port and Period for Run No. 7	6-82
6.28c	Results of Run No. 7 for Taconite Task Command	6-83
6.28d	Results of Run No. 7 for Oil Can Task Command	6-84
6.28e	Results of Run No. 7 for Coal Shovel Task Command	6-85
6.28f	Results of Run No. 7 for Seaway Task Command	6-86
6.28g	Extended Season Tonnage by Route for Run No. 7	6-87
6.29a	Summary of Input Conditions for Run No. 8	6-88
6.29b	Predicted Icebreaker Fleet by Home Port and Period for Run No. 8	6-89
6.29c	Results of Run No. 8 for Taconite Task Command	6-90
6.29d	Results of Run No. 8 for Oil Can Task Command	6-91
6.29e	Results of Run No. 8 for Coal Shovel Task Command	6-92
6.29f	Results of Run No. 8 for Seaway Task Command	6-93
6.29g	Extended Season Tonnage by Route for Run No. 8	6-94
6.30a	Summary of Input Conditions for Run No. 9	6-95
6.30b	Predicted Icebreaker Fleet by Home Port and Period for Run No. 9	6-96
6.30c	Results of Run No. 9 for Taconite Task Command	6-97
6.30d	Results of Run No. 9 for Oil Can Task Command	6-98
6.30e	Results of Run No. 9 for Coal Shovel Task Command	6-99
6.30f	Results of Run No. 9 for Seaway Task Command	6-100
6.30g	Extended Season Tonnage by Route for Run No. 9	6-101
6.31a	Summary of Input Conditions for Run No. 10	6-102
6.31b	USCG Estimated Fleet for Severe Winter for Run No. 10	6-103

LIST OF TABLES (Continued)

Table		Page
6.31c	Results of Run No. 10 for Taconite Task Command	6-104
6.31d	Results of Run No. 10 for Oil Can Task Command	6-105
6.31e	Results of Run No. 10 for Coal Shovel Task Command	6-106
6.31f	Results of Run No. 10 for Seaway Task Command	6-107
6.31g	Extended Season Tonnage by Route for Run No. 10	6-108
7.1	Comparison of Simulation Generated Icebreaker Fleet with Coast Guard Estimated Fleet for Normal Winter	7-2
7.2	Comparison of Simulation Generated Icebreaker Fleet with Coast Guard Estimated Fleet for Severe Winter	7-3

1. SUMMARY OF GREAT LAKES-ST. LAWRENCE SEAWAY ICEBREAKER REQUIREMENTS STUDY

OBJECTIVES

The overall objective of this study was to develop a planning tool for use by the U.S. Coast Guard to aid in establishing their future icebreaking requirements for the Great Lakes-St. Lawrence Seaway (GL-SLS) Navigation System as a function of projected cargo tonnage, trade routes, winter severity, vessel ice transiting capabilities, vessel operating restrictions, and alternate ice-breaking plans and concepts of operation (direct assistance, convoys, channel maintenance, and channel ice clearing). More specifically, the objectives were to modify the existing GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION so that it could be used as a tool to aid in:

- Determining Coast Guard icebreaker requirements for the Great Lakes-St. Lawrence Seaway.
- Determining benefits in terms of reduced commercial vessel transit time and shipping cost and increased fleet tonnage capacity derived from the presence of icebreakers.
- Determining the impact of user charges to help defray costs of icebreaking assistance and channel maintenance during extended navigation season operations.*
- Determining the impact of establishing minimum ship operating requirements, such as SHP/length for ships operating during the extended season.
- Investigating proposed alternate icebreaking plans and concepts of operation (direct assistance, convoys, channel maintenance, and channel ice clearing).
- Examining different fleet mixes of icebreakers and icebreaking tugs and their assigned areas.
- Determining the impact of short term variations in ice conditions on icebreaking effectiveness and requirements.

METHOD OF APPROACH

The GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION was developed by ARCTEC for the North Central Division of the U.S. Army Corps

* Capability included but not examined in this study.

of Engineers and subsequently expanded for the St. Lawrence Seaway Development Corporation to model the movement of ships and cargo within the Great Lakes-St. Lawrence Seaway Navigation System and to and from world areas, during both normal and winter navigation seasons. In simulating the movement of ships and cargo, the model incorporates the following interactions between ships and the system, as well as the interactions between the ships themselves:

- Port and lock limitations and constraints
- Draft limitations
- Speed limits
- Daylight only navigation
- Queues forming, expanding, and diminishing at lock and port facilities
- Increased transit, lockage, and port times due to the presence of ice during extended season operations
- Ships getting stuck in ice and having to wait for icebreaker assistance
- Ships having to convoy and wait for icebreaker escort.

To accomplish the stated objectives, the following modifications were made to the existing simulation:

- Revised ice conditions data in the simulation to better reflect normal and severe winter conditions for light, moderate, and heavy commercial navigation.
- Developed and incorporated a complete set of icebreaker operating subroutines capable of modeling the following modes of icebreaking operations: preventive icebreaking, convoying, and direct assistance for vessels stuck in ice.
- Modified the simulation to include the capability for icebreaker user charges in vessel operating costs.
- Modified the simulation to generate icebreaker statistics, such as number of vessels assisted, total time assisting vessels, response time, and operating hours, to be used to assess icebreaker efficiency and cost of operations.
- Revised icebreaker characteristics in the simulation to better reflect existing, planned, and proposed icebreakers.
- Revised the program to permit two study options: in the first, a fixed fleet of icebreakers is defined; in the second, a maximum response time (variable with area of operation) is defined and the icebreaking fleet determined accordingly.

- Provided data files which can be modified to assess the effect of short term variations in ice conditions on the ability of the icebreaker fleet to maintain commercial navigation.
- Modified the computer simulation as needed to clearly identify all savings in commercial vessel transit times attributable to icebreaker operations when comparing simulation runs with and without icebreaker support.

Once the modifications were incorporated, the simulation was validated using U.S. Coast Guard icebreaking records for the 1975-1976 winter navigation season. Upon completion of the simulation validation, a series of ten (10) production runs, listed in Table 1.1, were performed and analyzed to assess the following:

- Effect of a 20% increase in cargo tonnage with a fixed fleet of icebreakers (normal winter).
- Effect of a 12-hour variation in maximum response time on icebreaker requirements (normal winter).
- Effect of convoys on icebreaker requirements (normal winter).
- Comparison of the maximum response time (MRT) generated icebreaker fleet to the USCG estimated fleet (normal winter).
- Effect of winter severity (normal vs severe) on icebreaker requirements.
- Effect of having only Class B icebreakers escort convoys, as opposed to both Class B and Class C icebreakers, on icebreaker requirements (severe winter).
- Effect of prohibiting vessels with low SHP from operating in the extended season on icebreaker requirements (severe winter).
- Effect of conducting channel clearing in certain channels on icebreaker requirements (severe winter).
- Comparison of the maximum response time (MRT) generated icebreaker fleet to the USCG estimated fleet (severe winter).

TABLE 1.1
PRODUCTION RUNS FOR SIMULATION OF
GL-SLS ICEBREAKER REQUIREMENTS

RUN NO.	WINTER TYPE	MINIMUM LAKER CLASS	RUN MODE ¹	USCG ESTIMATED FLEET	MRT (hr)	CONVOYING IB TYPES ²	CHANNEL CLEARING ² (in/2wks)	CARGO TONNAGE (year)
1	Normal	5	FIBF	Normal ⁵	---	C,B	---	2000
2	Normal	5	MRT	---	Min ³	C,B	---	2000
3	Normal	5	MRT	---	Min+12	C,B	---	2000
4	Normal	5	FIBF	Normal ⁵	---	C,B	---	2000+20%
6	Normal	5	MRT	---	Min+12	No Convoys	---	2000
5	Severe	5	MRT	---	Min+12	B	---	2000
7	Severe	5	MRT	---	Min+12	C,B	---	2000
8	Severe	6	MRT	---	Min+12	C,B	---	2000 ⁴
9	Severe	6	MRT	---	Min+12	C,B	12	2000 ⁴
10	Severe	6	FIBF	Severe ⁵	---	C,B	---	2000 ⁴

NOTES:

- ¹ FIBF = Fixed icebreaker fleet; MRT = Maximum response time.
- ² Convoys and channel clearing in: St. Marys River/Whitefish Bay, Straits of Mackinac, Detroit/St. Clair Rivers, Welland Canal, St. Lawrence Seaway.
- ³ Minimum time is that required to get to furthest point in reach from closest home port at 5 mph.
- ⁴ Cargo tonnage on restricted ships assumed carried in normal season.
- ⁵ USCG estimated icebreaker fleet listed in Table 6.10b.

COMPARISONS:

- 1,4 -Effect of increased cargo tonnage (20%)(normal winter).
- 2,3 -Effect of variation in maximum response time (normal winter).
- 3,1 -Difference between MRT generated icebreaker fleet and fixed icebreaker fleet (normal winter)
- 3,6 -Effect of convoys (normal winter).
- 3,7 -Effect of winter severity.
- 5,7 -Effect of not allowing Class C icebreakers to convoy (severe winter).
- 7,8 -Effect of vessel class restriction (severe winter).
- 8,9 -Effect of channel clearing (severe winter).
- 8,10-Difference between MRT generated icebreaker fleet and fixed icebreaker fleet (severe winter).

A summary of the results of the production runs, along with a discussion of the above items, are presented in Section 6 of this report. Based on those results and discussions, the following conclusions and recommendations were drawn:

CONCLUSIONS

1. Usefulness of the Simulation - Based on the validation presented in Section 6.2 and the experience and knowledge we have gained from working with the model, from conversations with ship operators, port officials, and personnel at Coast Guard, MarAd, Corps of Engineers, and the St. Lawrence Seaway Development Corporation, we believe the simulation, as developed, realistically models the Great Lakes-St. Lawrence Seaway System. As a result, it can be used as a valuable tool to aid in the planning process of the Coast Guard in establishing their future icebreaking requirements and alternate icebreaking plans and concepts of operation.
2. Normal and Severe Winter Icebreaker Fleets* - Using the results of the simulation for the fixed icebreaker fleet runs and the generated icebreaker fleet runs, simulation estimated icebreaker fleets were prepared and are presented in Tables 1.2 and 1.3 along with the Coast Guard estimated fleets for normal and severe winters. In finalizing the simulation fleet, consideration was given to additional icebreaking demands, such as preventive icebreaking and channel maintenance. In comparing the results of the simulation to those of the Coast Guard, it is interesting to note how closely they compared in number with some shifting in location. *It is important to note that the size and location of the fleet is completely dependent upon the magnitude of the projected tonnage during the extended navigation season and the projected trade routes. A change in either the magnitude of tonnage or trade route can alter the icebreaker requirements significantly.*
3. Formation of New Task Command for Duluth/Superior - Icebreakers in the simulation for the fixed fleet mode continually traveled across Lake Superior to provide assistance in both Duluth/Superior and at the Soo since assistance was provided on a first come-first serve basis. As a result, a large amount of time was spent transiting Lake Superior compared to time spent either assisting or convoying. For example, in Run 1 for the normal winter, the fixed fleet of 7 Class C and 3 Class B icebreakers operated at 100% utilization performing 781 direct assists and escorting 629 convoys. Of the 100% utilization in periods 5, 6, and 7, only 10%,

* Rationale for simulation generated fleet presented in Section 7

TABLE 1.2

COMPARISON OF SIMULATION GENERATED
ICEBREAKER FLEET WITH COAST GUARD ESTIMATED FLEET
FOR NORMAL WINTER

Task Command & Home Port	U.S. COAST GUARD ESTIMATED ICEBREAKER FLEET				SIMULATION GENERATED ICEBREAKER FLEET			
	Icebreaker Class				Icebreaker Class			
	B	C	D	TOTAL	B	C	D	TOTAL
<u>Taconite Command</u>								
Duluth/Superior	-	2	-	2	2	-	-	2
Presque Isle	-	-	-	-	-	-	-	-
Sault Ste. Marie	2	4	-	6	1	5	-	6
St. Ignace	<u>1</u>	<u>1</u>	<u>-</u>	<u>2</u>	<u>-</u>	<u>2</u>	<u>-</u>	<u>2</u>
TOTAL	3	7	-	10	3	7	-	10
<u>Oil Can Command</u>								
Escanaba	-	1	-	1	-	2	-	2
Green Bay	-	-	-	-	-	-	-	-
Milwaukee	-	-	-	-	-	-	-	-
Chicago	-	1	-	1	-	-	-	-
Grand Haven	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>
TOTAL	-	2	-	2	-	2	-	2
<u>Coal Shovel Command</u>								
Saginaw	-	-	-	-	-	-	-	-
Port Huron/Detroit/ Toledo	1	2	-	3	-	5	-	5
Sandusky	-	1	-	1	-	-	-	-
Buffalo	<u>1</u>	<u>2</u>	<u>-</u>	<u>3</u>	<u>1</u>	<u>2</u>	<u>-</u>	<u>3</u>
TOTAL	2	5	-	7	1	7	-	8
<u>Seaway Command</u>								
Oswego	-	3	-	3	-	-	-	-
Alexandria Bay	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>4</u>	<u>-</u>	<u>4</u>
TOTAL	-	3	-	3	-	4	-	4
TOTAL	5	17	-	22	4	20	-	24

TABLE 1.3
COMPARISON OF SIMULATION GENERATED
ICEBREAKER FLEET WITH COAST GUARD ESTIMATED FLEET
FOR SEVERE WINTER

Task Command & Home Port	U.S. COAST GUARD ESTIMATED ICEBREAKER FLEET				SIMULATION GENERATED ICEBREAKER FLEET			
	Icebreaker Class				Icebreaker Class			
	B	C	D	TOTAL	B	C	D	TOTAL
<u>Taconite Command</u>								
Duluth/Superior	1	2	-	3	2	2	-	4
Presque Isle	-	-	-	-	-	-	-	-
Sault Ste. Marie	3	6	-	9	2	6	-	8
St. Ignace	<u>2</u>	<u>2</u>	<u>2</u>	<u>6</u>	<u>1</u>	<u>3</u>	<u>-</u>	<u>4</u>
TOTAL	6	10	2	18	5	11	-	16
<u>Oil Can Command</u>								
Escanaba	-	1	-	1	1	-	1	2
Green Bay	-	-	-	-	-	1	-	1
Milwaukee	-	-	-	-	-	-	-	-
Chicago	1	2	-	3	-	1	-	1
Grand Haven	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>
TOTAL	1	3	-	4	1	2	1	4
<u>Coal Shovel Command</u>								
Saginaw	2	3	-	5	-	-	-	-
Port Huron/Detroit/ Toledo	1	4	-	5	1	5	2	8
Sandusky	1	2	-	3	-	2	-	2
Buffalo	<u>1</u>	<u>4</u>	<u>-</u>	<u>5</u>	<u>3</u>	<u>5</u>	<u>-</u>	<u>8</u>
TOTAL	5	13	-	18	4	12	2	18
<u>Seaway Command</u>								
Oswego	-	3	-	3	-	-	-	-
Alexandria Bay	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>1</u>	<u>3</u>	<u>-</u>	<u>4</u>
TOTAL	-	3	-	3	1	3	-	4
TOTAL	12	29	2	43	11	28	3	42

20%, and 29% of the total direct assist miles and 20%, 58% and 44% of the total convoy miles were spent in actual assistance and convoying for each period, respectively. In comparison, the somewhat larger MRT generated fleet, which was restricted to operating within assigned areas near the icebreaker's home port, averaged 61%, 74%, and 75% of total direct assistance miles and 74%, 70%, and 66% of total convoy miles performing actual direct assistance and convoying in periods 5, 6, and 7, respectively. Future runs should have a 200 mile limitation placed on an icebreaker's area of operation to prohibit crossing Lake Superior, thereby effectively making Duluth/Superior a separate task command.

4. Effect of Increased Tonnage - For the fixed normal winter icebreaker fleet, the designated icebreakers in Oil Can and Coal Shovel could handle the 20% increased tonnage above the projected year 2000 tonnage with no significant problems. For the Seaway, the 3 Class C icebreakers operated at 100% utilization in periods 5 through 8 escorting 173 convoys between Alexandria Bay and Cornwall. Based on the MRT runs 2 and 3, 5 or 6 Class C icebreakers or 1 Class B plus 3 Class C icebreakers are probably required to escort all vessels in convoys at a reasonable icebreaker utilization rate. In Taconite, the fixed fleet operated at 100% utilization because a large portion of the time was spent by icebreakers transiting between Duluth/Superior and the Soo. Based on the MRT runs 2 and 3, in which icebreakers are restricted to operating within assigned areas near the icebreaker's home port, the specified fixed fleet of 7 Class C and 3 Class B icebreakers needs to be increased to 9 Class C and 4 Class B icebreakers with Duluth/Superior being treated as a separate task command.
5. Effect of Increased Maximum Response Time - For Taconite, Oil Can and Coal Shovel Task Commands, there appeared to be only a slight effect on the generated icebreaker fleet due to increasing the MRT by 12 hours. For the Seaway, the maximum number of required Class C icebreakers dropped from 6 to 5.
6. Effect of Convoying - For Oil Can and Coal Shovel, where there were no convoys, the effect of convoying was a change in the arrival of ships from other commands which altered the generated icebreaker fleet slightly. For the Seaway, the elimination of convoying reduced the icebreaker requirements significantly since salties, which were capable of proceeding on their own, were being forced to convoy, thereby requiring more icebreakers. In Taconite, elimination of convoying caused the generated icebreaker fleet to double in periods 5 through 10.

7. Effect of Winter Severity - As one would expect, the ice-breaking requirements increased with increasing winter severity. In Taconite, the total number of direct assists increased from 792 to 1032 and the total number of convoys increased from 699 to 937, resulting in an increase of required icebreakers from an average of 11 to 20, with an increase in Class B icebreakers from an average of 4 to approximately 6. In Oil Can, the total number of direct assists increased from 86 to 102, but because the location of the problem reach was closer to the icebreaker home port of Escanaba, fewer icebreakers were required during the severe year. The reason for this seemingly contradictory trend is a result of the use of actual historical weather and ice data which is sometimes inconsistent. In Coal Shovel, the number of direct assists increased by almost 200% from 198 to 573 with 347 convoys being escorted during the severe winter. This resulted in the number of icebreakers being doubled with an average of 4 Class B icebreakers being required during the severe winter while none were required during the normal winter. For the Seaway, the total number of direct assists increased from zero in the normal winter to 40 in the severe winter, but the total number of convoys decreased from 185 to 154. This reduction was due to Class B icebreakers being generated instead of Class C icebreakers (Class B icebreakers can handle twice as many ships per convoy as can Class C icebreakers). For the normal winter, between 3 and 5 Class C icebreakers were required, while for the severe winter the icebreaker fleet ranged from 1 Class D and 4 Class C icebreakers to 4 Class B icebreakers.
8. Effect of Prohibiting Class C Icebreakers from Convoing - For Oil Can and Coal Shovel, restricting Class C icebreakers from convoing did not significantly reduce the number of icebreakers generated. For Coal Shovel, however, it did tend to replace each Class C icebreaker eliminated with an equal number of Class B icebreakers, indicating that the increased convoing capability of Class B icebreakers was not utilized. For the Seaway, the maximum generated icebreaker fleet changed from 11 Class C icebreakers to 1 Class C and 4 Class B icebreakers for period 6. At Taconite, for all periods, the average total number of icebreakers required decreased by 21%, with Class C icebreakers almost completely eliminated and 1 additional Class B icebreaker added for every 2 Class C icebreakers eliminated.
9. Effect of Increased SHP/Length Restriction - The removal of Class 5 laker vessels (SHP/lengths = 6.25) from the fleet reduced the icebreaking requirements significantly in all task commands. In Taconite, the number of direct assists dropped from 1032 to 671 and the number of convoys escorted dropped from 937 to 587. This resulted in a reduction of

the generated icebreaker fleet by more than 50%. In Oil Can the number of direct assists decreased from 102 to 11, resulting in a reduction in the number of icebreakers from an average of 5 icebreakers in periods 3 through 7 to an average of 1 icebreaker in periods 6 and 7. In Coal Shovel, with the exception of period 7, the number of required icebreakers decreased by a factor of 2 due to the total number of direct assists dropping from 573 to 337 and the elimination of 347 convoys. In the Seaway, the total number of direct assists decreased from 40 to 20 and the total number of convoys decreased slightly from 160 to 154, resulting in a reduction in icebreaking requirements by approximately one third.

10. Effect of Channel Clearing - The primary effect of channel clearing which, in run 9, was performed in reaches where convoying occurred, was to: (1) decrease the size of icebreakers required for convoying, and (2) increase icebreaker speeds which allowed each icebreaker to effectively handle more convoys, at times comprised of fewer ships due to ship arrival frequency. For Oil Can and Coal Shovel where there was no convoying, almost no effect from channel clearing was observed. In the Seaway, both the size and number of icebreakers were reduced. For example, in period 6, 8 Class C icebreakers were replaced by 5 Class C icebreakers with channel clearing. In period 7, 5 Class B icebreakers were replaced with 3 Class B icebreakers and 1 Class C. For Taconite, a similar condition occurred in that both the number and size of icebreakers were reduced. In period 8, the required 12 icebreakers (8 Class C and 4 Class B) were replaced by 7 icebreakers (5 Class C and 2 Class B).

RECOMMENDATIONS

1. The GL-SLS NAVIGATION SIMULATION should be kept current by revising the input data files and changing the basic rules and assumptions as required. We believe this simulation is an excellent planning tool which can be used as an aid to the U.S. Coast Guard in establishing their future icebreaking requirements and evaluating alternate icebreaker plans and concepts of operation, such as direct assistance, convoying, channel maintenance and channel ice clearing, as to their impact on extended commercial navigation operations and economics. In addition, the simulation can be used by the Corps of Engineers as a planning tool to aid in their assessment of the potential benefits and impacts of various proposed GL-SLS System improvements for normal navigation season operations as well as extended navigation season operations.

2. We also recommend that, as additional extended navigation season operations continue and more icebreaker operational data is gathered, additional validation runs be performed to ensure the continued credibility of the simulation.
3. To gain further insight and a more comprehensive understanding of the impacts on icebreaker requirements and commercial navigation operations and economics, we recommend that additional sensitivity runs be performed on:
 - Variations of fixed icebreaker fleets and home ports
 - Variations in channel clearing and preventive icebreaking
 - Variations in MRT mode conditions
 - Variations in ice conditions
 - Variations in low SHP/length restriction
4. During the course of modifying the simulation and conducting the runs, we found that the following revisions to the simulation should be considered:
 - Revise Fixed Fleet Mode to prohibit icebreakers from traveling over long distances within a task command, such as an icebreaker continually traversing Lake Superior between Duluth/Superior and the Soo.
 - Incorporate a probability basis for ships getting or not getting stuck rather than the current assumption of all ships of a given class getting stuck if their speed of advance is less than 2 mph; that is, apply a probability distribution which would vary linearly with the speed of advance between a probability of getting stuck equal to 1 at some designated speed, and a probability equal to 0.0 at some higher designated speed. In this manner, the "off-on" switch for all ships in a given class either being or not being stuck would be eliminated.
 - For ease of data analysis, revise the REPORT GENERATING MODEL to provide summary tables similar to those listed in Section 6.4 for each run.

2. INTRODUCTION

2.1 Objectives

The overall objective of this study was to develop a planning tool for use by the U.S. Coast Guard to aid in establishing their future icebreaking requirements for the Great Lakes-St. Lawrence Seaway (GL-SLS) Navigation System as a function of projected cargo tonnage, trade routes, winter severity, vessel ice transiting capabilities, vessel operating restrictions and alternate icebreaking plans and concepts of operation (direct assistance, convoys, channel maintenance, and channel ice clearing). More specifically, the objectives were to modify the existing GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION so that it could be used as a tool to aid in:

- Determining Coast Guard icebreaker requirements for the Great Lakes-St. Lawrence Seaway.
- Determining benefits in terms of reduced commercial vessel transit time and shipping cost and increased fleet tonnage capacity derived from the presence of icebreakers.
- Determining the impact of user charges to help defray costs of icebreaking assistance and channel maintenance during extended navigation season operations.
- Determining the impact of establishing minimum ship operating requirements, such as SHP/length for ships operating during the extended season.
- Investigating proposed alternate icebreaking plans and concepts of operation (direct assistance, convoys, channel maintenance, and channel ice clearing).
- Examining different fleet mixes of icebreakers and icebreaking tugs and their assigned areas.
- Determining the impact of short term variations in ice conditions on icebreaking effectiveness and requirements.

2. INTRODUCTION

2.2 Background

The existing GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION was developed by ARCTEC for the North Central Division of the U.S. Army Corps of Engineers under Contract No. DACW-23-75-C-0043 [1]* and subsequently expanded for the St. Lawrence Seaway Development Corporation under Contract No. DOT-SL-70-467 [2] to model the movement of ships and cargo within the Great Lakes-St. Lawrence Seaway Navigation System and to and from world areas, during both the normal and winter navigation seasons. This existing simulation was developed as one part (Phase II) of a total program referred to as the GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SYSTEM STUDY, which was comprised of the following phases:


- PHASE I: TRAFFIC FORECAST STUDY
 - A. Preliminary Traffic Forecast
1980-2040
 - B. Shipper Preference Study
 - C. Development of a CARGO FLOW MODEL
- PHASE II: RATE AND COST STUDY
 - A. Normal Season
 - B. Extended Season
- PHASE III: SYSTEM INTERRELATIONSHIP STUDY
 - A. System Capacity
 - B. System Optimization

In Phase I, the primary objective was to develop a method of estimating future traffic suitable for waterborne movement in the GL-SLS System. This phase consisted of a Preliminary Traffic Forecast of U.S. and Canadian general cargo, grain, and mineral bulk commodities for the years 1980-2040, followed by a Shipper Preference Survey and development of a CARGO FLOW MODEL. The output from Phase I were then used as input into Phase II (Development of the GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION) to provide an estimate of the impact on annual vessel operating costs and the associated required freight rates.

Using the results of Phases I and II, an overall computer model of the GL-SLS System was to be developed in Phase III to study the system's capacity and to evaluate the potential benefits of proposed improvements. A conceptual flow diagram [3] depicting the model is given in Figure 2.1. The WINTER RATE STUDY contained in Figure 2.1 corresponds to the model (GL-SLS SIMULATION) described in this report. As seen from the flow diagram, the CARGO FLOW MODEL converts the hinterland cargo forecast information, length of the navigation season and initial rate and cost data into cargo forecast data. This cargo forecast data, in the form of cargo origin and destination data, along with the

* Numbers in brackets denote references listed in Section 9 of the report.

FIGURE 2.1
CONCEPTUAL BLOCK DIAGRAM FOR TOTAL PROGRAM



length of the navigation season, fleet mix, vessel characteristics, winter severity, and improvement levels, is entered into the GL-SLS SIMULATION which models the movement of ships and cargo through the system and to and from overseas ports. The SIMULATION computes statistics for each class of ship operating on each route and converts these statistics into annual vessel operating costs and the associated annual required freight rates for each route. In simulating the movements of ships and cargo, the model incorporates the following interactions between ships and the system, as well as the interaction between the ships themselves:

- Port and lock limitations and constraints
- Draft limitations
- Speed limits
- Daylight only navigation
- Queues forming, expanding, and diminishing at lock and port facilities
- Increased transit, lockage, and port times due to presence of ice during extended season operations
- Ships getting stuck in ice and having to wait for icebreaker assistance
- Ships having to convoy and wait for icebreaker escort.

The Corps of Engineers model, as seen from the flow diagram, is an iterative one in which the output from the CARGO FLOW MODEL is required as input to the SIMULATION and vice versa. The program can therefore be thought of as a spiral in which several iterations are required to achieve a final solution. Where the spiral is entered is relatively unimportant as long as reasonable initial input data is available and a sufficient number of iterations are performed. Once a solution within the required accuracy is obtained, the annual required freight rates and annual vessel operating costs are fed back into the CARGO FLOW MODEL and the cycle is repeated until an overall solution is achieved within the desired accuracy limits on annual cargo throughput and required freight rates. The final results are then entered into the IMPACT MODEL of the Bureau of Economic Analysis (BEA) to determine the direct and indirect benefits.

2. INTRODUCTION

2.3 Method of Approach

To accomplish the stated objectives, the method of approach was to modify the existing simulation in the following ways:

- Revised ice conditions data in the simulation to better reflect normal and severe winter conditions for light, moderate, and heavy commercial navigation.
- Developed and incorporated a complete set of icebreaker operating subroutines capable of modeling the following modes of icebreaking operations: preventive icebreaking, convoying, and direct assistance for vessels stuck in ice.
- Modified the simulation to include the capability for icebreaker user charges in vessel operating costs.
- Modified the simulation to generate icebreaker statistics, such as number of vessels assisted, total time assisting vessels, response time, and operating hours, to be used to assess icebreaker efficiency and cost of operations.
- Revised icebreaker characteristics in the simulation to better reflect existing, planned, and proposed icebreakers.
- Revised the program to permit two study options: in the first, a fixed fleet of icebreakers is defined; in the second, a maximum response time (variable with area of operation) is defined and the icebreaking fleet determined accordingly.
- Provided data files which can be modified to assess the effect of short term variations in ice conditions on the ability of the icebreaker fleet to maintain commercial navigation.
- Modified the computer simulation as needed to clearly identify all savings in commercial vessel transit times attributable to icebreaker operations when comparing simulation runs with and without icebreaker support.

Once the modifications were incorporated, the simulation was validated using U.S. Coast Guard icebreaking records for the 1975-1976 winter navigation

season. Upon completion of the simulation validation, a series of ten (10) runs, listed in Section 6.3, were performed and analyzed to assess the impact of winter severity, vessel restrictions, icebreaker fleet, use of convoys, and channel ice clearing. The results, along with the conclusions and recommendations drawn from these runs, are presented in Sections 6, 7, and 8 of this report.

3. DESCRIPTION OF GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION

3.1 Overview

As stated in the Introduction, the GL/SLS NAVIGATION SIMULATION was developed initially as the Winter Rate Study [1] for the North Central Division of the U.S. Army Corps of Engineers. The purpose of this computer simulation was to model the movement of ships and cargo, during both the normal and winter navigation seasons within the Great Lakes-St. Lawrence Seaway System, and to and from overseas ports. In simulating the movement of ships and cargo, the model incorporated both the interactions between ships and the system, and the interactions between the ships themselves, such as:

- Port and lock limitations and constraints
- Draft limitations
- Speed limits
- Daylight only navigation
- Queues forming, expanding, and diminishing at lock and port facilities
- Increased transit, lockage, and port times due to presence of ice during extended season operations
- Ships getting stuck in ice and having to wait for icebreaker direct assistance
- Ship convoying with icebreaker escort through critical areas.

During the running of the simulation, statistics are compiled for each class of ship operating on each route. These statistics, along with vessel data, are converted into icebreaker performance measures, annual vessel operating costs, annual required freight rates, and performance measures for each route.

In order to develop a computer simulation which has sufficient detail to yield reasonable results while requiring a minimum of computer time, the total simulation model was divided into the following four individual models:

- ICE GROWTH MODEL
- SHIP SPEED GENERATING MODEL
- SHIP PROCESSING MODEL
- FREIGHT RATE/REPORT GENERATING MODEL

The relationship of these four models to one another and to the input data is illustrated by the block diagram shown in Figure 3.1. By dividing the total simulation model in this manner, repetitive calculations, such as determining the transit speed with which a particular vessel class traverses a given reach, need only be performed once and stored in a data file for use every time a ship of that vessel class traverses the reach. Each of these models is described briefly in the following subsections.




Figure 3.1. Conceptual Block Diagram for GL-SLS Navigation Simulation

3. DESCRIPTION OF GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION

3.2 Ice Growth Model

3.2.1 Purpose

For simulation runs that extend into winter operations, the purpose of the ICE GROWTH MODEL is to prepare a data file which contains

- Ice type as a function of level of traffic
- Ice thickness as a function of temperature, location, and level of traffic
- Channel width in a turn as a function of preventive icebreaking

in each reach for every two week time period. This data file is then used by the SHIP SPEED GENERATING MODEL to determine the speed of advance of each vessel class in each reach for every time period in the simulation. The calendar dates of the simulation time periods are given in Table 3.1.

3.2.2 Method of Approach

As described in Section 4, ice conditions for every channel and lock reach are defined for each two-week time period in the simulation by dividing each reach into five (5) sections corresponding to the existence of different ice conditions along the length of the reach. Each of these sections, with the exception of the middle one (Section 3), is described by a length and the existing level ice thickness, refrozen brash ice thickness, and brash ice thickness. The middle section (Section 3) is reserved for open water and only its length is denoted.

The ice conditions for any reach and time period are thus defined by:

ICE CONDITIONS IN A REACH

Section 1

$$L_1 \quad h_{1L} \quad h_{1RB} \quad h_{1B}$$

Section 2

$$L_2 \quad h_{2L} \quad h_{2RB} \quad h_{2B}$$

Section 3 (Open Water)

$$L_3$$

Section 4

$$L_4 \quad h_{4L} \quad h_{4RB} \quad h_{4B}$$

Section 5

$$L_5 \quad h_5 \quad h_{5RB} \quad h_{5B}$$

TABLE 3.1
CALENDAR DATES OF SIMULATION PERIODS

<u>PERIOD</u>	<u>NORMAL YEAR 1975-76</u>	<u>SEVERE YEAR 1976-77</u>
1	Normal Season	Normal Season
2	8 Dec - 21 Dec	6 Dec - 19 Dec
3	22 Dec - 4 Jan	20 Dec - 2 Jan
4	5 Jan - 18 Jan	3 Jan - 16 Jan
5	19 Jan - 1 Feb	17 Jan - 30 Jan
6	2 Feb - 15 Feb	31 Jan - 13 Feb
7	16 Feb - 29 Feb	14 Feb - 27 Feb
8	1 Mar - 14 Mar	28 Feb - 13 Mar
9	15 Mar - 28 Mar	14 Mar - 27 Mar
10	29 Mar - 11 Apr	28 Mar - 10 Apr

Note: Periods start on a Monday to coincide with ice data sources.

where

$$\left. \begin{array}{l} L_i = \text{length of subreach (mi)} \\ h_{iL} = \text{thickness of level ice (in)} \\ h_{iRB} = \text{thickness of refrozen brash (in)} \\ h_{iB} = \text{thickness of unconsolidated brash (in)} \\ i = \text{section} \end{array} \right\} i = 1, 2, 3, 4, 5$$

The selection of representative normal and severe winters was based on a comparison of cumulative freezing degree days with historical weather records for different portions of the Great Lakes area. In addition to the above criteria, it was required that recent winters be selected in order to obtain historical ice condition data as well as icebreaker support data during extended navigation season operations. The winters of 1975-76 and 1976-77 met the above conditions and were judged to be representative of normal and severe winters on the Great Lakes. In fact, as stated by Quinn and Leshkevich of GLERL* "...the 1975-76 winter season can be characterized as near normal for all of the Great Lakes.... The winter of 1976-77 was the fifth coldest in the past 200 years." [12, 13]. To define ice conditions, all available ice data for the winters 1975-76 and 1976-77 were gathered and analyzed to provide a description of ice conditions for a normal and a severe winter, respectively, on the Great Lakes-St. Lawrence Seaway. The sources of data included:

- | | |
|--|---|
| SLAR Ice Charts | - Prepared by USCG/NWS/NASA |
| Satellite Photographs | - Prepared by NOAA/NESS |
| Ice Condition Charts | - Prepared by Ice Forecasting Central,
Department of the Environment, Canada |
| Great Lakes Ice Summaries | - Prepared by the Ninth Coast Guard District |
| "Great Lakes Ice Cover,
Winter 1975-76" | - Prepared by George A. Leshkevich,
NOAA Technical Memorandum, ERL-GLERL-12 |

This data provided an excellent method for estimating the type and extent of coverage on the Great Lakes-St. Lawrence Seaway during the two winters being analyzed. However, this data did not provide the needed values of level ice thickness, brash ice thickness, or refrozen brash ice thickness in the ship navigation channels. In order to make these estimates, separate mathematical models for level ice growth, brash ice formation in a navigation channel, and refrozen brash ice thickness were developed. Each of these models is described in detail below.

Level Ice Thickness Estimate - For each subreach in each time period, the level ice thickness is estimated using the traditional method of defining level ice thickness as a function of the square root of cumulative freezing degree days since the first formation of ice [4]:

*Great Lakes Environmental Research Laboratory

$$h_{iLj} = \alpha \left[\sum_{m=k}^j \text{FDD}_m \right]^{1/2} = \left[h_{iL(j-1)}^2 + \alpha^2 \text{FDD}_j \right]^{1/2} \quad (3-1)$$

where

h_{iLj} = level ice thickness for period j
 α = freezing degree day coefficient for each reach
 FDD_j = freezing degree days during period j
 k = period K when ice first appeared

If the air temperature is above freezing, the ice will melt at a rate assumed directly proportional to freezing degree days expressed by:

$$h_{iLj} = h_{iL(j-1)} + (0.2187 \times \text{FDD}_i) \quad (3-2)$$

Refrozen Brash Ice Growth Estimate - When a ship passes through an ice field, it leaves a mixture of broken ice pieces and water in its track. If the air temperature is below freezing, the water at the surface in the spaces between ice pieces will start to freeze. The crust, which forms at the surface, consists of old broken pieces frozen together by new ice, and is referred to as refrozen brash ice. Figure 3.2 depicts brash and refrozen brash ice in a ship track with level ice on both sides of the navigation channel.

The ice growth models assume that the air temperature is constant during each of the 14 day periods in the simulation. The ice growth models further assume that the ship transits along each reach are uniformly distributed in time within each time period. Utilizing these two assumptions, the refrozen brash ice thickness in a ship track can be calculated by the equation:

$$h_{Ri} = \alpha \left[\frac{\text{FDD}_i}{\text{NSPP}} \right]^{1/2} \quad (3-3)$$

where

h_{Ri} = refrozen brash ice thickness during period i
 NSPP = number of ship transits per period.

NSPP , the number of ship transits per period, is defined by the traffic level: light, moderate or heavy.




*Figure 3.2. Broken and Refrozen Ice
in a Ship Track*

Unconsolidated Brash Ice Growth Estimate - As stated previously, when a ship passes through an ice field it leaves a mixture of broken ice pieces and water in its track. The amount of ice is the same as before the ship passage; however, the newly formed ice-water mixture occupies more volume than the ice alone did prior to the ship passage. The thickness of the mixture after a ship passes through a level ice field is:

$$h_B = \frac{h_L}{(1-\beta)} \quad (3-4)$$

where

h_B = unconsolidated brash ice thickness

β = porosity = $\frac{\text{volume of voids}}{\text{total volume}}$

In each case where the surface refreezes before the next ship comes along, each ship breaks up the refrozen crust and turns it into unconsolidated brash ice. Therefore, each succeeding ship sees a slightly thicker unconsolidated brash ice layer.

Ashton [5] and Michel and Lafleur [6] have proposed similar models for the growth of ice in a ship track. The model used in the simulation for growth of unconsolidated brash ice is based upon these two models, but incorporates the assumptions of constant temperature and uniform distribution of ships in a period.

The first ship in period i will encounter a total depth of ice slightly thicker than that left by the last ship in the previous period:

$$D_1 = \left[D_{Bi-1}^2 + \alpha^2 \frac{\text{FDD}_i}{\text{NSPP}} \right]^{1/2} \quad (3-5)$$

where

D_1 = depth of ice that the first ship in the period sees

D_{Bi-1} = depth of brash ice at the end of period $i-1$

$$D = h_R + h_B = \left[D_{Bi-1}^2 + h_{Ri}^2 \right]^{1/2} \quad (3-6)$$

The second ship in the period encounters additional ice thickness due to breaking up the refrozen crust and the ice growth under the broken pieces at the surface.

$$D_2 = \left[\left(D_1 + \frac{\beta h_{Ri}}{(1-\beta)} + \frac{\beta(1-\beta)}{(1-\beta)} ((h_{Ri}^2 + h_{Ri}^2)^{1/2} - h_{Ri}) \right. \right. \quad (3-7)$$

$$\left. \frac{\beta(1-\beta)^2}{(1-\beta)} (((2h_{Ri})^2 + h_{Ri}^2)^{1/2} - 2h_{Ri}) + \dots \right) + h_{Ri}^2 \Big]^{1/2}$$

The long expression which makes the first squared term is, itself, composed of terms which represent different contributions to the growth of the ice. The first term, D_1 , is the depth of unconsolidated brash ice sheet by the previous ship. The second term is the additional thickness due to breakup of the refrozen crust. The third term is the additional thickness due to the breakup of the ice forming under the first layer of ice pieces. The fourth term is the additional thickness due to the breakup of the ice forming under the second layer of ice pieces.

As the total amount of ice grows, more ice floats above the waterline due to the density difference between ice and water. As these ice pieces emerge from the water, they act as an insulator and slow down the rate at which new ice is generated. Effectively, a layer of ice is added above the waterline. The effective thickness of this layer, h_{ue} , is:

$$h_{ue} = D(1 - \rho_i/\rho_w) (1 - \beta) \quad (3-8)$$

Equation (3-7) changes to:

$$D_2 = \left[\left(D_1 + \frac{\beta}{(1-\beta)} ((h_{ue}^2 + h_{Ri}^2)^{1/2} - h_{ue}) + \right. \right. \quad (3-9)$$

$$\left. \frac{\beta(1-\beta)}{(1-\beta)} (((h_{ue} + h_{Ri})^2 + h_{Ri}^2)^{1/2} - h_{ue} + h_{Ri}) + \right. \\ \left. \frac{\beta(1-\beta)^2}{(1-\beta)} (((h_{ue} + 2h_{Ri})^2 + h_{Ri}^2)^{1/2} - (h_{ue} + 2h_{Ri})) \right)^2 + ((h_{ue}^2 + h_{Ri}^2)^{1/2} - h_{ue}^2) \Big]^{1/2}$$

The calculation of the unconsolidated brash ice depth by this method is an iterative procedure. Due to the insulation effect, the refrozen brash ice thickness is not constant as the insulating layer grows. The refrozen brash ice thickness that the ship experiences is no longer defined by equation (3-3) but rather by:

$$h_{Ri} = (h_{ue}^2 + h_{Ri}^2)^{1/2} - h_{ue} \quad (3-10)$$

Melting of the unconsolidated brash ice is treated much the same as the melting of the level ice. Since the temperature is above freezing, no refrozen brash ice can form and the unconsolidated brash ice melts according to:

$$h_{Bi} = h_{Bi-1} + (0.2187 \times FDD_i)/(1 - \beta) \quad (3-11)$$

3. DESCRIPTION OF GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION

3.3 Ship Speed Generating Model

3.3.1 Purpose

The purpose of the SHIP SPEED GENERATING MODEL is to:

- Convert the ship characteristics, reach characteristics, ice conditions, and improvement levels, into the speed for each class of ship in each reach for open water (during normal season operations) and for every two-week season extension period. This information is stored in three (3) data files for light, moderate and heavy traffic levels.
- Generate an increased service time factor based on ice conditions for each port and lock facility for every two-week season extension period.
- Determine the maximum ship length and maximum allowable ship draft permitted to move from each port to every other port.
- Assemble the data in an appropriate format required by the SHIP PROCESSING MODEL.

In addition, the SHIP SPEED GENERATING MODEL also indicates in which reaches a particular class of ship will become stuck in ice. Delay times due to a ship's becoming stuck and then waiting for icebreaker assistance are not determined in this model but rather in the SHIP PROCESSING MODEL, since these delays are related to the availability of icebreaker support. Similarly, delay times due to ships waiting in queues for a port or lock facility are also determined in the SHIP PROCESSING MODEL.

3.3.2 Method of Approach

The average speed of advance for a particular class of ship to traverse a given reach is equal to the total length of the reach divided by the transit time required for the ship to traverse each section of the reach; that is:

$$V_{\text{average}_i} = 88.00 \frac{d_1 + d_2 + d_3 + d_4 + d_5}{t_1 + t_2 + t_3 + t_4 + t_5} \quad (3-12)$$

where

$V_{\text{average } i}$ = average speed of advance (fps) for a ship to traverse the i th reach

t_j = transit time (minutes) for a ship to traverse the j th section of the reach ($j = 1, 2, 3, 4, 5$)

d_j = length (miles) of the j th section of the reach ($j = 1, 2, 3, 4, 5$)

To use equation (3-12), t_j must be determined. In general, t_j is a function of the ship's thrust capability, its resistance characteristics, the ice conditions, river current, winds, visibility, and imposed speed limits. The delaying effects of high winds and low visibility are accounted for by using an average weather delay factor of 1.08 based on historical data provided by United States Steel Corporation, while the effect of river current has been neglected. Equation (3-12) can therefore be expressed as:

$$\begin{aligned} t_j &= \left(88.0 \frac{d_j}{V_j} \right) \times 1.08 \\ &= 95.04 \frac{d_j}{V_j} \end{aligned} \quad (3-13)$$

where

V_j = average speed of advance of a ship traversing the j th section of the reach neglecting weather delays (fps)

One of the basic assumptions in developing the simulation is that ships would attempt to proceed at their maximum speed capability provided it is less than any imposed speed limit. If a ship's maximum speed capability is greater than the speed limit, the ship would reduce its speed accordingly. Expressed mathematically,

$$V_j = \begin{cases} V_{\text{max}}: & \text{if } V_{\text{max}} < V_{sl} \\ V_{sl}: & \text{if } V_{\text{max}} > V_{sl} \end{cases} \quad (3-14)$$

or

$$V_j = \text{minimum of} \begin{cases} V_{\text{max}} \\ V_{sl} \end{cases}$$

where

$V_{\max}$ = maximum speed capability of the ship in the j th section of reach (fps)

V_{sl} = imposed speed limit

For steady state motion, the available thrust of a ship $T(V)$, is equal to the ship's resistance, $R(V)$, where both the thrust and resistance are functions of the ship's speed:

$$T(V) = R(V) \quad (3-15)$$

To determine the thrust-speed relationship for a given ship, the propulsion system of the ship must be analyzed. Most ships, with the exception of icebreakers or ships equipped with controllable pitch propellers, can be assumed to operate along constant torque curves independent of propeller RPM. Icebreakers, because of their need for extra thrust capability at low speeds, and ships equipped with controllable pitch propellers operate along constant horsepower curves permitting higher torques to be attained at lower speeds. Using these assumptions, the thrust-speed relationships can be determined from representative propeller curves* for the following typical propulsion systems:

Steam Turbine Propulsion System

$$T(V) = (1.59 - 0.398 (V/V_{\text{design}}) - 0.192 (V/V_{\text{design}})^2) T_{\text{design}} \quad (3-16)$$

Diesel Propulsion System

$$T(V) = (1.32 - 0.196 (V/V_{\text{design}}) - 0.124 (V/V_{\text{design}})^2) T_{\text{design}} \quad (3-17)$$

Class D Icebreakers

$$T(V) = (2.21 - 1.06 (V/V_{\text{design}}) - 0.140 (V/V_{\text{design}})^2) T_{\text{design}} \quad (3-18)$$

Class C Icebreakers

$$T(V) = (1.49 - 0.206 (V/V_{\text{design}}) - 0.284 (V/V_{\text{design}})^2) T_{\text{design}} \quad (3-19)$$

Class B Icebreakers

$$T(V) = (2.08 - 1.02 (V/V_{\text{design}}) - 0.060 (V/V_{\text{design}})^2) T_{\text{design}} \quad (3-20)$$

* Icebreaker propeller performance is based on analysis of the MACKINAW, WTGB and 110's propeller data provided by USCG. Laker and salty propeller performance is based on an analysis of propeller data provided by U.S. Steel and MARINER CLASS VESSEL, respectively.

where

$$T_{\text{design}} = 550 \frac{(P.C.) (\text{shp})}{V_{\text{design}}} \quad (3-21)$$

T = thrust of ship (pounds)

T_{design} = design thrust (pounds)

V = speed of ship (fps)

V_{design} = design speed of ship (fps)

$P.C.$ = propulsive coefficient = $\eta_o \cdot \eta_R \cdot \eta_H \cdot \eta_T$

shp = installed rate of shaft horsepower

η_o = propeller efficiency = 0.57

η_R = relative rotative efficiency = 1.0

η_H = $1-t/1-w$ = hull efficiency = 1.0

η_T = transmission efficiency = .98

These relationships are presented graphically in nondimensional form in Figure 3.3.

Resistance of a given ship is a function of the ship's characteristics, its speed, and the ice conditions (type and thickness). For the purposes of this simulation, the resistance of a given vessel is assumed equal to:

$$R_T = R_{OW} + R_{LI} + R_{RB} + R_B \quad (3-22)$$

where

R_T = total resistance (pounds)

R_{OW} = open water resistance (pounds)

R_{LI} = level ice resistance (pounds)

R_{RB} = refrozen brash ice resistance (pounds)

R_B = brash ice resistance (pounds)

As a first order approximation, the open water resistance is assumed to obey a velocity squared relation passing through the design-speed point.

$$R_{OW} = T_{\text{design}} \left(\frac{V}{V_{\text{design}}} \right)^2 \quad (3-23)$$




Figure 3.3. Thrust - Velocity Relation

where

T_{design} = design thrust required to overcome the resistance at design speed (pounds)

V_{design} = design speed (fps)

From model and full-scale resistance tests of the MACKINAW, WIND CLASS, WGTB, RYERSON, and NEW 1000' GL BULK CARRIERS, the resistance of ships in level ice, brash ice, and refrozen brash ice are estimated to be:

Level Ice

$$R_{LI} = \rho_w g B h_{LI}^2 \left[(0.273 + 1.96\mu_0) (1 + 4.51f) + (0.0011 + 0.0116\mu_0^2/\eta_2) (1 + 2.92f) \left(\frac{V}{\sqrt{gh_{LI}}} \times \frac{\sigma_f}{\rho_w g h_{LI}} \right) \right] \quad (3-24)$$

Refrozen Brash Ice

$$R_{RB} = 0.8 R_{LI} \quad \left| \quad h_{LI} = h_{RB} \right. \quad (3-25)$$

Brash Ice

$$R_B = \rho_w g B h_B^2 \left[0.320 + 1.51\mu_0 + (0.0369 + 0.0745 \frac{\mu_0^2}{\eta_2}) \frac{V^2}{gh_B} \right] \quad (3-26)$$

where

g = acceleration of gravity = 32.2 ft/sec²

ρ_w = mass density of water = 1.94 slugs/ft³

σ = flexural strength of ice = 18,000 psf

f = hull-ice friction factor = 0.25

h_{LI}, h_{RB}, h_B = level ice, refrozen brash ice, and brash ice thickness (ft)

μ_0, η_2 = hull shape geometric coefficients (obtained from analysis of vessel lines drawings)

	μ_0	η_2
Ocean-Going Vessels	2.06	5.53
Lakers	5.56	1.94
Icebreakers: Class B	1.45	2.85
Class C	1.45	2.96
Class D	1.61	2.79

It should be noted that while equation (3-22) shows total resistance to be additive of the independent ice resistance components, the current state-of-the-art in predicting ice resistance has not proven or disproven this assumption. It is felt, however, that this assumed additive condition provides a good first approximation since in the limit the total resistance reduces to the individual components. For example, if there is no ice, then the total resistance equals the open water resistance and similarly if the brash ice thickness and refrozen brash ice thickness are zero, the ice resistance equals that of the level ice resistance. The only discrepancy occurs in that the open water resistance has been incorporated twice when the ship is operating in ice. While this gives a slight overestimate to the total resistance, the current-state-of-the-art in ice model testing has not developed a verified methodology to remove the open water resistance portion from the total measured resistance. Thus equation (3-22) is somewhat conservative, predicting a slightly higher resistance than one would expect in the real world. The open water resistance R_{OW} is included in equation (3-22) to enable the total resistance to be a continuous function at zero ice thickness (open water); expressed mathematically:

$$R_{OW} = \lim_{h \rightarrow 0} (R_T) \quad (3-27)$$

In ice, the error introduced by including open water resistance twice is slight since ice resistance is much greater than R_{OW} .

Since both $T(V)$ and $R(V)$ are of quadratic form, equation (3-15) can be solved for the ship's maximum speed capability (V_{max}) in the i th section of the reach using the standard quadratic formula. The procedure is illustrated graphically in Figure 3.4. In solving this quadratic equation, two roots are obtained, consisting of positive and negative real roots, two negative real roots, or two complex roots, depending on the value of ice thickness for a given ship. If positive and negative real roots are obtained, the ship can proceed through the ice at a speed equal to the positive root, while the negative root is an extraneous solution to the equation. If two negative real roots or two complex roots are obtained, the ice is too thick for the ship to proceed through; that is, the ship does not have enough available thrust to overcome the resistance and its speed of advance will therefore correspond to zero. In practice, a minimum speed of advance of approximately 2 mph exists below which ships will not proceed and can be assumed stuck. Thus, if V_{max} is less than 2 mph, the ship is assumed to be stuck in ice and an icebreaker must be called to free the ship. If this occurs, the speed of advance of the ship is set to the speed in the remaining sections of the reach and an appropriate stuck code is added to the indicated speed.




Figure 3.4. Typical Thrust and Resistance Characteristics

In addition to transit times, delay factors are calculated for each port and lock facility to indicate increased service time due to the following problems caused by the presence of ice:

- Turning in port basins
- Maneuvering into docks
- Need for ice lockages
- Removal of ice from lock walls
- Removal of ice from gate recesses

The problems associated with locks operating during winter are discussed in detail in reference [7]. These delays are assumed to be proportional to the ice thickness existing at the facility and to increase linearly at the rate of 1% per inch of ice based upon the results from the SPAN Study [7, 8] and discussions with fleet operators.

Thus,

$$f_{\text{delay}} = 1.0 + h/100. \quad (3-28)$$

where

f_{delay} = delay factor

h = ice thickness (inches) = $h_{LI} + h_{RB} + h_B$

Another ice problem which can restrict the movement of large ships in river reaches is their capability to maneuver around a turn in a river in a broken ice channel. The computer program simulates a ship becoming stuck in a tight turn by comparing the broken channel width required by the vessel to negotiate the turn to the radius of the turn as shown in Figure 3.5. Also shown in the figure is the effect on the turn radius of preventive icebreaking expressed as the widening of the turn versus the number of preventive icebreaker transits per period. It is assumed that the channel is widened from 150 ft by one-third of the icebreaker's beam per transit. The preventive icebreaking is simulated in the Ice Growth Model, which outputs the broken channel width for each reach by period, along with the ice conditions. The Speed Generating Model flags any vessel class that will become stuck in a given turn. The actual freeing of the stuck ship by an icebreaker is performed in the Ship Processing Model, which calculates how many passes of an icebreaker will be required to meet the minimum turn width, assuming the broken channel is widened one icebreaker beam per transit.




Figure 3.5 Required Turn Width vs Channel Turn Radius and Turn Width vs Preventive Icebreaking Transits

3. DESCRIPTION OF GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION

3.4 Ship Processing Model

3.4.1 Purpose

The SHIP PROCESSING MODEL uses the output from SHIP SPEED GENERATING MODEL, cargo origin and destination data, fleet mix, ship and reach characteristics, and improvement levels, to simulate the movement of ships and cargo while compiling the following statistics for each vessel class on every route for normal season operations and for every two-week season extension period.

- Tons of cargo transported
- Time underway with cargo
- Time stopped with cargo
- Total number of trips
- Number of trips made by ships equipped with bow thrusters
- Number of trips made by self-unloaders
- Time underway during empty backhaul
- Time stopped during empty backhaul
- Number of trips through the Seaway with cargo
- Number of trips through the Seaway without cargo
- Number of trips through the Welland with cargo
- Number of trips through the Welland without cargo
- Icebreaker assistance and convoy statistics

In processing ships from port to port, queues at ports and locks are allowed to form, expand, and diminish as necessary. The time spent in a queue waiting to be serviced is allocated to the route the ship is transiting. Similarly, when a ship becomes stuck and requires icebreaker assistance, the ship's waiting time is allocated to its current route. If an icebreaker is not immediately available, this additional waiting time is included.

3.4.2 Method of Approach

In order to meet the cargo tonnage criteria, ships are dispatched from port of origin at a required frequency rate and then proceed toward their port of destination. In the process, they obey the following basic rules and assumptions.

Commercial Ships

1. All ships in the fleet are represented by specific ship classes whose properties are specified for typical ships.
2. All ships attempt to maintain their maximum capable speed at all times except where speed limits exist.

3. A ship's maximum speed capability is determined by equating the ship's thrust capability to its resistance characteristics.
4. Ship delays due to bad weather are accounted for by decreasing the speed by a weather delay factor based on historical data.
5. A ship may be stuck due to resistance or it may become stuck because it is too long to turn within the required radius of a given channel width.
6. A ship is assumed to be stuck due to resistance if its maximum capable speed of advance is less than 2 mph in any subreach.
7. A ship is said to become stuck at the upper end of the reach, at the lower end of the reach, or both. This information, and how the ship became stuck, is encoded into the speed.
8. No accidents involving ships are assumed to occur in the system and no time delays due to accidents are considered.
9. All ships observe winter draft restrictions during extended season operations.
10. All lakers are assumed to lay-up at the end of the navigation season, while all ocean-going ships are assumed to operate elsewhere.
11. All ships are treated on an equal basis.
12. All ships operate only during daylight hours in areas where nighttime navigation is prohibited.
13. Once stuck, a ship calls on an icebreaker for assistance and waits until the icebreaker arrives at the ship's location.
14. If an icebreaker is not available and a ship becomes stuck, the ship must wait until one becomes available.
15. Ships are "created" by the simulation on a frequency basis as required to carry the specified tonnage on a particular route. Ships complete a round trip on a specified route, and are then "destroyed" by the simulation.
16. The number of vessels in the system floats according to the delays encountered since the tonnage to be carried is fixed.
17. Ships queue up at ports and locks and are serviced on a first-come first-served basis.
18. The frequency of ship generation varies as a function of time to simulate the seasonal tonnage variation that occurs with a fixed fleet as transit times increase during the extended season.

19. The speed of a ship in a reach depends on the type of ice conditions (level ice/brash ice with thick refrozen crust/thicker brash ice with thin refrozen crust) which, in turn, depends on the level of traffic (light/moderate/heavy).
20. The level of traffic for a given reach in any period is determined by the number of ship transits in the previous period: 0-2 light, 3-30 moderate, 31-∞ heavy.
21. Lakers are assigned to one route (origin/destination/commodity grouping) or two routes if on a triangular pattern. One round trip is made which includes an empty backhaul.
22. Salty General Cargo ships follow preassigned itineraries, spending two days in each port of call in the Great Lakes-St. Lawrence Seaway System and 2.5 days in the overseas ports.
23. Ships are routed only to ports which can accommodate their length.
24. The ship's draft is adjusted to meet the minimum requirements of the origin or destination.
25. Ships cannot go through locks which are shorter than their length.

Icebreakers - General

1. Icebreakers are assigned to one of seven task commands. In the fixed fleet mode, each icebreaker is free to respond anywhere within the task command. In the maximum response time mode, an icebreaker may respond only in reaches that have the same designated home port as the icebreaker.
2. When released from a specific task, an icebreaker is assigned to a direct assistance (DA) task, to escort a convoy, or to proceed back to home port reach-by-reach if not needed.
3. When both convoy and DA queues are waiting to be processed, the icebreaker is assigned to the ship which has been waiting the longest.
4. Icebreaker transits through reaches containing locks do not include lock queuing time since it is assumed icebreakers will be given top priority and will be locked through ahead of commercial vessels.
5. An icebreaker becomes stuck if its speed is less than 5 mph in any subreach. A ramming speed of 2 mph is then used.
6. If an icebreaker must ram in any subreach, a flag is encoded into the speed.

Icebreaker Selection and Response

1. When selecting an icebreaker for a task, two decision criteria are used: icebreaker capability and response time, as defined in rules and assumptions associated with convoying and direct assistance. In the fixed fleet mode, the *soonest capable* icebreaker is selected. A class is capable by default if the task command has no icebreakers of a higher class. In the MRT mode, the *lowest capable* class is selected.
2. If it is at its home port, an icebreaker's response time includes a standby time which is specified on a class basis (for production runs all icebreakers were assumed on an alert status and the standby time was input as 15 minutes).
3. When looking for an icebreaker for direct assistance duty, the convoy queues first have icebreakers "reserved" for all ships arriving within 12 hours. This gives priority to the convoys based on the assumption that a ship's master can radio ahead the ETA for a convoy point, whereas he would not be predicting where and when his ship will get stuck in the ice and require direct assistance.

Icebreaker Convoying

1. An icebreaker is "capable" of responding to a convoying task if the icebreaker does not have to ram through any of the reaches comprising the convoy route and if the time to transit the convoy route is less than the maximum endurance for that class icebreaker.
2. The icebreaker escorts the convoy at 80 percent of the calculated speed in each reach of the convoy route.
3. All ships in the convoy travel at the same speed as the icebreaker.
4. Convoys begin and end at reach nodes.
5. The escorting icebreaker is freed as soon as it completes the convoy route.
6. No ships will get stuck while traveling in a convoy.
7. After the icebreaker transit time to a convoy point is computed, it is decremented by the amount of time that the icebreaker has been free to account for icebreakers having been reserved for convoy duty. In this manner, the simulation models the assumption that task commands have prior knowledge of upcoming convoy requirements.
8. The following algorithm is used to determine if and when a convoy will leave. A convoy is checked for processing whenever a ship arrives at the convoy point and whenever an icebreaker in the same task command becomes free. If, at the time the icebreaker arrives at the convoy, the queue has enough ships to meet or exceed the escort capacity of the icebreaker, the convoy is deemed ready to leave. In addition, if at the

time the icebreaker arrives, the first ship in the queue has waited longer than its maximum allowable delay, the convoy is deemed ready to leave. In the fixed icebreaker fleet mode, this delay is equal to six hours; in the maximum response time mode, it is equal to the maximum response time of the downstream reach.

9. The size of a convoy is the number of ships in the convoy queue at the time the icebreaker arrives or the escort capacity of the icebreaker, whichever is less.

Icebreaker Direct Assistance - General

1. An icebreaker is "capable" of assisting a stuck ship if the icebreaker does not have to ram in the same reach that the ship is stuck in.
2. Each reach has four possible "stuck points". Points 1 and 4 are at the reach nodes; points 2 and 3 are 20% of the reach length from the nodes.

Icebreaker Direct Assistance - Ship Stuck Due to Resistance

1. The direct assistance deployment time when a ship is stuck due to resistance includes breakout time, which is defined as the time for the assisting icebreaker to travel ten miles in level ice in the reach that the ship is stuck in (maximum time is four hours). Breakout mileage is not included in the statistics.
2. Once the ship is free, the icebreaker escorts the ship to the end of the reach, traveling at 80 percent of its calculated speed in that reach.
3. The escorting icebreaker is deallocated when one of the following conditions are met:
 - a convoy point is reached
 - a port is reached
 - the next reach is passable by the ship without escort, or
 - the icebreaker reaches the task command boundary.

Icebreaker Direct Assistance - Ship Stuck in a Turn

1. Direct assistance deployment time for this case includes breakout time, which is defined as the time for the icebreaker to make the number of passes required to sufficiently widen the turn using the speed in level ice, assuming that the turn is widened one beam width each pass (maximum time is four hours).
2. The icebreaker is freed as soon as the ship is broken out of the turn.

Maximum Response Time (MRT) Mode*

1. The value of the maximum response time is input data specified by reach. (Note that this time must be greater than the time required for an icebreaker to get to the reach from the nearest home port.)
2. The lowest capable class of icebreaker is selected for a task (even if a higher class icebreaker has a shorter response time) to ensure that a minimum number of large icebreakers are created in the MRT mode.
3. When an icebreaker must be created to meet the maximum response time for a specific task, the lowest capable class is chosen and assigned to the nearest home port.
4. In the MRT mode, a free icebreaker is not deployed if it cannot reach its destination by the time the waiting ship has passed its maximum delay time.
5. The icebreaker fleet is zeroed at the beginning of each period, and grows as required to meet the demands for assistance.

Icebreaker Statistics

1. Statistics accumulated by reach reflect icebreaker escort (either direct assistance or convoy) within each reach.
2. Statistics accumulated by commercial vessel route include the time required for the icebreaker to get to the point of assistance from wherever it was when it was called.
3. Statistics accumulated by icebreaker class/task command include time getting to the point of assistance and returning to home port, as well as time for the assistance itself.
4. The direct assistance and convoy counters are incremented when the request is processed, not when it is requested.

Lock Reaches

1. Night operations are permitted except where restricted.
2. Ships are locked through in a manner which maximizes the lock's utilization.
3. If queues exist on both sides of the lock, the lock alternates in processing upbound and downbound ships.
4. Ships are processed out of each queue on a first-come first-served basis.

* The MRT mode is described in detail as to its logic in the USERS MANUAL AND DOCUMENTATION in subroutines NEWIB, IBFREE, STKVS, PROSTK, PROCVY, ALLOC, ICEBRK, and CAPBLE.

5. If a queue exists on one side of the lock and the time of arrival of a ship at the other side of the lock is less than the turnback time of the lock, the lock waits to process the arriving ship. Otherwise, it turns back to process the next ship in the queue.
6. Only one ship at a time is locked through.
7. Locking times are assumed to increase equally for all classes of ships at the rate of one percent for each inch of ice existing in the reach.

Port Reaches

1. Port facilities are assumed to operate 24 hours a day.
2. Ships are loaded (unloaded) on a first-come first-served basis.
3. Ships are loaded with only one type of cargo at a time.
4. Stockpiles are assumed to exist at all ports of origin and all ships are loaded to capacity or to some draft limitation with the exception of general cargo ships.
5. Stockpiles are assumed to exist at all ports of destination and all ships are unloaded completely with the exception of general cargo ships.
6. General cargo ships are loaded and unloaded depending on the cargo destined for each port.
7. The port turnaround times are assumed to increase equally for all classes of ships at the rate of one percent for each inch of ice in the next downbound reach.
8. Ocean-going ships carrying grain stop in Baie Comeau to top-off before proceeding overseas.

Channel Reaches

1. Ships are not permitted to exceed a speed limit if one exists in a particular reach.
2. Passing is permitted in all reaches.
3. Night operation is permitted except in areas where restricted.

3. DESCRIPTION OF GREAT LAKES-ST. LAWRENCE SEAWAY NAVIGATION SIMULATION

3.5 Freight Rate/Report Generating Model

3.5.1 Purpose

The FREIGHT RATE/REPORT GENERATING MODEL translates the statistics collected by the SHIP PROCESSING MODEL, along with vessel data, into the following icebreaker statistics, vessel operating costs, performance measures, and required freight rates.

ICEBREAKING DATA

- Direct assistance queue size by task command every 2 days (7 times per time period)
- Convoy queue size by direction every 2 days (7 times per time period)
- Icebreaker statistics by icebreaker class, task command, home port, and reach for every time period:
 - number of icebreakers
 - channel clearing (inches/period)
 - preventive icebreaking (hours/period)
 - number of direct assists
 - hours of direct assists
 - miles of direct assists
 - direct assistance average response time (hours)
 - direct assistance maximum response time (hours)
 - hours of convoys escorted
 - miles of convoys escorted

VESSEL TRADE ROUTE DATA

For each route and every time period, the following information is output on a cumulative basis for the fleet on each route as well as for each individual ship class:

- Total tonnage
- Time underway (domestic and world-wide)
- Time stopped (domestic and world-wide)
- Number of trips (total, and broken into ships with bow thrusters and ships that are self-unloaders)
- Crew Costs
- Maintenance and repair costs
- Store and supply costs

- Insurance costs
- Overhead costs
- Towing costs
- Lay-up charges
- Fuel costs
- Gallons of fuel consumed
- Tolls
- Total operating costs
- Operating cost per ton
- Operating cost per hour
- Operating cost per ton-mile
- Revenues per ton-mile
- Taxes per ton-mile
- Depreciation per ton-mile
- Profit per ton-mile
- Required freight rate (dollars/ton)
- Per-unit required freight rate (normalized to the normal season value)
- Revenue ton-miles (ton-miles on which cargo was carried)
- Total miles with cargo
- Total miles backhaul
- Dollar-miles (the value of the cargo times distance moved)
- Average trip time per trip (including loading/unloading time)
- Average trip time per ton-mile (including loading/unloading time)
- Average length of haul (miles)
- Icebreaker direct assistance required (number, hours, miles)
- Number of convoys with icebreaker escort.

PORT AND LOCK DATA

- Number of ships in port and lock queues every 2 days
- Number of events by port and cargo commodity
- Number of events at each lock
- Average delays at ports and locks.

4. REACH SELECTION

In the simulation, the GL-SLS Navigation System is represented as the series of reaches shown in Figures 4.1 and 4.2, and listed in Tables 4.1 and 4.2 at the end of this section. Also shown in Figures 4.1 and 4.2 are the designated icebreaker commands and designated icebreaker home ports. In describing these reaches, each reach is initially classified as either a port reach, lock reach, or channel reach with boundaries defined as listed in Table 4.2. For port and lock reaches, boundaries were chosen to correspond to the entrance and exit points of the facility, while boundaries for adjacent channel reaches were chosen to correspond to points where trade routes joined, where characteristics of the system changed significantly, or where the U.S. Coast Guard task command boundaries existed.

Once selected, every reach was described by a series of attributes. Port reaches, which were defined as any facility where ships moving over specified trade routes could either load or unload cargo, were described by:

- Maximum Allowable Ship Draft
- Maximum Allowable Ship Length
- Port Turnaround Time

and, for each type of cargo (iron ore, coal, grain, stone, and general cargo), by:

- Stockpile Level
- Number of Docks
- Cargo Arrival (Usage Rate)
- Cargo Loading/Unloading Rate
- Dock Restrictions (Self-Unloaders Only)

where the port turnaround time is the time for a ship to move to and from the docks, excluding time spent in a queue waiting for a dock to become available.

Lock reaches, which were defined as any reach containing a single lock or a system of locks, such as the Welland Canal or St. Lawrence Seaway, were described by the following attributes:

- Ice Conditions
- Maximum Allowable Ship Draft
- Maximum Allowable Ship Length
- Imposed Speed Limit
- Beginning of Daylight Only Navigation




FIGURE 4.1 REACHES COMPRISING THE GL-SLS NAVIGATION SYSTEM




FIGURE 4.2 REACHES COMPRISING THE GL-SLS NAVIGATION SYSTEM

- End of Daylight Only Navigation
- Number of Locks
- Lock Turnback Time

The remaining reaches comprising the lakes and rivers were defined as channel reaches and described by:

- Ice Conditions
- Maximum Allowable Ship Draft
- Maximum Allowable Ship Length
- Imposed Speed Limits
- Beginning of Daylight Only Navigation
- End of Daylight Only Navigation

Ice conditions for every channel and lock reach were defined for each two-week time period in the simulation by dividing each reach into five (5) sections corresponding to the existence of different ice conditions along the length of the reach. Each of these sections, with the exception of the middle one (section 3), was described by a length and the existing level ice thickness, refrozen brash ice thickness, and brash ice thickness. The middle section (section 3) was reserved for open water and only its length was denoted. The elimination of any section was achieved by equating its length to zero. For example, a totally open water reach has the length of section 3 equal to the total length of the reach while the lengths of the other sections equal zero. Similarly, the elimination of any type of ice condition was achieved by setting its respective ice thickness equal to zero. Thus, for example, a reach which contained only brash and refrozen brash ice and did not contain a level ice section has the level ice thickness of all sections set equal to zero. Ice conditions for each reach were prepared for every two week time period for a representative normal and severe winter assuming light, moderate, and heavy ship traffic levels. A more detailed description of the methodology used in defining the ice conditions is presented in Section 3.2 of this report. The values for freezing degree day coefficients (α) and the brash ice porosity (β) for each reach is listed in Table 4.3.

TABLE 4.1
LIST OF PORT REACHES

<u>Port Number</u>	<u>Port Name</u>	<u>Port Number</u>	<u>Port Name</u>
1	<i>Thunder Bay</i>	21	<i>Detroit</i>
2	Taconite Harbor	22	Rouge River
3	Silver Bay	23	Trenton Ch.
4	Two Harbors	24	<i>Toledo</i>
5	<i>Duluth</i>	25	<i>Sandusky</i>
6	Superior	26	Lorain
7	<i>Presque Isle</i>	27	<i>Cleveland</i>
8	<i>Sault Ste. Marie</i>	28	Ashtabula
9	<i>St. Ignace</i>	29	Conneaut
10	<i>Escanaba</i>	30	<i>Port Colborne</i>
11	<i>Green Bay</i>	31	<i>Buffalo</i>
12	<i>Milwaukee</i>	32	<i>Toronto</i>
13	<i>Chicago & Calumet</i>	33	<i>Oswego</i>
14	Indiana Harbor	34	<i>Alexandria Bay</i>
15	Gary	35	Cornwall
16	Burns Harbor	36	<i>Montreal</i>
17	Muskegon & <i>Grand Haven</i>	37	<i>Quebec</i>
18	Calcite	38	Baie-Comeau
19	<i>Bay City & Saginaw</i>	39	Sept-Iles
20	<i>Port Huron</i>	40	Overseas Ports

NOTE: Icebreaker home ports are in italics.

TABLE 4.2

LIST OF CHANNEL AND LOCK REACHES

REACH	LENGTH (mi)	UPSTREAM NODE		DOWNSTREAM NODE		LANDMARK
		N. LAT.	W. LONG.	N. LAT.	W. LONG.	
41	29	46°45'	92°00'	46°56'	91°29'	
42	10	47°01'	91°40'	46°56'	91°29'	
43	36	46°56'	91°29'	47°10'	90°48'	Minnesota Pt. Two Harbors
44	21	47°17'	91°16'	47°10'	90°48'	Silver Bay
45	16	47°10'	90°48'	47°17'	90°31'	
46	25	47°31'	90°55'	47°17'	90°31'	Taconite
47	145	47°17'	90°31'	47°35'	87°30'	
48	226	48°26'	89°12'	46°48'	84°56'	Thunder Bay
49	119	46°34'	87°22'	46°48'	84°56'	Presque Isle
50	40	46°48'	84°56'	46°30'	84°21'	Whitefish Pt.
51	46	46°30'	84°21'	45°57'	83°54'	Sault Ste. Marie
52	36	45°51'	84°37'	45°57'	83°54'	DeTour Reef
53	46	45°53'	85°34'	45°51'	84°37'	DeTour Reef
54	78	45°24'	87°00'	45°53'	85°34'	Round Island
55	150	44°05'	87°10'	45°53'	85°34'	Lansing Shoal
56	24	45°45'	87°03'	45°24'	87°00'	
57	80	44°32'	88°00'	45°24'	87°00'	Escanaba Green Bay
58	93	44°05'	87°10'	45°24'	87°00'	
59	55	43°06'	87°14'	44°05'	87°10'	
60	32	43°01'	87°52'	43°06'	87°14'	Milwaukee
61	46	43°13'	86°21'	43°06'	87°14'	Muskegon
62	62	42°12'	87°18'	43°06'	87°14'	
63	35	41°43'	87°29'	42°12'	87°18'	
64	39	41°39'	87°14'	42°12'	87°18'	
65	52	45°50'	84°37'	45°33'	83°39'	Round Island
66	68	45°57'	83°54'	45°11'	83°02'	DeTour Reef

Whitefish Pt.
Whitefish Pt.
Sault Ste. Marie
DeTour Reef
DeTour Reef
Round Island
Lansing Shoal
Lansing Shoal

TABLE 4.2 (CONTINUED)

REACH	LENGTH (mi)	UPSTREAM NODE		DOWNSTREAM NODE		
		N. LAT.	- W. LONG.	N. LAT.	- W. LONG.	LANDMARK
67	11	45°26'	- 83°48'	45°33'	- 83°39'	Calcite
68	40	45°33'	- 83°39'	45°11'	- 83°02'	
69	63	45°11'	- 83°02'	44°19'	- 82°37'	
70	82	43°39'	- 83°51'	44°19'	- 82°37'	
71	94	44°19'	- 82°37'	43°00'	- 82°25'	Mouth of Saginaw River
72	28	43°00'	- 82°25'	42°37'	- 82°31'	
73	34	42°37'	- 82°31'	42°20'	- 83°01'	
74	9	42°20'	- 83°01'	42°15'	- 83°08'	
75	7	42°09'	- 83°11'	42°15'	- 83°08'	Trenton Ch. Rouge River
76	24	42°15'	- 83°08'	41°54'	- 83°06'	
77	23	41°42'	- 83°28'	41°54'	- 83°06'	
78	34	41°54'	- 83°06'	41°49'	- 82°28'	
79	27	41°28'	- 82°42'	41°49'	- 82°28'	Sandusky Lorain
80	25	41°29'	- 82°12'	41°49'	- 82°28'	
81	40	41°32'	- 81°44'	41°59'	- 80°42'	
82	91	41°49'	- 82°28'	42°03'	- 81°30'	
83	52	41°49'	- 82°28'	42°03'	- 81°30'	Pelee Passage Pelee Passage Pelee Passage
84	54	41°29'	- 82°12'	42°03'	- 81°30'	
85	37	41°32'	- 81°44'	42°03'	- 81°30'	
86	125	42°03'	- 81°30'	42°49'	- 79°17'	
87	91	41°59'	- 80°42'	42°49'	- 79°17'	Cleveland
88	22	42°52'	- 78°56'	42°49'	- 79°17'	
89	43	42°49'	- 79°17'	43°16'	- 79°13'	
90	29	43°37'	- 49°25'	43°16'	- 79°13'	
91	134	43°37'	- 49°25'	43°49'	- 76°49'	Toronto Toronto Welland Oswego
92	129	43°16'	- 79°13'	43°49'	- 76°49'	
93	29	43°29'	- 76°32'	43°49'	- 76°49'	
94	60	43°49'	- 76°49'	44°21'	- 75°55'	
						Welland Canal
						Welland Canal
						Alexandria Bay

TABLE 4.2 (CONTINUED)

REACH	LENGTH (mi)	UPSTREAM NODE		DOWNSTREAM NODE	
		N. LAT. - W. LONG.	LANDMARK	N. LAT. - W. LONG.	LANDMARK
95	145	44°21' - 75°55'	Alexandria Bay	45°00' - 74°40'	Cornwall
96	145	45°00' - 74°40'	Cornwall	45°34' - 73°29'	Montreal
97	273	45°34' - 73°29'	Montreal	46°47' - 71°13'	Quebec
98	435	46°47' - 71°13'	Quebec	49°04' - 68°02'	Baie Comeau
99	203	49°04' - 68°02'	Baie Comeau	49°47' - 66°00'	
100	70	50°12' - 66°20'	Sept-Iles	49°47' - 66°00'	
101	406	49°47' - 66°00'		48°18' - 62°16'	To Overseas Ports
102	69	46°34' - 87°22'	Presque Isle	47°35' - 87°30'	
103	131	47°35' - 87°30'		46°48' - 84°56'	Whitefish Pt.

TABLE 4.3

FREEZING DEGREE DAY COEFFICIENTS (α)
AND BRASH ICE POROSITY (β) FOR EACH REACH

NORMAL WINTER			SEVERE WINTER		
REACH	α	β	REACH	α	β
41	.74	.25	81	.66	.25
42	.20	.25	82	.82	.25
43	.20	.25	83	.66	.25
44	.20	.25	84	.66	.25
45	.20	.25	85	.87	.25
46	.20	.25	86	.82	.25
47	.20	.25	87	.82	.25
48	.95	.25	88	.82	.25
49	.68	.25	89	.84	.25
50	.48	.25	90	.84	.25
51	.53	.25	91	.84	.25
52	.53	.25	92	.84	.25
53	.52	.25	93	1.27	.25
54	1.07	.25	94	.58	.25
55	1.28	.25	95	.61	.25
56	.75	.25	96	.63	.25
57	.60	.25	97	.63	.25
58	1.17	.25	98	.63	.25
59	.86	.25	99	.63	.25
60	.43	.25	100	.63	.25
61	.57	.25	101	.63	.25
62	.52	.25	102	.77	.25
63	.47	.25	103	.62	.25
64	.62	.25			
65	.48	.25			
66	.70	.25			
67	1.16	.25			
68	.90	.25			
69	.90	.25			
70	.84	.25			
71	.78	.25			
72	.75	.25			
73	.72	.25			
74	1.11	.25			
75	1.11	.25			
76	.72	.25			
77	.65	.25			
78	.65	.25			
79	.66	.25			
80	.57	.25			

5. ICEBREAKER AND SHIP CLASS SELECTION

In the simulation, ships which transit the GL/SLS Navigation System were divided into four major types:

- Laker Bulk Vessels
- Ocean-Going Bulk Vessels
- Ocean-Going General Cargo Vessels
- Icebreakers

These major vessel types, with the exception of icebreakers, were further divided into classes to distinguish between different vessel sizes, carrying capacities, and characteristics using the following standard Corps of Engineers Classification based on ship length:

CORPS OF ENGINEERS VESSEL CLASSIFICATION BY LENGTH

<u>Class</u>	<u>Vessel Length (feet)</u>
1	Under 400
2	400 - 499
3	500 - 549
4	550 - 599
5	600 - 649
6	650 - 699
7	700 - 730
8	731 - 849
9	850 - 949
10	950 - 1000

For icebreakers, three (3) vessel classes were used corresponding to the U.S. Coast Guard's classification of Class B, C, and D icebreakers. Each vessel type and class, other than icebreakers, used in the simulation to represent the vessels operating in the extended navigation season are described in Tables 5.1, 5.2, and 5.3 by the following characteristics listed below. In a similar manner, each icebreaker class is described by the series of characteristics in Table 5.4.

<u>Characteristic</u>	<u>Description</u>
Length	Overall length of ship (feet).
Beam	Maximum width of ship at the waterline (feet).
Horsepower	Maximum shaft horsepower generated by engines (hp).
Engine Type	Type of propulsion system.

TABLE 5.1

LAKER BULK VESSEL CHARACTERISTICS

CHARACTERISTICS	SHIP CLASS					
	5	6	7	8	10	
Length (feet)	640	699	730	767	1,000	
Beam (feet)	67	70	75	70	105	
Horsepower	4,000	7,700	8,800	7,000	14,000	
Engine Type	Steam Turbine	Steam Turbine	Steam Turbine	Steam Turbine	Diesel	
V_{design}	14.5	16.5	16.5	16.5	18.0	
Locking Time SLS (minutes)	37	39	41	41	59	
Locking Time WELLAND (minutes)	36	37	39	40	43	
Locking Time S00 (minutes)	56	57	55	66	87	
Midsummer Draft (feet)	24.6	26.3	27.9	26.2	28.6	
Winter Draft (feet)	22.0	24.5	26.0	24.5	28.6	
Long Tons/Foot Immersion	996	1,206	1,452	1,404	2,542	
Self-Unloading Rate (long tons/hr.)	3,000	4,000	5,000	5,000	8,500	
MS Iron Ore (long tons)	18,150	22,400	27,600	26,500	57,500	
MS Coal (long tons)	16,340	20,160	24,840	23,850	51,750	
MS Grain (long tons)	16,340	20,160	24,840	23,850	51,750	
Ice Class	II	IC	II	II	IC	
Number of Crew	27	32	32	38	21	
Total Sale Price (10^6)	6.97	12.15	17.29	17.28	33.60	
Cubic Number	15,526	18,817	21,710	22,008	50,946	
Gross Registered Tons	10,291	10,317	13,390	15,483	24,199	
Capital Recovery Factor	0.157	0.139	0.134	0.139	0.131	
Horsepower/Length Ratio	6.25	11.02	12.05	9.13	14.00	

TABLE 5.2
OCEAN-GOING BULK VESSEL CHARACTERISTICS

CHARACTERISTICS	SHIP CLASS						
	4	5	6	7			
Length (feet)	566	635	681	709			
Beam (feet)	72	75	75	75			
Horsepower	9,000	9,600	11,500	12,800			
Engine Type	Diesel	Diesel	Diesel	Diesel			
V_{design}	19.0	17.3	18.4	17.3			
Locking Time SLS (minutes)	33	37	39	41			
Locking Time WELLAND (minutes)	35	36	37	39			
Locking Time S00 (minutes)	56	56	57	55			
Midsummer Draft (feet)	31.0	33.4	35.1	36.0			
Winter Draft (feet)	31.0	33.4	35.1	36.0			
Long Tons/Foot Immersion	1,125	901	1,266	1,290			
MS Grain (long tons)	16,257	19,698	21,870	32,105			
Ice Class	IB	IC	IC	IB			
Number of Crew	30	30	30	30			
Total Sale Price (10^6)	2.38	7.20	10.27	11.31			
Cubic Number	13,510	17,148	19,312	20,671			
Gross Registered Tonnage	14,468	12,100	19,644	21,288			
Capital Recovery Factor	0.33	0.20	0.17	0.17			

TABLE 5.3
OCEAN-GOING GENERAL CARGO CHARACTERISTICS

CHARACTERISTICS	SHIP CLASS		
	1	2	3
Length (feet)	397	477	528
Beam (feet)	55	64	75
Horsepower	5,400	10,000	18,400
Engine Type	Diesel	Diesel	Diesel
<i>V design</i> (mph)	18.4	19.6	23.6
Locking Time SLS (minutes)	30	31	32
Locking Time WELLAND (minutes)	31	32	34
Locking Time S00 (minutes)	42	48	54
Midsummer Draft (feet)	25.3	28.6	31.5
Winter Draft (feet)	25.3	28.6	31.5
Long Tons/Foot Immersion	420	720	662
MS General (long tons)	5,313	10,863	10,226
Ice Class	IA	IA	IA
Number of Crew	30	30	30
Total Sale Price (10 ⁶)	5,310	5,525	8,670
Cubic Number	5,523	8,908	12,473
Gross Registered Tons	5,419	9,003	10,846
Capital Recovery Factor	0.17	0.17	0.16

TABLE 5.4
ICEBREAKER CHARACTERISTICS

Characteristics	Class B	Class C	Class D
Length (feet)	280	130	107
Beam (feet)	70	34	25
Horsepower	10,000	2,500	1,000
V_{design} (mph)	19.2	17.1	14.7
Maximum Number of Ships in Convoy	6	3	--
Maximum Endurance for Convoy (hr)	∞	36	--

CHARACTERISTIC - Cont.

V_{design}

Locking Time - SLS

Locking Time - WELLAND

Locking Time - S00

Midsummer Draft

Winter Draft

Long Tons/Foot Immersion

Self-Unloading Rate

MS Iron Ore

MS Coal

MS Grain

MS General Cargo

DESCRIPTION - Cont.

Maximum speed capability of the ship in open water (mph)

Time required for ship to lock through one lock at the St. Lawrence Seaway excluding delays (minutes)

Time required for ship to lock through one lock at the Welland Canal excluding delays (minutes)

Time required for ship to lock through a lock at Sault Ste. Marie excluding delays (minutes)

Draft to which a vessel can load amid-ships during the designated Midsummer Season (feet)

Draft to which a vessel can load amid-ships during the designated Winter Season (feet)

Long tons required to increase draft of vessel one foot (long tons per foot)

Rate at which cargo can be unloaded by on-board unloading devices (long tons per hour)

Maximum iron ore capacity required to achieve Midsummer Draft (long tons)

Maximum coal capacity (long tons) at Midsummer Draft

Maximum grain capacity (long tons) at Midsummer Draft

Maximum general cargo capacity at Midsummer Draft (long tons)

CHARACTERISTIC - Cont.DESCRIPTION - Cont.

Ice Class

Rating as to the ice condition
the ship can proceed through:IA: Extremely severe ice
conditions

IB: Severe ice conditions

IC: Mild ice conditions

II: Light ice conditions

Number of Crew

Number of working personnel
aboard vessel

Total Sale Price

Estimated current sale price
of vessel

Cubic Number

Product of the vessel's length,
beam and depth divided by 100
(ft³)

Gross Registered Tonnage

Cubic feet of interior space
divided by 100

Capital Recovery Factor

Factor by which the initial
investment is multiplied in
order to find the annual cost
of capital recovery

These vessel characteristics were obtained by selecting representative ships for each class and gathering data for each from *Greenwood's Guide to Great Lakes Shipping* [9] and from discussions with owners. Once the data was gathered, certain characteristics were adjusted to more accurately reflect ships operating in specific trades. For example, lakers operating in the grain and coal trade generally have deeper cargo compartments than the usual iron ore ship because of the lower cargo density (lbs per cubic foot) of grain and coal compared to iron ore. These ships thus require more cubic volume capacity per ton of grain or coal than per ton of iron ore. To reflect this condition, the maximum grain and coal capacities indicated for laker bulk vessels were defined as 90% of the maximum iron ore capacities.

In discussing individual ship classes, an important measure of performance is their ice transiting capability or icebreaking performance. Numerous measures of icebreaking performance have been proposed in the past. Two of the more frequently encountered measures are thickness of sheet ice which can be broken in either a continuous or ramming mode of operation, and penetration distance after impact during ramming. These measures are not very meaningful in terms of cargo ships whose primary purpose is to move cargo from one point to another and not to break ice per se. Therefore, a much more meaningful measure of icebreaking or ice navigability is the speed a ship can attain through a given ice field. In Figures 5.1 through 5.5 the maximum speed of advance versus brash ice thickness for various refrozen brash ice thicknesses is given for representative ship classes. The method used in producing these figures is described in Section 3.3 of this report.




FIGURE 5.1 SPEED OF ADVANCE VS UNCONSOLIDATED BRASH ICE THICKNESS (0 inches Refrozen Brash Ice)




FIGURE 5.2 SPEED OF ADVANCE VS UNCONSOLIDATED BRASH ICE THICKNESS (5 inches Refrozen Brash Ice)




FIGURE 5.3 SPEED OF ADVANCE VS UNCONSOLIDATED BRASH ICE THICKNESS (10 inches Refrozen Brash Ice)




FIGURE 5.4 SPEED OF ADVANCE VS UNCONSOLIDATED BRASH ICE THICKNESS (15 inches Refrozen Brash Ice)




FIGURE 5.5 SPEED OF ADVANCE VS UNCONSOLIDATED BRASH ICE THICKNESS (20 inches Refrozen Brash Ice)

6. RESULTS OF SIMULATION RUNS

6.1 Overview

In the following subsections, the results of the validation and production runs are presented and discussed. The validation of the simulation, which is presented in Section 6.2, consisted of three (3) separate phases: (1) Series of step-by-step planned debugging procedures; (2) Comparison of 1975-76 "normal" winter with historical USCG icebreaker statistics; and, (3) Comparison of 1975-76 fixed icebreaker fleet statistics with icebreaker statistics generated by maximum response time mode. The production runs listed in Section 6.3 consisted of ten (10) executions of the simulation with input data varied to assess the following:

- Effect of a 20% increase in cargo tonnage with a fixed fleet of icebreakers (normal winter).
- Effect of a 12-hour variation in maximum response time on icebreaker requirements (normal winter).
- Effect of convoys on icebreaker requirements (normal winter).
- Comparison of the maximum response time (MRT) generated icebreaker fleet to the USCG estimated fleet (normal winter).
- Effect of winter severity (normal vs severe) on icebreaker requirements.
- Effect of having only Class B icebreakers escort convoys, as opposed to both Class B and Class C, on icebreaker requirements (severe winter).
- Effect of prohibiting vessels with low SHP from operating in the extended season on icebreaker requirements (severe winter).
- Effect of conducting channel clearing in certain channels on icebreaker requirements (severe winter).
- Comparison of the maximum response time (MRT) generated icebreaker fleet to the USCG estimated fleet (severe winter).

A comparison of the results assessing the above items is presented in Section 6.3. Detailed summaries of the results of the ten production runs are summarized in tabular form in Section 6.4.

6. RESULTS OF SIMULATION RUNS

6.2 Validation

There were three phases to the validation process:

- PHASE 1 - Detailed simulation module checkout
- PHASE 2 - Fixed icebreaker fleet run using historic 1975-76 data
- PHASE 3 - Maximum response time run to compare with Phase 2

6.2.1 Phase 1 of the Validation - Checkout of Simulation Modules

Input Data to Ship Processing Model

The two most important aspects of the simulation are the ice conditions and the maximum speed capability of the commercial vessels, since these translate directly into icebreaker support requirements. Figures 5.1 through 5.5 illustrate the maximum speed of advance versus ice type and thickness for various vessel classes. From these plots, the performance in ice of each ship class can easily be established. For example, a Class 5 Laker can proceed through approximately 40 inches of brash ice with zero refrozen thickness at a speed of advance of 5 mph, but it will become stuck in 50 inches of brash ice assuming a vessel speed of less than 2 mph corresponds to a vessel being stuck. For a Class 10 Laker, the maximum brash ice thickness it can proceed through is 69 inches with zero refrozen thickness, and 33 inches of brash with a 5 inch refrozen cover. These curves, particularly the maximum ice thickness at 2 mph, appear to be reasonable and consistent with experience.

The ice conditions data files were reviewed reach-by-reach to ensure that the predicted occurrences of ships becoming stuck and the trouble areas identified were also consistent with operating experience. The input data files for normal and severe winters contained ice growth calibration factors by reach, which were adjusted to obtain realistic ice conditions. For example, it is well known that brash ice accumulates to greater depths in the confined river channels than it does in the open lakes. Since the same equations and temperatures are used for both in the Ice Growth Model, these calibration factors provided the necessary differentiation in brash ice buildup. In Tables 6.1 through 6.4, the final results of this analysis are presented showing what class vessels will be stuck where, and when, for the laker fleet. These tables agree with operating experience in identifying the trouble areas as a function of winter severity and traffic level. By using the reach calibration factors, environmental aspects not directly accounted for in the Ice Growth Model, such as the effect of winds, currents, and channel widths, were included.

OCCURRENCES OF LAKERS BECOMING STUCK FOR SEVERE WINTER AND HEAVY TRAFFIC

6-4

TABLE 6.2

OCCURRENCES OF LAKERS BECOMING STUCK FOR SEVERE WINTER AND MODERATE TRAFFIC

Reach Number	CLASS 5	CLASS 6	CLASS 7	CLASS 8	CLASS 10
	Period	Period	Period	Period	Period
	2 3 4 5 6 7 8 9 10	2 3 4 5 6 7 8 9 10	2 3 4 5 6 7 8 9 10	2 3 4 5 6 7 8 9 10	2 3 4 5 6 7 8 9 10
41	X X X X X X X X	X X X	X	X X X X X X	X
42					
43					
44					
45					
46					
47					
48	X X X X X	X		X	
49					
50	X X X X X X X				
51	X X X X X X X			X X X	
52	X X X X X X X				
53	X X X X X X X				
54	X X X X X				
55	X X X X X				
56	X X X X X			X	
57	X X X X X X	X X	X X	X X X	X
58					
59					
60	X				
61	X				
62					
63	X				
64	X				
65					
66	X X				
67	X X				
68	X X				
69	X X X X X	X X X	X X X	X X X X	X X X
70	X X X X X X	X X X	X X X	X X X X	X X X
71	X X X X X				
72	X X X X X				
73	X X X X X				
74	X X X X X				
75	X X X X X				
76	X X X X X				
77	X X X X X				
78	X X X X X				
79	X X X X X				
80	X X X X X				
81	X X X X X				
82	X X X X X				
83	X X X X X				
84	X X X X X				
85	X X X X X				
86	X X X X X				
87	X X X X X				
88	X X X X X X	X X X X	X X X	X X X X	X X X
89	X X X X X	X		X	
90					
91					
92					
93					
94	X X X X X			X X X	
95	X X X X X	X	X	X X	
96	X X X X X X	X X	X	X X	X
97	X X X X X X	X X	X	X X	X
98	X X X X X X	X		X X	
99	X X X X X X				
100	X X X X X X				
101	X X X X X				
102					
103					

TABLE 6.3

OCCURRENCES OF LAKERS BECOMING STUCK FOR NORMAL WINTER AND HEAVY TRAFFIC

Reach Number	CLASS 5	CLASS 6	CLASS 7	CLASS 8	CLASS 10
	Period	Period	Period	Period	Period
	2 3 4 5 6 7 8 9 10	2 3 4 5 6 7 8 9 10	2 3 4 5 6 7 8 9 10	2 3 4 5 6 7 8 9 10	2 3 4 5 6 7 8 9 10
41	X X X X X X	X X X X X	X X X X X	X X X X X	X X X X X
42					
43					
44					
45					
46					
47					
48	X X X X X	X X X X	X X X X	X X X X	X X
49	X X X X X				
50	X X X X X				
51	X X X X X	X X		X X	
52				X X	
53	X X X X	X X		X X	
54	X X X	X	X	X	X
55	X X				
56	X X X				
57	X X X X X				
58					
59					
60					
61					
62					
63					
64					
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76	X X				
77	X X				
78	X X				
79					
80					
81					
82					
83					
84					
85					
86	X X				
87	X X				
88	X X X	X	X	X X	X
89					
90					
91					
92					
93					
94					
95	X X X			X	
96	X X X			X	
97	X X X X X	X X X X X	X X X X X	X X X X X	X X X X X
98	X X X X X	X X X X	X X X X	X X X X	X X X X
99	X X X X	X X X X	X X X	X X X X	X X X X
100	X X X X	X X X X	X X X	X X X X	X X X X
101	X X X X			X X X X	X X X X
102				X X	
103					

OCCURRENCES OF LAKERS BECOMING STUCK FOR NORMAL WINTER AND MODERATE TRAFFIC

6-7

Specific problem areas, which were identified and modeled in the simulation, are:

Duluth, Minnesota/Superior, Wisconsin - Some of the coldest air temperatures on the Great Lakes occur here because predominantly northwest winds reach the water only after passing over large expanses of land. The Apostle Islands east of the harbor entrance prevent ice from moving into open Lake Superior and occasional easterly winds may actually cause an ice jam at the harbor entrance. Currently there is no year-round shipping because of the ice conditions, while only a few miles to the northeast, Two Harbors does not experience blockage by ice.

Whitefish Bay, Lake Superior - This small area at the southeast corner of the lake is the first part of Lake Superior to experience problems. Ice accumulations occur here due to wind-driven ice from Lake Superior being trapped within the confines of the bay.

St. Marys River, Michigan - Heavy shipping in this shallow, narrow channel causes brash ice buildups, particularly just downstream of Sault Ste. Marie in Little Rapids Cut and Lake Nicolet. Some of the problems are due to ice moving with the current being trapped in narrow sections. Increased future traffic should be expected to bring more water to the surface, thus causing thicker brash accumulations.

Straits of Mackinac, Michigan - Wind-driven ice from Lake Michigan accumulates between St. Ignace and Lansing Shoal due to the constriction at this point.

Detroit/St. Clair System and Western Lake Erie - Shallow water leads to a low thermal inertia in the area so that ice forms here early in the season. Islands in the lake stabilize the ice cover, minimize waves, and thus prevent wind from moving the ice away from the western shore. Ice floes from Lake Huron pass through the St. Clair River, but stop in Lake St. Clair and the upper Detroit River, causing problems for shipping.

Buffalo, New York - The situation at Buffalo is similar in origin to that in Whitefish Bay, but much worse due to the shallow water in Lake Erie. Predominantly west winds concentrate all the ice formed on Lake Erie into heavily rafted windrows at the harbor entrance at the far eastern end of Lake Erie.

Welland Canal, Ontario - Although no winter shipping takes place now, heavy winter traffic would cause problems here similar to those in the St. Marys River.

St. Lawrence Seaway - The situation here is similar to that of the Welland Canal and St. Marys River. Brash buildups will occur in the shallow channels.

Lower St. Lawrence River, Quebec - Cold temperatures here cause a heavy ice growth.

Execution of Ship Processing Model

As part of the module checkout, a new or modified code in the Ship Processing Model was "computed" by hand by a debugging team to check the logic and mathematics of each subroutine. Then, special debugging input speed files were prepared such that each ship or icebreaker class traveled at 10 mph in every reach. A very detailed printout during the program execution was examined while a prepared sequence of runs for the Ship Processing Model was followed to exercise the model in a progressively more elaborate execution:

- Fixed icebreaker fleet mode; small commercial fleet; convoy flags off. Five runs to check stuck codes 1, 2, 3, 4, 5 (stuck at upper end of reach due to resistance, stuck at upper end of reach in a turn, stuck at lower end of reach due to resistance, stuck at lower end of reach in a turn, stuck at either end of the reach) in reach 103.
- Five runs, same as above, but stuck in reaches 103, 59, 47, 97.
- One run, with stuck code 1 in reach 103, 2 in reach 59, 3 in reach 47, 4 in reach 86, 5 in reach 97.
- One run with no ships stuck, but convoy in reaches 50-51.
- Same as preceding step, but also with convoys in 53, and 72-73-74-76.
- Same as preceding step, but also with stuck code 1 in reach 103, 2 in reach 59, 3 in reach 47, 4 in reach 86, 8 in reach 97.
- Maximum response time mode; small commercial fleet, convoy flags off. Five runs to check stuck codes 1, 2, 3, 4, 5 (stuck at upper end of reach due to resistance, stuck at upper end of reach in a turn, stuck at lower end of reach due to resistance, stuck at lower end of reach in a turn, stuck at either end of the reach) in reach 103.
- Five runs, same as above, but stuck in reaches 103, 59, 47, 97.

- One run, with stuck code 1 in reach 103, 2 in reach 59, 3 in reach 47, 4 in reach 86, 5 in reach 97.
- One run with no ships stuck, but convoy in reaches 50-51.
- Same as preceding step, but with large commercial fleet, also with convoys in reaches 53 and 72-73-74-76.
- Same as preceding step, but also with stuck code 1 in reach 103, 2 in reach 59, 3 in reach 47, 4 in reach 86, 5 in reach 97.

6.2.2 Phase 2 of the Validation - 1975-76 Run

As with any computer simulation, the results obtained are only as good as the basic input data and rules and assumptions. Every effort was made to ensure the simulation represented the Great Lakes-St. Lawrence Seaway System as realistically as possible. In doing so, use was made of knowledge and experience collected by interviewing USCG operations personnel at the outset of this contract and, in addition, of knowledge gained as a result of the SPAN Study [8], ice model testing in our towing basin, full-scale test programs on the Great Lakes, the Great Lakes Harbor Study [10], and conversations with ship operators, port officials, and personnel at the Coast Guard, MarAd, U.S. Army Corps of Engineers, and St. Lawrence Seaway Development Corporation. As much detail as possible was included in the algorithms while keeping execution of the simulation inexpensive enough to be used as a planning tool to identify problem areas and bottlenecks to extended season navigation and to evaluate potential improvements, particularly the allocation of ice-breaker support.

The real test of how realistically the simulation represents the Great Lakes-St. Lawrence Seaway System is by validation--and the degree to which the simulation is validated is a direct measure of its credibility. Much effort had already been given to validating the original simulation, particularly in regard to the commercial vessel transit times and freight rates, which is described in Volume II of Reference [1]. In validating any simulation, one would naturally like to have as much available historical data, as possible, not only for use in the validation but also for use in developing and refining the algorithms themselves. For this particular simulation, only limited data exists and, in fact, for parts of the system, the data is practically non-existent; the simulation should therefore be periodically revalidated as more data becomes available through continued shipping in the extended season. With these thoughts in mind, both ship and icebreaker performance were validated by comparing their performance to available historical data, since both play an equally important role in the simulation.

The 1975-76 severe winter was run with the Coast Guard icebreaker fleet listed in Table 6.5 and the cargo routes and tonnages listed in Table 6.6 For

TABLE 6.5
1975-76 VALIDATION ICEBREAKER ASSIGNMENTS

<u>Home Port</u>	<u>Icebreaker</u>	<u>Class</u>
Thunder Bay (Canadian)	ALEXANDER HENRY	D
Sault Ste. Marie	ARUNDEL	D
	NAUGATUCK	D
	RARITAN	D
	MACKINAW	B
St. Ignace	SUNDEW	D
	WOODRUSH	D
	WIND	B
Green Bay	MESQUITE	D
Port Huron	BRAMBLE	D
Detroit	KAW	D
	MARIPOSA	D
Toledo	OJIBWA	D
Toronto (Canadian)	NORMAN MCLEOD ROGERS	D
Oswego	(Dummy)	D
Quebec (Canadian)	LOUIS ST. LAURENT	B

TABLE 6.6
LAKER ROUTES AND TONNAGES
FOR 1975-76 VALIDATION

<u>Route</u>	<u>Origin</u>	<u>Destination</u>	<u>Cargo (Thousands of Short Tons)</u>
-----Iron Ore-----			
1	Escanaba	Cleveland	832
3	Escanaba	Chicago	724
6	Two Harbors	Toledo	546
7	Two Harbors	Detroit	609
8	Two Harbors	Chicago/Gary	6981
9	Thunder Bay	Cleveland	81
12	Thunder Bay	Chicago	320
		TOTAL IRON ORE	10093
-----Coal-----			
18	Toledo	Detroit	3000
		TOTAL COAL	3000

validation purposes, the Coast Guard provided copies of its 1975-76 Great Lakes Icebreaking Assistance Reports. These logs showed:

- Date of assistance
- Name of ship assisted
- User of ship assisted
- Cargo data (type, tonnage)
- Port of departure and port of destination
- Name of assisting icebreaker
- Geographical area of assistance
- Hours underway
- Mission miles
- Miscellaneous remarks

If one (or more) icebreakers simultaneously escorted more than one ship (i.e., a convoy), this was noted under "remarks". These logs were analyzed on an icebreaker-by-icebreaker basis to compile the statistics for comparing the validation run to historical data.

Table 6.7 summarizes these statistics on the lines labeled "USCG Log", grouped by task command and by period. The line labeled "Simulation" is the validation run output for comparison. Data given includes:

- Number of direct assists
- Number of convoyed (simultaneous) assists
- Hours of assistance (direct plus convoyed)
- Miles of assistance (direct plus convoyed)
- Average time per assist (hours/assist)

The agreement between the Coast Guard log and the simulation is best in the Taconite task command where the commercial traffic is most accurately modeled. In particular, the average hours per assist of 8.98 is very close to the USCG Log's 8.40. Agreement in the other task commands is not as good because traffic (primarily tug/barge transits) existed and was not included in the simulation. This significantly alters the icebreaking statistics. For example, in the Coal Shovel Task Command, many assists were logged to the fuel barge traffic on the Sarnia to Detroit route. Of the 934 hours, a total of 640 hours were by two or more icebreakers simultaneously assisting tows operated by the Hannah Waterways Company in the St. Clair River. In a similar manner, the hours per assist in the Oil Can Task Command is high because Green

TABLE 6.7

SUMMARY OF 1975-76 VALIDATION RUN

		PERIOD										TOTAL										
		2	3	4	5	6	7	8	9	10												
Assists	DA	C	DA	C	DA	C	DA	C	DA	C	DA	C	DA	C								
	Taconite	USCG Log	1	0	1	0	27	0	39	11	24	15	10	6	18	11	3	3	134	52		
	Simulation	0	0	0	0	4	42	0	35	0	22	0	21	0	13	0	32	0	2	4	167	
	Oil Can	USCG Log	4	0	0	0	1	0	4	0	2	0	0	0	0	0	2	0	1	0	14	0
	Simulation	0	0	0	0	4	0	0	0	12	0	1	0	7	0	0	0	0	0	24	0	
Coal Shovel	USCG Log	0	0	7	1	28	2	16	4	8	0	0	0	0	0	0	0	0	7	2	66	9
	Simulation	0	0	0	0	0	26	0	17	0	1	0	4	0	24	0	57	0	0	0	129	
Hours		Average Hours/Assist																				
Taconite	USCG Log	32	1	97	395	423	157	190	348	27	1670	8.98										
	Simulation	0	0	350	262	181	171	126	309	37	1436	8.40										
	Oil Can	31	0	1	26	47	0	0	31	0	136	9.71										
	Simulation	0	0	78	0	301	24	211	12	0	626	26.08										
Coal Shovel	USCG Log	0	86	268	447	106	0	0	0	27	934	12.45										
	Simulation	0	0	39	24	2	6	37	88	1	197	1.53										
Miles																						
Taconite	USCG Log	330	5	665	1741	1616	907	763	1737	1926	9690											
	Simulation	0	0	3618	2582	1768	1578	1066	2166	408	13186											
Oil Can	USCG Log	202	0	4	133	178	0	0	239	6	762											
	Simulation	0	0	784	0	3462	308	2352	158	0	7064											
Coal Shovel	USCG Log	0	508	1347	1233	213	0	0	0	45	3346											
	Simulation	0	0	333	207	18	54	315	756	9	1692											

Notes: 1. Convoys in reaches 51, 74, periods 1 to 9.
 2. DA = Direct Assist; C = Convey.

Bay was used for the icebreaker home port, whereas Escanaba was actually used in the extended season because the traffic out of Northern Lake Michigan (during the extended season) was entirely out of Escanaba in the validation year.

It should also be noted that a "convoy" on the Coast Guard log is not as rigorously categorized as in the simulation; that is, once the simulation defines a reach as a convoy reach, *all* ships must convoy through it, and a convoy of one ship is still called a convoy. On the other hand, a convoy of one ship in the Coast Guard log looks like a direct assist. For this reason, comparing the number of direct assists and number of convoys between the log and the simulation is not as accurate a comparison as comparing the total number of assists as shown below:

	<u>USCG Log</u>	<u>Simulation</u>
Taconite	186	171
Oil Can	14	24
Coal Shovel	75	129

Examining the above and the time per transit, it was concluded after review with U.S. Coast Guard representatives, that the simulation satisfactorily modeled icebreaker support on the Great Lakes.

6.2.3 Phase 3 of the Validation - Maximum Response Time

The same input conditions as for Phase 2 were run in the maximum response time (MRT) mode. The MRT for each reach which is tabulated below:

MRT (HOURS) VALUES FOR VALIDATION

<u>REACH</u>	<u>MRT</u>	<u>REACH</u>	<u>MRT</u>	<u>REACH</u>	<u>MRT</u>	<u>REACH</u>	<u>MRT</u>	<u>REACH</u>	<u>MRT</u>
41	7	54	33	67	15	80	13	93	7
42	9	55	49	68	21	81	9	94	13
43	15	56	23	69	31	82	25	95	31
44	19	57	17	70	19	83	17	96	31
45	17	58	37	71	21	84	19	97	57
46	23	59	19	72	7	85	9	98	89
47	45	60	9	73	9	86	31	99	129
48	47	61	11	74	3	87	25	100	143
49	25	62	21	75	5	88	7	101	211
50	9	63	9	76	9	89	11	102	15
51	11	64	17	77	7	90	7	103	31
52	9	65	13	78	13	91	29		
53	11	66	23	79	7	92	33		

was equal to the time that an icebreaker would require to get to the furthest point in the reach from the closest home port traveling at 10 mph. Table 6.8

TABLE 6.8
SUMMARY OF 1975-76 VALIDATION RUN (MRT MODE)

		PERIOD																		TOTAL		
		2	3	4	5	6	7	8	9	10												
Assists		DA	C	DA	C	DA	C	DA	C	DA	C	DA	C	DA	C	DA	C	DA	C	DA	C	
	Taconite	USCG Log	1	0	1	0	27	0	39	11	24	15	10	6	11	6	18	11	3	3	134	52
		Simulation	0	0	0	0	4	41	0	35	0	22	0	21	0	15	0	28	0	2	4	164
	Oil Can	USCG Log	4	0	0	0	1	0	9	0	2	0	0	0	0	0	2	0	1	0	14	0
		Simulation	0	0	0	0	4	0	0	0	13	0	0	0	7	0	1	0	0	0	25	0
Coal Shovel	USCG Log	0	0	7	1	28	2	16	4	8	0	0	0	0	0	0	0	0	7	2	66	9
	Simulation	0	0	0	0	0	26	0	16	0	1	0	6	0	24	0	56	0	1	0	130	
Hours																						
Taconite	USCG Log	32	1	97	395	423	157	190	348	27	1670											1670
	Simulation	0	0	388	294	195	199	199	316	24	1615											1615
Oil Can	USCG Log	31	0	1	26	47	0	0	31	0	136											136
	Simulation	0	0	79	0	339	0	221	23	0	662											662
Coal Shovel	USCG Log	0	86	268	447	106	0	0	0	27	934											934
	Simulation	0	0	46	26	2	11	44	96	6	231											231
Miles																						
Taconite	USCG Log	330	5	665	1741	1616	907	763	1737	1926	9690											9690
	Simulation	0	0	3527	2300	1334	1334	1058	1518	212	11203											11203
Oil Can	USCG Log	202	0	4	133	178	0	0	239	0	762											762
	Simulation	0	0	784	0	4350	0	2868	324	0	8326											8326
Coal Shovel	USCG Log	0	508	1347	1233	213	0	0	0	45	3346											3346
	Simulation	0	0	360	198	18	81	342	738	52	1789											1789

shows the number of assists, total hours, and total miles for the Taconite, Oil Can, and Coal Shovel task commands as a function of time. These results are essentially the same as those in the fixed fleet mode run (Table 6.7) which indicates that the same assistance pattern was reproduced in the MRT mode. That is, the same ships were stuck in the same places at the same time. Specifically, in Taconite there were a total of 4 direct assists and 167 convoys in the fixed fleet mode run versus 4 direct assists and 164 convoys in the MRT mode run. Similarly, in Oil Can there were 24 direct assists and no convoys in the fixed fleet mode run and 25 direct assists and no convoys in the MRT mode run, while in Coal Shovel there were no direct assists and 129 convoys in the fixed fleet mode run and no direct assists and 130 convoys in the MRT mode run. The time and mileage of the assists changed somewhat due to the different fleet mix/home port combinations that the MRT mode run produced. It also should be noted that in the convoy mode of operations the MRT and the fixed fleet modes are almost identical.

Table 6.9 shows the icebreaker fleet that was generated by the MRT simulation run, by Task Command, icebreaker class, and period. The maximum icebreaker requirements were 4 in Taconite Task Command in period 4, 2 in the Oil Can Task Command in periods 6 and 8, and 1 in the Coal Shovel Task Command in periods 4 through 10. As discussed previously, commercial traffic was best modeled in Taconite, where there were fewer barge transits during the extended season. The MRT run produced a maximum of 2 icebreakers in Sault Ste. Marie, and 2 in St. Ignace, for a total of 4 in Taconite. The Coast Guard assignments in Table 6.5 had 4 in Sault Ste. Marie and 3 in St. Ignace. It should be noted that only Class D icebreakers were generated by the simulation. This is because the simulation generates the least capable icebreaker that can still perform the required task. To prevent this from occurring on future runs will require a slight modification to MRT module to prohibit Class D icebreakers from being generated. Without barge traffic and realizing additional icebreaker support would be used for preventive icebreaking and channel maintenance, the MRT output appears reasonable, and it was concluded that the MRT mode functioned correctly.

6.2.4 Phase 4 of the Validation - Transit Times

Another source of validation data for the simulation is a ship's calculated round trip time on a route for which there is historic data readily available. The only readily available data showing exact vessel transit time of a significant portion of the extended navigation season and for several years was the Two Harbor-to-Gary iron ore route from reference [1], updated from reference [11]. This historical data is superimposed on the predictions obtained from production runs of the simulation in Figures 6.1 through 6.3 for laker ship classes 5, 8, and 10 respectively. While there is a large amount of fluctuation in the data, good agreement existed for the normal season, and there was no substantial disagreement in the extended season, recognizing the large amount of scatter in the historical data. Note for example that the peak transit times indicated by the simulation to occur in periods 5-6 of the normal winter (1975-76) actually occurred in the 1975-76 data points.

TABLE 6.9
ICEBREAKER FLEET GENERATED BY
1975-76 VALIDATION RUN (MRT MODE)

	PERIOD									
	1	2	3	4	5	6	7	8	9	10
Taconite										
Class D	0	0	0	4	2	1	1	2	2	1
Class C	0	0	0	0	0	0	0	0	0	0
Class B	0	0	0	0	0	0	0	0	0	0
Oil Can										
Class D	0	0	0	1	0	2	0	2	1	0
Class C	0	0	0	0	0	0	0	0	0	0
Class B	0	0	0	0	0	0	0	0	0	0
Coal Shovel										
Class D	0	0	0	1	1	1	1	1	1	1
Class C	0	0	0	0	0	0	0	0	0	0
Class B	0	0	0	0	0	0	0	0	0	0




Figure 6.1 Round Trip Time From Two Harbors to Gary for Class 5 Laker Vessel

AD-A082 164

ARCTEC INC COLUMBIA MD

COMPUTER SIMULATION OF GREAT LAKES-ST. LAWRENCE SEAWAY ICEBREAK--ETC(U)

JAN 80 T V KOTRAS, J J PETER

DOT-C6-81-78-1953

F/6 15/5

UNCLASSIFIED


296C-4

USCG-D-56-79

NL

2 of 3

208-716-4






Figure 6.2 Round Trip Time From Two Harbors to Gary for Class 8 Inland Vessel




Figure 6.3 Round Trip Time From Two Harbors to Gary for Class 10 Laker Vessel

6. RESULTS OF SIMULATION RUNS

6.3 Summary of Production Run Results

In order to assess the nine effects and comparisons listed in Section 6.1, ten (10) production runs tabulated in Table 6.10a, b were executed. The commercial vessel fleet used in those runs was tonnage driven; that is, vessels on each route were generated on a frequency basis to carry a specified amount of cargo over the extended season. Tables 6.11 and 6.12 give a list of the cargo routes and tonnages to be carried over the 126 days (4.14 months) of the simulation's extended season. These extended season tonnage projections were calculated from data supplied by the North Central Division of the U.S. Army Corps of Engineers and correspond to the most recent tonnage projection for the year 2000 made as part of the Great Lakes-St. Lawrence Seaway Navigation Season Extension Program. Detailed output of each simulation run has been provided to the Coast Guard separately as computer printout. Summary tables of the production runs outlining the input run conditions, fixed icebreaker fleet or MRT generated icebreaker fleet (by icebreaker class, task command and time period), icebreaker operating statistics for each icebreaker task command (by icebreaker class and period), and extended navigation season tonnage (by commodity and route) are presented in Section 6.4.

The comparisons of those ten (10) production runs are made in Tables 6.13 through 6.21 to assess the following nine effects and comparisons:

<u>Run Numbers</u>	<u>Effect of Comparison</u>	<u>Table Number</u>	<u>Page Number</u>
1,4	Effect of Increased Cargo Tonnage (20%)	6.13	6-29
2,3	Effect of Increased Maximum Response Time	6.14	6-30
3,6	Effect of Convoying	6.15	6-31
3,1	Comparison of MRT and Fixed Fleet for Normal Winter	6.16	6-32
3,7	Effect of Winter Severity	6.17	6-33
7,5	Effect of Prohibiting Class C Icebreakers from Convoying	6.18	6-34
7,8	Effect of Increased Low SHP/Length Restrictions	6.19	6-35
8,9	Effect of Channel Clearing	6.20	6-36
8,10	Comparison of MRT and Fixed Fleet for Severe Winter	6.21	6-37

TABLE 6.10a

PRODUCTION RUNS FOR SIMULATION OF
GL-SLS ICEBREAKER REQUIREMENTS

RUN NO.	WINTER TYPE	MINIMUM LAKER CLASS	RUN MODE ¹	USCG ESTIMATED FLEET	MRT (hr)	CONVOYING IB TYPES ²	CHANNEL CLEARING ² (in/2wks)	CARGO TONNAGE (year)
1	Normal	5	FIBF	Normal ⁵	---	C,B	---	2000
2	Normal	5	MRT	---	Min ³	C,B	---	2000
3	Normal	5	MRT	---	Min+12	C,B	---	2000
4	Normal	5	FIBF	Normal ⁵	---	C,B	---	2000+20%
6	Normal	5	MRT	---	Min+12	No Convoys	---	2000
5	Severe	5	MRT	---	Min+12	B	---	2000
7	Severe	5	MRT	---	Min+12	C,B	---	2000
8	Severe	6	MRT	---	Min+12	C,B	---	2000 ⁴
9	Severe	6	MRT	---	Min+12	C,B	12	2000 ⁴
10	Severe	6	FIBF	Severe ⁵	---	C,B	---	2000 ⁴

NOTES:

- ¹ FIBF = Fixed icebreaker fleet; MRT = Maximum response time.
- ² Convoys and channel clearing in: St. Marys River/Whitefish Bay, Straits of Mackinac, Detroit/St. Clair Rivers, Welland Canal, St. Lawrence Seaway.
- ³ Minimum time is that required to get to furthest point in reach from closest home port at 5 mph.
- ⁴ Cargo tonnage on restricted ships assumed carried in normal season.
- ⁵ USCG estimated icebreaker fleet listed in Table 6.10b.

COMPARISONS:

- 1,4 -Effect of increased cargo tonnage (20%)(normal winter).
- 2,3 -Effect of variation in maximum response time (normal winter).
- 3,1 -Difference between MRT generated icebreaker fleet and fixed icebreaker fleet (normal winter)
- 3,6 -Effect of convoys (normal winter).
- 3,7 -Effect of winter severity.
- 5,7 -Effect of not allowing Class C icebreakers to convoy (severe winter).
- 7,8 -Effect of vessel class restriction (severe winter).
- 8,9 -Effect of channel clearing (severe winter).
- 8,10-Difference between MRT generated icebreaker fleet and fixed icebreaker fleet (severe winter).

TABLE 6.10b
USCG ESTIMATED FLEET FOR YEAR 2000*

Area	Home Port	Normal Winter		Severe Winter		
		B	C	B	C	D
S-1	Duluth	-	2	1	2	-
C-1	Sault Ste. Marie	2	4	3	6	-
C-2	St. Ignace	1	1	2	2	2
C-3	Port Huron, Detroit, Toledo	1	2	1	4	-
M-1	Escanaba	-	1	-	1	-
M-2	Chicago	-	1	1	2	-
M-3A	(NE Lake Michigan)	-	-	-	-	-
H	Saginaw	-	-	2	3	-
E-1	Sandusky	-	1	1	2	-
E-3	Buffalo	1	2	1	4	-
SL-0	Oswego	-	3	-	3	-
	SUBTOTAL	5	17	12	29	2
	TOTAL	22		43		

Note: Principal ports; operations limited to vessels of reasonably high capability (SHP/L > 6); 12 hrs per day per icebreaker.

*Letter dated 8 June 1977 from Commander, Ninth Coast Guard District to the Commandant (G-0).

TABLE 6.11 MAJOR LAKER TRADE ROUTES
PROJECTED FOR YEAR 2000

Route No.	Origin Port	Destination Port	Cargo* (thousands of short tons)
-----IRON ORE-----			
1	Two Harbors	Calumet/Indiana Harbor	636
2		Gary/Burns Harbor	877
3		Detroit/Windsor	483
4		Toledo	160
5		Cleveland	759
6		Ashtabula/Conneaut	763
7		SPARE	
8	Duluth/Superior	Calumet/Indiana Harbor	1249
9		Gary/Burns Harbor	1324
10		Sandusky	757
11		Lorain	844
12		Cleveland	1476
13		Ashtabula/Conneaut	1483
14		Buffalo	750
15		Toronto/Hamilton	572
16	Presque Isle	SPARE	
17		Detroit	1086
18		SPARE	
19	Taconite	Calumet/Indiana Harbor	743
20		Gary/Burns Harbor	422
21		Detroit/Windsor	262
22		Lorain	610
23		Cleveland	759
24		Ashtabula/Conneaut	884
25		SPARE	
26	Silver Bay	Calumet/Indiana Harbor	530
27		Gary/Burns Harbor	388
28		Toledo	522
29		Cleveland	972
30	Thunder Bay	Ashtabula/Conneaut	1267
31		SPARE	
32		Sault Ste. Marie	551
33		Gary/Burns Harbor	757
34		Port Colbourne	567
35	Escanaba	Toronto/Hamilton	471
36		SPARE	
37		Calumet/Indiana Harbor	955
38		Detroit/Windsor	808
39		Toledo	838
40		SPARE	

* Tonnage projection for nine 14-day periods of season extension (4.14 mos.)

TABLE 6.11 MAJOR LAKER TRADE ROUTES
PROJECTED FOR YEAR 2000 (CON'T)

Route No.	Origin Port	Destination Port	Cargo* (thousands of short tons)
--IRON ORE CON'T--			
41**	Sept. Isle	Calumet/Indiana Harbor	610
42**		Cleveland	893
43		SPARE	
TOTAL IRON ORE			27028
-----COAL-----			
44	Duluth/Superior	Milwaukee/Port Washington	969
45		Port Huron/St. Clair	944
46		Detroit/Windsor	944
47		Cleveland	416
48		Buffalo	2497
49		Toledo/Monroe	907
50		SPARE	
51	Thunder Bay	Port Colbourne/Nanticoke	1026
52		SPARE	
53	Calumet/Indiana Harbor	Taconite	184
54		Milwaukee/Port Washington	849
55		SPARE	
56	Toledo	Duluth/Superior	115
57		Presque Isle/Marquette	108
58		Green Bay	221
59		Escanaba	210
60		Buffalo	507
61		Sault St. Marie	1698
62		SPARE	
63	Sandusky	Presque Isle/Marquette	153
64		Escanaba	246
65		Buffalo	204
66		Toronto/Hamilton	1260
67		SPARE	
68	Ashtabula/Conneaut	Duluth/Superior	193
69		Presque Isle/Marquette	188
70		Green Bay	380
71		Buffalo	537
72		Toronto/Hamilton	2417
73		SPARE	
TOTAL COAL			18153

* Tonnage projection for nine 14-day periods of season extension (4.14 mos.)

** Triangular route

TABLE 6.11 MAJOR LAKER TRADE ROUTES
PROJECTED FOR YEAR 2000 (CON'T)

Route No.	Origin Port	Destination Port	Cargo* (thousands of short tons)
-----GRAIN-----			
74	Duluth/Superior	Calumet/Indiana Harbor	32
75		Detroit/Windsor	35
76		Cleveland	18
77		Buffalo	599
78**		Baie Comeau	1916
79		SPARE	
80	Milwaukee/Port Wash.	Buffalo	44
81		Baie Comeau	84
82		SPARE	
83	Calumet/Indiana Harbor	Buffalo	35
84		SPARE	
85	Toledo	Baie Comeau	50
86		SPARE	
TOTAL GRAIN			2813

* Tonnage projection for nine 14-day periods of season extension (4.14 mos.)
 ** Triangular route

TABLE 6.12
SIMULATION SALTY TRADE ROUTES
PROJECTED FOR YEAR 2000

<u>ROUTE NO.</u>	<u>ORIGIN PORT</u>	<u>DESTINATION PORT</u>	<u>CARGO (THOUSANDS OF SHORT TONS)</u>
-----General Cargo-----			
87	World Area 1	Schedule 1	485
-----Ballast In/Grain Export-----			
88	Duluth/Superior	World Area No. 1	3183
89	Thunder Bay	World Area No. 1	2123
90	Calumet/Indiana Harbor	World Area No. 1	590
TOTAL (including triangular routes below)			5986
-----Iron & Steel Import/Grain Export (Triangular Route)-----			
91	World Area No. 1	Milwaukee/Port Washington	279
92	World Area No. 1	Detroit/Windsor	388
93	World Area No. 1	Toledo	545
TOTAL			1112

TABLE 6.13

EFFECT OF INCREASED CARGO TONNAGE ON SYSTEM¹

Run	Winter	Min. Laker Class	Icebreaker Fleet	Max. Resp. Time	Convoying Icebreaker	Channel Clearing	Extended Nav. Season Cargo Tonnage
1	Normal	5	USCG Est. Normal Winter	N.A.	Classes C & B	None	-63,000,000 Short Tons
4	Normal	5	USCG Est. Normal Winter	N.A.	Classes C & B	None	-74,900,000 Short Tons

ICEBREAKER TASK COMMANDS

	TACONITE	OIL CAN	COAL SHOVEL	SEAWAY
Number of Icebreakers	For both runs, a fixed fleet of 10 icebreakers (7 Class C and 3 Class B) were utilized almost 100% in periods 5-9. As a result, when tonnage was increased by almost 20%, the already large queues (Run 1) increased significantly.	For both runs, a fixed fleet of 2 Class C icebreakers were capable of handling the demand for their services with an average icebreaker utilization of 44% (Run 1) and 46% (Run 4) for periods 5-9. It should be noted that during 2-week periods 6 and 8, the utilization increased significantly to 95% and 80% for Run 1 and 95% and 84% for Run 4.	For both runs, a fixed fleet of 7 icebreakers (5 Class C and 2 Class B) were capable of handling the demand for their services with the exception of period 6 when all seven were utilized 100%.	For both runs, a fixed fleet of 3 Class C icebreakers were utilized 100% during periods 5 through 8 conveying ships through the Seaway.
Direct Assists	The total number of assists increased by 17.4% from 781 (Run 1) to 917 (Run 4). This increase is approximately the same as the increase in tonnage.	The total number of assists increased by 10% from 80 (Run 1) to 88 (Run 4). This increase is significantly below the tonnage increase due to large queues in Taconite Command.	The number of assists increased by 17.5% from 200 (Run 1) to 235 (Run 4). This increase is approximately the same as the tonnage increase.	There were no direct assists in this task command.
Convoys	The total number of convoys escorted increased by 16.1% from 629 (Run 1) to 730 (Run 4). Since this increase in percentage is somewhat less than the increase in tonnage, the faster arrival rate of vessels at convoy points enables more ships to be escorted per convoy before the time limit expired for the first ship.	There were no convoys in this task command.	There were no convoys in this task command.	The number of convoys increased by 8.7% from 173 (Run 1) to 188 (Run 4). This is much less than the increase in tonnage, and indicates that many convoys in Run 1 consisted of fewer ships than those in Run 4.
Queues	The increase in tonnage caused the average size of queues to increase significantly. Direct Assistance queues increased by 32% from an average of 6.8 (Run 1) to 9 (Run 4).	The Direct Assistance queues were small, having only 1 or 2 ships in both runs during periods 6 and 8.	The average Direct Assistance queue increased in period 6 from 2 ships to 6 ships, while in all other periods the queues were very small.	The average convoy queues increased significantly from an average of 5.5 ships for Run 1 to almost 12 ships for Run 4.

1. In the fixed icebreaker fleet mode, an icebreaker is free to respond anywhere in the task command, while for the maximum response time mode an icebreaker may respond only in those reaches with the same home port. As a result, the fixed fleet in Taconite is utilized inefficiently because a major amount of time is spent travelling between Duluth/Superior area and the Soo.

TABLE 6.14

EFFECT OF INCREASED MAXIMUM RESPONSE TIME ON ICEBREAKER REQUIREMENTS

Run	Winter	Min. Laker Class	Icebreaker Fleet	Max. Resp. Time	Convoying Icebreaker	Channel Clearing	Extended Nav. Season Cargo Tonnage
2	Normal	5	Max. Response Time Mode	Minimum	Classes C & B	None	-63,000,000 Short Tons
3	Normal	5	Max. Response Time Mode	Minimum + 12 hours	Classes C & B	None	-63,000,000 Short Tons

ICEBREAKER TASK COMMANDS							SEAWAY	
TACONITE				OIL CAN	COAL SHOVEL			
Number of Icebreakers		The effect of increasing the MRT by 12 hours tended to reduce the number of icebreakers generated in periods 5, 6, and 7 (9, 18, and 13 vs 6, 12 and 12) but increased the number in periods 8 and 9 (12 and 14 vs 17 and 16). In an overall sense there appears to be little difference in the generated icebreaker fleets when vessel utilization is considered; that is, for the entire winter both fleets appeared to operate at approximately 50% utilization.					A maximum of 6 icebreakers was required in period 7 of Run 2, versus 5 in period 5 of Run 3. The fleet mix was 100% Class C icebreakers in both runs. The decrease in the number of Class C icebreakers was due to the decrease in the number of convoys escorted. In both runs, icebreaker utilization averaged approximately 80% in periods 5 through 8.	
Direct Assists	A total of 789 direct assists occurred in Run 2, and 792 in Run 3.			There were 90 direct assists in Run 2, and 86 in Run 3.		There were no direct assists in this task command.		
Convoys	A total of 717 convoys were escorted in Run 2 versus 699 in Run 3, indicating that, due to the additional waiting time, some convoys consisted of a larger number of ships in Run 3.			There were no convoy routes in the normal winter for this task command.		A total of 200 convoys were escorted in Run 2 versus 185 in Run 3, indicating that, with the longer MRT, some convoys may have carried more ships.		
Queues	The direct assistance queue was empty in Run 2, and averaged 1 ship in Run 3.			The direct assistance queues ranged from 1 to 2 ships for Run 2 and 1 to 3 ships for Run 3.		There were no direct assistance queues in this task command.		

TABLE 6.15

EFFECT OF CONVOYING ON ICEBREAKER REQUIREMENTS

Run	Winter	Min. Laker Class	Icebreaker Fleet	Max. Resp. Time Mode	Max. Resp. Time	Convoicing Icebreaker	Channel Clearing	Extended Nav. Season
3	Normal	5	Max. Response Time Mode	Minimum + 12 hours	Classes C & B	None	None	63,000,000 Short Tons
6	Normal	5	Max. Response Time Mode	Minimum + 12 hours	No Convoys	None	None	63,200,000 Short Tons

ICEBREAKER TASK COMMANDS

	TACONITE	OIL CAN	COAL SHOVEL	SEAWAY
Number of Icebreakers	The elimination of convoying increases the required icebreaker fleet from an average of 14 icebreakers (2 Class D, 8 Class C, 4 Class B) to 30 icebreakers (11 Class D, 8 Class C, 11 Class B) for periods 6 through 10. It is important to note that when convoying was used, the average icebreaker utilization was 52% while, when convoying was eliminated, the average icebreaker utilization was 32%.	Because there were no convoys in this task command, both runs generated approximately the same icebreaker fleet with 15 Class D icebreakers operating at 16% utilization in periods 6 and 8, and 4 Class D icebreakers operating at approximately 10% in periods 5, 7, and 9.	For both runs, significant icebreaker assistance was required during periods 5 and 6 to provide direct assistance aid. In Run 3, 20 Class D icebreakers were generated in period 5, and 25 Class D and 5 Class C icebreakers in period 6. In Run 6, 19 Class D icebreakers were generated in period 5, and 21 Class D and 5 Class C icebreakers in period 6. It is important to note that while a large number of icebreakers were generated they were operating at between 20% and 30% utilization.	The maximum number of icebreakers dropped from 5 Class C in period 5 for Run 3, to 4 Class C in period 7 for Run 6. This reflects the fact that salties, which were capable of proceeding on their own, were being forced to convoy thereby requiring more icebreakers.
Direct Assists	Without convoys the total number of direct assists increased from 792 to 1422, an increase of almost 80%.	Because there were no convoys in this task command, the number of direct assists were the same (86 assists for Run 3 and 85 for Run 6).	The total number of direct assists was approximately the same (198 for Run 3 and 193 for Run 6).	There were no direct assists in Run 3 due to convoying, while there was a total of 16 in Run 6 when convoying was not performed.
Convoys	In Run 3 a total of 699 convoys were escorted while in Run 6 none were escorted.	There were no convoys in this task command.	There were no convoys in this task command during a normal winter.	In Run 3 a total of 185 convoys were escorted. In Run 6, none were escorted.
Queues	The average direct assistance queues in Run 3 ranged from 0 to 1, while in Run 6 they ranged from 1 to 2.	For both runs, average direct assistance queues ranged from 1 ship to 3 ships waiting for assistance.	The average direct assistance queue was slightly smaller in Run 6 (1 ship in period 5 and 2 ships in period 6) compared to Run 3 (2 ships in period 5 and 3 ships in period 6).	In Run 6, average direct assistance queues were negligible.

TABLE 6.16

COMPARISON OF MINIMUM RESPONSE TIME WITH FIRED ICEBREAKER FLEET FOR A NORMAL WINTER¹

Run	Winter	Min. Labor Class	Icebreaker Fleet	Max. Resp. Time	Channel Clearing	Extended Nav. Season
1	Normal	5	USCGC Est. Normal Winter	N.A.	None	Cargo Tonnage
2	Normal	5	Max. Response Time Mode	Maximum 12 hours	Classes C & B	61,000,000 Short Tons
3	Normal	5	Max. Response Time Mode	Maximum 12 hours	Classes C & B	61,000,000 Short Tons

ICEBREAKER TASK COMMANDS			
INCIDENT		OIL CAN	CUMI SUDWILL
Number of Icebreakers	The fired icebreaker fleet consisted of 7 Class C and 3 Class B icebreakers operated at 100% utilization in periods 5 through 9 performing 781 direct assists and escorting 629 convoys. It should be noted that these icebreakers spent a large amount of time moving around between the lines of assistance and convoys. In periods 6 through 9, the MHI Mode generated 12 icebreakers (2 Class D, 7 Class C, 3 Class B) in period 7 to 17 icebreakers (3 Class D, 9 Class C, 5 Class B) in period 8.	The fired icebreaker fleet consisted of 2 Class C icebreakers which operated at less than 25% utilization in all periods other than 6 and 8. In periods 6 and 8, they operated at 95% and 80% respectively, performing 80% of the total number of direct assists. In periods other than 6 and 8, the MHI Mode generated a maximum of 4 Class C icebreakers which operated at an average utilization of 10%. In periods 6 and 8, 15 and 16 Class D icebreakers were generated to perform 63 direct assists at an average utilization of 15%.	The fired icebreaker fleet consisted of 5 Class C and 2 Class B icebreakers operating at approximately 50% utilization in period 5 to perform 70 direct assists, and at 100% utilization in period 6 to perform 119 direct assists. The MHI Mode generated a fleet of 20 Class D icebreakers operating at 21% utilization in period 5 to perform 80 direct assists, and 25 Class C icebreakers operating at 26% utilization, to handle 119 direct assists.
Direct Assists	The total number of direct assists in the MHI Mode run was 792, while in the fired fleet run it was 781. In the MHI Mode run (for all icebreakers), the portion of the mileage spent actually escorting was 61%, 74%, and 75% (periods 5, 6, and 7 respectively), compared to 10%, 25%, and 29% for the fired fleet run. The rest of the mileage was incurred going to the point of assistance or returning to home port.	There were 86 direct assists by Class D icebreakers in Run 3 and 80 by Class C icebreakers in Run 1.	There were 198 direct assists in Run 3 as compared to 200 in Run 1.
Convoys	In the MHI Mode run a total of 699 convoys were processed, while the fired fleet escorted 629. In the MHI Mode run (for all icebreakers), the portion of the mileage spent actually escorting was 74%, 102%, and 65% (periods 5, 6, and 7 respectively), compared to 20%, 50%, and 44% for the fired fleet run.	There were no convoys in this task command.	There were no convoys specified in this task command for the normal winter.
Queues	The direct assistance queue, which was negligible in the MHI Mode run, was as high as 11 ships in the fired fleet run.	The direct assistance queue averaged 2 ships in Run 3 and zero in Run 1.	The direct assistance queue size was essentially the same.

SEAWAY			
Number of Icebreakers	The fired icebreaker fleet consisted of 3 Class C icebreakers which operated at 100% utilization in periods 5 through 8 to handle 173 convoys. In periods 5 through 8, the MHI Mode generated icebreaker fleets ranging from 3 Class C fleets to 5 Class C icebreakers operating at 82% utilization in period 5 to handle a total of 185 convoys.	There were no direct assists in this task command.	There were a total of 105 convoys processed in Run 3 compared to 123 in Run 1, indicating that the MHI Mode fleet was escorting convoys of slightly fewer ships.
Direct Assists			
Convoys			
Queues			There were no direct assistance queues in the Seaway Command.

1. In the fired icebreaker fleet mode, an icebreaker is free to respond anywhere in the task command, while in the maximum response time mode an icebreaker may respond only to those convoys with the same home port. As a result, the fired fleet in Incidents 1 is utilized inefficiently because a major amount of time is spent travelling between Inland/Superior area and the Sea.

TABLE 6.17

EFFECT OF WINTER SEVERITY ON ICEBREAKER REQUIREMENTS

Run	Winter	Min. Labor Class	Icebreaker Fleet	Max. Response Time	Resp. Time	Min. Response Time	Max. Response Time	Convoying Icebreaker	Channel Clearing	Extended Nav. Season
3	Normal	5			Minimum + 12 hours			Classes C & B	None	63,000,000 Short Tons
7	Severe	5			Minimum + 12 hours			Classes C & B	None	67,500,000 Short Tons

ICEBREAKER TASK COMMANDS									
TACOMILE					OIL CAN		COAL SHUTTLE		SEAWAY
Number of Icebreakers	For the normal winter, an average icebreaker fleet of 14 vessels (2 Class D, 8 Class C, and 4 Class B) was generated in periods 6 through 9. Icebreaker utilization for the severe winter ranged from 47 to 91% with an average of 50%. For the severe winter, the generated icebreaker fleet ranged from 17 icebreakers (4 Class D, 13 Class C, 4 Class B) to 20 icebreakers (11 Class C, 9 Class B) to 22 icebreakers (12 Class C, 10 Class B) in periods 5 through 9 respectively. The utilization of these vessels ranged from 9% to 94% with an average of 50%.				For the normal winter, an icebreaker fleet of 4, 16, 4, 16, and 3 Class D icebreakers was generated in periods 5, 6, 7, 8 and 9 respectively. These icebreakers operated at an average utilization of 45% for the severe winter, 14% for the normal winter, and 3 Class D icebreakers in periods 3, 4, and 5 were generated. In periods 6 and 7, an icebreaker fleet of 4 vessels (1 Class D, 3 Class C) and 7 vessels (3 Class C and 4 Class B) were generated. The average utilization for this fleet was 45% for the severe winter and 30% for the normal winter. In the severe winter ships were stuck in a reach much closer to the home port (see below). This is a result of using actual historic data which sometimes is inconsistent.		For the normal winter, the generated icebreaker fleet ranged from 20 Class D icebreakers in period 5, 30 icebreakers (25 Class D, 5 Class C) in period 6 through 8 to handle 104 convoys. For the severe winter, the generated icebreaker fleet varied from 5 icebreakers (1 Class D and 4 Class C) in period 5, 11 Class C icebreakers in period 6, 6 to 3 icebreakers (1 Class D, 2 Class B) in period 8. Icebreaker utilization ranged from 22 to 94% with an average of 49%.		For the normal winter, between 3 and 5 Class C icebreakers, operating at 80% utilization, were generated in periods 5 through 8 to handle 104 convoys. For the severe winter, the generated icebreaker fleet varied from 5 icebreakers (1 Class D and 4 Class C) in period 5, 11 Class C icebreakers in period 6, 6 to 3 icebreakers (1 Class D, 2 Class B) in period 8. Icebreaker utilization ranged from 22 to 94% with an average of 49%.
	The total number of direct assists increased from 282 in the normal winter to 1032 in the severe winter, an increase of 365%.				There were 86 direct assists in the normal winter run and 102 in the severe run. However, these equated to a total of 1936 for the normal winter and 1340 for the severe winter (for 27% miles) in the severe winter. In the normal winter, ships were stuck most often in reach 35, whereas in the severe run ships most often required assistance in reach 56, which is much closer to the home port of Escanaba.		There were 190 direct assists in the normal winter as compared to 573 in the severe winter, an increase of 109%.		There were no direct assists in the normal winter and 40 in the severe winter.

Convoys	The convoys routes were defined over longer periods of time for the severe winter, which resulted in an increase of escorted convoys from 699 to 937, an increase of 34%.				Convoys in the Detroit/SE. Clair River System were operated only in the severe winter when 347 convoys were escorted.		Convoys in the Detroit/SE. Clair River System were operated only in the severe winter when 347 convoys were escorted.		The size of the convoys was defined in the same time periods in both runs. 105 convoys were escorted in the normal winter as compared to 154 in the severe winter. Fewer convoys were required because Class B icebreakers were generated in periods 7 and 8, and can handle twice as many ships per convoy as Class C icebreakers.	
	The average direct assistance figures increased from a maximum of 3 ships in the normal winter to a maximum of 5 ships in the severe winter.				The average direct assistance figures increased from a maximum of 3 ships in the normal winter to a maximum of 5 ships in the severe winter.		The average direct assistance figures increased from a maximum of 3 ships in the normal winter to a maximum of 5 ships in the severe winter.		The size of the convoys was defined in the same time periods in both runs. 105 convoys were escorted in the normal winter as compared to 154 in the severe winter. Fewer convoys were required because Class B icebreakers were generated in periods 7 and 8, and can handle twice as many ships per convoy as Class C icebreakers.	

Convoys	The convoys routes were defined over longer periods of time for the severe winter, which resulted in an increase of escorted convoys from 699 to 937, an increase of 34%.				Convoys in the Detroit/SE. Clair River System were operated only in the severe winter when 347 convoys were escorted.		Convoys in the Detroit/SE. Clair River System were operated only in the severe winter when 347 convoys were escorted.		The size of the convoys was defined in the same time periods in both runs. 105 convoys were escorted in the normal winter as compared to 154 in the severe winter. Fewer convoys were required because Class B icebreakers were generated in periods 7 and 8, and can handle twice as many ships per convoy as Class C icebreakers.	
	The average direct assistance figures increased from a maximum of 3 ships in the normal winter to a maximum of 5 ships in the severe winter.				The average direct assistance figures increased from a maximum of 3 ships in the normal winter to a maximum of 5 ships in the severe winter.		The average direct assistance figures increased from a maximum of 3 ships in the normal winter to a maximum of 5 ships in the severe winter.		The size of the convoys was defined in the same time periods in both runs. 105 convoys were escorted in the normal winter as compared to 154 in the severe winter. Fewer convoys were required because Class B icebreakers were generated in periods 7 and 8, and can handle twice as many ships per convoy as Class C icebreakers.	

TABLE 6.18
EFFECT OF PROHIBITING CLASS C ICEBREAKERS FROM CONVOYING

Run	Winter	Min. Laker Class	Icebreaker Fleet	Max. Resp. Time	Convoys Icebreaker	Channel Clearing	Extended Nav. Season Cargo Tonnage
5	Severe	5	Max. Response Time Mode	Minimum + 12 hours	Class B Only	None	62,900,000 Short Tons
7	Severe	5	Max. Response Time Mode	Minimum + 12 hours	Classes C & B	None	62,900,000 Short Tons

ICEBREAKER TASK COMMANDS				SEAWAY	
				COAL SHOVEL	
				OIL CAN	
				TACONITE	
Number of Icebreakers	The number of required icebreakers varies from a maximum of 41 in period 7 of Run 2 to 39 in Run 5 because of the larger conveying capability of Class B icebreakers. Over all periods the average number of icebreakers required was decreased by 21%.			Since there are no convoys in Oil Can, the generated icebreaker fleet was approximately the same with 2 Class D icebreakers, 8 Class D icebreakers, 4 icebreakers (1 Class D, 3 Class C) and 7 icebreakers (3 Class C and 4 Class B) in periods 3 through 7 respectively. For Run 5 in period 6, one of the Class C icebreakers was replaced with a Class D icebreaker. Icebreaker utilization ranged from 11% to 34% with an average of 17%.	
Direct Assists	There were essentially the same number of direct assists in both runs (1032 versus 1036). 64% as much time was spent in direct assists as conveying in Run 7.			The number of direct assists was essentially the same in both runs (40 versus 42).	
Convoys	The number of convoys decreased from 937 to 581 because of the larger conveying capacity of the Class B icebreaker (6 versus 3).			The number of convoys escorted was reduced from 347, all by Class C icebreakers, in Run 7 to 177, all by Class B icebreakers, in Run 5, reflecting that more ships were escorted per convoy.	
Queues	The size of the queues remained approximately the same with average direct assistance queues ranging from 1 ship to 6 ships.			The average queue sizes remained approximately the same with direct assistance queues ranging from 1 ship to 6 ships.	

ICEBREAKER TASK COMMANDS				SEAWAY	
				COAL SHOVEL	
				OIL CAN	
				TACONITE	
Number of Icebreakers	The number of required icebreakers varies from a maximum of 41 in period 7 of Run 2 to 39 in Run 5 because of the larger conveying capability of Class B icebreakers. Over all periods the average number of icebreakers required was decreased by 21%.			Since there are no convoys in Oil Can, the generated icebreaker fleet was approximately the same with 2 Class D icebreakers, 8 Class D icebreakers, 4 icebreakers (1 Class D, 3 Class C) and 7 icebreakers (3 Class C and 4 Class B) in periods 3 through 7 respectively. For Run 5 in period 6, one of the Class C icebreakers was replaced with a Class D icebreaker. Icebreaker utilization ranged from 11% to 34% with an average of 17%.	
Direct Assists	There were essentially the same number of direct assists in both runs (1032 versus 1036). 64% as much time was spent in direct assists as conveying in Run 7.			The number of direct assists was essentially the same in both runs (40 versus 42).	
Convoys	The number of convoys decreased from 937 to 581 because of the larger conveying capacity of the Class B icebreaker (6 versus 3).			The number of convoys escorted was reduced from 347, all by Class C icebreakers, in Run 7 to 177, all by Class B icebreakers, in Run 5, reflecting that more ships were escorted per convoy.	
Queues	The size of the queues remained approximately the same with average direct assistance queues ranging from 1 ship to 6 ships.			The average queue sizes remained approximately the same with direct assistance queues of 1 ship.	

TABLE 6.19
EFFECT OF INCREASED LOW SHIP/LENGTH RESTRICTION ON ICEBREAKING REQUIREMENTS

Run	Winter	Min. Laker Class	Icebreaker Fleet	Max. Resp. Time	Max. Resp. Time Mode	Convoying Icebreaker	Channel Clearing	Extended Nav. Season
7	Severe	5	Max. Response Time Mode	Minimum + 12 hours	Classes C & B	None	None	-62,900,000 Short Tons
8	Severe	6	Max. Response Time Mode	Minimum + 12 hours	Classes C & B	None	None	-54,800,000 Short Tons

ICEBREAKER TASK COMMANDS				SEAWAY	
				OIL CAN	COAL SHOVEL
Number of Icebreakers	JACOWJTE	The maximum number of icebreakers required decreased significantly from 41 in period 7 when Class 5 Lakers are allowed to operate, to 12 in period 8 when Class 5 Lakers are not allowed to operate.	The restriction of Class 5 Lakers from operating reduced the required icebreaker fleet from a maximum of 8 Class D icebreakers (3 Class C and 4 Class B) in period 7, to 1 Class D icebreaker in period 6 and 4 icebreakers (1 Class D, 3 Class C) in period 7. The icebreaker utilization for both runs averaged less than 25%.	For all periods other than 7, the number of required icebreakers decreased by a factor of 2 by restricting the movement of Class 5 Lakers and the elimination of conveying in the Detroit/St. Clair System. In period 7 the number of icebreakers were approximately the same (50 for Run 7 and 52 for Run 8) due to a 45% icebreaker utilization in Run 7 and a 27% icebreaker utilization in Run 8.	
				The restriction of Class 5 Lakers from operating reduced the required icebreaker fleet from a maximum of 11 Class C icebreakers to 8 Class C icebreakers in period 6. It should be noted that in period 7 more icebreakers (4 Class B vs 5 Class B) were required in Run 8 due to an increased number of convoys. Also it should be noted that in period 8, 1 Class D and 2 Class B icebreakers were required in Run 7, while 2 Class D and 3 Class B icebreakers were required in Run 8. This apparent discrepancy can be explained by looking at the icebreaker utilization where in Run 7 the 2 Class B icebreakers are operating at 82% while in Run 8 the 3 Class B icebreakers are operating at 50%.	
Direct Assists		The total number of direct assists decreased from 1032 in Run 7 to 671 in Run 8, due to prohibiting Class 5 Lakers from operating.	The number of direct assists decreased from 102 to 11 when Class 5 Lakers were restricted from operating.	The total number of direct assists decreased from 40 to 23 with the restriction placed on Class 5 Lakers.	
Convoys		For Run 8, the starting time for the convoys was delayed 2 periods and the length of the St. Marys River convoy was cut by half. As a result the number of convoys escorted decreased from 937 to 587, and the number of hours spent conveying decreased from 13651 to 6511 hours.	There were no convoy routes defined for this task command.	The total number of convoys escorted decreased only slightly from 160 to 154 with the imposed restriction on Class 5 Lakers.	
Queues		The size of the direct assistance queue was reduced from a maximum of 5 to 2.	The direct assistance queue was negligible.	In Run 7, direct assistance queues averaged 1 ship in periods 6 and 7, while in Run 8 no direct assistance queues occurred.	

TABLE 6.20

EFFECT OF CHANNEL CLEARING ON ICEBREAKER REQUIREMENTS

Run	Winter	Min. Laker Class	Icebreaker Fleet	Max. Resp. Time	Convoying Icebreaker	Channel Clearing*	Extended Nav. Season
8	Severe	6	Max. Response Time Mode	Minimum + 12 hours	Classes C & B	None	54,800,000 Short Tons
9	Severe	6	Max. Response Time Mode	Minimum + 12 hours	Classes C & B	12 inches/period	55,000,000 Short Tons

ICEBREAKER TASK COMMANDS

	TACOMITE	OIL CAN	COAL SHOVEL	SEAWAY
Number of Icebreakers	Both the number of icebreakers and icebreaker size were reduced significantly due to channel clearing. For example in period 6, the required 9 icebreakers (2 Class D, 4 Class C, 3 Class B) operating at 49% utilization were reduced to 5 icebreakers (3 Class C, 2 Class B) operating at 79% utilization. In period 8, the required 12 icebreakers (8 Class C, 4 Class B) operating at 55% utilization were reduced to 7 icebreakers (5 Class C, 2 Class B) operating at 60% utilization.	There was no channel clearing in this task command. There was virtually no change in the number of required icebreakers with 1 Class D icebreaker in period 6, 1 Class D and 3 Class C icebreakers in period 7 and for Run 9, 1 Class D icebreaker in period 8. Average icebreaker utilization was approximately 13%.	The number of icebreakers required changed only slightly with 2 Class D icebreakers; 4 Class B icebreakers; 22 Class D and 4 Class B icebreakers; 47 Class C and 5 Class B icebreakers; 10 Class D, 2 Class B, and 2 Class C icebreakers in periods 4, 5, 6, 7, 8, and 9 respectively. Channel clearing appears to have the most effect on icebreaker utilization which was reduced from an average of 24% to 21%.	Both the number of icebreakers and icebreaker size were reduced significantly due to channel clearing. For example in period 6, 8 Class C icebreakers operating at 91% utilization were required, while only 5 Class C icebreakers operating at 86% utilization were required when channel clearing was performed. Similarly in period 7, 5 Class B icebreakers were required to operate at 6% utilization, while with channel clearing only 3 Class B icebreakers operating at 27% and 1 Class C icebreaker operating at 98% were required.
Direct Assists	The total number of direct assists decreased from 671 to 572 due to channel clearing allowing more ships to go to Sault Ste. Marie without becoming stuck.	There were 11 direct assists in both runs.	The number of direct assists decreased from 337 to 292 because fewer ships were becoming stuck in the Detroit/St. Clair Rivers.	The total number of direct assists decreased from 23 to 19.
Convoys	The total number of convoys escorted increased from 587 to 653 with channel clearing. This was due to increased icebreaker speeds which could handle more convoys consisting of fewer vessels and in periods 9 and 10, due to the use of both Class C and B icebreakers for convoying instead of only Class B icebreakers.	There were no convoys in this task command.	There were no convoys in this command because the Class 5 Lakers were restricted from operating.	The number of convoys increased from 160 to 177 indicating that the number of ships per convoy was lower due to convoys being escorted at higher speeds.
Queues	The direct assistance queues were small with a maximum of 2 ships for both cases.	The direct assistance queue was zero.	There was essentially no change in the size of the direct assistance queue with an average of 3 ships in periods 6 through 8.	The size of the convoy queue decreased slightly from an average of 3.1 in Run 8 to 2.8 in Run 9.

* Channel Clearing in the St. Marys River, Whitefish Bay, Straits of Mackinac, Detroit/St. Clair System, Welland Canal, and St. Lawrence Seaway.

TABLE 6.21

COMPARISON OF MAXIMUM RESPONSE TIME MADE WITH FIRED ICEBREAKER FLEET FOR A SEVERE WINTER¹

Run	Water	Min. Lat. Class	Icebreaker Fleet	Min. Resp. Time	Convoying Icebreaker	Channel Clearing	Extended War. Cargo Tonnage
0	Severe	0	Max. Response Time Made	Minimum 12 hours	Class C & B	None	54,000,000 Short Tons
10	Severe	0	USC Ft. Severe Winter	8 d.	Class C & B	None	54,000,000 Short Tons

ICEBREAKER TASK COMMANDS				CONV. SUPPORT		SEAFAR	
				OUT COM			
Number of Icebreakers	The total number of icebreakers required to handle the demand then were specified in the fixed fleet run (a maximum of 12 icebreakers versus a fixed fleet of 10). In addition, with the exception of periods 9 and 10, the MFI made generated a maximum of 8 icebreakers in period 10, the MFI made generated 6 Class B icebreakers in the fixed fleet. In period 9 and 10, the MFI generated 12 and 11 icebreakers, of which 9 and 8 were Class B respectively, and the remaining 3 were Class C as compared to the fixed fleet of 6 Class B, 10 Class C, and 2 Class B icebreakers.	The maximum number of icebreakers required in the MFI made run was 6 (1 Class B and 5 Class C) operating at 100% utilization in period 7. The number of icebreakers in the fixed fleet is also 6, consisting of 3 Class C and 3 Class B icebreakers operating at 27% utilization in period 7. In period 10, the MFI made generated only one required Class B icebreaker in period 6 to perform 3 direct assists.	For period 7, which was the most severe, the MFI made run generated 54 icebreakers (37 Class C and 17 Class B) operating at 27% utilization, while the fixed fleet of 17 icebreakers (12 Class C and 5 Class B) operated at 100% utilization. In period 6, the MFI made run generated 20 icebreakers (13 Class B and 7 Class C) operating at 28% utilization, while the fixed fleet of 17 icebreakers operated at 100% utilization. In all other periods, the number of icebreakers generated by the MFI made were less than the fixed fleet.	The MFI made run required a maximum of 6 Class C icebreakers in period 6 and 5 icebreakers in periods 7 and 8; while the fixed fleet with 2 Class C icebreakers operated at 100% utilization trying to meet the demand for convoying through the Seaway.			
Direct Assists	The total number of assists was essentially the same (677 versus 683) for both runs.	There were 11 direct assists in both runs occurring in periods 6 and 7.	The total number of direct assists was 316 in Run 10 and 338 in Run 8. This increase was caused by the number of ships held up in the Seaway convoys, resulting in more convoys of four ships.	There were 23 direct assists in Run 8 and 16 in Run 10. This decrease was caused by the fewer number of ships held up in the convoys until the most severe period, which was considerably less severe.			
Convoys	The total number of convoys escorted in the MFI made run was 587 as compared to 623 for the fixed icebreaker fleet, indicating that four vessels per convoy were escorted by the fixed icebreaker fleet.	There were no convoy routes defined in this task command.	There were no convoy routes defined in this task command.	A total of 160 convoys were escorted in Run 8 versus 131 in Run 10. This decrease was caused by the utilization of the 3 Class C icebreakers causing queues of ships waiting to convoy in Run 10 as compared to the average of 6 icebreakers operating in periods 6, 7, and 8.			
Queues	The direct assistance queue in the MFI made ranged between 0 and 2 ships over the periods. In the fixed fleet run, the average size direct assistance queue continued to grow over the periods. However, inspecting the computer printout shows that the queue was very small, it was not growing with out bound.	No significant direct assistance queues occurred.	The direct assistance queues were at the maximum of 5 (in the Seaway) in Run 8 but were zero in Run 10.	The convoys queues in the fixed fleet run grew excessively large, particularly in periods 7 and 8.			

1. In the fixed icebreaker fleet mode, icebreakers are free to respond anywhere in the task command, while in the maximum response time mode, icebreakers may respond only in those reaches with the same name part. As a result, the fixed fleet in tactical is utilized inefficiently because a major amount of time is spent travelling between BuInlt/Superior area and the Sea.

6. RESULTS OF SIMULATION RUNS

6.4 Discussion of Production Run Results

On the following pages, tables for each of the ten (10) production runs listed in Section 6.3 present a summary of:

- Input Run Condition
- Fixed Icebreaker Fleet or MRT Generated Icebreaker Fleet by Icebreaker Class, Task Command, and Period
- Statistics for Each Icebreaker Task Command (Taconite, Oil Can, Coal Shovel, Seaway)
 - Number of Icebreakers by Class and Period
 - Number of Icebreaker Direct Assists by Class and Period
 - Number of Icebreaker Hours Associated with Direct Assistance by Period
 - Number of Icebreaker Miles Associated with Direct Assistance by Period
 - Number of Icebreaker Convoys Escorted by Class and Period
 - Number of Icebreaker Hours Associated with Convoying by Period
 - Number of Icebreaker Miles Associated with Convoying by Period
 - Size of Direct Assistance and Convoy Queues
- Extended Navigation Season Tonnages by Commodity and Route

Detailed output from each of these production runs has been provided to the U.S. Coast Guard separately as computer print-outs.

For ease of reference, the summary tables for each of the runs listed in Table 6.10 in Section 6.3 are on the following pages.

<u>Run Number</u>	<u>Table Number</u>	<u>Page Number</u>
1	6.22a-g	6-39 - 6-45
2	6.23a-g	6-46 - 6-52
3	6.24a-g	6-53 - 6-59
4	6.25a-g	6-60 - 6-66
5	6.26a-g	6-67 - 6-73
6	6.27a-g	6-74 - 6-80
7	6.28a-g	6-81 - 6-87
8	6.29a-g	6-88 - 6-94
9	6.30a-g	6-95 - 6-101
10	6.31a-g	6-102- 6-108

TABLE 6.22a
SUMMARY OF INPUT CONDITIONS
FOR RUN NO. 1

Winter Type: Normal	Minimum Laker Class: 5
Run Mode: Fixed Icebreaker Fleet	
USCG Estimated Fleet: Normal	MRT (hr): N.A.
Convoying Icebreaker Types: C,B	Channel Clearing (in/per): None
Cargo Tonnage (year): 2000	
Convoy Routes:	

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	5
St. Marys River/Whitefish Bay	50,51	6-10
Straits of Mackinac	53	8
Detroit/St. Clair River System	72,73	None
Welland Canal	89	None
U.S. St. Lawrence Seaway	95	5-8
Canadian St. Lawrence Seaway	96	5-8

Data Files Used: SPDNRRL, SPDNRM, SPDNRH, SHIPPRO, EAGDFIB, RCH2NR5, RCH1S,
CLASS

Archived Output File Name: PR01A

TABLE 6.22b
USCG ESTIMATED FLEET* FOR NORMAL WINTER
FOR RUN NO. 1

<u>Home Port</u>	<u>Class B</u>	<u>Class C</u>
Duluth	-	2
Sault Ste. Marie	2	4
St. Ignace	1	1
Port Huron, Detroit, Toledo	1	2
Escanaba	-	1
Chicago	-	1
Saginaw	-	-
Sandusky	-	1
Buffalo	1	2
Oswego	-	3
SUBTOTAL	5	17
TOTAL	22	

NOTE: Principal ports; operations limited to vessels of reasonably high capability (SHP/L > 6); 12 hrs per day per icebreaker.

* Letter dated 8 June 1977 from Commander, Ninth Coast Guard District to the Commandant (G-0).

TABLE 6.22c
RESULTS OF RUN NO. 1
FOR TACONITE TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
Number of Icebreakers¹									
Class D	-	-	-	-	-	-	-	-	-
Class C	7-0%	7-0%	7-6%	7-102%	7-92%	7-97%	7-97%	7-101%	7-62%
Class B	3-0%	3-0%	3-5%	3-97%	3-101%	3-99%	3-100%	3-100%	3-49%
TOTAL	10-0%	10-0%	10-5%	10-100%	10-94%	10-98%	10-98%	10-100%	10-58%
Direct Assists									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	32	85	31	30	4	41	6
by Class B	-	-	3	35	128	147	96	133	10
TOTAL	-	-	35	120	159	177	100	174	16
Total Time (hr)	-	-	176	1621	1125	1118	772	1570	227
Total Miles	-	-	1703	21502	12522	11973	9557	14606	3189
Convoys Escorted									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	66	113	99	104	82	79
by Class B	-	-	-	35	8	7	9	5	22
TOTAL	-	-	-	101	121	106	113	87	101
Total Time (hr)	-	-	-	1744	2045	2162	2511	1797	1710
Total Miles	-	-	-	21544	17970	20839	22638	13474	15915
Avg. Size of Queues²									
Direct Assistance	-	-	-	4	10	11	6	9	1
St. Marys R. Convoy	-	-	-	27/3	24/11	15/11	7/8	15/8	18/11
Straits Convoy	-	-	-	-	-	-	2/2	-	-

- NOTES: 1. Second number is average percent time utilized; values greater than 100% sometimes result because time for assists and convoys not completed during previous period are included.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.
3. In the fixed icebreaker fleet mode, an icebreaker is free to respond anywhere in the task command, while for the maximum response time mode an icebreaker may respond only in those reaches with the same home port. As a result, the fixed fleet in Taconite is utilized inefficiently because a major amount of time is spent travelling between Duluth/Superior area and the Soo.

TABLE 6.22d
RESULTS OF RUN NO. 1
FOR OIL CAN TASK COMMAND

ITEM	Period									
	2	3	4	5	6	7	8	9	10	
Number of Icebreakers ¹										
Class D	-	-	-	-	-	-	-	-	-	
Class C	2-0%	2-0%	2-0%	2-23%	2-95%	2-17%	2-80%	2-6%	2-0%	
Class B	-	-	-	-	-	-	-	-	-	
TOTAL	2-0%	2-0%	2-0%	2-23%	2-95%	2-17%	2-80%	2-6%	2-0%	
Direct Assists										
by Class D	-	-	-	-	-	-	-	-	-	
by Class C	-	-	-	8	37	6	27	2	-	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	8	37	6	27	2	-	
Total Time (hr)	-	-	-	154	639	111	536	41	-	
Total Miles	-	-	-	1935	7841	1265	6413	593	-	
Convoys Escorted										
by Class D	-	-	-	-	-	-	-	-	-	
by Class C	-	-	-	-	-	-	-	-	-	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	-	-	-	-	-	-	
Total Time (hr)	-	-	-	-	-	-	-	-	-	
Total Miles	-	-	-	-	-	-	-	-	-	
Avg. Size of Queues										
Direct Assistance	-	-	-	0	2	0	0	0	-	

NOTE: 1. Second number is average percent time utilized.

TABLE 6.22e
RESULTS OF RUN NO. 1
FOR COAL SHOVEL TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	5-0%	5-0%	5-1%	5-54%	5-102%	5-5%	5-0%	5-0%	5-0%
Class B	2-0%	2-0%	2-0%	2-51%	2-97%	2-5%	2-0%	2-0%	2-0%
TOTAL	7-0%	7-0%	7-1%	7-53%	7-101%	7-5%	7-0%	7-0%	7-0%
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	1	46	77	4	-	-	-
by Class B	-	-	-	24	42	6	-	-	-
TOTAL	-	-	1	70	119	10	-	-	-
Total Time (hr)	-	-	18	1246	2365	123	-	-	-
Total Miles	-	-	208	11576	20806	1393	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	2	0	-	-	-
Detroit/St. Clair	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

- NOTES: 1. Second number is average percent time utilized; values greater than 100% sometimes result because time for assists and convoys not completed during previous period are included.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.
3. In the fixed icebreaker fleet mode, an icebreaker is free to respond anywhere in the task command, while for the maximum response time mode an icebreaker may respond only in those reaches with the same home port. As a result, the fixed fleet in Taconite is utilized inefficiently because a major amount of time is spent travelling between Duluth/Superior area and the Soo.

TABLE 6.22f
RESULTS OF RUN NO. 1
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	3-0%	3-0%	3-0%	3-109%	3-99%	3-97%	3-94%	3-2%	3-0%
Class B	-	-	-	-	-	-	-	-	-
TOTAL	3-0%	3-0%	3-0%	3-109%	3-99%	3-97%	3-94%	3-2%	3-0%
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	52	45	44	32	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	52	45	44	32	-	-
Total Time (hr)	-	-	-	1099	1000	977	945	-	-
Total Miles	-	-	-	10301	8188	8846	8537	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	-	-	-	-	-	-
St. Lawrence Seaway	-	-	-	2/4	2/6	2/4	0/2	-	-
Convoy	-	-	-	-	-	-	-	-	-

- NOTES: 1. Second number is average percent time utilized; values greater than 100% sometimes result because time for assists and convoys not completed during previous period are included.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.
3. In the fixed icebreaker fleet mode, an icebreaker is free to respond anywhere in the task command, while for the maximum response time mode an icebreaker may respond only in those reaches with the same home port. As a result, the fixed fleet in Tacofite is utilized inefficiently because a major amount of time is spent travelling between Duluth/Superior area and the Soo.

TABLE 6.22g
EXTENDED SEASON TONNAGE
BY ROUTE FOR RUN NO. 1

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>
1	647	22	649	44	1071	74	-
2	1024	23	877	45	1089	75	-
3	574	24	1023	46	1092	76	-
4	158	26	599	47	449	77	641
5	878	27	438	48	2862	78	1319
6	877	28	606	49	1038	80	50
8	1406	29	1043	51	1191	81	99
9	1459	30	1440	53	181	83	-
10	874	32	542	54	978	85	50
11	999	33	875	56	121	TOTAL	2159
12	1724	34	613	57	100		
13	1661	35	488	58	226		
14	877	37	1034	59	224		
15	602	38	913	60	597		
17	1193	39	999	61	1943		
19	879	41	640	63	155		
20	476	42	929	64	293	GENERAL CARGO-SALTY	
21	283	TOTAL	30299	65	221	<u>Route</u>	<u>Tons</u>
				66	1357	87	466
				68	201		
				69	201		
				70	439		
				71	607		
				72	2531		
				TOTAL	19167		
						BULK CARGO-SALTY	
						<u>Route</u>	<u>Tons</u>
						88	6220
						89	2621
						90	708
						91	327
						92	445
						93	606
						TOTAL	10927
						GRAND TOTAL	63018

Maximum Number of Vessels:

Lakers: 159
Salty General Cargo: 28
Salty Bulk: 126

NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.23a
SUMMARY OF INPUT CONDITIONS
FOR RUN NO. 2

Winter Type: Normal	Minimum Laker Class: 5
Run Mode: Maximum Response Time	
USCG Estimated Fleet: N.A.	MRT (hr): Minimum*
Convoying Icebreaker Types: C,B	Channel Clearing (in/per): None
Cargo Tonnage (year): 2000	
Convoy Routes:	

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	5
St. Marys River/Whitefish Bay	50,51	6-10
Straits of Mackinac	53	8
Detroit/St. Clair River System	72,73	None
Welland Canal	89	None
U.S. St. Lawrence Seaway	95	5-8
Canadian St. Lawrence Seaway	96	5-8

Data Files Used: SPDNR, SPDNRH, SHIPPRO, EAGDMRT, RCH2NR5, RCHIN, CLASS

Archived Output File Name: PR02Z

* The minimum value of the maximum response time is calculated as the time required to get to the furthest point in the reach from the closest home port, at 5 mph.

TABLE 6.23b

PREDICTED ICEBREAKER FLEET BY HOME PORT AND PERIOD FOR RUN NO. 2

LOCATION	CLASS D										CLASS C										CLASS B									
	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10			
THUNDER BAY TC	-	-	-	4	-	-	-	1	-	-	-	-	-	3	5	-	-	-	-	-	-	-	-	-	-	4	-			
Duluth	-	-	3	-	-	-	-	-	1	-	-	-	-	5	-	-	-	-	-	-	-	-	-	4	3	3	3			
Presque Isle	-	-	1	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Sault Ste. Marie	-	-	-	-	2	-	1	-	-	-	-	-	4	7	7	5	7	6	-	-	-	-	-	-	-	-	-			
St. Ignace	-	-	-	-	5	3	0	-	1	-	-	-	-	-	-	2	4	-	-	-	-	-	-	-	-	-	-			
TACONITE TC	-	-	4	-	7	3	2	-	2	-	-	-	9	7	7	7	11	6	-	-	-	-	4	3	3	3	-			
Escanaba	-	-	-	4	16	4	14	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Green Bay	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Milwaukee	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Chicago	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Grand Haven	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
OIL CAN TC	-	-	-	4	16	4	14	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Saginaw	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Port Huron	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Detroit	-	-	-	5	6	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Toledo	-	-	-	6	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Sandusky	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Cleveland	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Buffalo	-	-	-	7	12	1	-	-	-	-	-	-	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
COAL SHOVEL TC	-	-	1	18	24	4	-	-	-	-	-	-	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Port Colborne	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Toronto	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
WELLAND TC	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Oswego	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Alexandria Bay	-	-	-	-	-	-	-	-	-	-	-	-	5	4	6	4	1	-	-	-	-	-	-	-	-	-	-			
SEAWAY TC	-	-	-	-	-	-	-	-	-	-	-	-	5	4	6	4	1	-	-	-	-	-	-	-	-	-	-			
Montreal	-	-	-	-	-	-	-	-	-	-	-	-	6	5	5	3	1	-	-	-	-	-	-	-	0	-	0			
Quebec	-	4	4	4	4	2	3	2	5	-	-	-	1	-	4	-	-	-	-	-	-	-	-	-	5	6	12	8	-	
QUEBEC TC	-	4	4	4	4	2	3	2	5	-	-	-	7	5	9	3	1	-	-	-	-	-	-	-	-	5	6	12	8	-
U.S.	-	-	5	22	47	11	16	4	2	-	-	-	14	15	13	11	12	6	-	-	-	-	-	-	-	4	3	3	3	-

TABLE 6.23C

RESULTS OF RUN NO. 2

FOR TACONITE TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	4-13%	-	7-12%	3-25%	2-10%	-	2-2%
Class C	-	-	-	9-28%	7-87%	7-83%	7-80%	11-70%	6-85%
Class B	-	-	-	-	4-33%	3-40%	3-33%	3-37%	-
TOTAL	-	-	4-13%	9-28%	18-46%	13-60%	12-56%	14-63%	8-64%
<u>Direct Assists</u>									
by Class D	-	-	35	-	34	28	4	-	5
by Class C	-	-	-	133	1	1	2	48	1
by Class B	-	-	-	-	144	128	107	118	-
TOTAL	-	-	35	133	179	157	113	166	6
Total Time (hr)	-	-	181	478	736	663	417	995	24
Total Miles	-	-	1379	3081	4286	3997	2943	5819	187
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	148	129	121	115	95	109
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	148	129	121	115	95	109
Total Time (hr)	-	-	-	1234	2024	1934	1848	1946	1703
Total Miles	-	-	-	9706	17309	15901	13149	12777	14428
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	23/2	23/11	17/11	9/8	12/7	16/11
St. Marys R. Convoy	-	-	-	-	-	-	3/2	-	-
Straits Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.23d
RESULTS OF RUN NO. 2
FOR OIL CAN TASK COMMAND

ITEM	2	3	4	5	Period					
					6	7	8	9	10	
<u>Number of Icebreakers¹</u>										
Class D	-	-	-	4-10%	16-16%	4-11%	14-17%	4-7%	-	-
Class C	-	-	-	-	-	-	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	4-10%	16-16%	4-11%	14-17%	4-7%	-	-
<u>Direct Assists</u>										
by Class D	-	-	-	8	35	7	30	10	-	-
by Class C	-	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	8	35	7	30	10	-	-
Total Time (hr)	-	-	-	129	850	152	811	93	-	-
Total Miles	-	-	-	1129	8512	1368	7531	1041	-	-
<u>Convoys Escorted</u>										
by Class D	-	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues</u>										
Direct Assistance	-	-	-	0	2	1	2	1	-	-

NOTE: 1. Second number is average percent time utilized.

TABLE 6.23e
RESULTS OF RUN NO. 2
FOR COAL SHOVEL TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	1-3%	18-24%	24-26%	4-6%	-	-	-
Class C	-	-	-	-	4-37%	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	1-3%	18-24%	28-27%	4-6%	-	-	-
<u>Direct Assists</u>									
by Class D	-	-	1	68	77	10	-	-	-
by Class C	-	-	-	-	42	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	1	68	119	10	-	-	-
Total Time (hr)	-	-	10	1434	2574	78	-	-	-
Total Miles	-	-	74	8441	11305	386	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	1	1	0	-	-	-
Detroit/St. Clair	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.23f
RESULTS OF RUN NO. 2
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	-	-	-	-	-	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	-	-	-	-	-	-
St. Lawrence Seaway	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.23g

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>
1	649	22	649	44	1071	74	-
2	1024	23	875	45	1089	75	-
3	572	24	1023	46	1091	76	-
4	161	26	601	47	449	77	651
5	873	27	438	48	2866	78	1349
6	875	28	606	49	1040	80	50
8	1409	29	1045	51	1189	81	99
9	1457	30	1441	53	181	83	-
10	876	32	541	54	978	85	51
11	1000	33	877	56	121	TOTAL	2200
12	1727	34	612	57	100		
13	1661	35	485	58	226		
14	876	37	1035	59	224		
15	602	38	915	60	597		
17	1193	39	999	61	1942		
19	881	41	640	63	155		
20	476	42	938	64	293		
21	283	TOTAL	30315	65	221	GENERAL CARGO-	
				66	1357	SALTY	
				68	201	<u>Route</u>	<u>Tons</u>
				69	201	87	440
				70	439		
				71	607		
				72	2531		
				TOTAL	19169		

BULK CARGO-SALTY	
<u>Route</u>	<u>Tons</u>
88	6223
89	2620
90	707
91	331
92	445
93	604
TOTAL	10930
ND TOTAL	63054

Maximum Number of Vessels:
 Lakers: 145
 Salty General Cargo: 27
 Salty Bulk: 111

NOTES:

1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.24a
SUMMARY OF INPUT CONDITIONS
FOR RUN NO. 3

Winter Type: Normal	Minimum Laker Class: 5
Run Mode: Maximum Response Time	
USCG Estimated Fleet: N.A.	MRT (hr): Minimum + 12
Convoying Icebreaker Types: C,B	Channel Clearing (in/per): None
Cargo Tonnage (year): 2000	
Convoy Routes:	

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	5
St. Marys River/Whitefish Bay	50,51	6-10
Straits of Mackinac	53	8
Detroit/St. Clair River System	72,73	None
Welland Canal	89	None
U.S. St. Lawrence Seaway	95	5-8
Canadian St. Lawrence Seaway	96	5-8

Data Files Used: SPDNR1, SPDNR2, SPDNRH, SHIPPRO, EAGDMRT,
RCH2NR5, RCH1S, CLASS

Archived Output File Name: PR03Z

TABLE 6.24b

PREDICTED ICEBREAKER FLEET BY HOME PORT AND PERIOD FOR RUN No. 3

LOCATION	CLASS D										CLASS C										CLASS B									
	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10			
THUNDER BAY TC	-	-	-	3	-	-	-	1	-	-	-	-	-	4	7	-	-	-	-	-	-	-	-	-	-	-	-			
Duluth	-	-	5	-	-	-	-	-	1	-	-	-	2	-	-	-	-	-	-	-	-	-	4	3	5	6	-			
Presque Isle	-	-	1	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Sault Ste. Marie	-	-	-	-	-	-	1	-	-	-	-	-	4	6	7	7	5	5	-	-	-	-	-	-	-	-				
St. Ignace	-	-	-	-	3	2	1	-	1	-	-	-	-	-	2	5	-	-	-	-	-	-	-	-	-	-				
TACONITE TC	-	-	6	-	3	2	3	-	2	-	-	-	6	6	7	9	10	5	-	-	-	-	4	3	5	6				
Escanaba	-	-	-	4	15	4	16	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Green Bay	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Milwaukee	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Chicago	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Grand Haven	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
OIL CAN TC	-	-	-	4	15	4	16	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Saginaw	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Port Huron	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Detroit	-	-	-	6	7	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Toledo	-	-	-	6	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Sandusky	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Cleveland	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Buffalo	-	-	-	7	12	1	-	-	-	-	-	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-				
COAL SHOVEL TC	-	-	-	20	25	5	-	-	-	-	-	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-				
Port Colborne	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Toronto	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
WELLAND TC	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Oswego	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Alexandria Bay	-	-	-	-	-	-	-	-	-	-	-	-	5	4	4	3	1	-	-	-	-	-	-	-	-	-				
SEAWAY TC	-	-	-	-	-	-	-	-	-	-	-	-	5	4	4	3	1	-	-	-	-	-	-	-	-	-				
Montreal	-	-	-	-	-	-	-	-	-	-	-	-	5	4	4	3	1	-	-	-	-	-	-	-	-	-				
Quebec	-	3	4	4	3	2	3	2	6	-	-	-	1	3	6	-	-	-	-	-	-	-	-	-	-	-				
QUEBEC TC	-	3	4	4	3	2	3	2	6	-	-	-	6	7	10	3	1	-	-	-	-	-	-	-	-	-				
U.S.	-	-	6	24	43	11	19	3	2	-	-	-	11	15	11	12	11	5	-	-	-	-	-	-	-	-				

TABLE 6.24c

RESULTS OF RUN NO. 3

FOR TACONITE TASK COMMAND

ITEM	Period									
	2	3	4	5	6	7	8	9	10	
Number of Icebreakers ¹										
Class D	-	-	6-9%	-	3-24%	2-39%	3-8%	-	2-3%	
Class C	-	-	-	6-8%	6-91%	7-83%	9-61%	10-63%	5-96%	
Class B	-	-	-	-	4-34%	3-40%	5-19%	6-19%	-	
TOTAL	-	-	6-9%	6-8%	13-58%	12-65%	17-39%	16-46%	7-69%	
Direct Assists										
by Class D	-	-	35	-	28	30	5	-	6	
by Class C	-	-	-	129	4	1	2	50	1	
by Class B	-	-	-	-	144	130	105	122	-	
TOTAL	-	-	35	129	176	161	112	172	7	
Total Time (hr)	-	-	181	497	741	674	425	1024	25	
Total Miles	-	-	1379	3637	4737	3893	2920	5868	205	
Convoys Escorted										
by Class D	-	-	-	-	-	-	-	-	-	
by Class C	-	-	-	149	123	120	110	87	110	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	149	123	120	110	87	110	
Total Time (hr)	-	-	-	1179	1777	1932	1821	1456	1596	
Total Miles	-	-	-	9200	14951	15889	12967	9174	13339	
Avg. Size of Queues ²										
Direct Assistance	-	-	1	1	1	0	0	1	0	
St. Marys R. Convoy	-	-	-	23/2	24/12	17/13	9/9	14/10	17/15	
Straits Convoy	-	-	-	-	-	-	3/3	-	-	

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.24d
RESULTS OF RUN NO. 3
FOR OIL CAN TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	4-10%	15-16%	4-10%	16-15%	3-7%	-
Class C	-	-	-	-	-	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	4-10%	15-16%	4-10%	16-15%	3-7%	-
<u>Direct Assists</u>									
by Class D	-	-	-	8	33	6	30	9	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	8	33	6	30	9	-
Total Time (hr)	-	-	-	129	812	134	789	72	-
Total Miles	-	-	-	1129	8101	1212	7288	777	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues</u>									
Direct Assistance	-	-	-	1	2	1	3	1	-

NOTE: 1. Second number is average percent time utilized.

TABLE 6.24e

RESULTS OF RUN NO. 3

FOR COAL SHOVEL TASK COMMAND

ITEM	Period									
	2	3	4	5	6	7	8	9	10	
<u>Number of Icebreakers¹</u>										
Class D	-	-	-	20-21%	25-25%	5-7%	-	-	-	
Class C	-	-	-	-	5-29%	-	-	-	-	
Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	20-21%	30-26%	5-7%	-	-	-	
<u>Direct Assists</u>										
by Class D	-	-	-	68	78	11	-	-	-	
by Class C	-	-	-	-	41	-	-	-	-	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	68	119	11	-	-	-	
Total Time (hr)	-	-	-	1392	2610	120	-	-	-	
Total Miles	-	-	-	8173	11434	682	-	-	-	
<u>Convoys Escorted</u>										
by Class D	-	-	-	-	-	-	-	-	-	
by Class C	-	-	-	-	-	-	-	-	-	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	-	-	-	-	-	-	
Total Time (hr)	-	-	-	-	-	-	-	-	-	
Total Miles	-	-	-	-	-	-	-	-	-	
<u>Avg. Size of Queues²</u>										
Direct Assistance	-	-	-	2	3	0	-	-	-	
Detroit/St. Clair Convoy	-	-	-	-	-	-	-	-	-	

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.24f
RESULTS OF RUN NO. 3
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	-	-	-	-	-	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	-	-	-	-	-	-
St. Lawrence Seaway	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.24g

EXTENDED SEASON TONNAGE
BY ROUTE FOR RUN NO. 3

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>
1	649	22	649	44	1070	74	-
2	1023	23	877	45	1089	75	-
3	571	24	1025	46	1091	76	-
4	161	26	601	47	449	77	651
5	873	27	437	48	2866	78	1349
6	878	28	605	49	1038	80	50
8	1409	29	1044	51	1192	81	99
9	1455	30	1438	53	181	83	-
10	876	32	541	54	978	85	50
11	999	33	878	56	121	TOTAL	2199
12	1726	34	612	57	100		
13	1655	35	494	58	226		
14	878	37	1035	59	224		
15	602	38	915	60	597		
17	1191	39	999	61	1890		
19	877	41	641	63	155		
20	476	42	934	64	293		
21	283	TOTAL	30307	65	221	GENERAL CARGO-	
				66	1357	SALTY	
				68	201	<u>Route</u>	<u>Tons</u>
				69	201		
				70	438	87	446
				71	606		
				72	2531		
				TOTAL	19115		

BULK CARGO-SALTY	
<u>Route</u>	<u>Tons</u>
88	6224
89	2632
90	708
91	330
92	445
93	603
TOTAL	10942
ND TOTAL	63009

Maximum Number of Vessels:
 Lakers: 150
 Salty General Cargo: 28
 Salty Bulk: 114

NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.25a
SUMMARY OF INPUT CONDITIONS
FOR RUN NO. 4

Winter Type: Normal	Minimum Laker Class: 5
Run Mode: Fixed Icebreaker Fleet	
USCG Estimated Fleet: Normal	MRT (hr): N.A.
Convoying Icebreaker Types: C,B	Channel Clearing (in/per): None
Cargo Tonnage (year): 2000 + 20%	
Convoy Routes:	

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	5
St. Marys River/Whitefish Bay	50,51	6-10
Straits of Mackinac	53	8
Detroit/St. Clair River System	72,73	None
Welland Canal	89	None
U.S. St. Lawrence Seaway	95	5-8
Canadian St. Lawrence Seaway	96	5-8

Data Files Used: SPDNR, SPDNRH, SHIPP20, EAGDFIB,
RCH2NR5, RCH1S, CLASS

Archived Output File Name: PR04A

TABLE 6.25b
USCG ESTIMATED FLEET* FOR NORMAL WINTER
FOR RUN NO. 4

<u>Home Port</u>	<u>Class B</u>	<u>Class C</u>
Duluth	-	2
Sault Ste. Marie	2	4
St. Ignace	1	1
Port Huron, Detroit, Toledo	1	2
Escanaba	-	1
Chicago	-	1
Saginaw	-	-
Sandusky	-	1
Buffalo	1	2
Oswego	-	3
SUBTOTAL	5	17
TOTAL	22	

NOTE: Principal ports; operations limited to vessels of reasonably high capability (SHP/L > 6); 12 hrs per day per icebreaker.

* Letter dated 8 June 1977 from Commander, Ninth Coast Guard District to the Commandant (G-0).

TABLE 6.25c
RESULTS OF RUN NO. 4
FOR TACONITE TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	7-	7-	7-6%	7-99%	7-98%	7-101%	7-98%	7-101%	7-84%
Class B	3-	3-	3-16%	3-96%	3-98%	3-100%	3-102%	3-102%	3-62%
TOTAL	10-	10-	10-9%	10-98%	10-98%	10-100%	10-99%	10-101%	10-77%
<u>Direct Assists</u>									
by Class D	-	-	-	92	38	39	10	51	12
by Class C	-	-	36	43	155	180	127	116	13
by Class B	-	-	41	135	193	219	137	167	25
TOTAL	-	-	315	1663	1197	1227	818	1783	411
Total Time (hr)	-	-	3855	21760	12517	12140	8884	16302	5903
Total Miles	-	-	-	-	-	-	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	75	134	126	124	80	100
by Class C	-	-	-	30	9	8	11	7	26
by Class B	-	-	-	105	143	134	135	87	126
TOTAL	-	-	-	1637	2093	2142	2514	1613	2187
Total Time (hr)	-	-	-	20048	19501	19442	21267	12343	21168
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	5	14	12	8	12	3
St. Marys R. Convoy	-	-	-	33/9	34/18	20/13	10/8	18/11	23/23
Straits Convoy	-	-	-	-	-	-	3/2	1/0	-

NOTES: 1. Second number is average percent time utilized; values greater than 100% sometimes result because time for assists and convoys not completed during previous period are included.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

3. In the fixed icebreaker fleet mode, an icebreaker is free to respond anywhere in the task command, while for the maximum response time mode an icebreaker may respond only in those reaches with the same home port. As a result, the fixed fleet in Taconite is utilized inefficiently because a major amount of time is spent travelling between Duluth/Superior area and the Soo.

TABLE 6.25d

RESULTS OF RUN NO. 4

FOR OIL CAN TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	2-0%	2-0%	2-0%	2-19%	2-95%	2-26%	2-84%	2-8%	2-0%
Class B	-	-	-	-	-	-	-	-	-
TOTAL	2-0%	2-0%	2-0%	2-19%	2-95%	2-26%	2-84%	2-8%	2-0%
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	10	40	8	27	3	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	10	40	8	27	3	-
Total Time (hr)	-	-	-	127	639	173	563	53	-
Total Miles	-	-	-	1394	7697	2162	6934	764	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues</u>									
Direct Assistance	-	-	-	0	1	0	1	0	-

NOTE: 1. Second number is average percent time utilized.

TABLE 6.25e
RESULTS OF RUN NO. 4
FOR COAL SHOVEL TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	5-0%	5-0%	5-2%	5-64%	5-102%	5-14%	5-0%	5-0%	5-0%
Class B	2-0%	2-0%	2-0%	2-67%	2-101%	2-11%	2-1%	2-0%	2-0%
TOTAL	7-0%	7-0%	7-1%	7-65%	7-102%	7-13%	7-0%	7-0%	7-0%
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	2	53	77	14	-	-	-
by Class B	-	-	-	28	49	11	1	-	-
TOTAL	-	-	2	81	126	25	1	-	-
Total Time (hr)	-	-	35	1525	2392	314	4	-	-
Total Miles	-	-	416	14410	21220	3632	44	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	6	1	1	-	-
Detroit/St. Clair	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized; values greater than 100% sometimes result because time for assists and convoys not completed during previous period are included.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.25f
RESULTS OF RUN NO. 4
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	3-0%	3-0%	3-0%	3-107%	3-103%	3-100%	3-87%	3-4%	3-0%
Class B	-	-	-	-	-	-	-	-	-
TOTAL	3-0%	3-0%	3-0%	3-107%	3-103%	3-100%	3-87%	3-4%	3-0%
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	54	50	50	33	1	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	54	50	50	33	1	-
Total Time (hr)	-	-	-	1076	1041	1009	871	38	-
Total Miles	-	-	-	9927	8355	8790	7738	412	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	5/5	5/10	6/12	1/3	-	-
St. Lawrence Seaway Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized; values greater than 100% sometimes result because time for assists and convoys not completed during previous period are included.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.25g
EXTENDED SEASON TONNAGE
BY ROUTE FOR RUN NO. 4

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
Route	Tons	Route	Tons	Route	Tons	Route	Tons
1	872	22	814	44	1309	74	41
2	1141	23	1071	45	1322	75	25
3	632	24	1140	46	1326	76	-
4	210	26	648	47	587	77	782
5	1017	27	548	48	3330	78	1483
6	1013	28	648	49	1284	80	50
8	1687	29	1310	51	1406	81	123
9	1802	30	1742	53	226	83	25
10	1024	32	761	54	1179	85	74
11	1041	33	1019	56	141	TOTAL	2603
12	2047	34	718	57	141		
13	1919	35	589	58	283		
14	1028	37	1271	59	262		
15	748	38	1040	60	739		
17	1436	39	1070	61	2327		
19	1030	41	768	63	181		
20	576	42	1109	64	372		
21	299	TOTAL	35734	65	262	GENERAL CARGO-SALTY	
				66	1640	Route	Tons
				68	242		
				69	222	87	548
				70	527		
				71	744		
				72	3045		
				TOTAL	23097		

BULK CARGO-SALTY

Route	Tons
88	7201
89	3178
90	868
91	373
92	526
93	739
TOTAL	12885

GRAND TOTAL 74867

Maximum Number of Vessels:

Lakers: 198
Salty General Cargo: 35
Salty Bulk: 157

- NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.26a
SUMMARY OF INPUT CONDITIONS
FOR RUN NO. 5

Winter Type: Severe	Minimum Laker Class: 5
Run Mode: Maximum Response Time	
USCG Estimated Fleet: N.A.	MRT (hr): Minimum + 12
Convoying Icebreaker Types: B only	Channel Clearing (in/per): None
Cargo Tonnage (year): 2000	
Convoy Routes:	

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	4
St. Marys River/Whitefish Bay	50,51	5-10
Straits of Mackinac	53	5-10
Detroit/St. Clair River System	72,73	5-7
Welland Canal	89	5-7
U.S. St. Lawrence Seaway	95	5-8
Canadian St. Lawrence Seaway	96	5-8

Data Files Used: SPDSVL, SPDSVM, SPDSVH, SHIPPRO, EAGDMRT,
RCH2SV5, RCH1S, CLASSNC

Archived Output File Name: PRO5A

TABLE 6.26b

PREDICTED ICEBREAKER FLEET BY HOME PORT AND PERIOD FOR RUN NO. 5

LOCATION	CLASS D										CLASS C										CLASS B																	
	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10		
THUNDER BAY TC	-	-	1	2	-	-	-	2	3	-	-	-	-	6	-	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	8	-	-	-		
Duluth	-	-	3	-	-	-	-	-	-	-	-	-	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	4	2	4	4		
Presque Isle	-	-	-	-	-	29	12	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Sault Ste. Marie	-	-	-	2	-	-	1	-	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	3	4	3	3	3		
St. Ignace	-	-	-	-	-	-	2	1	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2	2	2	2	2	1		
TACONITE TC	-	-	3	2	-	29	15	1	2	-	-	-	4	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	5	10	9	7	9	8	
Esplanada	-	2	3	2	1	-	-	-	-	-	-	-	-	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	-	-	-		
Green Bay	-	-	-	-	1	-	-	-	-	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Milwaukee	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Chicago	-	-	5	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Grand Haven	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
OIL CAN TC	-	2	8	3	2	-	-	-	-	-	-	-	-	4	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	-	-	-		
Saginaw	-	-	-	29	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Port Huron	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2	2	2	1	-		
Detroit	-	-	-	2	8	-	2	-	-	-	-	-	-	-	10	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	3	2	1	-		
Toledo	-	-	-	1	20	-	-	-	-	-	-	-	-	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Sandusky	-	2	1	4	6	3	-	-	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Cleveland	-	1	-	4	3	-	-	-	-	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Buffalo	-	2	-	1	1	1	12	2	1	-	-	-	-	-	24	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	4	6	6	2	-			
COAL SHOVEL TC	-	3	3	40	44	4	14	2	1	-	-	-	-	-	43	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	9	11	10	4	-		
Port Colborne	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	3	4	1	-		
Toronto	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
WELLAND TC	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	3	4	1	-			
Oswego	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Alexandria Bay	-	-	1	1	-	-	1	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	4	5	3	-		
SEAWAY TC	-	-	1	1	-	-	1	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	4	5	3	-		
Montreal	-	-	1	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	6	5	4	2		
Quebec	-	3	4	5	5	2	3	5	-	-	-	-	-	-	4	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2	5	-	-		
QUEBEC TC	-	3	5	5	5	2	3	5	3	-	-	-	-	-	-	4	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	8	10	4	2		
	-	5	15	46	46	33	30	3	3	-	-	-	4	5	47	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	17	25	28	14	9	8

TABLE 6.26c
RESULTS OF RUN NO. 5
FOR TACONITE TASK COMMAND

ITEM	Period									
	2	3	4	5	6	7	8	9	10	
Number of Icebreakers ¹										
Class D	-	-	3-23%	2-13%	-	29-34%	15-09%	1-28%	2-22%	
Class C	-	-	-	4-76%	-	1-20%	-	-	-	
Class B	-	-	3-83%	5-60%	10-53%	9-56%	7-66%	9-51%	8-61%	
TOTAL	-	-	6-53%	11-57%	10-53%	39-39%	22-27%	10-49%	10-53%	
Direct Assists										
by Class D	-	-	39	7	-	59	34	15	23	
by Class C	-	-	-	122	-	5	-	-	-	
by Class B	-	-	-	3	154	154	135	147	139	
TOTAL	-	-	39	132	154	218	169	162	162	
Total Time (hr)	-	-	235	1131	637	4033	1100	769	803	
Total Miles	-	-	944	4451	3797	19471	7410	4322	4894	
Convoys Escorted										
by Class D	-	-	-	-	-	-	-	-	-	
by Class C	-	-	-	-	-	-	-	-	-	
by Class B	-	-	96	78	95	84	76	72	80	
TOTAL	-	-	96	78	95	84	76	72	80	
Total Time (hr)	-	-	840	968	1161	1063	927	877	978	
Total Miles	-	-	6670	7870	10372	9557	7773	7847	8853	
Avg. Size of Queues ²										
Direct Assistance	-	-	0	1	1	4	4	1	1	
St. Marys R. Convoy	-	-	32/1	21/18	19/24	14/19	13/11	15/13	16/14	
Straits Convoy	-	-	-	4/6	5/8	4/8	4/6	2/3	4/4	

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.26d
RESULTS OF RUN NO. 5
FOR OIL CAN TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	2-11%	8-10%	3-21%	2-16%	-	-	-	-
Class C	-	-	-	-	4-26%	3-15%	-	-	-
Class B	-	-	-	-	-	4-13%	-	-	-
TOTAL	-	2-11%	8-10%	3-21%	6-23%	7-14%	-	-	-
<u>Direct Assists</u>									
by Class D	-	9	21	12	3	-	-	-	-
by Class C	-	-	-	-	29	6	-	-	-
by Class B	-	-	-	-	-	23	-	-	-
TOTAL	-	9	21	12	32	29	-	-	-
Total Time (hr)	-	77	252	208	454	326	-	-	-
Total Miles	-	312	2228	1022	1524	2208	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues</u>									
Direct Assistance	-	0	1	0	0	0	-	-	-

NOTE: 1. Second number is average percent time utilized.

TABLE 6.26e
RESULTS OF RUN NO. 5
FOR COAL SHOVEL TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	3-10%	3-19%	40-34%	44-36%	4-58%	14-22%	2-13%	1-04%
Class C	-	-	-	-	-	43-32%	-	1-29%	-
Class B	-	-	-	9-45%	11-51%	10-42%	4-15%	0	-
TOTAL	-	3-10%	3-19%	49-36%	55-39%	57-36%	18-21%	3-18%	1-04%
<u>Direct Assists</u>									
by Class D	-	10	20	92	119	8	22	2	4
by Class C	-	-	-	-	-	123	-	22	-
by Class B	-	-	-	54	47	34	26	-	-
TOTAL	-	10	20	146	166	165	48	24	4
Total Time (hr)	-	98	190	5263	6304	6169	1250	183	13
Total Miles	-	731	688	26331	32468	30057	6027	1047	60
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	51	66	57	3	-	-
TOTAL	-	-	-	51	66	57	3	-	-
Total Time (hr)	-	-	-	660	854	695	50	-	-
Total Miles	-	-	-	5463	6926	5560	389	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	0	0	6	4	5	2	0	0
Detroit/St. Clair	-	-	-	14/15	17/13	14/11	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.26f
RESULTS OF RUN NO. 5
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	Period					
					6	7	8	9	10	
<u>Number of Icebreakers¹</u>										
Class D	-	-	1-25%	1-32%	-	-	1-24%	-	-	-
Class C	-	-	-	-	1-36%	-	-	-	-	-
Class B	-	-	-	3-77%	4-85%	5-57%	3-62%	-	-	-
TOTAL	-	-	1-25%	4-66%	5-75%	5-57%	4-52%	-	-	-
<u>Direct Assists</u>										
by Class D	-	-	2	4	-	-	6	-	-	-
by Class C	-	-	-	-	9	-	-	-	-	-
by Class B	-	-	-	-	6	13	2	-	-	-
TOTAL	-	-	2	4	15	13	8	-	-	-
Total Time (hr)	-	-	83	106	201	144	103	-	-	-
Total Miles	-	-	519	458	1065	888	576	-	-	-
<u>Convoys Escorted</u>										
by Class D	-	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	32	44	32	25	-	-	-
TOTAL	-	-	-	32	44	32	25	-	-	-
Total Time (hr)	-	-	-	778	1060	809	601	-	-	-
Total Miles	-	-	-	7395	10095	7575	5685	-	-	-
<u>Avg. Size of Queues²</u>										
Direct Assistance	-	-	0	0	0	0	0	-	-	-
St. Lawrence Seaway	-	-	-	1/3	3/5	1/3	0/4	-	-	-
Convoy	-	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.26g

EXTENDED SEASON TONNAGE
BY ROUTE FOR RUN NO. 5

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>
1	645	22	649	44	1072	74	-
2	1026	23	874	45	1089	75	-
3	569	24	1023	46	1088	76	-
4	161	26	602	47	449	77	641
5	872	27	438	48	2856	78	1372
6	876	28	605	49	1039	80	50
8	1399	29	1041	51	1187	81	100
9	1429	30	1445	53	181	83	-
10	872	32	542	54	978	85	50
11	995	33	859	56	121	TOTAL	2213
12	1721	34	610	57	100		
13	1643	35	489	58	226		
14	863	37	1034	59	224		
15	602	38	912	60	594		
17	1160	39	998	61	1890		
19	869	41	628	63	155		
20	475	42	937	64	293		
21	283	TOTAL	30146	65	221	GENERAL CARGO-	
				66	1357	SALTY	
				68	201	<u>Route</u>	<u>Tons</u>
				69	201		
				70	427	87	455
				71	607		
				72	2532		
				TOTAL	19089		

BULK CARGO-SALTY	
<u>Route</u>	<u>Tons</u>
88	6226
89	2639
90	710
91	331
92	444
93	606
TOTAL	10956
ND TOTAL	62859

Maximum Number of Vessels:
 Lakers: 209
 Salty General Cargo: 30
 Salty Bulk: 129

NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.27a
SUMMARY OF INPUT CONDITIONS
FOR RUN NO. 6

Winter Type: Normal	Minimum Laker Class: 5
Run Mode: Maximum Response Time	
USCG Estimated Fleet: N.A.	MRT (hr): Minimum + 12
Convoying Icebreaker Types: No Convoys	Channel Clearing (in/per): None
Cargo Tonnage (year): 2000	
Convoy Routes:	

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	-
St. Marys River/Whitefish Bay	50,51	-
Straits of Mackinac	53	-
Detroit/St. Clair River System	72,73	-
Welland Canal	89	-
U.S. St. Lawrence Seaway	95	-
Canadian St. Lawrence Seaway	96	-

Data Files Used: SPDNRL, SPDNRM, SPDNRH, SHIPPRO, EAGDMRT, RCH2NC, RCH1S, CLASS

Archived Output File Name: PR06A

TABLE 6.27b

PREDICTED ICEBREAKER FLEET BY HOME PORT AND PERIOD FOR RUN NO. 6

LOCATION	CLASS D										CLASS C										CLASS B																
	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	
THUNDER BAY TC	-	-	-	3	-	-	-	1	-	-	-	-	-	3	4	-	-	-	-	-	-	-	-	-	4	-	-	-	-	-	-	-	-	-	-	-	-
Duluth	-	-	5	-	-	-	-	-	1	-	-	-	10	-	-	-	-	-	-	-	-	-	11	9	10	12	-	-	-	-	-	-	-	-	-	-	-
Presque Isle	-	-	1	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Sault Ste. Marie	-	-	-	7	9	13	8	-	8	-	-	-	-	-	-	8	14	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
St. Ignace	-	-	-	-	3	4	7	-	2	-	-	-	-	-	-	-	10	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
TACONITE TC	-	-	6	7	12	17	16	-	11	-	-	-	10	-	-	8	24	-	-	-	-	-	11	9	10	12	-	-	-	-	-	-	-	-	-	-	-
Esplanaba	-	-	-	4	15	4	13	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Green Bay	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Milwaukee	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Chicago	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Grand Haven	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
OIL CAN TC	-	-	-	4	15	4	13	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Saginaw	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Port Huron	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Detroit	-	-	-	5	6	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Toledo	-	-	-	6	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Sandusky	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Cleveland	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Buffalo	-	-	-	7	11	1	-	-	-	-	-	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
COAL SHOVEL TC	-	-	-	19	21	3	-	-	-	-	-	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Port Colborne	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Toronto	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
WELLAND TC	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Oswego	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Alexandria Bay	-	-	-	-	3	4	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
SEAWAY TC	-	-	-	-	3	4	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Montreal	-	-	-	-	2	4	-	-	-	-	-	-	-	-	-	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Quebec	-	3	4	5	3	2	3	2	4	-	-	-	4	3	5	-	-	-	-	-	-	-	-	-	6	5	15	11	-	-	-	-	-	-	-	-	-
QUEBEC TC	-	3	4	5	5	6	3	2	4	-	-	-	4	3	5	2	-	-	-	-	-	-	-	-	6	5	15	11	-	-	-	-	-	-	-	-	-
U.S.	-	-	6	30	51	28	30	2	11	-	-	-	10	5	-	8	24	-	-	-	-	-	-	11	9	10	12	-	-	-	-	-	-	-	-	-	-

TABLE 6.27c

RESULTS OF RUN NO. 6

FOR TACONITE TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	6-9%	7-44%	12-48%	17-38%	16-44%	-	11-37%
Class C	-	-	-	10-13%	-	-	8-54%	24-44%	-
Class B	-	-	-	-	11-11%	9-13%	10-9%	12-10%	-
TOTAL	-	-	6-9%	17-26%	23-31%	26-29%	34-36%	36-33%	11-37%
<u>Direct Assists</u>									
by Class D	-	-	35	83	117	123	79	-	91
by Class C	-	-	-	132	-	-	74	190	-
by Class B	-	-	-	-	137	135	100	126	-
TOTAL	-	-	35	215	254	258	253	316	91
Total Time (hr)	-	-	181	1470	2364	2554	4123	3935	1431
Total Miles	-	-	1379	7610	12427	12535	16628	20611	8446
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	1	2	2	1	2	2	1
St. Marys R. Convoy	-	-	-	-	-	-	-	-	-
Straits Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.27d
RESULTS OF RUN NO. 6
FOR OIL CAN TASK COMMAND

ITEM	2	3	4	5	Period					
					6	7	8	9	10	
<u>Number of Icebreakers¹</u>										
Class D	-	-	-	4-10%	15-17%	4-10%	13-17%	2-8%	-	-
Class C	-	-	-	-	-	-	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	4-10%	15-17%	4-10%	13-17%	2-8%	-	-
<u>Direct Assists</u>										
by Class D	-	-	-	8	35	6	28	8	-	-
by Class C	-	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	8	35	6	28	8	-	-
Total Time (hr)	-	-	-	129	832	128	730	53	-	-
Total Miles	-	-	-	1129	8320	1164	6811	537	-	-
<u>Convoys Escorted</u>										
by Class D	-	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues</u>										
Direct Assistance	-	-	-	1	3	1	2	0	-	-

NOTE: 1. Second number is average percent time utilized.

TABLE 6.27e
RESULTS OF RUN NO. 6
FOR COAL SHOVEL TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	19-21%	21-30%	3-10%	-	-	-
Class C	-	-	-	-	5-29%	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	19-21%	26-29%	3-10%	-	-	-
<u>Direct Assists</u>									
by Class D	-	-	-	65	79	8	-	-	-
by Class C	-	-	-	-	41	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	65	120	8	-	-	-
Total Time (hr)	-	-	-	1350	2568	97	-	-	-
Total Miles	-	-	-	7961	11242	554	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	1	2	0	-	-	-
Detroit/St. Clair	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.27f
RESULTS OF RUN NO. 6
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	Period					
					6	7	8	9	10	
<u>Number of Icebreakers¹</u>										
Class D	-	-	-	-	3-23%	4-12%	1-43%	-	-	-
Class C	-	-	-	-	-	-	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	3-23%	4-12%	1-43%	-	-	-
<u>Direct Assists</u>										
by Class D	-	-	-	-	6	6	4	-	-	-
by Class C	-	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	6	6	4	-	-	-
Total Time (hr)	-	-	-	-	229	158	143	-	-	-
Total Miles	-	-	-	-	1305	1160	1015	-	-	-
<u>Convoys Escorted</u>										
by Class D	-	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>										
Direct Assistance	-	-	-	-	0	1	0	-	-	-
St. Lawrence Seaway	-	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting; while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.27g
EXTENDED SEASON TONNAGE
BY ROUTE FOR RUN NO. 6

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>
1	647	22	649	44	1081	74	-
2	1027	23	875	45	1089	75	-
3	572	24	1026	46	1092	76	-
4	162	26	601	47	448	77	652
5	873	27	438	48	2879	78	1350
6	876	28	605	49	1040	80	50
8	1408	29	1044	51	1190	81	99
9	1484	30	1443	53	190	83	-
10	878	32	559	54	978	85	50
11	1000	33	878	56	121	TOTAL	2201
12	1731	34	613	57	100		
13	1660	35	497	58	226		
14	878	37	1035	59	224		
15	605	38	915	60	597		
17	1191	39	999	61	1942		
19	881	41	641	63	155		
20	476	42	934	64	293		
21	283	TOTAL	30394	65	221	GENERAL CARGO-SALTY	
				66	1357	<u>Route</u>	<u>Tons</u>
				68	201		
				69	201	87	430
				70	439		
				71	606		
				72	2531		
				TOTAL	19201		

BULK CARGO-SALTY

<u>Route</u>	<u>Tons</u>
88	6265
89	2644
90	708
91	330
92	443
93	602
TOTAL	10992

GRAND TOTAL 63198

Maximum Number of Vessels:

Lakers: 153
Salty General Cargo: 26
Salty Bulk: 100

- NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.28a
SUMMARY OF INPUT CONDITIONS
FOR RUN NO. 7

Winter Type: Severe	Minimum Laker Class: 5
Run Mode: Maximum Response Time	
USCG Estimated Fleet: N.A.	MRT (hr): Minimum + 12
Convoying Icebreaker Types: C,B	Channel Clearing (in/per): None
Cargo Tonnage (year): 2000	
Convoy Routes:	

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	4
St. Marys River/Whitefish Bay	50,51	5-10
Straits of Mackinac	53	5-10
Detroit/St. Clair River System	72,73	5-7
Welland Canal	89	5-7
U.S. St. Lawrence Seaway	95	5-8
Canadian St. Lawrence Seaway	96	5-8

Data Files Used: SPDSVL, SPDSVM, SPDSVH, SHIPPRO, EAGDMRT, RCH25V5, RCH1S, CLASS

Archived Output File Name: PR07A

TABLE 6.28b

PREDICTED ICEBREAKER FLEET BY HOME PORT AND PERIOD FOR RUN NO. 7

LOCATION	CLASS D										CLASS C										CLASS B															
	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10
THUNDER BAY TC	-	-	1	2	-	-	-	-	3	-	-	-	-	3	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Duluth	-	-	3	-	-	-	-	-	-	-	-	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	3	2	4	5
Presque Isle	-	-	-	-	-	27	13	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Sault Ste. Marie	-	-	-	4	-	-	1	-	-	-	-	4	6	7	8	8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	3	
St. Ignace	-	-	-	-	-	-	1	2	7	-	-	-	2	2	3	4	3	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
TACONITE TC	-	-	3	4	-	27	15	2	7	-	-	4	13	9	11	12	3	3	-	-	-	-	-	-	-	-	-	-	-	-	-	4	3	2	7	8
Escanaba	-	2	3	2	-	-	-	-	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	-	-	-
Green Bay	-	-	-	1	-	-	-	-	-	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Milwaukee	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Chicago	-	-	5	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Grand Haven	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
OIL CAN TC	-	2	8	3	1	-	-	-	-	-	-	-	-	-	3	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	-	-	-
Saginaw	-	-	-	30	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Port Huron	-	-	-	-	-	-	-	-	-	-	-	-	3	3	3	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Detroit	-	-	-	4	8	-	1	-	-	-	-	-	4	4	9	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Toledo	-	-	-	1	19	-	1	-	-	-	-	-	-	-	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Sandusky	-	2	1	3	5	2	-	-	-	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Cleveland	-	1	-	4	3	-	-	-	-	-	-	-	-	-	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Buffalo	-	-	1	-	1	14	3	1	-	-	-	-	-	-	19	-	4	-	-	-	-	-	-	-	-	-	-	-	-	-	4	5	5	2	-	
COAL SHOVEL TC	-	3	2	42	42	3	16	3	1	-	-	-	7	7	42	4	4	-	-	-	-	-	-	-	-	-	-	-	-	-	4	5	5	2	-	
Port Colborne	-	-	-	-	-	-	-	-	-	-	-	-	3	5	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	-	-	-
Toronto	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
WELLAND TC	-	-	-	-	-	-	-	-	-	-	-	-	3	5	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	-	-	-
Oswego	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Alexandria Bay	-	-	1	1	-	-	1	-	-	-	-	-	5	11	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	2	-	-
SEAWAY TC	-	-	1	1	-	-	1	-	-	-	-	-	5	11	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	2	-	-
Montreal	-	1	-	-	-	-	-	-	2	-	-	-	7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	6	6	5	2	-
Quebec	-	3	4	5	5	2	3	7	-	-	-	-	-	-	3	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1	3	1	-	-
QUEBEC TC	-	3	5	5	5	2	3	7	2	-	-	-	7	-	3	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	7	9	6	2	-
U.S.	-	5	14	50	43	30	32	5	8	-	-	4	25	30	56	16	7	3	-	-	-	-	-	-	-	-	-	-	-	-	4	9	16	6	7	8

TABLE 6.28c

RESULTS OF RUN NO. 7

FOR TACONITE TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	3-24%	4-10%	-	27-34%	15-9%	2-19%	7-10%
Class C	-	-	4-89%	13-66%	9-86%	11-82%	12-70%	3-57%	3-54%
Class B	-	-	-	-	4-44%	3-55%	2-87%	7-55%	8-52%
TOTAL	-	-	7-61%	17-53%	13-73%	41-49%	29-40%	12-50%	18-36%
<u>Direct Assists</u>									
by Class D	-	-	40	10	-	57	32	19	34
by Class C	-	-	-	120	4	28	13	5	-
by Class B	-	-	-	-	148	127	130	132	133
TOTAL	-	-	40	130	152	212	175	156	167
Total Time (hr)	-	-	241	1102	658	3914	1196	788	821
Total Miles	-	-	955	3966	3825	19073	7681	4174	4234
<u>Convoys Escorted</u>									
by Class D	-	-	146	146	177	158	129	38	42
by Class C	-	-	-	-	-	-	-	46	55
by Class B	-	-	146	146	177	158	129	84	97
TOTAL	-	-	1188	1914	2522	2786	2680	1212	1349
Total Time (hr)	-	-	9292	16060	18276	17024	14442	8608	9899
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	1	4	5	0	1
St. Marys R. Convoy	-	-	31/2	20/19	17/24	14/18	15/12	15/14	17/13
Straits Convoy	-	-	-	5/6	3/6	5/6	4/5	2/4	3/4

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.28d
RESULTS OF RUN NO. /
FOR OIL CAN TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	2-11%	8-11%	3-23%	1-24%	-	-	-	-
Class C	-	-	-	-	3-34%	3-15%	-	-	-
Class B	-	-	-	-	-	4-13%	-	-	-
TOTAL	-	2-11%	8-11%	3-23%	4-32%	7-14%	-	-	-
<u>Direct Assists</u>									
by Class D	-	9	21	12	3	-	-	-	-
by Class C	-	-	-	-	29	6	-	-	-
by Class B	-	-	-	-	-	22	-	-	-
TOTAL	-	9	21	12	32	28	-	-	-
Total Time (hr)	-	77	286	230	427	320	-	-	-
Total Miles	-	312	2263	1123	1376	2160	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues</u>									
Direct Assistance	-	0	1	0	0	1	-	-	-

NOTE: 1. Second number is average percent time utilized.

TABLE 6.28e

RESULTS OF RUN NO. 7

FOR COAL SHOVEL TASK COMMAND

ITEM	Period									
	2	3	4	5	6	7	8	9	10	
Number of Icebreakers ¹										
Class D	-	3-10%	2-29%	42-35%	42-36%	3-78%	16-21%	3-13%	1-4%	
Class C	-	-	-	7-58%	7-80%	42-44%	4-12%	4-7%	-	
Class B	-	-	-	4-36%	5-58%	5-38%	2-24%	-	-	
TOTAL	-	3-10%	2-29%	52-38%	54-44%	50-45%	22-20%	7-9%	1-4%	
Direct Assists										
by Class D	-	10	20	99	117	7	24	3	4	
by Class C	-	-	-	4	2	120	-	22	-	
by Class B	-	-	-	42	46	27	26	-	-	
TOTAL	-	10	20	145	165	154	50	25	4	
Total Time (hr)	-	99	192	5479	6143	5629	1317	220	13	
Total Miles	-	731	702	26597	31507	26817	6342	1284	60	
Convoys Escorted										
by Class D	-	-	-	-	-	-	-	-	-	
by Class C	-	-	-	101	126	111	9	-	-	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	101	126	111	9	-	-	
Total Time (hr)	-	-	-	1277	1791	1934	143	-	-	
Total Miles	-	-	-	10283	13467	13377	1121	-	-	
Avg. Size of Queues ²										
Direct Assistance	-	0	0	5	4	5	2	1	0	
Detroit/St. Clair Convoy	-	-	-	15/14	15/15	12/15	-	-	-	

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established at ETA at convoy points and in general are not waiting.

TABLE 6.28f

RESULTS OF RUN NO. 7
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	1-25%	1-32%	-	-	1-28%	-	-
Class C	-	-	-	5-84%	11-71%	-	-	-	-
Class B	-	-	-	-	-	4-71%	2-82%	-	-
TOTAL	-	-	1-25%	6-75%	11-71%	4-71%	3-64%	-	-
<u>Direct Assists</u>									
by Class D	-	-	2	4	-	-	7	-	-
by Class C	-	-	-	-	12	-	-	-	-
by Class B	-	-	-	-	-	15	-	-	-
TOTAL	-	-	2	4	12	15	7	-	-
Total Time (hr)	-	-	83	106	224	175	94	-	-
Total Miles	-	-	519	458	972	1104	408	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	47	54	-	-	-	-
by Class B	-	-	-	-	-	31	22	-	-
TOTAL	-	-	-	47	54	31	22	-	-
Total Time (hr)	-	-	-	1403	2415	920	549	-	-
Total Miles	-	-	-	9570	11115	7780	5220	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	1	1	0	-	-
St. Lawrence Seaway	-	-	-	2/4	3/4	1/3	0/1	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.
 2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.28g
EXTENDED SEASON TONNAGE
BY ROUTE FOR RUN NO. 7

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
Route	Tons	Route	Tons	Route	Tons	Route	Tons
1	647	22	649	44	1069	74	-
2	1022	23	874	45	1088	75	-
3	569	24	1022	46	1090	76	-
4	159	26	603	47	450	77	640
5	874	27	437	48	2861	78	1376
6	874	28	606	49	1039	80	50
8	1403	29	1041	51	1186	81	101
9	1428	30	1440	53	181	83	-
10	875	32	542	54	978	85	50
11	994	33	870	56	121	TOTAL	2217
12	1706	34	612	57	100		
13	1640	35	490	58	226		
14	863	37	1034	59	224		
15	592	38	913	60	594		
17	1155	39	996	61	1939		
19	872	41	630	63	155		
20	473	42	938	64	293		
21	283	TOTAL	30126	65	221	GENERAL CARGO-SALTY	
				66	1357		
				68	201	Route	Tons
				69	201	87	453
				70	434		
				71	607		
				72	2533		
				TOTAL	19148		
						BULK CARGO-SALTY	
						Route	Tons
						88	6214
						89	2638
						90	703
						91	332
						92	444
						93	602
						TOTAL	10933
						GRAND TOTAL	62877

Maximum Number of Vessels:
Lakers: 206
Salty General Cargo: 30
Salty Bulk: 130

NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.29a

Winter Type: Severe

Minimum Laker Class: 6

Run Mode: Maximum Response Time

USCG Estimated Fleet: N.A.

MRT (hr): Minimum + 12

Convoying Icebreaker Types: C,B

Channel Clearing (in/per): None

Cargo Tonnage (year): 2000 (Class 5 Laker tonnage assumed carried in normal season)

Convoy Routes:

Location

Reaches

Periods

St. Marys River

51

6-10

St. Marys River/Whitefish Bay

50,51

Straits of Mackinac53

7-10

Detroit/St. Clair River System

72,73NoneWelland Canal896-7

U.S. St. Lawrence Seaway

95

5-8

Canadian St. Lawrence Seaway

96

5-8

Data Files Used: SPDSVL, SPDSVM, SPDSVH, SHIPNC5, EAGDMRT,
RCH2SV6, RCH1S, CLASS

Archived Output File Name: PR08A

TABLE 6.29b

PREDICTED ICEBREAKER FLEET BY HOME PORT AND PERIOD FOR RUN NO. 8

LOCATION	CLASS D										CLASS C										CLASS B									
	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10			
THUNDER BAY TC	-	-	-	1	-	-	-	-	-	-	-	-	-	4	-	3	-	-	-	-	-	-	-	-	5	-	-			
Duluth	-	-	2	-	-	-	-	-	-	-	-	-	9	-	-	-	-	-	-	-	-	-	-	3	3	4	6	4		
Presque Isle	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Sault Ste. Marie	-	-	-	-	-	-	-	-	-	-	-	-	-	4	5	6	1	1	-	-	-	-	-	-	-	-	3	4		
St. Ignace	-	-	-	-	2	-	-	-	-	-	-	-	-	-	2	2	2	2	-	-	-	-	-	-	-	-	-			
TACONITE TC	-	-	2	-	2	-	-	-	-	-	-	-	9	4	7	8	3	3	-	-	-	-	-	3	3	4	9	8		
Esplanada	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Green Bay	-	-	-	-	1	-	-	-	-	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-	-			
Milwaukee	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Chicago	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Grand Haven	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
OIL CAN TC	-	-	-	-	1	1	-	-	-	-	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-			
Saginaw	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Port Huron	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	-	-	-	-	-	-	-	-	-	-	-	-			
Detroit	-	-	-	-	-	-	2	-	-	-	-	-	-	-	8	-	-	-	-	-	-	-	-	-	-	-	-			
Toledo	-	-	-	-	18	-	1	-	-	-	-	-	-	-	8	-	-	-	-	-	-	-	-	-	-	-	-			
Sandusky	-	-	-	-	-	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Cleveland	-	-	-	-	2	-	-	-	-	-	-	-	-	2	-	-	-	-	-	-	-	-	-	-	-	-	-			
Buffalo	-	-	1	-	-	-	8	-	-	-	-	-	-	-	25	-	3	-	-	-	-	-	-	4	4	5	2			
COAL SHOVEL TC	-	-	1	-	22	-	11	-	-	-	-	-	-	-	47	-	3	-	-	-	-	-	-	4	4	5	2			
Port Colborne	-	-	-	-	-	-	-	-	-	-	-	-	6	-	3	-	-	-	-	-	-	-	-	-	3	-	-			
Toronto	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
WELLAND TC	-	-	-	-	-	-	-	-	-	-	-	-	6	-	3	-	-	-	-	-	-	-	-	-	3	-	-			
Oswego	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
Alexandria Bay	-	-	-	-	-	-	2	-	-	-	-	-	4	8	-	-	1	-	-	-	-	-	-	-	-	5	3			
SEAWAY TC	-	-	-	-	-	-	2	-	-	-	-	-	4	9	-	-	1	-	-	-	-	-	-	-	-	5	3			
Montreal	-	-	-	-	-	-	-	-	-	-	-	-	7	-	-	-	-	-	-	-	-	-	-	-	5	4	2			
Quebec	-	-	-	-	-	-	5	-	-	-	-	-	2	2	5	-	-	-	-	-	-	-	-	-	-	3	-			
QUEBEC TC	-	-	-	-	-	-	5	-	-	-	-	-	7	2	2	5	-	-	-	-	-	-	-	-	-	5	8	4	2	
U.S.	-	-	3	-	25	1	13	-	-	-	-	-	13	12	57	8	7	3	-	-	-	-	-	4	7	13	9	9	8	

TABLE 6.29c

RESULTS OF RUN NO. 8

FOR TACONITE TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	2-8%	-	2-17%	-	-	-	-
Class C	-	-	-	9-21%	4-71%	7-79%	8-68%	3-48%	3-55%
Class B	-	-	-	-	3-41%	3-39%	4-29%	9-37%	8-48%
TOTAL	-	-	2-8%	9-21%	9-49%	10-67%	12-55%	12-39%	11-50%
<u>Direct Assists</u>									
by Class D	-	-	9	-	11	-	-	-	-
by Class C	-	-	-	89	-	1	17	12	22
by Class B	-	-	-	-	104	93	94	104	115
TOTAL	-	-	9	89	115	94	111	116	137
Total Time (hr)	-	-	56	639	524	403	599	577	757
Total Miles	0	0	225	1861	2700	2071	2778	2923	4255
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	154	113	29	31
by Class C	-	-	-	-	99	-	-	78	83
by Class B	-	-	-	-	-	154	113	107	114
TOTAL	-	-	-	-	99	1833	1613	1009	1098
Total Time (hr)	-	-	-	-	958	9660	7580	6922	7898
Total Miles	-	-	-	-	6026	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	0	0	1	1	2
St. Marys R. Convoy	-	-	-	-	18/4	18/2	12/1	12/0	15/1
Straits Convoy	-	-	-	-	-	4/4	3/3	2/1	4/3

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.29d

RESULTS OF RUN NO. 8

FOR OIL CAN TASK COMMAND

ITEM	Period									
	2	3	4	5	6	7	8	9	10	
Number of Icebreakers ¹										
Class D	-	-	-	-	1-24%	1-7%	-	-	-	
Class C	-	-	-	-	-	3-15%	-	-	-	
Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	-	1-24%	4-13%	-	-	-	
Direct Assists										
by Class D	-	-	-	-	3	2	-	-	-	
by Class C	-	-	-	-	-	6	-	-	-	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	-	3	8	-	-	-	
Total Time (hr)	-	-	-	-	82	169	-	-	-	
Total Miles	-	-	-	-	320	792	-	-	-	
Convoys Escorted										
by Class D	-	-	-	-	-	-	-	-	-	
by Class C	-	-	-	-	-	-	-	-	-	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	-	-	-	-	-	-	
Total Time (hr)	-	-	-	-	-	-	-	-	-	
Total Miles	-	-	-	-	-	-	-	-	-	
Avg. Size of Queues										
Direct Assistance	-	-	-	-	0	0	-	-	-	

NOTE: 1. Second number is average percent time utilized.

TABLE 6.29e

RESULTS OF RUN NO. 8
FOR COAL SHOVEL TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	1-25%	-	22-20%	-	11-15%	-	-
Class C	-	-	-	-	-	47-27%	-	3-6%	-
Class B	-	-	-	4-11%	4-47%	5-29%	2-18%	-	-
TOTAL	-	-	1-25%	4-11%	26-24%	52-27%	13-16%	3-6%	-
<u>Direct Assists</u>									
by Class D	-	-	11	-	43	-	11	-	-
by Class C	-	-	-	-	-	138	-	18	-
by Class B	-	-	-	33	37	22	24	-	-
TOTAL	-	-	11	33	80	160	35	18	-
Total Time (hr)	-	-	83	152	2119	4752	701	64	-
Total Miles	-	-	172	926	11069	22080	3372	270	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	2	5	1	0	-
Detroit/St. Clair	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.29f

RESULTS OF RUN NO. 8
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	2-4%	-	-
Class C	-	-	-	-	-	-	-	1-5%	-
Class B	-	-	-	-	-	5-76%	3-50%	-	-
TOTAL	-	-	-	-	-	5-76%	5-32%	1-5%	-
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	2	-	-
by Class C	-	-	-	-	-	15	-	-	-
by Class B	-	-	-	-	-	15	-	-	-
TOTAL	-	-	-	-	-	188	29	-	-
Total Time (hr)	-	-	-	-	-	1236	120	-	-
Total Miles	-	-	-	-	-	456	4785	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	1	-
by Class C	-	-	-	-	-	43	21	-	-
by Class B	-	-	-	-	-	43	21	1	-
TOTAL	-	-	-	-	-	1183	504	33	-
Total Time (hr)	-	-	-	-	-	10535	4785	290	-
Total Miles	-	-	-	-	-	10820	4785	290	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	-	-	0	0	-	-
St. Lawrence Seaway	-	-	-	-	-	0/6	0/4	-	-
Convoy	-	-	-	-	-	0/6	0/4	-	-

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.29g
EXTENDED SEASON TONNAGE
BY ROUTE FOR RUN NO.8

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>
1	489	22	490	44	1070	74	-
2	794	23	673	45	1088	75	-
3	435	24	791	46	1088	76	-
4	-	26	460	47	450	77	641
5	672	27	314	48	2749	78	1029
6	673	28	463	49	1038	80	50
8	1063	29	790	51	1186	81	100
9	1077	30	1102	53	182	83	-
10	673	32	399	54	978	85	50
11	766	33	676	56	121	TOTAL	1870
12	1321	34	471	57	100		
13	1251	35	364	58	226		
14	675	37	782	59	224		
15	450	38	701	60	594		
17	861	39	765	61	1864		
19	662	41	486	63	155		
20	368	42	700	64	291	GENERAL CARGO-SALTY	
21	144	TOTAL	22801	65	221	<u>Route</u>	<u>Tons</u>
				66	1310	87	450
				68	201		
				69	201		
				70	430		
				71	607		
				72	2424		
				TOTAL	18798		
						BULK CARGO-SALTY	
						<u>Route</u>	<u>Tons</u>
						88	6224
						89	2621
						90	703
						91	331
						92	445
						93	604
						TOTAL	10928
						GRAND TOTAL	54847

Maximum Number of Vessels:

Lakers: 142

Salty General Cargo: 29

Salty Bulk: 119

NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.30a

Winter Type: Severe

Minimum Laker Class: 6

Run Mode: Maximum Response Time

USCG Estimated Fleet: N.A.

MRT (hr): Minimum + 12

Convoying Icebreaker Types: C,B

Channel Clearing (in/per)*: 12

Cargo Tonnage (year): 2000 (Class 5 laker tonnage assumed carried in normal season)

Convoy Routes:

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	6-10
St. Marys River/Whitefish Bay	50,51	-
Straits of Mackinac	53	7-10
Detroit/St. Clair River System	72,73	None
Welland Canal	89	6-7
U.S. St. Lawrence Seaway	95	5-8
Canadian St. Lawrence Seaway	96	5-8

Data Files Used: SPDSVLC, SPDSVMC, SPDSVHC, SHIPNC5, EAGDMRT, RC25V6C, RCH1S, CLASS

Archived Output File Name: PR09A

* Channel clearing was in the following reaches: 50, 51, 53, 72, 73, 74, 76, 89, 95, 96 periods 2 through 10.

TABLE 6.30b

PREDICTED ICEBREAKER FLEET BY HOME PORT AND PERIOD FOR RUN NO. 9

LOCATION	CLASS D										CLASS C										CLASS B																
	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	2	3	4	5	6	7	8	9	10	
THUNDER BAY TC	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Duluth	-	-	3	-	-	-	-	-	-	-	-	-	9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2	3	2	3	2		
Presque Isle	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Sault Ste. Marie	-	-	-	-	-	-	-	-	-	-	-	-	-	3	4	3	3	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
St. Ignace	-	-	-	-	-	-	-	-	-	-	-	-	-	-	2	2	1	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
TACONITE TC	-	-	3	-	-	-	-	-	-	-	-	-	9	3	6	5	4	3	-	-	-	-	-	-	-	-	-	-	-	-	2	3	2	3	2		
Escanaba	-	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Green Bay	-	-	-	-	1	1	-	-	-	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Milwaukee	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Chicago	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Grand Haven	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
OIL CAN TC	-	-	-	-	1	1	1	-	-	-	-	-	-	-	-	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Saginaw	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Port Huron	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Detroit	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Toledo	-	-	-	-	20	-	2	-	-	-	-	-	-	-	20	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Sandusky	-	-	-	-	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Cleveland	-	-	-	-	1	-	-	-	-	-	-	-	-	-	-	2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	4	6	3		
Buffalo	-	-	2	-	-	-	7	-	-	-	-	-	-	-	-	25	-	2	-	-	-	-	-	-	-	-	-	-	-	-	4	4	6	3	-		
COAL SHOVEL TC	-	-	2	-	23	-	9	-	-	-	-	-	-	-	-	47	-	2	-	-	-	-	-	-	-	-	-	-	-	-	4	4	6	3	-		
Port Colborne	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	5	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Toronto	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
WELLAND TC	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	5	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Oswego	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Alexandria Bay	-	-	-	-	-	-	-	-	-	-	-	-	-	4	5	1	3	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	-	-		
SEAWAY TC	-	-	-	-	-	-	-	-	-	-	-	-	-	4	5	1	3	1	-	-	-	-	-	-	-	-	-	-	-	-	-	-	3	-	-		
Montreal	-	-	-	-	-	-	-	-	-	-	-	-	5	4	4	4	4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Quebec	-	-	-	-	-	-	-	5	-	-	-	-	-	-	-	5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	6	3	-		
QUEBEC TC	-	-	-	-	-	-	-	5	-	-	-	-	5	4	4	9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	4	6	3	-		
U.S.	-	-	5	-	24	1	10	-	-	-	-	-	13	8	57	8	7	3	-	-	-	-	-	-	-	-	-	-	-	-	-	4	6	12	5	3	2

TABLE 6.30c

RESULTS OF RUN NO. 9

FOR TACONITE TASK COMMAND

ITEM	2	3	4	5	Period					
<u>Number of Icebreakers¹</u>										
Class D	-	-	3-17%	-	-	-	-	-	-	-
Class C	-	-	-	9-23%	3-89%	6-62%	5-60%	4-73%	3-77%	
Class B	-	-	-	-	2-64%	3-40%	2-59%	3-39%	2-57%	
TOTAL	-	-	3-17%	9-23%	5-79%	9-55%	7-60%	7-59%	5-69%	
<u>Direct Assists</u>										
by Class D	-	-	9	-	-	-	-	-	-	
by Class C	-	-	-	96	-	-	-	-	-	
by Class B	-	-	-	-	102	96	92	88	89	
TOTAL	-	-	9	96	102	96	92	88	89	
Total Time (hr)	-	-	56	682	430	401	393	397	383	
Total Miles	-	-	225	1956	2760	2072	2147	2136	2204	
<u>Convoys Escorted</u>										
by Class D	-	-	-	-	-	-	-	-	-	
by Class C	-	-	-	-	111	168	133	126	115	
by Class B	-	-	-	-	-	-	-	-	-	
TOTAL	-	-	-	-	111	168	133	126	115	
Total Time (hr)	-	-	-	-	891	1252	1007	978	775	
Total Miles	-	-	-	-	6946	10304	8694	8234	6578	
<u>Avg. Size of Queues²</u>										
Direct Assistance	-	-	0	0	0	0	2	0	0	
St. Marys R. Convoy	-	-	-	-	19/1	15/1	10/0	11/0	12/2	
Straits Convoy	-	-	-	-	-	4/4	2/3	1/1	3/2	

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.30d
RESULTS OF RUN NO. 9
FOR OIL CAN TASK COMMAND

ITEM	2	3	4	5	Period					
<u>Number of Icebreakers¹</u>										
Class D	-	-	-	-	1-19%	1-7%	1-10%	-	-	-
Class C	-	-	-	-	-	3-15%	-	-	-	-
Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	1-19%	4-13%	1-10%	-	-	-
<u>Direct Assists</u>										
by Class D	-	-	-	-	2	2	1	-	-	-
by Class C	-	-	-	-	-	6	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	2	8	1	-	-	-
Total Time (hr)	-	-	-	-	59	169	32	-	-	-
Total Miles	-	-	-	-	240	792	160	-	-	-
<u>Convoys Escorted</u>										
by Class D	-	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues</u>										
Direct Assistance	-	-	-	-	0	0	0	-	-	-

NOTE: 1. Second number is average percent time utilized.

TABLE 6.30e

RESULTS OF RUN NO. 9

FOR COAL SHOVEL TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	2-12%	-	23-20%	47-22%	9-16%	-	-
Class C	-	-	-	-	-	6-24%	-	2-19%	-
Class B	-	-	-	4-13%	4-43%	53-22%	3-12%	-	-
TOTAL	-	-	2-12%	4-13%	27-23%		12-17%	2-19%	-
<u>Direct Assists</u>									
by Class D	-	-	11	-	44	-	10	-	-
by Class C	-	-	-	-	-	90	-	18	-
by Class B	-	-	-	36	34	24	25	-	-
TOTAL	-	-	11	36	78	114	35	18	-
Total Time (hr)	-	-	83	169	2092	3971	667	64	-
Total Miles	-	-	172	1036	10733	18073	3100	270	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	2	4	2	0	-
Detroit/St. Clair	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.30f
RESULTS OF RUN NO. 9
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	-	-	-	-	-	1-98%	3-63%	1-5%	-
Class B	-	-	-	-	-	3-27%	-	-	-
TOTAL	-	-	-	4-85%	5-86%	4-86%	3-63%	1-5%	-
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	10	-	-	-	-
by Class B	-	-	-	-	-	9	-	-	-
TOTAL	-	-	-	-	10	9	-	-	-
Total Time (hr)	-	-	-	-	181	102	-	-	-
Total Miles	-	-	-	-	1056	636	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	52	57	11	25	1	-
by Class B	-	-	-	-	-	31	-	-	-
TOTAL	-	-	-	52	57	42	25	1	-
Total Time (hr)	-	-	-	1147	1256	1050	653	17	-
Total Miles	-	-	-	10730	11665	10040	6235	145	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	0	0	0	-	-	-
St. Lawrence Seaway	-	-	-	3/5	2/5	1/4	1/1	-	-

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.30g

EXTENDED SEASON TONNAGE

BY ROUTE FOR RUN NO. 9

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>
1	490	22	489	44	1080	74	-
2	794	23	673	45	1090	75	-
3	434	24	792	46	1090	76	-
4	-	26	458	47	448	77	651
5	671	27	315	48	2763	78	1036
6	673	28	462	49	1038	80	50
8	1069	29	789	51	1186	81	99
9	1111	30	1109	53	181	83	-
10	673	32	413	54	978	85	50
11	765	33	673	56	121	TOTAL	1886
12	1320	34	472	57	100		
13	1248	35	369	58	226		
14	673	37	782	59	224		
15	461	38	703	60	594		
17	890	39	766	61	1864		
19	672	41	483	63	155		
20	369	42	697	64	293		
21	144	TOTAL	22902	65	221	GENERAL CARGO-	
				66	1310	SALTY	
				68	201	<u>Route</u>	<u>Tons</u>
				69	201	87	443
				70	428		
				71	607		
				72	2424		
				TOTAL	18823		

BULK CARGO-SALTY

<u>Route</u>	<u>Tons</u>
88	6250
89	2641
90	710
91	330
92	444
93	603
TOTAL	10978
TOTAL	55032

GRAND TOTAL

Maximum Number of Vessels:

Lakers: 130
Salty General Cargo: 28
Salty Bulk: 114

NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

TABLE 6.31a
SUMMARY OF INPUT CONDITIONS
FOR RUN NO. 10

Winter Type: Severe

Minimum Laker Class: 6

Run Mode: Fixed Icebreaker Fleet

USCG Estimated Fleet: Severe

MRT (hr): N.A.

Convoying Icebreaker Types: C,B

Channel Clearing (in/per): None

Cargo Tonnage (year): 2000 (Class 5 laker tonnage assumed carried in normal season)

Convoy Routes:

<u>Location</u>	<u>Reaches</u>	<u>Periods</u>
St. Marys River	51	6-10
St. Marys River/Whitefish Bay	50,51	-
Straits of Mackinac	53	7-10
Detroit/St. Clair River System	72,73	None
Welland Canal	89	6-7
U.S. St. Lawrence Seaway	95	5-8
Canadian St. Lawrence Seaway	96	5-8

Data Files Used: SPDSVL, SPDSVM, SPDSVH, SHSVNC5, EAGDFIB,
RCH2SV6, RCH1S, CLASS

Archived Output File Name: PR010

TABLE 6.31b
USCG ESTIMATED FLEET* FOR SEVERE WINTER
FOR RUN NO. 10

<u>Home Port</u>	<u>Class B</u>	<u>Class C</u>	<u>Class D</u>
Duluth	1	2	-
Sault Ste. Marie	3	6	-
St. Ignace	3	6	-
Port Huron, Detroit, Toledo	1	4	-
Escanaba	-	1	-
Chicago	1	2	-
Saginaw	2	3	-
Sandusky	1	2	-
Buffalo	1	4	-
Oswego	-	3	-
SUBTOTAL	12	29	2
TOTAL		43	

NOTE: Principal ports; operations limited to vessels of reasonably high capability (SHP/L > 6); 12 hrs per day per icebreaker.

* Letter dated 8 June 1977 from Commander, Ninth Coast Guard District to the Commandant (G-0).

TABLE 6.31c
RESULTS OF RUN NO. 10
FOR TACONITE TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	2-0%	2-0%	2-0%	2-0%	2-15%	2-0%	2-68%	2-8%	2-0%
Class C	10-0%	10-0%	10-1%	10-9%	10-55%	10-64%	10-73%	10-56%	10-99%
Class B	6-0%	6-0%	6-0%	6-29%	6-102%	6-98%	6-103%	6-96%	6-10%
TOTAL	18-0%	18-0%	18-1%	18-15%	18-66%	18-6%	18-82%	18-64%	18-88%
<u>Direct Assists</u>									
by Class D	-	-	-	-	10	-	10	-	-
by Class C	-	-	7	41	-	-	5	14	56
by Class B	-	-	2	48	101	89	89	83	104
TOTAL	-	-	9	89	111	89	104	99	160
Total Time (hr)	-	-	40	894	1350	1007	1691	1378	2360
Total Miles	-	-	225	9096	16168	11547	16115	14096	18581
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	129	-	114	37	41
by Class C	-	-	-	-	27	29	26	42	50
by Class B	-	-	-	-	156	155	140	79	91
TOTAL	-	-	-	-	2641	3089	3284	2488	2976
Total Time (hr)	-	-	-	-	26713	27742	28046	19018	20204
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	1	3	2	3	5
St. Marys R. Convoy	-	-	-	-	11/0	12/0	9/0	16/3	19/3
Straits Convoy	-	-	-	-	-	2/2	2/2	3/2	1/1

NOTES: 1. Second number is average percent time utilized.
2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues indicate vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.31d
RESULTS OF RUN NO. 10
FOR OIL CAN TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	3-0%	3-0%	3-0%	3-0%	3-8%	3-24%	3-0%	3-0%	3-0%
Class B	1-0%	1-0%	1-0%	1-0%	1-0%	1-12%	1-0%	1-0%	1-0%
TOTAL	4-0%	4-0%	4-0%	4-0%	4-6%	4-21%	4-0%	4-0%	4-0%
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	3	7	-	-	-
by Class B	-	-	-	-	-	1	-	-	-
TOTAL	-	-	-	-	3	8	-	-	-
Total Time (hr)	-	-	-	-	85	284	-	-	-
Total Miles	-	-	-	-	544	2698	-	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues</u>									
Direct Assistance	-	-	-	-	0	0	-	-	-

NOTE: 1. Second number is average percent time utilized.

TABLE 6.31e

RESULTS OF RUN NO. 10

FOR COAL SHOVEL TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	12-	12-	12-1%	12-0%	12-23%	12-84%	12-6%	12-0%	12-0%
Class B	5-	5-	5-0%	5-16%	5-82%	5-91%	5-25%	5-1%	5-0%
TOTAL	17-	17-	17-1%	17-5%	17-40%	17-86%	17-12%	17-0%	17-0%
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	6	-	31	101	3	-	-
by Class B	-	-	5	33	50	62	25	-	-
TOTAL	-	-	11	33	81	163	28	-	-
Total Time (hr)	-	-	39	272	2300	4914	671	-	-
Total Miles	-	-	132	2696	19080	34174	6888	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	-	-	-	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	-	-	-	-	-
Total Time (hr)	-	-	-	-	-	-	-	-	-
Total Miles	-	-	-	-	-	-	-	-	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	0	0	0	0	0	-	-
Detroit/St. Clair	-	-	-	-	-	-	-	-	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.31f
RESULTS OF RUN NO. 10
FOR SEAWAY TASK COMMAND

ITEM	2	3	4	5	6	7	8	9	10
<u>Number of Icebreakers¹</u>									
Class D	-	-	-	-	-	-	-	-	-
Class C	3-0%	3-0%	3-0%	3-108%	3-99%	3-112%	3-99%	3-33%	3-0%
Class B	-	-	-	-	-	-	-	-	-
TOTAL	3-0%	3-0%	3-0%	3-108%	3-99%	3-112%	3-99%	3-33%	3-0%
<u>Direct Assists</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	-	3	4	7	-	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	-	3	4	7	-	-
Total Time (hr)	-	-	-	-	77	117	125	-	-
Total Miles	-	-	-	-	360	312	600	-	-
<u>Convoys Escorted</u>									
by Class D	-	-	-	-	-	-	-	-	-
by Class C	-	-	-	43	27	21	22	18	-
by Class B	-	-	-	-	-	-	-	-	-
TOTAL	-	-	-	43	27	21	22	18	-
Total Time (hr)	-	-	-	1089	919	1012	830	331	-
Total Miles	-	-	-	7227	3975	3135	3310	3022	-
<u>Avg. Size of Queues²</u>									
Direct Assistance	-	-	-	-	1	4	4	-	-
St. Lawrence Seaway	-	-	-	5/8	20/13	51/24	45/26	8/6	-
Convoy	-	-	-	-	-	-	-	-	-

NOTES: 1. Second number is average percent time utilized; values greater than 100% sometimes result because time for assists and convoys not completed during previous period are included.

2. First entry is upbound, second is downbound; DA Queues indicate vessels which are waiting, while Convoy Queues denote vessels which have established an ETA at convoy points and in general are not waiting.

TABLE 6.31g
EXTENDED SEASON TONNAGE
BY ROUTE FOR RUN NO. 10

IRON ORE-LAKER		IRON ORE-LAKER		COAL-LAKER		GRAIN-LAKER	
<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>	<u>Route</u>	<u>Tons</u>
1	489	22	490	44	1068	74	-
2	794	23	673	45	1072	75	-
3	434	24	792	46	1073	76	-
4	-	26	460	47	450	77	626
5	672	27	313	48	2691	78	1016
6	673	28	463	49	1040	80	50
8	1045	29	783	51	1176	81	100
9	1077	30	1063	53	182	83	-
10	675	32	399	54	978	85	50
11	765	33	664	56	121	TOTAL	1842
12	1320	34	464	57	100		
13	1253	35	364	58	226		
14	670	37	782	59	224		
15	449	38	701	60	595		
17	860	39	765	61	1812		
19	616	41	484	63	155		
20	369	42	698	64	291	GENERAL CARGO-SALTY	
21	144	TOTAL	22663	65	221	<u>Route</u>	<u>Tons</u>
				66	1310	87	473
				68	201		
				69	201		
				70	435		
				71	606		
				72	2424		
				TOTAL	18652		
						BULK CARGO-SALTY	
						<u>Route</u>	<u>Tons</u>
						88	6083
						89	2615
						90	703
						91	332
						92	446
						93	609
						TOTAL	10788
						GRAND TOTAL	54418

Maximum Number of Vessels:

Lakers: 140

Salty General Cargo: 29

Salty Bulk: 123

- NOTES: 1. Units are thousands of short tons.
2. Extended season consists of nine 14-day periods.

7. CONCLUSIONS

Based on the results and discussion of the ten (10) production runs presented in Section 7, the following conclusions were drawn:

1. Usefulness of the Simulation - Based on the validation presented in Section 6.2 and the experience and knowledge we have gained from working with the model, from conversations with ship operators, port officials, and personnel at Coast Guard, MarAd, Corps of Engineers, and the St. Lawrence Seaway Development Corporation, we believe the simulation, as developed, realistically models the Great Lakes-St. Lawrence Seaway System. As a result, it can be used as a valuable tool to aid in the planning process of the Coast Guard in establishing their future icebreaking requirements and alternate icebreaking plans and concepts of operation.
2. Normal and Severe Winter Icebreaker Fleets - Using the results of the simulation for the fixed icebreaker fleet runs and the generated icebreaker fleet runs, simulation estimated icebreaker fleets were prepared and are presented in Tables 7.1 and 7.2 along with the Coast Guard estimated fleet for normal and severe winters. In finalizing the simulation fleet, consideration was given to additional icebreaking demands, such as preventive icebreaking and channel maintenance. In comparing the results of the simulation to those of the Coast Guard it is interesting to note how closely they compared in number with some shifting in location.

The procedure used for development of the "simulation generated icebreaker fleet" was a subjective process in which we tried to weigh the results of the 10 simulation runs to come up with a fleet we could recommend to the Coast Guard as a starting point for further sensitivity studies of the icebreaker requirements as discussed in the recommendations. Specifically the rationale we used to generate the fleets tested in Tables 7.1 and 7.2 were as follows:

TACONITE: For the severe winter, based on the results of runs 8 and 10 and noting the time spent by icebreakers transiting Lake Superior, it was concluded that 2 Class B and 2 Class C icebreakers in Duluth/Superior, 2 Class B and 6 Class C icebreakers in Sault Ste. Marie and 1 Class B and 3 Class C icebreakers in St. Ignace could handle the projected traffic. Similarly for the normal winter based on the results of runs 1 and 3 and the time spent by icebreakers transiting Lake Superior, it was concluded that

TABLE 7.1

COMPARISON OF SIMULATION GENERATED
ICEBREAKER FLEET WITH COAST GUARD ESTIMATED FLEET
FOR NORMAL WINTER

Task Command & Home Port	U.S. COAST GUARD ESTIMATED ICEBREAKER FLEET				SIMULATION GENERATED ICEBREAKER FLEET			
	Icebreaker Class				Icebreaker Class			
	B	C	D	TOTAL	B	C	D	TOTAL
<u>Taconite Command</u>								
Duluth/Superior	-	2	-	2	2	-	-	2
Presque Isle	-	-	-	-	-	-	-	-
Sault Ste. Marie	2	4	-	6	1	5	-	6
St. Ignace	<u>1</u>	<u>1</u>	<u>-</u>	<u>2</u>	<u>-</u>	<u>2</u>	<u>-</u>	<u>2</u>
TOTAL	3	7	-	10	3	7	-	10
<u>Oil Can Command</u>								
Escanaba	-	1	-	1	-	2	-	2
Green Bay	-	-	-	-	-	-	-	-
Milwaukee	-	-	-	-	-	-	-	-
Chicago	-	1	-	1	-	-	-	-
Grand Haven	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>
TOTAL	-	2	-	2	-	2	-	2
<u>Coal Shovel Command</u>								
Saginaw	-	-	-	-	-	-	-	-
Port Huron/Detroit/ Toledo	1	2	-	3	-	5	-	5
Sandusky	-	1	-	1	-	-	-	-
Buffalo	<u>1</u>	<u>2</u>	<u>-</u>	<u>3</u>	<u>1</u>	<u>2</u>	<u>-</u>	<u>3</u>
TOTAL	2	5	-	7	1	7	-	8
<u>Seaway Command</u>								
Oswego	-	3	-	3	-	-	-	-
Alexandria Bay	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>4</u>	<u>-</u>	<u>4</u>
TOTAL	-	3	-	3	-	4	-	4
TOTAL	5	17	-	22	4	20	-	24

TABLE 7.2
COMPARISON OF SIMULATION GENERATED
ICEBREAKER FLEET WITH COAST GUARD ESTIMATED FLEET
FOR SEVERE WINTER

Task Command & Home Port	U.S. COAST GUARD ESTIMATED ICEBREAKER FLEET				SIMULATION GENERATED ICEBREAKER FLEET			
	Icebreaker Class				Icebreaker Class			
	B	C	D	TOTAL	B	C	D	TOTAL
<u>Taconite Command</u>								
Duluth/Superior	1	2	-	3	2	2	-	4
Presque Isle	-	-	-	-	-	-	-	-
Sault Ste. Marie	3	6	-	9	2	6	-	8
St. Ignace	<u>2</u>	<u>2</u>	<u>2</u>	<u>6</u>	<u>1</u>	<u>3</u>	<u>-</u>	<u>4</u>
TOTAL	6	10	2	18	5	11	-	16
<u>Oil Can Command</u>								
Escanaba	-	1	-	1	1	-	1	2
Green Bay	-	-	-	-	-	1	-	1
Milwaukee	-	-	-	-	-	-	-	-
Chicago	1	2	-	3	-	1	-	1
Grand Haven	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>
TOTAL	1	3	-	4	1	2	1	4
<u>Coal Shovel Command</u>								
Saginaw	2	3	-	5	-	-	-	-
Port Huron/Detroit/ Toledo	1	4	-	5	1	5	2	8
Sandusky	1	2	-	3	-	2	-	2
Buffalo	<u>1</u>	<u>4</u>	<u>-</u>	<u>5</u>	<u>3</u>	<u>5</u>	<u>-</u>	<u>8</u>
TOTAL	5	13	-	18	4	12	2	18
<u>Seaway Command</u>								
Oswego	-	3	-	3	-	-	-	-
Alexandria Bay	<u>-</u>	<u>-</u>	<u>-</u>	<u>-</u>	<u>1</u>	<u>3</u>	<u>-</u>	<u>4</u>
TOTAL	-	3	-	3	1	3	-	4
TOTAL	12	29	2	43	11	28	3	42

2 Class B icebreakers in Duluth/Superior, 1 Class B and 5 Class C icebreakers in Sault Ste. Marie, and 2 Class C icebreakers in St. Ignace could handle the projected traffic. In generating both of these fleets, it was assumed that icebreakers would be prohibited from traversing Lake Superior between Duluth/Superior and the Soo.

OIL CAN: For the severe winter, based on the results of runs 8 and 10, and, in particular, the magnitude of the icebreaker utilization, it was concluded that 1 Class B and 1 Class D icebreaker in Escanaba, 1 Class C icebreaker in Green Bay and 1 Class C icebreaker in Chicago could handle the projected traffic. In a similar manner, for the normal winter based on the results of runs 1 and 3 it was concluded that 2 Class C icebreakers in Escanaba could handle the projected traffic.

COAL SHOVEL: For the severe winter based on results of runs 8 and 10 and looking particularly at icebreaker utilization and the locations where assistance was needed within the command, it was concluded that 1 Class B, 5 Class C and 2 Class D icebreakers in the Detroit area, 2 Class C icebreakers in Sandusky and, 3 Class B and 5 Class C in Buffalo could handle the projected traffic. In a similar manner for the normal winter, it was concluded that 5 Class C icebreakers in the Detroit area and 1 Class B and 2 Class C icebreakers in Buffalo could handle the projected traffic.

SEAWAY: Based on the results of runs 8 and 10 for the severe winter and runs 1 and 3 for the normal winter, and looking particularly at icebreaker utilization, the location of direct assists and the number of convoys escorted, it was concluded that 1 Class B and 3 Class C icebreakers could handle the projected traffic in a severe winter and the 4 Class C icebreakers could handle the projected traffic in a normal winter.

3. Formation of New Task Command for Duluth/Superior - Icebreakers in the simulation for the fixed fleet mode continually traveled across Lake Superior to provide assistance in both Duluth/Superior and at the Soo since assistance was provided on a first come-first serve basis. As a result, a large amount of time was spent transiting Lake Superior compared to time spent either assisting or convoying. For example, in Run 1 for the normal winter, the fixed fleet of 7 Class C and 3 Class B icebreakers operated at 100% utilization performing 781 direct assists and escorting 629 convoys. Of the 100% utilization in periods 5, 6, and 7, only 10%, 20%, and 29% of the total direct assist miles and 20%, 58% and 44% of the total convoy miles were spent in actual assistance and convoying

for each period, respectively. In comparison, the somewhat larger MRT generated fleet, which was restricted to operating within assigned areas near the icebreaker's home port, averaged 61%, 74%, and 75% of total direct assistance miles and 74%, 70%, and 66% of total convoy miles performing actual direct assistance and convoying in periods 5, 6, and 7, respectively. Future runs should have a 200 mile limitation placed on the icebreaker's area of operation to prohibit transiting Lake Superior, thereby effectively making Duluth/Superior a separate task command.

4. Effect of Increased Tonnage - For the fixed normal winter icebreaker fleet, the designated icebreakers in Oil Can and Coal Shovel could handle the 20% increased tonnage above the projected year 2000 tonnage with no significant problems. For the Seaway, the 3 Class C icebreakers operated 100% utilization in periods 5 through 8 escorting 173 convoys between Alexandria Bay and Cornwall. Based on the MRT runs 2 and 3, 5 or 6 Class C icebreakers or 1 Class B plus 3 Class C icebreakers were probably required to escort all vessels in convoys at a reasonable icebreaker utilization rate. In Taconite, the fixed fleet operated at 100% utilization because a large portion of the time was spent by icebreakers transiting between Duluth/Superior and the Soo. Based on the MRT runs 2 and 3, in which icebreakers were restricted to operating within assigned areas near the icebreaker's home port, the specified fixed fleet of 7 Class C and 3 Class B icebreakers needs to be increased to 9 Class C and 4 Class B icebreakers with Duluth/Superior being treated as a separate task command.
5. Effect of Increased Maximum Response Time - For Taconite, Oil Can and Coal Shovel Task Commands, there appeared to be only a slight effect on the generated icebreaker fleet due to increasing the MRT by 12 hours. For the Seaway, the maximum number of required Class C icebreakers dropped from 6 to 5.
6. Effect of Convoying - For Oil Can and Coal Shovel, where there were no convoys, the effect of convoying was a change in the arrival of ships from other commands which altered the generated icebreaker fleet slightly. For the Seaway, the elimination of convoying reduced the icebreaker requirements significantly since salties, which were capable of proceeding on their own, were being forced to convoy, thereby requiring more icebreakers. In Taconite, elimination of convoying caused the generated icebreaker fleet to double in periods 5 through 10.
7. Effect of Winter Severity - As one would expect, the ice-breaking requirements increased with increasing winter

severity. In Taconite, the total number of direct assists increased from 792 to 1032 and the total number of convoys increased from 699 to 937, resulting in an increase of required icebreakers from an average of 11 to 20, with an increase in Class B icebreakers from an average of 4 to approximately 6. In Oil Can, the total number of direct assists increased from 86 to 102, but because the location of the problem reach was closer to the icebreaker home port of Escanaba, fewer icebreakers were required during the severe year. The reason for this seemingly contradictory trend is a result of the use of actual historical weather and ice data which is sometimes inconsistent. In Coal Shovel, the number of direct assists increased by almost 200% from 198 to 573 with 347 convoys being escorted during the severe winter. This resulted in the number of icebreakers being doubled with an average of 4 Class B icebreakers being required during the severe winter while none were required during the normal winter. For the Seaway, the total number of direct assists increased from zero in the normal winter to 40 in the severe winter, but the total number of convoys decreased from 185 to 154. This reduction was due to Class B icebreakers being generated instead of Class C icebreakers (Class B icebreakers can handle twice as many ships per convoy as can Class C icebreakers). For the normal winter, between 3 and 5 Class C icebreakers were required while for the severe winter the icebreaker fleet ranged from 1 Class D and 4 Class C icebreakers to 4 Class B icebreakers.

8. Effect of Prohibiting Class C Icebreakers from Convoying - For Oil Can and Coal Shovel, restricting Class C icebreakers from convoying did not significantly reduce the number of icebreakers generated. For Coal Shovel, however, it did tend to replace each Class C icebreaker eliminated with an equal number of Class B icebreakers, indicating that the increased convoying capability of Class B icebreakers was not utilized. For the Seaway, the maximum generated icebreaker fleet changed from 11 Class C icebreakers to 1 Class C and 4 Class B icebreakers for period 6. At Taconite, for all periods, the average total number of icebreakers required decreased by 21%, with Class C icebreakers almost completely eliminated and 1 additional Class B icebreaker added for every 2 Class C icebreakers eliminated.
9. Effect of Increased SHP/Length Restriction - The removal of Class 5 laker vessels (SHP/lengths = 6.25) from the fleet reduced the icebreaking requirements significantly in all task commands. In Taconite, the number of direct assists dropped from 1032 to 671 and the number of convoys escorted dropped from 937 to 587. This resulted in a reduction in the generated icebreaker fleet by more than 50%. In Oil Can the number of direct assists decreased from 102 to 11,

resulting in a reduction in the number of icebreakers from an average of 5 icebreakers in periods 3 through 7 to an average of one icebreaker in periods 6 and 7. In Coal Shovel, with the exception of period 7, the number of required icebreakers decreased by a factor of 2 due to the total number of direct assists dropping from 573 to 337 and the elimination of 347 convoys. In the Seaway, the total number of direct assists decreased from 40 to 20 and the total number of convoys decreased slightly from 160 to 154, resulting in a reduction in icebreaking requirements by approximately one third.

10. Effect of Channel Clearing - The primary effect of channel clearing which, in run 9, was performed in reaches where convoying occurred, was to: (1) decrease the size of icebreakers required for convoying, and (2) increase icebreaker speeds which allowed each icebreaker to effectively handle more convoys, at times comprised of fewer ships due to ship arrival frequency. For Oil Can and Coal Shovel where there was no convoying, almost no effect from channel clearing was observed. In the Seaway, both the size and number of icebreakers were reduced. For example, in period 6, 8 Class C icebreakers were replaced by 5 Class C icebreakers with channel clearing. In period 7, 5 Class B icebreakers were replaced with 3 Class B icebreakers and 1 Class C. For Taconite, a similar condition occurred in that both the number and size of icebreakers were reduced. In period 8, the required 12 icebreakers (8 Class C and 4 Class B) were replaced by 7 icebreakers (5 Class C and 2 Class B).

AD-A062 164

ARCTEC INC COLUMBIA MD

COMPUTER SIMULATION OF GREAT LAKES-ST. LAWRENCE SEAWAY ICEBREAK--ETC(U)

JAN 80 T V KOTRAS, J J PETER

DOT-C6-81-78-1953

F/G 15/5

ML

UNCLASSIFIED

296C-4

USCG-D-56-79

3143
AB
SUBJEC



END

DATE

FIN

REC

4-80

DTIC

8. RECOMMENDATIONS

Based on the conclusions and general discussions included in this report, as well as the knowledge we have gained during the course of this study, we recommend the following:

1. The GL-SLS NAVIGATION SIMULATION should be kept current by revising the input data files and changing the basic rules and assumptions as required. We believe this simulation is an excellent planning tool which can be used as an aid to the U.S. Coast Guard in establishing their future icebreaking requirements and evaluating alternate icebreaker plans and concepts of operation, such as direct assistance, convoying, channel maintenance and channel ice clearing, as to their impact on extended commercial navigation operations and economics. In addition, the simulation can be used by the Corps of Engineers as a planning tool to aid in their assessment of the potential benefits and impacts of various proposed GL-SLS System improvements for normal navigation season operations as well as extended navigation season operations.
2. We also recommend that, as additional extended navigation season operations continue and more icebreaker operational data is gathered, additional validation runs be performed to ensure the continued credibility of the simulation.
3. To gain further insight and a more comprehensive understanding of the impacts on icebreaker requirements and commercial navigation operations and economics, we recommend that additional sensitivity runs be performed on:
 - Variations of fixed icebreaker fleets and home ports
 - Variations in channel clearing and preventive icebreaking
 - Variations in MRT mode conditions
 - Variations in ice conditions
 - Variations in low SHP/length restriction
4. During the course of modifying the simulation and conducting the runs, we found that the following revisions to the simulation should be considered.

- Revise Fixed Fleet Mode to prohibit ice-breakers from traveling over long distances within a task command, such as an ice-breaker continually traversing Lake Superior between Duluth/Superior and the Soo.
- Incorporate a probability basis for ships getting or not getting stuck rather than the current assumption of all ships of a given class getting stuck if their speed of advance is less than 2 mph; that is, apply a probability distribution which would vary linearly with the speed of advance between a probability of getting stuck equal to 1 at some designated speed, and a probability equal to 0.0 at some higher designated speed. In this manner, the "off-on" switch for all ships in a given class either being or not being stuck would be eliminated.
- For ease of data analysis, revise the REPORT GENERATING MODEL to provide summary tables similar to those listed in Section 6.4 for each run.

9. REFERENCES

1. Kotras, T. V. and J. J. Peter, "Winter Rate Study for Great Lakes-St. Lawrence Seaway System, Final Report," ARCTEC, Incorporated Report No. 246C, U.S. Army Corps of Engineers, Chicago, Illinois, December 1975.
2. Kotras, T. V., "Simulation of Commercial Navigation on the Great Lakes-St. Lawrence Seaway System, Final Report," ARCTEC, Incorporated Report No. 341C, St. Lawrence Seaway Development Corporation, Washington D.C., February 1976.
3. Enclosure to letter from W. O. Gelston of St. Lawrence Seaway Development Corporation to R. M. McIntyre, dated 23 December 1974.
4. Michel, Bernard, "Winter Regime of Rivers and Lakes," U.S. Army Corps of Engineers, CRREL, Monograph III-B1a, Hanover, N.H., April 1971.
5. Ashton, George, "Evaluation of Ice Management Problems Associated with Operation of a Mechanical Ice Cutter on the Mississippi River," U.S. Army Corps of Engineers, Cold Regions Research and Engineering Laboratory, Hanover, N.H., Special Report 214, October 1974.
6. Michel, B. and P. Lafleur, "Ice Management at Marine Terminal Hershel Island," Department of Public Works, Government of Canada, February 1971.
7. Kotras, T. V. and J. J. Peter, "Simulation of Lock Operations During Winter Ice Months," Paper presented at the Third International Symposium on Ice Problems, Hanover, N.H., November 1975.
8. Lewis, J. W., et al., "St. Lawrence Seaway System Plan for All Year Navigation," ARCTEC, Incorporated Report No. 105C, Department of Transportation, Washington, D.C., 1973.
9. J. Greenwood, Guide to Great Lakes Shipping, Freshwater Press, Incorporated, Cleveland, Ohio, 1975.
10. Kotras, T. V., "Great Lakes Navigation Season Extension Harbor Study, Final Report," Volumes I, II, and III, ARCTEC, Incorporated Report No. 392C, U.S. Army Corps of Engineers, Detroit, Michigan, June 1978.
11. Voelker, R. P., "Ice Transiting Bow Forms For Great Lakes Bulk Carriers," Paper presented at Joint Meeting Eastern Canadian Section and Great Lakes-Great Rivers Section of Society of Naval Architects and Marine Engineers, Toronto, Canada, May 1979.
12. Leshkevich, George A., "Great Lakes Ice Cover, Winter 1975-76," NOAA Technical Memorandum ERL GLERL-12, Great Lakes Environmental Research Laboratory, Ann Arbor, MI, June 1977.
13. Quinn, F. H., et. al., "Summary of Great Lakes Weather and Ice Conditions, Winter 1976-77," NOAA Technical Memorandum ERL GLERL-20, Great Lakes Environmental Research Laboratory, Ann Arbor, MI, October 1978.