

AD-A 083 449

TECHNICAL
LIBRARY

AD-A 083 449

WVT-PP-1

DESIGN OF
LAMINATED TORSION BAR SPRINGS

BY
JOSEPH A. GENTILUOMO

FEBRUARY 1980



PROCUREMENT DIRECTORATE
WATERVLIET ARSENAL
WATERVLIET, N.Y. 12189

TECHNICAL REPORT

Pron No. M1-8P 5282(01)M7-M7

APPROVED FOR PUBLIC RELEASE : DISTRIBUTION UNLIMITED

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official indorsement or approval.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER WVT-PP-1	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) DESIGN OF LAMINATED TORSION BAR SPRINGS		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Joseph A. Gentiluomo		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Procurement Directorate Value Analysis Division Watervliet Arsenal, Watervliet, NY 12189		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS M1-8P5282(01)M7-M7
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army ARRCOM Rock Island, IL 61299		12. REPORT DATE February 1980
		13. NUMBER OF PAGES 21
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for Public Release: Distribution Unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Laminated Torsion Bar Springs Principal Stresses Combined Shearing Stress		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report provides an analytical approach to the design of torsion leaf spring packs for use in cannon breech mechanisms, vehicle suspensions, etc. The design procedure presents an expeditious simple method for determining spring pack dimensions when parameters such as total required torque, spring pack angle of twist, free length of leaf spring, maximum tensile working stress, and maximum torsional working stress are known. The unknown parameters to be determined are leaf spring thickness, leaf spring width, and the number of leaf springs (CONT'D)		

20. Abstract (CONT'D)

required per pack to provide the required total torque. Of interest is the fact that leaf spring thickness is dependent solely on maximum shearing stress, angle of twist per unit length, and shear modulus of elasticity. Also, leaf spring width is dependent solely on maximum tensile stress, angle of twist per unit length, and tensile modulus of elasticity.

TABLE OF CONTENTS

	<u>Page</u>
NOTATIONS	ii
INTRODUCTION	1
THEORETICAL ANALYSIS	2
EXAMPLE PROBLEM AND SOLUTION	6
REFERENCES	10

ILLUSTRATIONS

1. Longitudinal stress in leaf spring under torsion.	11
2. Representation of torsional shear stress across strip width.	12
3. Shearing and longitudinal stresses in leaf springs under torsion.	13
DISTRIBUTION LIST	14

NOTATIONS

α	Coefficient depending on ratio b/c .
β	Coefficient depending on ratio b/c .
θ	Angle of twist per unit length, Radians/inch.
ϕ	Angle of twist, degrees.
σ_1	Maximum principal tensile stress, psi.
σ_2	Maximum principal compressive stress, psi.
σ_A	Compressive stress at mid-point of width "b", psi.
σ_B	Tensile stress at both ends of width "b", psi.
σ_W	Tensile working stress, psi.
σ_Y	Tensile yield stress, psi.
σ_Z	Tensile or compressive stress at distance "y", psi.
σ_U	Ultimate tensile stress, psi.
τ_A	Maximum shearing stress at mid-point of width "b", psi.
τ_M	Maximum combined shearing stress, psi.
τ_P	Shearing stress at distance "y", psi.
τ_W	Torsional working stress, psi.
τ_Y	Torsional yield stress, psi.
τ_{ZY}	Shearing stress at distance "y", psi.
b	Width of rectangular strip, inches.
c	Thickness of rectangular strip, inches.
ℓ	Free length of rectangular strip, inches.
y	Distance from Z-axis, inches.

n	Number of leaf springs per pack.
E	Tensile modulus of elasticity, psi.
G	Shear modulus of elasticity, psi.
H	Total height of laminated spring pack, inches.
S.F.	Safety factor.
T	Total torque per laminated spring pack, in-lbs.
T_1	Torque due to torsional shear, in-lbs.
T_2	Torque due to longitudinal stress, in-lbs.
T_n	Torque per leaf spring, in-lbs.

INTRODUCTION

The Saint Venant's analysis indicates that when a flat strip is twisted by applying moments at its ends, a plane transverse section therewithin does not remain a plane section after twisting. Said section becomes a warped surface which effectuates an increase in shearing stress in some parts of the section and a decrease in other parts when compared to stresses that would occur if the section did not warp. The center of the strip's long side will experience maximum shearing stress, and the corners will experience zero shearing stress. Also, due to said twisting, the longitudinal edges form a helix whose fibers become longer than the center fibers. Simultaneously, said twisting causes the strip to shorten axially. Therefore, the net effect is the introduction of tensile stresses in the outer fibers, and compressive stresses within the central fibers. These longitudinal secondary stresses introduce a secondary torque which supplements the torque associated with the torsional shearing stresses. It should be noted that these stresses prevail at a sufficient distance from the strip ends, without consideration as to the manner in which the strip's ends are secured.

When a pack of flat strip springs are twisted while secured within rectangular type end restraints, localized stresses develop where said strips emerge from the end restraints. Depending on the particular type of end restraint design, stress of considerable magnitude can exist at the juncture to cause fatigue failure. Since sections perpendicular to the strip spring's torsional axis warp when twisted, the strip ends should be allowed to warp freely within the rectangular cavity of the end restraints in order to

minimize operational stresses. Therefore, strip spring working stresses should be established with due consideration given to the type of end restraint design used.

Due to friction between unlubricated strips of a laminated torsion bar spring pack during twisting, hysteresis will prevail between the loading and unloading action of the spring pack. To reduce inter-strip friction damping, liquid or solid film lubricant may be used.

THEORETICAL ANALYSIS

The analytical treatment of solid noncircular members in torsion, as presented herein, is based on the following assumptions:

- (1) The strip is straight, of uniform rectangular section, and of homogeneous isotropic material.
- (2) The strip is loaded only by equal and opposite twisting couples which are applied at its ends in planes normal to its longitudinal axis.
- (3) The strip is stressed within the elastic limit of the material.
- (4) The condition of loading is such that the end sections of the strip are free to warp within the end restraints.

Torque Due To Torsional Shear

$$T_1 = \alpha bc^2 \tau_A$$

$$T_1 = \beta bc^3 G \theta$$

Data indicates that α and β are approximately equal to $1/3$ for $b/c \geq 10$.

$$T_1 = \frac{1}{3} bc^3 G \theta \quad (1)$$

$$T_1 = \frac{1}{3} bc^2 \tau_A \quad (2)$$

Thickness of Rectangular Strip

Equating Eqs. (1) and (2) and solving for "c".

$$c = \frac{\tau_A}{G\theta} \quad (3)$$

Longitudinal Stress Distribution in Rectangular Strip

$$\sigma_z = \frac{E\theta^2}{b} \left[y^2 - \frac{b^2}{12} \right] \quad (4)$$

When $\sigma_z = 0$

$$y = \sqrt{\frac{b^2}{12}} \quad (5)$$

When $y = 0$

$$\sigma_A = - \frac{E\theta^2 b^2}{24} \quad (\text{Max. Compressive Stress}) \quad (6)$$

When $y = \pm b/2$

$$\sigma_B = \frac{E\theta^2 b^2}{12} \quad (\text{Max. Tensile Stress}) \quad (7)$$

$$\sigma_B = -2\sigma_A \quad (8)$$

Solving Eqs. (6) and (7) for "b²"

$$b^2 = - \frac{24\sigma_A}{E\theta^2} \quad (9)$$

$$b^2 = \frac{12\sigma_B}{E\theta^2} \quad (10)$$

Torque Due to Longitudinal Stress

$$T_2 = \frac{1}{360} Ecb^5\theta^3 \quad (11)$$

Total Twisting Torque Per Strip Spring

Combine Eqs. (1) and (11)

$$T_n = T_1 + T_2$$
$$T_n = \frac{1}{3} bc^3 G \theta + \frac{1}{360} E c b^5 \theta^3 \quad (12)$$

Number of Strip Springs Required Per Pack

Neglecting inter-spring friction between strip springs of equal width and thickness, it has been determined that the developed total torque is essentially that of a single strip spring multiplied by the number of strip springs in the pack.

$$n = \frac{T}{T_n} \quad (13)$$

Total Height of Laminated Spring Pack

$$H = nc \quad (14)$$

Shearing Stress Distribution in Rectangular Strip

With reference to Fig. 2, the maximum shearing stress " τ_A " exists at point "A", the center of side "b". Assume the shearing stress to vary from "A" to "B" approximately as the ordinates of a parabola. Therefore, the stresses along AB are represented by the ordinates of the portion HMB of a parabola.

Let AH represent " τ_A ", and MP represent " τ_P "

$$AH = BK = \tau_A$$

$$PM = \tau_P$$

Equation of Parabola:

$$y^2 = kx'$$

When $y = b/2$; $x' = BK$

$$(b/2)^2 = k(BK)$$

$$k = \frac{(b/2)^2}{BK}$$

When $y = HN$; $x' = (BK-MP) = NM$

$$y^2 = \frac{(b/2)^2}{BK} x'$$

$$y^2 = \frac{(b/2)^2}{BK} (BK-MP)$$

$$\frac{BK-MP}{BK} = \frac{y^2}{(b/2)^2}$$

$$1 - \frac{MP}{BK} = \left[\frac{2y}{b} \right]^2$$

$$1 - \frac{\tau_P}{\tau_A} = \left[\frac{2y}{b} \right]^2$$

$$\tau_P = \tau_A \left[1 - \left(\frac{2y}{b} \right)^2 \right] \quad (15)$$

Combination of Longitudinal and Shearing Stresses

With reference to Fig. 3, note that the portion of the parabola AP'B' represents the portion of the parabola HMB shown in Fig. 2.

(a) At point "A", the longitudinal stress " σ_A " is maximum compressive, and the shearing stress is " τ_A ".

$$\sigma_1 = \frac{\sigma_A}{2} + \sqrt{\left[\frac{\sigma_A}{2}\right]^2 + \tau_A^2} \quad (\text{Max. Principal Tensile Stress}) \quad (16)$$

$$\sigma_2 = \frac{\sigma_A}{2} - \sqrt{\left[\frac{\sigma_A}{2}\right]^2 + \tau_A^2} \quad (\text{Max. Principal Compressive Stress}) \quad (17)$$

$$\tau_M = \sqrt{\left[\frac{\sigma_A}{2}\right]^2 + \tau_A^2} \quad (\text{Max. Combined Shearing Stress}) \quad (18)$$

(b) At point "P", the longitudinal stress is zero, and the shearing stress is " τ_P ".

$$\sigma_1 = \tau_P \quad (\text{Max. Principal Tensile Stress}) \quad (19)$$

$$\sigma_2 = -\tau_P \quad (\text{Max. Principal Compressive Stress}) \quad (20)$$

$$\tau_M = \tau_P \quad (\text{Max. Combined Shearing Stress}) \quad (21)$$

(c) At point "B", the longitudinal stress " σ_B " is maximum tensile, and the shearing stress " τ_B " is zero.

$$\sigma_1 = \sigma_B \quad (\text{Max. Principal Tensile Stress}) \quad (22)$$

$$\sigma_2 = 0 \quad (\text{Max. Principal Compressive Stress}) \quad (23)$$

$$\tau_M = \sigma_B/2 \quad (\text{Max. Combined Shearing Stress}) \quad (24)$$

EXAMPLE PROBLEM AND SOLUTION

Given: $T = 3600$ in-lbs.

$G = 11.5 \times 10^6$ psi

$\phi = 135^\circ$

$E = 30 \times 10^6$ psi

$\ell = 11.75$ "

$\sigma_U = 256,000$ psi

$\theta = .2005$ Rad./in.

Material: AISI 1095 Clock Spring Steel

Find: c , b , T_n , n , H , σ_1 , σ_2 , and τ_M

Tensile Yield Stress

$$\sigma_Y = .85 \sigma_U = .85 \times 256,000 = 217,600 \text{ psi}$$

Compressive Yield Stress

$$\sigma_Y = 392,000 \text{ psi}$$

Torsional Yield Stress

$$\tau_Y = .6 \sigma_Y = .6 \times 217,600 = 130,560 \text{ psi}$$

Tensile Working Stress (At Pt. B)

$$\sigma_W = \sigma_B = \frac{\sigma_Y}{\text{S.F.}} = \frac{217,600}{1.38} = 157,681 \text{ psi}$$

Maximum Combined Shearing Stress (At Pt. A)

$$\tau_M = \frac{\tau_Y}{\text{S.F.}} = \frac{130,560}{1.8} = 72,533 \text{ psi}$$

From Eq. (8):

$$\sigma_A = -\frac{\sigma_B}{2} = -\frac{157,681}{2} = -78,840 \text{ psi}$$

From Eq. (18):

$$\tau_A^2 = \tau_M^2 - \left[\frac{\sigma_A}{2} \right]^2 = (72,533)^2 - \left[\frac{-78,840}{2} \right]^2$$

$$\tau_A = 57,338 \text{ psi}$$

From Eq. (3):

$$c = \frac{\tau_A}{G\theta} = \frac{57,338}{11.5 \times 10^6 \times .2005}$$

$$c = .0249$$

Let

$$c = .025''$$

From Eq. (10):

$$b^2 = \frac{12 \sigma_B}{E\theta^2} = \frac{12(157,681)}{30 \times 10^6 (.2005)^2}$$

$$b = 1.2526$$

Let

$$b = 1.250''$$

From Eq. (12):

$$T_n = \frac{1}{3} bc^3 G\theta + \frac{1}{360} Ec b^5 \theta^3$$

$$T_n = \frac{1.250(.025)^3 11.5 \times 10^6 \times .2005}{3} + \frac{30 \times 10^6 \times .025(1.25)^5 (.2005)^3}{360}$$

$$T_n = 66.2564 \text{ in-lbs.}$$

From Eq. (13):

$$n = \frac{T}{T_n} = \frac{3600}{66.2564} = 54.3343$$

Let

$$n = 54$$

From Eq. (14):

$$H = nc = 54 \times .025$$

$$H = 1.350''$$

From Eq. (16):

$$\sigma_1 = \frac{\sigma_A}{2} + \sqrt{\left[\frac{\sigma_A}{2}\right]^2 + \tau_A^2}$$

$$\sigma_1 = \frac{-78,840}{2} + \sqrt{\left[\frac{-78,840}{2}\right]^2 + (57,338)^2}$$

$$\sigma_1 = 30,161 \text{ psi (Max. Principal Tensile Stress)}$$

From Eq. (17):

$$\sigma_2 = \frac{\sigma_A}{2} - \sqrt{\left[\frac{\sigma_A}{2}\right]^2 + \tau_A^2}$$
$$\sigma_2 = \frac{-78,840}{2} - \sqrt{\left[\frac{-78,840}{2}\right]^2 + (57,338)^2}$$

$$\sigma_2 = -109,000 \text{ psi (Max. Principal Compressive Stress)}$$

From Eq. (18):

$$\tau_M = 72,533 \text{ psi (Max. Combined Shearing Stress)}$$

From Eq. (22):

$$\sigma_1 = \sigma_B$$
$$\sigma_1 = 157,681 \text{ psi (Max. Principal Tensile Stress)}$$

From Eq. (23):

$$\sigma_2 = 0 \text{ (Max. Principal Compressive Stress)}$$


From Eq. (24):

$$\tau_M = \frac{\sigma_B}{2}$$
$$\tau_M = \frac{157,681}{2}$$
$$\tau_M = 78,840 \text{ psi (Max. Combined Shearing Stress)}$$

$$\text{S.F.} = \frac{\tau_Y}{\tau_M} = \frac{130,560}{78,840} = 1.66$$


REFERENCES

1. S. Timoshenko, Strength of Materials, Part II, Third Edition, D. Van Nostrand Co., Inc., NY, 1956, pp. 235-299.
2. T. B. Seeley and J. O. Smith, Advanced Mechanics of Materials, Second Edition, John Wiley & Sons, Inc., NY, 1952, pp. 266-271.
3. High Carbon Strip Steels, Brochure Form No. 900, Wallace Barnes Steel, Bristo , CT.
4. W. C. Leslie and R. J. Sober, "The Strength of Ferrite and of Martensite as Functions of Composition, Temperature, and Strain Rate," Trans. ASM, 60, 459 (1967).




LONGITUDINAL STRESS IN LEAF SPRING UNDER TORSION

FIG. I



REPRESENTATION OF TORSIONAL SHEAR STRESS ACROSS
STRIP WIDTH

FIG. 2



SHEARING & LONGITUDINAL STRESS IN LEAF SPRINGS UNDER TORSION

FIG. 3

WATERVLIET ARSENAL INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
COMMANDER	1
DIRECTOR, BENET WEAPONS LABORATORY	1
CHIEF, DEVELOPMENT ENGINEERING BRANCH	1
ATTN: DRDAR-LCB-DA	1
-DM	1
-DP	1
-DR	1
-DS	1
-DC	1
CHIEF, ENGINEERING SUPPORT BRANCH	1
CHIEF, RESEARCH BRANCH	2
ATTN: DRDAR-LCB-RA	1
-RC	1
-RM	1
-RP	1
TECHNICAL LIBRARY	10
DIRECTOR, OPERATIONS DIRECTORATE	1
DIRECTOR, PROCUREMENT DIRECTORATE	1
DIRECTOR, PRODUCT ASSURANCE DIRECTORATE	1

EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
ASST SEC OF THE ARMY RESEARCH & DEVELOPMENT ATTN: DEP FOR SCI & TECH THE PENTAGON WASHINGTON, D.C. 20315	1
COMMANDER US ARMY MAT DEV & READ. COMD ATTN: DRCDE 5001 EISENHOWER AVE ALEXANDRIA, VA 22333	1
COMMANDER US ARMY ARRADCOM ATTN: DRDAR-TSS DOVER, NJ 07801	2
COMMANDER US ARMY ARRCOM ATTN: DRSAR-LEP-L ROCK ISLAND ARSENAL ROCK ISLAND, IL 61299	1
COMMANDER US ARMY MOBILITY EQUIP R&D COMD ATTN: TECH LIB FT BELVOIR, VA 22060	1
COMMANDER US ARMY TANK-AUTMV R&D COMD ATTN: TECH LIB-DRDTA-UL MAT LAB-DRDTA-RK WARREN, Michigan 48090	1 1
COMMANDER US MILITARY ACADEMY ATTN: CHMN, MECH ENGR DEPT WEST POINT, NY 10996	1
COMMANDER ROCK ISLAND ARSENAL ATTN: SARRI-ENM (MAT SCI DIV) ROCK ISLAND, IL 61202	1

EXTERNAL DISTRIBUTION LIST (CONT)

	<u>NO. OF COPIES</u>
COMMANDER REDSTONE ARSENAL ATTN: DRSMI-RB	2
DRSMI-RRS	1
DRSMI-RSM	1
ALABAMA 35809	
COMMANDER HQ, US ARMY AVN SCH ATTN: OFC OF THE LIBRARIAN	1
FT RUCKER, ALABAMA 36362	
COMMANDER US ARMY FGN SCIENCE & TECH CEN ATTN: DRXST-SD	1
220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	
COMMANDER US ARMY MATERIALS & MECHANICS RESEARCH CENTER ATTN: TECH LIB-DRXMR-PL	2
WATERTOWN, MASS 02172	
COMMANDER US ARMY RESEARCH OFFICE P.O. BOX 1211	1
RESEARCH TRIANGLE PARK, NC 27709	
COMMANDER US ARMY HARRY DIAMOND LAB ATTN: TECH LIB	1
2800 POWDER MILL ROAD ADELPHIA, MD 20783	
CHIEF, MATERIALS BRANCH US ARMY R&S GROUP, EUR BOX 65, FPO N.Y. 09510	1
COMMANDER NAVAL SURFACE WEAPONS CEN ATTN: CHIEF, MAT SCIENCE DIV	1
DAHLGREN, VA 22448	

EXTERNAL DISTRIBUTION LIST (CONT)

	<u>NO. OF COPIES</u>
DIRECTOR US NAVAL RESEARCH LAB ATTN: DIR, MECH DIV CODE 26-27 (DOC LIB) WASHINGTON, D.C. 20375	1 1
NASA SCIENTIFIC & TECH INFO FAC P.O. BOX 8757, ATTN: ACQ BR BALTIMORE/WASHINGTON INTL AIRPORT MARYLAND 21240	1
COMMANDER DEFENCE TECH. INFO. CTR. ATTN: DTIC-TCA CAMERON STATION ALEXANDRIA, VA 22314	15
MPDC 13919 W. BAY SHORE DR. TRAVERSE CITY, MI 49684	1
MATERIEL SYSTEMS ANALYSIS ACTV ATTN: DRXSY-MP ABERDEEN PROVING GROUND MARYLAND 21005	1