

AD-A085 526

COASTAL ENGINEERING RESEARCH CENTER FORT BELVOIR VA F/O 8/10
COMPUTATION OF LONGSHORE ENERGY FLUX USING LEO CURRENT OBSERVAT--ETC(1)
MAR 80 T L WALTON
CERC-CETA-80-3 NL

UNCLASSIFIED

1 OF 1
5205-108

END
DATE
FILMED
7-80
DTIC

1000000

12

CETA 80-3

Computation of Longshore Energy Flux Using LEO Current Observations

by
Todd L. Walton, Jr.

COASTAL ENGINEERING TECHNICAL AID NO. 80-3

MARCH 1980



DTIC
JUN 17 1980
A

Approved for public release;
distribution unlimited.

U.S. ARMY. CORPS OF ENGINEERS
COASTAL ENGINEERING
RESEARCH CENTER

Kingman Building
Fort Belvoir, Va. 22060

80 6 16 034

DDC FILE COPY, ADA 085526

Reprint or republication of any of this material shall give appropriate credit to the U.S. Army Coastal Engineering Research Center.

Limited free distribution within the United States of single copies of this publication has been made by this Center. Additional copies are available from:

*National Technical Information Service
ATTN: Operations Division
5285 Port Royal Road
Springfield, Virginia 22161*

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER CETA 80-5	2. GOVT ACCESSION NO. AD-A085526	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) COMPUTATION OF LONGSHORE ENERGY FLUX USING LEO CURRENT OBSERVATIONS.	5. TYPE OF REPORT & PERIOD COVERED Coastal Engineering Technical Aid report	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Todd L. Walton, Jr.	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Department of the Army Coastal Engineering Research Center (CEREN-EV) Kingman Building, Fort Belvoir, Virginia 22060	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS D31181	
11. CONTROLLING OFFICE NAME AND ADDRESS Department of the Army Coastal Engineering Research Center Kingman Building, Fort Belvoir, Virginia 22060	12. REPORT DATE March 1980	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	13. NUMBER OF PAGES 12	
	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
	15a. DECLASSIFICATION DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) (14) CERC-CETA-80-3		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Coastal engineering LEO Longshore energy flux Part 80		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A computational technique is presented for the longshore energy flux factor, P_{ls} using current observations from the Littoral Environment Observation (LEO) program. Chapter 4 of the Shore Protection Manual (SPM) gives various equations for P_{ls} as a function of wave height, wave period, and breaking wave angle. The present report details how P_{ls} can be calculated using longshore current and breaking wave height data only. An example problem is given for this method.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

037050

PREFACE

This report presents a computational technique for determining the long-shore energy flux factor, P_{ls} , using current observations from the Littoral Environmental Observation (LEO) program. P_{ls} is discussed in Chapter 4 of the Shore Protection Manual (SPM) (U.S. Army, Corps of Engineers, Coastal Engineering Research Center, 1977). The work was carried out under the coastal engineering research program of the U.S. Army Coastal Engineering Research Center (CERC).

The report was prepared by Dr. Todd L. Walton, Jr., Hydraulic Engineer, under the general supervision of Dr. J.R. Weggel, Chief, Evaluation Branch, Engineering Development Division.

Comments on this publication are invited.

Approved for publication in accordance with Public Law 166, 79th Congress, approved 31 July 1945, as supplemented by Public Law 172, 88th Congress, approved 7 November 1963.


TED E. BISHOP
Colonel, Corps of Engineers
Commander and Director

CONTENTS

	Page
CONVERSION FACTORS, U.S. CUSTOMARY TO METRIC (SI)	5
I INTRODUCTION	7
II DATA SOURCE.	7
III DETERMINATION OF LONGSHORE ENERGY FLUX FACTOR.	8
IV EXAMPLE PROBLEM.	8
LITERATURE CITED	10
APPENDIX DERIVATION FOR LONGSHORE ENERGY FLUX FACTOR.	11

CONVERSION FACTORS, U.S. CUSTOMARY TO METRIC (SI) UNITS OF MEASUREMENT

U.S. customary units of measurement used in this report can be converted to metric (SI) units as follows:

Multiply	by	To obtain
inches	25.4	millimeters
	2.54	centimeters
square inches	6.452	square centimeters
cubic inches	16.39	cubic centimeters
feet	30.48	centimeters
	0.3048	meters
square feet	0.0929	square meters
cubic feet	0.0283	cubic meters
yards	0.9144	meters
square yards	0.836	square meters
cubic yards	0.7646	cubic meters
miles	1.6093	kilometers
square miles	259.0	hectares
knots	1.852	kilometers per hour
acres	0.4047	hectares
foot-pounds	1.3558	newton meters
millibars	1.0197×10^{-3}	kilograms per square centimeter
ounces	28.35	grams
pounds	453.6	grams
	0.4536	kilograms
ton, long	1.0160	metric tons
ton, short	0.9072	metric tons
degrees (angle)	0.01745	radians
Fahrenheit degrees	5/9	Celsius degrees or Kelvins ¹

¹To obtain Celsius (C) temperature readings from Fahrenheit (F) readings, use formula: $C = (5/9) (F - 32)$.

To obtain Kelvin (K) readings, use formula: $K = (5/9) (F - 32) + 273.15$.

COMPUTATION OF LONGSHORE ENERGY FLUX USING LEO CURRENT OBSERVATIONS

By
Toll L. Wilton, Jr.

I. INTRODUCTION

Prediction of sand transport rates along beaches is necessary to determine dredging quantities at inlets, effective life of various coastal structures such as jetties, and magnitude of erosion-accretion on beaches adjacent to inlets. Most computations of sand transport rate have previously been determined by computing a wave parameter dependent quantity termed the longshore energy flux factor $P_{L\phi}$. Chapter 4 of the Shore Protection Manual (SPM) (U.S. Army, Corps of Engineers, Coastal Engineering Research Center, 1977) gives various equations for $P_{L\phi}$ as a function of wave height, wave period, and wave angle with the shoreline at breaking. As wave angle is a difficult parameter to measure, an alternate approach is to use the longshore current as an independent quantity with which to determine $P_{L\phi}$, since the wave angle with the shoreline is explicitly contained within the most acceptable formulas for longshore currents due to breaking waves (e.g., Longuet-Higgins, 1970). The present report incorporates the longshore current model (due to breaking waves) of Longuet-Higgins to determine the longshore energy flux factor, which in turn, can be used to estimate longshore sand transport rates.

II. DATA SOURCE

The computational technique in this report uses current observations from the Littoral Environmental Observation (LEO) program. The LEO program was developed by the Coastal Engineering Research Center (CERC) and is discussed by various investigators (Berg, 1969; Szuwalski, 1970; Bruno and Hiipakka, 1973; and Balsillie, 1975a). In the LEO program nearly simultaneous visual observations of breaker conditions (height, period, angle of approach, and type), local winds, longshore currents, rip currents, and beach geometry are made daily for a year or more. The selection of observation sites is not generally hindered by lack of access to the beach which often limits the use of instrumentation. Thus, depending on availability of trained observers, many sites along a considerable segment of shoreline may be established using LEO techniques.

The longshore current is estimated by measuring the shore-parallel distance and observing the direction that a sodium-fluorescein dye packet injected into the surf (between the breakers and shore) travels in 1 minute. Observation of longshore current movement from the dye injections is representative of surface movement at the injection site, but may not always reflect the movement of water at depth or represent the average speed across the surf zone. As LEO measurements include the width of the surf zone as well as the distance from shore to the injection point of the dye, the longshore current can be treated as a point measurement on a spatially variable (across the surf zone) longshore current, the longshore current chosen in accordance with a theoretical profile having an assumed mixing constant. Balsillie (1975b) has shown that the LEO measurements of longshore currents (across surf zone) correlate very well with longshore currents calculated by the theoretical formula of Longuet-Higgins (1970).

III. DETERMINATION OF LONGSHORE ENERGY FLUX FACTOR

The following equation is equivalent to equation (4-28) in the SPM when calculating the longshore energy flux factor,

$$P_{LS} = \frac{\rho g H_b W V_{LEO} C_f}{\left(\frac{5\pi}{2}\right) \left(\frac{V}{V_o}\right)_{LH}} \quad (1)$$

where

- ρ = fluid density
- g = acceleration of gravity
- H_b = breaking wave height
- W = width of surf zone
- V_{LEO} = average longshore current due to breaking waves
- C_f = friction factor (assume 0.01)

and

$$\left(\frac{V}{V_o}\right)_{LH} = 0.2 \left(\frac{X}{W}\right) - 0.714 \left(\frac{X}{W}\right) \ln \left(\frac{X}{W}\right) \quad (2)$$

where X is the distance to dye patch from shoreline and $(V/V_o)_{LH}$ is the Longuet-Higgins dimensionless longshore current velocity for an assumed mixing coefficient, $P = 0.4$, which agrees reasonably well with laboratory data (see Longuet-Higgins, 1970). The derivation of equation (1) is presented in the Appendix, as well as reference to equation (2).

It should be noted that as previous calculation equations for P_{LS} are based on significant wave heights (e.g., Ch. 4 in the SPM) equation (1) should also use significant wave height for breaking wave height. The recorded value of H_b in the LEO observation program is a reasonable approximation to significant breaking wave height. It should also be noted that as the LEO current observations are time-averaged, computing P_{LS} by the present method may provide a lower value of the longshore energy flux factor than given by equations based on significant breaking wave height to higher powers such as those in Chapter 4 of the SPM.

IV. EXAMPLE PROBLEM

GIVEN: A LEO observation with the following measured values of wave height, longshore current velocity, width of surf zone, and distance of dye patch from the shoreline

- H_b = 3.0 feet (0.91 meter)
- V_{LEO} = 0.5 foot (0.15 meter) per second
- W = 150 feet (45.7 meters)
- X = 50 feet (15.2 meters)

FIND: Longshore energy flux factor, P_{ls}

SOLUTION:

(a) Using equation (2) calculate V/V_{oLH}

$$\left(\frac{V}{V_o}\right)_{LH} = 0.2 \left(\frac{50}{150}\right) - 0.714 \left(\frac{50}{150}\right) \ln \left(\frac{50}{150}\right) = 0.33$$

(b) Now, using equation (1) calculate P_{ls} .

$$P_{ls} = \frac{64(3)(150)(0.5)(0.01)}{\left(\frac{5\pi}{2}\right)(0.33)} = 55.3 \text{ pounds (25.1 kilograms) per second}$$

(c) The value of P_{ls} corresponds to a sediment transport rate of 415,000 cubic yards (317,310 cubic meters) per year using the SPM equation (4-40) ($Q = 7.5 \times 10^3 P_{ls}$ in feet-per-second system).

(d) Annual average sediment transport rates for any field site would be estimated from LEO with a P_{ls} value obtained by averaging the P_{ls} values computed for each observation by the above method.

LITERATURE CITED

- BALSILLIE, J.H., "Analysis and Interpretation of Littoral Environment Observation (LEO) and Profile Data Along the Western Panhandle Coast of Florida," TM-49, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., Mar. 1975a.
- BALSILLIE, J.H., "Surf Observations and Longshore Current Prediction," TM-58, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., Nov. 1975b.
- BERG, D.W., "Systematic Collection of Beach Data," *Proceedings of the 11th Conference on Coastal Engineering*, American Society of Civil Engineers, Vol. 1, 1969, pp. 273-277 (also Reprint 4-69, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., NTIS 697 533).
- BRUNO, R.O., and HIIPAKKA, L.W., "Littoral Environment Observation Program in the State of Michigan," *Proceedings of the 16th Conference on Great Lakes Research*, International Association of Great Lakes Research, 1973, pp. 492-507 (also Reprint 4-74, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., NTIS 777 706).
- LONGUET-HIGGINS, M.S., "Longshore Currents Generated by Obliquely Incident Sea Waves," Parts 1 and 2, *Journal of Geophysical Research*, Vol. 75, No. 33, Nov. 1970, pp. 6778-6801.
- SZUWALSKI, A., "Littoral Environment Observation Program in California, Preliminary Report, February-December 1968," MP 2-70, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Washington, D.C., Feb. 1970.
- U.S. ARMY, CORPS OF ENGINEERS, COASTAL ENGINEERING RESEARCH CENTER, *Shore Protection Manual*, 3d ed., Vols. I, II, and III, Stock No. 008-022-00113-1, U.S. Government Printing Office, Washington, D.C., 1977, 1,262 pp.

APPENDIX

DERIVATION FOR LONGSHORE ENERGY FLUX FACTOR

Derivation of equation (1) for longshore energy flux factor:

(a) From Longuet-Higgins (1970)

$$V_L = \frac{5\pi}{8} \left(\frac{\kappa\beta}{C_f} \right) (g d_b)^{1/2} (m \sin \alpha_b \cos \alpha_b) \quad (A-1)$$

where

V_b = longshore current at breaking zone

β = a mixing parameter

d_b = breaking depth

m = beach slope

α_b = breaking wave angle

κ = ratio of breaking wave amplitude to water depth

(b) Using relationship $2\kappa = \frac{H_b}{d_b}$ equation (A-1) becomes

$$V_b = \frac{5\pi}{16} \left(\frac{\kappa\beta}{C_f} \right) \left(\frac{1}{2\kappa} \right)^{1/2} m (gH_b)^{1/2} \sin 2\alpha_b \quad (A-2)$$

(c) Longshore velocity at any point within surf zone can be defined as

$$V = V_b \left(\frac{V_o}{V_b} \right) \left(\frac{V}{V_o} \right) \quad (A-3)$$

where V is longshore current within surf zone and V_o is theoretical longshore velocity at breaking, no mixing.

(d) From equation (58) of Longuet-Higgins (1970)

$$\frac{V_o}{V_b} = \frac{1}{\beta} \quad (A-4)$$

(e) Using equations (A-4), (A-3), and (A-2), longshore velocity is

$$V = \left(\frac{V}{V_o} \right) \left(\frac{5\pi}{16} \right) \left(\frac{\kappa}{C_f} \right) \left(\frac{1}{2\kappa} \right)^{1/2} m (gH_b)^{1/2} \sin 2\alpha_b \quad (A-5)$$

(f) Using the SPM equation (4-28)

$$P_{LS} = \frac{\rho g H_b^2}{16} C_{gr} \sin 2\alpha \quad (A-6)$$

where C_{gr} equals group wave celerity equals $(g d_b)^{1/2}$ linear wave theory; therefore

$$P_{LS} = \frac{\rho g H_b^2}{16} \left(\frac{d_b}{H_b} \right)^{1/2} (g H_b)^{1/2} \sin 2\alpha \quad (A-7)$$

(g) Using equation (A-2), (A-5), and (A-7) and assuming $m = d_b/W$

$$P_{LS} = \frac{\rho g H_b^2 W V C_r}{\left(\frac{5\pi}{2} \right) \left(\frac{V}{V_o} \right)} \quad (A-8)$$

(h) The value of (V/V_o) can be assumed equal to that given by Longuet-Higgins (1970)

$$\left(\frac{V}{V_o} \right) = \left(\frac{V}{V_o} \right)_{LH} \quad (A-9)$$

(i) The value of V is measured using LEO technique

$$V = V_{LEO} \quad (A-10)$$

(j) Equation (A-8) now becomes

$$P_{LS} = \frac{\rho g H_b^2 W V_{LEO} C_r}{\left(\frac{5\pi}{2} \right) \left(\frac{V}{V_o} \right)_{LH}} \quad (A-11)$$

Walton, Todd L., Jr.

Computation of longshore energy flux using LEO current observations / by Todd L. Walton, Jr. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1980.

[12] p. appendix : ill. : 27 cm. - (Technical aid - U.S. Coastal Engineering Research Center ; no. 80-3). Cover title.

Includes bibliographical references.

Appendix: Derivation for longshore energy flux factor.

A computational technique is presented for the longshore energy flux factor, P_{lg} , using current observations from the Littoral Environment Observation (LEO) program. Chapter 4 of the Shore Protection Manual (SPM) gives various equations for P_{lg} as a function of wave height, wave period, and breaking wave angle. The present report details how P_{lg} can be calculated using longshore current and breaking wave height data only.

1. Coastal engineering. 2. Littoral processes. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical aid no. 80-3. TC203 .U581ta no. 80-3 627

Walton, Todd L., Jr.

Computation of longshore energy flux using LEO current observations / by Todd L. Walton, Jr. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1980.

[12] p. appendix : ill. : 27 cm. - (Technical aid - U.S. Coastal Engineering Research Center ; no. 80-3). Cover title.

Includes bibliographical references.

Appendix: Derivation for longshore energy flux factor.

A computational technique is presented for the longshore energy flux factor, P_{lg} , using current observations from the Littoral Environment Observation (LEO) program. Chapter 4 of the Shore Protection Manual (SPM) gives various equations for P_{lg} as a function of wave height, wave period, and breaking wave angle. The present report details how P_{lg} can be calculated using longshore current and breaking wave height data only.

1. Coastal engineering. 2. Littoral processes. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical aid no. 80-3. TC203 .U581ta no. 80-3 627

Walton, Todd L., Jr.

Computation of longshore energy flux using LEO current observations / by Todd L. Walton, Jr. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1980.

[12] p. appendix : ill. : 27 cm. - (Technical aid - U.S. Coastal Engineering Research Center ; no. 80-3). Cover title.

Includes bibliographical references.

Appendix: Derivation for longshore energy flux factor.

A computational technique is presented for the longshore energy flux factor, P_{lg} , using current observations from the Littoral Environment Observation (LEO) program. Chapter 4 of the Shore Protection Manual (SPM) gives various equations for P_{lg} as a function of wave height, wave period, and breaking wave angle. The present report details how P_{lg} can be calculated using longshore current and breaking wave height data only.

1. Coastal engineering. 2. Littoral processes. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical aid no. 80-3. TC203 .U581ta no. 80-3 627

Walton, Todd L., Jr.

Computation of longshore energy flux using LEO current observations / by Todd L. Walton, Jr. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1980.

[12] p. appendix : ill. : 27 cm. - (Technical aid - U.S. Coastal Engineering Research Center ; no. 80-3). Cover title.

Includes bibliographical references.

Appendix: Derivation for longshore energy flux factor.

A computational technique is presented for the longshore energy flux factor, P_{lg} , using current observations from the Littoral Environment Observation (LEO) program. Chapter 4 of the Shore Protection Manual (SPM) gives various equations for P_{lg} as a function of wave height, wave period, and breaking wave angle. The present report details how P_{lg} can be calculated using longshore current and breaking wave height data only.

1. Coastal engineering. 2. Littoral processes. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical aid no. 80-3. TC203 .U581ta no. 80-3 627