

AD-A087 396


ARIZONA UNIV TUCSON DEPT OF MATHEMATICS F/G 12/1
ON THE NUMERICAL INTEGRATION OF TWO-POINT BOUNDARY VALUE PROBLE--ETC(U)
JUN 80 J E FLAHERTY, R E O'MALLEY N00014-76-C-0326
30 NL

UNCLASSIFIED

111
111
111



END
DATE
FILMED
9 80
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

LEVEL

Presented at the ...
on Boundary and Interior Layers, Dublin
June 3-6, 1980.

Technical Report

ON THE NUMERICAL INTEGRATION OF TWO-POINT BOUNDARY VALUE PROBLEMS FOR STIFF SYSTEMS OF ORDINARY DIFFERENTIAL EQUATIONS

Joseph E. Flaherty

Department of Mathematical Sciences
Rensselaer Polytechnic Institute
Troy, New York 12181, U.S.A.

and

Robert E. O'Malley, Jr

Department of Mathematics and Program in Applied Mathematics
University of Arizona
Tucson, Arizona 85721, U.S.A.

12

ADA 087396

11 Jul 84

10 11

14 30

Abstract

We consider a class of two-point boundary value problems for systems of the form $\dot{x} = f(x, y, t, \epsilon)$, $\epsilon y' = g_1(x, t, \epsilon) + g_2(x, t, \epsilon)y$ where the matrix $g_2(x, t, 0)$ has a hyperbolic splitting with a fixed number of stable and unstable eigenvalues. Solutions to such boundary value problems can then be expected to have boundary layer behavior near both endpoints in the limit $\epsilon \rightarrow 0$. We obtain uniform asymptotic representations of solutions. Our analysis shows, in particular, how to determine the reduced order boundary value problem satisfied by the limiting interior solution. Orthogonal matrix methods are used to determine this reduced problem and appropriate boundary layer corrections in a computationally effective manner. Numerical experiments with model problems illustrate the possibility of multiple solutions and show how our asymptotic results can be used in combination with the COLSYS code for solving two-point problems via collocation.

Initial value problems for stiff systems of ordinary differential equations are now considered to be relatively tractable numerically (cf. Enright et al. (1975)), though still the subject of current research and difficulty (cf., e.g., Miranker (1979) and Kreiss (1978)). Codes appropriate for two-point problems whose solutions involve rapid changes near the endpoints are not readily available, though these problems occur in many applications. We must study them as a prelude to analyzing more difficult problems with interior layers of rapid transition at unknown locations.

*This work was supported in part by the Air Force Office of Scientific Research under Grant AFOSR-80-0192 and by the Office of Naval Research under Contract N00014-76-C-0326.

This document has been approved for public release and sale; its distribution is unlimited.

445313
80 7 21 13

DTIC
JUL 30 1980

DDC FILE COPY

Specifically, let us consider singular perturbation problems of the form

- (1) $\dot{x} = f(x, y, t, \epsilon)$,
- (2) $\epsilon \dot{y} = g(x, y, t, \epsilon) = g_1(x, t, \epsilon) + g_2(x, t, \epsilon)y$,
- (3) $A(x(0), y(0), \epsilon) = a_1(x(0), \epsilon) + a_2(x(0), \epsilon)y(0) = 0$,
- (4) $B(x(1), y(1), \epsilon) = b_1(x(1), \epsilon) + b_2(x(1), \epsilon)y(1) = 0$,

where x and y are vectors of dimensions m and n , respectively, and where the $n \times n$ matrix $g_2(x, t, 0)$ has $k > 0$ (strictly) stable and $n-k > 0$ (strictly) unstable eigenvalues for all x and for $0 \leq t \leq 1$. We shall assume that there are $q \geq k$ initial conditions (3) and $r = m + n - q \geq n-k$ terminal conditions (4), and that the coefficients in (1)-(4) have asymptotic expansions in ϵ with all terms being smooth functions of their remaining arguments. Limiting solutions of (1)-(4) will be sought as the small positive parameter ϵ tends toward zero.

O'Malley (1980) discusses the behavior of solutions to more non-linear problems. We've simplified that treatment by supposing that the (potentially) stiff differential system (2) and the separated boundary conditions (3)-(4) are linear in the "fast" variable y . Vasil'eva and Butuzov (1978) and O'Malley and Flaherty (1980) discuss problems where $g_2(x, t, 0)$ has a nullspace, while Miranker and Wahba (1976) and Kreiss (1979) discuss problems where $g_2(x, t, 0)$ has purely imaginary eigenvalues. The numerical treatment of certain interior and shock layer problems is considered in Kreiss (1975), Hemker (1977), Osher (1980), and elsewhere.

For the special problem (1)-(4), we can expect bounded solutions to have the limiting form

- (5) $x(t, \epsilon) = X_0(t) + O(\epsilon)$,
- $y(t, \epsilon) = Y_0(t) + \mu_0(t/\epsilon) + \nu_0((1-t)/\epsilon) + O(\epsilon)$,

although unbounded solutions to such problems are also possible (cf. O'Malley (1970) and Ferguson (1975)). Indeed, impulsive endpoint behavior is important in applications to control and systems theory (cf. O'Malley (1978)). Here, we'll ask that $\mu_0(\tau)$ and $\nu_0(\sigma)$ decay to zero as τ and σ , respectively, tend to infinity. Then, μ_0 will provide a rapid transition from $y(0, 0)$ to $Y_0(0)$ near $t = 0$, and ν_0 will allow analogous nonuniform convergence as $\epsilon \rightarrow 0$ at the terminal endpoint. The limiting solution, (X_0, Y_0) , within $(0, 1)$ will necessarily satisfy the limiting system $\dot{X}_0 = f(X_0, Y_0, t, 0)$, $g(X_0, Y_0, t, 0) = 0$, so

- (6) $Y_0(t) = G(X_0, t) \equiv -g_2^{-1}(X_0, t, 0)g_1(X_0, t, 0)$,

Accession For	RTIS GRAMI		
	DOC TAB		
	Unannounced		
	Justification		
By			
Distribution/			
Availability Codes			
Avail and/or			
Dist			
			special
			A

and X_0 must satisfy the m th order nonlinear (and non-stiff) system

$$(7) \quad \dot{X}_0 = F(X_0, t) \equiv f(X_0, G(X_0, t), t, 0) .$$

We need to specify an appropriate set of m boundary conditions for our limiting solution $X_0(t) = x(t, 0)$ within $(0, 1)$. Thus, we seek a "cancellation law" (cf. Wasow (1944) and Harris (1973)) which selects a combination of $q-k$ of the limiting initial conditions (3) and of $r-n+k$ of the terminal conditions (4) to be satisfied by X_0 .

The limiting solution (X_0, Y_0) will not generally satisfy the m limiting boundary conditions, i.e. $A_0(X_0(0)) \equiv A(X_0(0), Y_0(0), 0)$ and $B_1(X_0(1)) \equiv B(X_0(1), Y_0(1), 0)$ will not vanish. We will, however, find m boundary conditions for X_0 of the form

$$(8) \quad \Phi(X_0(0)) \equiv Z_{0+}(X_0(0))A_0(X_0(0)) = 0 ,$$

$$(9) \quad \Psi(X_0(1)) \equiv Z_{1-}(X_0(1))B_1(X_0(1)) = 0 ,$$

for appropriate matrices Z_{0+} and Z_{1-} with ranks $q-k$ and $r-n+k$, respectively. The nonlinear "reduced" two-point problem (7)-(9) can be expected to have no solution, a unique solution, or many solutions.

To begin our numerical discussion, recall that the Schur decomposition (cf., e.g., Stewart (1973)) guarantees the existence of an orthogonal matrix E such that

$$(10) \quad g_2(x, t, 0)E(x, t) = E(x, t) \begin{pmatrix} T_-(x, t) & U(x, t) \\ 0 & T_+(x, t) \end{pmatrix} ,$$

where T_- is $k \times k$ and upper triangular with the stable eigenvalues of g_2 and where T_+ is upper triangular with $n-k$ unstable eigenvalues. The matrix E can be determined numerically through the QR algorithm, i.e. through a sequence of Householder transformations. We actually need much less than this, and would prefer a procedure which only block triangularized g_2 . Partitioning

$$(11) \quad E = [E_- \ E_+] ,$$

after its k th column, note that E_- (E_+) spans the stable (unstable) eigenspace of g_2 , so $P = E_-E_-'$ and $Q = E_+E_+'$ are complementary projections onto these eigenspaces.

In order to have a limiting solution of the form (4), the initial layer correction term $\mu_0(\tau)$ must be a decaying solution of

$$(12) \quad \frac{d\mu_0}{d\tau} = g_2(X_0(0), 0, 0)\mu_0 \equiv G_0\mu_0 ,$$

since $\frac{d\mu_0}{d\tau} = \lim_{\epsilon \rightarrow 0} \epsilon \left(\frac{dy}{dt} - \frac{dy_0}{dt} \right)$ and $\tau = \epsilon t$. Thus

$$(13) \quad \mu_0(\tau) = \exp(G_0 \tau) \mu_0(0),$$

will decay provided $\mu_0(0)$ lies in the stable eigenspace of G_0 , i.e. $\mu_0(0) = E_{0-} c_0$ where $E_{0-} = E_-(X_0(0), 0)$.

Since we are seeking solutions of the form (5), our representations (6) and (13) imply that the q limiting initial conditions (3) take the form $A(x(0,0), y(0,0), 0) = A(X_0(0), Y_0(0) + E_{0-} c_0, 0) = A_0(X_0(0)) + a_2(X_0(0), 0) E_{0-} c_0 = 0$, so $c_0 = -(a_{20} E_{0-})^\dagger A_0$ where the dagger represents a matrix pseudoinverse. Assuming that $a_{20} E_{0-}$ has its maximal rank k , there will be an orthogonal matrix $Z_0 = (Z_{0-}' \ Z_{0+}')$ which reduces it to its row echelon form, i.e. $Z_0 a_{20} E_{0-} = (V_0' \ 0)'$ where V_0 is $k \times k$ and nonsingular. After multiplying by Z_0 , the first k rows of the product provide the unknown (but, due to the flexibility in selecting Z_0 , not necessarily unique) vector

$$(14) \quad \mu_0(0) = -E_{0-} V_0^{-1} Z_{0-}' A_0,$$

needed to specify $\mu_0(\tau)$. The remaining $q-k$ equations of the product provide the initial conditions (8) needed to define the reduced problem for $X_0(t)$.

In analogous fashion, if we suppose that $b_{21} E_{1+} = b_2(X_0(1), 0) \cdot E_+(X_0(1), 1)$ has its maximal rank $n-k$, and let $Z_1 = (Z_{1+}' \ Z_{1-}')$ be such that $Z_1 b_{21} E_{1+} = (V_1' \ 0)'$ is row-reduced, the decaying terminal boundary layer correction term

$$(15) \quad v_0(\sigma) = -\exp(g_2(X_0(1), 1, 0)\sigma) E_{1+} V_1^{-1} Z_{1+}' B_0,$$

becomes (usually nonuniquely) specified as does the set of terminal conditions (9) for $X_0(t)$.

Because the orthogonal matrices E_0 , Z_0 , E_1 , and Z_1 depend on the corresponding m vectors $X_0(0) = x(0,0)$ and $X_0(1) = x(1,0)$, we shall usually have to use Newton's method to actually determine them whenever $g_2(x, t, 0)$, $a_2(x, 0)$, or $b_2(x, 0)$ actually depend on the x variable at $t = 0$ or 1 . [Alternatively, unless the boundary conditions (3) and (4) directly prescribe or determine $x(0, \epsilon)$ or $x(1, \epsilon)$, a shooting technique (cf. Keller (1968)), which involves guessing the endvalue $X_0(0)$ or $X_0(1)$ of the slow $x(t, 0)$ vector and integrating X_0 to the opposite endpoint, could be attempted. Such a procedure would be far better than shooting for the full vector (x, y) , an approach which does not work well for problems with boundary layer behavior at both

endpoints.] Newton's method requires a satisfactory initial guess $X^0(t)$ for $X_0(t)$. We would proceed to determine successive iterates $X^v(t)$ until we achieved numerical convergence. At the v th step, we would calculate an approximation E_p^v to $E(X_0(p), p, 0)$ for $p = 0$ and 1 by applying the QR procedure to $g_2(X^v(p), p, 0)$. One QR step with the matrix Z_p^v will reduce each of $a_2(X^v(0), 0)E_-(X^v(0), 0)$ and $b_2(X^v(1), 0) \cdot E_+(X^v(1), 1)$ to row echelon form. A linear problem for $\delta X^v(t) = X^{v+1}(t) - X^v(t)$ is thereby determined, presuming we can neglect the influence of derivatives of Z_{0-} and Z_{1+} on the selection of the boundary conditions.

To illustrate such problems numerically, we have experimented with the simple harmonic oscillator system

$$(16) \quad \dot{x} = 1 - x, \quad \dot{\epsilon}y_1 = y_2, \quad \dot{\epsilon}y_2 = \alpha^2(x)y_1 + \beta(x),$$

made nonlinear since the coefficients $\alpha(x) = 1 + 2x$ and $\beta(x) = 8x(1-x)$ depend on the slow vector x . The three linear boundary conditions are

$$(17) \quad x(0) + y_1(0) = 0, \quad -bx(0) + y_2(0) = 0, \quad \text{and} \quad x(1) + y_1(1) = 0.$$

Since g_2 has one positive and one negative eigenvalue whenever α is nonzero, we can expect the limiting solution within $(0, 1)$ to be determined by a cancellation law which retains only one initial condition. Thus, the reduced problem will consist of the limiting system

$$(18) \quad \dot{x}_0 = 1 - x_0, \quad y_{20} = 0, \quad \alpha^2(x_0)y_{10} + \beta(x_0) = 0,$$

and some combination of $x_0(0) + y_{10}(0)$ and $-bx_0(0)$ set to zero.

The E matrix for this example is explicitly determined as

$$E(x, t) = \frac{1}{\sqrt{1 + \alpha^2(x)}} \begin{pmatrix} 1 & |\alpha(x)| \\ -|\alpha(x)| & 1 \end{pmatrix}, \quad \text{and we can take } Z_0 \text{ to be any}$$

multiple of $E'(X_0(0), 0)$. Thus, the initial condition (8) appropriate for the reduced system (19) is

$$(20) \quad |\alpha(x_0(0))| (x_0(0) + y_{10}(0)) - bx_0(0) = 0.$$

Rewriting this as a function of $x_0 = X_0(0)$ alone, x_0 must satisfy a cubic equation with the three roots $x_0 = 0$ and $\frac{1}{4}[b \operatorname{sgn} \alpha_0 - 6 \pm ((b \operatorname{sgn} \alpha_0 - 4)^2 + 48)^{1/2}]$ selected so that $\operatorname{sgn} \alpha_0 = \pm 1$ according to the sign of $1 + 2x_0$. (For $b = 2$, the corresponding initial values are $x_0 = 0, 0.803, \text{ and } -4.29$.) Values of x_0 must be avoided for which the corresponding $\alpha(X_0) = 3 + 2(x_0 - 1)e^{-t}$ has a zero within $0 \leq t \leq 1$.

Since $X_0(0) + Y_{10}(0) = -bX_0(0)/(1 + 2X_0(0))$ neither of the separate limiting initial conditions $\Lambda_0(X_0(0)) = 0$ will be satisfied unless $bX_0(0) = 0$. Only then, will the initial boundary layer term $\mu_0(\tau)$ be trivial. Unless $Y_{10}(1) = -X_0(1) = -1 - (x_0 - 1)e^{-1}$, the terminal boundary layer term $v_0(\sigma)$ is also nontrivial.

We are guaranteed that the three "outer" solutions (X_0, Y_0) so obtained provide limiting solutions within $(0,1)$ for corresponding actual solutions in the limit $\epsilon \rightarrow 0$ (cf. Hoppensteadt (1971)). Moreover, adding the corresponding boundary layer corrections $\mu_0(t/\epsilon)$ and $v_0((1-t)/\epsilon)$ (cf. (13) and (16)) will improve the outer approximation $Y_0(t)$ in the endpoint boundary layers.

One would expect our approximation (5) to be a good first guess to provide a two-point boundary value solver. This is not necessarily true, however, because of stiffness as $\epsilon \rightarrow 0$. Our experience, instead, suggests using our (then crude) asymptotic solution as a first guess for problems where ϵ is only moderately small and then gradually reducing ϵ . This scheme allows mesh points to be gradually redistributed in boundary layer regions of rapid transition, and provides good numerical results.

We used the COLSYS code of Ascher et al. (1979), but note that more specialized methods for singular perturbation problems might also be tried (cf. Flaherty and Mathon (1980)). We calculated three distinct solutions to our boundary value problem for $b = 0, 1, 2$, and -2 following the procedure: The asymptotic solution and a uniform mesh was used as an initial guess for $\epsilon = 10^{-1}$. The ϵ -sequence $10^{-1}, 10^{-2}, 10^{-4}$, and 10^{-6} was used, with the previously computed solution and mesh used as the initial approximation. If the solution failed to converge or used more than 222 subintervals, $\epsilon = 10^{-3}$ and/or $\epsilon = 10^{-5}$ values were inserted into the sequence. Calculations used both cubic and quintic splines, and error tolerances of 10^{-6} for x and y_1 and either 10^{-3} or 10^{-6} for y_2 . In general, good accuracy was obtained with both cubic and quintic splines, though calculation time was generally less with the lower order polynomials. Alternative solutions with slightly different initial guesses took much more computing time. For $b = -2$ and $X_0(0) = -2.80$, we have a turning point since $\alpha(X_0(0.930)) = 0$. Actual solutions become unbounded there as $\epsilon \rightarrow 0$, though for moderate values of ϵ (like 10^{-2}) COLSYS could provide a corresponding solution with difficulty. For $b = 0$, and $X_0(0) = -3.5$, α has a zero above $t = 1$. This forces the boundary layer jump $|Y_{10}(0) - y(1,0)|$ to be large (89.8 compared to 0.4 and 0.6 for the other roots $X_0(0) = 0$ and 0.5), yet we get good results for $\epsilon = 10^{-6}$. As a typical example, we display our results (Figures 1, 2, and 3) for

$b = 2$ and tabulate our results (Table 1) for cubic splines. The column headings for Table 1 are: (1) ϵ , (2) the number of subintervals used by COLSYS to solve the problem with the given tolerances, (3) and (4) the number of subintervals in the right (left) boundary layer, defined as $t \leq 10\epsilon$ ($t \geq 1 - 10\epsilon$), (5) the percentage of subintervals in the boundary layers, (6) time to perform the calculation, excluding input/output, and (7) accumulated CP time on an IBM 3033.

References

1. U. Ascher, J. Christiansen, and R. D. Russell (1979), "COLSYS—a collocation code for boundary value problems," Lecture Notes in Computer Science 76, Springer-Verlag, Berlin, 164-185.
2. W. H. Enright, T. E. Hull, and B. Lindberg (1975), "Comparing numerical methods for stiff systems of ODE's," BIT 15, 10-48.
3. W. E. Ferguson, Jr., A Singularly Perturbed Linear Two-Point Boundary Value Problem, doctoral dissertation, California Institute of Technology, Pasadena, 1975.
4. J. E. Flaherty and W. Mathon (1980), "Collocation methods for singularly perturbed boundary value problems," these Proceedings.
5. W. A. Harris, Jr. (1973), "Singularly perturbed boundary value problems revisited," Lecture Notes in Mathematics 312, Springer-Verlag, Berlin, 54-64.
6. P. W. Hemker (1977), A Numerical Study of Stiff Two Point Boundary Problems, Mathematisch Centrum, Amsterdam.
7. F. Hoppensteadt (1971), "Properties of solutions of ordinary differential equations with a small parameter," Comm. Pure Appl. Math. 24, 807-840.
8. H. B. Keller (1968), Numerical Methods for Two-Point Boundary Value Problems, Blaisdell, Waltham.
9. H.-O. Kreiss (1975), "Difference approximations for singular perturbation problems," Numerical Solutions of Boundary Value Problems for Ordinary Differential Equations, A. K. Aziz, editor, Academic Press, New York.
10. H.-O. Kreiss (1978), "Difference methods for stiff ordinary differential equations," SIAM J. Numerical Analysis 15, 21-58.
11. H.-O. Kreiss (1979), "Problems with different time scales for ordinary differential equations," SIAM J. Numerical Analysis 16, 980-998.
12. W. L. Miranker (1979), Numerical Methods for Stiff Equations and Singular Perturbation Problems, IBM Research Center, Yorktown Heights.

13. W. L. Miranker and G. Wahba (1976), "An averaging method for the stiff highly oscillatory problem," Math. Comp. 30, 383-399.
14. R. E. O'Malley, Jr. (1970), "Singular perturbation of boundary value problems for a system of nonlinear differential equations," J. Differential Equations 8, 431-447.
15. R. E. O'Malley, Jr. (1978), "Singular perturbations and optimal control," Lecture Notes in Mathematics 680, 170-218.
16. R. E. O'Malley, Jr. (1980), "On multiple solutions of singularly perturbed systems in the conditionally stable case," Proceedings, Advanced Seminar on Singular Perturbations and Asymptotics, Mathematics Research Center, Madison.
17. R. E. O'Malley, Jr. and J. E. Flaherty (1980), "Analytical and numerical methods for nonlinear singular singularly-perturbed initial value problems," SIAM J. Appl. Math. 38, 225-248.
18. S. Osher (1980), "Nonlinear singular perturbation problems and one-sided difference schemes," preprint, Mathematics Department, University of California, Los Angeles.
19. G. W. Stewart (1973), Introduction to Matrix Computations, Academic Press, New York.
20. A. B. Vasil'eva and V. F. Butuzov (1978), Singularly Perturbed Equations in the Critical Case, Moscow State University. (Translated as MRC Technical Summary Report 2039, Mathematics Research Center, Madison, 1980).
21. W. Wasow (1944), "On the asymptotic solution of boundary value problems for ordinary differential equations containing a parameter," J. of Math. and Physics 23, 173-183.

TABLE

 $X_0(0) = 0:$

ϵ	no. subints.	no. sub. $t \leq 10\epsilon$	no. sub. $t \geq 1-10\epsilon$	% sub. in BL	CP time (sec.)	acc. CP time
10^{-1}	80	-	-	-	.589	.589 [†]
10^{-2}	80	23	25	60	.650	1.239
10^{-4}	116	14	50	55	1.816	3.055
10^{-6}	134	15	71	64	1.668	4.723

 $X_0(0) = 0.803:$




10^{-1}	80	-	-	-	.551	.551
10^{-2}	160	78	62	88	1.216	1.767
10^{-3}	128	59	51	86	1.165	2.932*
10^{-4}	128	53	49	80	1.280	4.212
10^{-5}	182	75	67	78	2.152	.6.364*
10^{-6}	196	83	75	81	2.728	9.092

 $X_0(0) = -4.29:$

10^{-1}	160	-	-	-	1.344	1.344
10^{-2}	142	52	47	70	1.932	3.276
10^{-4}	196	69	57	64	4.331	7.607
10^{-6}	222	87	77	74	8.599	16.206

[†]When the tolerance on y_2 was changed from 10^{-3} to 10^{-6} the calculation with $\epsilon = 10^{-1}$ used 222 subintervals and took 2.483 sec.

*Solution jumped to $X_0(0)$ solution without these values of ϵ .



Figures 1, 2, and 3:

Solution $y_1(t)$ for the third order problem (16)-(17) with $b = 2$ and $X_0(0) = 0$, 0.803 , and -4.29 , respectively.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Numerical integration of two-point boundary value problems for stiff systems of ordinary differential equations.		5. TYPE OF REPORT & PERIOD COVERED Technical Report, July 1980
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Flaherty and R.E. O'Malley, Jr.		8. CONTRACT OR GRANT NUMBER(s) N00014-76-C-0326
9. PERFORMING ORGANIZATION NAME AND ADDRESS Department of Applied Mathematics Mathematics Bldg., University of Arizona Tucson, Arizona 85721		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 041-466
11. CONTROLLING OFFICE NAME AND ADDRESS Mathematics Branch Department of Naval Research Washington, Virginia		12. REPORT DATE July 1980
13. CONTROLLING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 10
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. ABSTRACT STATEMENT (of this Report)
 Approved for public release. Distribution unlimited.

17. ABSTRACT STATEMENT (of the abstract entered in Block 20, if different from Report)

18. KEYWORD(S) AND ENTRY NOTES

19. SUBJECT TERMS (Continue on reverse side if necessary and identify by block number)
 Linear Perturbations, Numerical Methods, Nonlinear Boundary Value Problems, Stiff Equations

20. SUMMARY (Continue on reverse side if necessary and identify by block number)
 Two-point boundary value problems for systems $\dot{x} = f(x, y, t, \epsilon)$, $\epsilon \dot{y} = g_1(x, y, t, \epsilon) + g_2(x, t, \epsilon)y$ where the matrix $g_2(x, t, 0)$ has a hyperbolic splitting with a fixed number of stable and unstable eigenvalues. Solutions can then have boundary layer behavior near both endpoints as $\epsilon \rightarrow 0^+$. We obtain uniform asymptotic representations of solutions. Our analysis shows how to determine the reduced problem for the limiting interior solution. Orthogonal matrix method used to find this reduced problem and appropriate boundary layer corrector in a computationally effective manner. Numerical experiments illustrate the accuracy of multiple solutions and show how our asymptotic results can be used in conjunction with the COLSYS code.