

AD-A089 567

MARK RESOURCES INC MARINA DEL REY CA
TIMING FOR EXTENDED TARGET SIMULATION, (U)
JAN 78 R L MITCHELL
MRI-149-6

F/6 14/2

UNCLASSIFIED

DAAK40-78-C-0031
NL

1 of 1
AD &
Order

END
DATE
FILMED
10-80
DTIC

AD A089567

LEAD III (2)



RFSS

TIMING FOR EXTENDED TARGET SIMULATION

TECH NOTE 105-033

4 JAN 78

PREPARED FOR: RF SYSTEMS BRANCH (DRDMI-TDR)
SYSTEMS SIMULATION DIRECTORATE
TECHNOLOGY LABORATORY
US ARMY MIRADCOM
REDSTONE ARSENAL, AL 35809

DARK 40-7PC-0031

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

PREPARED BY: DR R. L. MITCHELL
MARK RESOURCES, INC.
4676 ADMIRALTY WAY
SUITE 303
MARINA DEL REY, CA 90291

DTIC ELECTE
SEP 26 1980

A

80 9 22 141

21172

DDC FILE COPY



TIMING FOR EXTENDED TARGET SIMULATION

R. L. Mitchell

MRI Report 149-6 ✓

4 January 1978

Several timing runs were conducted on the CDC Cyber 73 system for the baseline extended target simulation program. The results for FORTRAN are *

Geometry Update	ETGEO: .42 + .19N (msec)	(CDC)
Glint & Doppler Modulation	ETGDM: .75 + .61N (msec)	(CDC)

where N is the number of visible scatterers. The library routines of ATAN2, SQRT, SIN, and COS were replaced by dummy routines so the above times would be representative of the use of fast table lookup algorithms for these functions.

The timing is dominated by the Doppler update in ETGDM, the subroutine that should also be called more frequently than ETGEO. For a 20 msec update on TARGEO and a 10 msec update on ETGDM, we can accommodate about 12 scatterers, as

ETGEO:	1.35 msec/10 msec
ETGDM:	8.07 msec/10 msec
both :	9.42 msec/10 msec

If both subroutines are implemented on the Datacraft/6, one can anticipate about a factor of 3 slower performance. Thus about 4 scatterers can be accommodated.)

The glint and Doppler modulation (ETGDM) is best done on the AP120B. Assuming a conservative factor of 20 faster performance for this processor, we now have

* These subroutines formerly were named TARGEO and TARGDM, respectively.

ETGEO: 1.26 + .57N (msec) (Datacraft)
 ETGDM: .038 + .03N (msec) (AP120B)

The limiting factor is now ETGEO, but we do not have to update this sub-routine very frequently. Assuming a 25 msec update on ETGEO and a 5 msec update on ETGDM, which is likely to be a realistic situation, we can now accommodate about 40 scatterers as

ETGEO: 24.1 msec/25 msec
 ETGDM: 1.2 msec/ 5 msec

The last loop in ETGEO (DO-20) could also be implemented on the AP120B. For this situation we have

ETGEO: .42 + .01N (msec) (Datacraft/AP120B)
 ETGDM: .038 + .03N (msec) (AP120B)

Assuming the same 5 msec update on ETGEO and ETGDM, we could accommodate 150 scatterers as

ETGEO: 1.9 msec/5 msec
 ETGDM: 4.5 msec/5 msec

Accession For	
NTIS GARDI	<input checked="" type="checkbox"/>
DDC RAB	<input type="checkbox"/>
Unclassified	<input type="checkbox"/>
Justification	
By <i>TN-105-29</i>	
Distribution/	
Availability Codes	
Dist	Available/or special
<i>A</i>	