

AD-A096 567 ADVISORY GROUP FOR AEROSPACE RESEARCH AND DEVELOPMENT--ETC F/6 1/3
APPLICATION OF A STRUCTURAL OPTIMIZATION PROCEDURE FOR ADVANCED--ETC(U)
JAN 81 H GOEDEL, G SCHNEIDER
UNCLASSIFIED AGARD-R-691 NL

1 of 1
AD-A
1000000



END
4-81

LEVEL

AGARD-R-691

AGARD-R-691

AGARD

ADVISORY GROUP FOR AEROSPACE RESEARCH & DEVELOPMENT

7 RUE ANCELLE 92200 NEUILLY SUR SEINE FRANCE

AD A 096567

AGARD REPORT No. 691

Application of a Structural Optimization Procedure for Advanced Wings

This document has been approved
for public release and sale; its
distribution is unlimited.

DTIC
ELECTE
MAR 19 1981
S D F

NORTH ATLANTIC TREATY ORGANIZATION



DISTRIBUTION AND AVAILABILITY
ON BACK COVER

FILE COPY

81 3 18 041

14

AGARD-R-691

NORTH ATLANTIC TREATY ORGANIZATION
ADVISORY GROUP FOR AEROSPACE RESEARCH AND DEVELOPMENT
(ORGANISATION DU TRAITE DE L'ATLANTIQUE NORD)

11 Jan 81

12/22/

AGARD Report No.691

6) APPLICATION OF A STRUCTURAL OPTIMIZATION PROCEDURE
FOR ADVANCED WINGS

by

10) H. Gödel and G. Schneider
Messerschmitt-Bölkow-Blohm GmbH
Postfach 80 11 60
D-8000 München 80
West Germany

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

Paper presented at the 51st Meeting of the AGARD Structures and Materials Panel
held in Aix-en-Provence, France on 14-19 September 1980.

400042

mt

THE MISSION OF AGARD

The mission of AGARD is to bring together the leading personalities of the NATO nations in the fields of science and technology relating to aerospace for the following purposes:

- Exchanging of scientific and technical information;
- Continuously stimulating advances in the aerospace sciences relevant to strengthening the common defence posture;
- Improving the co-operation among member nations in aerospace research and development;
- Providing scientific and technical advice and assistance to the North Atlantic Military Committee in the field of aerospace research and development;
- Rendering scientific and technical assistance, as requested, to other NATO bodies and to member nations in connection with research and development problems in the aerospace field;
- Providing assistance to member nations for the purpose of increasing their scientific and technical potential;
- Recommending effective ways for the member nations to use their research and development capabilities for the common benefit of the NATO community.

The highest authority within AGARD is the National Delegates Board consisting of officially appointed senior representatives from each member nation. The mission of AGARD is carried out through the Panels which are composed of experts appointed by the National Delegates, the Consultant and Exchange Programme and the Aerospace Applications Studies Programme. The results of AGARD work are reported to the member nations and the NATO Authorities through the AGARD series of publications of which this is one.

Participation in AGARD activities is by invitation only and is normally limited to citizens of the NATO nations.

The content of this publication has been reproduced
directly from material supplied by AGARD or the authors.

Published January 1981

Copyright © AGARD 1981
All Rights Reserved

ISBN 92-835-1379-7



*Printed by Technical Editing and Reproduction Ltd
Harford House, 7-9 Charlotte St, London, W1P 1HD*

PREFACE

During its Meeting in Aix-en-Provence, in Fall 1980, a paper was presented by Mr H.Gödel to the Sub-Committee on Aeroelasticity of the Structures and Materials Panel on the use of structural optimization methods to obtain practical minimum-weight designs which meet the constraints of loads, stresses, buckling, deflections, divergence and flutter. Impressive results were exhibited.

The excellent presentation of this advanced application of optimization procedures was welcomed by the Sub-Committee as being a very important contribution to its activities in Aeroelasticity. Its publication as an AGARD Report will help dissemination of new methods and techniques amongst the NATO community.

G.COUPRY
Chairman, Sub-Committee
on Aeroelasticity

APPLICATION OF A STRUCTURAL OPTIMIZATION PROCEDURE FOR ADVANCED WINGS

by

H. Gödel
Aerospace Engineer, Aeroelastic Branch
and

G. Schneider
Aerospace Engineer, Aeroelastic Branch
MESSERSCHMITT-BÖLKOW-BLOHM GMBH
Airplane Division
P.O.Box 80 11 60, 8000 Munich 80
W.-Germany

SUMMARY

A computer software system called ASAT exists at MBB which allows an automatic design of minimum weight structures. In this paper, the application of this system to several structures is described.

It is shown that a structural optimization system can be very useful in the preliminary design of an airplane, especially when it consists of several modules such as static load calculation, deformations and stress calculation by finite elements, static aeroelastics, weight calculation, unsteady aerodynamic forces, vibration calculation, flutter calculation, flutter and strength optimization which all can be used separately and independently.

INTRODUCTION

For structural design of modern airplanes, the use of an optimization computer program is mandatory in order to achieve a minimum weight structure whilst taking into account both strength and aeroelastic requirements.

During a cooperation program [1] with the U.S. Air Force Flight Dynamics Laboratory, the MBB company exchanged several computer programs in return for receiving the FASTOP-computer-system [2]. This exchange took place in 1977, and for the last three years, the structural dynamic group of MBB has further refined the program and also added a static aeroelastic part to it. This new system is now called ASAT. (Automatische Struktur-Auslegung für Tragflächen). This paper deals with the application of ASAT.

Several structural examples are treated in this paper:

- . A simplified structure to show the capabilities of the system (the analysis of this structure was partly sponsored by the ZTL-Research Program of the German Ministry of Defense).
- . Aeroelastic efficiency calcs for fin and rudder.
- . Structural layout of a carbon fibre composite Delta wing.

TECHNICAL APPROACH

The ASAT-program is able to size cantilevered or free-free surface structures for flutter speed or strength constraints. It is based on a finite element method. Buckling of elements is considered. Also minimum skin gauges can be a limiting factor for sizing. The aeroelastic efficiencies are calculated directly by using the aerodynamic influence coefficients - no iteration procedure is applied. The mathematical approach can be found in [3] and [4].

SIZING OF A SIMPLIFIED METAL WING STRUCTURE FOR STRENGTH AND FLUTTER CONSTRAINTS

In order to try out the computer system, a simplified structural model was chosen (Fig. 1). The thickness to chord ratio is constant 5 %. The surface is cantilevered.

The conditions which are sizing the skin thickness against buckling are presented in Fig. 2. Two aerodynamic load cases were defined:

Load case 1: $Ma = 0.9$, $q = 5.52 \frac{N}{cm^2}$, $\alpha = 8^\circ$

Load case 2: $Ma = 1.4$, $q = 8.28 \frac{N}{cm^2}$, $\alpha = 5.5^\circ$





Fig. 1 GEOMETRY AND STRUCTURAL IDEALIZATION Fig. 2 ALLOWABLE COMPRESSIVE STRESS σ_x AS FUNCTION OF NORMAL FORCE FLOW N_x AND SHEAR FLOW Q

The stationary pressure distributions as calculated by the computer program are shown in Fig. 3. A transformation procedure is implemented which transfers the aerodynamic loads from the panel center to the structural grid points.




Fig. 3 STATIONARY PRESSURE DISTRIBUTIONS

The optimization process is explained best by Table 1 and 2.

Thicknesses and flutter derivatives for characteristical structural elements for

the upper and lower skin are printed for successive steps of the optimization procedure. Initially, a constant skin thickness is provided. After three steps of the SOP-module (Struktur Optimierung) a fully stressed design is reached where the last weight change is only 0.7 kg. This is plotted in Table 1.

Weight	Initial weight for constant skin thickness	Iteration Step		
		1	2	3
kg	51.4	56.7	55.0	54.3

TABLE 1 Weight for structural optimization procedure (SOP)

In Table 2, the iteration procedure is shown for selected structural elements. It starts with the skin thicknesses of step 3 of SOP and then it iterates between FOP (Flatter Optimierung) to fulfill the required flutter speed with a minimum weight increase and still keeps the fully stressed design by running through SOP.


													
		UPPER COVER SKIN						LOWER COVER SKIN					
		THICKNESS mm						THICKNESS mm					
Element	Start Value	SOP	FOP	SOP	FOP	SOP	FOP	SOP	FOP	SOP	FOP	SOP	FOP
4	2.00	0.76	0.76	0.76	0.96	0.96	0.99	0.99	0.96	0.96	0.96	0.96	0.96
6	2.00	2.78	2.73	2.64	2.63	2.58	2.58	2.56	2.56	2.56	2.56	2.56	2.56
9	2.00	1.58	1.91	1.91	2.96	2.96	3.73	3.73	3.95	3.95	3.95	3.95	3.95
10	2.00	2.46	2.34	2.62	2.95	2.95	3.12	3.12	2.97	2.95	2.95	2.95	2.95
11	2.00	1.72	1.76	1.85	2.72	2.72	3.43	3.43	3.69	3.69	3.69	3.69	3.69
12	2.00	2.13	2.17	2.29	3.05	3.05	3.53	3.53	3.51	3.51	3.51	3.51	3.51
13	2.00	2.18	2.28	2.52	3.13	3.13	3.20	3.20	3.13	3.13	3.13	3.13	3.13
24	2.00	5.84	5.89	5.88	5.88	5.87	5.86	5.85	5.85	5.85	5.85	5.85	5.85
28	2.00	5.39	5.59	5.47	5.47	5.30	5.23	5.16	5.13	5.12	5.12	5.12	5.12
29	2.00	1.67	1.54	1.53	1.54	1.60	1.64	1.67	1.69	1.69	1.69	1.69	1.69
32	2.00	7.82	8.00	7.94	7.94	7.81	7.76	7.70	7.68	7.68	7.68	7.68	7.68
FLUTTER VELOCITY DERIVATIVES kts/kg													
4		10.38	13.41	11.09	10.92	<u>11.30</u>							
6		2.52	4.09	5.32	5.60	<u>5.58</u>							
9		17.82	20.50	16.42	13.79	<u>13.16</u>							
10		7.92	10.85	11.56	10.85	<u>10.97</u>							
11		12.92	18.47	16.49	14.14	<u>13.58</u>							
12		10.39	15.23	13.78	12.13	<u>12.08</u>							
13		13.46	13.22	10.79	10.32	<u>10.23</u>							
24		0.27	0.62	1.13	1.32	<u>1.32</u>							
28		-0.29	-0.15	0.14	0.26	<u>0.27</u>							
29		0.90	1.58	2.29	2.51	<u>2.46</u>							
32		-0.50	-0.46	-0.34	-0.29	<u>-0.28</u>							
FLUTTER VELOCITY DERIVATIVES kts/kg													
36		10.19	13.61	10.98	10.96	<u>11.29</u>							
38		12.37	12.82	9.96	9.42	<u>9.14</u>							
41		100.04	27.81	13.92	11.74	<u>12.23</u>							
42		50.07	26.09	15.30	12.85	<u>12.63</u>							
43		72.06	28.60	15.03	12.68	<u>12.55</u>							
44		49.40	27.31	15.09	12.69	<u>12.49</u>							
45		72.78	18.68	11.87	11.30	<u>12.01</u>							
56		1.93	2.91	4.10	4.42	<u>4.41</u>							
60		-1.01	-0.24	0.96	1.36	<u>1.35</u>							
61		6.37	8.82	11.57	12.03	<u>12.16</u>							
64		-1.25	-1.11	-0.81	-0.66	<u>-0.63</u>							
FINAL STRUCTURAL WEIGHT 64.6 kg													

TABLE 2 Optimization Progress for selected structural elements

The elements most important for flutter speed (stiffness change) are underlined. It is interesting to note that for instance the upper skin is mostly designed by strength requirements whereas the lower skin thickness can be used to raise the flutter speed by a stiffness change. After a constant flutter derivative for each important flutter element is reached then the process is finished. Graphically, this is shown in Fig. 4.




Fig. 4 RESULTS OF REDESIGN STUDY

A flutter speed is calculated for the initial fully stressed design (FSD) being 700 kts. After five iteration steps, the desired flutter speed of 900 kts is reached with an increase of less than 3 % of total weight. The loss of flutter speed from 2' to 2 and 3' to 3 can be explained this way: The program uses the old vibration modes to get from 1 to 2', but these modes change a little which is reflected in point 2. When the structural changes are smaller and smaller then the modes stay practically the same (see point 4', 4 and 5). In Fig. 5, the elastic deformations before and after optimization are shown.

In Fig. 6, the vibration mode shapes are depicted. From this picture, it can be seen that the mode shapes stay almost the same, and only the frequencies are changed.




FIG. 5 DEFORMATION OF THE STRUCTURE DUE TO LOAD CASE 1 AND 2




FIG. 6 NORMAL MODES, CALCULATED AFTER INITIAL FSD AND AFTER FLUTTER OPTIMIZATION




FIG. 7 RESULTS OF FLUTTER ANALYSIS

The flutter speed increase stems mainly from the frequency separation of mode 1 (bending) and mode 2 (torsion) as shown in Fig. 7.

The program FOP has also the possibility to increase flutter speed by mass balancing. Seven mass positions at the outer wing to apply balance masses were provided but the flutter derivatives were so small that this possibility was neglected automatically.

The final results are presented in Fig. 8 and 9 as skin thicknesses for the upper and lower skin before and after optimization. Also the stress ratios - which should be unity when fully stressed - and the flutter derivatives are shown.




FIG. 8 REDESIGN RESULTS FOR UPPER COVER SKIN




FIG. 9 REDESIGN RESULTS FOR LOWER COVER SKIN

The normal force flow for load case 2 is shown in Fig. 10 as a typical example of the strength calculation.




Fig. 10 NORMAL FORCE FLOW IN SPAR DIRECTION FOR LOAD CASE 2

Comparisons for stress calculations with different elements are presented in Fig. 11. This figure proves that with a relative crude element and mesh system good correlation with analyses using more sophisticated elements - such as NASTRAN (triangular membrane with linearly varying stress) - can be achieved. This is an important result because the cruder the idealization can be, the less computer time is needed to run the optimization program.





Fig. 11 STRESSES FOR DIFFERENT ELEMENT TYPES AND MESH SYSTEMS

Fig. 12 IDEALIZATION OF A CFC-VERTICAL TAIL

AEROELASTIC EFFICIENCY CALCULATION FOR A CFC FIN AND RUDDER

For the structural design of fin and rudder, stiffness considerations are overriding and not strength. Also the size of these surfaces is influenced by their aeroelastic efficiency. The program ASAT was used to calculate the efficiency for a fin and rudder of a modern fighter plane. The aeroelastic deformations were calculated directly without using any iteration procedure which is possible because a full matrix of aerodynamic influence coefficients is produced by the aerodynamic module of ASAT.

The properties of CFC were introduced by the stress-strain law.

Fig. 12 shows the structural idealization for a CFC-fin and rudder. Fig. 13 shows the deflections of the structure due to a steady load case.




Fig. 13 DEFLECTION DUE TO A STATIC LOAD

Fig. 14 presents relatively large changes in the pressure distributions due to elastic fin deformations especially for the subsonic case.




Fig. 14 PRESSURE DISTRIBUTIONS AND DEFORMATIONS AT SECTION A-A DUE TO A FIN ANGLE OF ATTACK β




Fig. 15 PRESSURE DISTRIBUTIONS AND DEFORMATIONS AT SECTION A-A DUE TO A RUDDER ROTATION ANGLE ξ

Fig. 15 is depicting even larger effects on the fin pressure distribution due to rudder angle when elastic effects are considered.

Fig. 16 and Fig. 17 present the aeroelastic effectiveness of fin and rudder, and it is shown that the requirements which were postulated by the aerodynamic department can almost be fulfilled.




Fig. 16 VERTICAL TAIL AEROELASTIC EFFECTIVENESS




Fig. 17 RUDDER EFFECTIVENESS

STRUCTURAL OPTIMIZATION OF A CFC-DELTA-WING

For a preliminary design of a CFC-Delta-Wing, a structural optimization was performed to achieve a minimum weight structure by retaining sufficient control surface effectiveness. An additional constraint - a certain amount of wing twist off at a high g-manoeuvre - had to be fulfilled as well [57].

The direction of the laminates were selected in prestudies by the MBB-stress department which have accumulated a lot of experience with the CFC material over the last years [67].

Despite the fact that a huge amount of papers has been published lately about aeroelastic tailoring with CFC, it is our opinion that the possibilities for laying the laminates are limited for two major reasons:

- . Material properties are only known for specific composites.
- . Production considerations are dominating.

For these reasons, we took the preselected material properties [77] and fed it into the ASAT program as

$$\begin{Bmatrix} \sigma_x \\ \sigma_y \\ \tau_{xy} \end{Bmatrix} = \begin{bmatrix} A_{11} & A_{12} & A_{13} \\ A_{21} & A_{22} & A_{23} \\ A_{31} & A_{32} & A_{33} \end{bmatrix} \cdot \begin{Bmatrix} \epsilon_x \\ \epsilon_y \\ \gamma_{xy} \end{Bmatrix}$$

The structure is practically idealized as a thin sandwich plate with the stress carrying capability in the skin. Deformation results for this model were compared with results calculated by the stress group who had a much finer grid, and good correlation was achieved.

Calculations were performed for the idealized structure of Fig. 18 and Fig. 19.




Fig. 18 IDEALIZED DELTA WING FOR STRUCTURAL DESIGN STUDIES




Fig. 19 WING BOX STRUCTURE





Fig. 20 COMPARISON OF DIFFERENT WING BOX IDEALIZATION

The structure is represented as follows:

Grid points:	106
Degrees of freedom:	278
Membranes:	74
Rod elements:	55
Shear panels:	67

The final result of these calcs were skin thicknesses adjusted to strength and buckling requirements and the effectivenesses for the control surfaces.

Fig. 20 shows the stress group grid and that one used by ASAT. Only from looking at these pictures, one can imagine that local stress concentrations - at attachments for instance - cannot be accounted for by the ASAT-idealization. For this reason, it is always necessary to follow up the optimization process with a normal stress analysis to confirm the results.

DETERMINATION OF LOADS

Two load cases were chosen according to the definitions of our loads group $\bar{87}$:

- Load case 1: Symmetrical high g pullout
This is a manoeuvre case in the subsonic regime giving the highest shear force and bending moment at the wing root.
- Load case 2: This is a roll case in the supersonic flight regime where the aerodynamic center of pressure is backward. This case is not symmetrical (initiated by the ailerons) but was applied to both wings symmetrically.

In order to make the loads calculated by ASAT comparable to the loads from our loads group, the wing attitude and aileron angles are somewhat different - the presence of a canard had to be reflected which the ASAT program is not able to consider at the moment.

RESULTS OF DEFORMATION CALCULATIONS WITH ASAT AND COMPARISONS

After establishing the structural model and the loads, deformation calculations were performed which match the stress group results very well. Implicitly, this is also a prove that comparable loads were used. Fig. 21 shows the vertical deflection along the wing span for load case 1.




Fig. 21 COMPARISON OF WING DEFLECTIONS

In Fig. 22, the wing twist angle along the span is depicted. The 4° twist off angle at the wing tip fulfills the requirement coming from aerodynamic performance.




Fig. 22 COMPARISON OF WING TWIST ANGLE α

In Fig. 23, the internal skin load distribution for load case 1 is presented. From this figure, it can be deduced that extreme care must be taken to accommodate such high local forces into the two rear CFC attachments fitted to the fuselage.




Fig. 23 INTERNAL SKIN LOAD DISTRIBUTION




Fig. 24 WEIGHT OPTIMIZED SKIN THICKNESS
ACCORDING TO STRENGTH CRITERIA (SUB-
SONIC AND SUPERSONIC LOAD CASES)

RESULTS OF THE OPTIMIZATION PROCESS

After three steps of the SOP program, the skin weight stayed almost constant. The final weight was

Step	Skin Weight [kg]
1	221.7
2	164.4
3	163.9
4	164.1

practically reached after the first step but the convergence had to be proven.

The weight saving amounts to about 5 % of the total wing weight which is a very considerable achievement.

Fig. 24 shows the skin thickness distributions before and after structural optimization.




Fig. 25 WING-FLAP CONTROL EFFECTIVENESS

The aeroelastic efficiencies for the aileron are shown in Fig. 25 together with the effectiveness definition to fulfill the roll requirement. For the supersonic case where the roll manoeuvre is initiated with the two inner flaps only we have higher than required efficiency. For the subsonic pullout manoeuvre, the efficiency for all four flaps is somewhat below the requirement but it still is sufficient.

CONCLUSIONS

In this paper, it was shown that the very useful structural optimization program ASAT exists at MBB which was used for several practical design studies.

The major advantage of the system is that it merges several airplane designing disciplines such as:

- . static loads
- . stress calculations
- . unsteady aerodynamics
- . flutter calculations
- . static aeroelastics
- . weights

For this reason, communication errors are avoided.

Due to the versatility of the computer system, separate modules of it can be used solely, and it is also possible to make cross checks with results from other structural design groups. CFC structures can be treated efficiently, and the design goals postulated from aerodynamic performance could be reached.

REFERENCES

- 1 SENSBURG O., HÖNLINGER H., NOLL T. E.
 Active Flutter Suppression on a F-4F Aircraft with External Stores Using Already
 Existing Control Surfaces
 Paper presented at 21st Structures, Structural Dynamics and Materials Conference
 of the AIAA, 12 - 14 May 1980, Seattle/Washington, USA
- 2 WILKINSON K., MARKOWITZ J. et. al.
 An Automated Procedure for Flutter and Strength Analysis and Optimization of Aero-
 space Vehicles
 Vol. 1, Theory and Application, AFFDL-TR-75-137
- 3 GÜDEL H., SCHNEIDER G.
 Vergleich des Strukturoptimierungsprogramms FASTOP mit einem Optimierungsprogramm
 ähnlicher Aufgabenstellung
 MBB-internal Report, July 1980
- 4 SCHNEIDER G.
 Aeroelastikuntersuchungen für TKF-SLW
 MBB-internal Report, Jan. 1980
- 5 JOHN H.
 Aeroelastik für Delta-Canard
 MBB-internal Report
- 6 GSCHLÖSSL F.
 Ergebnisse der statischen Vordimensionierung für den TKF-Delta-Flügel
 MBB-internal Report 1980
- 7 BRÖCKER W.
 CFK-Dimensionierungswerte für TKF-Anwendung
 MBB-internal Report
- 8 SCHMIDINGER G.
 Lastansätze für Konfiguration 8.18 10 C
 MBB-internal Report
- 9 LASCHKA B.
 Zur Theorie der harmonisch schwingenden tragenden Fläche bei Unterschallströmung
 ZfW, Heft 7, 1963
- 10 FÖRSCHING H.
 Grundlagen der Aeroelastik
 Springer-Verlag Berlin 1974

REPORT DOCUMENTATION PAGE													
1. Recipient's Reference	2. Originator's Reference	3. Further Reference	4. Security Classification of Document										
	AGARD-R-691	ISBN 92-835-1379-7	UNCLASSIFIED										
5. Originator	Advisory Group for Aerospace Research and Development North Atlantic Treaty Organization 7 rue Ancelle, 92200 Neuilly sur Seine, France												
6. Title	APPLICATION OF A STRUCTURAL OPTIMIZATION PROCEDURE FOR ADVANCED WINGS												
7. Presented at	the 51st Meeting of the AGARD Structures and Materials Panel held in Aix-en-Provence, France on 14-19 September 1980.												
8. Author(s)/Editor(s)	H.Gödel and G.Schneider		9. Date January 1981										
10. Author's/Editor's Address	Messerschmitt-Bölkow-Blohm GmbH Postfach 80 11 60 D-8000 München 80, FRG		11. Pages 19										
12. Distribution Statement	This document is distributed in accordance with AGARD policies and regulations, which are outlined on the Outside Back Covers of all AGARD publications.												
13. Keywords/Descriptors	<table border="0"> <tr> <td>Wings</td> <td>Aerodynamic characteristics</td> </tr> <tr> <td>Airframes</td> <td>Aerodynamic stability</td> </tr> <tr> <td>Computer aided design</td> <td>Flutter</td> </tr> <tr> <td>Computer programs</td> <td>Vibration</td> </tr> <tr> <td>Weight control</td> <td></td> </tr> </table>			Wings	Aerodynamic characteristics	Airframes	Aerodynamic stability	Computer aided design	Flutter	Computer programs	Vibration	Weight control	
Wings	Aerodynamic characteristics												
Airframes	Aerodynamic stability												
Computer aided design	Flutter												
Computer programs	Vibration												
Weight control													
14. Abstract	A computer software system called ASAT exists at MBB which allows an automatic design of minimum weight structures. In this paper, the application of this system to several structures is described. It is shown that a structural optimization system can be very useful in the preliminary design of an airplane, especially when it consists of several modules such as static load calculation, deformations and stress calculation by finite elements, static aeroelastics, weight calculation, unsteady aerodynamic forces, vibration calculation, flutter calculation, flutter and strength optimization which all can be used separately and independently.												

especially when it consists of several modules such as static load calculation, deformations and stress calculation by finite elements, static aeroelastics, weight calculation, unsteady aerodynamic forces, vibration calculation, flutter calculation, flutter and strength optimization which all can be used separately and independently. Paper presented at the 51st Meeting of the AGARD Structures and Materials Panel held in Aix-en-Provence, France on 14-19 September 1980. ISBN 92-835-1379-7	especially when it consists of several modules such as static load calculation, deformations and stress calculation by finite elements, static aeroelastics, weight calculation, unsteady aerodynamic forces, vibration calculation, flutter calculation, flutter and strength optimization which all can be used separately and independently. Paper presented at the 51st Meeting of the AGARD Structures and Materials Panel held in Aix-en-Provence, France on 14-19 September 1980. ISBN 92-835-1379-7
especially when it consists of several modules such as static load calculation, deformations and stress calculation by finite elements, static aeroelastics, weight calculation, unsteady aerodynamic forces, vibration calculation, flutter calculation, flutter and strength optimization which all can be used separately and independently. Paper presented at the 51st Meeting of the AGARD Structures and Materials Panel held in Aix-en-Provence, France on 14-19 September 1980. ISBN 92-835-1379-7	especially when it consists of several modules such as static load calculation, deformations and stress calculation by finite elements, static aeroelastics, weight calculation, unsteady aerodynamic forces, vibration calculation, flutter calculation, flutter and strength optimization which all can be used separately and independently. Paper presented at the 51st Meeting of the AGARD Structures and Materials Panel held in Aix-en-Provence, France on 14-19 September 1980. ISBN 92-835-1379-7

AGARD Report No.691 Advisory Group for Aerospace Research and Development, NATO APPLICATION OF A STRUCTURAL OPTIMIZATION PROCEDURE FOR ADVANCED WINGS H.Gödel and G.Schneider Published January 1981 19 pages A computer software system called ASAT exists at MBB which allows an automatic design of minimum weight structures. In this paper, the application of this system to several structures is described. It is shown that a structural optimization system can be very useful in the preliminary design of an airplane. P.T.O.	AGARD-R-691 Wings Airframes Computer aided design Computer programs Weight control Aerodynamic characteristics Aerodynamic stability Flutter Vibration	AGARD Report No.691 Advisory Group for Aerospace Research and Development, NATO APPLICATION OF A STRUCTURAL OPTIMIZATION PROCEDURE FOR ADVANCED WINGS H.Gödel and G.Schneider Published January 1981 19 pages A computer software system called ASAT exists at MBB which allows an automatic design of minimum weight structures. In this paper, the application of this system to several structures is described. It is shown that a structural optimization system can be very useful in the preliminary design of an airplane. P.T.O.	AGARD-R-691 Wings Airframes Computer aided design Computer programs Weight control Aerodynamic characteristics Aerodynamic stability Flutter Vibration
AGARD Report No.691 Advisory Group for Aerospace Research and Development, NATO APPLICATION OF A STRUCTURAL OPTIMIZATION PROCEDURE FOR ADVANCED WINGS H.Gödel and G.Schneider Published January 1981 19 pages A computer software system called ASAT exists at MBB which allows an automatic design of minimum weight structures. In this paper, the application of this system to several structures is described. It is shown that a structural optimization system can be very useful in the preliminary design of an airplane. P.T.O.	AGARD-R-691 Wings Airframes Computer aided design Computer programs Weight control Aerodynamic characteristics Aerodynamic stability Flutter Vibration	AGARD Report No.691 Advisory Group for Aerospace Research and Development, NATO APPLICATION OF A STRUCTURAL OPTIMIZATION PROCEDURE FOR ADVANCED WINGS H.Gödel and G.Schneider Published January 1981 19 pages A computer software system called ASAT exists at MBB which allows an automatic design of minimum weight structures. In this paper, the application of this system to several structures is described. It is shown that a structural optimization system can be very useful in the preliminary design of an airplane. P.T.O.	AGARD-R-691 Wings Airframes Computer aided design Computer programs Weight control Aerodynamic characteristics Aerodynamic stability Flutter Vibration

3382

4

AGARDNATO  OTAN7 RUE ANCELLE · 92200 NEUILLY-SUR-SEINE
FRANCE

Telephone 745.08.10 · Telex 610176

**DISTRIBUTION OF UNCLASSIFIED
AGARD PUBLICATIONS**

AGARD does NOT hold stocks of AGARD publications at the above address for general distribution. Initial distribution of AGARD publications is made to AGARD Member Nations through the following National Distribution Centres. Further copies are sometimes available from these Centres, but if not may be purchased in Microfiche or Photocopy form from the Purchase Agencies listed below.

NATIONAL DISTRIBUTION CENTRES**BELGIUM**

Coordonnateur AGARD - VSL
Etat-Major de la Force Aérienne
Quartier Reine Elisabeth
Rue d'Evere, 1140 Bruxelles

CANADA

Defence Science Information Services
Department of National Defence
Ottawa, Ontario K1A 0K2

DENMARK

Danish Defence Research Board
Østerbrogades Kaserne
Copenhagen Ø

FRANCE

O.N.E.R.A. (Direction)
29 Avenue de la Division Leclerc
92320 Châtillon sous Bagneux

GERMANY

Fachinformationszentrum Energie,
Physik, Mathematik GmbH
Kernforschungszentrum
D-7514 Eggenstein-Leopoldshafen 2

GREECE

Hellenic Air Force General Staff
Research and Development Directorate
Holargos, Athens

ICELAND

Director of Aviation
c/o Flugrad
Reykjavik

ITALY

Aeronautica Militare
Ufficio del Delegato Nazionale all'AGARD
3, Piazzale Adenauer
Roma/EUR

LUXEMBOURG

See Belgium

NETHERLANDS

Netherlands Delegation to AGARD
National Aerospace Laboratory, NLR
P.O. Box 126
2600 A.C. Delft

NORWAY

Norwegian Defence Research Establishment
Main Library
P.O. Box 25
N-2007 Kjeller

PORTUGAL

Direcção do Serviço de Material
da Força Aérea
Rua da Escola Politécnica 42
Lisboa
Attn: AGARD National Delegate

TURKEY

Department of Research and Development (ARGE)
Ministry of National Defence, Ankara

UNITED KINGDOM

Defence Research Information Centre
Station Square House
St. Mary Cray
Orpington, Kent BR5 3RE

UNITED STATES

National Aeronautics and Space Administration (NASA)
Langley Field, Virginia 23365
Attn: Report Distribution and Storage Unit

THE UNITED STATES NATIONAL DISTRIBUTION CENTRE (NASA) DOES NOT HOLD
STOCKS OF AGARD PUBLICATIONS, AND APPLICATIONS FOR COPIES SHOULD BE MADE
DIRECT TO THE NATIONAL TECHNICAL INFORMATION SERVICE (NTIS) AT THE ADDRESS BELOW.

PURCHASE AGENCIES***Microfiche or Photocopy***

National Technical
Information Service (NTIS)
5285 Port Royal Road
Springfield
Virginia 22161, USA

Microfiche

Space Documentation Service
European Space Agency
10, rue Mario Nikis
75015 Paris, France

Microfiche

Technology Reports
Centre (DTI)
Station Square House
St. Mary Cray
Orpington, Kent BR5 3RF
England

Requests for microfiche or photocopies of AGARD documents should include the AGARD serial number, title, author or editor, and publication date. Requests to NTIS should include the NASA accession report number. Full bibliographical references and abstracts of AGARD publications are given in the following journals:

Scientific and Technical Aerospace Reports (STAR)
published by NASA Scientific and Technical
Information Facility
Post Office Box 8757
Baltimore/Washington International Airport
Maryland 21240, USA

Government Reports Announcements (GRA)
published by the National Technical
Information Services, Springfield
Virginia 22161, USA



Printed by Technical Editing and Reproduction Ltd
Marford House, 7-9 Charlotte St, London W1P 1HQ