

AD A 097472

(12) LEVEL III

5

AD

AD-E400 576

CONTRACTOR REPORT ARLCD-CR-81007

TNT EQUIVALENCY OF BULK NITROCELLULOSE

F. L. MCINTYRE
COMPUTER SCIENCES CORPORATION
NSTL STATION, MS 39529

P. PRICE
PROJECT LEADER
D. WESTOVER
PROJECT ENGINEER
ARRADCOM

DTIC
ELECTE
APR 8 1981
S D
B

MARCH 1981



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
LARGE CALIBER
WEAPON SYSTEMS LABORATORY
DOVER, NEW JERSEY

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

DTIC FILE COPY

81 3 27 043

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.

Destroy this report when no longer needed. Do not return it to the originator.


The citation in this report of the names of commercial firms or commercially available products or services does not constitute official endorsement or approval of such commercial firms, products, or services by the United States Government.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
Contractor Report ARLCD-CR-81007	AD-A097472	
4. TITLE (and Subtitle)	5. TYPE OF REPORT & PERIOD COVERED	
TNT EQUIVALENCY OF BULK NITROCELLULOSE	Final August 1978 - September 1978	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s)	8. CONTRACT OR GRANT NUMBER(s)	
F. L. McIntyre, Computer Sciences Corporation P. Price, Project Leader, ARRADCOM D. Westover, Project Engineer, ARRADCOM	MIPR 8311-0089	
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
Computer Sciences Corporation NSTL Station, MS 39529	MMT-5784285	
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE	
ARRADCOM, TSD STINFO Division (DRDAR-TSS) Dover, NJ 07801	March 1981	
	13. NUMBER OF PAGES	
	65	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report)	
ARRADCOM, LCWSL Energetics Systems Process Div (DRDAR-LCM-SP) Dover, NJ 07801	Unclassified	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report)		
Approved for public release, distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
This project was accomplished as part of the U.S. Army's Manufacturing Methods and Technology Program. The primary objective of this program is to develop, on a timely basis, manufacturing processes, techniques, and equipment for use in production of Army materiel.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
MMT-ammunition Scaled shipping container Nitrocellulose Peak side-on pressure TNT equivalency Scaled positive impulse Apparent bulk density Scaled distance Scaled weigh feeder tub Thermal dehydration unit		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)		
Peak side-on blast overpressure and scaled positive impulse have been measured for Nitrocellulose MIL-N-244A using configurations that simulate in-plant processing. Quantities of 11.34, 19.5, 22.68, 45 and 63.5 kg were tested in cylindrical storage containers, an orthorhombic scaled weigh feeder tube and a simulated section of the Thermal Dehydration Unit. High explosive equivalency values for each test series were obtained as a function of scaled distance by comparison to known pressure and impulse characteristics for TNT hemispherical surface bursts.		

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)




SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

SUMMARY

Nitrocellulose, 13.15% nitrogen MIL-N-244A Grade C (Lot number RAD78F0015027) was detonated in configurations representative of in-plant scaled storage cans, scaled weigh feeder tub and a simulated section of the Thermal Dehydration Unit. Blast output parameters were measured and TNT equivalency was computed based on comparison with TNT hemispherical surface bursts. The results of these tests are presented in the table below and in figures on the following page. To within experimental error the pressure and impulse of the nitrocellulose with an L/D ratio greater than one-to-one in charge weights of 11.34, 19.5, 22.7 and 63.5 kg scaled with the cube root of the charge weight. TNT equivalency was greater than 100% at the near field values ($Z \leq 6\text{m/kg}^{1/3}$) and less than 100% for the far field values ($Z > 6\text{m/kg}^{1/3}$). TNT equivalency values for the Thermal Dehydration Unit, 45 kg and with an L/D ratio less than one-to-one, were generally less than 100% at all scaled distances with the exception of ($Z = 1.19\text{m/kg}^{1/3}$) which was greater than 100%, and the far field value of $7.14\text{ m/kg}^{1/3}$ where the impulse equivalency was 105%.

Configuration Mass	Pressure (P) and impulse (I) TNT equivalency (%) at scaled distance											
	1.19m/kg ^{1/3} (3.0 ft/lb ^{1/3})		1.61m/kg ^{1/3} (4.05 ft/lb ^{1/3})		2.13m/kg ^{1/3} (5.38 ft/lb ^{1/3})		3.57m/kg ^{1/3} (9.0 ft/lb ^{1/3})		7.14m/kg ^{1/3} (18.0 ft/lb ^{1/3})		15.9m/kg ^{1/3} (40 ft/lb ^{1/3})	
	P	I	P	I	P	I	P	I	P	I	P	I
11.34kg • 19.5kg •• 22.68kg • 63.5kg •••	145	100	105	75	100	65	100	75	95	70	65	70
Thermal dehydration unit 45 kg	130	80	80	70	70	60	60	70	75	105	90	90

- Scaled storage cans
- Scaled weigh feeder tub
- Standard shipping drum



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/ _____	
Availability Codes	
Avail and/or	
Dist	Special
A	





TABLE OF CONTENTS

<u>Title</u>	<u>Page</u>
INTRODUCTION	1-9
Background	1-9
Objective	1-9
EXPERIMENTAL METHODS	10
Material	10
Test Plan	10
Instrumentation	12
RESULTS	15
Data Analysis	15
Test Results	15
Discussion	15
CONCLUSIONS	29
REFERENCES	30
APPENDIX A - TEST DATA SHEETS, TNT EQUIVALENCY OF NITROCELLULOSE	31
APPENDIX B - SELECTED PHOTOGRAPHS	45
APPENDIX C - TNT EQUIVALENCY PROGRAM	53
DISTRIBUTION LIST	59

LIST OF TABLES

<u>Table No.</u>	<u>Title</u>	<u>Page</u>
1	Transducer Calibration and Placement	13
2	Summary of Test Results, 11.24 kg Charges	17

TABLE OF CONTENTS (Cont'd)

LIST OF TABLES

<u>Table No.</u>	<u>Title</u>	<u>Page</u>
3	Summary of Test Results, 19.5 kg Charges	17
4	Summary of Test Results, 22.68 kg Charges	18
5	Summary of Test Results, 45 kg Charges	18
6	Summary of Test Results, 63.5 kg Charges	19
7	Summary of Test Results of Composite Charges With an L/D Ratio of 1:1	19
8	Fireball Diameter and Duration	28

LIST OF ILLUSTRATIONS

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
1	Test Container Configuration	11
2	Typical Charge Placement for Equivalency Tests	14
3	Test Area Showing Transducer and Camera Placement	14
4	TNT Hemispherical Surface Burst Reference Data	16
5	Pressure and Impulse vs. Scaled Distance 11.34 kg Charges . . .	20
6	Pressure and Impulse vs. Scaled Distance 19.5 kg Charges . . .	21
7	Pressure and Impulse vs. Scaled Distance 22.68 kg Charges . . .	22
8	Pressure and Impulse vs. Scaled Distance 45 kg Charges . . .	23
9	Pressure and Impulse vs. Scaled Distance 63.5 kg Charges . . .	24
10	Pressure and Impulse vs. Scaled Distance for Combined Charge Weight with a Nominal L/D Ratio Approximately 1:1	25
11	Pressure and Impulse Equivalencies	26
12	Deviation from Cube-Root Scaling of Nitrocellulose with an L/D Ratio Greater than 1:1	27

INTRODUCTION

BACKGROUND

A Thermal Dehydration Facility (Project 5752666) for continuous manufacturing of nitrocellulose (NC) has been installed at a GOCO Plant. Thermal Dehydration equipment is being installed at another GOCO Plant (Project 5802875) for the CAMBL 1 Line.

At the can pack operation (Project 5752666) the nitrocellulose (5%) is pumped to the Thermal Dehydration Unit where it enters as a 95% water slurry. After the conveyor of the unit has moved the material for 1.83 m (6 ft), 3.93 m (12.9 ft), and approximately 7.62 m (25 ft), its moisture content has been reduced to 30%, 8% and 0.5 to 1% respectively. At this point of the drying process the nitrocellulose material is in cake form 19 mm (0.75 in) thick by 2.44 m (8 ft) wide with a density of 1.6 g/cm³. The nitrocellulose is sprayed with ethyl alcohol (to a maximum of 14%), the cake is broken up, and conveyed to a weigh feeder where it is weighed into storage containers with a height-to-diameter ratio 68.6/55.9 cm (27/22 in).

The NC drying process is the same for Project 5802875 except, as the material leaves the Thermal Dehydration Unit, it is conveyed to a gravimetric feeder, and fed into a pre-mixer and mixed with other materials.

Safety engineering and cost effectiveness considerations require knowledge of hazardous material characteristics as an input to facility design requirements. In this instance, specific data is required on the explosive output characteristics of nitrocellulose in quantities and configurations representative of those found in processing.

OBJECTIVE

To determine the maximum output from the detonation of nitrocellulose in terms of the airblast overpressure and positive impulse. The measured pressure and impulse data will be compared with known TNT test data (curves) to determine the equivalency of nitrocellulose in relation to TNT.

EXPERIMENTAL METHODS

MATERIALS


The test material was dehydrated nitrocellulose 13.15% nitrogen Mil-N-244A Grade C (Lot number RAD78F0015027). It was received in 208-liter (55-gallon) steel drums approximately 25% alcohol wet, with a net mass of 107.9 kg (238 lb).

TEST PLAN

Airblast output was evaluated for masses and configuration of nitrocellulose representative of four in-plant situations. Physical characteristics of the test items were as follows:

- (1) A cylindrical container (figure 1a) was used to simulate a scaled storage container. The container was constructed from 16-gage steel with a height of 35.6 cm by 25.4 cm diameter (14 in by 10 in) and was filled with 11.34 kg (25 lb) of nitrocellulose 14% alcohol wet.
- (2) An orthorhombic container (figure 1b) was used to simulate a scaled weigh feeder tub. This container was constructed from 16-gage steel with dimensions of 35.6 cm by 30.5 cm by 30.5 cm (14 in by 12 in by 12 in). This container was filled with 19.5 kg (43 lb) of nitrocellulose 14% alcohol wet.
- (3) A cylindrical container (figure 1c) was used to simulate a scaled storage container. The container was constructed from 16-gage steel with dimensions of 35.6 cm by 33 cm (14 in by 13 in). This container was filled with 22.68 kg (50 lb) of nitrocellulose 14% alcohol wet.
- (4) An orthorhombic fixture (figure 1d) was used to simulate a section of the Thermal Dehydration Unit (TDU). The fixture was constructed from plywood with dimensions of 121.9 by 121.9 by 30.5 cm (48 in by 48 in by 12 in). The bottom of the fixture was open and covered with wire mesh window screen. Nitrocellulose, 53 kg (116 lb) at 14% alcohol wet was weighed out and spread evenly to a height of approximately 2.54 cm (1 in). A lid was placed atop the fixture and a dry air purge with a dew point of -76.1°C (-105°F) was allowed to run for a minimum of 30 minutes to remove the alcohol from the material. The weight of the material at time of test was 45 kg (99 lb).
- (5) A full-scale shipping drum (figure 1e) was used to test 63.5-kg (140-lb) quantities to determine cube root scaling as a function of charge weight. These tests were in addition to those called for in the original test plan. Nitrocellulose 14% alcohol wet was used in this test series.

A Composition C1 conically shaped booster charge with a ratio of 1.5:2 height to diameter (h/d) was centered on top of each test charge. The height to diameter ratio for the Thermal Dehydration Unit configuration was 1:4. The booster was initiated with an engineer's special J2 blasting cap inserted at the apex and embedded to the center of the cone.



NOTE: Shaded area represents the nominal height of the sample material

Figure 1-Test Container Configurations

The test plan called for booster weights varying between 6 and 8% with a maximum of 10%. An initial test was conducted with 5.44 kg (12 lb) nitrocellulose material 14% alcohol wet and a 0.5 kg (1.2 lb) booster (C4) in a container 20.3 cm (3 in.) diameter and 30.5 cm (12 in.) high. No mass detonation occurred. ARRADCOM approved the use of the containers shown in figure 1 and the employment of a 10% booster for all tests in all configurations.

The test charges in each configuration were placed on a 1010 carbon steel witness plate 1.27 cm (0.5 in) thick with the dimensions being at least 5.08 cm (2 in) greater than the size of the test container.

INSTRUMENTATION

Twelve PCB Piezotronics side-on-pressure transducers were mounted flush to the surface in each of two sand-filled arrays within the test area shown in figure 2. Distances from the charge to the transducer corresponded to scaled distances from 1.19 to 15.87 $\text{m/kg}^{1/3}$ (3 to 40 $\text{ft/lb}^{1/3}$). The transducers were individually calibrated prior to the beginning of each test series with pressure pulses from a standard solenoid-actuated air pressure calibration fixture, adjusted to correspond to expected blast pressure based on an assumed TNT equivalency of 100 percent. Signal line continuity and channelization were checked prior to each test along with a daily electrical calibration of the recording system. Details of distances between charge and transducers, calibration pressure and expected peak blast pressure at each distance are shown in table 1.

Each transducer with inherent charge amplifier was connected to an underground coaxial cable system which leads to the Test Control Center. All signals are amplified and conditioned by PCB Model 494A06 Power Supply Amplifier. The signals were recorded in digital form on 4 Blomation Model 8100 Transient Recorders and in analog form on a Honeywell Model 96 Tape Recorder.

Photographic coverage was restricted to one test of each configuration (figure 3). Motion picture coverage included a Mitchell camera Model H516-E4 operating at 500 frames per second (fps) and one Mitchell camera (same model) operating at 24 fps. Before and after color still photographs were taken of each test showing typical setup and results. Standard meteorological data were recorded for each test.

TABLE 1. TRANSDUCER CALIBRATION AND PLACEMENT FOR
NITROCELLULOSE EQUIVALENCY TESTING

Channel number	Scaled distance m/kg ^{1/3} (ft/lb ^{1/3})	Full-scale calibration pressure kPa (psig)	Expected pressure kPa (psig)	R distance in meters (ft) from charge			
				R ₁ distance in meters (ft) from charge			
				Charge weight 11.34 kg (25 lb)	Charge weight 22.68 kg (50 lb)	Charge weight 41.87 kg (92.3 lb)	Charge weight 45 kg (99 lb)
1, 2	1.19 (3.0)	1034 (150)	917 (133)	2.67 (8.77)	3.37 (11.05)	4.13 (13.558)	4.46 (14.63)
3, 4	1.61 (4.05)	517.1 (75)	479.74 (69.58)	3.56 (11.696)	4.49 (14.738)	5.51 (18.077)	5.95 (19.508)
5, 6	2.13 (5.38)	344.7 (50)	242.49 (35.17)	4.81 (15.789)	6.06 (19.89)	7.44 (24.404)	8.03 (26.336)
7, 8	3.57 (9.0)	103.4 (15)	87.9 (12.74)	8.02 (26.32)	10.11 (33.2)	12.40 (40.67)	13.38 (43.89)
9, 10	7.14 (18.0)	34.5 (5)	24.9 (3.6)	16.04 (52.63)	20.21 (66.3)	24.79 (81.347)	26.76 (87.786)
11, 12	15.87 (40.0)	34.5 (5)	7.58 (1.1)	35.64 (117.0)	44.92 (147.4)	55.10 (180.77)	59.46 (195.08)




Figure 2. Typical Charge Placement for Equivalency Tests




Figure 3. Test Area Showing Transducer and Camera Placement

RESULTS

DATA ANALYSIS

Peak blast overpressure and positive impulse information were obtained in digital form by the Tektronix 4051 Graphic System. After exclusion of inconsistent results that could be attributed to instrumentation or explosive malfunction, average values for pressure and impulse were used to calculate equivalencies based on comparison to data from TNT hemispheres¹ (figure 4). McKown² describes the program written for the Graphic System which utilizes an iterative process first reported by Swatosh and Cook³ which factors out the contribution of the booster charge weight and calculates the pressure and impulse equivalencies (see Appendix C). With the effect of the booster weight factored out, the calculated TNT equivalencies were tabularized and plotted as functions of sample scaled distance.

TEST RESULTS

Data sheets for all tests with pertinent measured parameters are given in Appendix A. Selected pretest and posttest still photographs are given in Appendix B. Test numbers shown are for local reference only and provide access to original range data files.

Average pressure, scaled positive impulse, and time of arrival data are summarized by test configuration in tables 2 through 6 and figures 5 through 9. Composite pressure and impulse curves for all charge weights and configurations are given in figure 10, and are summarized in tables 2 through 7 of this report. Percent TNT equivalencies for all charge weights and configurations are shown in figure 11 as functions of scaled distance. Deviation from cube-root scaling for pressure at each scaled distance versus charge weight for nitrocellulose with an L/D ratio is shown in figure 12. Fireball duration and diameter as measured from the high speed motion pictures are given in table 8.

DISCUSSION

The plots of peak pressure and scaled impulse versus scaled distance (figures 5, 6, and 7) for the L/D ratio of 1:1 or greater show the same general trend. Compared to (figure 4) corresponding TNT hemispherical surface burst, the observed pressures are greater than 100 percent at the near field values ($Z \leq 6 \text{ m/kg}^{1/3}$) and less than 100% for the far field values ($Z > 6 \text{ m/kg}^{1/3}$). Impulse versus scaled distance was generally less than 100 percent at all measured distances. The peak pressures for the Thermal Dehydration Unit simulation tests were less than those found in the tests with a nominal L/D ratio 1:1. Peak pressure equivalency was found to be greater than 100% at one near field value of $1.19 \text{ m/kg}^{1/3}$ and all other pressure equivalencies were less than 100%. Impulse equivalency was found to be less than 100 percent at all scaled distances. The lower pressures and impulse values for the TDU can be attributed to the difference in geometry. Wisotski and Syner⁴ and McKown and McIntyre⁵ have noted the effect of geometry in producing lower peak pressure and impulse values when the L/D ratio is less than 1:1.




Figure 4. TNT Hemispherical Surface Burst Reference Data

TABLE 2. SUMMARY OF TEST RESULTS, 11.34 kg CHARGE, SCALED STORAGE CONTAINER

Radius meters (ft)	Scaled Distance $m/kg^{1/3}$ (ft/lb ^{1/3})	Time of Arrival (msec)	Peak Pressure kPa (psi)	Scaled Positive Impulse $kPa \cdot ms/kg^{1/3}$ (psi · ms/lb ^{1/3})	Pressure TNT Equivalency	Impulse TNT Equivalency
2.67 (8.77)	1.19 (3.0)	2.95	1245.1 (180.6)	170.7 (19.02)	141	93
3.61 (11.7)	1.61 (4.05)	3.89	549.6 (79.71)	118.01 (13.15)	158	74
4.8 (15.79)	2.13 (5.38)	5.51	291.8 (43.3)	79.06 (8.91)	108	57
8.02 (26.32)	3.57 (9.0)	12.24	83.8 (12.15)	59.41 (6.62)	97	72
16.04 (52.63)	7.14 (18.0)	32.65	23.7 (3.44)	27.64 (3.08)	89	57
35.7 (117.0)	15.87 (40.0)	86.01	7 (1.02)	13.55 (1.51)	59	63

TABLE 3. SUMMARY OF TEST RESULTS, 19.5 kg CHARGE SCALED WEIGH FEEDER TUB

Radius meters (ft)	Scaled Distance $m/kg^{1/3}$ (ft/lb ^{1/3})	Time of Arrival (msec)	Peak Pressure kPa (psi)	Scaled Positive Impulse $kPa \cdot ms/kg^{1/3}$ (psi · ms/lb ^{1/3})	Pressure TNT Equivalency	Impulse TNT Equivalency
3.2 (10.51)	1.19 (3.0)	3	1202.7 (174.43)	166.47 (18.55)	135	81
4.33 (14.19)	1.61 (4.05)	3.98	532.6 (77.24)	121.60 (13.55)	108	76
5.74 (18.84)	2.13 (5.38)	5.84	276.6 (40.12)	22.78 (8.11)	103	48
9.61 (31.53)	3.57 (9.0)	13.83	80.7 (11.71)	67.57 (7.53)	91	66
19.22 (63.06)	7.14 (18.0)	37.91	25.9 (3.76)	34.01 (3.79)	112	76
42.71 (140.14)	15.87 (40.0)	102.11	7.58 (1.10)	15.44 (1.72)	72	83

TABLE 4. SUMMARY OF TEST RESULTS, 22.68 kg CHARGE, SCALED STORAGE CONTAINER

Radius meters (ft)	Scaled Distance $m/kg^{1/3}$ (ft/lb ^{1/3})	Time of Arrival (msec)	Peak Pressure kPa (psi)	Scaled Positive Impulse $kPa \cdot ms/kg^{1/3}$ (psi · ms/lb ^{1/3})	Pressure TNT Equivalency %	Impulse TNT Equivalency %
3.37 (11.05)	1.19 (3.0)	3.26	1327.8 (192.58)	202.9 (22.61)	156	126
4.49 (14.74)	1.61 (4.05)	4.27	543.7 (78.85)	124.47 (13.87)	107	80
6.06 (19.89)	2.13 (5.38)	6.51	271.45 (39.36)	90.1 (10.04)	102	71
10.11 (33.2)	3.57 (9.0)	15.17	88.53 (12.84)	60.13 (6.70)	109	74
20.21 (66.3)	7.14 (18.0)	40.24	23.92 (3.47)	31.5 (3.51)	91	71
44.92 (147.4)	15.87 (40.0)	107.53	7.31 (1.06)	14.27 (1.59)	65	69

TABLE 5. SUMMARY OF TEST RESULTS, 45 kg CHARGE THERMAL DEHYDRATION UNIT

Radius meters (ft)	Scaled Distance $m/kg^{1/3}$ (ft/lb ^{1/3})	Time of Arrival (msec)	Peak Pressure kPa (psi)	Scaled Positive Impulse $kPa \cdot ms/kg^{1/3}$ (psi · ms/lb ^{1/3})	Pressure TNT Equivalency %	Impulse TNT Equivalency %
1.46 (11.63)	1.25 (3.16)	4.42	1070.8 (155.3)	161.12 (16.84)	132	80
6.02 (19.75)	1.69 (4.26)	6.27	353. (51.18)	108.22 (12.08)	79	69
8 (26.24)	2.25 (5.67)	9.84	194.6 (28.22)	80.41 (8.96)	69	61
13.38 (43.89)	3.76 (9.48)	22.04	59.7 (8.66)	57.52 (6.41)	57	73
26.76 (87.79)	7.52 (18.98)	56.71	19.99 (2.9)	38.50 (4.29)	75	106
59.46 (195.08)	16.71 (42.12)	146.32	7.93 (1.15)	16.51 (1.84)	94	93

TABLE 6. SUMMARY OF TEST RESULTS, 63.5 kg CHARGE, SHIPPING CONTAINER

Radius meters (ft)	Scaled Distance $m/kg^{1/3}$ (ft/lb ^{1/3})	Time of Arrival (msec)	Peak Pressure kPa (psi)	Scaled Positive Impulse $kPa \cdot ms/kg^{1/3}$ (psi $\cdot$ ms/lb ^{1/3})	Pressure TNT Equivalency	Impulse TNT Equivalency
4.75 (15.58)	1.19 (3.0)	4.5	1251.4 (181.5)	181.81 (20.76)	143	89
6.33 (20.77)	1.61 (4.05)	6.22	469.4 (68.08)	126.4 (14.09)	85	84
8.55 (28.04)	2.13 (5.38)	9.57	252.14 (36.57)	93.24 (10.39)	91	76
14.24 (46.73)	3.57 (9.0)	21.28	86.5 (12.54)	58.3 (6.5)	103	69
28.49 (93.46)	7.14 (18.0)	57.1	25.44 (3.69)	34.19 (3.81)	107	81
63.32 (207.73)	15.87 (40.0)	152.9	7.86 (1.14)	14.27 (1.59)	79	68

TABLE 7. SUMMARY OF TEST RESULTS, COMPOSITE CHARGE WEIGHTS WITH A NOMINAL L/D RATIO OF 1:1

Scaled Distance $m/kg^{1/3}$ (ft/lb ^{1/3})	Scaled Time of Arrival (msec)	Peak Pressure kPa (psi)	Scaled Positive Impulse $kPa \cdot ms/kg^{1/3}$ (psi $\cdot$ ms/lb ^{1/3})	Pressure TNT Equivalency	Impulse TNT Equivalency
1.19 (3.0)	(0.90)	1433 (207.78)	178.3 (19.87)	143	100
1.61 (4.05)	(1.20)	621.08 90.	120.97 (13.48)	106	76
2.13 (5.38)	(1.80)	311.21 (45.12)	85.34 (9.51)	101	65
3.57 (9.0)	(4.09)	93.37 (13.56)	60.13 (6.7)	100	74
7.14 (18.0)	(11)	23.18 (3.36)	31.68 (3.53)	94	71
15.87 (40.0)	(29.34)	3.29 (.47)	14.36 (1.6)	63	70




Figure 5. Pressure and Impulse vs. Scaled Distance 11.34 kg Charges





Figure 6. Pressure and Impulse vs. Scaled Distance 19.5 kg Charges




Figure 7. Pressure and Impulse vs. Scaled Distance 22.68 kg Charges





Figure 8. Pressure and Impulse vs. Scaled Distance 45 kg Charges





Figure 9. Pressure and Impulse vs. Scaled Distance 63.5 kg Charges




Figure 10. Pressure and Impulse vs. Scaled Distance for Combined Charge Weight with a Nominal L/D Ratio Approximately 1:1




Figure 11. Pressure and Impulse Equivalencies




Figure 12. Deviation from Cube-Root Scaling of Nitrocellulose with an L/D Ratio Greater Than 1:1

Examination of the pressure and impulse data obtained from the 11.34, 19.5, 22.68 and 63.5 kg having similar L/D ratios indicated that the corresponding values fit a single curve. The composite data are shown in table 7 and figure 10.

Figure 12 is a graphic presentation of the deviation from cube root scaling for the 11.34-, 19.5-, 22.68- and 63.5-kg charge weight for pressure and impulse. A positive slope indicates that increasing charge masses at constant scaled distances result in an increase in pressure or impulse equivalency. Conversely, a negative slope is indicative of a decrease in pressure or impulse equivalency for increased charge masses. Generally the pressure slopes were slightly negative with the exception of scaled distances of 3.57 and 15.87 m/kg^{1/3} where these values scaled slightly positive with increasing charge weights. Impulse values scaled slightly positive with increasing charge weights. Both the slight negative slope for pressure and the slightly positive slope for scaled impulse were within experimental error of the standard TNT cube root scaling.

Time of arrival data is reported for individual test in each data sheet (see Appendix A) and in the Summary Tables 2 through 6. There was no attempt made to determine TNT equivalencies based upon arrival times. Rather, these were used to aid in determining the good and bad data.

Fireball diameter and duration information was taken from the movies and these data are summarized in table 8. They are reported as information only as there is no reference to effectively gauge the significance.

TABLE 8 FIREBALL DURATION AND DIAMETER

Charge Weight kg (lb)	Maximum Fireball Diameter meters (ft)	Fireball Duration msec
11.34 (25)	10.4 (34)	274
19.5 (43)	13.1 (43)	278
22.68 (50)	14.02 (46)	402
45 (99)	18.9 (62)	415

CONCLUSIONS

(1) TNT equivalency values of nitrocellulose in three in-plant situations were found to have pressure equivalencies greater than 100% for the near field values ($Z \leq 6 \text{ m/kg}^{1/3}$) and less than 100% for the far field values ($Z > 6 \text{ m/kg}^{1/3}$). Impulse equivalencies were generally less than 100% at all scaled distances. This was true for charge weights of 11.34, 19.5, 22.68 and 63.5 kg with a nominal L/D ratio of 1:1.

(2) Within the limits of the experiments, blast pressures and impulse scaled as a cube root function of the charge weights with test charges of a nominal L/D ratio of 1:1.

(3) TNT equivalency values of nitrocellulose under simulated conditions found in the Thermal Dehydration Unit were generally less than 100% for pressure and scaled impulse. The exceptions were at the near field value of $1.19 \text{ m/kg}^{1/3}$ where the pressure equivalency was 130%, and the far field value of $7.14 \text{ m/kg}^{1/3}$ where the impulse equivalency was 105%.

RECOMMENDATION

The TNT equivalency of pressure and impulse values determined from this test series should be used, where applicable, in the structural design of protective facilities.


REFERENCES

1. Kingery, C. N., BRL Report No. 1344, Airblast Parameters Versus Distance for Hemispherical TNT Surface Bursts, September 1966.
2. KcKown, G. L., "TNT Equivalency of R284, I559, and I560 Tracer Composition," Technical Report ARLCD-TR-79026, ARRADCOM, Dover, NJ, October 1978.
3. Swatosh, J. J., and J. Cook, "TNT Equivalency of M1 Propellant (Bulk)," Technical Report 4885, Picatinny Arsenal, December 1975.
4. Wisotski, John and W. H. Syner, Characteristics of Blast Waves Obtained from Cylindrical High Explosive Charges, Denver Research Institute, November 1975.
5. McKown, G. L. and F. L. McIntyre, "TNT Equivalency of Composition A5," Technical Report ARLCD-TR-78018, ARRADCOM, Dover, NJ, March 1977.

APPENDIX A

TEST DATA SHEETS, TNT EQUIVALENCY OF NITROCELLULOSE


TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/15/78
 TEST SAMPLE NITROCELLULOSE 14.5% ALCOHOL RIL-B-244A TIME 1118
 SAMPLE WEIGHT 11.34kg (25 lb) TEMP 31.1°C (88°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 56%
 BOOSTER WEIGHT 1.124g (2.5 lb) BAR. PRESS. 30.09
 TEST NO. (33-B-02) WIND DIR 280°
 CONTRACT NO. NAS13-50 WIND VEL. 2 knots



FIELD EVALUATION Detonation occurred, clean hole in witness plate.

Photographic coverage 1 documentary 24 fps, 1 high speed 500 fps motion picture and pre- and posttest still photos.

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/15/78
 TEST SAMPLE NITROCELLULOSE 14.5% ALCOHOL RIL-B-244A TIME 1219
 SAMPLE WEIGHT 11.34kg (25 lb) TEMP. 32.8 (91°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 48%
 BOOSTER WEIGHT 1.124g (2.5 lb) BAR. PRESS. 37.68
 TEST NO. A2 (33-B-03) WIND DIR. 250°
 CONTRACT NO. NAS13-50 WIND VEL. 5 knots



FIELD EVALUATION Detonation, clean hole in witness plate

EXPERIMENTAL

RESULTS


TNT EQUIVALENCY TEST 11.34 kg (25 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/ft ^{1/3} (psi msec/ft ^{1/3})	Time of Arrival (msec)	Remarks
1	2.67	1282.5 (186.01)	163.3 (10.2)	3.15	
2	(8.77)	1369.3 (198.6)	(—)	3.2	Bad Impulse Data
3	3.57	490.2 (71.09)	62.4 (8.95)	4	
4	(11.7)	595.4 (86.36)	111.8 (12.46)	4.1	
5	4.81	(—)	(—)	4.7	No Data "ader had loose connect.
6	(15.79)	283.8 (41.16)	85.3 (9.51)	5.15	
7	8.02	87.2 (12.65)	51.2 (5.71)	11.75	
8	(26.32)	69.6 (10.09)	55.6 (6.19)	11.7	
9	16.04	29.8 (4.32)	36.5 (4.07)	32.8	
10	(52.63)	22.8 (3.31)	28.8 (3.21)	32.9	
11	35.66	7.17 (1.04)	13.7 (1.53)	86.6	
12	(117)	6.76 (0.98)	16.3 (1.82)	86.55	

EXPERIMENTAL

RESULTS


TNT EQUIVALENCY TEST 11.34 kg (25 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/ft ^{1/3} (psi msec/ft ^{1/3})	Time of Arrival (msec)	Remarks
1	2.67	1052.5 (152.65)	171.9 (19.16)	2.75	
2	(8.77)	1426.4 (206.88)	184.6 (20.57)	2.7	
3	3.57	539.2 (78.2)	118.2 (13.17)	3.75	
4	(11.7)	624.7 (90.61)	113.7 (12.67)	3.7	
5	4.81	(—)	(—)	5.75	No Data Loose tester connection
6	(15.79)	216.2 (31.36)	71.07 (7.92)	5.35	
7	8.02	82.4 (11.98)	59.7 (6.65)	12.45	
8	(26.32)	94.39 (13.69)	65.2 (7.26)	12.35	
9	16.04	25.1 (3.35)	25.8 (2.87)	32.5	
10	(52.63)	21.6 (3.13)	29.4 (3.28)	32.4	
11	35.66	9.24 (1.34)	7.99 (0.89)	85.9	
12	(117)	6.31 (0.92)	12.8 (1.43)	86.1	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/15/78
 TEST SAMPLE NITROCELLULOSE 14⁵SEALCOHOL MIL-R-244A TIME 1611
 SAMPLE WEIGHT 11.34kg (25 lb) TEMP 33.3°C (92°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 45%
 BOOSTER WEIGHT 1.13kg (2.5 lb) BAR. PRESS. 30.00
 TEST NO A₃ (33-B-04) WIND DIR. 250°
 CONTRACT NO. NAS13-50 WIND VEL. 8 knots



FIELD EVALUATION Detonation, clean hole in witness plate

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/15/78
 TEST SAMPLE NITROCELLULOSE 14⁵SEALCOHOL MIL-R-244A TIME 1506
 SAMPLE WEIGHT 11.34kg (25 lb) TEMP 33.3°C (92°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 43%
 BOOSTER WEIGHT 1.13kg (2.5 lb) BAR. PRESS. 30.05
 TEST NO A₄ (33-B-05) WIND DIR. 110°
 CONTRACT NO. NAS13-50 WIND VEL. 1 knot



FIELD EVALUATION Detonation, clean hole in witness plate


EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 11.34 kg (25 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/ft ^{1/3} (psi msec/ft ^{1/3})	Time of Arrival (msec)	Remarks
1	2.67 (8.77)	1185.2 (171.90)	154.8 (17.25)	2.3	
2		1350.3 (195.85)	152.6 (17.01)	2.2	
3	3.57 (11.7)	553.9 (80.33)	115.9 (12.91)	3.4	
4		561.3 (81.41)	(—)	3.2	Ringing bad impulse data
5	4.81 (15.77)	293.5 (42.57)	79.5 (8.86)	5.2	
6		189.2 (27.44)	40.5 (4.51)	5.0	
7	8.02 (26.32)	80.7 (11.71)	60.9 (6.79)	11.8	
8		87.8 (12.73)	51.2 (5.82)	11.8	
9	16.04 (52.63)	25.3 (3.67)	25.4 (2.83)	32	
10		24.8 (3.59)	31.5 (3.51)	32	
11	35.66 (117)	8 (1.16)	13.1 (1.46)	85.55	
12		6.62 (0.96)	13.7 (1.53)	85.75	

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 11.34 kg (25 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/ft ^{1/3} (psi msec/ft ^{1/3})	Time of Arrival (msec)	Remarks
1	2.67 (8.77)	1096.75 (159.07)	107.3 (11.96)	2.9	
2		1378.8 (199.98)	183.3 (20.43)	3.0	
3	3.57 (11.7)	473.6 (68.25)	126.6 (14.11)	3.9	
4		522.3 (75.75)	(—)	3.9	Bad Impulse Data
5	4.81 (15.79)	276.2 (40.06)	81.3 (9.06)	6.0	
6		(—)	(—)	—	No Data
7	8.02 (26.32)	82.6 (11.98)	71.7 (7.99)	12.65	
8		69.6 (10.09)	70.2 (7.82)	12.4	
9	16.04 (52.63)	23.9 (3.46)	2.64 (2.94)	32.5	
10		22.4 (3.25)	27.3 (3.04)	32.65	
11	35.66 (117)	7.03 (1.02)	12.7 (1.42)	85.85	
12		(—)	(—)	86.0	No Data loose isder connection

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/16/78
 TEST SAMPLE NITROCELLULOSE 14'SSALCONOL MIL-N-244A TIME 1052
 SAMPLE WEIGHT 11.34kg (25 lb) TEMP 32.2°C (90°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 53%
 BOOSTER WEIGHT 1.13kg (2.5 lb) BAR. PRESS 30.07
 TEST NO AS (33-B-06) WIND DIR. 250°
 CONTRACT NO NAS13-50 WIND VEL 3 knots




FIELD EVALUATION Detonation, clean hole in witness plate

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST 11.34 kg (25 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/kg ^{1/3} (psi msec/lb ^{1/3})	Time of Arrival (msec)	Remarks
1	2.67	882.3 (127.97)	92.3 (10.29)	3.4	
2	(8.77)	855.8 (124.12)	181.7 (20.25)	3.4	
3		509.7 (73.93)	72.7 (8.1)	4.3	
4	(11.7)	759.7 (110.18)	121.9 (13.58)	4.3	
5		285.8 (41.45)	88.7 (9.88)	6.15	
6	(15.79)	244.8 (35.51)	70.3 (7.83)	6.25	
7		76.2 (11.05)	50.3 (5.6)	12.75	
8	(26.32)	89.22 (12.94)	54.1 (6.03)	12.85	
9		25.4 (3.64)	27.7 (3.09)	32.8	
10	(52.63)	22.6 (3.28)	26.7 (2.97)	33	
11		7.03 (1.02)	15.2 (1.69)	86.45	
12	(117)	6.69 (0.97)	8.7 (0.97)	86.6	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 3/25/78
 TEST SAMPLE NITROCELLULOSE 14'SSALCONOL MIL-N-244A TIME 1050
 SAMPLE WEIGHT 19.5kg (43 lb) TEMP 32.8°C (91°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 36%
 BOOSTER WEIGHT 1.95kg (4.3 lb) BAR. PRESS 30.08
 TEST NO 81 (34-B-05) WIND DIR. 60°
 CONTRACT NO NAS13-50 WIND VEL 13 knots




FIELD EVALUATION Detonation, clean hole in witness plate

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST 19.5 kg (43 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/kg ^{1/3} (psi msec/lb ^{1/3})	Time of Arrival (msec)	Remarks
1		625.9 (90.78)	147.9 (16.48)	3.6	
2	(10.51)	1,027.8 (146.32)	159.1 (17.73)	3.7	
3		343.57 (49.83)	79.7 (8.88)	4.7	
4	(14.19)	435.9 (63.22)	126.1 (14.05)	5.0	
5		212.4 (30.81)	40.5 (4.52)	7.2	
6	(18.84)	214.8 (31.16)	52.3 (5.82)	7.15	
7		89.9 (12.9)	48.9 (5.45)	15.85	
8	(31.53)	101.4 (14.7)	63 (7.02)	15.55	
9		29.8 (4.32)	34.1 (3.80)	41.2	
10	(43.06)	(—)	(—)	—	No data from recorder
11		7.4 (1.07)	15.9 (1.77)	108.75	
12	(140.14)	6.81 (0.98)	16.7 (1.86)	108.1	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/25/78
 TEST SAMPLE NITROCELLULOSE 14-55 ALCOXOL MIL-W-244A TIME 1805
 SAMPLE WEIGHT 19.54g (43 lb) TEMP 35°C (95°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 33%
 BOOSTER WEIGHT 1.951g (4.3 lb) BAR. PRESS. 30.04
 TEST NO. 82 (34-B-06) WIND DIR. 10°
 CONTRACT NO. NAS13-50 WIND VEL. 1 knot




FIELD EVALUATION: Detonation occurred, clean hole in witness plate motion picture and still photographs taken.

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 19.5 kg (43 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/kg ^{1/3} (psi msec/lb ^{1/3})	Time of Arrival (msec)	Remarks
1	3.2	920.5 (133.5)	147.7 (16.46)	2.5	
2	(10.51)	1437.1 (208.43)	189.6 (21.13)	2.45	
3	4.33	625.9 (90.78)	104.7 (11.67)	3.65	
4	(14.19)	653.8 (94.83)	42.3 (4.71)	3.65	
5	5.74	265.5 (38.51)	8.54 (9.52)	5.55	
6	(18.84)	280.3 (40.65)	74.5 (8.3)	5.55	
7	9.61	92.5 (13.41)	114.3 (12.74)	13.7	
8	(31.53)	65.4 (9.48)	100.4 (11.19)	13.45	
9	19.22	26.1 (3.78)	31.1 (3.47)	37.2	
10	(63.06)	25.2 (3.65)	32.8 (3.66)	37.2	
11	42.71	7.24 (1.05)	16.1 (1.79)	100.8	
12	(140.14)	7.72 (1.12)	17.4 (1.94)	101.3	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/25/78
 TEST SAMPLE NITROCELLULOSE 14-55 ALCOXOL MIL-W-244A TIME 1524
 SAMPLE WEIGHT 19.54g (43 lb) TEMP 34.4°C (94°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 46%
 BOOSTER WEIGHT 1.951g (4.3 lb) BAR. PRESS. 30.02
 TEST NO. 82 (34-B-07) WIND DIR. 50°
 CONTRACT NO. NAS13-50 WIND VEL. 7 knots




FIELD EVALUATION: Detonation, clean hole in witness plate

EXPERIMENTAL RESULTS


TNT EQUIVALENCY TEST: 19.5 kg (43 lb) 8					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/kg ^{1/3} (psi msec/lb ^{1/3})	Time of Arrival (msec)	Remarks
1	3.2	(—)	(—)	—	
2	(10.51)	1153.4 (167.29)	176.8 (19.7)	3.0	
3	4.33	400 (58.02)	110.7 (12.34)	4.05	
4	(14.19)	544.9 (79.03)	144.2 (16.07)	4.25	
5	5.74	(—)	(—)	—	No useable data
6	(18.84)	242.9 (35.23)	52.9 (5.89)	6.45	
7	9.61	92.5 (13.41)	98.1 (10.93)	14.1	
8	(31.53)	101.4 (14.7)	51.9 (5.78)	14.2	
9	19.22	26.9 (3.9)	35.99 (4.01)	38.1	
10	(63.06)	21.96 (3.23)	33.5 (3.73)	38.35	
11	42.71	7.83 (1.13)	13.5 (1.5)	101.7	
12	(140.14)	7.72 (1.12)	12.3 (1.37)	102.6	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/28/78
 TEST SAMPLE NITROCELLULOSE 1455 ALCOHOL MIL-N-244A TIME 1109
 SAMPLE WEIGHT 19.5kg (43 lb) TEMP. 29.4°C (85°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 64%
 BOOSTER WEIGHT 1.95kg (4.3 lb) BAR. PRESS. 29.94
 TEST NO. B₂ (35-B-02) WIND DIR. 130°
 CONTRACT NO. NAS13-50 WIND VEL. 10 knots



FIELD EVALUATION: Detonation, clean hole in witness plate

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/28/78
 TEST SAMPLE NITROCELLULOSE 1455 ALCOHOL MIL-N-244A TIME 1015
 SAMPLE WEIGHT 19.5kg (43 lb) TEMP. 30°C (86°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 64%
 BOOSTER WEIGHT 1.95kg (4.3 lb) BAR. PRESS. 29.94
 TEST NO. B₂ (35-B-0) WIND DIR. 130°
 CONTRACT NO. NAS13-50 WIND VEL. 17 knots



FIELD EVALUATION: Detonation, clean hole in witness plate


EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 19.5 kg (43 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/ft ^{1/3} (ft-lb sec/ft ^{1/3})	Time of Arrival (msec)	Remarks
1	3.2	1242.4 (183.09)	142.2 (38.07)	2.6	
2	(10.51)	1481.1 (214.02)	113.2 (32.61)	2.6	
3	4.33	494.4 (71.7)	110.6 (32.32)	3.7	
4	(14.19)	449.4 (65.18)	120.8 (33.46)	3.65	
5	5.74	290.8 (42.17)	33.4 (3.72)	5.6	
6	(18.04)	309.9 (44.95)	127.3 (34.91)	5.5	
7	9.61	65.8 (9.55)	32.8 (3.43)	12.6	
8	(31.53)	(11.19)	60.5 (8.74)	13.3	
9	19.22	77.2 (—)	(—)		No useable Data
10	(63.06)	24.4 (3.54)	(—)	37.4	Bad impulse Data
11	42.71	8.96 (1.3)	15.8 (1.76)	101.3	
12	(140.14)	(—)	(—)		No Data

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 19.5 kg (43 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/ft ^{1/3} (ft-lb sec/ft ^{1/3})	Time of Arrival (msec)	Remarks
1	3.2	1244.6 (180.51)	133.8 (34.58)	3.4	
2	(10.51)	1044.4 (151.48)	182.1 (20.29)	3.4	
3	4.33	655.9 (95.14)	135.3 (35.08)	4.25	
4	(14.19)	851.5 (123.50)	120.4 (33.44)	4.6	
5	5.74	468.90 (68.02)	85.5 (9.53)	5.6	
6	(18.04)	332.1 (48.16)	86.2 (9.61)	6.05	
7	9.61	61.21 (8.88)	31.1 (3.46)	12.7	
8	(31.53)	67.1 (9.73)	82.8 (9.23)	14.25	
9	19.22	(—)	35.5 (3.95)	38.35	
10	(63.06)	27.03 (3.92)	(—)	38.8	Bad impulse Data
11	42.71	(—)	(—)	102.1	Bad Data
12	(140.14)	24.41 (3.54)	5.2 (0.57)	102.45	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/17/78
 TEST SAMPLE NITROCELLULOSE 1455 ALCOHOL MIL-H-244A TIME 1214
 SAMPLE WEIGHT 22.68kg (50 lb) TEMP 33.9°C (93°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 49%
 BOOSTER WEIGHT 2.27kg (5 lb) BAR. PRESS 30.02
 TEST NO. C₁ (33-8-08) WIND DIR. 260°
 CONTRACT NO. NAS13-50 WIND VEL. 5 knots




FIELD EVALUATION Detonation occurred, hole in witness plate

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST- 22.68 kg (50 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/10 1/3 (psi msec/10 1/3)	Time of Arrival (msec)	Remarks
1	3.37 (11.05)	1834.3 (266.04)	221.1 (24.64)	3.4	
2		1522.9 (220.89)	207.6 (23.13)	3.4	
3		836.6 (121.34)	174.1 (19.4)	4.5	
4	4.49 (14.74)	531.9 (77.14)	131.92 (14.7)	4.6	
5	6.06 (19.89)	414.2 (60.07)	95.75 (10.67)	6.6	
6		325.7 (47.24)	99.97 (11.14)	6.75	
7		97.5 (14.14)	64.6 (7.2)	15.1	
8	10.11 (33.2)	84.4 (12.24)	68.5 (7.63)	15.15	
9		25.7 (3.72)	37.1 (4.13)	39.9	
10	20.23 (66.3)	26.4 (3.83)	30.6 (3.41)	40.2	
11		7.52 (1.09)	14 (1.56)	107.4	
12	44.92 (147.4)	9.03 (1.31)	17.95 (2.0)	107.8	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/17/78
 TEST SAMPLE NITROCELLULOSE 1455 ALCOHOL MIL-H-244A TIME 1435
 SAMPLE WEIGHT 22.68kg (50 lb) TEMP 35.6°C (96°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 42%
 BOOSTER WEIGHT 2.27kg (5 lb) BAR. PRESS 29.96
 TEST NO. C₂ (33-8-09) WIND DIR. 115°
 CONTRACT NO. NAS13-50 WIND VEL. 3 knots




FIELD EVALUATION Detonation occurred, no hole in witness plate due to stand off

EXPERIMENTAL RESULTS


TNT EQUIVALENCY TEST- 22.68 kg (50 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/10 1/3 (psi msec/10 1/3)	Time of Arrival (msec)	Remarks
1		1315.5 (190.8)	199.8 (22.26)	2.15	
2	3.37 (11.05)	1427.8 (207.09)	205.4 (22.89)	2.15	
3		612.9 (88.89)	142.8 (15.91)	3.5	
4	4.49 (14.74)	396.5 (57.51)	117.1 (13.05)	3.0	
5	6.06 (19.89)	396.5 (57.51)	72.7 (8.1)	5.45	
6		262.48 (38.07)	95.2 (10.6)	5.4	
7		102.8 (14.91)	50.2 (6.49)	13.8	
8	10.11 (33.2)	97.4 (14.12)	63.98 (7.13)	14.0	
9		27.1 (3.92)	33.3 (3.71)	38.8	
10	20.21 (66.3)	23.5 (3.41)	30.1 (3.35)	39.1	
11		7.52 (1.09)	14.99 (1.67)	106.1	
12	44.92 (147.4)	8.48 (1.23)	15.97 (1.78)	106.7	

TEST TITLE: TNT EQUIVALENCY NITROCELLULOSE DATE: 8/17/78
 TEST SAMPLE: NITROCELLULOSE 14-5EALCONOL MIL-N-244A TIME: 1543
 SAMPLE WEIGHT: 22.68kg (50 lb) TEMP: 33.3°C (92°F)
 IGNITION SOURCE: J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY: 60%
 BOOSTER WEIGHT: 2.27kg (5 lb) BAR. PRESS: 29.96
 TEST NO: C₁ (33-8-10) WIND DIR: 145°
 CONTRACT NO: NAS13-50 WIND VEL: 6 knots



FIELD EVALUATION: Detonation occurred

TEST TITLE: TNT EQUIVALENCY NITROCELLULOSE DATE: 8/18/78
 TEST SAMPLE: NITROCELLULOSE 14-5EALCONOL MIL-N-244A TIME: 1015
 SAMPLE WEIGHT: 22.68kg (50 lb) TEMP: 32.8°C (91°F)
 IGNITION SOURCE: J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY: 55%
 BOOSTER WEIGHT: 2.27kg (5 lb) BAR. PRESS: 29.99
 TEST NO: C₁ (33-8-11) WIND DIR: 255°
 CONTRACT NO: NAS13-50 WIND VEL: 2 knots



FIELD EVALUATION: Detonation occurred

EXPERIMENTAL

RESULTS


TNT EQUIVALENCY TEST: 22.68 kg (50 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/in 1/3 (psi msec/in 1/3)	Time of Arrival (msec)	Remarks
1	3.37 (11.05)	1260 (182.74)	206.4 (29)	3.4	
2		1275.5 (184.99)	182.9 (26.38)	3.4	
3		583.7 (84.66)	118.7 (17.23)	4.45	
4	4.49 (14.74)	560.9 (81.35)	122.8 (17.68)	4.6	
5		220.3 (31.95)	92.9 (13.35)	6.5	
6	6.06 (19.89)	262.5 (38.07)	86.1 (12.59)	7	
7		79.7 (11.56)	50.9 (7.38)	15.5	
8	10.11 (33.2)	81.2 (11.77)	57.5 (8.41)	15.5	
9		22.8 (3.31)	32.6 (4.74)	40.8	
10	20.21 (66.3)	23.5 (3.41)	29.7 (4.31)	40.4	
11		6.62 (0.96)	13.01 (1.85)	108.3	
12	44.92 (147.4)	7.93 (1.15)	15.88 (2.27)	107.8	

EXPERIMENTAL

RESULTS

TNT EQUIVALENCY TEST: 22.68 kg (50 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/in 1/3 (psi msec/in 1/3)	Time of Arrival (msec)	Remarks
1		1156 (167.66)	173.7 (24.36)	3.5	
2	3.37 (11.05)	1337.1 (193.92)	196.9 (28.34)	3.4	
3		445.1 (64.56)	143.1 (20.55)	4.45	
4	4.49 (14.74)	460.6 (66.8)	115.3 (16.85)	4.7	
5		(---)	(---)	---	No Data
6	6.06 (19.89)	220.3 (31.95)	71.8 (10.4)	7	
7		90 (13.05)	56.1 (8.05)	15.8	
8	10.11 (33.2)	84.5 (12.25)	61.2 (8.82)	15.6	
9		24.5 (3.55)	33.5 (4.85)	41.1	
10	20.21 (66.3)	22.9 (3.32)	26.7 (3.85)	41.2	
11		7.17 (1.04)	12.65 (1.81)	108.8	
12	44.92 (147.4)	6.21 (0.9)	13.46 (1.95)	108.95	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/18/78
 TEST SAMPLE NITROCELLULOSE 14-SKALCONOL MIL-N-244A TIME 1227
 SAMPLE WEIGHT 22.60 kg (50 lb) TEMP. 33.9°C (93°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 47%
 BOOSTER WEIGHT 2.27 kg (5 lb) BAR. PRESS. 29.99
 TEST NO. C₅ (33-B-12) WIND DIR. 225°
 CONTRACT NO. NAS13-50 WIND VEL. 6 knots




FIELD EVALUATION: Detonation occurred.

EXPERIMENTAL

RESULTS

TNT EQUIVALENCY TEST 22.60 kg (50 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/kg 1/3 (psi msec/in 1/3)	Time of Arrival (msec)	Remarks
1		()	()	—	No Data
2	4.37 (14.35)	1146.3 (166.23)	294.4 (32.8)	2.3	
3		563.9 (81.78)	124.4 (13.59)	3.2	
4	4.49 (14.74)	590.1 (85.59)	72.9 (8.13)	3.55	
5		()	()	—	No Data
6	6.06 (19.89)	286.1 (41.5)	80.7 (8.99)	5.8	
7		93.6 (13.57)	25.9 (2.89)	13.8	
8	10.11 (33.2)	71.4 (10.34)	107.5 (11.98)	14.15	
9		24.5 (3.55)	35.9 (4)	39.1	
10	20.21 (66.3)	20.6 (2.99)	29.8 (3.32)	39.7	
11		7.03 (1.02)	12.47 (1.39)	106.6	
12	44.92 (147.4)	6.21 (0.9)	19.92 (2.22)	107.2	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/29/78
 TEST SAMPLE NITROCELLULOSE 1-0 S₁ ALCONOL MIL-N-244A TIME 1532
 SAMPLE WEIGHT 45 kg (99 lb) TEMP. 24.6°C (76°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 99%
 BOOSTER WEIGHT 5.26 kg (11.6 lb) BAR. PRESS. 29.84
 TEST NO. D₁ (35-B-03) WIND DIR. 220°
 CONTRACT NO. NAS13-50 WIND VEL. 0 k




FIELD EVALUATION: Detonation occurred no hole in witness plate due to the stand off. Still photographs of pretest and posttest taken. 500 fps and 24 fps motion picture film taken.

EXPERIMENTAL

RESULTS


TNT EQUIVALENCY TEST 45 kg (99 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/kg 1/3 (psi msec/in 1/3)	Time of Arrival (msec)	Remarks
1		1526.1 (221.34)	139.6 (15.56)	3.6	
2	4.46 (14.63)	999.7 (144.99)	143.7 (16.03)	4.15	
3		624.9 (90.63)	115.3 (12.85)	5.4	
4	6.02 (19.75)	340.6 (49.4)	114.1 (12.71)	6.2	
5		276.2 (40.04)	83.6 (9.31)	8.55	
6	8 (26.24)	224 (31.04)	79.3 (8.84)	9.85	
7		64 (9.28)	55.1 (6.14)	20.2	
8	13.38 (43.89)	74.9 (10.86)	55.3 (6.16)	21.8	
9		16.9 (2.45)	()	55.55	Bad Impulse Data
10	26.76 (87.79)	19.2 (2.78)	32.7 (3.64)	56.9	
11		7.31 (1.06)	()	146.4	Bad Impulse Data
12	59.46 (195.08)	7.65 (1.11)	16.51 (1.84)	147.4	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/31/78
 TEST SAMPLE NITROCELLULOSE 1-0.5% ALCOHOL MIL-N-244A TIME 1435
 SAMPLE WEIGHT 45 kg (99 lb) TEMP. 26.1°C (78°F)
 IGNITION SOURCE 32 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 83%
 BOOSTER WEIGHT 5.26 kg (11.6 lb) BAR. PRESS. 29.93
 TEST NO D₂ (35-B-04) WIND DIR. 115°
 CONTRACT NO. MAS13-50 WIND VEL 3 knots



FIELD EVALUATION: Detonation occurred, no hole in witness plate

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 9/1/78
 TEST SAMPLE NITROCELLULOSE 1-0.5% ALCOHOL MIL-N-244A TIME 1120
 SAMPLE WEIGHT 45 kg (99 lb) TEMP. 31.7°C (89°F)
 IGNITION SOURCE 23 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 45%
 BOOSTER WEIGHT 5.26 kg (11.6 lb) BAR. PRESS. 30.01
 TEST NO D₁ (35-B-05) WIND DIR. 300°
 CONTRACT NO. MAS13-50 WIND VEL 6 knots



FIELD EVALUATION: Detonation occurred, no hole in witness plate


EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 45 kg (99 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/in 1/3 (psi msec/in 1/3)	Time of Arrival (msec)	Remarks
1	4.46 (14.63)	608.5 (88.25)	128.2 (14.28)	4.3	
2		592.1 (85.88)	128.4 (14.31)	4.8	
3	6.02 (19.75)	300 (43.51)	88 (9.81)	6.5	
4		244.9 (38.42)	57.2 (6.37)	7.1	
5	8 (26.24)	192 (27.85)	(—)	10.45	Bad Impulse Data
6		187.2 (27.15)	(—)	11.25	Bad Impulse Data
7	13.38 (43.89)	50.7 (7.35)	43.6 (4.86)	22.8	
8		41.8 (6.96)	56.4 (6.28)	23.4	
9	26.76 (87.79)	25 (3.78)	36.4 (4.06)	57.3	
10		22.3 (3.24)	32.8 (3.66)	57.7	
11	59.46 (195.08)	8.42 (1.25)	14.72 (1.64)	146.75	
12		7.38 (1.07)	14 (1.56)	147.1	

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 45 kg (99 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/in 1/3 (psi msec/in 1/3)	Time of Arrival (msec)	Remarks
1	4.46 (14.63)	1167 (169.20)	164.4 (18.32)	2.2	
2		1372.2 (199.02)	160.5 (17.88)	2.4	
3	6.02 (19.75)	515.1 (74.71)	106.3 (11.84)	3.8	
4		605.5 (87.82)	97.8 (10.9)	4.1	
5	8 (26.24)	(—)	74.5 (8.3)	6.6	
6		190.6 (27.65)	(—)	7.1	Bad Impulse Data
7	13.38 (43.89)	38.1 (5.53)	(—)	18.8	
8		67.2 (9.75)	61.9 (6.9)	19.8	
9	26.76 (87.79)	20.1 (2.91)	37.4 (4.17)	53.6	
10		17.9 (2.6)	35.7 (3.98)	54.25	
11	59.46 (195.08)	8.34 (1.18)	13.2 (1.47)	143.7	
12		8.20 (1.19)	15.97 (1.78)	143.5	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 9/1/78
 TEST SAMPLE NITROCELLULOSE 1-0 5 ALCOHOL MIL-N 244A TIME 1435
 SAMPLE WEIGHT 45 kg (99 lb) TEMP. 33.3°C (92°F)
 INITIATION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 37%
 BOOSTER WEIGHT 5.26 kg (11.6 lb) BAR. PRESS. 29.99
 TEST NO 06 (35-8-06) WIND DIR. 340
 CONTRACT NO NAS12-50 WIND VEL. 3 knots




FIELD EVALUATION Detonation occurred, no hole in witness plate

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 45 kg (99 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/in 1/3 (psi msec/in 1/3)	Time of Arrival (msec)	Remarks
1	4.46 (14.63)	951.6 (138.01)	212.1 (23.63)	4.7	
2		1165.4 (169.03)	()	4.5	
3	6.02 (19.75)	381.6 (55.34)	102.1 (11.38)	6.5	
4		501.5 (72.73)	112.6 (12.55)	6.0	
5	8 (26.24)	160.9 (23.34)	76.3 (8.5)	10.1	
6		222.4 (32.26)	75.7 (8.43)	9.3	
7	13.38 (43.89)	55.6 (8.07)	51.9 (5.79)	22.4	
8		63.9 (9.27)	57.3 (6.38)	21.7	
9	26.76 (87.79)	24.9 (3.61)	40.7 (4.54)	56.7	
10		20.1 (2.92)	36.5 (4.07)	56.4	
11	59.46 (195.08)	9.17 (1.33)	20.37 (2.27)	145.9	
12		8.2 (1.19)	18.76 (2.09)	145.7	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 9/5/78
 TEST SAMPLE NITROCELLULOSE 1-0 5 ALCOHOL MIL-N 244A TIME 1220
 SAMPLE WEIGHT 45 kg (99 lb) TEMP. 32.2°C (90°F)
 INITIATION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 36%
 BOOSTER WEIGHT 5.26 kg (11.6 lb) BAR. PRESS. 29.96
 TEST NO 06 (36-8-01) WIND DIR. 40°
 CONTRACT NO NAS12-50 WIND VEL. 4 knots




FIELD EVALUATION Detonation occurred, no hole in witness plate

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 45 kg (99 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/in 1/3 (psi msec/in 1/3)	Time of Arrival (msec)	Remarks
1	4.46 (14.63)	908.9 (131.87)	115.8 (12.13)	4.6	
2		930.5 (134.96)	148.9 (16.59)	4.7	
3	6.02 (19.75)	379 (54.97)	106.2 (11.92)	6.6	
4		340.5 (50.26)	83.5 (9.3)	6.7	
5	8 (26.24)	170.7 (24.74)	39 (4.35)	10.2	
6		185 (26.87)	66.5 (7.41)	10.4	
7	13.38 (43.89)	54.4 (7.89)	60.8 (6.77)	21.7	
8		60.3 (8.74)	52.2 (5.82)	22.7	
9	26.76 (87.79)	22.3 (3.23)	39.9 (4.45)	57	
10		18.3 (2.65)	37.2 (4.14)	57.15	
11	59.46 (195.08)	7.52 (1.07)	12.03 (1.34)	145.8	
12		7.86 (1.14)	17.41 (1.94)	146.6	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/23/78
 TEST SAMPLE NITROCELLULOSE 14-SS ALCONOL MIL-R-244A TIME 1043
 SAMPLE WEIGHT 63.5kg (140 lb) TEMP. 31.1°C (88°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 45%
 BOOSTER WEIGHT 6.35kg (14 lb) Composition C4 BAR. PRESS. 30.08
 TEST NO. E1 (34-B-01) WIND DIR. 260°
 CONTRACT NO. NAS13-50 WIND VEL. 3 knots




FIELD EVALUATION: Detonation; a clean hole in witness plate; still photographs taken of set-up and posttest. No motion picture taken.

EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 63.5 kg (140 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/in 1/3 (psi msec/in 1/3)	Time of Arrival msec	Remarks
1	4.75	1028.9 (148.65)	118.4 (13.19)	4.5	
2	(15.58)	1205.8 (106.49)	164.2 (18.3)	4.5	
3		486.8 (70.6)	134.5 (14.99)	6.2	
4	6.32 (20.77)	538.8 (78.14)	138.2 (15.4)	6.25	
5		264.6 (35.77)	91.4 (10.18)	9.55	
6	8.55 (28.04)	245 (35.54)	95.6 (10.65)	9.6	
7		86 (12.47)	59.9 (6.64)	21.2	
8	14.24 (46.73)	86.9 (12.61)	55.7 (6.21)	21.35	
9		25.1 (3.64)	34.7 (3.87)	57	
10	28.49 (93.46)	21.2 (3.07)	31.7 (3.53)	57.2	
11		8.41 (1.22)	13.73 (1.53)	152.1	
12	63.32 (207.73)	7.24 (1.05)	14.81 (1.65)	153.8	

TEST TITLE TNT EQUIVALENCY NITROCELLULOSE DATE 8/24/78
 TEST SAMPLE NITROCELLULOSE 14-SS ALCONOL MIL-R-244A TIME 1534
 SAMPLE WEIGHT 63.5kg (140 lb) TEMP. 32.8°C (91°F)
 IGNITION SOURCE J2 ENGINEERS' SPECIAL BLASTING CAP HUMIDITY 45%
 BOOSTER WEIGHT 6.35kg (14 lb) Composition C4 BAR. PRESS. 30.04
 TEST NO. E2 (34-B-04) WIND DIR. 145°
 CONTRACT NO. NAS13-50 WIND VEL. 15 knots



FIELD EVALUATION: Detonation occurred; a clean hole in the witness plate.

Still & motion pictures taken of set-up and posttest. No motion pictures taken.


EXPERIMENTAL RESULTS

TNT EQUIVALENCY TEST: 63.5 kg (140 lb)					
Channel Number	Distance Meters (ft)	Peak Pressure kPa (psi)	Scaled Impulse kPa msec/in 1/3 (psi msec/in 1/3)	Time of Arrival msec	Remarks
1	4.75	1257.9 (190.34)	207.1 (22.52)		No Timing Marks
2	(15.58)	1337.1 (193.93)	179.1 (19.96)		No Timing Marks
3		428.2 (62.12)	106.7 (11.89)		No Timing Marks
4	6.32 (20.77)	423.3 (61.4)	66.1 (7.36)		No Timing Marks
5		240.4 (34.86)	97 (10.81)		No Timing Marks
6	8.55 (28.04)	276.4 (40.09)	92 (9.92)		No Timing Marks
7		()	()		Unable to Retrieve from Mag Tape
8	14.24 (46.73)	()	()		Unable to Retrieve from Mag Tape
9		30 (4.35)	34.17 (3.83)		No Timing Marks
10	28.49 (93.46)	()	()		Unable to Retrieve from Mag Tape
11		()	()		Unable to Retrieve from Mag Tape
12	63.32 (207.73)	()	()		Unable to Retrieve from Mag Tape

APPENDIX B

SELECTED PHOTOGRAPHS

APPENDIX B
SELECTED PHOTOGRAPHS



Pretest Configuration 11.34-kg Charge



Posttest Crater 11.34-kg Charge


DETERMINATION
 OF TNT
 EQUIVALENCY
 NITROCELLULOSE
 42.25 LBS
 MASTER 4.3 LBS C4
 24 11 07
 28 AUGUST 1976



Pretest Configuration 19.5-kg Charge

DETERMINATION
 OF TNT
 EQUIVALENCY
 NITROCELLULOSE
 42.25 LBS
 MASTER 4.3 LBS C4
 24 11 07
 28 AUGUST 1976

Posttest Crater and Witness Plate 19.5-kg Charge



Pretest Configuration 22.68-kg Charge



Posttest Crater and Witness Plate 22.68-kg Charge




Pretest Configuration before Drying 45 kg Charge



Posttest Crater and Witness Plate 45 kg Charge



Pretest Configuration 63.5-kg Charge



Posttest Crater and Witness Plate 63.5-kg Charge

APPENDIX C

TNT EQUIVALENCY PROGRAM

APPENDIX C

TNT EQUIVALENCY PROGRAM

This program calculates the pressure and impulse TNT equivalency by an iterative process which factors out the contributions from C4 booster charges*. For each set of input data, the parameters are calculated according to the following procedure:

1. Assume zero contribution from the booster charge. Then $W1 = W2 = W$, where $W1$ and $W2$ are the pressure- and impulse-related sample weights, respectively, and W is the sample charge weight.

2. Calculate approximate sample scaled distances from

$$Z1 = R / (W1)^{1/3} \quad (\text{pressure})$$

$$Z2 = R / (W2)^{1/3} \quad (\text{impulse})$$

3. Calculate an approximate TNT (equivalent) scaled distance, $Z5$, from the estimated sample TNT impulse equivalency, $E5$:

$$Z5 = Z2 / (.01 E5)^{1/3}$$

4. Calculate the TNT pressure and impulse scaled distances, $Z3$ and $Z4$ respectively, from curve-fits of reference data, see figure A1. Use separate straight line (log-log) segments depending on the value of $Z5$:

(a) If $Z5 \leq 9$,

$$Z3 = 27.133 P^{-0.4513}$$

$$Z4 = 47.247 I^{-(1/1.8215)}$$

(b) If $9 < Z5 \leq 18$,

$$Z3 = 36.016 P^{-0.5672}$$

$$Z4 = 55.874 I^{-(1/1.5672)}$$

(c) If $Z5 > 18$,

$$Z3 = 45.555 P^{-0.7557}$$

$$Z4 = 67.37 I^{-(1/1.9626)}$$

* Swatosh, J. J., and J. Cook, "TNT Equivalency of M1 Propellant (Bulk), Technical Report 4885, Ploatinny Arsenal, December 1975.

5. Calculate the approximate TNT pressure and impulse equivalencies, E1 and E2, from:

$$E1 = (Z1)^3 / (Z3)^3$$

$$E2 = (Z2)^3 / (Z4)^3$$

6. Using the equivalencies obtained in step 5, recalculate the pressure- and impulse-related sample weights, and the estimated TNT impulse equivalency:

$$W1 = W + (W3)(1.25/E1)$$

$$W2 = W + (W3)(1.25/E2)$$

$$E5 = (100)(E2)$$

where W3 is the booster charge weight.

7. Using the values obtained in step 6, work through from step 2 again to obtain new, improved values for E1, E2, W1, W2, and E5. Each iteration improves both the curve-fits in step 4 and the minimization of booster contributions in step 6. Continue the iteration until changes in E1 and E2 are insignificant.

8. Begin calculation for a new set of data at step 1.

The entire program with 10 sets of input data requires less than 4 Kbytes of memory. Therefore it can be used in small, portable microcomputer systems and desktop programmable calculators. The mean accuracy of the calculations over the range of scaled distances from 2.5 to 60 is about 1%. The maximum errors occur at scaled distances of 9 and 18, i.e., the inflection points of the straight-line TNT data curve fits, and amount to less than 5% of the calculated equivalencies.

TNT EQUIVALENCY PROGRAM

```

100 REM      INPUT DATA REQUIRED IS:
110 REM      (1) MATERIAL, CONFIGURATION, APPX. EQUIVALENCY
120 REM      (2) SAMPLE WT, BOOSTER WT, DISTANCE, PRESSURE,
130 REM      IMPULSE UP TO 10 CALCULATIONS CAN BE MADE IN
140 REM      ONE PASS.
150 INIT
160 DIM W(10), W3(10), R(10), Z(10), P(10), I1(10), I2(10)
170 DIM E1(10), E2(10)
180 PRINT "MATERIAL?"
190 INPUT M$
200 PRINT "CONFIGURATION?"
210 INPUT C$
220 PRINT "APPROXIMATE % EQUIVALENCY?"
230 INPUT E5
240 I=0
250 I=I+1
260 N1=I
270 PRINT "INPUT W(LB), BOOSTER(LB), R(FT), P(PSI), I(PSI*MSEC)"
280 INPUT W(I), W3(I), R(I), P(I), I1(I)
290 Z(I)=R(I)/W(I)+0.333
300 I1(I)=I1(I)/W(I)+0.333
310 PRINT "ANY MORE DATA?"
320 INPUT L$
330 IFL$= "Y" THEN 250
340 FOR I=1 TO N1
350 W1=W(I)
360 W2=W(I)
370 Z1=R(I)/W1+0.333
380 Z2=R(I)/W2+0.333
390 Z5=Z2/(0.01*E5)+0.333
400 IF Z5 > 18 THEN 520
410 IF Z5 > 9 THEN 470
420 A1=27.133
430 B1=0.4513
440 A2=47.247
450 B2=0.8215
460 GO TO 560
470 A1=36.016
480 B1=0.5672
490 A2=55.874
500 B2=0.8979
510 GO TO 560

```

```

520 A1=45.555
530 B1=0.7557
540 A2=67.37
550 B2=0.9626
560 B=1/(1+B2)
570 Z3=A1/P(I)+B1
580 Z4=(A2*Z2/I1(I))+B
590 E1(I)=Z1+3/Z3+3
600 E2(I)=Z2+3/Z4+3
610 W1=W(I)+W3(I)*1.25/E1(I)
620 W2=W(I)+W3(I)*1.25/E2(I)
630 E5=100*E2(I)
640 PRINT USING 650:"E(P)=", E1(I), "E(I)=", E2(I)
650 IMAGE 8X, 5A, 2X, 4D, 2D, 10X, 5A, 2X, 4D, 2D
660 PRINT "ITERATE AGAIN? ? ?"
670 INPUT T$
680 IF T$=>"Y" THEN 370
690 E1(I)=100*E1(I)
700 E2(I)=100*E2(I)
710 NEXT I
720 PAGE
730 PRINT USING 740:"TNT EQUIVALENCY OF", M$
740 IMAGE 18X, 19A, 3X, 20A/
750 PRINT USING 760:"CONFIGURATION:", C$
760 IMAGE 14X, 15A, 3X, 30A//
770 PRINT USING 780:"W", "R", "Z", "P", "I", "E(P)", "E(I) "
780 IMAGE 4X, 1A, 9X, 1A, 9X, 1A, 9X, 1A, 9X, 1A, 8X, 4A, 6X, 4A
790 PRINT USING 800:"LB", "FT", "SCALED", "PSF", "SCALED", "(%)", "(%) "
800 IMAGE 4X, 2A, 8X, 2A, 6X, 6A, 5X, 3A, 6X, 6A, 5X, 3A, 7X, 3A/
810 FOR I=1 TO N1
820 PRINT USING 830:W(I), R(I), Z(I), P(I), I1(I), E1(I), E2(I)
830 IMAGE 1X, 3D, 3D, 2X, 4D, 3D, 2X, 4D, 3D, 2X, 4D, 3D, 2X, 4D, 3D, 3X, 4D, 3X, 4D/
840 NEXT I
850 END

```

DISTRIBUTION LIST

Commander
U.S. Army Armament Research
and Development Command
ATTN: DRDAR-CG
DRDAR-LCM-3
DRDAR-LCM-S (5)
DRDAR-SF
DRDAR-GCL
DRDAR-TSS (5)
Dover, NJ 07801

Chairman
Department of Defense
Explosive Safety Board (2)
Room 856C, Hoffman Building I
2461 Eisenhower Avenue
Alexandria, VA 22331

Administrator
Defense Technical Information Center (12)
ATTN: Accessions Division
Cameron Station
Alexandria, VA 22314

Commander
Department of the Army
Office, Chief of Research, Development
and Acquisition
ATTN: DAMA-CSM-P
Washington, DC 20310

Office, Chief of Engineers
ATTN: DAEN-MCZ
Washington, DC 20314

Commander
U.S. Army Materiel Development
and Readiness Command
ATTN: DRCSF
DRCDE
DRCRP
DRCIS
5001 Eisenhower Avenue
Alexandria, VA 22333

Commander
DARCOM Installations and Services Agency
ATTN: DRCIS-RI
Rock Island, IL 61299

Director
Industrial Base Engineering Activity
ATTN: DRXIB
Rock Island, IL 61299

Commander
U.S. Army Munitions Production Base
Modernization Agency
ATTN: SARPM-PBM-T
SARPM-PBM-L
SARPM-PBM-E
Dover, NJ 07801

Commander
U.S. Army Armament Materiel
Readiness Command
ATTN: DRSAR-SF (2)
DRSAR-SC
DRSAR-EN
DRSAR-IRC
DRSAR-RD
DRSAR-IS
DRSAR-ASF
DRSAR-LEP-L
Rock Island, IL 61299

Director
DARCOM Field Safety Activity
ATTN: DRXOS-ES
Charlestown, IN 47111

Commander/Director
Chemical Systems Laboratory
U.S. Army Armament Research
and Development Command
ATTN: DRDAR-CLJ-L
APG, Edgewood Area, MD 21010

Director
U.S. Army Ballistic Research Laboratory
U.S. Army Armament Research
and Development Command
ATTN: DRDAR-TSB-S
Aberdeen Proving Ground, MD 21005

Chief
Benet Weapons Laboratory, LCWSL
U.S. Army Armament Research
and Development Command
ATTN: DRDAR-LCB-TL
Watervliet, NY 12189

Ammann and Whitney (2)
2 World Trade Center
New York, NY 10048

Commander
U.S. Army Armament Research
and Development Command
Weapons System Concept Team
ATTN: DRDAR-ACW
APG, Edgewood Area, MD 21010

Director
U.S. Army Materiel System
Analysis Activity
ATTN: DRXSY-MP
Aberdeen Proving Ground, MD 21005

Commander
Radford Army Ammunition Plant
Radford, VA 24141

Division Engineer
U.S. Army Engineer Division, Huntsville
ATTN: HNDCD
P.O. Box 1600, West Station
Huntsville, AL 35809

Civil Engineering Laboratory
Naval Construction Battalion Center
ATTN: L51
Port Hueneme, CA 93043

Commander
Naval Facilities Engineering Command
(Code 04, J. Tyrell)
200 Stovall Street
Alexandria, VA 22322

Commander
Kansas Army Ammunition Plant
Parsons, KS 67357

Commander
Badger Army Ammunition Plant
Baraboo, WI 53913

Commander
Indiana Army Ammunition Plant
Charlestown, IN 47111

Commander
Holston Army Ammunition Plant
Kingsport, TN 37660

Commander
Lone Star Army Ammunition Plant
Texarkana, TX 75501

Commander
Milan Army Ammunition Plant
Milan, TN 38358

Commander
Iowa Army Ammunition Plant
Middletown, IA 52638

Commander
Longhorn Army Ammunition Plant
Marshall, TX 75760

Commander
Louisiana Army Ammunition Plant
Shreveport, LA 71130