

AD-A097 665

NAVAL POSTGRADUATE SCHOOL MONTEREY CA
INITIAL VALIDATION OF AN AMBIENT AIR QUALITY MODEL FOR NAVAL AI--ETC(U)
DEC 80 T S DOUGLAS, D W NETZER


F/6 13/2

UNCLASSIFIED

NPS67-81-002

NL

1-2
AL
AL 00000




LEVEL *III*

②

14/ NPS67-81-002

NAVAL POSTGRADUATE SCHOOL
Monterey, California

AD A 097 665



DTIC
SELECTED
APR 8 1981
C

6) INITIAL VALIDATION OF AN AMBIENT
AIR QUALITY MODEL
FOR
NAVAL AIR OPERATIONS.
by
10 T. S. Douglas and D. W. Netzer

11 Dec 1980

12/13/1

Approved for public release; distribution unlimited.

Prepared for: Naval Air Propulsion Center
Trenton, New Jersey 09628

DTIC FILE COPY

81 4 13 064

NAVAL POSTGRADUATE SCHOOL
Monterey, California

Rear Admiral J. J. Ekelund
Superintendent

D. A. Schrady
Acting Provost

The work reported herein was supported by the Naval Air Propulsion Center, Trenton, New Jersey as part of the Naval Environmental Protection Technology Program.

Reproduction of all or part of this report is authorized.

This report was prepared by:

Terry Scott Douglas
T. S. Douglas
LT. U. S. Navy

David W. Netzer
D. W. Netzer, Associate
Professor of Aeronautics

Reviewed by

Released by:

M. F. Platzer
M. F. PLATZER, Chairman
Department of Aeronautics

William M. Tolles
W. M. Tolles
Dean of Research

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NPS67-81-002	2. GOVT ACCESSION NO. AD A097665	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) INITIAL VALIDATION OF AN AMBIENT AIR QUALITY MODEL FOR NAVAL AIR OPERATIONS		5. TYPE OF REPORT & PERIOD COVERED Final Report December 1980
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) T. S. Douglas and D. W. Netzer		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93940		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS N6237679WR00014
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Air Propulsion Center Trenton, New Jersey 09628		12. REPORT DATE December 1980
		13. NUMBER OF PAGES 126
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Naval Postgraduate School Monterey, CA 93940		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Air Pollution Aircraft Model		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) An initial validation of an Air Quality Assessment Model for Naval air operations was conducted at NAS Miramar, CA. A previously developed model was updated to appropriately represent 1978/79 operations and then evaluated for prediction sensitivity to variations in meteorological and dispersion model parameters. A joint effort with the Naval Air Propulsion Center, the Environmental Protection Agency/Northrup Services, Inc. and PMTC, Pt. Mugu		

DD FORM 1473
1 JAN 73EDITION OF 1 NOV 65 IS OBSOLETE
S N 1102-114-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE/When Data Entered

was conducted to obtain detailed data over a one-week period. Much of the measured pollution concentration data (including all of the suspended particulate data) was lost due to instrument and measurement technique problems. This severely limited the validation effort. Comparison of model predictions with the limited initial measured concentration data indicated that: (1) predicted CO concentrations were in good agreement with measurement, (2) predicted NOX concentrations from aircraft idle/taxi operations were too low, and (3) predicted total hydrocarbons and particulate concentrations were too high for aircraft idle/taxi operations and too low for environ sources. Model predictions were significantly improved by increasing engine RPM settings to above idle for all modes normally specified as idle. Model validation efforts would be improved if one-half integer stability categories could be measured and used in the model.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or
A	Special

DD Form 1473
1 Jan 73
S N 0102-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE/When Data Entered

TABLE OF CONTENTS

I.	INTRODUCTION-----	1
II.	OVERALL MODEL VALIDATION EFFORT-----	6
III.	NAS MIRAMAR INTENSIVE DATA ACQUISITION-----	8
IV.	AQAM MODIFICATIONS AND SENSITIVITY STUDY-----	17
A.	MODEL MODIFICATIONS-----	17
B.	SENSITIVITY STUDY PARAMETERS AND PREDICTIONS---	18
C.	EFFECT OF METEOROLOGICAL PARAMETERS ON MAXIMUM RECEPTOR CONCENTRATIONS-----	24
1.	Stability Category-----	26
2.	Lid Height-----	26
3.	Wind Speed-----	27
4.	Wind Direction-----	27
D.	EFFECT OF METEOROLOGICAL PARAMETERS ON CONCENTRATIONS AT SPECIAL RECEPTORS-----	27
1.	Stability Category-----	28
2.	Lid Height-----	33
3.	Wind Speed-----	33
4.	Wind Direction-----	33
5.	Special Receptor Locations-----	34
E.	EFFECT OF SPECIFIED AREA SOURCE SIZE ON RECEPTOR CONCENTRATIONS-----	36
F.	VARIATION OF JET PENETRATION LENGTH, INITIAL LINE SOURCE DIMENSIONS AND DISPERSION PARAMETERS-----	37
G.	CONCLUSIONS-----	39

V. COMPARISON OF AQAM PREDICTIONS WITH DATA FROM THE INTENSIVE STUDY-----	40
A. VALIDATION REQUIREMENTS-----	40
B. DATA REDUCTION AND MODEL INPUTS-----	42
C. DISCUSSION OF RESULTS-----	50
1. CO Emissions-----	51
2. NOX Emissions-----	55
3. THC Emissions-----	59
4. PT Emissions-----	60
D. CONCLUSIONS AND RECOMMENDATIONS-----	63
APPENDIX A Special Receptor Concentrations for Sensitivity Study-----	65
APPENDIX B CO and PT Concentration Profiles from Aircraft Sources (Sensitivity Study)-----	76
APPENDIX C CO and PT Concentration Profiles from Aircraft Sources (Intensive Study)-----	98
LIST OF REFERENCES-----	121
INITIAL DISTRIBUTION LIST-----	123

LIST OF TABLES

I.	Monitoring Station Locations-----	10
II.	Aircraft Activity Monitoring Times (Local)-----	12
III.	Special Receptor Locations-----	19
IV.	Meteorology for Sensitivity Study-----	20
V.	Aircraft Activity for Sensitivity Study-----	22
VI.	Maximum Receptor Concentrations-----	25
VIIa.	Special Receptor Concentrations (Stability Category Variation)-----	29
VIIb.	Special Receptor Concentrations (Lid Height Variation)-----	30
VIIc.	Special Receptor Concentrations (Wind Speed Variation)-----	31
VIId.	Special Receptor Concentrations (Wind Direction Variation)-----	32
VIII.	Difference Factors in Special Receptor Concentrations-----	35
IX.	AQAM Runs Made for Intensive Study-----	44

LIST OF FIGURES

1.	Grid Identification at NAS Miramar-----	9
2.	Takeoff Data Sheet-----	13
3.	Landing Data Sheet-----	14
4.	Hot Refuel Sequence Data Sheet-----	15
5.	Pit Refuel Sequence Data Sheet-----	16
6a.	Meteorological Conditions at NAS Miramar vs. Time of Day (1 Aug)-----	45
6b.	Meteorological Conditions at NAS Miramar vs. Time of Day (2 Aug)-----	46
6c.	Meteorological Conditions at NAS Miramar vs. Time of Day (3 Aug)-----	47
6d.	Meteorological Conditions at NAS Miramar vs. Time of Day (6 Aug)-----	48
6e.	Meteorological Conditions at NAS Miramar vs. Time of Day (7 Aug)-----	49
7.	Measured Versus Predicted Hourly Average CO Concentrations for Intensive Study-----	53
8.	Predicted CO Concentration Profiles Along 3 km. Y-Coordinate-----	56
9.	Measured Versus Predicted Hourly Average NOX Concentrations for Intensive Study-----	58
10.	Measured Versus Predicted Hourly Average THC Concentrations for Intensive Study-----	61
11.	Measured Versus Predicted Hourly Average PT Concentrations for Intensive Study-----	62

I. INTRODUCTION

In recent years several mathematical models have been developed to predict the atmospheric dispersion of pollutants emitted from aircraft-related activities at and around airports. These models have used the steady state Gaussian plume formulation. The Gaussian formulation is used because it is adaptable to distances and pollutant travel times associated with airports. An early contract sponsored by the U.S. Environmental Protection Agency (EPA) resulted in a model being developed by the Northern Research and Engineering Corporation (Ref. 1). This model was later modified by GEOMET, Inc. (Ref. 2), and dealt specifically with civilian airport operations. A more recent model has been developed by Argonne National Laboratory (ANL) for the USAF and was termed the Air Quality Assessment Model for Air Force Operations (AQAM) (Ref. 3). This computer model was based upon an earlier TRW model, the Air Quality Display Model (Ref. 4).

Each of the models utilizes a method for solution of diffusion equations assuming Gaussian dispersion in both the horizontal and vertical directions. Gaussian formulation in air quality model calculations requires meteorological inputs including stability of the atmosphere, mixing layer height, and wind direction and speed. Detailed pollution source data are also required. The resultant models consisted of emission and dispersion programs. AQAM included three major parts, a Source Inventory model which yields annual emission at an

activity by source, a Short Term dispersion model which performs hourly-averaged calculations using input dispersion parameters and a Long Term dispersion model. The models predict average steady-state concentrations during the specified time interval over a specified grid surrounding the airport.

Model verifications have to be conducted to test the algorithms and plume dispersion equations. Initial efforts to validate AQAM were begun by the Air Force at Williams AFB, Arizona. Williams AFB was chosen because it was a high traffic-volume, military airfield where accurate statistics would be available. These statistics included aircraft type, mix, and activity schedules from which emissions input data could be calculated (Ref. 5). The objectives of the validation effort were three-fold:

1. Collect a data base of airport-related air quality measurements to evaluate the Air Force AQAM model.
2. Determine the impact (if any) of airport-related activity on local (5 km radius) air quality.
3. Conduct a series of special studies to provide information on horizontal and vertical dispersion to supplement any model revision by ANL (Ref. 6).

The Navy became interested in the Argonne model capabilities relative to Naval Air operations. Under sponsorship of the Naval Air Propulsion Center (NAPC) Trenton, N.J., the Naval Postgraduate School (NPS), Monterey, Ca., obtained copies of both the Source Inventory and the Short Term models of AQAM

for evaluation and adaptation to Navy operations. Upon completion of modifications, a validation effort similar to the one at Williams AFB was planned at NAS Miramar, California.

The Source Inventory Program, as originally received from ANL, computes annual emissions of three types of sources: aircraft, airbase (non-aircraft) and environment (off-airbase). Each of these types is further reduced by geometric configuration to either a point, line or area source. Data are input to the Source Inventory program relative to the type and size of source, location of the emission plume in three-dimensional space and the mass emission rate of each pollutant emitted by the source. The model input is often comprehensive and voluminous, leaving a great margin for possible error. The program calculates annual emissions and provides a qualitative ranking of the contributions to the ambient air pollution of any individual source. It also prepares a data bank containing source characteristics, annual emission rates and temporal distribution activity for utilization by the Short Term program.

The Short Term program receives the above compiled annual results and calculates the dispersion of generated pollutants over a specified receptor grid during a given hour, day and month utilizing average meteorological data input for that hour (Ref. 7). For point and area sources this is accomplished by using initial source dimensions and meteorological stability criteria to project a pseudo-upwind point source. Line sources are generated along the route of travel of the source vehicles.

The Short Term model utilizes a line dispersion theory developed by ANL. The line of finite cross-section is segmented into shorter lines, or "puffs", which are then dispersed from pseudo-upwind line sources in much the same manner as point and area sources (Ref. 3,8).

Principal modifications to AQAM were required by the Navy due to differences in flight operations between the Navy and Air Force. Subroutines were added to AQAM to account for Visual Flight Rule (VFR) approaches including aircraft entry break above the runway, Navy touch-and-go cycles, field carrier landing practices (FCLP), takeoff delays, and hot refueling (refueling of aircraft while engines are operating). Also AQAM was expanded to handle helicopter operations. It should be noted that modifications were only made to subroutines involving aircraft sources. Airbase and environ source data remain relatively consistent from base to base whether Navy, Air Force or civilian. The Short Term portion of AQAM was modified to calculate dispersion of pollutants over 412 grid receptors rather than the Air Force's 312 receptors. This was done so that a larger off airbase area could be included in the analysis. Finally, Navy aircraft engines and fuel types are often different than those of the Air Force and, consequently, aircraft performance data and emissions data had to be input to reflect the changes. A plot routine was also incorporated into AQAM so that predicted pollutant distribution patterns could be more readily observed (Ref. 9).

The aforementioned model verification performed by the Air Force at Williams AFB involved 13 months of continuous air monitoring during the period June 1976 through June 1977. Air quality data were collected at five ground stations and meteorological data were taken routinely at the base weather station. Aircraft operations data and airbase and environ source information were then input to AQAM and predicted values of pollutant concentrations were compared with observed, or measured data from the monitoring stations. Preliminary results have indicated that a reasonable correlation exists between predicted and observed hourly pollutant levels (Ref. 10).

The Air Force effort included a wide range of meteorological conditions collected over a long period of time. It was decided to concentrate the Navy validation effort on a specific meteorological "window" which would be reasonably stable for several days and which would occur when a large amount of aircraft activity occurred. The latter was necessary in order to minimize the problem inherent with high background pollution levels. Specifically, it was desired to perform the validation effort at NAS Miramar, CA and to obtain more detailed data relative to (1) aircraft taxi and refueling operations, (2) hourly aircraft flight activity, and (3) meteorology.

Once the Navy modifications were completed and input data were obtained for NAS Miramar, it was necessary to determine

the sensitivity of the model predictions to the input meteorological and operational conditions and to certain dispersion model parameters. An initial model sensitivity study was performed using the Navy version of AQAM and 1975 activity at NAS Miramar as a representative data base (Ref. 9).

The purposes of the present study were (1) to update the data in the Source Inventory program of AQAM in order to represent 1978/1979 operations at NAS Miramar and (2) to compare the predicted and measured levels of pollutant concentrations for the purpose of validating the Short Term program of AQAM. A necessary component of the validation effort was the conducting of an updated model prediction sensitivity study.

II. OVERALL MODEL VALIDATION EFFORT

The Navy version of the AQAM model validation effort was initiated by the Naval Air Propulsion Center (NAPC). NAPC provided the funding and necessary program coordination as well as technical assistance in selection of the monitoring site locations and the required data acquisition. NAS Miramar was chosen because it had the largest number of flight operations of any NAS and because it had been used in previous work performed by the Naval Postgraduate School in developing the Navy version of AQAM.

The overall objectives of the NAPC program were to:

- a. validate the AQAM model,
- b. document the effects of aircraft operations on air quality, and

- c. assess the possibility of using AQAM (as an alternative to an expensive monitoring program) to determine the effects of aircraft operations on air quality at other NASs (Ref. 11).

The program was divided into two related parts. The first part was to consist of a one year continuous monitoring study. In late 1979 - early 1980 air quality was being measured 24 hours a day using an automated data acquisition system. This effort was directed primarily at objective (b) noted above. The second part was to consist of two special studies, each one-week in duration. The latter studies were to be intensive in nature with detailed operational, meteorological and pollution concentration data being collected. These studies were to be directed primarily at objectives (a) and (c) above. The first special study took place in August 1979 and data received from that week were used in the model validation discussed herein. The second special study was scheduled for the spring of 1980 but was subsequently cancelled. The two periods were chosen to occur during distinctly different meteorological conditions, especially lid height and stability category. Organizations involved in the special study and individual responsibilities of each included:

- a. Northrup Services Incorporated (NSI) contracted by EPA: Air quality monitoring and data reduction to provide hourly averaged pollutant levels.
- b. Pacific Missile Test Center (PMTTC): Meteorological measurements and data reduction to provide hourly


averaged weather conditions throughout the receptor grid.

- c. NAPC/NPS: Aircraft activity monitoring.
- d. NPS: Reduction of aircraft activity data for input into AQAM, model predictions using items b. and c. above, and comparison of predictions with measured values.

III. NAS MIRAMAR INTENSIVE DATA ACQUISITION

Planning the special study for validation of AQAM began with identifying both the emittants to be monitored to best characterize dispersion and, as previously mentioned, locating appropriate monitoring stations.

The major pollutants in aircraft engine exhausts include particulates/smoke (PT), carbon monoxide (CO), unburned hydrocarbons (HC) and oxides of nitrogen (NOX). The relative amounts emitted depend primarily upon the engine thrust setting. In addition, sulfur oxide emissions (SOX) are often significant from industrial and domestic furnaces. Therefore, CO, HC, NOX, PT and SOX were selected as the pollutants to characterize emissions of both aircraft and airbase related activity. Figure 1 identifies the grid system used to locate the receptors in AQAM. The grid spacing was 1 km. and the x-y coordinates varied from (0,0) to (24,15) representing 400 separate receptor locations.



GRID IDENTIFICATION AT NAS MIRAMAH

FIGURE 1

Locating measuring stations where continuous-air-monitoring instruments would be placed was of prime importance in the validation effort. The behavior of the model predictions at a particular receptor will depend to a great extent on its location relative to numerous sources throughout the receptor grid, especially those located upwind. To validate the model, it was important to compare air quality samples at locations where the airbase and aircraft contributions were large relative to background levels of pollution. Ultimate placement of the stations assumed a dominant wind from the WNW (292°) as advised by PMTC.

Up to 12 special receptor locations can be input to the Short Term program. Special receptor locations were assigned to each of the four pollution monitoring stations as indicated in Table I. They are also identified in Figure 1.

TABLE I
MONITORING STATION LOCATIONS

TRAILER NUMBER	GRID COORDINATES	SPECIAL RECEPTOR NUMBER IN AQAM
1	10.01, 8.24	401
2	10.52, 8.46	402
3	11.24, 8.35	406
4	12.82, 7.31	410

The intended use of trailer 1 was to determine background levels of pollution upwind of aircraft/airbase sources. Trailer 2 was located just downwind of the hot refueling site.

Trailer 3 was situated just upwind of the hot refueling pits. It was also downwind of the hot refueling area. Trailer 4 was located well downwind at the outer boundary of NAS Miramar.

During the planning stage, NSI made equipment preparations for each trailer site for the air quality monitoring experiment. PMTC analyzed the meteorological history for the San Diego area to determine the best time period for the special study. Optimum weather conditions for validation were considered to consist of a moderate wind coming from the 290 degree direction, a Turner stability category of 2-3, and a moderate lid height (mixing layer depth) of 400-500 meters. It was desirable to have relatively constant weather conditions for the week of intensive data acquisition. This would allow the dispersion model to be validated with multiple tests in which aircraft operations varied but weather remained approximately fixed. The week of 1-7 August 1979 was chosen as the most feasible for meeting these objectives for the first intensive study.

Operating procedures for the week proceeded on a previously planned routine. Specific tasks performed by NSI (pollution monitoring) and PMTC (meteorological monitoring) will be presented by those activities under separate cover. NPS and NAPC personnel monitored the detailed aircraft activity in accordance with the time schedule listed in Table II.

TABLE II
AIRCRAFT ACTIVITY MONITORING TIMES (LOCAL)

1 AUG	1300 - 1600
2 AUG	1000 - 1230 1400 - 1700
3 AUG	0800 - 1230
6 AUG	0900 - 1230 1330 - 1630
7 AUG	0830 - 1100 1330 - 1630

Observation of aircraft activity was performed/recorded from three locations -- the control tower, the hot refueling site (octagon) and the refueling pits.

The functions performed in the control tower involved (1) timing the sequences of every aircraft on departure from initial startup to takeoff, (2) timing the sequences of every aircraft on recovery from entry into the airport traffic area (defined here as having a three-mile radius) to landing and taxi to the refueling area. Also, the parking areas and taxiways used by each aircraft and the type of landing performed (VFR, IFR) were monitored. Data sheets used to record the aircraft activities observed from the control tower are presented in figures 2 and 3.

Data collected at the hot refueling sites (octagon) and refueling pits included time-in-mode, amount of fuel taken, and aircraft type (see data sheets in figures 4 and 5).

TAKEOFF DATA SHEET

DUTY RUNWAY _____ WIND _____ TIME _____

register/time

Side number _____ Aircraft type _____

Parking area _____

Commence sequence 0/0

Start complete _____ / _____

Taxi complete _____ / _____
(holding at runway)
(engine check complete)

Takeoff complete _____ / _____

EVOLUTION (check one)

Takeoff and depart area _____

FCLP _____ number _____

Touch and go _____ number _____

FIGURE 2

LANDING DATA SHEET
(full stop landings only)

DUTY RUNWAY _____ WIND _____ TIME _____

register/time

Side number _____ Aircraft type _____

Commence sequence _____ 0/0
(enter break or 3 mi. on IFR approach)

Landing complete _____
(clear of runway)

Taxi complete _____
(pits/hot refuel holding area)

Fuel commence _____
(enter pits/hot refuel area)

Fuel complete _____
(depart pits/hot refuel area)

Shutdown _____

Parking area _____
(hot refuel aircraft only)

FIGURE 3

HOT REFUEL SEQUENCE DATA SHEET
(OCTAGON)

TIME _____

A/C Type (circle one)

Side number _____

Arrival time
at
holding area _____

Arrival time
into
octagon _____

Departure time
from
octagon _____

Pounds fuel
received _____

Fuel spilled yes/no _____

F-4
F-5
F-8
F-14
A-4
E-2
Transient

FIGURE 4

PIT REFUEL SEQUENCE DATA SHEET

TIME _____

A/C Type (circle one)

Side number _____

Arrival time
at
holding area _____

Arrival time
into
refuel pit _____

F-4
F-5
F-8
F-14
A-4
E-2
Transient

Shutdown

(circle one)

Hot refuel

Pounds fuel
received _____

Fuel spilled yes/no

Departure time
from
refuel pit _____

Pounds fuel
received _____

Fuel spilled yes/no

FIGURE 5

The aircraft/airbase operational data that were collected were used as input to the Source Inventory program. Air quality measurements (by NSI) and meteorological data (by PMTC) were also being collected during the entire period of observation.

IV. AQAM MODIFICATIONS AND SENSITIVITY STUDY

A. MODEL MODIFICATIONS

In order to perform a model validation, the data input to the Source Inventory program must reflect, as closely as possible, conditions and emittant sources as they exist at the time of validation. Therefore, one of the purposes of this study was to update the data in AQAM to represent 1978/1979 operations at NAS Miramar.

Changes made to the input routines of the AQAM program included data input on the E-2 aircraft -- an addition at NAS Miramar since 1975. Parking area coordinates, taxiway usage and aircraft landing and take-off operational cycle time-in-mode (LTO) were all modified to accept E-2 aircraft activity. All data were input in accordance with guidelines stipulated in Refs. 7 - 9 and 12. Averaged meteorological data were changed to reflect 1978 figures. The annual amount of aircraft activity for 1978, including arrivals, departures, touch-and-go cycles, and FCLP's was entered according to aircraft type. The specific parking areas and taxiways used by each aircraft were modified. Other emissions information

(specifically; fuel spillage, training fires, environ land use area factors, and off base vehicle miles per year) was either added or updated. Airbase, non-aircraft activity modifications included changes in test cell and run-up stand usage.

B. SENSITIVITY STUDY PARAMETERS AND PREDICTIONS

With the update completed and reflecting conditions as they existed at the time of the first intensive study, an investigation was performed to determine the sensitivity of the model predictions to meteorological and operational conditions anticipated for 1-7 August 1979 (special study). Sensitivity results indicate under what conditions and at what receptor locations the model can best be validated. In addition, these results are needed before conclusions can be drawn from the comparison of measured and predicted pollution levels. In a model validation effort, predicted concentrations are compared to measured values at specific receptor locations. When making these comparisons it is necessary to know how sensitive the model predictions are to the uncertainties in the specified meteorological and operational input data. For example, stability category is normally specified as an integer value between one and six; if the hourly averaged value can only be specified as two or three, what effect would this variation have on the model predictions? In addition, it is necessary to know whether the monitoring stations are located in regions where there are large horizontal gradients in pollution concentrations.

Twelve special receptors were used to examine the sensitivity of predicted pollution levels in the vicinity of the four monitoring stations to various meteorological conditions and model parameters. A previous model sensitivity study had been conducted by Netzer (Ref. 9) using 1975 operational data and different nominal meteorological conditions. Table III describes the special receptor locations used in AQAM for both the sensitivity study and the validation effort. Locations relative to runways, taxiways and refueling areas are depicted in Figure 1.

TABLE III
SPECIAL RECEPTOR LOCATIONS

AQAM RECEPTOR NUMBER	DESCRIPTION/LOCATION
401	trailer 1
402	trailer 2
403	100 m downwind of trailer 2
404	100 m crosswind (south) of trailer 2
405	100 m crosswind (south- east) of trailer 2
406	trailer 3
407	100 m downwind of trailer 3
408	100 m crosswind (south) of trailer 3
409	approach end of runway 1
410	trailer 4
411	500 m upwind of trailer 4
412	100 m crosswind (north) of trailer 4

In order to perform the sensitivity study it was necessary to establish a reference or nominal case meteorologically and operationally. The anticipated weather conditions for the intensive study period, listed in Section III, were used as the reference weather. Meteorological parameters were varied independently, with aircraft activity kept constant. Table IV indicates the meteorology data input for each of nine computer runs.

TABLE IV
METEOROLOGY FOR SENSITIVITY STUDY

Run Number	Turner Stability	Wind Speed (m/s)	Wind Direction (deg)	Temperature (°F)	Lid Height (m)
1 (Reference)	2	4.12	290	80	400
2	1	4.12	290	80	400
3	3	4.12	290	80	400
4	2	4.12	290	80	300
5	2	4.12	290	80	500
6	2	2.06	290	80	400
7	2	6.18	290	80	400
8	2	4.12	270	80	400
9	2	4.12	310	80	400

Run number 1 was the reference case. The ambient air temperature was not varied because previous results (Ref. 9) had shown it to have little effect on predicted pollution levels.

The aircraft activity data input to the Source Inventory program were representative of one hour of daytime flight operations. In addition, airbase and environ sources were kept constant with updated 1978 data. In the normal mode of utilization of AQAM, annual totals are input and frequency factors are used to determine the total operations in any one month, week, day, and hour. For the present effort, the "desired" one hour input data had to be scaled up to annual operations in order that the Short Term and Source Inventory programs would function properly. The "scale-up" factor used was:

$$12 \text{ hr/day} \times 31 \text{ day/mo (Aug)} \times 12 \text{ mo/yr} = \underline{\underline{4464}} \text{ hr/yr (1)}$$

(12 hr/day represents no night operations)

Table V presents the aircraft activity values which were held constant for the entire sensitivity study.

TABLE V
AIRCRAFT ACTIVITY FOR SENSITIVITY STUDY

1 HOUR OPERATIONS					
AIRCRAFT	ARRIVALS	DEPARTURES	TOUCH & GO'S	VFR ARRIVALS	FCLP'S
F-4	3	3	2	2	6
F-8	1	1	1	1	0
E-2	1	1	1	1	0
F-14	3	3	2	2	6
A-4	2	2	1	1	0
F-5	1	1	0	1	0
TRANSIENT	1	1	0	0	0
H-3	0	0	0	0	0

1 YEAR OPERATIONS					
AIRCRAFT	ARRIVALS	DEPARTURES	TOUCH & GO'S	VFR ARRIVALS	FCLP'S
F-4	13392	13392	8928	8928	26784
F-8	4464	4464	4464	4464	0
E-2	4464	4464	4464	4464	0
F-14	13392	13392	8928	8928	26784
A-4	8928	8928	4464	4464	0
F-5	4464	4464	0	4464	0
TRANSIENT	4464	4464	0	0	0
H-3	0	0	0	0	0

As explained in Section I, the results from the Source Inventory program are used along with the meteorological data as input to the Short Term program. Output from the Short Term program was arranged in seven tables. Four tables consisted

of pollutant levels in micrograms per cubic meter from environ, airbase, aircraft and total sources at all specified grid receptors. Each table listed, for all receptors, the receptor number and x-y coordinate location, and the concentrations for all five pollutants. The remaining three tables expressed the same results in terms of fractions of the total emissions from environ, airbase and aircraft sources.

The receptors of interest in the sensitivity study were the twelve special receptors (401-412) and that one where the maximum concentrations existed.

To compare the expected effects of the meteorological variables on the predicted ground level ($z=0$) concentrations, the Gaussian dispersion formula for point sources can be used (Ref. 13).

$$\chi(x,y,z=0;H) = \frac{Q}{\pi\sigma_y\sigma_z\bar{U}} \exp\left[-\frac{1}{2}\left(\frac{y}{\sigma_y}\right)^2\right] \exp\left[-\frac{1}{2}\left(\frac{H}{\sigma_z}\right)^2\right] \quad (2)$$

where:

χ = concentration, g/m³

Q = uniform emission rate, g/sec

σ_y, σ_z = standard deviations of plume concentrations in the horizontal and vertical directions respectively, m

$\bar{U}$ = mean wind speed, m/sec

H = initial plume height, m

$y = 0$ along plume centerline

When vertical diffusion is limited by a stable layer at height h_{lid} the diffusion equation is modified as follows:

$$\chi(x,y,z;H) = \frac{q}{\sqrt{2\pi} \sigma_y h_{lid} \bar{U}} \exp \left[-\frac{1}{2} \left(\frac{y}{\sigma_y} \right)^2 \right] \quad (3)$$

For infinite line sources Turner (Ref. 13) utilized:

$$\chi(x,y,z=0;H) = \frac{2q}{\sin \phi \sqrt{2\pi} \sigma_z \bar{U}} \exp \left[-\frac{1}{2} \left(\frac{H}{\sigma_z} \right)^2 \right] \quad (4)$$

where:

q = source strength per unit distance, g/sec-m

ϕ = angle between line source and wind direction,
 $45^\circ < \phi < 90^\circ$

Major variations of the Short Term program predictions under different meteorological conditions should follow equations (2), (3), or (4), depending upon the receptor location relative to the dominant emission sources (Ref. 9).

C. EFFECT OF METEOROLOGICAL PARAMETERS ON MAXIMUM RECEPTOR CONCENTRATIONS

Table VI presents the predicted maximum concentrations of four of the five pollutants and the location of each for the reference case. Also shown are the maximum predicted CO and PT from aircraft sources for each of the other conditions investigated. The meteorological variable is listed in each case.

The reference case indicated that the maximum contributions from the environ sources occurred south of the airbase (at receptors (9,2) and (11,2)). However, high levels of environ pollution (background) also were predicted to occur throughout

TABLE VI
MAXIMUM CONCENTRATION CALCULATIONS
(GRID LOCATION, CONCENTRATION ($\mu\text{m}/\text{m}^3$), FRACTION OF TOTAL)

RUN NUMBER	AIRCRAFT			PT	AIRCRAFT			ENVIRON		
	CO	HC	HOX		CO	HC	HOX	CO	HC	PT
1	11,8	11,8	11,8	11,8	14,8	14,8	14,8	9,2	11,2	11,2
REFERENCE CASE	101	31	14	139	5	2	3	313	110	29
	.61	.74	.74	.98	.04	.05	.22	1.0	1.0	1.0

TOTAL				
CO	HC	HOX	PT	
9,2	11,2	11,2	11,8	
313	110	29	141	

1
REFERENCE
CASE

RUN NUMBER	AIRCRAFT		
	CO	HC	PT
2	11,8	11,8	
STAB CAT = 1	60	61	
	.50	.97	
3	13,8	11,8	
STAB CAT = 3	194	255	
	.69	.99	
4	11,8	11,8	
LID HT = 300m	103	150	
	.59	.99	
5	11,8	11,8	
LID HT = 500m	101	139	
	.66	.99	

RUN NUMBER	AIRCRAFT		
	CO	HC	PT
6	11,8	11,8	
WIND SPD = 2.06 m/sec	272	321	
	.63	.99	
7	11,8	11,8	
WIND SPD = 6.18 m/sec	71	94	
	.63	.97	
8	10,8	10,8	
WIND DIR = 270°	131	121	
	.61	.98	
9	11,8	11,8	
WIND DIR = 310°	96	106	
	.66	.98	

the airbase. On the airbase, the contribution from airbase sources was generally negligible, whereas aircraft sources of PT were dominant. Maximum concentrations from aircraft sources occurred for CO and PT at receptor (11,8), near the intersection of the runways. This was generally the case for all the conditions investigated.

1. Stability Category

Increasing the stability category (more stable conditions) decreases σ_y and σ_z , and therefore should increase the predicted ground level concentration along the wind vector downwind of the source (see equation (2)). At the peak concentration receptors (Table VI), which are necessarily near the plume centerline, the increase in stability category increased the concentration and shifted the maximum concentration receptor downwind.

2. Lid Height

As a plume develops downwind of a source it will spread in a vertical, as well as horizontal, direction. The ground and lid height (elevated inversion layer) act as reflectors of the plume. Increasing the lid height would decrease the concentration only at receptors which are far enough downwind from the source for reflections to occur (see equation (3)). For the maximum receptor location (11,8), lid height had negligible effect on the predicted aircraft concentrations of CO and PT (Table VI) since it was located near the major aircraft sources. However the aircraft contributions increased with lid height since concentrations from environs decreased.

3. Wind Speed

Increasing the wind speed should decrease predicted concentrations along the plume centerline for a single source (equations (2), (3) and (4)). This behavior was apparent for the maximum concentration receptors (Table VI, run nos. 6, 1 and 7).

4. Wind Direction

Changing wind direction changes the orientation of the plume dispersion. As a result, the receptor where concentrations were a maximum from aircraft sources was predicted to shift to receptor (10,8) when the wind direction became 270° (Table VI, run no. 8).

D. EFFECT OF METEOROLOGICAL PARAMETERS ON CONCENTRATIONS AT SPECIAL RECEPTORS

Short Term output for each of the nine sensitivity runs is presented in Appendix A for the special receptors. The reference case (run no. 1) output includes receptor concentrations for environ, airbase, aircraft, and total sources in $\mu\text{gm}/\text{m}^3$ as well as fractional values for aircraft sources. Receptor concentrations for aircraft sources (run nos. 2-9) are included in $\mu\text{gm}/\text{m}^3$ and fraction of total. In order to visualize variations in pollutant concentration, the overall grid system was mapped with contour levels for the sensitivity study in Appendix B. Contours for the reference case are included for CO and PT concentrations from airbase, aircraft, and total sources. Contours for run nos. 2-9 are included for CO and PT concentrations from aircraft sources.

Tables VIIa-d summarize the special receptor concentrations of CO and PT for each of the nine sensitivity runs. In general, the comments relating to the maximum receptor concentrations pertain to the special receptor concentrations. From a modeling standpoint special receptor 401 (trailer 1) proved to be well located for the purpose of measuring background pollutants. As can be seen in Tables VIIa-d, very little CO and PT due to aircraft exist at receptor 401. When finite values did occur (run nos. 2, 3, 7, 8 and 9) they resulted from the aforementioned method of projecting area sources (in this case -- the hot refueling area) upwind to pseudoc-point sources.

1. Stability Category

An increase in stability category increases the downwind concentration along the plume centerline from a single source since the plume spreads more slowly. Table VIIa indicates that the area around trailer 1 (receptors 402-405) receives emittants from multiple sources since the concentrations of CO and PT first decreased and then increased with increasing stability category. These receptors are also located very near large sources.

CO and PT concentrations around trailer 3 (receptors 406-408) were significantly higher than those around trailer 2 due to the effect of an increased number of plumes overlapping downwind. Some multiple/near source effects were also evident at this location. The receptor concentrations around trailer 4 (receptors 410-412) changed only slightly with variations

TABLE VIII
 SPECIAL READER CERTIFICATIONS
 (STABILITY CAMERA VARIATION)

NO. 2400	ALIAS LAT. DATE	401 TRAILER 1	402 TRAILER 2	403 100m TRAILER 2	404 100m TRAILER 2	405 100m TRAILER 2	406 100m TRAILER 2	407 100m TRAILER 2	408 100m TRAILER 2	410 TRAILER 4	411 500 TRAILER 4	412 100m TRAILER 4	409 100m TRAILER 4
2	CU	3	55	81	85	63	121	285	270	21	21	24	827
STAB CAT -	PT	20	53	54	123	65	77	204	226	23	25	25	572
1	CU	0	3	30	49	45	98	314	225	23	25	33	575
STAB CAT -	PT	0	13	35	106	178	78	331	241	26	30	29	2706
3	CU	5	98	111	141	119	246	444	366	38	53	43	1074
STAB CAT -	PT	28	130	174	225	228	162	424	306	50	68	52	660
3		93	99	98	99	99	98	99	99	96	97	96	99

Concentration, 100/m³
 Fraction of Total
 KEY - Concentration, 100/m³
 Fraction of Total

TABLE VII
SPECIAL RECEPTION CONCENTRATIONS
(LID HEIGHT VARIATION)

WATER NUMBER	ALUMINUM CONCENTRATION	401 TRAILER 1	402 TRAILER 2	403 100m DOWNWIND	404 100m DOWNWIND	405 100m DOWN WIND CROSS	406 TRAILER 3	407 100m DOWNWIND	408 100m DOWNWIND	410 TRAILER 4	411 500m DOWNWIND	412 100m DOWNWIND	409 APPROX LID OF IN
4 LID HT = 300m	CO PT	0 0 0	3 13 88	30 25 93	49 106 98	45 178 99	95 78 97	220 331 99	221 240 99	29 34 93	30 38 94	32 37 94	3072 2710 3575
1 LID HT = 500m	CO PT	0 0 0	3 13 87	30 25 93	49 106 98	45 178 99	98 78 97	314 331 99	225 241 99	22 26 93	25 30 95	26 29 94	3575 2706 3575
5 LID HT = 500m	CO PT	0 0 0	3 13 89	30 25 94	49 106 98	45 178 99	98 78 98	314 331 99	225 240 99	19 22 94	23 28 95	23 25 95	3575 2706 3575

Concentration, $\mu\text{g}/\text{m}^3$
Fraction of Total
KEY = Concentration, $\mu\text{g}/\text{m}^3$
Fraction of Total

TABLE VIII

KEY =

TABLE VIII
SPECIAL LOCATION CONCENTRATIONS
(WIND DIRECTION VARIATION)

RUN NUMBER	AUXILIARY EQUIPMENT	401 TRAILER 1	402 TRAILER 2	403 100m DOWNWIND	404 100m (CROSSWIND)	405 100m DOWN AND CROSS	406 TRAILER 3	407 100m (DOWNWIND)	408 100m (CROSSWIND)	410 TRAILER 1	411 50m (DOWNWIND)	412 100m (CROSSWIND)	409 ATTACHED END OF ROW
8 WIND DIR = 270°	OD PT	0 0	27 143	22 52	125 167	72 132	152 135	535 610	225 240	7 9	10 12	9 11	973 517
1 WIND DIR = 270°	OD PT	0 0	3 13	30 25	49 106	45 178	98 78	314 331	225 241	22 26	25 30	26 29	3575 2706
9 WIND DIR = 310°	OD PT	3 18	2 1	5 4	14 30	54 88	4 5	71 38	51 30	41 34	31 29	48 39	1692 1192

Concentration, $\mu\text{g}/\text{m}^3$ Fraction of Total
Key = Concentration, $\mu\text{g}/\text{m}^3$ Fraction of Total

in meteorological conditions due to the large downwind distance from the primary sources. Concentrations at receptor 409 were high as expected due to its close proximity to runway and taxiway line sources.

2. Lid Height

At trailers 2 and 3 lid height had no effect (Table VIIb). This was expected since these locations are very near the sources of pollution. At trailer 4, which is far downwind, increasing lid height decreased concentrations.

3. Wind Speed

As indicated in Table VIIc, an increase in wind speed decreased the concentration downwind at trailers 3 and 4. Again, however, at trailer 2 the behavior was more random.

4. Wind Direction

Changing the wind direction from the reference 290° to 310° (run no. 9) resulted in the expected reduction in aircraft CO and PT at trailers 2 and 3 (Table VIId). In this case the plumes from the major upwind aircraft sources miss receptors 402 and 406. However, when the wind direction was changed to 270° (run no. 8), the concentrations increased significantly. This indicates that trailer 2 was apparently outside the plume from the hot refueling area when the wind was from 290° . Further evidence of this was that receptors 404 and 405 (crosswind to 402) had significantly higher concentrations than receptors 402 and 403.

The trailer 4 receptor exhibited an increase in concentration with an increase in wind direction. This was expected

since most aircraft source plumes (including the maximum receptor location at coordinate (11,8) are located upwind of trailer 4, from the 290° - 310° direction.

5. Special Receptor Locations

As discussed above, for model validation efforts it is necessary to know whether the monitoring stations are located in regions where there are large horizontal gradients in pollution concentration or where the concentrations are very sensitive to the specified hourly-averaged meteorological conditions. Table VIII presents a summary of the effects of distance from the monitoring stations on the predicted pollution concentrations. Concentrations are presented for each of the nine cases for conditions 100m downwind and 100m crosswind. As a receptor is moved toward a specific plume centerline, the concentration would increase. When a receptor is located downwind from several sources, horizontal movement of the receptor may increase or decrease the receptor pollution level, depending on the multiple plume effects.

Increases in concentration varied by factors of two to sixteen at trailers 2 and 3 for the reference case as a result of moving the receptor 100m downwind or closer to plume centerline. No appreciable horizontal gradients in concentration existed around trailer 4. In almost every case (variation of meteorological parameters), concentrations increased as expected, since the receptors were moved closer to the centerlines of the major aircraft-related plumes for the 290° wind. In run no. 8,

TABLE VIII
DIFFERENCE FACTORS IN SPECIAL RECEPTOR CONCENTRATIONS

RUN NO.		<u>Trailer 2</u>		<u>Trailer 3</u>		<u>Trailer 4</u>
		100m down- wind 403/402	100m cross- wind 404/402	100m down- wind 407/406	100m cross- wind 408/406	
1 Reference	CO	inc 10	inc 16	inc 3	inc 2.3	No change
	PT	inc 2	inc 8	inc 4.3	inc 3	
2 Stability Category	CO	inc 1.5	inc 1.5	inc 2.5	inc 2.3	No change
	PT	no change	inc 2.5	inc 3.8	inc 3.3	
3	CO	inc 1.5	inc 1.5	inc 1.8	inc 1.5	No change
	PT	dec 1.1	inc 1.7	inc 2.5	inc 2.3	
4 Lid Height	CO	inc 10	inc 16	inc 3	inc 2.3	No change
	PT	inc 2	inc 8	inc 4.3	inc 3	
5	CO	inc 10	inc 16	inc 3	inc 2.3	No change
	PT	inc 2	inc 8	inc 4.3	inc 3	
6 Wind Speed	CO	inc 1.3	inc 1.7	inc 3.8	inc 2.8	No change
	PT	dec 1.5	inc 1.8	inc 5	inc 4	
7	CO	inc 1.3	inc 1.8	inc 2.5	inc 2	No change
	PT	inc 1.5	inc 4.5	inc 3.3	inc 2.8	
8 Wind Direction	CO	dec 1.3	inc 5	inc 3.5	inc 1.5	No change
	PT	dec 2.8	inc 2.5	inc 4.5	inc 2	
9	CO	inc 2.5	inc 7	inc 18	inc 13	No change
	PT	inc 4	inc 30	inc 7.5	inc 6	

where the wind direction was changed from 290° to 270° , the concentration at the 100m downwind location decreased at trailer 2.

These results again indicate that comparison between measurements and predictions will be most difficult at trailer 2. Not only do multiple plume effects and the close proximity to ground aircraft sources cause unusual variations in concentration with changing meteorology but also the horizontal gradients are quite large.

E. EFFECT OF SPECIFIED AREA SOURCE SIZE ON RECEPTOR CONCENTRATIONS

When large sources are input into AQAM they are normally modeled as area sources. The dimensions of the area sources have to be specified and some judgement is required to pick the most representative dimensions of these "uniform concentration sources." To determine what effect the specified size of aircraft area sources had on concentrations at various receptors, the lengths of the sides of three prime sources were both increased and decreased by forty percent. The specific sources included the hot refueling area, the hot refueling delay area and the pit refueling delay area. The length of the sides of each area source in the reference case was 500 meters. This length was changed to 300 meters and then to 700 meters.

Increasing the size of an area source effectively moves the pseudo-upwind point source further upwind. Keeping the

emittants and meteorology constant, the plume would spread at the same rate. At a specific receptor, the concentration can increase or decrease, depending on its location relative to the area sources. For this study, the variations in concentrations at trailers 2, 3, and 4 never exceeded six percent.

F. VARIATION OF JET PENETRATION LENGTH AND HORIZONTAL AND VERTICAL DISPERSION PARAMETERS

In AQAM, turbojet exhausts during taxi and takeoff are treated as finite line sources. Initial line source dimensions and locations have to be specified and these are somewhat arbitrary. Currently in AQAM the jet is assumed to "penetrate 140 meters" (i.e., approximately 140 jet diameters) before coming to rest relative to the ambient air. Default values for the line source cross-sectional size are 8m high by 20m wide. No plume rise is considered to occur. These line sources are then treated as pseudo-upwind lines which disperse in a Gaussian manner with the same empirical dispersion parameters (σ_y, σ_z) as used for elevated point sources.

In a recent study at the Naval Postgraduate School (Ref. 14) jet characteristics were measured in a simulated, neutrally stable atmosphere. It was found that jet penetration length was considerably less than 140 jet diameters; being more nearly 35 jet diameters. Initial plume dimensions were found to vary significantly with jet orientation to the ambient wind direction and some plume rise was observed. Jet dispersion rates were also found to be more rapid than currently used in AQAM.

In order to determine whether the above findings would have any significant effects on the predicted concentrations from aircraft sources, AQAM was modified in sequential steps as follows:

- (1) decrease the jet penetration length from 140 to 35 meters.
- (2) step (1) and specification of initial aircraft line source (taxiway and runway) dimensions as a function of orientation to the wind (per fig. 40, Ref. 14).
- (3) steps (1) and (2) and decrease the stability category by one to increase the jet plume spreading rate.

Decreasing the penetration length was found to have little effect. This was somewhat expected since the aircraft line sources at NAS Miramar have lengths up to 3.7 km. The reduction in jet penetration length was but three percent of the longest line source. In step (2) the angle of incidence formed by the wind with each line source was determined, and using the σ_y and σ_z versus angle of incidence relationship determined by Brendmoen and Netzer, new horizontal and vertical dispersion parameters were input to the Short Term program. In general, the changes involved increases in initial line source dimensions. At the maximum concentration receptor and at trailers 3 and 4, a nominal reduction in concentrations of up to a maximum of 16 percent was predicted.

In step (3) the above changes were kept in AQAM and the stability category was decreased from 3 to 2 (more unstable conditions). Output indicated a decrease in concentration of up to a factor of two at the maximum concentration receptor and at trailers 3 and 4. It should be noted that in its present form AQAM only allows variation of stability category for all dispersions as opposed to variation of aircraft sources alone. This decrease was expected as previously determined in the meteorological sensitivity study.

G. CONCLUSIONS

Stability category and wind speed were the two meteorological parameters that most affected maximum receptor concentrations. Model predictions will therefore be most sensitive to uncertainties in the hourly-averaged values of these parameters which are input into AQAM. Wind direction had a large effect on the concentrations at trailer 2. Trailer 2 is apparently located in an area where large horizontal gradients of pollutant concentrations exist, i.e., near the edges of the plumes from large aircraft sources.

Trailer 1 appears to be a good location for measurement of background pollution levels.

Variations in aircraft area source sizes did not appreciably affect concentration levels at specific receptors.

Variations of the specified jet penetration length and initial horizontal and vertical dispersion parameters of aircraft exhaust plumes during taxi, takeoff and landing modes

changed concentrations by a maximum of only 16 percent. The data of Brendmoen and Netzer (Ref. 14) indicated that turbo-jet exhausts spread more rapidly than elevated point sources. This result, when incorporated into AQAM, significantly affected predicted concentration levels (by a factor of 2) at the monitoring trailer locations.

V. COMPARISON OF AQAM PREDICTIONS
WITH
DATA FROM THE INTENSIVE STUDY

A. VALIDATION REQUIREMENTS

As previously stated, model validation consists of comparing predicted hourly-averaged pollutant concentrations to hourly-averaged measured values at specific receptor locations. A determination of model accuracy must be made within the context of the accuracy of the input operational data and of the hourly-averaged meteorology and measured concentrations. It is important to note that although the meteorology and pollutant concentrations may be constantly varying, only hourly-averaged values are used. Comparisons between measured and predicted concentration values in areas where large horizontal gradients exist (trailer 2) are likely to exhibit widely-varying results. Because of these factors, a need exists for a vast amount of accurate data with which to conduct model validation.

Prior to the comparison of measured and predicted values, background levels/local air quality must be determined in order

to be able to separate the contributions of aircraft, airbase and environ sources throughout the receptor grid. The Source Inventory program allows for input of environ sources. If these data are not available, approximate inputs can be included through the use of land-use factors. The factors (Ref. 12) distinguish between city center, urban, rural, park areas, etc. Input for off-base line sources (roadways) requires appropriate vehicle mileage and speed values. The selection of appropriate land-use factors used in this study was somewhat judgemental. The roadway line source values used were based on actual average daily traffic volumes for 1978 as provided by the Comprehensive Planning Organization of the San Diego Region. One method for determining actual concentrations from aircraft/airbase sources is to subtract values from an upwind measurement (i.e., trailer 1 data) from values obtained at each of the other special receptors.

Comparison of weekend measured data at each special receptor with weekday data should also provide a good indication of background/envIRON pollutant levels due to the reduction in aircraft activity at NAS Miramar on weekends. The measured data indicated a wind speed varying from calm to five knots on Saturday and Sunday approximately 90% of the time. The wind direction also varied up to 130° throughout the two-day period. This slight-to-stagnant air motion apparently caused an accumulation of pollutants at NAS Miramar from environ (local San Diego) sources. Unfortunately, this behavior

invalidated any comparison between weekday and weekend concentrations for the purposes of validating weekday background levels on the airbase. Therefore, a need exists for additional weekend data when the meteorological conditions are more representative of those experienced during the period of intensive measurement.

B. DATA REDUCTION AND MODEL INPUTS

Measured data for CO, NOX and THC were provided by NSI in parts per million (ppm). Comparison of these values to AQAM predictions requires conversion to micrograms per cubic meter ($\mu\text{gm}/\text{m}^3$). An accurate conversion exists for CO under standard conditions; $1111.11 \times \text{ppm CO} = \mu\text{gm}/\text{m}^3 \text{ CO}$. The most often used conversion for NOX is based upon NO_2 : $2000 \times \text{ppm NOX} = \mu\text{gm}/\text{m}^3 \text{ NOX}$. Measured data were obtained for THC and CH_4 . CH_4 often is the major portion of THC concentration in urban atmospheres of North American latitudes. Typical concentrations are 1.25-1.5 ppm (Ref. 6). The CH_4 conversion is $666.67 \times \text{ppm CH}_4 = \mu\text{gm}/\text{m}^3 \text{ CH}_4$. However, aircraft generated hydrocarbons may be significantly heavier than CH_4 . The only PT data available were measured by a nephelometer in terms of the scattering coefficient, b (bscat). Air samples were also taken to determine total particulates (TP), but the data were invalidated as a result of a filter preparation error by contractors at U. C. Davis. This loss of the TP data severely affected the model validation effort. Particulate concentrations on the airbase had the best chance to be dominated by aircraft sources and therefore provided one of the best means for comparing predictions with measurements. For the bscat data,

an average conversion factor was employed (Ref. 15 : 16.15 $\mu\text{g}/\text{m}^3$ Neph (Obscat) $\approx \mu\text{g}/\text{m}^3$ FT). The latter conversion factor may be in considerable error.

The AQAM model was run over ten one-hour time periods as listed in Table IX. The type of aircraft activity varied considerably throughout the ten AQAM runs. When different from normal operations, remarks of the activity are included in Table IX. The chosen periods of time were primarily in the afternoon when the wind speed and lid height are greatest.


Figures 6a-e present the meteorological conditions at NAS Miramar (obtained from NAS, Pt. Mugu investigators) for the days of intensive measurements and detailed observation of aircraft activity. The values are hourly-averaged and plotted over the 1000-2000 time period for each day. All weather conditions were averaged over the applicable time periods shown cross-hatched in Figures 6a-e.

Runs 5 and 9 were performed to determine whether or not transit time of emittants affected predicted concentration levels relative to runs 4 and 8. A fifteen minute emittant travel time was chosen due to the wind speed and average distance from source to monitoring station. It should be noted that the final runs (6-7 August) had significantly higher wind speed, temperature and lid height. This variation in meteorology was not anticipated and was somewhat undesirable from a model validation viewpoint.

Due to variations in meteorology within the calculated dispersion times, it is generally agreed that the values of


TABLE IX
AQM RUNS MADE FOR INTENSIVE STUDY

RUN NUMBER	DATE AND TIME PERIOD	WEATHER CONDITIONS					AIRCRAFT ACTIVITY	
		TURNER STABILITY CATEGORY	WIND SPED (M/SEC)	WIND DIRECTION (DEG)	TEMP (°F)	LID HEIGHT (M)	REMARKS	
1	1 AUG 1300-1400	2	2.57	290	81	353	--	--
2	1400-1500	2	2.57	290	81	353	--	--
3	2 AUG 1400-1500	3	2.57	290	77	522	--	--
4	1500-1600	3	2.57	270	77	517	H1 T/O, H1 LDG	
5	1515-1615	2	1.54	270	76	515	H1 T/O, H1 LDG	
6	3 AUG 1100-1200	1	2.57	230	77	586	--	--
7	6 AUG 1400-1500	3	3.60	270	91	1287	LO T/O, LC LDG, LO FCLP	
8	1500-1600	3	3.09	270	90	1229	H1 T/O, LOW LDG	
9	1515-1615	3	3.09	270	90	1229	H1 T/O, NORMAL LDG	
10	7 AUG 1500-1600	3	3.09	300	82	539	LO T/O, NORMAL LDG, FCLP	




METEOROLOGICAL CONDITIONS AT NAS MIRAMAR VS. TIME OF DAY (1 AUG)

Figure 6a




METEOROLOGICAL CONDITIONS AT NAS MIRAMAR VS. TIME OF DAY (2 AUG)

Figure 6b




METEOROLOGICAL CONDITIONS AT NAS MIRAMAR VS. TIME OF DAY (3 AUG)

Figure 6c



METEOROLOGICAL CONDITIONS AT NAS MIRAMAR VS. TIME OF DAY (6 AUG)

Figure 6d



METEOROLOGICAL CONDITIONS AT NAS MIRAMAR VS. TIME OF DAY (7 AUG)

Figure 6e

σ_y and σ_z cannot be more accurate than a factor of 2. In addition to this uncertainty, model predictions are sensitive to the average meteorology used as input as discussed above. For example, consider the data presented in Fig. 6a for the period 1300-1400 hrs. During this period the wind direction changed from 270° to 300° and the stability category changed from 1 to 2. The lid height and wind speed were steady. Values employed for wind direction and stability category for this period (Table IX, run no. 1) were 290° and 2, respectively. The sensitivity study of section IV has shown that a decrease in wind direction of 20° and a decrease in stability category from 2 to 1 can increase the predicted concentrations at trailer 3 by factors of 1.5 and 1.3 respectively. Thus, measured data and predictions could be different by a factor of approximately 2 due to uncertainty in model meteorological input alone.

C. DISCUSSION OF RESULTS

This discussion is divided into four sections -- one for each of the pollutants measured. The included figures are scatter plots of measured CO, NOX, THC and nephelometer readings versus predicted concentrations. The diagonal lines drawn in these figures enclose predictions that are within a factor of two of the corresponding measurements. These lines were found to enclose greater than 50% of all the plotted points. Much of the measured data were invalidated by NSI and were therefore not available for plotting. This is the reason for the differences in numbers of

plotted points from graph to graph and was a major limitation in the validation effort. In fact, only approximately 45% of the pollution data taken during the intensive study were considered acceptable. None of the data taken during the first three days of the intensive study met the validation criteria in the EPA quality plan. However, those data had to be used in order to have even a minimum of data to compare with model predictions.

Variations in predicted pollutant concentrations over the airbase were mapped with contour levels for the intensive study and are presented in Appendix C. Contours for run no. 4 (2 Aug, 1500-1600) are included for CO and PT concentrations from airbase, aircraft and total sources. Contours for the other nine runs are included only for CO and PT concentrations from aircraft sources.

1. Carbon Monoxide (CO) Emissions

A comparison of the CO emitted each weekday with the CO emitted during the weekend (period of reduced aircraft activity) was performed to better determine the CO background level. It was found that on Saturday afternoon the level was higher than that on Monday by a factor of two, possibly due to heavy traffic conditions on the surrounding roadways. Also, on Sunday, when the winds were mostly calm or from the south, a high level of CO was measured at trailer 1. As previously stated, weather conditions for the weekend during the period of intensive measurement were not representative of

weather conditions during the weekdays. Therefore, no conclusions could be drawn from this comparison regarding the validity of using trailer 1 measurements as indicators of background CO levels.

Figure 7 indicates that measured concentrations agreed with predicted total concentrations within a factor of two at trailers 1 and 4. The agreement was within a factor of approximately three for trailer 3 data. (No measured CO data for trailer 2 was available during the ten one-hour time periods used in this study.) However, the good agreement may be chance since the environ input (land-use factors, vehicle mileage data, etc.) was only estimated. In other words, what if the high levels of CO concentration at trailer 1 were due to aircraft, but the model did not have properly input aircraft operations or did not correctly determine dispersion rates? AQAM predicted that the CO concentration due to aircraft at trailer 1 was essentially zero. To check this, the Source Inventory program was modified so that all aircraft climb angles on takeoff were decreased. This maximized the near ground emissions from aircraft in the area near trailer 1. This change had no effect on CO at trailer 1. Also, the sensitivity study discussed above indicated no effect from increasing the hot refueling area and hot refueling delay area source sizes. In other words, some inaccuracy in aircraft source specification near trailer 1 would not cause increased concentrations at that receptor. Therefore, it appears to be a valid assumption that trailer 1 was a good




FIGURE 7
Measured vs. Predicted Hourly Average CO Concentrations for Intensive Study

background level indicator when a westerly wind prevailed, and the AQAM environ input for CO was reasonable. The model predicted that CO concentrations due to environ sources were nearly constant over the entire airbase.

To check the validity of AQAM predictions for CO emissions due to aircraft, trailer 1 measured concentrations (now assumed to be reasonable background CO) were subtracted from the measured concentrations at trailers 3 and 4. Figure 7 shows good agreement for the very limited data available. The higher predicted aircraft CO values at trailer 3 may result either from inaccurate specification of aircraft idle CO emissions in the hot refueling area or from a too slowly-spreading plume. It was observed at NAS, Miramar that many times aircraft were operated at above idle RPM in modes traditionally input into the model as "idle". To briefly examine the effect of the specified engine RPM on the model predictions, all "idle" operations were changed to "normal". For most engines this decreases the relative amounts of CO and UHC while increasing NOX and PM. However, total emittants increase since the fuel flow rate increases. In reality the "normal" setting is far too high to be realistic. This high throttle setting is more realistic for CO and UHC (since they generally decrease rapidly with RPM at low speeds and then level off) than for NOX and PT (which generally increase in a linear manner with RPM). A more accurate method would have been to use " $\frac{1}{2}$ idle + $\frac{1}{2}$ normal", or etc. The increased power setting improved the comparison with measured CO at trailer 3 (Fig. 7). A change of 1 in stability category input to AQAM could also

significantly change the predicted concentrations at trailer 3.

In addition to predicting reasonably accurate concentrations at specific receptors, a model should also correctly predict concentration profiles across the receptor grid. A CO concentration profile across the airbase was constructed (Figure 8) to illustrate the variation in predicted concentration along the wind direction. In the two cases plotted, the wind was from 270° and the stability category was 3. The two profiles were plotted along the 8 km. y-coordinate since this y-coordinate most nearly passed through the trailer 1-4 locations. Predicted and measured trailer data that were available were also plotted. "Trailer profiles" were sketched only to indicate general trends and do not necessarily represent actual variations. The comparison shows, as expected, that the predicted trailer 1-4 variation had a much larger gradient than the 8 km. profile due to closer proximity to aircraft ground operations (taxiways, hot refueling areas, parking areas). The measured profiles for both 2 Aug and 6 Aug were similar to the predicted profiles, peaking between trailers 2 and 3. The higher predicted values at trailer 3 were discussed above. Also shown in Figure 8 is the improved "trailer profile" obtained when engine RPM was increased from "idle" to "normal" as discussed above.

2. NOX Emissions

Comparison of weekend/weekday data again permitted no significant conclusions regarding the validity of using trailer 1 as an indicator of background NOX.





FIGURE 8
Predicted CO Concentration Profiles Along 8 km. y-coordinate

Figure 9 presents measured versus predicted hourly-average NOX concentrations for trailers 1, 2, and 4. (No measured data were available for trailer 3 during the ten one-hour time periods selected for validation efforts). As previously stated, the comparison was based upon an NO₂ conversion factor for ppm to $\mu\text{gm}/\text{m}^3$. Predicted concentrations from both aircraft sources alone and total sources are plotted to indicate their relative magnitudes. Predicted total concentrations at trailers 1 and 4 agreed with measured concentrations within a factor of approximately three. It should be noted that the predicted concentrations were all very small and varied much less than the measured data. Also, the measured data at trailer 2 were much greater than predicted NOX concentrations.

Because of the general agreement between trailer 1 measured and predicted concentrations, it appears that trailer 1 again provided a good representation of background concentrations. Therefore, trailer 1 measured concentrations were subtracted from those measured at trailers 2 and 4 and compared to predicted aircraft NOX emissions. Again, at trailer 2 the measured (difference) values were much greater than predicted aircraft concentrations. At trailer 4 the measured (difference) data agreed reasonably well with predicted aircraft data (both were very small). Since trailer 4 and trailer 1 concentrations were nearly the same for both measured and predicted data, and only approximately one-half of



Measured vs. Predicted Hourly Average NOx Concentrations For Intensive Study

FIGURE 9

the predicted trailer 4 values were due to aircraft, trailer 4 was probably outside most of the aircraft plumes for the existing wind conditions.

Because trailer 2 was located in a near-source region where lateral concentration gradients were large, comparisons were also made to crosswind receptor concentrations. The (trailer 2 - trailer 1) measured concentrations were compared to the predicted concentrations from aircraft at special receptor 404 (100m crosswind/south of trailer 2). The predicted concentrations were still much less than measured concentrations, indicating that the predicted concentration gradients around trailer 2 were not enough to significantly improve the comparison between predictions and measurements.

These results indicate that the NOX emissions from aircraft engines specified in AQAM are too low for low power engine operations (idle and taxi). An alternative explanation is that the aircraft engine settings for aircraft located around trailer 2 (hot refueling area, taxiways, and parking areas) are well above idle, thus producing more NOX than assumed by AQAM. Increasing the engine settings from idle to normal as discussed above did greatly improve the comparison between (trailer 2 - trailer 1) predictions and measurements (from 10 to 136 $\mu\text{gm}/\text{m}^3$ vs. 120 $\mu\text{gm}/\text{m}^3$ measured for 2 Aug from 1400-1500 hrs).


3. Total Hydrocarbon (THC) Emissions

The measured versus predicted total hourly-averaged THC concentrations for trailers 1, 3 and 4 are plotted in


Figure 10. (No measured data were available for trailer 2). The conversion factor used for ppm to $\mu\text{gm}/\text{m}^3$ was based on CH_4 and was therefore only an approximation for total hydrocarbons. As can be seen from the figure, predicted data were significantly lower and varied much more than measured data. Measured trailer 1 concentrations were approximately 1.5 times greater than trailer 3 concentrations. This decrease is nearly the same as expected for downwind dispersion from far upwind sources (i.e., due to changes in σ_y in equation 3). These results indicate that almost all THC was probably from environ sources. AQAM predicted concentrations at trailer 3 were greater than those at trailers 1 and 4 due to aircraft ground activity. If most of the measured concentrations of THC are in fact due to environ sources and measured trailer 1 values are accurate, then either AQAM values for THC emittants due to environ sources are low (i.e., land-use factors are low) or the conversion factor to $\mu\text{gm}/\text{m}^3$ is in significant error. The former would also imply that the values used in AQAM for THC emittants from aircraft sources are too high (at trailer 3 downwind of the hot refueling area). This particular observation could have been better clarified had measured data been available from trailer 2. Increasing engine RPM as discussed above in this case reduces THC from aircraft. When combined with increased environ sources of THC, this change would improve the agreement with measurements.

4. Particulate (PT) Emissions

Figure 11 is a plot of the measured (converted bscat) versus predicted total hourly averaged PT concentrations. The



Measured vs. Predicted Hourly Average THC Concentrations for Intensive Study



Measured vs. Predicted Hourly Average FT Concentrations for Intensive Study

measured data were within $\pm 40\%$ of the mean value. The measured values at trailers 1 and 4 were essentially the same. The comparison is fairly good (within a factor of three for 70% of the data) at trailers 1 and 4 using the aforementioned conversion factor for bscat to $\mu\text{gm}/\text{m}^3$. The model, however, appears to overpredict PT concentrations at trailer 2. AQAM predicts that most of the PT concentration is from aircraft sources. Therefore, if trailer 1 data are good indicators of background PT concentration, then AQAM has low environ source PT input (land-use factors, vehicle mileage, etc.) and/or high aircraft source PT input. Increasing engine RPM as discussed above increases PT and makes the comparison generally less favorable.

C. CONCLUSIONS AND RECOMMENDATIONS

Approximately 50% of the predicted levels of concentration were found to agree with measured levels within a factor of two. The results also indicated that: (1) predicted CO concentrations agreed quite well with measured data; (2) model predictions were too low for NOX emissions from aircraft operating in the idle/taxi mode; and (3) predicted THC and PT concentrations were too high for aircraft operating in the idle/taxi mode and/or were too low for environ sources. The latter appears more reasonable. Agreement between model predictions and measured values was significantly improved by increasing engine RPM settings above idle in all modes normally specified at idle.

For a reasonably complete model validation to be accomplished much more measured data must be obtained during a specific time period of observed meteorological and operational activity. The conclusions from this intensive study were based on very limited data and can only be considered preliminary results. Accurate data for background levels/local air quality are important for determination of aircraft source contributions to total emittants. It would be most beneficial to obtain pollution measurements on weekends at a time when aircraft activity is low and meteorological conditions are very similar to weekday conditions. If at all possible, any additional intensive efforts should be conducted during a period with less variations in meteorology. Detailed data collection should begin several days before the detailed operational data are collected in order to ensure a more complete data set than was obtained in this initial effort.

Model predictions were very sensitive to the specified stability category. Model validation efforts could be improved if stability classes could be measured and specified to half-integer values.

Jet dispersion rate differences from those for elevated, low velocity sources and variations with orientation to the wind direction require further study. Plume rise of jet exhausts should also receive additional study.

Special Receptor Concentrations for Sensitivity Study

[illegible]

THIS PAGE IS BEST QUALITY PRINTING
COPY FURNISHED TO NSA

THIS PAGE IS BEST QUALITY FRAMING
FROM COPY FURNISHED TO BDC

[illegible]

1951-1952 - 465
1952-1953 - 600
1953-1954 - 1000
1954-1955 - 1000
1955-1956 - 1000
1956-1957 - 1000
1957-1958 - 1000
1958-1959 - 1000
1959-1960 - 1000
1960-1961 - 1000
1961-1962 - 1000
1962-1963 - 1000
1963-1964 - 1000
1964-1965 - 1000
1965-1966 - 1000
1966-1967 - 1000
1967-1968 - 1000
1968-1969 - 1000
1969-1970 - 1000
1970-1971 - 1000
1971-1972 - 1000
1972-1973 - 1000
1973-1974 - 1000
1974-1975 - 1000
1975-1976 - 1000
1976-1977 - 1000
1977-1978 - 1000
1978-1979 - 1000
1979-1980 - 1000
1980-1981 - 1000
1981-1982 - 1000
1982-1983 - 1000
1983-1984 - 1000
1984-1985 - 1000
1985-1986 - 1000
1986-1987 - 1000
1987-1988 - 1000
1988-1989 - 1000
1989-1990 - 1000
1990-1991 - 1000
1991-1992 - 1000
1992-1993 - 1000
1993-1994 - 1000
1994-1995 - 1000
1995-1996 - 1000
1996-1997 - 1000
1997-1998 - 1000
1998-1999 - 1000
1999-2000 - 1000
2000-2001 - 1000
2001-2002 - 1000
2002-2003 - 1000
2003-2004 - 1000
2004-2005 - 1000
2005-2006 - 1000
2006-2007 - 1000
2007-2008 - 1000
2008-2009 - 1000
2009-2010 - 1000
2010-2011 - 1000
2011-2012 - 1000
2012-2013 - 1000
2013-2014 - 1000
2014-2015 - 1000
2015-2016 - 1000
2016-2017 - 1000
2017-2018 - 1000
2018-2019 - 1000
2019-2020 - 1000
2020-2021 - 1000
2021-2022 - 1000
2022-2023 - 1000
2023-2024 - 1000
2024-2025 - 1000
2025-2026 - 1000
2026-2027 - 1000
2027-2028 - 1000
2028-2029 - 1000
2029-2030 - 1000
2030-2031 - 1000
2031-2032 - 1000
2032-2033 - 1000
2033-2034 - 1000
2034-2035 - 1000
2035-2036 - 1000
2036-2037 - 1000
2037-2038 - 1000
2038-2039 - 1000
2039-2040 - 1000
2040-2041 - 1000
2041-2042 - 1000
2042-2043 - 1000
2043-2044 - 1000
2044-2045 - 1000
2045-2046 - 1000
2046-2047 - 1000
2047-2048 - 1000
2048-2049 - 1000
2049-2050 - 1000
2050-2051 - 1000
2051-2052 - 1000
2052-2053 - 1000
2053-2054 - 1000
2054-2055 - 1000
2055-2056 - 1000
2056-2057 - 1000
2057-2058 - 1000
2058-2059 - 1000
2059-2060 - 1000
2060-2061 - 1000
2061-2062 - 1000
2062-2063 - 1000
2063-2064 - 1000
2064-2065 - 1000
2065-2066 - 1000
2066-2067 - 1000
2067-2068 - 1000
2068-2069 - 1000
2069-2070 - 1000
2070-2071 - 1000
2071-2072 - 1000
2072-2073 - 1000
2073-2074 - 1000
2074-2075 - 1000
2075-2076 - 1000
2076-2077 - 1000
2077-2078 - 1000
2078-2079 - 1000
2079-2080 - 1000
2080-2081 - 1000
2081-2082 - 1000
2082-2083 - 1000
2083-2084 - 1000
2084-2085 - 1000
2085-2086 - 1000
2086-2087 - 1000
2087-2088 - 1000
2088-2089 - 1000
2089-2090 - 1000
2090-2091 - 1000
2091-2092 - 1000
2092-2093 - 1000
2093-2094 - 1000
2094-2095 - 1000
2095-2096 - 1000
2096-2097 - 1000
2097-2098 - 1000
2098-2099 - 1000
2099-2100 - 1000
2100-2101 - 1000
2101-2102 - 1000
2102-2103 - 1000
2103-2104 - 1000
2104-2105 - 1000
2105-2106 - 1000
2106-2107 - 1000
2107-2108 - 1000
2108-2109 - 1000
2109-2110 - 1000
2110-2111 - 1000
2111-2112 - 1000
2112-2113 - 1000
2113-2114 - 1000
2114-2115 - 1000
2115-2116 - 1000
2116-2117 - 1000
2117-2118 - 1000
2118-2119 - 1000
2119-2120 - 1000
2120-2121 - 1000
2121-2122 - 1000
2122-2123 - 1000
2123-2124 - 1000
2124-2125 - 1000
2125-2126 - 1000
2126-2127 - 1000
2127-2128 - 1000
2128-2129 - 1000
2129-2130 - 1000
2130-2131 - 1000
2131-2132 - 1000
2132-2133 - 1000
2133-2134 - 1000
2134-2135 - 1000
2135-2136 - 1000
2136-2137 - 1000
2137-2138 - 1000
2138-2139 - 1000
2139-2140 - 1000
2140-2141 - 1000
2141-2142 - 1000
2142-2143 - 1000
2143-2144 - 1000
2144-2145 - 1000
2145-2146 - 1000
2146-2147 - 1000
2147-2148 - 1000
2148-2149 - 1000
2149-2150 - 1000
2150-2151 - 1000
2151-2152 - 1000
2152-2153 - 1000
2153-2154 - 1000
2154-2155 - 1000
2155-2156 - 1000
2156-2157 - 1000
2157-2158 - 1000
2158-2159 - 1000
2159-2160 - 1000
2160-2161 - 1000
2161-2162 - 1000
2162-2163 - 1000
2163-2164 - 1000
2164-2165 - 1000
2165-2166 - 1000
2166-2167 - 1000
2167-2168 - 1000
2168-2169 - 1000
2169-2170 - 1000
2170-2171 - 1000
2171-2172 - 1000
2172-2173 - 1000
2173-2174 - 1000
2174-2175 - 1000
2175-2176 - 1000
2176-2177 - 1000
2177-2178 - 1000
2178-2179 - 1000
2179-2180 - 1000
2180-2181 - 1000
2181-2182 - 1000
2182-2183 - 1000
2183-2184 - 1000
2184-2185 - 1000
2185-2186 - 1000
2186-2187 - 1000
2187-2188 - 1000
2188-2189 - 1000
2189-2190 - 1000
2190-2191 - 1000
2191-2192 - 1000

[illegible]

Run No. 4

TABLE 1.00. DATA FOR THE 1000 HOURS OF THE WEEKEND

PERIOD	INCOME	EXPENSE	SALES	PROFIT	LOSS	NET
1000	1000	1000	1000	1000	1000	1000
1001	1001	1001	1001	1001	1001	1001
1002	1002	1002	1002	1002	1002	1002
1003	1003	1003	1003	1003	1003	1003
1004	1004	1004	1004	1004	1004	1004
1005	1005	1005	1005	1005	1005	1005
1006	1006	1006	1006	1006	1006	1006
1007	1007	1007	1007	1007	1007	1007
1008	1008	1008	1008	1008	1008	1008
1009	1009	1009	1009	1009	1009	1009
1010	1010	1010	1010	1010	1010	1010
1011	1011	1011	1011	1011	1011	1011
1012	1012	1012	1012	1012	1012	1012
1013	1013	1013	1013	1013	1013	1013
1014	1014	1014	1014	1014	1014	1014
1015	1015	1015	1015	1015	1015	1015
1016	1016	1016	1016	1016	1016	1016
1017	1017	1017	1017	1017	1017	1017
1018	1018	1018	1018	1018	1018	1018
1019	1019	1019	1019	1019	1019	1019
1020	1020	1020	1020	1020	1020	1020

TABLE 1.01. DATA FOR THE 1000 HOURS OF THE WEEKEND

PERIOD	INCOME	EXPENSE	SALES	PROFIT	LOSS	NET
1000	1000	1000	1000	1000	1000	1000
1001	1001	1001	1001	1001	1001	1001
1002	1002	1002	1002	1002	1002	1002
1003	1003	1003	1003	1003	1003	1003
1004	1004	1004	1004	1004	1004	1004
1005	1005	1005	1005	1005	1005	1005
1006	1006	1006	1006	1006	1006	1006
1007	1007	1007	1007	1007	1007	1007
1008	1008	1008	1008	1008	1008	1008
1009	1009	1009	1009	1009	1009	1009
1010	1010	1010	1010	1010	1010	1010
1011	1011	1011	1011	1011	1011	1011
1012	1012	1012	1012	1012	1012	1012
1013	1013	1013	1013	1013	1013	1013
1014	1014	1014	1014	1014	1014	1014
1015	1015	1015	1015	1015	1015	1015
1016	1016	1016	1016	1016	1016	1016
1017	1017	1017	1017	1017	1017	1017
1018	1018	1018	1018	1018	1018	1018
1019	1019	1019	1019	1019	1019	1019
1020	1020	1020	1020	1020	1020	1020

Run No. 7

Run No. 9									
Time	Lat	Long	Alt	Temp	Wind	Dir	Speed	Pressure	Remarks
0000	34 00	118 00	100	50	0	0	0	30.00	Clear
0100	34 00	118 00	100	50	0	0	0	30.00	Clear
0200	34 00	118 00	100	50	0	0	0	30.00	Clear
0300	34 00	118 00	100	50	0	0	0	30.00	Clear
0400	34 00	118 00	100	50	0	0	0	30.00	Clear
0500	34 00	118 00	100	50	0	0	0	30.00	Clear
0600	34 00	118 00	100	50	0	0	0	30.00	Clear
0700	34 00	118 00	100	50	0	0	0	30.00	Clear
0800	34 00	118 00	100	50	0	0	0	30.00	Clear
0900	34 00	118 00	100	50	0	0	0	30.00	Clear
1000	34 00	118 00	100	50	0	0	0	30.00	Clear
1100	34 00	118 00	100	50	0	0	0	30.00	Clear
1200	34 00	118 00	100	50	0	0	0	30.00	Clear
1300	34 00	118 00	100	50	0	0	0	30.00	Clear
1400	34 00	118 00	100	50	0	0	0	30.00	Clear
1500	34 00	118 00	100	50	0	0	0	30.00	Clear
1600	34 00	118 00	100	50	0	0	0	30.00	Clear
1700	34 00	118 00	100	50	0	0	0	30.00	Clear
1800	34 00	118 00	100	50	0	0	0	30.00	Clear
1900	34 00	118 00	100	50	0	0	0	30.00	Clear
2000	34 00	118 00	100	50	0	0	0	30.00	Clear
2100	34 00	118 00	100	50	0	0	0	30.00	Clear
2200	34 00	118 00	100	50	0	0	0	30.00	Clear
2300	34 00	118 00	100	50	0	0	0	30.00	Clear
2400	34 00	118 00	100	50	0	0	0	30.00	Clear


Run No. 9

Run No. 9									
Time	Lat	Long	Alt	Temp	Wind	Dir	Speed	Pressure	Remarks
0000	34 00	118 00	100	50	0	0	0	30.00	Clear
0100	34 00	118 00	100	50	0	0	0	30.00	Clear
0200	34 00	118 00	100	50	0	0	0	30.00	Clear
0300	34 00	118 00	100	50	0	0	0	30.00	Clear
0400	34 00	118 00	100	50	0	0	0	30.00	Clear
0500	34 00	118 00	100	50	0	0	0	30.00	Clear
0600	34 00	118 00	100	50	0	0	0	30.00	Clear
0700	34 00	118 00	100	50	0	0	0	30.00	Clear
0800	34 00	118 00	100	50	0	0	0	30.00	Clear
0900	34 00	118 00	100	50	0	0	0	30.00	Clear
1000	34 00	118 00	100	50	0	0	0	30.00	Clear
1100	34 00	118 00	100	50	0	0	0	30.00	Clear
1200	34 00	118 00	100	50	0	0	0	30.00	Clear
1300	34 00	118 00	100	50	0	0	0	30.00	Clear
1400	34 00	118 00	100	50	0	0	0	30.00	Clear
1500	34 00	118 00	100	50	0	0	0	30.00	Clear
1600	34 00	118 00	100	50	0	0	0	30.00	Clear
1700	34 00	118 00	100	50	0	0	0	30.00	Clear
1800	34 00	118 00	100	50	0	0	0	30.00	Clear
1900	34 00	118 00	100	50	0	0	0	30.00	Clear
2000	34 00	118 00	100	50	0	0	0	30.00	Clear
2100	34 00	118 00	100	50	0	0	0	30.00	Clear
2200	34 00	118 00	100	50	0	0	0	30.00	Clear
2300	34 00	118 00	100	50	0	0	0	30.00	Clear
2400	34 00	118 00	100	50	0	0	0	30.00	Clear


THIS IS A LOW QUALITY REPRODUCTION
FROM A COPY FURNISHED TO THE

APPENDIX B

CO AND PT CONCENTRATION PROFILES FROM AIRCRAFT SOURCES
(SENSITIVITY STUDY)




AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 1)
(Scale = 20 $\mu\text{gm}/\text{m}^3$ per contour)




10.0

AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 1)
(Scale = 20 $\mu\text{gm}/\text{m}^3$ per contour)




1.3

AIRBASE CO CONCENTRATION PROFILE (RUN NO. 1)
(Scale = $1 \mu\text{gm}/\text{m}^3$ per contour)




1.3

AIRBASE PT CONCENTRATION PROFILE (RUN NO. 1)
(Scale = 1 $\mu\text{gm}/\text{m}^3$ per contour)




TOTAL CO CONCENTRATION PROFILE (RUN NO. 1)
(Scale = $50 \mu\text{gm}/\text{m}^3$ per contour)




10.0

TOTAL PT CONCENTRATION PROFILE (RUN NO. 1)
(Scale = $20 \mu\text{gm}/\text{m}^3$ per contour)




AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 2)




10.3


AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 2)



AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 3)




AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 3)




12.13

AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 4)



19.0

AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 4)



10.0

AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 5)

AD-A097 665

NAVAL POSTGRADUATE SCHOOL MONTEREY CA
INITIAL VALIDATION OF AN AMBIENT AIR QUALITY MODEL FOR NAVAL AI--ETC(U)
DEC 80 T S DOUGLAS, D W NETZER
NPS67-81-002


F/G 13/2


NL

UNCLASSIFIED


2-2

411
4112/80







AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 5)




AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 6)




AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 6)




AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 7)



AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 7)




AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 8)




10.0

AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 8)




AIRCRAFT CO CONCENTRATION PROFILE (RUN NO. 9)




AIRCRAFT PT CONCENTRATION PROFILE (RUN NO. 9)


APPENDIX C
CO AND PT CONCENTRATION PROFILES FROM AIRCRAFT SOURCES
(INTENSIVE STUDY)




AIRCRAFT CO CONCENTRATION PROFILE (1 AUG 1300-1400)
INCREMENTED FROM 50.0
(Scale = $50 \mu\text{gm}/\text{m}^3$ per contour)




AIRCRAFT PT CONCENTRATION PROFILE (1 AUG 1300-1400)
INCREMENTED FROM 30.0
(Scale = $30 \mu\text{gm}/\text{m}^3$ per contour)




AIRCRAFT CO CONCENTRATION PROFILE (1 AUG 1400-1500)
INCREMENTED FROM 50.0




AIRCRAFT PT CONCENTRATION PROFILE (1 AUG 1400-1500)
INCREMENTED FROM 30.0




AIRCRAFT CO CONCENTRATION PROFILE (2 AUG 1400-1500)
INCREMENTED FROM 50.0



AIRCRAFT PT CONCENTRATION PROFILE (2 AUG 1400-1500)
INCREMENTED FROM 30.0




AIRCRAFT CO CONCENTRATION PROFILE (2 AUG 1500-1600)
INCREMENTED FROM 50.0



AIRBASE CO CONCENTRATION PROFILE (2 AUG 1500-1600)

INCREMENTED FROM 1.0


(Scale = $4 \mu\text{gm}/\text{m}^3$ per contour)




AIRBASE PT CONCENTRATION PROFILE (2 AUG 1500-1600)

INCREMENTED FROM 10.0


(Scale = $5 \mu\text{gm}/\text{m}^3$ per contour)




TOTAL CO CONCENTRATION PROFILE (2 AUG 1500-1600)
INCREMENTED FROM 100.0
(Scale = 100 $\mu\text{gm}/\text{m}^3$ per contour)




TOTAL PT CONCENTRATION PROFILE (2 AUG 1500-1600)
INCREMENTED FROM 50.0
(Scale = 50 $\mu\text{gm}/\text{m}^3$ per contour)




AIRCRAFT CO CONCENTRATION PROFILE (2 AUG 1515-1615)
INCREMENTED FROM 50.0




AIRCRAFT PT CONCENTRATION PROFILE (2 AUG 1515-1615)
INCREMENTED FROM 30.0




AIRCRAFT CO CONCENTRATION PROFILE (3 AUG 1100-1200)
INCREMENTED FROM 50.0




AIRCRAFT PT CONCENTRATION PROFILE (3 AUG 1100-1200)
INCREMENTED FROM 30.0




AIRCRAFT CO CONCENTRATION PROFILE (6 AUG 1400-1500)
INCREMENTED FROM 50.0




AIRCRAFT PT CONCENTRATION PROFILE (6 AUG 1400-1500)
INCREMENTED FROM 30.0




AIRCRAFT 30 CONCENTRATION PROFILE (6 AUG 1500-1600)
INCREMENTED FROM 50.0




AIRCRAFT PT CONCENTRATION PROFILE (6 AUG 1500-1600)
INCREMENTED FROM 30.0




AIRCRAFT CO CONCENTRATION PROFILE (6 AUG 1515-1615)
INCREMENTED FROM 50.0



AIRCRAFT PT CONCENTRATION PROFILE (6 AUG 1515-1615)
INCREMENTED FROM 30.0



AIRCRAFT CO CONCENTRATION PROFILE (7 AUG 1500-1600)
INCREMENTED FROM 50.0



AIRCRAFT PT CONCENTRATION PROFILE (7 AUG 1500-1600)
INCREMENTED FROM 30.0

LIST OF REFERENCES

1. Northern Research and Engineering Corporation Report 1167 (Volumes 1 and 2), The Potential Impact of Aircraft Emissions on Air Quality, by M. Platt, R. C. Baker, E. K. Bastress, K. M. Chug and R. D. Siegel, 1971.
2. GEOMET, Inc. Report EF-262, Model Verification-Aircraft Emissions Impact on Air Quality, by S. D. Thayer, D. J. Felton, G. H. Stadsklev and B. D. Weaver, 1974.
3. Air Force Weapons Laboratory Technical Report-74-304, A Generalized Air Quality Assessment Model for Air Force Operations, by D. M. Rote and L. E. Wangen, March 1975.
4. TRW Systems Group Report NTIS no. PB-189194, Air Quality Display Model, November, 1969.
5. J. H. Wiggins, Co., Report No. 75-1231-1, A Survey of Computer Models for Predicting Air Pollution From Airports, by J. M. Haber, May 1975.
6. EPA Environmental Monitoring and Support Laboratory Contract No. 68-03-2591, Williams Air Force Base Air Quality Monitoring Operations, by D. C. Sheesley, S. J. Gordon, M. L. Ehlert, D. F. Zeller, and J. C. Connolly.
7. G. R. Thompson and D. W. Netzer, An Ambient Air Quality Model for Assessment of U. S. Naval Aviation Emittants, Naval Postgraduate School, Monterey, CA, Technical Report NPS-67Nt76091, September 1976.
8. K. I. Weal and D. W. Netzer, Modification of an Ambient Air Quality Model for Assessment of U. S. Naval Aviation Emittants, Naval Postgraduate School, Monterey, CA, Technical Report NPS-57Nt75071A, August 1975.
9. Naval Postgraduate School Technical Report NPS-67Nt78051, Sensitivity of AQAM Predictions for Naval Air Operations to Meteorological and Dispersion Model Parameters, by D. W. Netzer, May 1978.
10. D. M. Rote, R. J. Yamartino, K. L. Brubaker, Preliminary Evaluation of AQAM at Williams AFB, paper, presented at Air Quality and Aviation: An International Conference, Reston, VA, 16-18 October 1978.

11. Naval Air Propulsion Center Letter PE71:AFK 10340 Serial F924 to Commanding Officer, NAS Miramar, Subject: Effects of Aircraft Operations on Air Quality; NAS Miramar test for, 12 February 1979.
12. Air Force Weapons Laboratory Technical Report-74-54, A Generalized Air Quality Assessment Model-An Operator's Guide, by Argonne National Laboratory, July 1974 (Ref. May 1975).
13. EPA Report No. AP-26, Workbook of Atmospheric Dispersion Estimates, by D. B. Turner, 1970.
14. J. V. Brendmoen and D. W. Netzer, Measurements of Jet Dispersion Simulated in an Aeronautical Wind Tunnel, Naval Postgraduate School, Monterey, CA, Technical Report NPS-67-79-012, September 1979.
15. Williamson, S. J., Fundamentals of Air Pollution, Addison-Wesley, 1973.

DISTRIBUTION LIST

	No. of Copies
1. Chief of Naval Operations Navy Department Washington, DC 20760 (Attn: Codes: OP451, OP453)	2
2. Chief of Naval Material Navy Department Washington, DC 20360 (Attn: Codes: 08T291, 055P1)	2
3. Commander Naval Air Systems Command Washington, DC 20361 (Codes: AIR-01B, 330D, 340E, 4147A, 50184, 5341B, 536B1, 5364S)	8
4. Commander Naval Air Force U.S. Pacific Fleet Naval Air Station North Island San Diego, CA 92135 (Code: 722)	1
5. Commanding Officer Naval Air Rework Facility Naval Air Station North Island San Diego, CA 92135 (Code: 64270)	1
6. Commander Naval Facilities Engineering Command 200 Stoval Street Alexandria, VA 22332 (Codes: 104, 032B)	2
7. Commanding Officer Naval Facilities Engineering Command Western Division San Bruno, CA 94066 (Code: 09BE)	1
8. Naval Construction Battalion Center Port Hueneme, CA 93043 (Codes 25, 251, 252)	3
9. U.S. Naval Academy Annapolis, MD 21402 (Attn: Prof. J. Williams)	1

	No. of Copies
10. U.S. Marine Corps Washington, DC 20380 (Attn: Code: AAJ)	1
11. U.S. Air Force Washington, DC 20330 (Attn: Code PREV)	1
12. Arnold Engineering Development Ctr. Arnold AFS, TN 37342 (Code: DYR)	1
13. Air Force Aero Propulsion Laboratory Wright-Patterson Air Force Base, OH 45433 (Code: SFF)	1
14. Detachment 1 Civil & Environmental Eng. Dev. Agency HQ ADTC/ECA Tyndall AFB, TN 32403 (Code: EV, EVA)	2
15. Air Force School of Aerospace Medicine Brooks, AFB, TX 78235 (Code: VNL)	1
16. Army Aviation Systems Command P.O. Box 209 St. Louis, MO 63166 (Code: EQP)	1
17. Eustis Directorate USA AMR & DL Ft. Eustis, VA 23604 (Code: SAVDL-EU-TAP)	1
18. National Aeronautics and Space Admin. Lewis Research Center 2100 Brookpark Road Cleveland, OH 44135 (Attn: Mail Stop 60-6 (R. Rudey))	1
19. National Aeronautics and Space Administration Langley Research Center Hampton, VA 23365 (Attn: Mail Stop 217K, Dr. Levine)	1
20. Environmental Protection Agency 401 M. Street, S.W. Washington, DC 20024 (Attn: G. Kittredge)	1

	No. of Copies
21. Environmental Protection Agency Procedures Development Branch 2565 Plymouth Road Ann Arbor, MI 48105 (Attn: D. Munt)	1
22. Environmental Protection Agency National Environmental Research Center Meteorology Laboratory Research Triangle Park, NC 27711 (Attn: P. Humphry)	1
23. Environmental Protection Agency National Environmental Research Center P. O. Box 15027 Las Vegas, NV 89114 (Attn: Mr. Snelling)	2
24. Federal Aviation Administration 800 Independence Avenue, SW Washington, DC 20590 (Code AEQ-10; A. Broderick)	2
25. Federal Aviation Administration 2100 2nd Street Washington, DC 20591 (Code: ARD550, W. Westfield)	1
26. Federal Aviation Administration National Aviation Facility Experimental Ctr. Atlantic City, NJ 08405 (Code: ANA-420)	1
27. Defense Documentation Center Cameron Station Alexandria, VA 22314	2
28. Naval Air Propulsion Center Trenton, NJ 08608 (Attn: A. Klarman, Code PE71:AK)	3
29. Library Code 0142 Naval Postgraduate School Monterey, CA 93940	2
30. Dept. of Aeronautics Code 67 Monterey, CA 93940 M. F. Platzler, Chairman D. W. Netzer	1 10

	No. of Copies
31. Dean of Research Naval Postgraduate School Monterey, CA 93940	1
32. Commanding Officer Naval Air Station Miramar San Diego, CA 92145 (Attn: R. K. Miller)	1
33. Navy Environmental Health Center 333 Vine Street Cincinnati, OH 45220 Attn: CAPT. Markham	1

DATE
FILMED
- 8