

AD-A098 341

NAVAL POSTGRADUATE SCHOOL MONTEREY CA
OFFSHORE TRANSPORT AND DIFFUSION IN THE LOS ANGELES BIGHT. II. --ETC(U)
1981 G E SCHACHER, K L DAVIDSON
NPS-61-81-025


F/G 4/2


UNCLASSIFIED

NL

1 of 2

AD-A
1098-841





LEVEL III

2

NPS-61-81-025 ✓

AD A098341

NAVAL POSTGRADUATE SCHOOL
Monterey, California



DTIC
ELECTE
S APR 30 1981 D
D

OFFSHORE TRANSPORT AND DIFFUSION IN THE
LOS ANGELES BIGHT - II, NPS DATA SUMMARY

G.E. Schacher, K.L. Davidson
and C.A. Leonard

D.E. Spiel and C.W. Fairall

Environmental Physics Group
Naval Postgraduate School
Monterey, California

Approved for public release; distribution unlimited

Prepared for: Outer Continental Shelf Division
Bureau of Land Management
Los Angeles, California 90017

DTIC FILE COPY

81 4 30 030

NAVAL POSTGRADUATE SCHOOL
Monterey, California


Rear Admiral J. J. Ekelund
Superintendent

D. A. Schrady
Acting Provost

The work reported herein was supported in part by the Bureau of Land Management, Outer Continental Shelf Division, Los Angeles, California 90017.

Reproduction of all or part of this report is authorized.

This report was prepared by:


G. E. Schacher
Professor of Physics



K. L. Davidson
Associate Professor of
Meteorology



D. E. Spiel
BDM Corporation


C. W. Fairall
BDM Corporation

Approved by:


J. N. Dyer, Chairman
Department of Physics and
Chemistry


R. J. Renard, Chairman
Department of Meteorology


William M. Tolles
Dean of Research

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
	AD-A098	342
4. TITLE (and Subtitle)	5. TYPE OF REPORT & PERIOD COVERED	
OFFSHORE TRANSPORT AND DIFFUSION IN THE LOS ANGELES BIGHT - II. NPS DATA SUMMARY.	Technical Report	
6. AUTHOR(s)	7. PERFORMING ORG. REPORT NUMBER	
G.E./Schacher, K.L./Davidson, C.A./Leonard, D.E./Spiel and C.W./Fairall	11-2982	
8. PERFORMING ORGANIZATION NAME AND ADDRESS	9. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
Naval Postgraduate School Monterey, California 93940	(1) 12	
10. CONTROLLING OFFICE NAME AND ADDRESS	11. REPORT DATE	
Outer Continental Shelf Division Bureau of Land Management Los Angeles, California 90017	12. NUMBER OF PAGES	
13. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	14. SECURITY CLASS. (of this report)	
(14) NPS-62-81-035	Unclassified	
15. DISTRIBUTION STATEMENT (of this Report)		16. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
Overwater Transport, Diffusion, Marine Boundary Layer		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)		
The second in a series of tracer measurements of overwater transport and diffusion has been completed. This report includes the meteorological data obtained aboard the RV/Acania. Analyses of radiosonde data to yield mixed layer parameters for mixed layer assessment is also included.		

DD FORM 1473
1 JAN 73
(Page 1)

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6001

3

Unclassified
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Table of Contents

	Page No.
I. Introduction	10
II. Ship Operation Scenario	12
III. Shipboard Equipment	15
IV. Tracer Release Data	16
V. Wind Histories	19
VI. Radiosonde Results	23
VII. Acoustic Sounder Inversion Height	41
VIII. Meteorological Data	47
IX. Mixed Layer Parameters	52
Appendix A. BLM-I Radiosonde and Mixed Layer Parameter Results	70

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

List of Figures

	Page
Figures 1a-c. Wind histories: true wind speed versus time in immediate area of tracer gas releases. Vertical bars show wind speed.	20-22
Figures 2a-q. Temperature (solid line) and relative humidity profiles (broken line) determined from radiosonde releases.	24-40
Figures 3a-c. Acoustic sounder strip charts. The sounder was located on the RV/Acania.	42-44
Figures 4a-q. Mixed layer parameters, virtual potential temperature (solid line) and water vapor mixing ratio (broken line) determined from radiosonde data.	53-69
Figures 5a1-s2 Profiles of temperature (solid line), relative humidity (broken line), virtual potential temperature (solid line), and water vapor mixing ratio (broken line) determined from radiosonde releases for BLM-1.	71-108

List of Tables

	Page
Table 1. Significant shipboard events.	14
Table 2. Characteristics of exhausts used during tracer gas releases.	16
Table 3. Exact locations and start and end times for each release. Times are local, Pacific Daylight Time.	17
Table 4. SF ₆ bottle weights before and after the four releases. The total times for each release and the total weights of SF ₆ used are also given.	18
Table 5. Heights of acoustic echo return from the acoustic sounder. Also listed, and designated with an R, are the heights of the base and top of the temperature inversion as determined from the radiosondes.	45,46
Table 6. Meteorological data.	48-51

I. Introduction

During January of 1981 the Environmental Physics Group of the Naval Postgraduate School (NPS) and Aerovironment, Inc. conducted the second of two transport and dispersion experiments in the Santa Barbara Channel area of the California coast. The purpose of these operations was to perform offshore tracer experiments in order to parameterize dispersion models that are in current use and to build a data base for future model development. The purpose of this and the previous data report is to present the pertinent meteorological and source data for use by those who will be involved in the modeling effort. In the previous report only the basic data, reduced to engineering units, was presented. This report presents the second operations data in the same format and, in addition, includes mixed layer parameters for both operations. Application of these results to the models will be the subject of a future joint report by Aerovironment and NPS. A great deal of the discussion of the data in this report is the same as the first report and is included for the sake of completeness.

Although the data gathered in this experiment has much wider application, it was collected for the specific purpose of parameterizing models that will be used to assess the onshore impact of offshore oil exploration

and production sites. Such impact currently has great importance since many coastal areas are near the legal air pollution limit and any significant additional loading could push them over the limit. Air pollution models in current use have not been adequately validated for the overwater regime. The results of this study should remedy the inadequacy of the models.

During the tracer experiments SF_6 gas was released from the ship RV/Acania and tracked by an aircraft, a small boat, and one mobile and fixed stations on shore. Meteorological data was gathered on the ship and on the shore. This report contains shipboard meteorological data and gas source strength. Shore meteorological data and tracer results can be found in a report by Aerovironment.

II. Ship Operation Scenario

Since the impact of offshore sources on the shore is the purpose of these investigations the experiments must be performed during periods of onshore winds. These winds must be of a fairly long duration since it takes a minimum of 6 hours to gather enough data during any one experiment. The preliminary decision to release the tracer gas on any given day must be made on the previous day due to the time needed to prepare all of the sampling sites. Thus, the following schedule was used.

All Days

1. 0800-1200-2000: radio shipboard meteorological data to shore.
2. 1000: Shore obtains weather forecast from Point Mugu.
3. 1200: shore command center makes a go/no-go decision for a release on the following day.

Release Day

4. 0700: begin hourly wind reports to shore.
5. 1000: decision on release made by ship-shore communication, final decision made on shore.
6. Final positioning of ship.
7. 1100: start tracer gas release.
8. 1800: end tracer gas release and hourly wind reports.

Due to the variability of the wind during the period it was normally not possible to start the release by 1100.

Because of difficulty in moving the shore stations, targeting of the plume was accomplished by moving the ship. This had to be done before the release was begun because moving the ship would introduce wander into the plume trajectory and contaminate the results. In order to hold the ship stationary to the degree needed it was anchored during a release.

Significant Events:

At times, the ship was performing tasks not directly associated with this study or was in port. As an aid in interpreting the data we list times of "significant shipboard events" in Table 1.

1/5	0940	Underway from Monterey
1/6	1250	Arrive off Ventura
1/9	1820	Underway for Port Hueneme
	1955	Dock
1/13	0500	Underway
	0610	Arrive at operation area
1/15	1723	Underway for Port Hueneme, operation completed

Table 1 - Significant Shipboard Events

III. Shipboard Equipment

We give here a brief description of the meteorological measurements that were made on the ship. Details of the equipment and calibration procedures can be found in a previous report. Two meteorological stations at heights of 7 m and 20.5 m above mean sea level were used. At each level the following parameters were measured:

relative wind speed

relative wind direction (upper level only)

air temperature

dew point

wind speed fluctuation

The following parameters were also measured:

sea surface temperature

ship roll

ship location

inversion height

temperature and humidity profiles to 5,000 ft.

sky cloud cover

The temperature and humidity profiles were obtained by shipboard radiosonde launch and were taken every 12 hours. The temperature inversion height was determined by an acoustic sounder which gave a continuous strip chart record. Most data listed above was averaged for one half hour intervals. The exceptions were relative wind direction and ships roll. For both, 10 sec averages were obtained and recorded for the full period of a gas release.

IV. Tracer Release Data

Four separate experiments were performed. For each the gas was released through the exhaust of one of the ship's motor generator sets. The exhaust is inclined at an angle of 45° above the horizontal. The motor is a 2 cycle diesel so exhaust flow rate is obtained by multiplying 2/3 times the displacement times the revolutions per minute. The pertinent exhaust outlet data to characterize plum rise are:

<u>rpm</u>	<u>displacement (Cu in)</u>	<u>Stack Temp. (°F)</u>	<u>Flow Rate (cu in/sec)</u>	<u>Diameter (in)</u>
1500	426	250	7.13×10^3	4.5

Table 2. Characteristics of exhaust used during tracer gas releases.

For a release, 4 tanks of SF₆ were connected to a single manifold. The manifold has a pressure gauge and two rotometers, one supplied by the manufacturer and one calibrated and supplied by Aerovironment. The second meter was used to set the flow rate the first to monitor it since it was less subject to fluctuations. The gas pressure to the rotometers was maintained at 25 lbs/in.

Using the data found in Table 4 the flow rates for the four releases were

Release 1	48.35	lbs/hr
Release 2	48.06	lbs/hr
Release 3	44.45	lbs/hr
Release 4	46.21	lbs/hr

During the releases the ship was anchored approximately 5 Nmi SWW of Ventura. As stated above the releases started at approximately 1100 and ended at approximately 1800. The exact times and locations are given in Table 3.

<u>Release</u>	<u>Date</u>	<u>Latitude</u>	<u>Longitude</u>	<u>Start Time</u>	<u>End Time</u>
1	1/6	34°15.0'N	119°20.0'W	1322	1800
2	1/9	34°14.4'N	119°20.3'W	1123	1800
3	1/13	34°14.4'N	119°20.3'W	1134	1702
4	1/15	34°11.4'N	119°19.4'W	1406	1700

Table 3. Exact locations and start and end times for each release. Times are local, Pacific Daylight Time.

<u>Bottle Number</u>	<u>Initial Weight (lbs)</u>	<u>Release 1</u>	<u>Release 2</u>	<u>Weight after Release 3</u>	<u>Release 4</u>
8	252				186
9	256				188
10	259	148			
11	252	139			
12	251		140		
13	254		142		
14	252		157		
15	260			185	
16	278			185	
17	250			175	
Total Weight		<u>224</u>	<u>318</u>	<u>243</u>	<u>134</u>
Total Release Time		4:38	6:37	5:28	2:54

Table 4. SF₆ bottle weights before and after the four releases. The total times for each release and the total weights of SF₆ used are also given.

V. Wind Histories

Hourly average wind histories taken aboard the RV/Acania are shown in Figures 1. The winds were recorded at least every hour and every half hour immediately before and during each release. These visual presentations were kept up to date on the ship and aided in the go/no-go decisions on release days.

If one compares these histories with those for the first operation during September 1980, it is immediately apparent that the wind was much less predictable during January. During the fall a well established land-sea breeze cycle existed. During the winter the sea breeze during the afternoon was not at all reliable in magnitude nor direction and, on some days, never became established at all.

Figure 1a




Figure 1b





Figure 1c




VI. Radiosonde Results

Radiosondes were released from the ship twice in each 24-hour period, generally at 0700 and 1900 PDT. Releases were made and interpreted by a Navy radiosonde team. Temperature and humidity were determined at standard levels and significant points. Since we are interested in the detailed structure of the boundary layer such a treatment is too coarse. Thus, the original strip chart output and the met team determined calibration points were used to construct fine scale graphs, which are presented in Figures 2.


There are two apparent sources of error in these radiosonde results. The lowest height reading, which is obtained at the ship, is subject to ships influence and should not be used. Thus, it is not possible to use the radiosonde to determine properties of the surface layer. The radiosonde humidity system was not capable of measuring a relative humidity below 20%. This is especially apparent in Figure 2i.

Figure 2a
REL HUMIDITY (%)




BLM-II 05 JAN 81 1953

Figure 2b
REL HUMIDITY (%)




BLM-II 06 JAN 81 740

Figure 2c
REL HUMIDITY (%)




BLM-II 06 JAN 81 1905

Figure 2d
REL HUMIDITY (%)




BLM-II 07 JAN 81 800

Figure 2e
REL HUMIDITY (%)




BLM-II 07 JAN 81 1850

Figure 2f
REL HUMIDITY . %



BLM-II 08 JAN 81 815


Figure 2g



BLM-II 08 TAN 81 1915

Figure 2h


REL HUMIDITY (%)



BLM-II 09 - JAN 81 810


Figure 2i

REL HUMIDITY (%)




BLM-II 09 JAN 81 1800

Figure 2j
REL HUMIDITY (%)



BLM-II 15 JAN 81 900


Figure 2k
REL HUMIDITY (%)



BLM-II 13 JAN 81 1930


Figure 21

REL HUMIDITY (%)



BLM-II 14 JAN 81 755


Figure 2m
REL HUMIDITY (%)



BLM-II 14 JAN 81 1920

Figure 2n


REL HUMIDITY (%)



BLM-II 15 JAN 81 830

Figure 20


REL HUMIDITY (%)



BLM-II 15 JAN 81 1950

Figure 2p


REL HUMIDITY (%)



BLM-II 16 JAN 81 820

Figure 2q

REL HUMIDITY (%)



BLM-II 16 JAN 81 1935

VII. Acoustic Sounder Results

The acoustic sounder was operated continuously throughout the cruise and Figures 3 are photographs of the strip chart output. As can be seen there was very seldom a well defined return that would allow one to easily determine the boundary layer depth. In Table 5 we list the heights of detectable acoustic returns. In many cases the returns were so weak that one is not certain if they indicate the height of the base of the inversion. Also listed in the table are the heights of the base and top of the temperature inversion as determined from the radiosondes. These are designated with an R in the table. The radiosonde determined heights are listed as an aid since it is very difficult to determine the boundary layer depth from sounder data alone for these cases.

Figure 3a



BIM-2

Figure 3b



BIM-2

Figure 3c



Table 5. Heights of acoustic echo return from the acoustic sounder. Also listed, and designated with ar. R, are the heights of the base and top of the temperature inversion as determined from the radiosondes.

DATE	TIME	Z(m)		DATE	TIME	Z(m)	
1/6	1230	120		1/8	1936	R 320-600	
	1300	140			2000	330	
	1330	140			2100	320	
	1400	160			2200	320	
	1700	180			2230	240	
	1730	180			2300	270	
	1800	240			2330	360	
	1830	160					
	1900	300		1/9	0430	200	
	1930	280			0500	190	
		R 0-200			0530	200	300
	2000	300			0600	200	300
	2030	200			0630	160	240
	2100	200			0730	250	
					0800	160	
					0830	200	
						R 0-200, 200-700	
					0900	160	
1/7	0200	140			1000	160	
	0600	120			1030	100	
		R 0-150			1100	100	
	0900	120			1130	100	
	1100	80			1200	120	
	1130	80			1230	140	
	1200	80			1430	100	
	1230	100	180		1530	260	
	1300	200			1600	360	
	1500	250			1630	140	300
	1530	260			1700	180	340
	1600	200			1730	300	
	1730	160			1800	260	
		R 120-650				R 90-160, 220-300	
	1930	300			1900	80	160
	2000	300			1930	200	
	2130	400			2000	160	
	2200	280			2030	120	280
	2230	160	450		2100	120	
	2300	120					
	2330	340		1/13	0200	160	
	2400	440			0230	220	
					0300	260	
1/8	0030	520			0330	250	
	0100	500			0400	260	
	0130	540			0430	240	
	0200	100			0500	220	
	0230	140			0800	180	500
	0300	80			0924	R 0-170 weak	
	0330	100			1800	100	
	0400	100			1830	130	
	0530	260			1900	120	
	0830	180			1930	100	
	0845	R 70-160, 560-900			2000	140	
						R 150-350	

DATE	TIME	Z(m)	
1/13	2030	160	
	2100	200	
	2130	180	
	2330	180	
1/14	0130	100	
	0200	180	
	0230	180	
	0300	160	
	0400	80	
	0500	100	
	0630	160	
	0823	R 30-420	
	1000	200	
	1100	170	
	1130	160	
	1200	100	
	1230	80	
	1300	100	
	1400	180	
	1500	200	
	1600	160	
	1700	80	
	1730	80	
	1800	160	
	1830	120	
	1900	160	
		R 0-150, 230-480	
	2000	200	
	2030	230	
	2100	220	
	2130	160	240
	2200	200	300
	2230	210	300
	2300	300	
	2330	190	
1/15	0100	350	
	0130	260	
	0200	180	
	0230	160	
	0300	100	300
	0330	300	
	0400	420	
	0500	420	
	0530	360	
	0600	400	
	0700	460	
	0730	450	
	0800	380	
	0830	340	
		R 150-350	
	0930	140	

VIII. Meteorological Data

Table 6 presents the basic meteorological data and calculated parameters. Only data taken during the tracer gas release periods are included. Wind speed, relative humidity, and air temperature values are those measured at the upper level (20.5 m). All calculated parameters were determined using the bulk aerodynamic method.

The boundary layer mixing rate and mixing height depend on the boundary layer depth, Z_i . We have already mentioned the difficulty in determining the depth for these data. We have used a combination of the radiosonde data and the acoustic sounder data to find Z_i , and, unless a radiosonde was launched close to the time of interest, the value used was only an estimate. Thus, most of the mixing rate values, w_* , and the mixing times, t , are suspect.

Table 6. Meteorological Data

BIM II-81
Release #1

Date/Time	U (m/sec)	RH (%)	T (C)	Ts (C)	Zi (m)	U* (m/sec)	T* (C)	10 ³ Δ (m/sec)	Z/L	w* (m/sec)	t (min)
01/06 1355	5.6	66	16.7	15.6	160	0.175	-0.039	-18.6	7.40E-02	0.3	8.0
01/06 1425	5.3	66	16.8	15.6	160	0.163	-0.041	-21.5	9.79E-02	0.3	8.0
01/06 1455	4.3	60	17.3	15.7	160	0.118	-0.051	-30.6	2.65E-01	0.3	8.3
01/06 1542	2.6	64	17.1	15.8	160	0.057	-0.036	-19.6	7.39E-01	0.2	11.9
01/06 1612	5.4	53	17.7	15.7	170	0.157	-0.068	-42.2	2.05E-01	0.4	7.2
01/06 1642	4.7	58	17.3	15.6	170	0.132	-0.056	-34.1	2.35E-01	0.4	8.1
01/06 1712	5.3	61	17.1	15.6	180	0.159	-0.051	-29.4	1.40E-01	0.4	8.2
01/06 1742	4.5	61	17.2	15.6	180	0.128	-0.050	-30.5	2.24E-01	0.3	8.8
01/06 1812	4.8	52	18.0	15.5	160	0.137	-0.064	-42.2	2.72E-01	0.4	7.4
01/06 1842	3.7	66	16.7	15.5	160	0.101	-0.041	-22.5	2.65E-01	0.3	9.5
01/06 1912	2.7	69	16.5	15.5	140	0.066	-0.032	-16.9	4.74E-01	0.2	10.8
01/06 1942	1.6	55	16.0	15.4	140	0.053	-0.015	18.7	-7.62E-01	0.2	14.9

BLM 11-81
Release #2

Date/Time	U (m/sec)	RH (%)	T (C)	Ts (C)	Zi (m)	U* (m/sec)	T* (C)	10 ³ *QO (m/sec)	z/L	w* (m/sec)	t (min)
01/09 1149	3.7	79	14.0	15.4	80	0.122	0.046	68.9	-5.49E-01	0.2	5.4
01/09 1221	4.1	84	14.0	15.3	180	0.134	0.042	59.9	-3.94E-01	0.3	9.2
01/09 1309	4.1	85	14.1	15.3	200	0.137	0.037	54.2	-3.42E-01	0.3	10.2
01/09 1339	4.6	87	14.2	15.3	240	0.154	0.036	51.0	-2.53E-01	0.4	11.2
01/09 1409	4.7	88	14.2	15.3	240	0.156	0.033	47.1	-2.30E-01	0.3	11.5
01/09 1439	4.6	87	14.4	15.3	250	0.153	0.028	42.0	-2.13E-01	0.3	12.6
01/09 1509	5.0	84	14.6	15.3	260	0.166	0.019	34.0	-1.45E-01	0.3	14.2
01/09 1539	4.2	85	14.8	15.4	260	0.136	0.014	28.2	-1.79E-01	0.3	15.7
01/09 1609	3.2	85	15.0	15.3	200	0.101	0.008	21.0	-2.43E-01	0.2	18.9
01/09 1639	2.9	83	15.2	15.3	180	0.091	0.001	15.0	-2.10E-01	0.1	32.2
01/09 1709	4.1	87	15.1	15.3	160	0.131	0.004	15.7	-1.07E-01	0.1	18.3
01/09 1739	4.7	88	15.0	15.3	120	0.154	0.008	18.6	-9.16E-02	0.2	11.9
01/09 1809	5.2	85	15.0	15.3	100	0.170	0.005	17.8	-7.25E-02	0.1	11.5

BLH II-81
Release #3

Date/Time	U (m/sec)	Rd (°)	T (C)	Ts (C)	Zi (m)	U* (m/sec)	T* (C)	10 ⁴ J*Qo (m/second)	Z/L	W* (m/sec)	t (min)
01/13 0852	3.9	70	14.4	15.0	180	0.129	0.021	44.1	-3.14E-01	0.3	11.7
01/13 0948	3.0	79	15.1	15.0	100	0.090	-0.007	7.5	-1.06E-01	0.1	13.0
01/13 1049	3.3	67	16.0	15.2	100	0.096	-0.024	-6.2	8.59E-02	0.2	8.4
01/13 1119	4.5	78	15.5	15.2	100	0.141	-0.014	-0.2	2.68E-03	0.2	8.9
01/13 1239	4.9	73	16.0	15.3	100	0.152	-0.024	-9.0	4.79E-02	0.2	7.2
01/13 1309	5.4	77	15.9	15.4	100	0.172	-0.022	-8.2	3.42E-02	0.2	7.1
01/13 1339	5.3	71	16.3	15.4	100	0.167	-0.030	-14.8	6.49E-02	0.3	5.5
01/13 1409	6.1	61	17.0	15.4	100	0.194	-0.046	-27.5	8.83E-02	0.3	5.3
01/13 1439	5.5	64	16.9	15.5	100	0.171	-0.045	-26.6	1.10E-01	0.3	5.6
01/13 1509	5.6	71	16.5	15.5	100	0.176	-0.036	-20.5	8.02E-02	0.3	5.0
01/13 1521	5.1	81	16.1	15.4	100	0.157	-0.027	-16.4	8.07E-02	0.2	5.9
01/13 1559	5.4	83	15.9	15.3	130	0.169	-0.023	-13.2	5.58E-02	0.3	8.4
01/13 1629	4.0	87	15.7	15.4	130	0.120	-0.015	-6.8	5.71E-02	0.2	10.9
01/13 1659	4.3	83	15.8	15.4	130	0.132	-0.014	-4.7	3.32E-02	0.2	10.7
01/13 1729	4.4	83	15.7	15.4	130	0.137	-0.013	-2.2	1.52E-02	0.2	11.0

BLM II-81
release #4


Date/Time	U (m/sec)	RH (%)	T (C)	Ts (C)	zi (m)	U* (m/sec)	T* (C)	10+3*Qo (m/sec)	z/L	w* (m/sec)	t (min)
01/15 1441	3.3	86	14.8	15.7	150	0.106	0.026	40.2	-4.23E-01	0.2	10.4
01/15 1500	4.6	84	14.8	15.7	200	0.160	0.026	41.1	-1.90E-01	0.3	10.9
01/15 1552	4.0	84	15.1	15.6	100	0.128	0.013	26.2	-1.87E-01	0.2	9.4
01/15 1622	5.3	85	14.9	15.6	360	0.176	0.021	34.6	-1.32E-01	0.4	16.8
01/15 1652	6.2	85	14.8	15.6	260	0.210	0.022	35.6	-9.56E-02	0.3	12.6
01/15 1722	5.9	85	14.8	15.5	120	0.200	0.021	34.9	-1.02E-01	0.3	7.6

IX. Mixed Layer Parameters

It is very important in understanding transport and dispersion to determine whether the boundary layer is well mixed. We do this by examining the virtual potential temperature and water vapor mixing ratio. These parameters will be well mixed in the well mixed boundary layer and will, then, be constant with height. The two parameters have been determined from the radiosonde results and are shown in Figures 4a-q. Again note that the lowest point for each sounding is not reliable. These results can be easily used to determine if the boundary layer is well mixed.

Figure 4a


MIX RATIO (G/KG)



BLM-II 05 JAN 81 1953

Figure 4b


MIX RATIO (G/KG)



BLM-II 06 JAN 81 740


Figure 4c

MIX RATIO (G/KG)



BLM-II 06 JAN 81 1905


Figure 4d
MIX RATIO (G/KG)



BLM-II 07 JAN 81 800

Figure 4e


MIX RATIO (G/KG)



BLM-II 07 JAN 81 1850


Figure 4f

MIX RATIO (G/KG)



BLM-II 08 JAN 81 815


Figure 4g
MIX RATIO (G/KG)



BLM-II 08 JAN 81 1915

Figure 4h


MIX RATIO (G/KG)



BLM-II 09 JAN 81 810


Figure 4i

MIX RATIO (G/KG)




BLM-II 09 JAN 81 1800

Figure 4j
MIX RATIO (G/KG)



BLM-II 15 JAN 81 900


Figure 4k
MIX RATIO (G/KG)



BLM-II 13 JAN 81 1930

Figure 41


MIX RATIO (G/KG)



BLM-II 14 JAN 81 755

Figure 4m


MIX RATIO (G/KG)



BLM-II 14 JAN 81 1920

Figure 4n


MIX RATIO (G/KG)



BLM-II 15 JAN 81 830

Figure 4a


MIX RATIO (G/KG)



BLM-II 15 JAN 81 1950


Figure 4p

MIX RATIO (G/KG)



BLM-II 16 JAN 81 820

Figure 4q
MIX RATIO (G/KG)




BLM-II 16 JAN 81 1935

Appendix A. BLM-1 Radiosonde and Mixed
Layer Parameter Results

The radiosonde results for BLM-1 have been reprocessed by computer in order to put them in the same format as used here for BLM-II results. Also the mixed layer parameters have been calculated. These results are shown in Figures 5.

Figure 5a1


REL HUMIDITY (%)



BLM-I 21 SEPT 80 1205

Figure 5a2


MIX RATIO (G/KG)



BLM-I 21 SEPT 80 1205

Figure 5b1


REL HUMIDITY (%)



BLM-I 22 SEPT 80 15

Figure 5b2


MIX RATIO (G/KG)



BLM-I 22 SEPT 80 15

Figure 5c1


REL HUMIDITY (%)



BLM-I 22 SEPT 80 1215

Figure 5c2


MIX RATIO (G/KG)



BLM-I 22 SEPT 80 1215

Figure 5d1


REL HUMIDITY (%)



BLM-I 23 SEPT 80 715

Figure 5d2


MIX RATIO (G/KG)



BLM-I 23 SEPT 80 715

Figure 5e1


REL HUMIDITY (%)



BLM-I 23 SEPT 80 1250

Figure 5e2


MIX RATIO (G/KG)



BLM-I 23 SEPT 80 1250

Figure 5f1


REL HUMIDITY (%)



BLM-I 24 SEPT 80 10

Figure 5f2


MIX RATIO (G/KG)



BLM-I 24 SEPT 80 10


Figure 591

REL HUMIDITY (%)



BLM-I 24 SEPT 80 1215


Figure 5g2



BLM-I 24 SEPT 80 1215

Figure 5h1


REL HUMIDITY (%)



BLM-I 25 SEPT 80 40

Figure 5h2


MIX RATIO (G/KG)



BLM-I 25 SEPT 80 40

Figure 511


REL HUMIDITY (%)



BLM-I 27 SEPT 80 607

Figure 5i2


MIX RATIO (G/KG)



BLM-I 27 SEPT 80 607

Figure 5j1


REL HUMIDITY (%)



BLM-I 27 SEPT 80 1820


Figure 5j2

MIX RATIO (G/KG)



BLM-I 27 SEPT 80 1820


Figure 5k1



BLM-I 28 SEPT 80 740

Figure 5k2


MIX RATIO (G/KG)



BLM-I 28 SEPT 80 740

Figure 511


REL HUMIDITY (%)



BLM-I 28 SEPT 80 1705


Figure 512

MIX RATIO (G/KG)



BLM-I 28 SEPT 80 1705


Figure 5ml



BLM-I 29 SEPT 80 630

Figure 5m2


MIX RATIO (G/KG)



BLM-I 29 SEPT 80 630

Figure 5nl


REL HUMIDITY (%)



BLM-I 29 SEPT 80 1735

Figure 5n2


MIX RATIO (G/KG)



BLM-I 29 SEPT 80 1735

Figure 501

REL HUMIDITY (%)



BLM-I 30 SEPT 80 1207

AD-A098 341

NAVAL POSTGRADUATE SCHOOL MONTEREY CA
OFFSHORE TRANSPORT AND DIFFUSION IN THE LOS ANGELES BIGHT. II. --ETC(U)
1981 G E SCHACHER, K L DAVIDSON

F/G 4/2

UNCLASSIFIED

NPS-61-81-025


NL

2 of 2

ATC
10/1/81




END
DATE
FILMED
5-81
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

Figure 5o2


MIX RATIO (G/KG)



BLM-I 30 SEPT 80 1207

Figure 5pl


REL HUMIDITY (%)



BLM-I 1 OCT 80 25

Figure 5p2


MIX RATIO (G/KG)



BLM-I 1 OCT 80 25

Figure 5q1

REL HUMIDITY (%)



BLM-I 1 OCT 80 1230

Figure 5q2


MIX RATIO (G/KG)



BLM-I 1 OCT 80 1230

Figure 5ql


REL HUMIDITY (%)



BLM-I 1 OCT 80 2200

Figure 5r2


MIX RATIO (G/KG)



BLM-I 1 OCT 80 2200

Figure 5sl


REL HUMIDITY (%)



BLM-I 2 OCT 80 1038

Figure 5s2

MIX RATIO (G/KG)



BLM-I 2 OCT 80 1038

DISTRIBUTION LIST

	No. of copies
1. Defense Documentation Center Cameron Station Alexandria, Virginia 22314	2
2. Library, Code 0142 Naval Postgraduate School Monterey, California 93940	2
3. Dean of Research, Code 012 Naval Postgraduate School Monterey, California 93940	1
4. Dr. C.W. Fairall BDM Corporation, 1340 Munras St. Monterey, California 93940	2
5. Professor J. Dyer, Code 61Dy Naval Postgraduate School Monterey, California 93940	1
6. Professor R.J. Renard, Code 63Rd Naval Postgraduate School Monterey, California 93940	1
7. Assoc. Profeser K. L. Davidson, Code 63Ds Naval Postgraduate School Monterey, California 93940	2
8. Professor G.E. Schacher, Code 61Sq Naval Postgraduate School Monterey, California 93940	10
9. Mr. Dick Wilhelmsen Room 200 OCS Division Bureau of Land Management 1340 West 6th Street Los Angeles, California 90017	15
10. Mr. David M. Wilbur Aerovironment Inc. 145 North Vista Avenue Pasadena, California 91107	2
11. Mr. Tom Rapolt Energy Resources Co., Inc. 3344 N. Torrey Pines Ct. La Jolla, California 92037	1

LMED
-8