

ADA 098 657

TECHNICAL
LIBRARY

AD

TECHNICAL REPORT ARBRL-TR-02294

TRANSIENT COMBUSTION CALCULATIONS WITH
VARIABLE THERMAL PROPERTIES

Carl W. Nelson

February 1981



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating or sponsoring activity is prohibited.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22161.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute endorsement of any commercial product.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TECHNICAL REPORT ARBRL-TR-02294	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) TRANSIENT COMBUSTION CALCULATIONS WITH VARIABLE THERMAL PROPERTIES		5. TYPE OF REPORT & PERIOD COVERED BRL Technical Report
7. AUTHOR(s) Carl W. Nelson		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Armament Research and Development Command U.S. Army Ballistic Research Laboratory ATTN: DRDAR-BL Aberdeen Proving Ground, MD 21005		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Armament Research and Development Command U.S. Army Ballistic Research Laboratory ATTN: DRDAR-BLP Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L161102AH43
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE FEBRUARY 1981
		13. NUMBER OF PAGES 26
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Solid propellant combustion Transient combustion thermal conductivity guns		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) (clt) The response of solid propellant combustion to steep pressurization pulses has been calculated with consideration of temperature dependent thermal properties of the solid and quasi-steady gas phase. Response has been calculated for a uniformly distributed gas phase reaction and for the Zeldovich heat feedback theory with variations in surface heat release, pressurization rate, and thermal properties of the solid. (Continued)		

20. ABSTRACT (Continued)

Regression rate excursions of two to three times the quasi-steady rate ($r = a p^n$) are calculated for nominal values of propellant properties. Such excursions agree roughly with the few transient combustion measurements of Turk, et al. and Brulard, et al. Higher excursions are calculated for the distributed flame with assumed constant thermal properties. For pressurization rates approximating calculated DDT rates, the excursions survive at high pressures. Higher assumed surface heat release produces sharper response in the distributed flame models. The Zeldovich approach predicts protracted excursions from quasi-steady behavior.

TABLE OF CONTENTS

	<u>Page</u>
LIST OF ILLUSTRATIONS	5
I. INTRODUCTION	7
II. THEORY	9
III. MEASURED THERMAL PROPERTIES	12
IV. RESULTS	12
CONCLUSIONS	16
REFERENCES	17
LIST OF SYMBOLS	19
DISTRIBUTION LIST	21

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
1. Effect of Variable Properties	13
2. Effect of Pressurization Rate	14
3. Zeldovich Model Results	15
4. Effect of Surface Heat Release	15
5. Effect of Pressure Step Change	16

I. INTRODUCTION

Many calculations of transient solid propellant regression rates assume a quasi-steady dependence on pressure (and perhaps initial temperature). Constant volume bombs and constant pressure strand burner measurements are the usual source of the supporting data. Experiments, however, have demonstrated that in a rapidly changing pressure field, the regression rate can deviate substantially from the quasi-steady rate for increasing^{1,2} or decreasing^{3,4} or oscillating pressure. Because the immediate interest is in increasing pressures found in gun chambers, the body of theory and experiment for oscillating pressures will be largely ignored.

As observed in Kuo's⁵ recent review, models which rely only on rate of change of pressure are valid only when the excursions are small enough for linear analysis. For larger excursions from steady state, a thermal theory model has been frequently used wherein only the gas phase is assumed quasi-steady. For extreme excursions even this approximation must be abandoned although estimates have been seriously proposed of the application limits of the quasi-steady gas.

Nelson⁶ has shown that for a given gun pressurization history, calculated transient rates can vary widely with the model used. Kooker

¹J. Brulard, P. Kuentzmann, R. Kling, "Réponse d'un Propergol Solide à un Echelon de Pression", *La Recherche Aérospatiale*, 5, 279-287 (1975).

²S. L. Turk, R. A. Battista, K. K. Kuo, L. H. Caveny, and M. Summerfield, "Dynamic Responses of Solid Rockets during Rapid Pressure CHange", *J. Spacecraft & Rockets*, 10, 137-142 (1973).

³C. F. Yin and C. E. Hermance, "Continuous Measurement Transient Burning Rates of a Composite Propellant Undergoing Depressurization", *AIAA Paper 71-173* (1971).

⁴C. E. Woolridge and G. A. Marxman, "A Comparison Between Theoretical and Experimental Extinction Behavior of Composite Solid Propellants", *AIAA Paper 70-666* (1970).

⁵K. K. Kuo and G. R. Coates, "Review of Dynamic Burning of Solid Propellants in Gun and Rocket Propulsion Systems", *Sixteenth (International) Symposium on Combustion*, 1177-1192 (1976).

⁶C. W. Nelson, "Response of Three Types of Transient Combustion Models to Gun Pressurization", *Combustion and Flame*, 32, 317-319 (1978).

and Nelson⁷ showed that three thermal theory models of the KTSS⁸ type give essentially the same response.

Most of these calculations assumed (1) a quasi-steady gas phase with uniform heat release and (2) constant thermal properties of both solid and gas. The uniform gas phase assumption derived from a concept of a diffusion controlled flame of composite propellants not generally held applicable to homogeneous propellants with kinetically controlled gas phase reaction. Thermal properties of the solid have been found, in the few measurements made,^{9,10} to depend on temperature. The quasi-steady gas phase remains the only tractable approach for reasonable computing until methods like those of Kooker¹¹ can be applied to solid propellant combustion and considerably simplified. Attempts at simplified unsteady gas phase treatments tend to make critical but indefensible assumptions.^{12,13}

Nelson, et al.¹⁴ have shown that predicted pressure wave development in gun chambers is magnified by using a Zeldovich transient burning model to replace the quasi-steady regression. DDT calculations (e.g.,

-
- ⁷D. E. Kooker and C. W. Nelson, "Numerical Solution of Three Solid Propellant Combustion Models During a Gun Pressure Transient", USA Ballistic Research Laboratory, Report 1953 (1977). (See also ASME Journal of Heat Transfer, in press). (AD #A035250)
- ⁸H. Krier, J. S. T'ien, W. A. Sirignano and M. Summerfield, "Non-Steady Burning Phenomenon of Solid Propellants: Theory and Experiments", AIAA Journal, 6, 278-285 (1968).
- ⁹J. R. Ward, "Determination of the Heat Capacities of Gun Propellants by Differential Scanning Calorimetry", Analytical Calorimetry, 4, 143-153 (1977).
- ¹⁰M. L. Cohen, M. Imber "Variation of the Thermal Conductivity of Solid Propellants in an Acoustic Field", AIAA Journal 5, 1295-1299 (1967).
- ¹¹D. E. Kooker, "Numerical Predictions for Laminar Flame Propagation in Confined Ozone/Oxygen Mixtures: Influence of Initial Temperature and Pressure", AIAA Paper 79-0292, New Orleans (1979).
- ¹²C. W. Nelson, "Another Comment on the Transient Burning Rate Model of Suhas and Bose", Combustion and Flame, in press.
- ¹³H. K. Suhas and T. K. Bose, "A Mathematical Model to Predict Transient Burning Rate and Pressure Decay Rates for Extinction of Composite Propellants", Combustion and Flame, 28, 145-153 (1977).
- ¹⁴C. W. Nelson, P. S. Gough, and F. W. Robbins, "Ignition Transients in Flamespreading Calculations", AIAA Paper 79-0166, New Orleans (1979).

Beckstead, et al.¹⁵) where steep pressure fronts are well documented typically use a quasi-steady regression law.

The purpose of this short report is to examine theoretically the effect of an assumption of variable thermal properties on the transient regression rates of solid propellants.

II. THEORY

Thermal theory models solve the energy equation in the solid,

$$\rho c \frac{\partial T}{\partial t} + r \rho c \frac{\partial T}{\partial x} = \frac{\partial}{\partial x} \left(\lambda \frac{\partial T}{\partial x} \right), \quad (1)$$

which in the nondimensional variables of Kooker and Nelson⁷ plus

$$L = \lambda / \lambda_0 \quad (2)$$

$$C = c / c_0 \quad (3)$$

becomes

$$\frac{\partial \theta}{\partial \tau} + R \frac{\partial \theta}{\partial \eta} = \frac{1}{C} \frac{\partial}{\partial \eta} \left(L \frac{\partial \theta}{\partial \eta} \right). \quad (4)$$

Boundary conditions for the solid are:

$$\theta = 0 \text{ as } \eta = -\infty \quad (5)$$

$$\frac{\partial \theta}{\partial \eta} = f[L_s, C_s, R, P(\tau)] \text{ at } \eta = 0.$$

The specific form of the surface boundary condition is set by the choice of gas phase model.

The initial condition is one of steady state burning at an initial pressure. In problems where transients seem likely to be important, the actual initial condition is a cold propellant. A complete calculation would include ignition and the transition to self-sustaining combustion.

¹⁵M. W. Beckstead, N. L. Peterson, D. T. Pilcher, and B. D. Hopkins, "Convective Combustion Modeling Applied to Deflagration to Detonation Transition of HMX", *Combustion and Flame* 30, 231-241 (1977).

Unfortunately, since there is no useful model of the transition, the problem is avoided by assuming steady state combustion has already been achieved.

At steady state, the temperature profile is given by the solution of the energy equation

$$R \frac{\partial \theta}{\partial \eta} = \frac{1}{C} \frac{\partial}{\partial \eta} \left(L \frac{\partial \theta}{\partial \eta} \right) \quad (6)$$

subject to boundary conditions

$$\theta = 0 \quad \text{as } \eta \rightarrow -\infty$$

$$\theta = 1 \quad \text{at } \eta = 0.$$

Note that without the temperature dependent properties, the initial condition would be the familiar

$$\theta = e^{\eta}$$

With variable properties, a numerical solution of Eq. (6) provides the initial condition.

In contrast with the constant properties case where the initial value of the surface gradient is

$$\frac{\partial \theta}{\partial \eta} = 1 \quad ,$$

the variable properties value is approximately

$$\frac{\partial \theta}{\partial \eta} = 0.65$$

for the specific values of this problem. It will in general vary from unity in the direction opposing the change in the thermal diffusivity.

One simple treatment of the gas phase is to assume a uniform reaction rate as has been done by several models (e.g., KTSS⁸). With the reaction rate so specified, the gas phase energy equation can then be integrated to find the conduction term at the solid boundary. The Kooker-Zinn¹⁶ model here yields the boundary condition

¹⁶ D. E. Kooker and B. T. Zinn, "Numerical Investigation of Nonlinear Axial Instabilities in Solid Rocket Motors", USA Ballistic Research Laboratories Contract Report 141 (1974). (AD #776954)

$$\frac{\partial \theta}{\partial \eta} = \frac{R}{L} \left[H + (\theta_s - 1) \left(C - \frac{c_p}{c_o} \right) \right] + \frac{Z P^n}{RL} .$$

The constant Z is determined from the initial condition. H is the non-dimensional surface heat release.

$$H = Q_s / c_o (T_{so} - T_o) .$$

Another treatment is to ignore the gas phase details as is done in the Zeldovich approach wherein it is assumed that the functional form of the heat feedback is the same for any combination of regression rate and pressure.

For constant properties, the heat feedback term is the transformed version of the Zeldovich boundary condition,⁶

$$\frac{\partial \theta}{\partial \eta} = \frac{R}{L} \left(\theta_s - \frac{1}{\sigma_p (T_{so} - T_o)} \ln \frac{R}{R_s} \right) .$$

For variable properties, the term is more complicated after considering that at steady state

$$L \frac{\partial \theta}{\partial \eta} = R \int_{\theta_o}^{\theta_s} C(\theta) d\theta .$$

The essence of the Zeldovich treatment is to replace θ with an equivalent θ_{eq} to give the same regression rate-pressure relationship. For a linear heat capacity dependence ($C = C_A + C_B \theta$), the surface gradient then becomes

$$\frac{\partial \theta}{\partial \eta} = R \left[C_A (\theta_s - \theta_{eq}) + \frac{C_B}{2} (\theta_s^2 - \theta_{eq}^2) \right] ,$$

where

$$\theta_{eq} = \frac{1}{\sigma_p (T_{so} - T_o)} \ln \frac{R}{R_s} .$$

III. MEASURED THERMAL PROPERTIES

Ward⁹ measured temperature dependence of heat capacity below the decomposition point for nitrocellulose and X14 propellant. For the X14 propellant the reported value was

$$C = .118 + .66 \times 10^{-3} T(K) \text{ cal/gK}$$

over the temperature range 283-343 K.

A difficulty enters here because the theory has assumed an inert solid at all temperatures. Reactions in the solid which prevent heat capacity measurement have been assumed to occur only in a collapsed zone at the surface. A simple solution is to extrapolate the measurements to the calculated temperature, however high. The alternative is a complete recasting of the model which would require knowledge of the chemical reactions in the solid.

Cohen¹⁰ measured the thermal conductivity of two double base propellants. For DQO propellant the value is

$$\lambda = 1.90 \times 10^{-5} + 2.46 \times 10^{-6} T(K) \text{ cal/cmsecK}$$

over the temperature range 267-317 K. Again, the simplicity of an extrapolation outweighs the more difficult alternatives.

IV. RESULTS

With the variable properties, transients are less pronounced than with constant, low temperature properties. Figure 1 shows the effect of property variation on a calculation reported by Kooker and Nelson⁷ for a distributed flame. It shows that transient response is muted by the variable properties. Pressure was rising monotonically from 7 to 20 MPa during the transient as taken from the records of a 105 mm tank gun which reaches 400 MPa in about 3 ms. In Figure 1, CONCOLD means constant properties evaluated at the cold boundary; CONAVG means constant properties evaluated at an interim temperature (460 K); VAR means the variable properties.




Figure 1. Effect of Variable Properties

The effect of pressurization rate on the Kooker model is shown in Figure 2. In the 105 mm tank gun, the pressurization rate at the 7-20 MPa levels is about 7000 MPa/sec. The pressurization rate of a grain during the flamespreading process in a 155 mm howitzer is calculated to be about 14,000 MPa/sec at the middle of the bed and about 40,000 MPa/sec at the stagnation of bed against the projectile base. If the Kooker flame assumptions applied, these results suggest that burning rate excursions would extend to pressures over 100 MPa. With the high pressurization rates of DDT, such an effect cannot be ignored on the assumption that the excursions apply only at low pressures.




Figure 2. Effect of Pressurization Rate

Predictions of the Zeldovich model are shown in Figure 3 which shows the effect of varying temperature sensitivity and pressurization rate. Of note is the slow return of the relative rate toward unity. For the gun pressurization, an excursion of over 50% is predicted to survive for the whole ballistic cycle. With a steep pressurization rate (7×10^5 MPa/sec) the excursion is rapid on the time scale of a gun but does not peak until 50 MPa. Notable here is the transition from a lag (25% of quasi-steady rate) to an overshoot of 150% in the entire calculated cycle to a non-dimensional pressure of 173 (about 1.2 Kbars). For DDT analysis, these results say that a quasi-steady assumption ignores the predicted highly transient behavior.

Surface heat release is a critical parameter in the Kooker type model; the non-dimensional heat release is

$$H = Q_s / c_o (T_{s_o} - T_o)$$

The effect of varying H is shown in Figure 4. The response is similar to that of the constant properties solutions of Kooker and Nelson.⁷

Experimental values for Q_s are not well known; Kubota, et al.¹⁷ have suggested experimental values which vary with regression rate.




Figure 3. Zeldovich Model Results




Figure 4. Effect of Surface Heat Release

The model's response to a step doubling of pressure from 1 to 2 is shown in Figure 5. Such a pressure transient represents a limit of a steep pressure wave. The step used here has no immediate practical value; it is intended only as a test of the regression rate response lag.

STEP PRESSURE RESPONSE




Figure 5. Effect of Pressure Step Change

CONCLUSIONS

1. The regression rate overshoots predicted with constant initial temperature thermal properties are muted by the substitution of variable thermal properties.
2. Higher pressurization rates lead to higher transients and higher pressures at the peak overshoot.
3. No simple correlation of regression rate excursion with pressurization rate.
4. Predicted excursions are dependent on assumed surface heat release.
5. Regression rate excursions of two times the quasi-steady rate are predicted.

REFERENCES

1. J. Brulard, P. Kuentzmann, R. Kling, "Réponse d'un Propergol Solide à un Echelon de Pression", La Recherche Aéronautique, 5, 279-287 (1975).
2. S. L. Turk, R. A. Battista, K. K. Kuo, L. H. Caveny, and M. Summerfield, "Dynamic Responses of Solid Rockets during Rapid Pressure Change", J. Spacecraft & Rockets, 10, 137-142 (1973).
3. C. F. Yin and C. E. Hermance, "Continuous Measurement of Transient Burning Rates of a Composite Propellant Undergoing Depressurization", AIAA Paper 71-173 (1971).
4. C. E. Woolridge and G. A. Marxman, "A Comparison Between Theoretical and Experimental Extinction Behavior of Composite Solid Propellants", AIAA Paper 70-666 (1970).
5. K. K. Kuo and G. R. Coates, "Review of Dynamic Burning of Solid Propellants in Gun and Rocket Propulsion Systems", Sixteenth (International) Symposium on Combustion, 1177-1192 (1976).
6. C. W. Nelson, "Response of Three Types of Transient Combustion Models to Gun Pressurization", Combustion and Flame, 32, 317-319 (1978).
7. D. E. Kooker and C. W. Nelson, "Numerical Solution of Three Solid Propellant Combustion Models During a Gun Pressure Transient", USA Ballistic Research Laboratory, Report 1953 (1977). (See also ASME Journal of Heat Transfer, in press).
8. H. Krier, J. S. T'ien, W. A. Sirignano and M. Summerfield, "Non-Steady Burning Phenomenon of Solid Propellants: Theory and Experiments", AIAA Journal, 6, 278-285 (1968).
9. J. R. Ward, "Determination of the Heat Capacities of Gun Propellants by Differential Scanning Calorimetry", Analytical Calorimetry, 4, 143-153 (1977).
10. M. L. Cohen, M. Imber, "Variation of the Thermal Conductivity of Solid Propellants in an Acoustic Field", AIAA Journal 5, 1295-1299 (1967).
11. D. E. Kooker, "Numerical Predictions for Laminar Flame Propagation in Confined Ozone/Oxygen Mixtures: Influence of Initial Temperature and Pressure", AIAA Paper 79-0292, New Orleans (1979).
12. C. W. Nelson, "Another Comment on the Transient Burning Rate Model of Suhas and Bose", Combustion and Flame, 35, 213-215 (1979).

13. H. K. Suhas and T. K. Bose, "A Mathematical Model to Predict Transient Burning Rate and Pressure Decay Rates for Extinction of Composite Propellants", *Combustion and Flame*, 28, 145-153 (1977).
14. C. W. Nelson, P. S. Gough, and F. W. Robbins, "Ignition Transients in Flamespreading Calculations", AIAA Paper 79-0166, New Orleans (1979).
15. M. W. Beckstead, N. L. Peterson, D. T. Pilcher, and B. D. Hopkins, "Convective Combustion Modeling Applied to Deflagration to Detonation Transition of HMX", *Combustion and Flame* 30, 231-241 (1977).
16. D. E. Kooker and B. T. Zinn, "Numerical Investigation of Nonlinear Axial Instabilities in Solid Rocket Motors", USA Ballistic Research Laboratories Contract Report 141 (1974).
17. N. Kubota, T. J. Ohlemiller, L. H. Caveny, and M. Summerfield, "Site and Mode of Action of Platonizers in Double Base Propellants", *AIAA Journal* 12, 1709-1714 (1974).

LIST OF SYMBOLS

C	heat capacity (nd) c/c_o
c_o	reference heat capacity
c_p	gas phase heat capacity
H	surface heat release (nd)
C_A C_B	constants in heat capacity temperature dependence
L	conductivity (nd) λ/λ_o
P	pressure (nd) P/P_o
P_o	initial pressure
r	regression rate
R	regression rate (nd) r/r_o
r_s	steady state regression rate
r_o	initial regression rate
T	temperature
T_o	reference temperature
T_{so}	reference surface temperature
α_o	reference thermal diffusivity
η	distance (nd) xr_o/α_o
λ	thermal conductivity
λ_o	reference thermal conductivity
ρ	density
θ	temperature (nd) $(T-T_o)/(T_{so}-T_o)$
σ_p	temperature sensitivity of regression rate
τ	time (nd) $t r_o^2/\alpha$

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
12	Commander Defense Technical Info Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	1	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Watervliet, NY 12189
1	Director Defense Advanced Research Projects Agency ATTN: LTC C. Buck 1400 Wilson Boulevard Arlington, VA 22209	1	Commander US Army Watervliet Arsenal ATTN: SARWV-RD, R. Thierry Watervliet, NY 12189
2	Director Institute for Defense Analyses ATTN: H. Wolfhard R. T. Oliver 400 Army-Navy Drive Arlington, VA 22202	1	Commander US Army Aviation Research and Development Command ATTN: DRSAB-E P. O. Box 209 St. Louis, MO 63166
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333	1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035
2	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS Dover, NJ 07801	1	Commander US Army Communications Rsch and Development Command ATTN: DRDCO-PPA-SA Fort Monmouth, NJ 07703
3	Commander US Army Armament Research and Development Command ATTN: DRDAR-LC, T.Vladimiroff DRDAR-LCE, R.F. Walker DRDAR-LC, D. Downs Dover, NJ 07801	1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703
1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299	1	Commander US Army Missile Command ATTN: DRSMI-R Redstone Arsenal, AL 35809
		1	Commander US Army Missile Command ATTN: DRSMI-YDL Redstone Arsenal, AL 35809

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Natick Research and Development Command ATTN: DRXRE, D. Sieling Natick, MA 01762	1	Commander Naval Sea Systems Command ATTN: J.W. Murrin, SEA-62R2 National Center Bldg. 2, Room 6E08 Washington, DC 20362
1	Commander US Army Tank Automotive Rsch and Development Command ATTN: DRDTA-UL Warren, MI 48090	1	Commander Naval Surface Weapons Center ATTN: Library Br, DX-21 Dahlgren, VA 22448
1	Commander US Army White Sands Missile Range ATTN: STEWS-VT White Sands, NM 88002	2	Commander Naval Surface Weapons Center ATTN: S.J. Jacobs, Code 240 Code 730 Silver Springs, MD 20910
1	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL Watertown, MA 02172	1	Commander Naval Underwater Sys Center Energy Conversion Department ATTN: R.S. Lasar, Code 5B331 Newport, RI 02840
3	Commander US Army Research Office ATTN: Tech Lib D. Squire R. Singleton Research Triangle Park NC 27706	2	Commander Naval Weapons Center ATTN: R. Derr C. Thelen China Lake, CA 93555
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL, Tech Lib White Sands Missile Range NM 88002	1	Commander Naval Research Laboratory ATTN: Code 6180 Washington, DC 20375
1	Office of Naval Research ATTN: Code 473 800 N. Quincy Street Arlington, VA 22217	2	Superintendent Naval Postgraduate School ATTN: Tech Lib D. Netzer Monterey, CA 93940

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Commander Naval Ordnance Station ATTN: S. Mitchell Tech Lib Indian Head, MD 20640	1	Calspan Corporation ATTN: E. B. Fisher P. O. Box 400 Buffalo, NY 14211
2	AFOSR ATTN: L. Caveny B. T. Wolfson Bolling AFB, DC 20332	1	Foster Miller Associates, Inc. ATTN: A. J. Erickson 135 Second Avenue Waltham, MA 02154
2	AFRPL (DYSC) ATTN: D. George J. N. Levine Edwards AFB, CA 93523	1	General Electric Company Armament Department ATTN: M. J. Bulman Lakeside Avenue Burlington, VT 05402
2	National Bureau of Standards ATTN: T. Kashiwagi Washington, DC 20234	2	Hercules Incorporated Alleghany Ballistic Lab ATTN: R. Miller Tech Lib Cumberland, MD 21501
1	Lockheed Palo Alto Rsch Labs ATTN: Tech Info Ctr 3521 Hanover Street Palo Alto, CA 94304	1	IITRI ATTN: M. J. Klein 10 West 35th Street Chicago, IL 60615
1	Aerojet Solid Propulsion Co. ATTN: P. Micheli Sacramento, CA 95813	1	Olin Corporation Badger Army Ammunition Plant ATTN: J. Ramnarace Baraboo, WI 53913
1	ARO Incorporated ATTN: N. Dougherty Arnold AFS, TN 37389	2	Olin Corporation New Haven Plant ATTN: R. L. Cook D. W. Riefler 275 Winchester Avenue New Haven, CT 06504
1	Atlantic Research Corporation ATTN: M. K. King 5390 Cherokee Avenue Alexandria, VA 22314	1	Paul Gough Associates, Inc. ATTN: P. S. Gough P. O. Box 1614 Portsmouth, NH 03801
1	AVCO Corporation AVCO Everett Research Lab Div ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149		

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Physics International Co. 2700 Merced Street Leandro, CA 94577	2	Thiokol Corporation Wasatch Division ATTN: J. Peterson Tech Lib P. O. Box 524 Brigham City, UT 84302
1	Pulsepower Systems, Inc. ATTN: L. C. Elmore 815 American Street San Carlos, CA 94070	1	TRW Systems Group ATTN: H. Korman One Space Park Redondo Beach, CA 90278
2	Rockwell International Corp. Rocketdyne Division ATTN: C. Obert J. E. Flanagan 6633 Canoga Avenue Canoga Park, CA 91304	2	United Technologies Chemical Systems Division ATTN: R. Brown Tech Lib P. O. Box 358 Sunnyvale, CA 94086
2	Rockwell International Corp. Rocketdyne Division ATTN: W. Haymes Tech Lib McGregor, TX 76657	1	Universal Propulsion Co. ATTN: H. J. McSpadden 1800 W. Deer Valley Road Phoenix, AZ 85027
1	Science Applications, Inc. ATTN: R. B. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364	1	Battelle Memorial Institute ATTN: Tech Lib 505 King Avenue Columbus, OH 43201
1	Shock Hydrodynamics, Inc. ATTN: W. H. Anderson 4710-16 Vineland Avenue North Hollywood, CA 91602	1	Brigham Young University Dept of Chemical Engineering ATTN: M. W. Beckstead Provo, UT 84601
1	Thiokol Corporation Elkton Division ATTN: E. Sutton Elkton, MD 21921	1	California Institute of Tech 204 Karmar Lab ATTN: F.E.C. Culick 1201 E. California Street Pasadena, CA 91125
3	Thiokol Corporation Huntsville Division ATTN: D. Flanigan R. Glick Tech Lib Huntsville, AL 35807	1	Case Western Reserve Univ Division of Aerospace Sciences ATTN: J. Tien Cleveland, OH 44135

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
3	Georgia Institute of Tech School of Aerospace Engineering ATTN: B. T. Zinn E. Price W. C. Strahle Atlanta, GA 30332	1	Rutgers State University Dept of Mechanical and Aerospace Engineering ATTN: S. Temkin University Heights Campus New Brunswick, NJ 08903
1	Johns Hopkins University/APL Chemical Propulsion Info Agcy ATTN: T. Christian Johns Hopkins Road Laurel, MD 20810	4	SRI International ATTN: Tech Lib D. Crosley J. Barker D. Golden 333 Ravenswood Avenue Menlo Park, CA 94025
1	Massachusetts Institute of Technology Dept of Mechanical Engineering ATTN: T. Toong Cambridge, MD 02139	1	Stevens Institute of Tech Davidson Laboratory ATTN: R. McAlevy, III Hoboken, NJ 07030
1	Pennsylvania State University Applied Research Lab ATTN: G. M. Faeth P. O. Box 30 State College, PA 16801	1	University of Illinois Dept of Aeronautical Engineering ATTN: H. Krier Transportation Bldg., Rm 105 Urbana, IL 61801
1	Pennsylvania State University Dept of Mechanical Engineering ATTN: K. Kuo University Park, PA 16801	1	University of Minnesota Dept of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455
1	Pennsylvania State University Dept of Material Sciences ATTN: H. Palmer University Park, PA 16810	1	University of Southern California Department of Chemistry ATTN: S. Benson Los Angeles, CA 90007
1	Princeton University Forrestal Campus Library ATTN: Tech Lib P. O. Box 710 Princeton, NJ 08540	2	University of Texas Department of Chemistry ATTN: W. Gardiner H. Schaefer Austin, TX 78712
1	Purdue University School of Mechanical Eng. ATTN: J. Osborn TSPC Chaffee Hall West Lafayette, IN 47906		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>
2	University of Utah Dept of Chemical Engineering ATTN: A. Baer G. Flandro Salt Lake City, UT 84112

Aberdeen Proving Ground

Dir, USAMSAA
ATTN: DRXSY-D
DRXSY-MP, H. Cohen
Cdr, USATECOM
ATTN: DRSTE-TO-F
Dir, USACSL, Bldg. E3516
ATTN: DRDAR-CLB-PA

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____

2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

