


AD-A099 758 ARMY ELECTRONICS RESEARCH AND DEVELOPMENT COMMAND FO--ETC F/8 9/3  
OBSERVER PERFORMANCE MEASURED AGAINST HYBRID COMPRESSED VIDEO I--ETC(U)  
MAR 81 J E SWISTAK  
UNCLASSIFIED DELNV-TR-0019 NL

1 of 1  
1/1/81



END  
DATE  
FILMED  
6-81  
DTIC



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

9

LEVEL II

AD

AD A 099 758

Report DELNV-TR-0019 ✓

OBSERVER PERFORMANCE MEASURED AGAINST  
HYBRID COMPRESSED VIDEO IMAGERY

by  
Joseph E. Swistak


DTIC  
ELECTE  
JUN 5 1981  
S B D

March 1981

Approved for public release; distribution unlimited.

DTIC FILE COPY

U.S. ARMY ELECTRONICS R&D COMMAND  
NIGHT VISION & ELECTRO-OPTICS LABORATORY  
FT. BELVOIR, VIRGINIA 22060



81 6 05 049

**Destroy this report when no longer needed.  
Do not return it to the originator.**

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
14) 1. REPORT NUMBER DELNV-TR-0019	2. GOVT ACCESSION NO. AD-A099758	3. RECIPIENT'S CATALOG NUMBER 9	
6) 4. TITLE (and Subtitle) OBSERVER PERFORMANCE MEASURED AGAINST HYBRID COMPRESSED VIDEO IMAGERY		5. TYPE OF REPORT & PERIOD COVERED Technical Report 21	
		6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) 10) Joseph E. Swistak		8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS ERADCOM Night Vision & Electro-Optics Laboratory Fort Belvoir, Virginia 22060		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE 11) March 1981	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 20	
		15. SECURITY CLASS. (of this report) Unclassified	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Target Detection Target Recognition Remotely Piloted Vehicle Image Compression Video Bandwidth Compression			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) → A study was conducted in which the effects of bits per pixel reductions on target detection and recognition were measured. A hybrid DCT/DPCM compression algorithm was used to manipulate the bit-per-pixel reduction rate. The algorithm was implemented in the form of a software simulation package on a general-purpose minicomputer facility. Using this facility, real-time imagery was reduced from analog to 8- and 2-bit-per-pixel levels at 1-frame-per-second update rates. Observers were asked to detect and recognize targets located in the imagery. (Continued) → cont.			

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

(Continued from Block 20)

cont Average detection and recognition slant ranges were calculated for each target and compression level. No significant differences in performance were noted due to the different compression levels.

↖

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

## CONTENTS

Section	Title	Page
	ILLUSTRATIONS	iv
	TABLES	iv
	INTRODUCTION	1
	METHOD	2
	RESULTS AND DISCUSSION	3
	CONCLUSIONS	9

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
<b>A</b>	

## ILLUSTRATIONS

Figure	Title	Page
1	Mean Detection Ranges as a Function of Bits-per-pixel for the APC and 5/4-Ton Truck.	6
2	Mean Recognition Ranges as a function of Bits-per-pixel for the APC and 5/4-Ton Truck.	7
3	The APC Target at Minimum Range for all Three Information Levels: (a) analog, (b) 8 bits per pixel, (c) 2 bits per pixel.	8

## TABLES

Table	Title	Page
1	Mean Detection Ranges and Standard Deviations for the APC and 5/4-Ton Targets.	5
2	Mean Recognition Ranges and Standard Deviations for the APC and 5/4-Ton Truck Targets.	5

# OBSERVER PERFORMANCE MEASURED AGAINST HYBRID COMPRESSED VIDEO IMAGERY

## INTRODUCTION

The U.S. Army currently has a contract for the development of a Modular Integrated Communication and Navigation System (MICNS) which will be used as a communication link for such remote sensors as RPV and SOTAS. Since the communication link is RF, a means of reliably providing antijam (AJ) protection for the transmission of reconnaissance image data must be provided. A video image compression system is currently being developed along with and integral to the MICNS system which will provide this AJ protection. Current design has the bandwidth compression system consisting of a hybrid processor which uses a combination of a discrete cosine transform (DCT) followed by a differential pulse code modulation (DPCM) encoding of the resulting frequency coefficients to achieve intraframe compression.

One of the greatest concerns of developers is how much the video can be compressed before the performance of the operator falls below acceptable levels. The current planned spatial reduction level is 2 bits per pixel. The information refresh rate will vary from 1 to 15 frames per second. As presently planned, there are 19 different possible combinations of bit-per-pixel and frame rates which the operator will be able to choose from.

Until recently, the effects of various spatial compression levels have been determined by subjectively comparing a given level of reduction on a single frame to the original frame. This technique, although adequate for a laboratory quick-look assessment, falls far short of providing accurate and definitive data for an operational scenario. The frame-to-frame integration performed by the eye during a typical dynamic flight goes a long way toward smoothing the scene being viewed. It seems, therefore, that a better approach to measuring the effects of various compression levels on video information would be to perform the compression on a sequence of video frames rather than on just one frame.

Such a study<sup>1</sup> was conducted using an HAAR transform<sup>2</sup> to perform the spatial compression. These results indicated a 20-percent loss in detection and recognition

<sup>1</sup> J. E. Swistak, *Bandwidth Compression: Its Effect on Observer Performance*. SPIE Proceedings (Fall 79).

<sup>2</sup> T. Leibhoff, H. Henning, T. Noda, and B. Deal, *Final Report for Experimental Development of a FLIR Sensor Processor*. Technical Report 77Y106, Northrup Corporation, Anaheim, California (September 77).

range when the bits per pixel were reduced from 8 to 2.

More recently, a software simulation package was developed by the Lockheed Palo Alto Research Laboratory.<sup>3</sup> This facility is currently programmed to use the hybrid DCT/DPCM compression algorithm which will be used in the MICNS communications link. This facility was used to compress a subset of the imagery used in the previously referenced study. This imagery was then used as the stimulus material in a similar but much less exhaustive study of bandwidth compression effects on observer performance.

## METHOD

**Observers.** Twenty paid volunteers (1 male; 19 females) served as subjects. None had prior experience with an RPV system or with military target detection in general.

**Apparatus.** The subjects were required to view a 15-inch (38 cm) black-and-white video monitor (Ball Miratel Model BH-15). The video stimuli were two "runs" selected from a set of actual flight-test recordings of an RPV system being evaluated at Fort Huachuca, Arizona. A run comprised a single straight and level flight segment oriented so as to fly toward and over a specified target on the ground. Both runs were made at the same altitude (500 meters), heading, and ground speed (50 knots). Both runs were made over the same section of terrain. The only conditions to vary between the two runs were the type and location of the target. One run contained an APC; the other, a 5/4-ton truck. Both targets were located in off-road positions. These runs were a subset of those used in the study by Swistak<sup>4</sup> and were processed at three levels. The first level was simply a throughput compression; i.e., the tape was played through the facility without any frequency compression. This was effectively an analog-to-analog recording with only the electronics noise in the system having an effect. The analog tape was then played through again and digitized to 8 bits per pixel. The third level was a compression to 2 bits per pixel from the original analog tape. For each compression level, the same frames of video were selected and processed to prevent any anomalies in the performance data due to frame-to-frame variation. This resulted in a set of 6 target runs of approximately 145 seconds duration. Since each target run would be presented three times, there was some concern that the observers would recognize this fact and respond in an apriori fashion. To minimize this effect, 7 additional runs from a previous test were selected and alternated with the 6 test runs. The test runs were presented in a random fashion rather than sequentially to prevent an order effect in the results.

<sup>3</sup> K. Dutta, and M. Millman, *Dynamic Simulation of Hybrid Video Compression*. SPIE Proceedings (Fall 80).

<sup>4</sup> J. F. Swistak, *Bandwidth Compression: Its Effect on Observer Performance*. SPIE Proceedings (Fall 79).

During this study, the equipment was arranged so that four observers could be tested simultaneously. Each observer performed in a cubicle that was visually isolated from the other three observers.

Each observer responded to the video stimuli by means of a set of six switches mounted on a single control box. The functions of the switches were as follows: Number 1 was used to report "target detection"; numbers 3 through 6 were used to report recognition of the jeep, 5/4-ton truck, 2½-ton truck, and armored personnel carrier, respectively. Number 2 switch was designated as "reset" and was used by the observer to cancel any responses made within a trial as, for example, to cancel an incorrect "target detected" response when, upon closer inspection of the scene by the observer, that response proved to be in error.

**Procedures.** Observers were randomly assigned to 5 experimental groups of 4 observers each and scheduled for participation in the experiment. The first part of each session was devoted to orientation and practice. Formal data collection then followed with all tests on any observer being completed within a 2-hour time period.

Each observer viewed a total of 26 runs – 2 sets of 13. Six of the 13 were actual test runs; 7 were fillers. The fillers were used to prevent the observers from realizing the actual test runs were the same two target runs being repeated. The order in which the 13 runs were shown to the observers was always the same. The observers were shown the first set of 13 runs, given a break, then shown the same 13 runs a second time. This resulted in two complete sets of data. For each data trial (run) an observer had an opportunity to make a detection response and a recognition response by pressing the corresponding switches on his/her panel. A trial was considered valid and recognition data were recorded only if a target was recognized correctly. Observer responses were recorded against a time line commencing with the start of each trial. Given this measure of elapsed time plus the speed and altitude of the photographic aircraft, it was possible to calculate the respective detection and recognition ranges.

## RESULTS AND DISCUSSION

Preliminary analysis indicated a significant difference in the results for session one versus session two, thus precluding the use of the data as a combined set. As can be seen in Table 1, the means for session two are considerably greater for both targets regardless of compression condition. The conclusion here was that observer training was not completed prior to the presentation of session one and resulted in the significant increase in performance on session two. Therefore, it was felt that session two data more accurately reflected the performance a trained observer would exhibit. Because of this, only session two data were used for further analysis.

Overall, the mean detection range, as a function of bits per pixel, did not vary significantly. Figure 1 presents the detection data for bit-per-pixel effects for the APC and the 5/4-ton truck. The analysis showed a significant difference for the results between targets ( $F(1,38) = 13.59, p > .01$ ). However, no significant difference was obtained between the compression levels ( $F(2,76) = 0.11, p < .01$ ). These results indicate that no significant loss in detection performance occurs when video imagery is spatially compressed to 2 bits per pixel and displayed at 1 frame per second using the hybrid transform technique described earlier.

The statistical results and visual impressions conveyed in Figure 1 appear at odds, due to the dip and hump for the APC and 5/4-ton truck target, respectively. At first, it was felt that the order of presentation might account for the variation. The circled numbers above the data points in Figure 1 indicate the order in which each target and spatial compression combination were presented. It can be seen that no consistent trend can be accounted for due to the order of presentation. Examination of both the video tapes and data provided no rational reason why the larger excursions in the curves are present. At best, the variation can be described as an experimental anomaly which did not have a significant effect.

A similar analysis was conducted on the recognition data. The mean recognition ranges, shown in Table 2, do not have as clear a distinction between the session one and the session two data. This is especially true in the case of the 5/4-ton truck. Nevertheless, for reasons of consistency, only the session two data were used for further analysis.

Overall, the mean recognition range, as a function of bits per pixel, did not vary significantly. Figure 2 presents the recognition data for bit-per-pixel effects for the APC and the 5/4-ton truck. The analysis showed a significant difference for the results between targets ( $F(1,38) = 22.47, p > .01$ ). However, no significant difference was obtained between the compression levels ( $F(2,76) = 4.76, p < .01$ ). These results indicate that no significant loss in recognition performance occurs when video imagery is spatially compressed to 2 bits per pixel and displayed at one frame per second using the hybrid transform technique described earlier.

Once again, the visual impressions conveyed in Figure 2 do not appear substantiated by the statistical results. However, the large variation in the data shown as the standard deviation in Tables 1 and 2 does play a major role in accounting for the non-significant results. Figure 3 shows the APC target at minimum range for all three information levels (a) analog, (b) 8 bits per pixel, (c) 2 bits per pixel.

Table 1. Mean Detection Ranges and Standard Deviations  
for the APC and 5/4-Ton Truck Targets

			Analog	8-Bit	2-Bit
APC	Session 1	$\bar{x}$	2411	1828	2235
		s	298	372	388
	Session 2	$\bar{x}$	2631	2289	2540
		s	140	238	263
5/4	Session 1	$\bar{x}$	1375	1813	1784
		s	164	246	306
	Session 2	$\bar{x}$	1670	2081	1906
		s	318	256	511

Table 2. Mean Recognition Ranges and Standard Deviations  
for the APC and 5/4-Ton Truck Targets

			Analog	8-Bit	2-Bit
APC	Session 1	$\bar{x}$	1252	922	1257
		s	442	345	418
	Session 2	$\bar{x}$	1509	1182	1454
		s	494	327	413
5/4	Session 1	$\bar{x}$	550	791	950
		s	0	316	417
	Session 2	$\bar{x}$	588	738	840
		s	53	229	232




Figure 1. Mean detection ranges as a function of bits-per-pixel for the APC and 5/4-ton truck.




Figure 2. Mean recognition ranges as a function of bits-per-pixel for the APC and 5/4-ton truck.



b



a



c

Figure 3. The APC target at minimum range for all three information levels: (a) analog, (b) 8 bits per pixel, (c) 2 bits per pixel.

## CONCLUSIONS

Two major results are evident: First, the bit-per-pixel variation did not significantly affect observers ability to detect or recognize targets. Second, the type of target did have an effect. The results for the two targets used here are distinctly different.

For any future studies, it would be wise to select targets which more closely resemble one another either in size or shape. This would allow the data to be combined across targets and would lessen the variation in the results. Furthermore, the differences between individual observers should be minimized. This could be accomplished by training each observer to a given level of proficiency rather than by giving all observers the same amount of training. The short lead time and immediate need of the results precluded such a training method from being used in this study. However, any future studies would benefit greatly by using such a training technique.

**DISTRIBUTION FOR NV&EOL REPORT DELNV-TR-0019**

<b>No. Copies</b>	<b>Addressee</b>	<b>No. Copies</b>	<b>Addressee</b>
20	Commander ERADCOM ATTN: DRDEL-AP-OA M. Geisler Adelphi, MD 20783	1	Project Manager MICV Warren, MI 48090
1	Director Atmospheric Sciences Lab ATTN: DELAS-D White Sands Missile Range, NM 88002	1	Project Manager TOW/DRAGON Redstone Arsenal, AL 35809
1	Director CS&TA Laboratory ATTN: DELCS-D Fort Monmouth, NJ 07703	1	Project Manager GLLD/LTD Redstone Arsenal, AL 35809
1	Director Electronic Warfare Lab ATTN: DELEW-D Fort Monmouth, NJ 07703	1	Project Manager VIPER/AHAMS Redstone Arsenal, AL 35809
1	Director Electronics Tech & Devices Lab ATTN: DELET-D Fort Monmouth, NJ 07703	1	Project Manager AAH AVARADCOM St Louis, MO 63166
1	Commander Harry Diamond Labs ATTN: DELHD-AC Adelphi, MD 20783	1	Project Manager TADS/PNVS AVARADCOM St Louis, MO 63166
1	Director Signal Warfare Lab ATTN: DELSW-D Vint Hill Station, VA 22186	1	Commander ARRCOM ATTN: DRSAR-CPE Rock Island, IL 61299
1	Project Manager XM-1 Tank System Warren, MI 48090	1	Project Manager RPV AVARADCOM St Louis, MO 63166
1	Project Manager M60 Tank System Warren, MI 48090	1	Commander ARRADCOM ATTN: DRDAR-SEC Dover, NJ 07801

No. Copies	Addressee	No. Copies	Addressee
1	Commander CORADCOM ATTN: DRDCO-PPA-CA Fort Monmouth, NJ 07703	1	Commander NARADCOM ATTN: DRDNA-O Natick, MA 01760
1	Commander CERCOM ATTN: DRSEL-CP-CR Fort Monmouth, NJ 07703	1	Commander AMMRC Watertown, MA 02172
1	Commander MERADCOM ATTN: DRDME-CA	1	Commandant US Army Infantry School Ft Benning, GA 31905
3	DRDME-WP Fort Belvoir, VA 22060	1	Director Defense Advanced Research Projects Agency Rosslyn, VA 22209
1	Commander MIRADCOM ATTN: DRDMI-DC Redstone Arsenal, AL 35809	1	Commander US Naval Research Lab Washington, DC 20375
1	Commander MIRCOM ATTN: DRSMI-FO Redstone Arsenal, AL 35809	1	Commander HQ DARCOM ATTN: DRCCP-E Alexandria, VA 22333
1	Commander AVARADCOM ATTN: DRCAV-BC St Louis, MO 63166	1	Commandant Defense Systems Mgmt School Ft Belvoir, VA 22060
1	Commander TSARCOM ATTN: DRSTS-CO St Louis, MO 63166	1	Commandant US Army Engineer School Ft Belvoir, VA 22060
1	Commander TARADCOM ATTN: DRCTA-VC Warren, MI 48090	1	Commander US Operational Test and Evaluation Agency Ft Belvoir, VA 22060
1	Commander TARCOM ATTN: DRSTA-NC Warren, MI 48090	1	Commander USACSC Ft Belvoir, VA 22060
		1	HQDA ATTN: DACA-CA Washington, DC 20310

No. Copies	Addressee	No. Copies	Addressee
12	Defense Documentation Ctr ATTN: DDC-TCA Cameron Station (Bldg 5) Alexandria, VA 22314	1	Project Manager FIREFINDER ATTN: DRCPM-FF Fort Monmouth, NJ 07703
1	Commander US Army Training & Doctrine Com ATTN: ATCD-AN Ft Monroe, VA 23651	1	Department of Defense Production Engineering Spt Ofc (PESO) ATTN: D. Anderson Cameron Station Alexandria, VA 22314
2	Commander US Army Logistics Ctr Fort Lee, VA 23801	1	Project Manager CAC ATTN: DRCPM-CAC Vint Hill Station, VA 22186
1	Commander US Army Systems Analysis Agency Aberdeen Proving Ground, MD 21005	1	Project Manager SOTAS ATTN: DRCPM-STA Ft Monmouth, NJ 07703
1	NASA Scientific & Test Info Facility ATTN: Acquisitions Branch (S-AK/DL) P.O. Box 33 College Park, MD 20740	1	Commandant US Army Armor School Fort Knox, KY 40121
1	Study Center National Maritime Research Ctr King's Point, NY 11024	1	Commandant US Army Field Artillery School Fort Sill, OK 73503
1	Commander USAAVNC Ft Rucker, AL 36362	1	Commandant US Army Air Defense School Fort Bliss, TX 79916
1	Director NV&EOL ATTN: DELNU-TMS/SEMCO Ft Belvoir, VA 22060	1	Director US Army Air Mobility R&D Ctr Arnes Research Ctr Moffett Field, CA 94035
1	Project Manager REMBASS ATTN: DRCPM-RBS Fort Monmouth, NJ 07703	3	Commander AFSC/ACC Andrews AFB, MD 20334
		2	Commander ESD/ACC Hanscomb AFB, MA 01730

No. Copies	Addressee
1	Commander US Naval Ordnance Lab/White Oak ATTN: Technical Library Silver Spring, MD 20910
1	Commander Naval Electronics Lab Ctr ATTN: Library San Diego, CA 92152
1	Armament Development and Test Ctr ATTN: DLOSL, Tech Library Eglin Air Force Base, FL 32542
50	Director NV&EOL ATTN: DELNV-AC Fort Belvoir, VA 22060
1	Commander Sacramento Army Depot Sacramento, CA 95813
1	Commander New Cumberland Army Depot New Cumberland, PA 17070
1	Commander Anniston Army Depot Anniston, AL 36201
1	Dept of Defense Production Engineering Spt Ofc (PESO) ATTN: H.K. MacKechnie Cameron Station Alexandria, VA 22314

**DATE**  
**ILME**