

AD

MEMORANDUM REPORT ARBRL-MR-03094

CALCULATION OF HEAT TRANSFER TO THE
GUN BARREL WALL

TECHNICAL
LIBRARY

Carl W. Nelson
J. Richard Ward

March 1981

19971009 120



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

DTIC QUALITY INSPECTED 3

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute endorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR-03094	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) CALCULATION OF HEAT TRANSFER TO THE GUN BARREL WALL		5. TYPE OF REPORT & PERIOD COVERED Memorandum Report
7. AUTHOR(s) Carl W. Nelson J. Richard Ward		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS USA Ballistic Research Laboratory ATTN: DRDAR-BLI Aberdeen Proving Ground, MD 21005		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory ATTN: DRDAR-BL Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L162218AH80
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE MARCH 1981
		13. NUMBER OF PAGES 14
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Paper was presented at the Fifth International Ballistics Symposium, Toulouse, France, April 1980.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) NOVA Code XM203E2 Charge Heat Transfer Gun Barrel Wear 155mm Howitzer		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) bh, jmk Heat transfer to the barrel wall of a 155mm howitzer was calculated as part of an interior ballistics calculation with Gough's two phase flow code NOVA. The heat transfer coefficient between the core flow and the barrel wall was estimated by reference to a turbulent pipe flow correlation. The unsteady conduction in the wall was solved for the entire length of the chamber and tube. Comparisons of the calculated heat flow with measured heat absorption show that the calculated heat transfer of 1.5 J/mm^2 overestimates the measured value of 1.3 J/mm^2 .		

TABLE OF CONTENTS

	Page
I. INTRODUCTION.	5
II. RESULTS	6
III. DISCUSSION.	8
IV. CONCLUSIONS	9
REFERENCES.	10
DISTRIBUTION LIST	11

I. INTRODUCTION

There has been an evolution of the idea that erosion of metal from the surface of gun tubes is controlled by the heat transfer during the ballistic cycle. Despite the arguments that chemical surface reactions or mechanical friction may be major contributors, the intuitive appeal of heat transfer control persists.

Early efforts at correlating erosion rate with heat transfer were limited to inferences about the heat transfer rate from measured ballistic variables. Nordheim's methodology¹ was used by Jones and Breitbart² to compute heat transfer and thus wear. UK investigators used the Hicks-Thornhill methodology³ to correlate wear with the maximum computed temperature rise. Smith and O'Brasky⁴ used Nordheim's method to obtain a surface temperature and with it devised an empirical correlation for erosion rate.

All these methods depend on a wall surface temperature obtained from simplifying assumptions about the flow inside the gun. No coupling of the flow to the heat transfer appeared until Shelton, et al⁵, calculated heat transfer to the tube wall while simultaneously calculating the time and space dependent flow in the barrel. Shelton's analysis simplified the flow by assuming it was a one phase gas flow.

Attempts at calculating the two phase flow have just recently produced some reasonable agreement between calculated and measured ballistics. Gough's analysis⁶ has been seen to correctly predict

¹L.W. Nordheim, H. Soodak and G. Nordheim: "Thermal Effect of Propellant Gases in Erosion Vents and Guns," National Defense Research Committee Report A-262, March 1944.

²R.N. Jones and S. Breitbart: "A Thermal Theory for Erosion of Guns by Powder Gases," BRL Report 747, January 1951. (AD #801741)

³J. Corner, *Theory of the Interior Ballistics of Guns*, Wiley and Sons, Inc., New York, 1950.

⁴C.S. Smith and J.S. O'Brasky: "A Procedure for Gun Barrel Erosion Life Estimation," *Proceedings of the Tri-Service Symposium on Gun Tube Wear and Erosion*, March 1977.

⁵S. Shelton, A. Bergles and P. Saha: "Study of Heat Transfer and Erosion in Gun Barrels," US Air Force Armament Laboratory Report AFATL-TR-73-69, March 1973.

⁶P.S. Gough: "Numerical Analysis of a Two Phase Flow with Explicit Internal Boundaries," IHCR 77-5, US Naval Ordnance Station, April 1977.

pressure waves in large caliber guns⁷. An inference may be drawn that if the measurable behavior is correctly predicted, the unmeasurable may be reasonably accurate. In that vein, there should be a prospect of calculating the heat transfer once the core flow calculation has been established. Present research is attempting to do both simultaneously with two dimensional, two phase analyses.

This paper will report a calculation of the heat transfer to the wall of a 155mm howitzer from the zone 8S XM203E2 charge minus its wear-reducing additive, using the Gough analysis for the core flow with a simple pipe flow correlation for the heat transfer coefficient to the wall surface. The results will be compared to experimental measurements made by Ward and Brosseau⁸.

II. RESULTS

The pipe flow correlation for heat transfer coefficient is after Holman⁹:

$$q = h(T_g - T_s), \quad (1)$$

where q = heat transfer rate,
 h = convective heat transfer coefficient,
 T_g = core gas temperature, and
 T_s = wall surface temperature.

The convective heat transfer coefficient, h , is defined as

$$h = \frac{\lambda}{D_h} [3.65 + 0.243(R_e^{0.8})(P_r^{0.4})], \quad (2)$$

⁷A. Horst, C. Nelson and I. May: "Flame Spreading in Granular Propellant Beds: A Diagnostic Comparison of Theory to Experiment," AIAA Paper 77-856, July 1977.

⁸J.R. Ward and T.L. Brosseau: "Effect of Wear Reducing Additives on Heat Transfer into the 155mm M185 Cannon," BRL Memorandum Report 2730, February 1977. (AD #A037374)

⁹J.P. Holman: "Heat Transfer," McGraw-Hill, 1968.

where λ = thermal conductivity of propellant gas,
 D_h = hydraulic diameter,
 R_e = Reynolds number, and
 Pr = Prantl number.

The hydraulic diameter is related to the tube radius by

$$D_h = 2\epsilon R_T \left[1 + 2R_T \frac{\epsilon}{D_p} \right], \quad (3)$$

where ϵ = porosity,
 R_T = tube radius, and
 D_p = particle diameter.

The analysis for the core flow (assumed to be unaffected by the boundary layer) is that of Gough⁶. The calculation starts with a cold bed of propellant at rest in the chamber. Igniter gas input simulates the convective processes which lead to ignition, bed motion, flame-spreading, and projectile motion. The two phase flow accounts inter alia for bed compaction, bed stagnation at the projectile base, and wave motion in the chamber, all of which would have profound influences on the gas flow and therefore the instantaneous heat transfer.

The solution in the tube wall, to obtain the surface temperature, assumes a cubic profile integral approximation. This method has been shown to produce a surface temperature change error of about 2% for a constant heat flux and 6% for a linearly increasing flux¹⁰.

Figure 1 presents the calculated heat transfer rate and wall surface temperature versus time from gun igniter flow initiation. The axial distance is 6mm (0.25 inch) forward of the commencement of rifling.

The calculated cumulative heat transfer at 60ms was 1.5 J/mm^2 .

¹⁰C.W. Nelson: "On Calculating Ignition of a Propellant Bed," BRL Report ARBRL-MR-02864, September 1978. (AD #A062266)




Fig. 1. Calculated Heat Flux and Wall Temperature

III. DISCUSSION

Measurement of the heat transfer in the 155mm howitzer was made by Ward and Brosseau⁸. With four thermocouples, the temperature distribution was estimated inside the tube wall at 100ms after ignition. Graphical integration of the distribution was used to estimate the heat transfer on the assumption that no transfer occurred from the wall after projectile exit at about 20ms. For the charge simulated in the calculation, the measured heat absorbed by the tube wall was 1.3 J/mm^2 .

This calculation was intended only as a test to estimate the overall error inherent in NOVA's approach to the wall heat transfer problem. NOVA addressed the core flow; the heat transfer to the wall was an inexpensive aside. The pipe flow correlation should not be expected to be accurate in the gun condition which departs so much from a developed one phase steady flow.

Measured heat flow for this gun was 1.3 J/mm^2 whereas the calculated value is 1.5 J/mm^2 . Simple remedies of adjusting constants may correct the present answer but cannot be expected to provide a general correction applicable to other gun calculations. For the present, it would be speculation to allot error contributions to the several simplifications assumed in the formulation.

To avoid a rewrite of part of the code, it was assumed that tube emptying after projectile exit would be adequately simulated by making the tube indefinitely long. Such flow would be different from flow emptying to one atmosphere pressure, but whether this would be critically different has not been established. Of the total 1.5 J/mm^2 delivered to the barrel wall, 1.2 J/mm^2 was transferred before projectile exit.

It is interesting to note that the predicted peak wall temperature (1,200K) was well below the melting point of the steel (1,770K). If the erosion is high because of melting, the calculation that predicts a total heat well above the measured heat should come closer to the melt temperature than one that calculates the correct lower total heat. A too low peak temperature would result from a too slow heating or too high conductivity of the tube wall. Given the state of knowledge of the conductivity, the culprit seems more likely to be the heat transfer rate during the early heating phase.

In similar calculations with the zone 8 XM201E2 charge, Vassallo¹¹ found the peak surface temperature was well below the melting point of steel. He predicted a surface temperature of 1,300K and concluded the erosion resulted from surface reaction effects.

The modest error resulting from this first time calculation promises that some reasonable improvements may narrow the gap. It is limited, however, to situations where no melting occurs and where any chemical reaction heat release can be combined with purely convective phenomena. In its present form, it could be used as a method for first estimates of wear. Since it overpredicts the heat transfer and since erosion has been found to vary with heat transfer, it would lead to conservative estimates of the erosion.

IV. CONCLUSIONS

1. The NOVA Code overestimates heat transfer to the gun barrel wall in the origin of rifling region for the zone 8S, XM203E2 charge without additive.
2. The peak surface temperature computed by the NOVA Code for the zone 8S charge minus wear-reducing additive is 1,200K which is well below the steel melting temperature.

¹¹F.A. Vassallo and W.R. Brown: "Shock Tube Gun Melting Erosion Study," BRL Contract Report ARBRL-CR-406, August 1979. (AD #A076219)

REFERENCES

1. L.W. Nordheim, H. Soodak and G. Nordheim: "Thermal Effects of Propellant Gases in Erosion Vents and Guns," National Defense Research Committee Report A-262, March 1944.
2. R.N. Jones and S. Breitbart: "A Thermal Theory for Erosion of Guns by Powder Gases," BRL Report 747. January 1951. (AD #801741)
3. J. Corner, Theory of the Interior Ballistics of Guns, Wiley and Sons, Inc., New York, 1950.
4. C.S. Smith and J.S. O'Brasky: "A Procedure for Gun Barrel Erosion Life Estimation," Proceedings of the Tri-Service Symposium on Gun Tube Wear and Erosion, March 1977.
5. S. Shelton, A. Bergles and P. Saha: "Study of Heat Transfer and Erosion in Gun Barrels," US Air Force Armament Laboratory Report AFATL-TR-73-69, March 1973.
6. P.S. Gough: "Numerical Analysis of a Two Phase Flow with Explicit Internal Boundaries," IHCR 77-5, US Naval Ordnance Station, April 1977.
7. A. Horst, C. Nelson and I. May: "Flame Spreading in Granular Propellant Beds: A Diagnostic Comparison of Theory to Experiment," AIAA Paper 77-856, July 1977.
8. J.R. Ward and T.L. Brosseau: "Effect of Wear Reducing Additives on Heat Transfer into the 155mm M185 Cannon," BRL Memorandum Report 2730, February 1977. (AD #A037374)
9. J.P. Holman: "Heat Transfer," McGraw-Hill, 1968.
10. C.W. Nelson: "On Calculating Ignition of a Propellant Bed," BRL Report ARBRL-MR-02864, September 1978. (AD #A062266)
11. F.A. Vassallo and W.R. Brown: "Shock Tube Gun Melting Erosion Study," BRL Contract Report ARBRL-CR-406, August 1979. (AD #A076219)

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Technical Info Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	6	Commander US Army Armament Research & Development Command ATTN: DRDAR-LC, J. Frasier H. Fair J. Lannon A. Bracuti A. Moss R. Walker Dover, NJ 07801
1	Director of Defense Research and Engineering ATTN: R. Thorkildsen The Pentagon Arlington, VA 20301	6	Commander US Army Armament Research & Development Command ATTN: DRDAR-LC, J. Picard D. Costa E. Barrieres R. Corn K. Rubin J. Houle Dover, NJ 07801
1	Director Defense Advanced Research Projects Agency Director, Materials Division 1400 Wilson Boulevard Arlington, VA 22209	4	Commander US Army Armament Research & Development Command ATTN: DRDAR-LC, E. Wurzel K. Russell D. Downs R.L. Trask Dover, NJ 07801
3	HQDA (DAMA-ARZ; DAMA-CSM; DAMA-WSW) Washington, DC 20301	1	Commander US Army Armament Research & Development Command ATTN: DRDAR-QA, J. Rutkowski Dover, NJ 07801
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCMDM-ST 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299
2	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS Dover, NJ 07801		
5	Commander US Army Armament Research and Development Command ATTN: FC & SCWSL, D. Gyorog H. Kahn B. Brodman S. Cytron T. Hung Dover, NJ 07801		

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
5	Commander US Army Armament Research and Development Command Benet Weapons Laboratory ATTN: I. Ahmad T. Davidson J. Zweig G. Friar DRDAR-LCB-TL Watervliet, NY 12189	1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703
5	Commander US Army Armament Research and Development Command Benet Weapons Laboratory ATTN: J. Busuttil W. Austin R. Montgomery R. Billington J. Santini Watervliet, NY 12189	1	Commander US Army Missile Command ATTN: DRSMI-R Redstone Arsenal, AL 35809
1	Commander US Army Aviation Research and Development Command ATTN: DRSAB-E P. O. Box 209 St. Louis, MO 63166	1	Commander US Army Missile Command ATTN: DRSMI-YDL Redstone Arsenal, AL 35809
1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035	1	Commander US Army Tank Automotive Rsch and Development Command ATTN: DRDTA-UL Warren, MI 48090
1	Commander US Army Research and Technology Laboratories ATTN: R. A. Langworthy Fort Eustis, VA 23604	1	President US Army Armor & Engineer Bd Fort Knox, KY 40121
1	Commander US Army Communications Rsch and Development Command ATTN: DRDCO-PPA-SA Fort Monmouth, NJ 07703	1	Project Manager, M60 Tanks US Army Tank & Automotive Cmd 28150 Dequindre Road Warren, MI 48090
		4	Project Manager Cannon Artillery Weapons Sys ATTN: DRCPM-CAWS US Army Armament Research and Development Command Dover, NJ 07801
		2	Project Manager - M110E2 ATTN: J. Turkeltaub S. Smith Rock Island, IL 61299

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Project Manager - XM1 Tank US Army Tank Automotive Development Command 28150 Dequindre Road Warren, MI 48090	1	Commander US Army Armor Center ATTN: ATZK-XM1 Fort Knox, KY 40121
1	Project Manager - XM1 Tank Main Armament Dev Div Dover, NJ 07801	1	Commander US Army Field Artillery School ATTN: J. Porter Ft. Sill, OK 73503
1	Project Manager - ARGADS Dover, NJ 07801	5	Commander Naval Surface Weapons Center ATTN: M. Shamblen J. O'Brasky C. Smith L. Russell T. W. Smith Dahlgren, VA 22448
1	Commander US Army DARCOM Materiel Readiness Support Activity Lexington, KY 40511	2	Commander Naval Ordnance Station ATTN: L. Dickinson S. Mitchell Indian Head, MD 20640
2	Director US Army Materials and Mechanics Research Center ATTN: J. W. Johnson K. Shepard Watertown, MA 02172	1	Commander Naval Ordnance Station, Louisville ATTN: F. Blume Louisville, KY 40202
3	Director US Army Research Office ATTN: P. Parrish E. Saibel D. Squire P. O. Box 12211 Research Triangle Park NC 27709	2	AFATL (D. Uhrig, O. Heiney) Eglin AFB, FL 32542
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL, Tech Lib White Sands Missile Range NM 88002	1	National Bureau of Standards Materials Division ATTN: A. W. Ruff Washington, DC 20234
1	Commander US Army Air Defense Center ATTN: ATSA-SM-L Fort Bliss, TX 79916	1	National Science Foundation Materials Division Washington, DC 20550

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Battelle Columbus Laboratory ATTN: G. Wolken Columbus, OH 43201	1	SRI International Materials Research Center 333 Ravenswood Avenue Menlo Park, CA 94025
1	Lawrence Livermore Laboratory ATTN: J. Kury Livermore, CA 94550	1	University of Illinois Dept of Aeronautics and Aerospace Engineering ATTN: H. Krier Urbana, IL 61803
2	Calspan Corporation ATTN: G. Sterbutzel F. Vassallo P. O. Box 400 Buffalo, NY 14221		<u>Aberdeen Proving Ground</u> Dir, USAMSAA ATTN: DRXSY-D DRXSY-MP, H. Cohen D. Barnhardt, RAM Div G. Alexander, RAM Div Air Warfare Div Ground Warfare Div RAM Division
1	Director Chemical Propulsion Info Agcy Johns Hopkins University ATTN: T. Christian Johns Hopkins Road Laurel, MD 20810		Cdr, USATECOM ATTN: DRSTE-FA DRSTE-AR DRSTE-AD DRSTE-TO-F
1	Princeton University Forrestal Campus Library ATTN: Tech Lib B. Royce P. O. Box 710 Princeton, NJ 08540		Dir, USAMTD ATTN: H. Graves, Bldg. 400 L. Barnhardt, Bldg. 400 K. Jones, Bldg. 400 R. Moody, Bldg. 525
1	Purdue University School of Mech Engineering ATTN: J. R. Osborn W. Lafayette, IN 47909		Dir, USACSL, Bldg. E3516 ATTN: DRDAR-CLB-PA