

AD-A100 315 TEXAS A AND M UNIV COLLEGE STATION DEPT OF MATHEMATICS F/G 20/11
ANNUAL SCIENTIFIC REPORT, 1 APRIL 1980 THRU 31 MARCH 1981, (U)
MAR 81 J R WALTON AFOSR-77-3290

UNCLASSIFIED

AFOSR-TR-81-0492

NL

1 of 1
AD-A100 315



END

DATE

FILED

7 81

DTIC

4

LEVEL II

AD A100815

ANNUAL SCIENTIFIC REPORT
of work completed during the grant year
4-1-80 to 3-31-81
under [REDACTED]

AFOSR-77-3290

Prepared by

Jay R. Walton
Department of Mathematics
Texas A&M University
College Station, Texas 77843

DTIC
SELECTED
JUN 12 1981
C

DTIC FULL COPY

81 6 12 070

Approved for public release;

A) In collaboration with Prof. A. Nachman and Prof. J. Tweed of Old Dominion University, the investigation of energy release rate calculations for interface edge cracks was continued. An earlier paper by Nachman and Walton ("Energy release rate calculations for interface edge cracks based on a conservation integral," Int. J. Solids Structures, Vol. 16, 1980, pp. 695-699) addressed a mixed Mode I (opening mode) and Mode II (in plane shearing mode) elastic interface edge fracture. The latest work was for a Mode III (anti-plane shearing mode) deformation as might arise in the torsion of two welded rods. Specifically, the M-conservation integral is applied to the calculation of energy release rates for an edge crack along the interface between two elastic wedges of different opening angles and dissimilar elastic properties, and that is subjected to point loads at the apex. A relation is derived among the length of the crack, the energy release rate of the crack, the applied loads, the wedge angles and the material properties. This work is contained in the paper "Energy Release Rate Calculations for an Interface Mode III Edge Crack Based on a Conservation Integral" which is to appear in the Int. J. Engng. Sci..

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)
NOTICE OF TRANSMITTAL TO DDC
This technical report has been reviewed and is
approved for public release IAW AFR 190-12 (7b)
Distribution is unlimited.
A. D. BLOSE
Technical Information Officer

was continued. The principal investigator considered three separate dynamic crack problems as described in sections B), C) and D) below.

B) An analysis of the anti-plane strain problem of a steadily propagating, semi-infinite crack in an infinite linear viscoelastic body which is subjected to a distribution of shearing tractions moving with the crack was completed. This work is contained in the paper "On the steady state propagation of an anti-plane shear crack in an infinite general linearly viscoelastic body," which is to appear in the Quart. Appl. Math. A description of the results is contained in the abstract from the paper which is attached to this report.

C) An analysis was completed of the dynamic Mode III crack problem for a layer of finite thickness analogous to that described in section B) for an infinite body. A closed form expression for the stress intensity factor was obtained for very general viscoelastic shear modulus. The solution and analysis are very much more complicated for a layer than for an infinite body, but the Riemann-Hilbert method that was employed yields a form for the stress intensity factor that illuminates the combined effects of material inertia and boundary interactions. This work will appear in a paper that is soon to be written and submitted for publication.

D) A study was initiated of the steady-state, dynamic Mode I (opening mode) crack problem for an infinite general linearly viscoelastic body analogous to the Mode III problem described in section B). The Mode I model is more important to engineering applications than the Mode III, but introduces significant additional mathematical complications. The results obtained to date on this problem are preliminary and incomplete and hence will not be described here.

ON THE STEADY STATE PROPAGATION OF AN ANTI-PLANE SHEAR CRACK
IN AN INFINITE GENERAL LINEARLY VISCOELASTIC BODY

Abstract

The steady state propagation of a semi-infinite anti-plane shear crack is considered for a general infinite homogeneous and isotropic linearly viscoelastic body. Inertial terms are retained and the only restrictions placed on the shear modulus are that it be positive, continuous, decreasing and convex. For a given integrable distribution of shearing fractions travelling with the crack, a simple closed form solution is obtained for the stress intensity factor and for the entire stress field ahead of and in the plane of the advancing crack. As was observed previously for the standard linear solid, the separate considerations of two distinct cases, defined by parameters c and c^* , arises naturally in the analysis. Specifically, c and c^* denote the elastic shear wave speeds corresponding to zero and infinite time, and the two cases are 1) $0 < v < c^*$ and 2) $c^* < v < c$, where v is the speed of propagation of the crack. For case 1) it is shown that the stress field is the same as in the corresponding elastic problem and is hence independent of v and all material properties. Whereas, for case 2) the stress field depends on both v and material properties. This dependence is shown to be of a very elementary form even for a general viscoelastic shear modulus.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AFOSR-TR-81-0492	2. GOVT ACCESSION NO. AD-A100 315	3. RECIPIENT CATALOG NUMBER
4. TITLE (and Subtitle) ANNUAL SCIENTIFIC REPORT	5. TYPE OF REPORT & PERIOD COVERED Annual for 4/1/80 to 3/31/81	
6. AUTHOR(s) Jay R. Walton	7. CONTRACT OR GRANT NUMBER(s) ✓ AFOSR-77-3290	
8. PERFORMING ORGANIZATION NAME AND ADDRESS Texas A&M University Department of Mathematics College Station, Texas 77843	9. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 61102F, 2304/A4	
10. CONTROLLING OFFICE NAME AND ADDRESS Air Force Office of Scientific Research/NM Bolling AFB, Washington, DC 20332	11. REPORT DATE 3/21/81	
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	13. NUMBER OF PAGES 4 (Four)	
	14. SECURITY CLASS. (of this report) UNCLASSIFIED	
15. DECLASSIFICATION/DOWNGRADING SCHEDULE		
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Dynamic viscoelastic fracture, elastic interface edge fracture, Riemann- Hilbert boundary value problem, stress intensity factor, conservation integral		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report summarizes progress on certain theoretical questions arising in the study of the fracture mechanics of linearly elastic and viscoelastic material. Specifically, two classes of problems are described: A. Energy release rate calculations for a Mode III elastic interface edge crack based on the M-conservation integral;		

(continued on reverse side)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

- B. A description of the dynamic stress field ahead of a steadily propagating semi-infinite crack in a general infinite viscoelastic body and in a viscoelastic layer of finite thickness. Both Mode I and Mode III deformations are considered.

B

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

DAT
ILM