

AD-A100 891

NAVAL SURFACE WEAPONS CENTER SILVER SPRING MD

F/6 21/8.2

A METHOD FOR THE CORRECTION OF FINITE RISE TIME EFFECTS IN THE --ETC(U)

FEB 81 E 6 POWELL

UNCLASSIFIED

NSWC/MP-81-67

NL

1 of 1
484
10384



END

DATE

FILED

7-81

DTIC

NSWC MP 81-67

LEVEL

AD A 100891

**A METHOD FOR THE CORRECTION OF FINITE RISE
TIME EFFECTS IN THE CHARACTERIZATION OF
NON LINEAR VISCOELASTIC MATERIALS**

BY E. G. POWELL


RESEARCH AND TECHNOLOGY DEPARTMENT

FEBRUARY 1981

Approved for public release, distribution unlimited.

DTIC FILE COPY

DTIC
JUL 2 1981
C



NAVAL SURFACE WEAPONS CENTER

Dahlgren, Virginia 22448 • Silver Spring, Maryland 20910

81 6 29 301

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)


REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NSWC/MP-81-67	2. GOVT ACCESSION NO. ADA100591	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A Method for the Correction of Finite Rise Time Effects in the Characterization of Non Linear Viscoelastic Materials	5. TYPE OF REPORT & PERIOD COVERED Final Report Oct 88 - Jan 81	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) E. G. Powell	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Surface Weapons Center White Oak Wilver Spring, Maryland 20910	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 0;	
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE February 1981	13. NUMBER OF PAGES 10
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Prepared at the request of the Naval Ordnance Station, Indian Head, Maryland		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Rocket Motors Rocket Propellant Viscoelastic Nonlinear		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A method is presented here for the correction of the effect of finite rise time upon stress relaxation experiments. The basis for the correction relies on the Farris nonlinear homogeneous theory. In the limit of zero nonlinearity the correction is shown to agree with the correction by linear theory. In the limit of very strong nonlinearity the correction is achieved by redefining the zero of time to be at the end of the rise time.		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

FOREWORD

This report was prepared at the request of Mr. John Kelly, Naval Ordnance Station, as a justification for the commonly used engineering approximation of taking the stress relaxation time zero from the termination of the strain ramp. Although the extent of applicability of the Farris theory has been called into question recently, use of this report's rise time correction based on the Farris theory permits nearly an order of magnitude improvement in the useful short-time stress relaxation data.

J. F. PROCTOR
By direction

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	<input type="checkbox"/>
By	
Distribution	
Availability Codes	
Dist Special	
A	

CONTENTS

	<u>Page</u>
Introduction	5
Derivation of the Correction	5
Comparison with Linear Theory	7
Summary	7
Recommendations	7

INTRODUCTION

The characterization of viscoelastic materials usually requires measurement of stress relaxation while the specimen is held at a constant strain. A practical problem encountered in the interpretation of these data is accounting for the effect of finite rise time of the applied strain. For a variety of reasons, either instrumental or procedural, the rise time cannot be made very short. One common approach to the problem simply ignores data acquired soon after the full constant strain level is achieved. However this throws away nearly a decade of potentially useful data about the short-time behavior. For the case of linearly viscoelastic materials and for a linear ramp to full strain, there exists the well-known correction of taking the zero of time from the mid-point of the ramp. In practice this is most useful for unfilled polymers. We derive here a more general correction which applies to the Farris theory of viscoelasticity¹. The correction has been found to apply to solid rocket propellant.

DERIVATION OF THE CORRECTION

The Farris theory preserves one of the two requirements for linearity, homogeneity, but permits the other requirement, superposition, to have a particular non-linear form. This theory is usually applied to solid rocket propellants which are filled polymers with permanent memory. The phenomenon of permanent memory is physically modeled by assumptions about cumulative damage and is mathematically implemented by a functional of strain history. The functional of strain history is the Lebesgue norm, $||\epsilon||_p$, of strain from the zero point in time to the present:

$$||\epsilon||_p = \left[\int_0^t |\epsilon(x)|^p dx \right]^{1/p}, \quad p \geq 1$$

¹Farris, R. J., "Homogeneous Constitutive Equations for Materials with Permanent Memory", PhD Dissertation, College of Engineering, University of Utah, 1970.

where ϵ is the uniaxial strain and p is a parameter of the theory which measures the degree of nonlinearity.

Details of the theory can be found in reference (1), so we start here with a result of the theory which gives the stress, σ , of an isothermal uniaxial specimen:

$$\sigma(t) = E \epsilon \left(\frac{|\epsilon|}{||\epsilon||_p} \right)^m$$

We derive a correction for a finite rise time, T , by calculating the stress at a time, $t > T$, where the strain history is

$$\begin{array}{ll} \epsilon = 0 & t < 0 \\ \epsilon = Rt & 0 \leq t \leq T \\ \epsilon = RT & t > T \end{array}$$

and where R is the strain rate of the ramp. Thus, splitting the functional into two parts for the two non-zero domains of definition we have:

$$\epsilon(t) = E R T \left(\frac{|RT|}{\left[\int_0^T |Rt|^p dx + \int_T^t |RT|^p dx \right]^{1/p}} \right)^m$$

which reduces to

$$\sigma(t) = E \epsilon_0 \left\{ \frac{1}{\left[-T \left(\frac{p}{p+1} \right) + t \right]^{1/p}} \right\}^m$$

The desired correction is achieved by noting that, if the zero of time is redefined to start at $t = \left(\frac{p}{p+1} \right) T$, then exactly the same result is obtained as if the experiment had been conducted with a truly zero rise time.

COMPARISON WITH LINEAR THEORY

Note that in the limit $p \rightarrow 1$ the correction reduces to the linear viscoelastic correction derived by Farris (1). In the limit $p \rightarrow \infty$ the correction implies that the zero of time is taken from the time of ramp termination. In fact, materials with a high degree of solids loading often give the straightest line on a log-log plot when the ramp termination is taken as the zero point of time. This agrees with the observations of Farris indicating that p is frequently large, often exceeding three and sometimes becoming as large as twenty.

SUMMARY

In the Farris model of nonlinear viscoelasticity, the effect on a stress relaxation experiment of a finite rise time, T , can be corrected by taking the zero of time at

$$t' = \left(\frac{p}{p+1} \right) (T) \quad 1 \leq p \leq \infty$$

from the beginning of the ramp. Since $p \gg 1$, this constitutes a justification of the common engineering practice of taking the zero of time from the end of the ramp.

RECOMMENDATIONS

In recent years the range of applicability of the Farris theory has been questioned, however the field of nonlinear viscoelasticity is very difficult and remains incompletely developed. Therefore it is recommended additional study of rise time effects be done when a fully satisfactory theory arrives. Prof. R. Schapery of Texas A and M University continues to develop his thermodynamic theory². Because of the fundamental basis of that work we recommend further that particular attention be given to Prof. Schapery's theory in further studies of rise time effects.

²Schapery, R. A., "On the Characterization of Nonlinear Viscoelastic Materials", Polymer Eng. Sci., Vol. 9, pp 295-310, 1969.

DISTRIBUTION

	<u>Copies</u>		<u>Copies</u>
Commander		Hercules Inc.	
Naval Ordnance Station		Bacchus Works	
Attn: Code 20C	1	Attn: Dr. S. Beckwith	1
Code 5243C	2	P.O. Box 98	
Code 5251	2	Magna, UT 84044	
Code 5253	1		
Code 5253B	1	Johns Hopkins University	
Code PM4	1	Applied Physics Laboratory	
Code 3011	1	Chemical Propulsion Information	
Code 2021B	1	Agency	
Code TDT1T	1	Attn: Mr. R. Brown	1
Indian Head, MD 20640		Mr. H. Hoffman	1
		Laurel, MD 20810	
Chief of Naval Research		Commander	
Attn: ONR-473		Air Force Rocket Propulsion Lab.	
800 North Quincy St.		Attn: Code MKBB, Mr. D. Thrasher	1
Arlington, VA 22217	2	Edwards AFB, CA 93523	
Defense Technical Information Center		Library of Congress	
Cameron Station		Washington, DC 20540	
Alexandria, VA 22314	12	Attn: Gift and Exchange Division	4
Commander			
Naval Weapons Center			
Attn: Code 3858, Dr. A. Adicoff	1		
China Lake, CA 93555			
Commander			
Naval Research Laboratory			
Attn: Mr. W. D. Bascom			
Washington, DC 20375	1		
Commander			
Naval Sea Systems Command			
Attn: SEA-033	1		
SEA-03B	1		
SEA-09G32	2		
Naval Sea Systems Command Headquarters			
Washington, DC 20362			

ATE
LMED
-8