

AD-A104 190

NEW MEXICO STATE UNIV LAS CRUCES PHYSICAL SCIENCE LAB
DEVELOPMENT OF LARGE CYLINDRICAL STRIPLINE ANTENNA ARRAYS. (U)

F/G 9/5

JUN 81 H D WEINSCHEL, A WATERMAN

F19628-78-C-0052


UNCLASSIFIED

PD-00990

AFGL-TR-81-0181

NL

1 of 1
AD A
04190



END
DATE
FILMED
10-81
DTIC

LEVEL

Yes
12

AFGL-TR-81-0181

DEVELOPMENT OF LARGE CYLINDRICAL STRIPLINE ANTENNA ARRAYS

Henry Weinschel
Al Waterman

Physical Science Laboratory
New Mexico State University
Box 3-PSL
Las Cruces, New Mexico 88003

DTIC
SELECTED
SEP 16 1981
S D H

24 June 1981

Final Report for Period February 1978 - January 1981

Approved for Public Release; distribution unlimited.

AIR FORCE GEOPHYSICS LABORATORY
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
Hanscom AFB, Massachusetts 01731

AD A104190

FILE COPY

81 9

14 007

Qualified requestors may obtain additional copies from the Defense Technical Information Center. All others should apply to the National Technical Information Service.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

19 REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AFGL TR-81-0181 ✓	2. GOVT ACCESSION NO. AD-A104190	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Development of Large Cylindrical Stripline Antenna Arrays.	5. TYPE OF REPORT & PERIOD COVERED Final Report. February 1978 - January 1981	
7. AUTHOR(s) Henry D. Weinschel Alexander Waterman	6. PERFORMING ORG. REPORT NUMBER PD00990	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Physical Science Laboratory Box 3-PSL New Mexico State Univ., Las Cruces, NM 88003	8. CONTRACT OR GRANT NUMBER(s) F19628-78-C-0052	
11. CONTROLLING OFFICE NAME AND ADDRESS Air Force Geophysics Laboratory Hanscom AFB, Massachusetts 01731 Contract Monitor: Raymond E. Wilton: I CR	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62101F 765901AJ	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	12. REPORT DATE June 1981	
	13. NUMBER OF PAGES 69	
	15. SECURITY CLASS. (of this report) Unclassified	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report) A - Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Previously produced related publications under this contract appear in Appendices D and E.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Stripline S-Band Electrically small antennas Antenna Cylindrical antenna arrays Corporate harness Array Encapsulated antennas		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The Physical Science Laboratory, New Mexico State University has conducted re- search and development studies of antenna designs under contract to the Air Force Geophysics Laboratory. The studies included the development stripline telemetry antenna arrays for large diameter missiles. Electrically small antennas at 550 MHz. Encapsulated S-Band antennas for small spherical satellites.		

DTIC
SELECTED
SEP 16 1981
H

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 55 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

TABLE OF CONTENTS

	<u>Page No.</u>
1.0 INTRODUCTION	1
2.0 ANTENNA DEVELOPMENT	1
2.1 Overview	1
2.2 The Model 55.205 Antenna	1
2.3 The Model 55.1405 Antenna	2
2.4 The Model 55.1505 Antenna	2
2.5 The Model 55.2005 Antenna	2
2.6 The Ten Inch Diameter Sphere	2
2.7 The Model 67.004 Antenna	3
3.0 STRIPLINE ANTENNA FABRICATION PROCEDURE	3
APPENDICES	
Appendix A List of Figures	A-1
Appendix B Antennas developed under contract F19628-78-C-0052 . .	B-1
Appendix C Antennas shipped during the report period	C-1
Appendix D Cumulative index to the quarterly reports	D-1
Appendix E Index of published scientific reports and papers . . .	E-1

Accession For	
NTIS GCR&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Dist: _____ or _____	
A	

1.0 INTRODUCTION

This is the final report for the contract period from February 1978 to January 1981.

The authors wish to thank J. E. Litton, R. Lanphere and other members of the Physical Science Laboratory (PSL), Antenna Technology Section, who contributed to the work reported herein.

2.0 ANTENNA DEVELOPMENT

2.1 Overview

During the report period several stripline antennas were developed for large diameter vehicles. All of the antennas have a number of features in common and in order to avoid repetitive descriptions those features will be outlined here and the differences will be discussed in the sections pertaining to the particular antenna models.

The unit element common to all arrays is a stripline slot antenna. The array is formed by feeding a number of slots with a stripline corporate harness which terminates at the center junction into an SMA coaxial launcher. The constraints on the harness lengths are that the sections between junctions be multiples of half wavelengths and that the slots be all fed in phase. The optimum design is the one that meets the above constraints and has a minimum harness width. The number of arrays used for a particular vehicle is determined by the vehicle diameter. If more than one array is used the arrays are fed by coaxial cable from a common junction.

2.2 The Model 55.205 Antenna

The Model 55.205 antenna was designed to be used with a 17.2 inch diameter vehicle. The antenna is illustrated in Figure 1 through 4. The total array consists of two eight element and one four element sub-arrays. The sub-arrays are fed through a printed circuit power divider and coaxial harness. The power divider was specially designed for this array and carries

the designation PSL PWD 205. The antenna is mounted in a recess of the vehicle and its surface is flush with the O.D. of the vehicle.

2.3 The Model 55.1405 Antenna

The Model 55.1405 antenna was designed for a 14 inch diameter vehicle. The antenna is illustrated in Figures 9 and 10. It consists of two subarrays of 8 elements each. The antenna surface is flush with the O.D. of the vehicle.

2.4 The Model 55.1505 Antenna

The Model 55.1505 antenna was designed for a 15 inch diameter. It is very similar to the model 55.1405 antenna described in Section 2.3, except that the spacing between unit elements was increased to accommodate the larger vehicle diameter. Since the spacing was only increased by 0.038λ at 2.25 GHz it had no significant effect on the radiation pattern.

2.5 The Model 55.2005 Antenna

The Model 55.2005 antenna was designed for a 20 inch diameter vehicle. The antenna is illustrated in Figure 21 and 22. Three arrays with eight elements each are required for the 20 inch diameter vehicle. It should be noted that in Figure 24 the two antenna arrays shown at either end of the vehicle extension are independent antennas that operate at different frequencies.

2.6 The Ten Inch Diameter Sphere

The two antennas were designed for the sphere. The antenna for the S-Band frequency is the Model 55.511 stripline slot array. The 550 MHz frequency antenna is a two element array of Model 67.006 printed circuit transmission line antennas. The antennas are mounted on a 9 inch diameter cylinder which becomes part of the sphere. The spherical surface is obtained by encapsulating the antennas in FPH foam. To obtain a smooth surface the foam is filled with latex paint and is then sprayed with plasite paint. The antennas are illustrated in Figures 27 through 30.

2.7 The Model 67.004 Antenna

The Model 67.004 antenna is very similar to the Model 67.006 antenna described in Section 2.6. It differs only in size since it was designed for a 409 MHz operating frequency.

3.0 STRIPLINE ANTENNA FABRICATION PROCEDURE

The procedure for fabrication is the same for all models. After the harness has been designed, the amberlith master is cut and is used for photo-etching the printed circuit board. The material used is K-6098 teflon-fiber-glass, .060 thick, copper-clad board manufactured by the 3M Company. The slots and the harness are photoetched on opposite sides of the same board which is then glued to a second board from which the copper has been removed on one side of the board. During the gluing process, which requires both heat and pressure, the antenna is also shaped to the approximate vehicle diameter. The array is then trimmed to the correct dimensions and the holes that constitute the cavity walls are drilled. The feed connector is attached and the antenna is copper plated. After the copper plating the antenna receives a preliminary performance test after which it is nickel plated. The final tests are performed with the antenna mounted on a mockup or flight vehicle extension for impedance and radiation pattern measurements.



Figure 1. Model 55,205 stripline antenna mounted on a 17.2 inch diameter vehicle extension.




Figure 1. Photograph of the document, not fully counted.




Figure 3. X-Ray view of the Model 55.205 Antenna.




Figure 4. X-Ray view of the Model 55.205.5 Antenna.




Figure 1. Impedance versus frequency chart for the Model 53.1 11 element array.




Figure 6. Coordinates for the Model 55.105 and 55.105.5 pattern Measurements. Range Request No. 2-50.

POLARIZATION

☒ GAIN REF -----
☒ E θ -----
☒ E ϕ -----
☒ R.C. -----
☒ L.C. -----
 OTHER AS NOTED
 UNDER REMARKS.

COORDINATE
REFERENCE

$\phi = \text{---}^\circ$ $\theta = \text{---}^\circ$

$\phi = \text{---}^\circ$
 $\theta = \text{---}^\circ$




FIG 7

FREQUENCY 2.25 GHz

ANTENNA Model 53.205

REMARKS The gain of the reference antenna is 16 dBi

CALIBRATION
RELATIVE
FIELD STRENGTH
2 dB/DIV

PSLN# 12145 B
 R.R. 2-50

POLARIZATION

--- GAIN REF. -----
 --- E θ -----
 --- E ϕ -----
 --- R.C. -----
 --- L.C. -----
 --- OTHER AS NOTED
 UNDER REMARKS.

COORDINATE
REFERENCE

$\phi = 0^\circ$ $\theta = 90^\circ$

$\phi = 90^\circ$
 $\theta = 90^\circ$




FIG 3

FREQUENCY 2.25 GHz

ANTENNA Model 35.205

REMARKS

CALIBRATION
 RELATIVE
 FIELD STRENGTH
 2 dB/DIV.

PSL No 121509
 R.R. 2450

MOD. 55.1405




Figure 10. X-Ray view of the Model 55.1405 Antenna.

•




Figure 12. Coordinates for the Model 55.1405 pattern measurements.
Range Request No. 2549.

POLARIZATION

- ☒ GAIN REF.
☒ E_θ
☐ E_ϕ
☐ R.C.
☐ L.C.
☐ OTHER AS NOTED
 UNDER REMARKS.

$\phi = \underline{\hspace{1cm}}^\circ$ $\theta = \underline{0}^\circ$

COORDINATE
REFERENCE

$\phi = \underline{0}^\circ$
 $\theta = \underline{90}^\circ$




FIG. 13

FREQUENCY 2250 MHz

ANTENNA Mod. 55.1405

REMARKS The gain of the reference Antenna is 16 dBi

CALIBRATION
RELATIVE
FIELD STRENGTH
2 dB/DIV.

PSL No 17003B

R.R. 2549

POLARIZATION

- ☐ GAIN REF. -----
☒ E θ -----
☐ E ϕ -----
☐ R.C. -----
☐ L.C. -----
☐ OTHER AS NOTED
 UNDER REMARKS.

$\phi = 0^\circ$ $\theta = 90^\circ$

COORDINATE
REFERENCE

$\phi = 90^\circ$
 $\theta = 90^\circ$




FIG. 14

FREQUENCY 2250 MHz

ANTENNA Mod. 55.1405

REMARKS

CALIBRATION
RELATIVE
FIELD STRENGTH
2 dB/DIV.

PSL No 17099B
R.R. 2549

MOD. 55.1505




Figure 16. X-Ray view of the Model 55.1505 Antenna.




Figure 17. Impedance versus frequency curve for the Model 55.1505.




Figure 18. Coordinates for the Model 55.1505 patterns.
Range Request No. 2550.

POLARIZATION

- ☒ GAIN REF. -----
☒ E θ -----
☐ E ϕ -----
☐ R.C. -----
☐ L.C. -----
☐ OTHER AS NOTED
 UNDER REMARKS.

$\phi =$ _____ $\theta =$ 0 °

COORDINATE
REFERENCE

$\phi =$ 0 °
 $\theta =$ 90 °




FIG. 19

FREQUENCY 2251.5 MHz

ANTENNA Model 55.1505, AD 913/914

REMARKS The gain of the reference antenna is 16 dBi

CALIBRATION
RELATIVE
FIELD STRENGTH
2 dB/DIV.

PSL No 16227B

RR 2550

POLARIZATION

- ☐ GAIN REF. -----
☒ E_θ -----
☐ E_ϕ -----
☐ R.C. -----
☐ L.C. -----
☐ OTHER AS NOTED
 UNDER REMARKS.

$\phi = 0^\circ$ $\theta = 90^\circ$

COORDINATE
REFERENCE

$\phi = 90^\circ$
 $\theta = 90^\circ$




FIG. 20

FREQUENCY 2251.5 MHz

ANTENNA Model 55.1505, AD 913/914

REMARKS

CALIBRATION
RELATIVE
FIELD STRENGTH
2 dB/DIV.

PSL No 162338

RR 2550




Figure 24. View of the Model 55, 2005 Subarray.




Figure 22. X-Ray view of the Model 55.2005 Antenna.




Figure 23. Impedance versus frequency curve for the Model 55.2005 array.




Figure 24. Coordinates for the Model 20.005 pattern measurement.
Range Request No. 2468.

POLARIZATION

- ☒ GAIN REF. -----
- ☒ $E\theta$ -----
- ☐ $E\phi$ -----
- ☐ R.C. -----
- ☐ L.C. -----
- ☐ OTHER AS NOTED UNDER REMARKS.

$\phi = \underline{\hspace{1cm}}^\circ$ $\theta = \underline{0}^\circ$ COORDINATE REFERENCE

$\phi = \underline{0}^\circ$
 $\theta = \underline{90}^\circ$




FIG. 25

FREQUENCY 2.25 GHz

ANTENNA Model 55.2005 SN AD482, AD483, AD484

REMARKS With Extension
Ref. Antenna SGH 1.7, gain is +10 dB

CALIBRATION
RELATIVE
FIELD STRENGTH
 $\underline{2}$ dB/DIV.

PSLN# 12179 B
R. R. 2468

POLARIZATION

- ☐ GAIN REF.
- ☒ $E\theta$
- ☐ $E\phi$
- ☐ R.C.
- ☐ L.C.
- ☐ OTHER AS NOTED
UNDER REMARKS.

$\phi = 0^\circ$ $\theta = 90^\circ$

COORDINATE
REFERENCE

$\phi = 90^\circ$
 $\theta = 90^\circ$




FIG. 26


FREQUENCY 2.25 GHz

ANTENNA Model 55.2005 SNAD482, AD483, AD484


REMARKS

CALIBRATION
RELATIVE
FIELD STRENGTH
2 dB/DIV.

PSLN^o 12185 B
R. R. 2468



THE UNIVERSITY OF CHICAGO







Fig. 1. Exploded view of the Model 67,000 Antenna.






Figure 31. Impedance versus frequency curve of the Model 73.51 Antenna.




Figure 32. Coordinates for the pattern measurements of the Model 55.311 and Model 67.006 antennas.

POLARIZATION

- ☒ GAIN REF. -----
☒ E θ -----
☐ E ϕ -----
☐ R.C. -----
☐ L.C. -----
☐ OTHER AS NOTED
 UNDER REMARKS.

$\phi = \text{---}^\circ$ $\theta = 0^\circ$ COORDINATE
 REFERENCE

$\phi = 0^\circ$
 $\theta = 90^\circ$




FIG. 33

FREQUENCY 2269.5 MHz

ANTENNA Model 55.511 (10.12" diameter sphere)

REMARKS The gain of the reference antenna (SGH 1.7) is 16 dBi.

CALIBRATION
 RELATIVE
 FIELD STRENGTH
 2 dB/DIV.

PSL No 17301B

RR 2581

POLARIZATION

- ☒ GAIN REF.
☒ E θ
☐ E ϕ
☐ R.C.
☐ L.C.
☐ OTHER AS NOTED
 UNDER REMARKS.

COORDINATE
REFERENCE

$\phi = 0^\circ$ $\theta = 90^\circ$

$\phi = 90^\circ$
 $\theta = 90^\circ$




FIG. 34

FREQUENCY 2269.5 MHz

ANTENNA Model 55.511 (10.12" diameter sphere)

REMARKS

CALIBRATION
RELATIVE
FIELD STRENGTH
2 dB/DIV.

PSLN^o 172996
RR 2551




Figure 35. Impedance versus frequency curve for the Model 27,000 antenna array.

POLARIZATION

☒ GAIN REF. -----
☐ E θ -----
☒ E ϕ -----
☐ R.C. -----
☐ L.C. -----
☐ OTHER AS NOTED
 UNDER REMARKS.

$\phi = 0^\circ$ $\theta = 90^\circ$

COORDINATE
REFERENCE

$\phi = 0^\circ$
 $\theta = 90^\circ$




FIG 36

FREQUENCY 550 MHz

ANTENNA Model 67.006, S.N. AD 929, AD 930

REMARKS The gain of the reference antenna (Stoddart dipole) is 2 dBi. Ten dB attenuation was added to the reference antenna. The -10 dBi reference circle is for the test antenna only.

CALIBRATION
RELATIVE
FIELD STRENGTH
1 dB/DIV.

PSL No 15207B

RR 2573

POLARIZATION

☐ GAIN REF. -----
☒ E θ -----
☐ E ϕ -----
☐ R.C. -----
☐ L.C. -----
 OTHER AS NOTED
 UNDER REMARKS.

$\phi = 0^\circ$ $\theta = 90^\circ$

COORDINATE
REFERENCE

$\phi = 0^\circ$
 $\theta = 90^\circ$




FIG. 37

FREQUENCY 550 MHz

ANTENNA Model 67.006, S.N. AD 929, AD 930

REMARKS

CALIBRATION
 RELATIVE
 FIELD STRENGTH
 1 dB/DIV.

PSL No 15210B

RR 2573


POLARIZATION

- ☒ GAIN REF.-----
☒ E θ -----
☒ E ϕ -----
☐ R.C.-----
☐ L.C.-----
☐ OTHER AS NOTED
 UNDER REMARKS.

$\phi =$ _____ $\theta =$ 0°

COORDINATE
REFERENCE

$\phi =$ 0°
 $\theta =$ 90°



CALIBRATION
 RELATIVE
 FIELD STRENGTH
 2 dB/DIV

FIG. 38

FREQUENCY 550 MHz

ANTENNA Model 67.006. Two element array fed 180° out of phase.

REMARKS The gain of the reference antenna (Stoddart dipole) is +2 dBi. RR 2576
 Ten dB attenuation was placed in line with the reference
 antenna. The Model 67.006 radiates through a 1 x 3/8 inch
 slot in the metallic nose cone.

PSL No 17429B

POLARIZATION

☒ GAIN REF. -----
☒ E θ -----
☒ E ϕ -----
 --- R.C. -----
 --- L.C. -----
 --- OTHER AS NOTED
 UNDER REMARKS.

$\phi = 0^\circ$ $\theta = 90^\circ$ COORDINATE
 REFERENCE

$\phi = 90^\circ$
 $\theta = 30^\circ$




FIG. 39

FREQUENCY 550 MHz


ANTENNA Model 67.006. Two element array fed 180° out of phase.

REMARKS The gain of the reference antenna (Stoddart dipole) is +2 dBi. Ten dB attenuation was placed in line with the reference antenna. The Model 67.006 radiates through a $4 \times 3/8$ inch slot in the metallic nose cone.

CALIBRATION
 RELATIVE
 FIELD STRENGTH
 2 dB/DIV.

PSL No 17428B

RR 2576



Model 67.004 Antenna.




Figure 41. Impedance versus frequency curve for the Model 67.004 antenna array.




Figure 42. Coordinates for the Model 65,004 Stripline 409 MHz. Antenna. Range Request 2421.

POLARIZATION

☒ GAIN REF. -----
☒ E_θ -----
☒ E_ϕ -----
☐ R.C. -----
☐ L.C. -----
 OTHER AS NOTED
 UNDER REMARKS.

$\phi = \underline{\hspace{1cm}}^\circ$ $\theta = \underline{0}^\circ$ COORDINATE
 REFERENCE

$\phi = \underline{0}^\circ$
 $\theta = \underline{90}^\circ$




Figure 43

FREQUENCY 430 MHz

ANTENNA Model 67.004

REMARKS Gain of Reference Dipole is +2dBi

CALIBRATION
 RELATIVE
 FIELD STRENGTH
2 dB/DIV.

PSLN^o 12891 B

POLARIZATION

- ☐ GAIN REF. -----
☒ E θ -----
☒ E ϕ -----
☐ R.C. -----
☐ L.C. -----
☐ OTHER AS NOTED
 UNDER REMARKS.

$\phi = 0^\circ$ $\theta = 90^\circ$

COORDINATE
REFERENCE

$\phi = 90^\circ$
 $\theta = 90^\circ$




Figure 44

FREQUENCY 430 MHz

ANTENNA Model 67.004

REMARKS Reference PSI 128918

CALIBRATION
 RELATIVE
 FIELD STRENGTH
 2 dB/DIV.

PSLN^o 12896 B

Appendix A

LIST OF FIGURES

<u>Figure No.</u>		<u>Page No.</u>
1	Model 55.205 Stripline Antenna mounted on a 17.2 inch Diameter Vehicle Extension. (128-3-31)	4
2	Detail showing the Model 55.205 antenna partially mounted (128-3-40)	5
3	X-Ray view of the Model 55.205 Antenna	6
4	X-Ray view of the Model 55.205.5 Antenna	7
5	Impedance versus Frequency Chart for the Model 55.205 20 Element Array	8
6	Coordinates for the Model 55.205 and 55.205.5 pattern measurements. Range Request No. 2450	9
7	Antenna Model 55.205, Pattern No. 12145B, RR2450	10
8	Antenna Model 55.205, Pattern No. 12150B, RR2450	11
9	View of the Model 55.1405 Subarray (13165)	12
10	X-Ray view of the Model 55.1405 Antenna	13
11	Impedance versus frequency curve for the Model 55.1405 Antenna	14
12	Coordinates for the Model 55.1405 Pattern Measurements. Range Request No. 2549	15
13	Antenna Model 55.1405, Pattern No. 17003B, RR 2549	16
14	Antenna Model 55.1405, Pattern No. 17009B, RR 2549	17
15	Eight Element Subarray of the Model 55.1505 Antenna (13166).	18
16	X-Ray view of the Model 55.1505 Antenna	19
17	Impedance versus frequency curve for the Model 55.1505 array	20
18	Coordinates for the Model 55.1505 Patterns. Range Request No. 2550	21
19	Antenna Model 55.1505. AD 913/914, Pattern No. 16227B, RR 2550	22
20	Antenna Model 55.1505, AD 913/914, Pattern No. 16227B, RR 2550	23

LIST OF FIGURES (cont.)

<u>Figure No.</u>		<u>Page No.</u>
21	View of the Model 55.2005 Subarray (13172)	24
22	X-Ray view of the Model 55.2005 Antenna	25
23	Impedance versus frequency curve for the Model 55.2005 array	26
24	Coordinates for the Model 20.005 pattern measurement. Range Request No. 2468	27
25	Antenna Model 55.2005 SN AD482, AD483, AD484, Pattern No. 12179B, RR 2468	28
26	Antenna Model 55.2005 SNAD482, AD483, AD484, Pattern No. 12185B, 2468	29
27	View of the 10.2 Diameter inch Sphere (13159).	30
28	View of the cylindrical section of the 10.2 in Diameter Sphere before encapsulation, with the Model 55.511 and Model 67.006 Antennas mounted (13064).	31
29	Exploded view of the Model 67.006 Antenna (12931)	32
30	View of the Model 67.006 Antenna (12993)	33
31	Impedance versus frequency curve of the Model 55.511 Antenna	34
32	Coordinates for the pattern measurements of the Model 55.511 and Model 67.006 antennas	35
33	Antenna Model 55.511 (10.12" diameter sphere), Pattern No. 17301B, RR 2581	36
34	Antenna Model 55.511 (10.12" diameter sphere), Pattern No. 17299B, RR 2581	37
35	Impedance versus frequency curve for the Model 67.006 Antenna array	38
36	Antenna Model 67.006, S.N. AD929, AD 930, Pattern No. 15207B, RR 2573	39
37	Antenna Model 67.006, S.N. AD929, AD930, Pattern No. 15210B, RR 2573	40
38.	Antenna Model 67.006. Two element array fed 180° out of phase, Pattern No. 17428B, RR 2576	41

LIST OF FIGURES (con.t)

<u>Figure No.</u>		<u>Page No.</u>
39.	Antenna Model 67.006. Two element array fed 180° out of phase, Pattern No. 17428B, RR 2546	42
40.	Exploded view of the Model 67.004 Antenna (12742)	43
41.	Impedance versus frequency curve for the Model 67.004 Antenna array	44
42.	Coordinates for the Model 67.004 Stripline 409 MHz Antenna, Range Request 2421	45
43.	Antenna Model 67.004, Pattern No. 12891B	46
44.	Antenna Model 67.004, Pattern No. 12896B,	47

Appendix B

MODEL	ELEM PER SUBA.	NUMBER OF SUBA.	VEHICLE DIA. (INCHES)	MOUNTING	REFERENCE QUARTERLY REPORT NO.	ANTENNA SERIAL NO.	RANGE REQUEST NO.	FIRST VEHICLE	REMARKS
55.205	8	2½	17.2	F	4			Second Vehicle A18.805	
55.1405	8	2	14	F	8, 9, 10 11	AD909 AD910	2549	A13.030 AURORAL E TLM	
55.1505	8	2	15	F	2, 3, 4, 5 6, 9, 10, 11	AD913 AD914	2550	A31.701 ASTROBEE F	
55.1705	8	2	17.25	F	7, 8				2 arrays on the extension
55.2005	8	3	20.75	F	4, 5, 6	AD482 - AD487	2583 2468	A44.651-1 ZIP	Quadraloop 430 MHz
67.0004					7, 8				Quadraloop 550 MHz
67.0006					9, 10, 11				

F - flush, I - Internal

ANTENNAS DEVELOPED UNDER CONTRACT F19628-78-C-0052

Appendix C

ANTENNAS SHIPPED

<u>Model</u>	<u>Vehicle</u>
2.007	A44.6S1-1 ZIP
2.042	FLT #I830.09-1A
2.042	A10.82-1 A10.802-2
2.042	A30.072
2.042	242 MHz
4.003	Aries
4.003	A04.606-1
4.003	TEM-2B A24.609-3
4.003	A24.651-1
4.003	A24.7S2-2
4.003	44.28" Diameter
6.010	A04.606-1
6.017	MSMP/SPICE Drop Test
6.017	A24.7S2-2 FRISSE
6.017	44.28" Diameter
6.060	FLT #I830.09-1A
6.060	FLT #A07.712-2
6.060	FLT #A10.802-1 #A10.802-2
6.060	A30.072
6.060	A10.901-1 A10.901-2
6.060	A12.9A2
6.060	A11.074
6.060	A30.073

ANTENNAS SHIPPED

<u>Model</u>	<u>Vehicle</u>
6.060	A13.020
6.060	A13.030
6.060	A13.031
6.060	A10.903
7.015	A44.6S1-1 ZIP
7.015	A24.651-1
7.015	A24.7S2-2
7.015	44.28" Diameter
7.016	A08.708-1 A08.708-2
7.016	A31.702
7.016	A08.705-2
7.016	A18.805
23.020	A08.708-1 A08.708-2
23.020	FLT #1830.09-1A
23.020	FLT #A07.712-2
23.020	FLT #A10.802-1 #A10.802-2
23.020	A12.9A2
23.020	A18.805
23.020	A11.074
23.020	A30.072
23.020	550 MHz
23.020	A30.073
23.020	A13.020
23.020	A13.030

ANTENNAS SHIPPED

<u>Model</u>	<u>Vehicle</u>
23.020	A13.031
23.020	A10.903
23.021	A44.6S1-1 ZIP
39.003	Aries X-Band
39.003	TEM-2B A24.609-3
55.205	A31.702
55.205	A18.805
55.205	A30.072
55.205	A30.703
55.380	A24.752-1
55.380	IRBS
55.380	A24.651-1 ZIP-1
55.380	A24.7S2-2 FIRSSE
55.385	ARIES
55.385	TEM-2B A24.609-3
55.385T	
55.455	FLT Housings
55.455	A10.802-1
	A10.802-2
55.455	RADC-5
55.455	RADC-6
	RADC-7
55.505	A10.903
55.510	AC15
55.510C	10" Sphere

ANTENNAS SHIPPED

<u>Model</u>	<u>Vehicle</u>
55.510C	10" Sphere
55.511	A08.706-2, 10" Sphere
55.511	10" Sphere
55.511	10" Sphere
55.511	AC-15
55.511	AC-14 A10.903, 2269.5 MHz
55.805	A08.708-1 A08.708-2
55.805	A08.705-2
55.805	A11.074
55.805	A10.901-1 A10.901-2
55.805	A13.020
55.1405	A13.030
55.1405	A13.031
55.2005	A44.6S1-1 ZIP
67.006	AC14, A10.903, 10" Sphere, 550 MHz

Appendix D

CUMULATIVE INDEX FOR THE QUARTERLY PROGRESS REPORTS

QUARTERLY

Report No.

- 1 Mod. 55.380 for SPICE and IRBS
 Unit radiator investigation
 Printed circuit dipole investigation

- 2 Mod. 55.380 for IRBS
 Models 55.205 and 55.605
 Model 38.031 for the Finch. dia. sphere
 Layout for a 10 inch dia. sphere
 Unit radiator investigation
 Printed circuit dipole investigation.

- 3 Models 55.205 and 55.605
 Models 55.455 and 55.511
 Unit radiator investigation
 MSMP-2 Measurements
 Printed circuit dipole investigation

- 4 Model 55.205
 Model 55.1505
 Model 55.2005
 Unit radiator investigation

- 5 Model 55.205
 Model 55.2005
 Model 55.455
 Model 55.1505
 MSMP/SPICE Drop Test

- 6 Model 55.2005
 Model 55.1505
 Model 55.205
 Unit radiator investigation

- 7 Model 55.1705
 Model 67.005
 Aries X-Band Tracker
 Unit radiator investigation
 Printed Circuit Antenna Workshop
- 8 Model 55.1705
 Model 55.1405
 Model 67.004
 Model PD380 power dividers
 MSMP Program (TEM-2B)
 Unit radiator investigation
- 9 Model 55.1405
 Model 55.1505
 Model 67.006
 MSMP,TECOM Model 106002
 MSMP-2
- 10 Model 55.1405
 Model 55.1505
 Model 67.006
- 11 Model 55.1405
 Model 55.1505
 Model 67.006
 Vehicle No. A31.701
 Vehicle No. 10.093
 Vehicle No. A13.030
 Vehicle No. A13.031
- 12 Aries Vehicle
 Vehicle No A10.903
 Sphere AC-14

Appendix E

PUBLISHED SCIENTIFIC REPORTS AND PAPERS

1. Wilton, R. E. and A. Waterman, "Telemetry Antennas for Large Diameter Sounding Rockets," AFGL-TR-79-0205, Instrumentation Papers #280 United States Air Force, Hanscom AFB, Massachusetts, September 4, 1979.
2. Waterman, A., "Stripline Antenna Development," Proceedings of Workshop on Printed Circuit Antenna Technology, October 17-19, 1979, Physical Science Laboratory, NMSU, Las Cruces, New Mexico.

DATE
ILMED
-8