

AD-A104 906

HYDROLOGIC ENGINEERING CENTER DAVIS CA
A METHOD FOR ANALYZING EFFECTS OF DAM FAILURES IN DESIGN STUDIE--ETC(U)
AUG 72 W A THOMAS
HEC-TP-39

F/G 13/13

UNCLASSIFIED

NL

1 OF 1
41A
128-100

END
DATE
PRINTED
10-81
DTIC

AD A104906

DTIC FILE COPY

13


AUGUST 1972

TECHNICAL PAPER NO. 39

A METHOD FOR ANALYZING EFFECTS OF DAM FAILURES IN DESIGN STUDIES

by

WILLIAM A. THOMAS



CORPS OF ENGINEERS
U. S. ARMY

DTIC
ELECTE
S OCT 2 1981 D
D

THE HYDROLOGIC ENGINEERING CENTER

- research
- training
- application

DISTRIBUTION STATEMENT 1
Approved for public release;
Distribution Unlimited

Papers in this series have resulted from technical activities of the Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution within the Corps of Engineers.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM	
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER	
Technical Paper No. 39	AD-A204906		
4. TITLE (and Subtitle)		5. TYPE OF REPORT & PERIOD COVERED	
A METHOD FOR ANALYZING EFFECTS OF DAM FAILURES IN DESIGN STUDIES			
7. AUTHOR(s)		8. CONTRACT OR GRANT NUMBER(s)	
William A. Thomas			
9. PERFORMING ORGANIZATION NAME AND ADDRESS		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
U.S. Army Corps of Engineers The Hydrologic Engineering Center 609 Second Street, Davis, California 95616			
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE	
		August 1972 (12)	
		13. NUMBER OF PAGES	
		27	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report)	
(14) HEZ-TP-39		Unclassified	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
16. DISTRIBUTION STATEMENT (of this Report)			
Distribution of this publication is unlimited.			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
Presented at the ASCE Hydraulics Division Specialty Conference, Cornell University, August 1972			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)			
Dam design, Dam Failure, Flood waves, Model studies, Design flood, Flood routing, Reservoir capacity, Wave energy, Energy loss, Hydrostatic pressure, Unsteady flow, Kinetic energy, Gradually varied flow, calculations, Evaluation, Hydraulic pressure, Army Hydrologic Center, Flood Hydrographs, Pressure distribution, Impact loads.			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)			
<p>In the planning and design of dams and embankments for large multiple-purpose projects, it is usually necessary to evaluate the effect of potentially disastrous extreme events to insure that the proposed developments do not produce an unnecessary increase in the disaster potential. One such case which is being encountered more frequently now involves the the design of dams and embankments for projects located downstream from an existing dam. If the existing structure is relatively old or if there is</p> <p>(Continued)</p>			

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

407989

81 10 2 020

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

20 (Continued)

reason to believe that the probability of failure is relatively great, it may be desirable to consider the effect of a potential failure during the design of the downstream structure.

In the design studies for a dam to be located downstream from an existing dam, the effects of failure of the upstream structure have been calculated. The flood wave which would result from failure of the upstream dam has been calculated and routed through the reservoir that would be formed by the downstream structure. The analysis utilized the unsteady flow equations to evaluate the effect of the flood wave under three different conditions of impoundment in the downstream reservoir at the time of failure. The structure that was assumed to fail was treated as a finite discontinuity in the water surface elevation at an internal point in the computation net rather than as a boundary condition. The design, verification and use of the digital simulation model for the analysis are presented.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

A METHOD FOR ANALYZING EFFECTS OF DAM FAILURES

IN DESIGN STUDIES⁽¹⁾

by William A. Thomas⁽²⁾

ABSTRACT

In the planning and design of dams and embankments for large multiple-purpose projects, it is usually necessary to evaluate the effect of potentially disastrous extreme events to insure that the proposed developments do not produce an unnecessary increase in the disaster potential. One such case which is being encountered more frequently now involves the design of dams and embankments for projects located downstream from an existing dam. If the existing structure is relatively old or if there is reason to believe that the probability of failure is relatively great, it may be desirable to consider the effect of a potential failure during the design of the downstream structure.

In the design studies for a dam to be located downstream from an existing dam, the effects of failure of the upstream structure have been calculated. The flood wave which would result from failure of the upstream dam has been calculated and routed through the reservoir that would be formed by the downstream structure. The analysis utilized the

(1) For presentation at the ASCE Hydraulics Division Specialty Conference, Cornell University, August 1972

(2) Research Hydraulic Engineer, Research Branch, The Hydrologic Engineering Center, U. S. Army Corps of Engineers, Davis, California

unsteady flow equations to evaluate the effect of the flood wave under three different conditions of impoundment in the downstream reservoir at the time of failure. The structure that was assumed to fail was treated as a finite discontinuity in the water surface elevation at an internal point in the computation net rather than as a boundary condition. The design, verification and use of the digital simulation model for the analysis are presented.

A METHOD FOR ANALYZING EFFECTS OF DAM FAILURES
IN DESIGN STUDIES⁽¹⁾

by William A. Thomas⁽²⁾

In recent years, the failures of several small dams have prompted design, construction and regulatory agencies working in the field of water resources development to consider and analyze the effects of flood waves that could result from failure of existing or proposed dams. These flood waves, referred to herein as dam-break floods, are of particular importance because of the large momentum forces associated with them. Effects, such as the extent and duration of inundation in the flood plain below a breached dam, the rate of travel of the flood wave, the temporal and spatial variations in flood wave attenuation, the forces exerted by the flood wave on structures within the flood plain, and the environmental impact of the flood wave are examples of the types of effects that are important. In addition, each individual situation will introduce special considerations into the analysis.

The study which is discussed in this paper was conducted to determine how much force a dam-break flood wave would exert on a downstream dam. There are three major aspects to the problem: determining the discharge hydrograph when a dam is assumed to fail; routing that discharge downstream to the point of interest; and applying the resulting forces to the structure in question. The first two aspects are treated in this paper. The method that was utilized to calculate and route the dam-break

(1) For presentation at the ASCE Hydraulics Division Specialty Conference, Cornell University, August 1972.

(2) Research Hydraulic Engineer, Research Branch, The Hydrologic Engineering Center, U.S. Army Corps of Engineers, Davis, California.

flood waves in this study could also be used to analyze the dam-break flood wave in terms of the other effects mentioned above. However, special situations developed which required simplification of the problem in order to use this method, and these limitations are discussed also.

Interest in this analysis was stimulated by a difference in the design criteria used for two projects. The projects are owned by different agencies, and the criteria used to develop extreme hydrologic events to establish spillway requirements and the height of the dam for the proposed downstream structure produced a flood that would completely overtop the existing earthfill dam. Therefore, assumptions regarding failure had to be considered to adequately define loading conditions for the proposed dam. (At the present time, both the existing earth dam and its operating policy have been modified to reflect the same criteria being used for the proposed dam.)

Reservoir outlines of both the existing and proposed reservoirs are shown in figure 1.

Figure 2 shows a profile of the streambed from the site of the proposed Martins Fork Dam up Martins Fork of the Cumberland River to the confluence with Cranks Creek and thence up Cranks Creek. Pertinent elevations are shown for each dam.

Also, figure 2 illustrates a primary point of concern in the study. Cranks Creek Dam stands some 85 feet higher than the proposed Martins

Fork structure and is located only 3.9 miles upstream. How much of this energy head would be dissipated as the flood wave traveled to Martins Fork Dam? Saint Venant, Schoklitsch, Dressler and others have shown by theory and experiment that the energy producing a dam-break flood wave is the depth of water at the instant of failure, provided the downstream channel is dry. Their theoretical expression, in which energy losses are neglected, shows the peak discharge at a fully breached dam to be

$$Q_{\max} = \frac{8}{27} W_d \sqrt{g} Y_o^{3/2} \quad (1)$$

where:

- Q_{\max} = peak discharge of the dam-break flood hydrograph
- W_d = initial water surface width at the dam
- Y_o = initial reservoir depth at the dam
- g = acceleration of gravity

The value of peak discharge calculated with equation 1 agrees reasonably well with experimental data obtained from tests conducted by the U.S. Army Waterways Experiment Station (reference 6). Therefore, the fact that immediately after a failure the reservoir depth at the dam decreases rapidly to half its original value does not indicate a corresponding loss of total energy head at that location. Rather, total energy has been redistributed to include a large inertia component and a kinetic energy component, in addition to the pressure plus potential energy component; and the sum of these components yields the reservoir

elevation just prior to failure. The important energy losses occur as the flood wave moves downstream and include friction losses, bend losses, expansion and contraction losses and others.

In addition to energy considerations, the volume of water which is available in Cranks Creek Reservoir to sustain the flood wave must be considered. Figure 3 shows the capacity of each reservoir as a function of its elevation. The increase in elevation of Martins Fork Reservoir due to storing the volume of water in the flood wave could possibly be greater than the energy consideration. This would depend on rate of energy dissipation and the rate of outflow from Martins Fork. It is also possible that the maximum force could result from some combination of the energy and volume considerations. Therefore, a time history of the flood wave motion is required to adequately analyze the problem.

Methods which are commonly used in flood routing, such as the modified Puls, Muskingum, Tatum, and straddle-stagger, permit direct consideration of volumes only. Indirectly, energy considerations are inferred by calibrating these methods to some experienced event. Such methods are inadequate for routing the dam-break flood--at least in the early stages, because energy plays such a dominant role in the movement. Therefore, one must resort to a solution of the basic equations of unsteady flow to consider both continuity and momentum.

A number of solution techniques have been advanced over the past few years, but the method presented by Garrison, Granju and Price (reference 1) has been used in this study. It is, however, based on a solution of the gradually varied unsteady-flow equations through the use of an explicit finite difference scheme developed by Stoker. Terzidis and Strelkoff (reference 5), in studies involving a hydraulic bore, demonstrated that such a solution technique calculated the wave height correctly, but failed to maintain continuity in that an excess water volume was developed for the wave. The problem was corrected by accounting for energy losses resulting from flow conditions in the wave front. On the other hand, Martin and De Fazio (reference 3) studied cases of rapidly varied flow involving an undular type of flood wave movement rather than a bore type, and they found the solution developed by Stoker to be adequate for their design studies. Because of the depth of water downstream from Cranks Creek Dam, the flood movement in this study was expected to be more like the undular wave than a hydraulic bore. Therefore, Stoker's solution technique was considered satisfactory. However, continuity checks were made to insure a reasonable volume was being maintained during the routing.

Numerous assumptions were necessary in order to route the dam-break flood. Generally, they can be divided into two categories: (1) those basic to establishing the problem and method for solution, and

(2) those necessary in assigning values used in the actual calculations.

In most cases, judgment was guided by the effort to produce the most critical situation for Martins Fork Dam. The assumptions are listed below:

- a. The failure of Cranks Creek Dam is instantaneous and complete.
- b. Pressure distribution is hydrostatic at each cross section.
- c. Velocity distribution is uniform over that portion of the cross section conveying flow.
- d. Steady flow n-values are applicable.
- e. An existing railroad crossing just downstream from Cranks Creek Dam is washed out upon impact of the flood wave and the resulting energy loss is negligible.
- f. Energy lost at the junction of Cranks Creek and Martins Fork mainstem is negligible.
- g. The effect of transient waves on energy dissipation, due to sinuosity of the channel, can be ignored.
- h. Changes in boundary geometry due to scour and fill can be neglected.
- i. The model is verified when reservoir volumes and the spillway design flood outflow hydrograph matches data obtained from conventional routing techniques in earlier studies.

j. The overflow rating curve for Martins Fork Dam is not affected by tailwater.

Pertinent data for both projects are shown in table 1.

Table 1. Pertinent Data for Both Projects

<u>Item</u>	<u>Cranks Creek Dam, Existing</u>	<u>Proposed Martins Fork Dam</u>
<u>Location by Stream Name</u>	<u>Cranks Creek</u>	<u>Martins Fork of the Cumberland River</u>
Miles above mouth	2.4	15.6
<u>Drainage Area (sq. mi.)</u>	24.8	55.7
<u>Type of Dam</u>	<u>Earth Fill</u>	<u>Concrete</u>
Top of dam elevation (feet)	1443	1360
Streambed elevation (approx. feet)	1323	1263
Length of dam (feet)	640	504
<u>Spillway</u>		
Crest elevation (feet)	1430	1341
Crest length (feet)	200	200
Design flood, peak-discharge (cfs)	25100	57000
Design flood, peak-elevation (feet)	1441.5	1358.2
<u>Reservoir Capacity</u>		
Normal summer operating pool, elevation (feet)	1420	1310
capacity (acre-feet)	6400	6800
Capacity at spillway crest, elevation (acre-feet)	9000	21000
Top of dam elevation (acre-feet)	14000	33300
Distance between the two projects (miles)		3.9

Reservoir Elevations at Failure

Three cases were selected for study. These differed only in elevation of the reservoirs as shown below:

Reservoir Conditions at Failure

<u>Condition No.</u>	<u>Cranks Creek Res. Elev.</u>	<u>Martins Fork Res. Elev.</u>	<u>Net Head at Cranks Creek Dam</u>	<u>Remarks</u>
I	1441.5	1358.3	83.2	SDF crest (1)
II	1419.5	1309.5	110.0	Typical summer pool
III	1430.0	1341.0	89.0	Spillway crest

(1) Spillway Design Flood (SDF)

Condition I was selected because it represented the largest total energy available at Cranks Creek Dam. However, it did not produce the largest head differential possible at Cranks Creek Dam, nor did it produce the most severe condition for impact when the flood wave reached Martins Fork Dam. Therefore, Conditions II and III were selected. Condition II corresponds to a typical summer operating policy for the reservoirs and represents maximum energy head for producing the flood wave at Cranks Creek Dam; whereas Condition III represents an extreme condition for developing impact loads at Martins Fork Dam.

The study was divided into several major steps, each of which is discussed in detail in the following paragraphs.

Establishing the Geometric Model

The proposed Martins Fork Dam formed the downstream boundary of

the model, and the upstream end of Cranks Creek Reservoir formed the upstream boundary. Cross sections were located to define total volume in each reservoir, and, where they extended up tributary arms, artificial flow boundaries were imposed to separate that portion of the section which conveys flow from that portion which only stores water. From these sections geometric data were calculated for nodal points spaced 1/2 half mile apart, thus forming the basic geometric model for the unsteady flow computer program.

Determining Hydraulic Roughness

Since friction loss was such an important consideration in this study, the selection of realistic n-values for Manning's equation was of primary importance. Values of 0.05 for the channel and 0.10 for the overbanks had been used in other studies by engineers familiar with the streams in this area. These values were, however, based on natural conditions. Values of 0.03 and 0.01 had been used for reservoir conditions. Since the flow velocity associated with the dam-break flood was expected to be more nearly that for natural conditions than that which would be expected with the reservoir impounded, the natural conditions n-values were used. These were adjusted into composite values for the entire cross section and to account for the sinuosity of the valley, which resulted in a composite n-value of .07 for each cross section. In Cranks Creek this value was reduced to .05, since the flow conditions would tend toward preimpoundment conditions as the water drained out.

Verifying the Digital Model

Before routing the dam-break flood, the Spillway Design Flood for Martins Fork was routed through both reservoirs. The results compared favorably with those from earlier studies in which conventional routing techniques were used. Also, water surface profiles were calculated for the peak discharge of the spillway design flood. These profiles were compared with profiles calculated using a steady flow, backwater computer program. The comparisons from these tests were considered sufficient to verify the model for the proposed study.

Establishing Boundary Conditions and Initial Conditions

A discharge rating curve was used for the downstream boundary condition at Martins Fork Dam. It included flow over the top of the dam, as well as through the spillway.

The Spillway Design Flood discharge hydrograph was used at the upstream boundary in Condition I. In the other two cases, inflow was assumed to be zero.

Local area inflow entered the model at the confluence of Cranks Creek and Martins Fork mainstem. No other local inflow points were established.

For all three conditions of failure, Cranks Creek Dam was considered as a finite discontinuity in the initial water surface profile. Using this approach, as opposed to treating it as an end boundary, the increase in tailwater elevation accompanying the dam-break flood wave could

be included in calculations for the discharge hydrograph at the dam axis.

Routing the Dam-Break Flood for Condition I

The results of routing the dam-break flood for Condition I are shown in figure 4 in the form of discharge and elevation hydrographs at Cranks Creek Dam axis and at Martins Fork Dam axis.

The impact of the flood wave on Martins Fork Dam resulted in a 28-foot increase in water surface elevation above the SDF peak, as the inertia and kinetic energy components were transformed back into a pressure energy. The peak discharge at Martins Fork was 190,000 cfs. Four minutes were required for the wave to travel from Cranks Creek Dam to Martins Fork Dam.

Two alternative methods for computing travel time, a wave celerity computation based on initial depth and a forward characteristic computation based on celerity plus flow velocity, produced travel times of 6 minutes and 5.5 minutes, respectively. The travel time calculated by the routing method used in the study appears to be reasonable, based upon comparison with these values.

The peak outflow from Cranks Creek Reservoir, curve one of figure 4, is 1,400,000 cfs. The value obtained by applying equation 1, 1,200,000 cfs, compares favorably with this peak outflow.

The peak discharge is important because it influences the rate of energy dissipation due to friction. This point was illustrated in the study by first including all storage volume on Martins Fork mainstem, upstream from Cranks Creek, then recalculating the routing with that

volume excluded. The peak energy at Martins Fork Dam was 4 feet higher in the first case because the additional storage volume reduced the peak discharge and, consequently, the rate friction loss.

The results of a sensitivity study in which the composite n-values were varied is shown in figure 5. For Condition I failure, n-values of .05, .07 and .10 were assigned and the flood wave calculated and routed to Martins Fork Dam. The results show that total energy remaining in the flood wave when it reaches Martins Fork Dam is highly dependent upon the hydraulic roughness value. The determination of these values should, therefore, receive a great deal of consideration in planning a routing study.

Routing the Dam-Break Flood for Condition II

The flood that would result from a failure when both reservoirs are at normal, summer operating pools (Condition II) is represented in figure 6. Under this condition, the entire contents of Cranks Creek Reservoir would be stored in Martins Fork Reservoir and maximum pool elevation would be well below the spillway crest, even including the impact of the flood wave.

This condition was used to test for continuity by calculating the volume under the hydrograph at Cranks Creek Dam and comparing the result with the elevation-storage curve of figure 3. The comparison indicated that the volumes were within 15 percent of one another, with the routing method tending to produce an excess of water. This conformed with the

experience reported by Terzidas and Strelkoff. The discrepancy in continuity was not considered to be unreasonable when evaluated with respect to the uncertainties associated with other aspects of the study.

Routing the Dam-Break Flood for Condition III

The results of routing Condition III are shown in figure 7. The full impact loading of the flood wave is reflected in the 24-foot increase in water surface elevation at Martins Fork Dam. The reservoir outflow which was zero initially reached a maximum of 100,000 cfs under this condition.

The results from the three conditions are shown in table 2.

Table 2. Comparison of Results

Condition	Peak Outflow in cfs		Total Energy Head at Martins Fork Dam	
	<u>Cranks Creek</u>	<u>Martins Fork</u>	<u>Prior to Impact of Flood Wave</u>	<u>Peak</u>
I	1,400,000	190,000	1358	1386
II	1,100,000	0	1310	1332
III	1,200,000	100,000	1341	1364

Several special situations which developed during the analysis are discussed in the following paragraphs.

The Junction Problem

In planning for the study, a technique was proposed whereby flows at the junction of Cranks Creek and Martins Fork mainstem would be

determined by successive approximations using two routing models. Briefly, this technique was to be the following: The primary model would extend through Cranks Creek Reservoir to Martins Fork Dam. The secondary model would extend from the upstream end of the Martins Fork arm down to the confluence with Cranks Creek. The first routing would be made with the primary model, and would assume zero inflow from the Martins Fork mainstem. The second step would utilize elevations calculated for the junction in the first step and route down the Martins Fork arm of the reservoir to determine the discharge entering the junction. Step 1 would be repeated. This alternating between the primary and secondary routing models would continue until the same junction elevations and discharges resulted in two successive steps. Such "convergence" would indicate that a solution had been reached.

This technique proved to be unsuccessful. The changes in discharge and elevation were so rapid that convergence of results from the two models could not be achieved. Fortunately, the peak of the flood wave required only a minute to travel from the confluence to the dam. During this time, the wave would travel only a short distance up Martins Fork mainstem. Therefore, that wave travel distance could be neglected and the spillway design flood hydrograph could be entered as local inflow.

Critical Depth Controls

A sudden failure of a dam results in a negative wave which travels

up the reservoir while the positive wave is being produced downstream from the dam. The geometry of Cranks Creek Reservoir caused a critical depth control to form near river mile 4 which restricted this negative wave from developing upstream from that point during Condition II. Fortunately, the amount of storage capacity upstream from mile 4 was small and could be neglected because the computer program did not perform satisfactorily for supercritical flow. Therefore, the upstream boundary was shifted down to mile 4 in the routing model and the calculations continued with no serious error resulting from this simplification.

Dry Channel at the Upstream Boundary

In Conditions I and III, there was sufficient initial depth so the negative wave could pass upstream from mile 4 without developing transitions between supercritical and subcritical flow. However, as strong negative waves would approach the upstream boundary, the water depth would temporarily go to zero which, again, caused the computer program to malfunction. Attempts to eliminate this problem by specifying a minimum stage at the upstream boundary caused other instabilities even though 1-second computation intervals were employed. Therefore, routings were terminated. In all cases, the peak flow had passed Martins Fork Dam before routings terminated.

Initial Depth in the Channel

In all three cases studied, there was a substantial depth of water downstream from Cranks Creek Dam. Otherwise, a hydraulic bore would

have formed and a different formulation of the routing equations would have been required. (This depth contributed to movement of the flood wave, resulting in larger wave velocities than would have been experienced in a dry channel.)

Any one of these special conditions could render a study impossible with this model if its influence predominated. It is believed that in this study they were treated in a conservative manner. A generally applicable solution technique which could be used regardless of whether the channel is wet or dry, junctions with tributaries are present or not, or the flow changes between subcritical and supercritical conditions is not presently available. Since 1968 The Hydrologic Engineering Center has been working, through contracted research, to obtain such a solution, and progress is being made; but the complete solution of the general case is still in the future.

SUMMARY AND CONCLUSIONS

The objective of this study was to develop a reasonable method for calculating energy remaining in the flood wave at Martins Fork Dam and for converting the inertia and kinetic energies into total energy from which pressure loadings could be determined. The body of theory appears to be reasonably well established, but methods for implementing this theory require numerical techniques which utilize the electronic computer, and a complete solution of the general case is not presently available. Some progress is being made toward such a solution; however,

in the meantime, studies of dam-break floods will be required, and these studies will have to be limited in scope because of limitations in available methods. A great deal of engineering judgment will be required to simplify and approximate the actual problem so the existing methods can be employed.



Figure 1
 MARTINS FORK AND CRANKS CREEK RESERVOIRS




Figure 2. STREAMBED PROFILES




Figure 3. STORAGE IN EACH RESERVOIR




Figure 4. RESULTS FROM FAILURE AT
PEAK OF S. D. F. (CONDITION I)




Figure 5. THE INFLUENCE OF HYDRAULIC ROUGHNESS ON PEAK ENERGY AT MARTINS FORK DAM (CONDITION I)




Figure 6. FAILURE WITH BOTH RESERVOIRS AT SUMMER POOL ELEVATION (CONDITION II)




Figure 7. FAILURE WITH BOTH RESERVOIRS AT SPILLWAY CREST ELEVATIONS (CONDITION III)

REFERENCES

1. Garrison, Jack M., Jean-Pierre P. Granju, and James T. Price, "Unsteady Flow Simulation in Rivers and Reservoirs," *Journal of the Hydraulics Division, ASCE*, Vol. 95, No. HY5, September 1969.
2. Henderson, F. M., Open-Channel Flow, The Macmillan Company, New York, pp. 304-312, 1966.
3. Martin, C., Samuel and Frank G. De Fazio, "Open-Channel Surge Simulation by Digital Computer," *Journal of the Hydraulics Division, ASCE*, Vol. 95, No. HY6, November 1969.
4. Strelkoff, Theodor, "One-Dimensional Equations of Open-Channel Flow," *Journal of the Hydraulics Division, ASCE*, Vol. 95, No. HY3, May 1969.
5. Terzidis, George and Theodor Strelkoff, "Computation of Open-Channel Surges and Shocks," *Journal of the Hydraulics Division, ASCE*, Vol. 96, No. HY12, December 1970.
6. U.S. Army Corps of Engineers, Waterways Experiment Stations, Vicksburg, Mississippi, Floods Resulting from Suddenly Breached Dams, Conditions of Minimum Resistance, Report No. 1, 1960.

TECHNICAL PAPERS

PRICE: \$1.00 each

- # 1 USE OF INTERRELATED RECORDS TO SIMULATE STREAMFLOW, Leo R. Beard (Dec 1964)
- # 2 OPTIMIZATION TECHNIQUES FOR HYDROLOGIC ENGINEERING, Leo R. Beard (Apr 1966)
- # 3 METHODS FOR DETERMINATION OF SAFE YIELD AND COMPENSATION WATER FROM STORAGE RESERVOIRS, Leo R. Beard (Aug 1965)
- # 4 FUNCTIONAL EVALUATION OF A WATER RESOURCES SYSTEM, Leo R. Beard (Jan 1967)
- # 5 STREAMFLOW SYNTHESIS FOR UNGAGED RIVERS, Leo R. Beard (Oct 1967)
- # 6 SIMULATION OF DAILY STREAMFLOW, Leo R. Beard (Apr 1968)
- # 7 PILOT STUDY FOR STORAGE REQUIREMENTS FOR LOW FLOW AUGMENTATION, A. J. Fredrich (Apr 1968)
- # 8 WORTH OF STREAMFLOW DATA FOR PROJECT DESIGN - A PILOT STUDY, D. R. Dawdy, H. E. Kubik, L. R. Beard, and E. R. Close (Apr 1968)
- # 9 ECONOMIC EVALUATION OF RESERVOIR SYSTEM ACCOMPLISHMENTS, Leo R. Beard (May 1968)
- #10 HYDROLOGIC SIMULATION IN WATER-YIELD ANALYSIS, Leo R. Beard (1964)
- #11 SURVEY OF PROGRAMS FOR WATER SURFACE PROFILES, Bill S. Eichert (Aug 1968)
- #12 HYPOTHETICAL FLOOD COMPUTATION FOR A STREAM SYSTEM, Leo R. Beard (Apr 1968)
- #13 MAXIMUM UTILIZATION OF SCARCE DATA IN HYDROLOGIC DESIGN, L. R. Beard and A. J. Fredrich (Mar 1969)
- #14 TECHNIQUES FOR EVALUATING LONG-TERM RESERVOIR YIELDS, A. J. Fredrich (Feb 1969)
- #15 HYDROSTATISTICS - PRINCIPLES OF APPLICATION, Leo R. Beard (Dec 1969)
- #16 A HYDROLOGIC WATER RESOURCE SYSTEM MODELING TECHNIQUE, L. G. Hulman (1969)
- #17 HYDROLOGIC ENGINEERING TECHNIQUES FOR REGIONAL WATER RESOURCES PLANNING, A. J. Fredrich and E. F. Hawkins (Oct 1969)
- #18 ESTIMATING MONTHLY STREAMFLOWS WITHIN A REGION, Leo R. Beard, E. F. Hawkins, and A. J. Fredrich (Jan 1970)
- #19 SUSPENDED SEDIMENT DISCHARGE IN STREAMS, Charles E. Abraham (Apr 1969)
- #20 COMPUTER DETERMINATION OF FLOW THROUGH BRIDGES, B. S. Eichert and J. C. Peters (Dec 1970)

TECHNICAL PAPERS (CONT'D)

- #21 AN APPROACH TO RESERVOIR TEMPERATURE ANALYSIS, L. R. Beard and R. G. Willey (Apr 1970)
- #22 A FINITE DIFFERENCE METHOD FOR ANALYZING LIQUID FLOW IN VARIABLY SATURATED POROUS MEDIA, Richard L. Cooley (Apr 1970)
- #23 USES OF SIMULATION IN RIVER BASIN PLANNING, William K. Johnson and E. T. McGee (Aug 1970)
- #24 HYDROELECTRIC POWER ANALYSIS IN RESERVOIR SYSTEMS, A. J. Fredrich (Aug 1970)
- #25 STATUS OF WATER RESOURCE SYSTEMS ANALYSIS, Leo R. Beard (Jan 1971)
- ** #26 SYSTEM RELATIONSHIPS FOR PANAMA CANAL WATER SUPPLY, L. G. Hulman (Apr 1971)
- ** #27 SYSTEMS ANALYSIS OF THE PANAMA CANAL WATER SUPPLY, D. C. Lewis and L. R. Beard (Apr 1971)
- #28 DIGITAL SIMULATION OF AN EXISTING WATER RESOURCES SYSTEM, A. J. Fredrich (Oct 1971)
- #29 COMPUTER APPLICATIONS IN CONTINUING EDUCATION, A. J. Fredrich, B. S. Eichert, and D. W. Davis (Jan 1972)
- #30 DROUGHT SEVERITY AND WATER SUPPLY DEPENDABILITY, L. R. Beard and H. E. Kubik (Jan 1972)
- #31 DEVELOPMENT OF SYSTEM OPERATION RULES FOR AN EXISTING SYSTEM BY SIMULATION, C. Pat Davis and A. J. Fredrich (Oct 1971)
- #32 ALTERNATIVE APPROACHES TO WATER RESOURCE SYSTEM SIMULATION, L. R. Beard, Arden Weiss, and T. Al Austin (May 1972)
- #33 SYSTEM SIMULATION FOR INTEGRATED USE OF HYDROELECTRIC AND THERMAL POWER GENERATION, A. J. Fredrich and L. R. Beard (Oct 1972)
- #34 OPTIMIZING FLOOD CONTROL ALLOCATION FOR A MULTIPURPOSE RESERVOIR, Fred K. Duren and L. R. Beard (Aug 1972)
- #35 COMPUTER MODELS FOR RAINFALL-RUNOFF AND RIVER HYDRAULIC ANALYSIS, Darryl W. Davis (Mar 1973)
- ** #36 EVALUATION OF DROUGHT EFFECTS AT LAKE ATITLAN, Arlen D. Feldman (Sep 1972)
- #37 DOWNSTREAM EFFECTS OF THE LEVEE OVERTOPPING AT WILKES-BARRE, PA, DURING TROPICAL STORM AGNES, Arlen D. Feldman (Apr 1973)
- #38 WATER QUALITY EVALUATION OF AQUATIC SYSTEMS, R. G. Willey (Apr 1975)
- #39 A METHOD FOR ANALYZING EFFECTS OF DAM FAILURES IN DESIGN STUDIES, William A. Thomas (Aug 1972)
- #40 STORM DRAINAGE AND URBAN REGION FLOOD CONTROL PLANNING, Darryl Davis (Oct 1974)

TECHNICAL PAPERS (CONT'D)

- #41 HEC-5 , A SIMULATION MODEL FOR SYSTEM FORMULATION AND EVALUATION, Bill S. Eichert (Mar 1974)
- #42 OPTIMAL SIZING OF URBAN FLOOD CONTROL SYSTEMS, Darryl Davis (Mar 1974)
- #43 HYDROLOGIC AND ECONOMIC SIMULATION OF FLOOD CONTROL ASPECTS OF WATER RESOURCES SYSTEMS, Bill S. Eichert (Aug 1975)
- #44 SIZING FLOOD CONTROL RESERVOIR SYSTEMS BY SYSTEMS ANALYSIS, B. S. Eichert and D. W. Davis (Mar 1976)
- #45 TECHNIQUES FOR REAL-TIME OPERATION OF FLOOD CONTROL RESERVOIRS IN THE MERRIMACK RIVER BASIN, B. S. Eichert, J. C. Peters, and A. F. Pabst (Nov 1975)
- #46 SPATIAL DATA ANALYSIS OF NONSTRUCTURAL MEASURES, R. P. Webb and M. W. Burnham (Aug 1976)
- #47 COMPREHENSIVE FLOOD PLAIN STUDIES USING SPATIAL DATA MANAGEMENT TECHNIQUES, Darryl W. Davis (Oct 1976)
- #48 DIRECT RUNOFF HYDROGRAPH PARAMETERS VERSUS URBANIZATION, David L. Gundlach (Sep 1976)
- #49 EXPERIENCE OF HEC IN DISSEMINATING INFORMATION ON HYDROLOGIC MODELS, Bill S. Eichert (Jun 1977)
- #50 EFFECTS OF DAM REMOVAL: AN APPROACH TO SEDIMENTATION, David T. Williams (Oct 1977)
- #51 DESIGN OF FLOOD CONTROL IMPROVEMENTS BY SYSTEMS ANALYSIS: A CASE STUDY, H. W. Reese, A. V. Robbins, J. R. Jordan, and H. V. Doyal (Oct 1971)
- #52 POTENTIAL USE OF DIGITAL COMPUTER GROUND WATER MODELS, David L. Gundlach, (Apr 1978)
- #53 DEVELOPMENT OF GENERALIZED FREE SURFACE FLOW MODELS USING FINITE ELEMENT TECHNIQUES, D. Michael Gee and Robert C. MacArthur (Jul 1978)
- #54 ADJUSTMENT OF PEAK DISCHARGE RATES FOR URBANIZATION, David L. Gundlach (Feb 1979)
- #55 THE DEVELOPMENT AND SERVICING OF SPATIAL DATA MANAGEMENT TECHNIQUES IN THE CORPS OF ENGINEERS, R. Pat Webb and Darryl W. Davis (Jul 1978)
- #56 EXPERIENCES OF THE HYDROLOGIC ENGINEERING CENTER IN MAINTAINING WIDELY USED HYDROLOGIC AND WATER RESOURCE COMPUTER MODELS, Bill S. Eichert (Nov 1978)
- #57 FLOOD DAMAGE ASSESSMENTS USING SPATIAL DATA MANAGEMENT TECHNIQUES, Darryl W. Davis and R. Pat Webb (Nov 1978)
- #58 A MODEL FOR EVALUATING RUNOFF-QUALITY IN METROPOLITAN MASTER PLANNING, L. A. Roesner, H. M. Nicharndros, R. P. Shubinski, A. D. Feldman, J. W. Abbott, and A. O. Friedland (Apr 1974)

TECHNICAL PAPERS (CONT'D)

- #59 TESTING OF SEVERAL RUNOFF MODELS ON AN URBAN WATERSHED, Jess Abbott (Oct 1978)
- #60 OPERATIONAL SIMULATION OF A RESERVOIR SYSTEM WITH PUMPED STORAGE, George F. McMahon, Vern Bonner and Bill S. Eichert (Feb 1979)
- #61 TECHNICAL FACTORS IN SMALL HYDROPOWER PLANNING, Darryl W. Davis (Feb 1979)
- #62 FLOOD HYDROGRAPH AND PEAK FLOW FREQUENCY ANALYSIS, Arlen D. Feldman (Mar 1979)
- #63 HEC CONTRIBUTION TO RESERVOIR SYSTEM OPERATION, Bill S. Eichert and Vernon R. Bonner (Aug 79)
- #64 DETERMINING PEAK-DISCHARGE FREQUENCIES IN AN URBANIZING WATERSHED - A CASE STUDY, Steven F. Daly and John C. Peters (Jul 1979)
- #65 FEASIBILITY ANALYSIS IN SMALL HYDROPOWER PLANNING, Darryl W. Davis and Brian W. Smith (Aug 1979)
- #66 RESERVOIR STORAGE DETERMINATION BY COMPUTER SIMULATION OF FLOOD CONTROL AND CONSERVATION SYSTEMS, Bill S. Eichert (Sept 1979)
- #67 HYDROLOGIC LAND USE CLASSIFICATION USING LANDSAT, Robert J. Cermak, Arlen Feldman, and R. Pat Webb (June 1979)

** Publications containing information on third countries are not releasable to foreign countries.