

AD-A105 319

RIA-81-U968

TECHNICAL
LIBRARY

AD A-105319

MEMORANDUM REPORT ARBRL-MR-03134

DETAILED THERMAL RESPONSE OF A 155-mm,
M203 PROPELLING CHARGE DURING TEMPERATURE
CONDITIONING, HANDLING, AND LOADING

Arthur A. Koszoru
John R. Kelso

September 1981



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22151.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR-03134	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Detailed Thermal Response of a 155-mm, M203 Propelling Charge During Temperature Conditioning, Handling, and Loading		5. TYPE OF REPORT & PERIOD COVERED Memorandum Report
7. AUTHOR(s) Arthur A. Koszoru and John R. Kelso		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Ballistic Research Laboratory ATTN: DRDAR-BLI Aberdeen Proving Ground, MD 21005		8. CONTRACT OR GRANT NUMBER(s)
10. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research and Development Command US Army Ballistic Research Laboratory ATTN: DRDAR-BL Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L162618AH80
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE SEPTEMBER 1981
		13. NUMBER OF PAGES 24
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Charge Conditioning Conditioning Rates Environmental Effects Temperature Coefficient		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) jmk Extreme temperature conditioning of large-caliber propelling charges for a determination of temperature coefficients is a very important phase of charge design evaluation. Ambient conditions encountered during transit from conditioning chambers to gun sites have a profound effect on temperatures of conditioned charges. The M203, Zone 8 Propelling Charge for the Army 155-mm Howitzer contains a complex ignition train whose vulnerability to those ambient conditions must also be considered. Two M203 charges were instrumented with thermocouples		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

located at ten positions and subjected to extreme temperature conditioning. Temperatures at these positions were monitored during conditioning and exposure to new environments. A 24-hour period for conditioning to extreme temperatures was shown to be sufficient, in agreement with past results as well as with current testing procedures. However, exposure to a new environment (e.g., removal from the conditioning box) leads to rapid changes in charge temperatures, particularly at the surface of the charge. The influence of this response on performance is unknown but potentially important.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	5
I. INTRODUCTION.	7
II. EXPERIMENTAL.	8
A. Thermocouples	8
B. Preparation of Charges.	8
C. Test Procedure.	10
III. RESULTS	10
IV. CONCLUSIONS	18
DISTRIBUTION LIST	19

LIST OF ILLUSTRATIONS

Figure	Page
1. Location of Thermocouples Within the M203 Propelling Charge	8
2. Time Required to Extreme Condition an M203 Propelling Charge in Metal Container.	11
3. Time Required to Extreme Condition an M203 Propelling Charge in Plastic Wrap	12
4. Effect of 15°C Environment on Containerized Charge Conditioned at 62°C.	13
5. Effect of 15°C Environment on Plastic Wrapped Charge Conditioned at 62°C.	13
6. Time Required to Recondition an M203 Propelling Charge in Metal Container	14
7. Cooling Effect of Gun Chamber at 16°C on Charge Conditioned at 62°C.	15
8. Time Required to Condition a Containerized M203 Charge at -49°C.	16
9. Effect of 25°C Environment on an M203 Charge Conditioned at -49°C.	17

I. INTRODUCTION

Standardized ammunition safety performance test procedures require a determination of temperature coefficients to establish upper safe pressure levels for various weapons. For this phase of testing, ammunition is conditioned at temperatures ranging from -54°C (-65°F) to $+68^{\circ}\text{C}$ ($+155^{\circ}\text{F}$).

The US Army Test and Evaluation Command outline for limits of operation requires that for testing ammunition at 21°C (70°F) propellant temperature will not vary more than $\pm 0.5^{\circ}\text{C}$ at time of firing. Further, for extreme temperature testing (-54°C to $+68^{\circ}\text{C}$) propellant temperature must not vary by more than $\pm 2.5^{\circ}\text{C}$ at time of firing¹.

Times have been fairly well established for complete temperature conditioning of ammunition;² however, the environmental conditions this ammunition will encounter before being fired may have an enormous effect on the temperature at time of firing. Time of exposure to ambient air and wind conditions, direct rays of the sun and weapon temperature are but a few of the environmental conditions which can exert a strong effect on a conditioned charge. Anderson and Heppner³ did an extensive study on temperature change versus exposure time by imbedding thermocouples in a variety of charges and projectiles, and monitoring the temperatures during the initial conditioning process and after removal to a different atmosphere as might be encountered while moving those ammunition items to a gun site.

Seemingly, previous studies were devoted to ascertaining propellant temperatures under a variety of conditions, but we feel consideration should also be given to the individual components of the ignition system, in particular, of a large-caliber propelling charge. Therefore, the present study was undertaken to determine extreme conditioning times and the effect of a new temperature environment on the ignition system as well as the propellant by inserting thermocouples at selected locations in a typical high-performance artillery charge, the 155-mm, M203 Propelling Charge.

¹"Abnormal Temperature Testing of Artillery, Mortar and Recoilless Rifle Propellants," USATECOM Material Test Procedure No. 4-2-608, Aberdeen Proving Ground, MD, 20 February 1971.

²D.J. Francis, "Final Report of Research Study of Ammunition Temperature Conditioning Time Requirements," Report DPS-1665, Aberdeen Proving Ground, MD, May 1965.

³H.B. Anderson and L. Heppner, "Special Research Study on Temperature Change Versus Exposure Time for Extreme Temperature Conditioning of Artillery Ammunition," Report No. APG-MT-3571, Aberdeen Proving Ground, MD, July 1970.

II. EXPERIMENTAL

A. Thermocouples

The thermocouples were made by forming a junction between 24-gage enameled copper wire and 27-gage constantan wire, the resulting junctions having a diameter of approximately 1.2 mm. Of the 27 prepared, 23 were selected based on their uniformity of response during immersion in water at 25°C, water at 100°C, and a dry ice-acetone mixture at -78.5°C.

Temperatures were read directly from a Multipoint Digital Thermometer which is portable, battery operated, and reference-junction compensated. The unit is capable of indicating the output of any 1 of 10 thermocouples with like inputs to $\pm 0.1^\circ\text{C}$. A switching device was inserted between the thermocouple leads from the charges and the digital readout unit, which expanded its capability of indicating the output from any 1 of 23 like thermocouples.

B. Preparation of Charges

Two standard M203 charges were dismantled so that thermocouples could be inserted at selected points. Figure 1 shows the locations selected for the insertion of the thermocouples. The two charges were rebuilt simultaneously so that the least variation in thermocouple placement would result.

THERMOCOUPLE LOCATION

1. CENTER PERFORATION OF GRAIN
 2. OUTER WALL OF GRAIN
 3. CENTER PERFORATION OF GRAIN
 4. OUTER WALL OF GRAIN
 5. CENTER PERFORATION OF GRAIN - GRAIN BURIED
 6. APPROX. CENTER OF PROPELLANT BED.
 7. CENTER PERFORATION OF GRAIN - GRAIN ATTACHED TO KIDNEY WALL.
 8. IMBEDDED IN CENTERCORE WALL CENTER OF CHARGE.
 9. IMBEDDED IN BLACK POWDER OF SNAKE.
 10. IMBEDDED IN BLACK POWDER OF BASE PAD.
- GRAIN ATTACHED TO INNER WALL OF BAG
- GRAIN ATTACHED TO INNER WALL OF LINER




Figure 1. Location of Thermocouples Within the M203 Propelling Charge

Thermocouple No. 8 (TC-8) was inserted through the cloth wall of the snake and imbedded in the black powder at the midpoint of the snake. The lead wires were strapped to the outer walls of the snake, extending several inches beyond the forward end.

The snake was repositioned within the centercore tube, and TC-7 was inserted in a small hole drilled into the 3.5-mm thick sidewall of the centercore at its midpoint, longitudinally. Care was taken that this junction was truly imbedded in the wall and did not penetrate through the wall. TC-7 leads were strapped to the centercore walls so that they too extended beyond the forward end of the tube.

Several of the 7-perforation propellant grains were instrumented with thermocouples. TC-2 was cemented into a shallow groove cut into the side of a grain, and TC-1 was inserted into the center perforation of the same grain, this perforation having been enlarged to accommodate the 1.2-mm diameter of the junction. The same procedure was followed with TC-3 and TC-4, TC-3 inserted into the enlarged center perforation and TC-4 cemented in a shallow groove cut into the wall of the grain.

The propellant grain bearing TC-1 and 2 was attached to the inner wall of the bag, 15 cm from the base end of the charge, and the grain bearing TC-3 and 4 was attached to the wall of the TiO_2 liner, inside the charge, at a point 15 cm from the forward end of the charge. The grains were attached to these surfaces so that TC-2 and 4 were at the interface formed between the grain and the surface to which it was attached. The leads from these four thermocouples were brought out the forward end of the bag.

Another grain, instrumented with TC-6 through its center perforation was attached to the kidney wall at the midpoint of the charge, and its leads also brought out of the forward end of the bag.

With the grains bearing TC-1, 2, 3, 4, and 6 attached firmly inside the bag, one-half the propellant load was replaced, and another grain with TC-5 through the center perforation was placed on the surface of the propellant bed and its leads forced through the bag wall at that point. Care was taken so that this grain was centered within the space defined by the centercore wall and the outer wall of the bag. With this grain in place, the balance of the propellant load was added and the seam sewn shut.

With the instrumented centercore and snake in place within the charge and tie straps secured, TC-9 was imbedded in the black powder of the basepad and the leads brought up along opposing sides of the charge, and strapped lightly in place. The assembly of the charge was completed by the replacement of the lacing jacket. TC-10 was alternately taped to the outer surface of the lacing jacket or inserted between layers of the corrugated packing material surrounding the charge.

One charge was placed in the standard M203 metal shipping container lined with corrugated cardboard, and all TC leads brought through a small hole previously drilled in the lid. The second prepared charge was placed in a sealed plastic bag - a procedure often used to prepare experimental charges for conditioning.

C. Test Procedure

The two charges were extreme temperature conditioned in a chamber located at the Ballistic Research Laboratory Sandy Point Firing Facility. The chamber was designed for testing various ordnance items over a temperature range -73°C to $+93^{\circ}\text{C}$. The chamber was allowed to operate for a period of 24 hours to stabilize at the desired temperature before the charges were placed inside.

After temperature stabilization of the chamber, both charges were laid horizontally upon a lattice shelf located an equal distance (45 cm) from the top and bottom of the conditioning chamber. Thermocouple leads extended outside the box and had previously been attached to the readout unit. The charges were placed inside the box in a minimum of time (~ 1 minute) so that recovery time to initial conditioning temperature would be as short as possible. For purposes of timing, time-zero was defined by the closing of the chamber door.

Although the conditioning chamber was equipped with a temperature recording device, a thermocouple (for reference labeled TC-amb) was inserted into the top of the chamber, extending inward by 15 cm. Excellent agreement was obtained between the two temperature indicating devices during the heating cycles of this study, but not during the cooling cycle. TC-amb was also used to measure ambient air temperatures, and to measure gun chamber temperature when the conditioned charges were moved to a new environment.

During conditioning, temperature readings at all locations were taken every 2 minutes for the first 30 minutes, every 5 minutes for the next 30 minutes, and every hour for the following 6 hours. No readings were then taken for 16 hours. Finally, the readings were conducted at half-hour intervals for 2 hours prior to removal of charges from the conditioning chamber.

III. RESULTS

Figure 2 is a plot of the data, temperature vs time, obtained at five positions for a charge which had been placed in a chamber heated to $+62^{\circ}\text{C}$. Temperature histories for positions not shown were in substantial agreement with those of corresponding positions plotted (i.e., positions 1, 2 and 4 similar to 3; positions 6 and 7 similar to 8). The charge was in the standard metal shipping container, and TC-10 imbedded between two layers of corrugated packing material wrapped around the charge. Figure 3 is a plot of the data obtained at the same four

positions within a charge wrapped in plastic, also surrounded by the same corrugated packing material with TC-10 imbedded in that material. Although both charges were conditioned at the same time, the charge in the metal container appears to approach the chamber temperature somewhat faster than the charge in the plastic material. This observation can perhaps be ascribed to the faster heat conduction properties of the metal container over the plastic material.




Figure 2. Time Required to Extreme Condition an M203 Propelling Charge in Metal Container




Figure 3. Time Required to Extreme Condition a M203 Propelling Charge in Plastic Wrap

Figures 4 and 5 show the temperature vs time plots of the data obtained when these two charges, in their containers, were removed from the conditioning chamber and laid on a wooden surface in a draft-free room, in which the ambient temperature was 15.6°C. The time of transition from conditioning chamber to the new environment was less than 2 minutes, and monitoring of the thermocouples began at 2 minutes and continued for 1 hour. Note the accelerated cooling of exterior components (corrugated packing and basepad) in the plastic wrapped charge versus the containerized charge.




Figure 4. Effect of 15°C Environment on Containerized Charge Conditioned at 62°C




Figure 5. Effect of 15°C Environment on Plastic Wrapped Charge Conditioned at 62°C

Figure 6 is a plot of temperatures recorded at various points within the containerized charge during reconditioning to approximately 62°C. After 24 hours, the container and charge were removed from the conditioning chamber and transported to a gun site where the charge was removed from the container and placed inside the gun chamber at 16°C. The total transition time to the new environment was 2 minutes. Before temperature reconditioning, TC-10 had been removed from the corrugated wrapping, and secured to the jacket surface. Figure 7 shows the rate of cooling upon transition to the gun site and insertion within the gun chamber.




Figure 6. Time Required to Recondition an M203 Propelling Charge in Metal Container




Figure 7. Cooling Effect of Gun Chamber at 16°C on Charge Conditioned at 62°C

To determine the time required for all components of a containerized (metal) M203 Propelling Charge to become cold conditioned, the conditioning chamber was first allowed to come to equilibrium, as indicated by the recording device of the chamber, and the charge was then inserted. Figure 8 is a temperature vs time plot of thermocouples at four locations within the charge, and TC-10 on the jacket surface. After a 24-hour conditioning period, the containerized charge was removed from the conditioning chamber and from the container, (transition time of < 2 minutes) and laid on a metal surface in a draft-free room at +25°C. Figure 9 is a temperature vs time plot of temperatures recorded at four locations within the charge and at the jacket surface.




Figure 8. Time Required to Condition a Containerized M203 Charge at -49°C




Figure 9. Effect of 25°C Environment on a M203 Charge Conditioned at -49°C

Near the end of the extreme-cooling cycle it became evident that strong thermal gradients apparently exist in the conditioning chamber used for this study. Anderson and Heppner suggest that conditioning boxes be checked for this problem by placing several thermocouples at various locations within the chamber and noting any variations in temperature. Although the temperature chart recorder for the chamber used in this study indicated a temperature of -54°C during the cold conditioning cycle (Figure 8), the temperatures within the charge had not reached that temperature after 24 hours of conditioning. An extrapolation of those curves indicates that the temperature of the charge would probably never reach -54°C. Perhaps this was to be expected, since the chart-recorder sensor was located near the bottom of the chamber and the charge was laying on a shelf located in the center, 45 cm above the bottom. A thermocouple (TC-amb) extended 25 cm into the upper section of the chamber indicated a temperature of -47°C while an immersion thermometer extending 7.60 cm into the upper section of the chamber indicated a temperature of -45°C.

IV. CONCLUSIONS

Testing was performed to study the thermal response of various stations in a 155-mm bagged charge to extreme conditioning temperatures. The times required to condition such a charge to nearly uniform extreme temperatures throughout were measured and found to be in agreement with the earlier work reported by Francis². A 24-hour period appears to be adequate for conditioning this charge to both hot and cold temperature extremes. Exposure time to a new environment, however, was shown to exert a strong influence on the established temperature profiles within the propelling charge and the basepad, and, to a lesser extent, other ignition system components. This behavior may in part be responsible for observed variations in ignition delays, as the burning rate for black powder is strongly affected by initial temperature⁴. Further, it may be concluded that without extreme care to provide adequate thermal protection and minimum exposure times between conditioning chamber and moment of firing, significant variations in propelling charge performance may be observed; test results may not be truly representative of those expected in the arctic and desert environments that such tests are intended to simulate. We note that the plastic wrapping employed in this test provided a thermal barrier that was far less effective in this respect than the standard metal shipping container supplied with the M203 Charge.

A final caution is made to ensure that strong thermal gradients are not present in the conditioning chamber, as they may further degrade validity of test results.

⁴Private communication, K. J. White, Interior Ballistics Division, Ballistic Research Laboratory, Aberdeen Proving Ground, MD.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Technical Info Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	1	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Watervliet, NY 12189
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Watervliet Arsenal ATTN: SARWV-RD, R. Thierry Watervliet, NY 12189
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDE-DW 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Aviation Research and Development Command ATTN: DRDAV-E 4300 Goodfellow Boulevard St. Louis, MO 63120
4	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS (2 cys) DRDAR-LCE, R. Walker DRDAR-SCA, L. Stiefel Dover, NJ 07801	1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035
6	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCA H. Fair S. Bernstein S. Einstein P. Kemmey D. Downs L. Schlosberg Dover, NJ 07801	1	Commander US Army Communications Rsch and Development Command ATTN: DRDCO-PPA-SA Fort Monmouth, NJ 07703
1	Commander US Army Armament Materiel Readiness Command ATTN: DRDAR-LEP-L, Tech Lib Rock Island, IL 61299	1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703
		1	Commander US Army Missile Command ATTN: DRSMI-R Redstone Arsenal, AL 35809
		1	Commander US Army Missile Command ATTN: DRSMI-YDL Redstone Arsenal, AL 35809

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Natick Research and Development Command ATTN: DRXRE, D. Sieling Natick, MA 01762	5	Commander Naval Surface Weapons Center ATTN: Code G33, J. East D. McClure W. Burrell J. Johndrow Code DX-21, Tech Lib Dahlgren, VA 22448
1	Commander US Army Tank Automotive Research & Development Command ATTN: DRDTA-UL Warren, MI 48090	3	Commander Naval Surface Weapons Center ATTN: S. Jacobs, Code 240 Code 730 K. Kim, Code R-13 Silver Spring, MD 20910
2	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL Tech Lib Watertown, MA 02172	1	Commander Naval Underwater Systems Center Energy Conversion Department ATTN: Code 5B331, R. Lazar Newport, RI 02840
1	Commander US Army Research Office ATTN: Tech Lib P. O. Box 12211 Research Triangle Park NC 27706	2	Commander Naval Weapons Center ATTN: Code 388, R. Derr C. Price China Lake, CA 93555
1	Director US Army TRADOC Sytems Analysis Activity ATTN: ATAA-SL, Tech Lib White Sands Missile Range NM 88002	1	Superintendent Naval Postgraduate School Dept of Mechanical Engineering ATTN: A. Fuhs Monterey, CA 93940
1	Chief of Naval Research ATTN: Code 473, R. Miller 800 N. Quincy Street Arlington, VA 22217	2	Commander Naval Ordnance Station ATTN: P. Stang C. Smith Indian Head, MD 20640
1	Commander Naval Sea Systems Command ATTN: SEA-62R2, J. Murrin National Center, Bldg. 2 Room 6E08 Washington, DC 20360	1	AFOSR (L. Caveny) Bolling AFB, DC 20332
		2	AFRPL (DYSC) ATTN: D. George J. Levine Edwards AFB, CA 93523

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	AFATL/DL DL (O. Heiney) Eglin AFB, FL 32542	1	Hercules, Inc. Bacchus Works ATTN: K. McCarty P. O. Box 98 Magna, UT 84044
1	Aerojet Solid Propulsion Co. ATTN: P. Micheli Sacramento, CA 95813	1	Hercules, Inc. Eglin Operations AFATL/DL DL ATTN: R. Simmons Eglin AFB, FL 32542
1	ARO Incorporated ATTN: N. Dougherty Arnold AFS, TN 37389	1	IITRI ATTN: M. J. Klein 10 W. 35th Street Chicago, IL 60615
1	Atlantic Research Corporation ATTN: M. King 5390 Cherokee Avenue Alexandria, VA 22314	1	Lawrence Livermore Laboratory ATTN: M.S. L-355, A. Buckingham P. O. Box 808 Livermore, CA 94550
1	AVCO Corporation AVCO Everett Rsch Lab Div ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149	1	Olin Corporation Badger Army Ammunition Plant ATTN: R. Thiede Baraboo, WI 53913
1	Calspan Corporation ATTN: E. Fisher P. O. Box 400 Buffalo, NY 14221	1	Olin Corporation Smokeless Powder Operations ATTN: R. Cook P. O. Box 222 St. Marks, FL 32355
1	Foster Miller Associates, Inc. ATTN: A. Erickson 135 Second Avenue Waltham, MA 02154	1	Paul Gough Associates, Inc. ATTN: P. Gough P. O. Box 1614 Portsmouth, NH 03801
1	General Applied Sciences Labs ATTN: J. Erdos Merrick & Stewart Avenues Westbury Long Island, NY 11590	1	Physics International Company 2700 Merced Street Leandro, CA 94577
1	General Electric Company Armament Systems Department ATTN: M. Bulman, Rm 1311 Lakeside Avenue Burlington, VT 05402	1	Princeton Combustion Rsch Lab, Inc. ATTN: M. Summerfield 1041 US Highway One North Princeton, NJ 08540
1	Hercules, Inc. Allegany Ballistics Laboratory ATTN: R. Miller P. O. Box 210 Cumberland, MD 21502		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Pulsepower Systems, Inc. ATTN: L. Elmore 815 American Street San Carlos, CA 94070	1	Universal Propulsion Company ATTN: H. McSpadden 1800 W. Deer Valley Rd Phoenix, AZ 85027
1	Rockwell International Corp. Rocketdyne Division ATTN: BA08, J. Flanagan 6633 Canoga Avenue Canoga Park, CA 91304	1	Battelle Memorial Institute ATTN: Tech Library 505 King Avenue Columbus, OH 43201
1	Science Applications, Inc. ATTN: R. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364	1	Brigham Young University Dept. of Chemical Engineering ATTN: R. Coates Provo, UT 84601
1	Scientific Research Assoc., Inc. ATTN: H. McDonald P. O. Box 498 Glastonbury, CT 06033	1	California Institute of Tech 204 Karman Lab Mail Stop 301-46 ATTN: F.E.C. Culick 1201 E. California Street Pasadena, CA 91125
1	Shock Hydrodynamics, Inc. ATTN: W. Anderson 4710-16 Vineland Avenue North Hollywood, CA 91602	1	California Institute of Technology Jet Propulsion Laboratory ATTN: L. Strand 4800 Oak Grove Drive Pasadena, CA 91103
3	Thiokol Corporation Huntsville Division ATTN: D. Flanagan R. Glick Tech Library Huntsville, AL 35807	1	Case Western Reserve University Division of Aerospace Sciences ATTN: J. Tien Cleveland, OH 44135
2	Thiokol Corporation Wasatch Division ATTN: John Peterson Tech Library P. O. Box 524 Brigham City, UT 84302	3	Georgia Institute of Tech School of Aerospace Eng. ATTN: B. Zinn E. Price W. Strahle Atlanta, GA 30332
2	United Technologies ATTN: R. Brown Tech Library P. O. Box 358 Sunnyvale, CA 94088	1	Institute of Gas Technology ATTN: D. Gidaspow 3424 S. State Street Chicago, IL 60616

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Johns Hopkins University Applied Physics Laboratory Chemical Propulsion Information Agency ATTN: T. Christian Johns Hopkins Road Laurel, MD 20810	1	Stevens Institute of Technology Davidson Laboratory ATTN: R. McAlevy, III Hoboken, NJ 07030
1	Massachusetts Institute of Technology Dept. of Mechanical Engineering ATTN: T. Toong Cambridge, MA 02139	1	University of California Los Alamos Scientific Lab ATTN: T3, D. Butler Los Alamos, NM 87554
1	Pennsylvania State University Applied Research Lab ATTN: G. Faeth P. O. Box 30 State College, PA 16801	1	University of Southern California Mechanical Engineering Dept. ATTN: OHE200, M. Gerstein Los Angeles, CA 90007
1	Pennsylvania State University Dept. of Mechanical Engineering ATTN: K. Kuo University Park, PA 16802	1	University of California, San Diego AMES Department ATTN: F. Williams P. O. Box 109 La Jolla, CA 92037
1	Purdue University School of Mechanical Engineering ATTN: J. Osborn TSPC Chaffee Hall West Lafayette, IN 47906	1	University of Illinois Dept of Mech Engineering ATTN: H. Krier 144 MEB, 1206 W. Green Street Urbana, IL 61801
1	Rutgers State University Dept. of Mechanical and Aerospace Engineering ATTN: S. Temkin University Heights Campus New Brunswick, NJ 08903	1	University of Massachusetts Dept of Mechanical Engineering ATTN: K. Jakus Amherst, MA 01002
1	Rensselaer Polytechnic Inst. Department of Mathematics ATTN: D. Drew Troy, NY 12181	1	University of Minnesota Dept of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455
1	SRI International Propulsion Sciences Division ATTN: Tech Library 333 Ravenswood Avenue Menlo Park, CA 94024	2	University of Utah Dept of Chemical Engineering ATTN: A. Baer G. Flandro Salt Lake City, UT 84112
		1	Washington State University Dept of Mechanical Engineering ATTN: C. Crowe Pullman, WA 99163

DISTRIBUTION LIST

Aberdeen Proving Ground

Dir, USAMSAA

ATTN: DRXS-D

DRXS-MP, H. Cohen

Cdr, USATECOM

ATTN: DRSTE-TO-F

Dir, USACSL, Bldg. E3516, EA

ATTN: DRDAR-CLB-PA

Dir, USAMTD

ATTN: STEAP-MT-A, T.G. Hughes

M. Trumbore

D. Lacey

R. Falcone

STEAP-MT-G, H.L. Barnhart

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____

2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

