

AD-A108 130

NAVAL POSTGRADUATE SCHOOL MONTEREY CA
VOICE OF AMERICA HF CURTAIN ARRAY INTERFERENCE STUDY.(U)
OCT 81 S JAUREGUI, R W ADLER
NPS-62-81-036PR

F/8 20/14


UNCLASSIFIED

NL

1
2
3
4
5
6
7
8
9
10
11
12



END
DATE
FILMED
1-82
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS 1963-A

2

LEVEL 1

NPS-62-81-036PR

NAVAL POSTGRADUATE SCHOOL

Monterey, California

AD A108130



DTIC
SELECTED
NOV 27 1981
S E

VOICE OF AMERICA HF CURTAIN ARRAY
INTERFERENCE STUDY

Stephen Jauregui, Jr.
Richard W. Adler, BDM, Inc.

October 1981

Final Report for the period Nov 1980 - Sep 1981

Approved for public release; distribution unlimited
Prepared for: International Communication Agency
Voice of America
Code VOA/EPML
Washington, DC 20547

DTIC FILE COPY


81 11 26 038


NAVAL POSTGRADUATE SCHOOL
Monterey, California

Rear Admiral J.J. Ekelund
Superintendent


David A. Schrady
Acting Provost

This report was prepared by:


STEPHEN JAUREGUV, Jr.
Adjunct Professor of
Electrical Engineering


RICHARD W. ADLER
BDM, Inc.

Reviewed by:


ROBERT D. STRUM
Acting Chairman
Electrical Engineering Department

Released by:


WILLIAM M. TOLLES
Dean of Research

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NPS-62-81-036PR	2. GOVT ACCESSION NO. 10 41-15 130	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Voice of America HF Curtain Array		5. TYPE OF REPORT & PERIOD COVERED Project Report Nov 1980 - Sep 1981
7. AUTHOR(s) Stephen Jauregui, Jr. Richard W. Adler		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, CA 93940		8. CONTRACT OR GRANT NUMBER(s) Memorandum of Agreement Voice of America and Naval Postgraduate School
11. CONTROLLING OFFICE NAME AND ADDRESS International Communications Agency Voice of America Washington, DC 20547		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS /A
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE 25 October 1981
		13. NUMBER OF PAGES 12
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Antennas; Interference; Numerical Modeling		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report describes the results of a computer modeling investigation in which the interference to VHF and UHF communications/navigation equipments from a Voice of America HF relay station was determined. The radiating portions of the station were modeled using the Numerical Electromagnetic Code (NEC). Interference models predict, based on the data available, that the relay station and the nearby airport-based equipments are not compatible.		

LIST OF FIGURES

<u>Figure Number</u>	<u>Page</u>
1a NEC Versus TCI HF Array Model	6
1b NEC Versus TCI HF Array Model	7
2 Airport and Antenna Farm	9

A. THE PROBLEM

The Voice of America is planning to locate a HF relay station a few miles from an international airport. Electromagnetic interference is a possibility because of the closeness of the airport communication/navigation equipments and the radiating portions of the relay station (the curtain antenna array and the open-wire transmission line). The out-of-band (VHF and UHF) radiation characteristics of the VOA HF system must be determined as part of an interference calculation. The NEC program, with acceptable limits, can provide that information. Once the radiated interference levels are predicted, they can be compared to acceptable interference levels established by the avionics users, providing margins of safety or interference.

B. GIVEN DATA AND PARAMETERS

The following represent information provided by VOA, describing the HF site and the avionics interference criteria:

1. HF Relay Station (6 - 17 MHz)

Six 250 KW AM transmitters; two transmitters diplexed into one 4 x 4 horizontal half-wave dipole curtain array (similar to a TCI 611), fed through 1,000 to 3,000 feet of 300 ohm, 4-conductor open-wire transmission lines. The spurious output level of each transmitter is at least -60 dB below rated output.

2. Avionics Equipment

The equipment listed below is located distances of from one to three miles from the HF relay station. The airport is at three miles, but the nearest approach of the flight path to the relay station is one mile.

Maximum acceptable interference levels, as established by the International Civil Aeronautics Organization (ICAO), as applicable to this scenario are, in dBW/M²:

<u>Service</u>	<u>Level</u>
75 MHz VHF Marker	- 105.
120 MHz Aircraft ILS Localizer	- 136.8
120 MHz VOR	- 134.8
120 MHz Aircraft VHF Communications	- 136.2
120 MHz Ground VHF Communications	- 136.8
330 MHz Aircraft ILS Guide Path	- 116.8
1200 MHz Aircraft VOR/DME	- 102.

C. THE APPROACH

Since a VHF/UHF (out-of-band) performance prediction is required for the antenna and transmission line, and was nonexistent at commencement of the study, a step-by-step plan was developed to go from the known HF characteristics of the radiating system to the unknown VHF/UHF performance.

These steps were followed:

1. A full-model of the HF array was developed using NEC; the results were compared to the TCI published patterns, validating the modeling process in-band.
2. A vertical and a horizontal "cell" of the array were modeled at HF. Array theory was applied to produce the full array performance, demonstrating the principle for later application at VHF/UHF.
3. The smaller "cell" models were then run on NEC at VHF/UHF to produce out-of-band characteristics for these workable-sized representations of the antenna system.
4. Expected full-array out-of-band characteristics were calculated from the above, applying the same array theory. This established radiation for the antenna array portion of the RF system of the relay station.
5. The transmission line was modeled as an explicit wire model on NEC allowing prediction of radiation from the line at VHF/UHF.

6. The contribution of total RF system radiation caused by the transmission line was then established for use in the interference assessment portion of the study.
7. The worst case signal levels produced by the VOA system were estimated from (4) and (6) above, and interferences noted.

D. THE HF MODEL OF THE ARRAY


The HF array was modeled using NEC; with the exception that a conducting reflecting screen, behind the dipoles, was modeled as an image set of driven elements. This results in a bi-directional antenna pattern with peak gain 3 dB less than the unidirectional pattern of the antenna's manufacturer, TCI. The radiation patterns which were produced were very close to the published predicted patterns from TCI, if the bi-directional 3 dB difference in gain is accounted for. Figures 1a and 1b demonstrate a sample of the correlation of patterns. This validates the numerical model at HF and permits the next step: a model of a portion of the array at HF, later to be extended to VHF/UHF.

E. THE VHF MODEL OF THE ARRAY

As with all numerical analysis, model sizes must be limited to those which are reasonable both from an economic and time standpoint. A good example of a system which cannot be fully extended from HF to VHF/UHF is the VOA curtain array. A full-blown analysis of any radiating system using the NEC program or any other similar model is limited in terms of wavelengths of extent of the structure. The in-band HF model was large but not excessive, however, the full model run at the lowest VHF frequency of interest would have proven excessive in computer resource consumption.

V0A SRI LANKA CURTAIN ARRAY/TCI 611


ELEVATION PATT/PERF GND/ 8.00 MHZ



O = (TCI Data -3 dB)

Figure 1a. NEC VERSUS TCI HF ARRAY MODEL

VOR SRI LANKA CURTAIN ARRAY/TCI 611
AZ PATT/10 DEG EL ANG/PERF GND/8.00MHZ



○ = (TCI Data -3 dB)

Figure 1b. NEC VERSUS TCI HF ARRAY MODEL
(Bi-directional azimuth pattern)

To bound the VHF/UHF radiation, a vertical and a horizontal four element "cell" was run and validated at HF, then exercised at VHF/UHF. The HF cell model agreed as expected with the full model. When run at VHF/UHF the vertical and horizontal cells yielded 8 dB and 15 dBi gains respectively, resulting in:

$$\frac{8 + 15}{2} = 11.5 \text{ dBi peak gain for the array.}$$

The average gain was approximately -7.5 dBi.

F. THE TRANSMISSION LINE MODEL

A 2000' long line was modeled (no bends were assumed) to determine the attenuation and radiation characteristics out-of-band at VHF/UHF. The attenuation per wavelength and total attenuation for a 2000' run were calculated and found to dominate the radiation from the line at lower frequencies. At UHF, radiation patterns were examined and found to produce 12 dBi peak and -7 dBi average gain. The following table summarizes the NEC modeling:

<u>Frequency</u>	<u>Attenuation/λ</u>	<u>Total Attenuation (2000')</u>
75 MHz	0.04 dB	6 dB
120 MHz	0.045 dB	11 dB
330 MHz	0.06 dB	40 dB*
1200 MHz	2.2 dB	-- *

* = Radiation Dominates (12 dBi peak/-7 dBi average)

G. GEOMETRY OF THE AIRPORT/ANTENNA FARM

Figure 2 demonstrates the lines of bearings for the VOA arrays (320°, 350°, and 10° to 50°T) fairly well cover the airport runway and flight path. The closest distance to the flight path is one mile and the airport runway is at three miles. The worst case free space path loss calculated at one and three miles provides a range of possible values for interference calculations:




Figure 2. AIRPORT AND ANTENNA FARM

FREE SPACE LOSS

	<u>75 MHz</u>	<u>120 MHz</u>	<u>330 MHz</u>	<u>1200 MHz</u>
at 1 mile	-73 dB	-78 dB	-86 dB	-97 dB
at 3 miles	-83 dB	-88 dB	-96 dB	-107 dB

H. PREDICTED INTERFERENCES

1. HF Transmitter Emissions (-60 dB below output)

With 250 KW per transmitter and two transmitter per antenna, three antennas per site, the range of emitted VHF/UHF power runs from:

0.25 watts (-6 dBW) to 3.0 watts (+5 dBW)

2. Interference Equation

$$S_{\text{Receiver}} = P_{\text{Transmitter}} + G_{\text{Antenna or Transmission Line}} - L_{\text{Free Space}} - L_{\text{Transmission Line}} +$$

$\frac{\text{dBW}}{\text{M}^2}$

$4\pi - \lambda^2$ dB
 Effective Aperture Factor

where

S is Power Density,

P is Power,

G is Gain (radiation),

and L is Loss, all in decibels.

NOTE: Transmission line losses are actually long-wire type radiation losses or energy leakage along the line.

3. Interference Margins

When the interference power balance equation is exercised, considering ranges of values for some of the terms, the predicted range of received power densities is obtained. Comparing this to the allowable signal levels results in acceptable performance from an interference viewpoint, or from an interference margin (unacceptable).

The following limits are calculated for the conditions of one transmitter, three mile distance and average gains, as a best case and six transmitters, one mile distance and peak gains as the worst case. Thus, the values listed in the table cover the range of possible levels based on the data available at this time.

Frequency Band	Interference Margin
MHz	dB
75	+11.5 to +15.5
120	+37 to +77
330	+10.5 to +50.5
1200	-15.5 to +24.5

I. RECOMMENDATIONS

The rather dismal prospects for coexistence of the HF relay station and the airport avionics are readily apparent. There is only a slight possibility that some 1200 MHz equipment safety margins could be obtained. The Voice of America should not consider this site for the HF relay station.

DISTRIBUTION LIST

	<u>No. of copies</u>
1. International Communications Agency Code VOA/EPML ATTN: Ray Ulrich Washington, DC 20547	10
2. Dudley Knox Library (Code 0212) Naval Postgraduate School Monterey, CA 93940	2
3. Defense Technical Information Center Cameron Station, Building 5 Alexandria, VA 22314	2
4. Officer of Research (Code 012A) Naval Postgraduate School Monterey, CA 93940	1
5. Adjunct Professor Stephen Jauregui (Code 62Ja) Electrical Engineering Department Naval Postgraduate School Monterey, CA 93940	2
6. Dr. Richard W. Adler (Code 62Ab) Electrical Engineering Department Naval Postgraduate School Monterey, CA 93940	5

