

AD-A108 364

NAVAL RESEARCH LAB WASHINGTON DC  
ON DIGITAL PROCESSING VIA PDQ FACTORIZATION.(U)  
NOV 81 P BEY, C C YANG

F/G 5/8

UNCLASSIFIED


NRL-NR-4669

NL

1 of 1  
AD A  
108 364



END  
DATE  
FILMED  
01-82  
DTIC



MICROSCOPY RESOLUTION TEST CHART  
NBS 1010-A

AD A 1 0 6 3 8 4

97 Mar 1981

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

| REPORT DOCUMENTATION PAGE  |  | READ INSTRUCTIONS<br>BEFORE COMPLETING FORM   |  |
|--|--|---|--|
| 1. REPORT NUMBER<br>14 NRL-MF-<br>NRL Memorandum Report 4669   | 2. GOVT ACCESSION NO.<br>AD-A108364  | 3. RECIPIENT'S CATALOG NUMBER                 |  |
| 4. TITLE (and Subtitle)<br>ON DIGITAL PROCESSING VIA PDQ FACTORIZATION   | 5. TYPE OF REPORT & PERIOD COVERED<br>Preliminary report on a continuing<br>NRL problem.   | 6. PERFORMING ORG. REPORT NUMBER              |  |
| 7. AUTHOR(s)<br>P/Bey and C. C. Yang   | 8. CONTRACT OR GRANT NUMBER(s)   |   |  |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS<br>Naval Research Laboratory<br>Washington, DC 20375   | 10. PROGRAM ELEMENT, PROJECT, TASK<br>AREA & WORK UNIT NUMBERS<br>NRL Problem 79-0719-0-2<br>Program Element 61153N14<br>RR014024101 |   |  |
| 11. CONTROLLING OFFICE NAME AND ADDRESS  | 12. REPORT DATE<br>November 30, 1981   | 13. NUMBER OF PAGES<br>13                     |  |
| 14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)<br>16 R.F. 2402<br>17 R.F. 240041  | 15. SECURITY CLASS. (of this report)<br>Unclassified   | 15a. DECLASSIFICATION/DOWNGRADING<br>SCHEDULE |  |
| 16. DISTRIBUTION STATEMENT (of this Report)<br>Approved for public release; distribution unlimited.  |  |   |  |
| 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)   |  |   |  |
| 18. SUPPLEMENTARY NOTES  |  |   |  |
| 19. KEY WORDS (Continue on reverse side if necessary and identify by block number)<br>Digital images Rank<br>Pictorial database Approximation<br>Matrices<br>PDQ factorization   |  |   |  |
| 20. ABSTRACT (Continue on reverse side if necessary and identify by block number)<br>In this preliminary report, we present a computer program called MAT for implementing the PDQ factorization for digitized images of large pictorial data base. Within a mini-computer particular emphasis has been placed on the study of the efficiency of the algorithm in the storage and process of the images. |  |   |  |

DD FORM 1473 1 JAN 73

EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

1 201951

CONTENTS

I. INTRODUCTION ..... 1

II. ANALYSIS OF PDQ FACTORIZATION ..... 1

III. DESCRIPTION OF THE MATRIX FACTORIZATION SOFTWARE ..... 4

IV. TEST RESULTS ..... 4

V. PDQ FACTORIZATION FOR BLURRED IMAGES ..... 4

VI. CONCLUDING REMARKS ..... 6

VII. LIST OF PROGRAMS ..... 6

ACKNOWLEDGEMENT ..... 11

REFERENCES ..... 11

|                     |                                     |
|---------------------|-------------------------------------|
| Accession For       |                                     |
| NTIS GRA&I          | <input checked="" type="checkbox"/> |
| DTIC TAB            | <input type="checkbox"/>            |
| Unannounced         | <input type="checkbox"/>            |
| Justification       |                                     |
| By _____            |                                     |
| Distribution/ _____ |                                     |
| Availability Codes  |                                     |
| Dist                | Avail and/or Special                |
| A                   |                                     |

PRECEDING PAGE BLANK-NOT FILMED

## ON DIGITAL PROCESSING VIA PDQ FACTORIZATION

### I. Introduction

This report discusses a method of compressing data bases that describe large digital images. The ultimate objective of such a procedure is to effect savings in computer memory required to process images and to decrease the amount of data necessary to transmit images over a communication channel.

A digital picture (of photograph or video image) can be represented as a matrix consisting of rectangular blocks of size  $m \times n$  where  $m$  and  $n$  are the number of pels (picture elements) in the horizontal and vertical directions, respectively. To process such a picture most effectively (in terms of processing time and quantities of the pictures) by a computer, it is desirable that the main memory of the computer, during the computation, has enough capacity for storage of the entries of the whole image matrix. Unfortunately, this is not the case for most modern minicomputers. Therefore, different adaptive techniques have been devised to cope with this situation. For instance, C. B. Moler and G. W. Stewart [2] described a matrix factorization, the so called PDQ factorization technique and applied it to image representation. The factorization is closely related to SVD (singular value decomposition technique developed by H. C. Andrews and C. L. Patterson [1]). The merit of PDQ factorization over SVD is that it requires, during computation, much less arithmetic and the entire matrix need not be stored in the main memory.

We have applied the PDQ factorization technique to various digitized pictures, and studied their approximations by different ranks with fixed initial column vector and observed the relationships between initial column vectors  $P_i$  and resolution of the approximated image with fixed rank.

In the implementation of PDQ factorization, we have developed a computer program called MATRXVAX written in Fortran. This program is described in some detail.

### II. Analysis of PDQ Factorization

Specifically, the PDQ factorization aims to express a matrix  $A$  with  $m$  rows and  $n$  columns as

$$A = PDQ^T, \quad (E)$$



$$R(m, n, r) = \frac{mr+2r+nr}{mr} .$$

Particularly, when  $m = n$ , we have

$$R(m, n, r) = \frac{2nr+2r}{n^2}$$

clearly in order to save storage it is necessarily that  $2nr < n^2$ .

That is

$$2r < n.$$

Thus PDQ decomposition will provide significant saving of storage and/or transmitting time if  $r$  is chosen much smaller than  $n$ .

It seems that, in general, for a matrix of low rank (its corresponding image is of relatively low detail), the PDQ factorization will be effective in processing and restoring the picture. In practice, it is not clear how to choose the value of  $r$  in order to have an efficient representation of a picture  $A_n$  with less computer storage and processing time. However, from our experiments, so far,  $\frac{n}{4}$  seems to be a suitable threshold for the reduced rank  $r$ . Of course, the properties that lead to such low numerical rank remain to be studied.

Recall that [1] Andrews defines a condition number  $C_R(G) = d_1/d_k$  in the discussion of the potentially efficient representation of the image (picture) in terms of its eigenimages, where  $G$  is the original picture (matrix),  $d_1$  is the maximal eigenvalue, and  $d_k$  the minimal eigenvalue ( $\neq 0$ ) in the SVD decomposition for  $G$ .

Similarly, we would like to define in PDQ factorization a condition number for reduced matrix of rank  $k$ :  $C_k(A) = \text{Max}\{d_i, g_i, i = 1, 2, \dots, k\}$ ,

$$\text{where } d_i = \max\{\alpha_1, \alpha_2, \dots, \alpha_i\} / \min\{\alpha_1, \alpha_2, \dots, \alpha_i\}$$

$$\text{and } g_i = \max\{\beta_1, \beta_2, \dots, \beta_i\} / \min\{\beta_1, \beta_2, \dots, \beta_i\}$$

A threshold for  $r$  values would be a value of  $k$  such that both  $C_k(A)$  and  $C_{k+1}(A)$  as well as their difference are large (of course, here the quantity of largeness remains to be decided). Another way that one may measure the closeness between  $A$  and  $A_r$  is by defining the quantity

$$D(A, A_r) = 1 - \frac{\sum_{i=1}^{r-1} |\alpha_i| + \sum_{j=1}^{r-1} |\beta_j|}{\sum_{i=1}^n |\alpha_i| + \sum_{j=1}^n |\beta_j|}$$

Clearly if  $r = n$ , then  $D(A, A_r) = 0$ . Therefore a threshold that one may consider for the approximated value  $r$  is to require  $D(A, A_r)$  to be sufficiently small. We hope to extend our efforts to include the study of the threshold of  $r$  values in our next report.

### III. Description of the Matrix Factorization Software.

Because of the limited memory of the NOVA 800, our principal computing tool, factorization of the image matrix is accomplished by the program MATRXVAX running on the VAX 11/780. A formatted image disk file 'MATAF' is created by the program VAXDATA on the NOVA 800 and written onto a magnetic tape by the program MAGTAP using a blocking factor equal to 1. Program MATRXVAX (1) reads the image magnetic tape file into memory on the VAX, (2) factors the image matrix into the matrices  $P, D$  and  $Q^T$  of specified rank  $r$  (3) reconstruct the image  $PDQ^T$  onto a magnetic file and (4) writes the matrices  $P, D$  and  $Q^T$  onto a magnetic tape file.

The image and matrix magnetic tape files created by VAX are written into disk files 'MATAFIN' and 'MATP', respectively, by the Program MAGTAP on the NOVA 800. The program WRMATAFIN writes the reconstructed image stored in 'MATAFIN' on the COMTAL CRT and the program XCOMT writes the COMTAL disk file onto magnetic tape. Images of rank  $r_1$ , where  $r_1 \leq r$  are written either on the COMTAL CRT by the program XMTCT or Optronics C-4300 Colorwriter by the Image Writing Software System PWREC.

### IV. Test Results (Pictures)

#### V. PDQ Factorization for Blurred Images

Denote the original image by  $A$  (without loss of generality, we may assume  $A$  is a square matrix). Suppose that the noise is modelled by the presence of two unknown matrices  $N_1$  and  $N_2$  such that for any given image  $A$ ,  $B = N_1 A + N_2$  will be the blurred image of  $A$ . In order to apply PDQ factorization to  $A$ , we first have to determine the two unknown matrices. To do this we use identity matrices  $I$  and  $2I$  to define

$$B_1 = N_1 I + N_2 \text{ and } B_2 = 2N_1 I + N_2.$$

Then  $B_1$  and  $B_2$  are the two known matrices. Therefore  $N_1 = B_2 - B_1$  and  $N_2 = 2B_1 - B_2$ . Once  $N_1$  and  $N_2$  are obtained and stored, then for each blurred image  $B$ , we apply  $N_1^{-1} (B - N_2)$  (provided that  $N_1^{-1}$  exists). We get the original image  $A$  and then proceed with PDQ factorization.




RANK 256



RANK 64



RANK 32



RANK 16

## VI. Concluding Remarks

The above results will be used for further exploration of the PDQ factorization to digital images. As part of this work efficiency of factorization needs to be improved.

So far, we have seen, through some tests that the PDQ factorization did provide significant saving of storage as well as processing time in the representation of some ordinary pictures. We hope that further research will shed some light on the underlying theory. Our next topics of studies will be (i) properties of images (matrices) whose PDQ factorizations produce good (effective) approximations (i.e., the effective numerically reduced rank  $r$  is much less than the rank  $n$  of the original matrix, say, rank  $r$  less than  $n/4$ ). (ii) Applying PDQ factorization to the enhancement of the images.

## VII. List of Programs

```
*****  
VAXDATA  
08/28/81 10:35:28  
CURRENT DIR. YANG  
*****
```

```
C      PDQS FILE NAME=VAXDATA  
C      INPUT DATA TO VAX FROM TAPE  
      PARAMETER N=128,M=256  
      DIMENSION IA(N),P(M),IB(M)  
      COMMON/PPAP/A,B  
      DATA A,B/0.,1./  
      PF(X)=A*X+B  
      ACCEPT 'MATRIX DIMENSION = ',NA  
      ACCEPT 'MATRIX RANK = ',NR  
      CALL OPEN(2,'MATAF',2,IER)  
      WRITE(2,10)NA,NR  
10     FORMAT(1X,2(I3,1X))  
      ACCEPT 'TAPE FILE NUMBER = ',NFILE  
      I2=NA/8  
      ICNT=0  
      IF(NFILE.EQ.0)GO TO 100  
      CALL SKFLMT(IER,NFILE)  
100    ILL=0  
      CALL READMT(IER,IA,ILL)  
      IF(IEK.NE.5)GO TO 120  
110    DO 130 J=1,NA  
      IB(J)=0  
130    CONTINUE  
      GO TO 125  
120    CALL FNLN(IA,IB,NA/2)  
125    DO 20 I=1,I2  
      K1=(I-1)*8+1  
      K2=K1+7  
      WRITE(2,30)(IB(L),L=K1,K2)  
30     FORMAT(1X,8(I6,2X))  
20     CONTINUE  
      ICNT=ICNT+1  
      IF(ICNT.EQ.NA)GO TO 100  
      IF(IEK.EQ.5)GO TO 110  
      GO TO 100  
100    CONTINUE  
      DO 50 J=1,NA  
      P(J)=PF(FLOAT(I))
```

```

50 CONTINUE
   DO 60 I=1,I2
   K1=(I-1)*8+1
   K2=K1+7
   WRITE(2,70) (P(L),L=K1,K2)
70  FORMAT(1X,8(F6.8,1X))
60  CONTINUE
   CALL CLOSE(2,IER)
   STOP
   END

```

\*\*\*\*\*  
MTRXVAX

08/28/81 18147146  
CURRENT DIR. YANG

\*\*\*\*\*

```

C  KODS FILE NAME: MTRXVAX
C  MATRIX FACTORIZATION
   PARAMETER N=10,NRR=10
   COMMON/MATR/ Q(N,NRR),P(N,NRR),PT(N),QT(N),PTI(N),QTI(N),
   IALPHA(N),BETA(N),IAR(N,N),IA(N,N)
X  OPEN(UNIT=21,TYPE='OLD',FILE='MATA.DAT')
X  OPEN(UNIT=23,TYPE='NEW',FILE='MATAF.DAT')
X  OPEN(UNIT=24,TYPE='NEW',FILE='MATP.DAT')
   READ(21,40) NA,NR
40  FORMAT(2(I3,1X))
   DO 420 J=1,256
   DO 410 I=1,32
   K1=(I-1)*8+1
   K2=K1+7
   READ(21,430) (IA(L,J),L=K1,K2)
430  FORMAT(8(I6,2X))
410  CONTINUE
420  CONTINUE
   DO 440 I=1,32
   K1=(I-1)*8+1
   K2=K1+7
   READ(21,450) (P(L,1),L=K1,K2)
450  FORMAT(8(F6.8,1X))
440  CONTINUE
   BETA(1)=0.
   SUM=0.
   DO 2 I=1,NA
   SUM=SUM+P(I,1)*P(I,1)
2  CONTINUE
   SUM=SQRT(SUM)
   DO 4 I=1,NA
   P(I,1)=P(I,1)/SUM
4  CONTINUE
   DO 20 I=1,NA
   SUM=0.
   DO 10 K=1,NA
   SUM=SUM+FLOAT(IA(K,I))*P(K,1)
10  CONTINUE
   Q(I,1)=SUM
20  CONTINUE
   SUM=0.
   DO 30 I=1,NA
   SUM=SUM+Q(I,1)*Q(I,1)
30  CONTINUE
   ALPHA(1)=SQRT(SUM)
   DO 40 I=1,NA
   Q(I,1)=Q(I,1)/ALPHA(1)

```

```

40  CONTINUE
    J=J+1
50  IF(J.GT.NR)GO TO 230
    DO 70 J2=1,NA
    SUM=0.
    DO 60 K=1,NA
    SUM=SUM+FLOAT(IA(J2,K))*Q(K,J-1)
60  CONTINUE
    PT(J2)=SUM-ALPHA(J-1)*P(J2,J-1)
70  CONTINUE
    K2=J-1
    DO 100 J2=1,NA
    SUM1=0.
    DO 90 K=1,K2
    SUM=0.
    DO 80 JJ=1,NA
    SUM=SUM+PT(JJ)*P(JJ,K)
80  CONTINUE
    SUM1=SUM1+SUM*P(J2,K)
90  CONTINUE
    PTI(J2)=PT(J2)-SUM1
100 CONTINUE
    SUM=0.
    DO 110 I=1,NA
    SUM=SUM+PTI(I)*PTI(I)
110 CONTINUE
    BETA(J)=SQRT(SUM)
    DO 120 I=1,NA
    P(I,J)=PTI(I)/BETA(J)
120 CONTINUE
    DO 170 J2=1,NA
    SUM=0.
    DO 160 K=1,NA
    SUM=SUM+FLOAT(IA(K,J2))*P(K,J)
160 CONTINUE
    QT(J2)=SUM-BETA(J)*Q(J2,J-1)
170 CONTINUE
    K2=J-1
    DO 200 J2=1,NA
    SUM1=0.
    DO 190 K=1,K2
    SUM=0.
    DO 180 JJ=1,NA
    SUM=SUM+QT(JJ)*Q(JJ,K)
180 CONTINUE
    SUM1=SUM1+SUM*Q(J2,K)
190 CONTINUE
    QTI(J2)=QT(J2)-SUM1
200 CONTINUE
    DO 210 I=1,NA
    SUM=SUM+QTI(I)*QTI(I)
210 CONTINUE
    ALPHA(J)=SQRT(SUM)
    DO 220 I=1,NA
    Q(I,J)=QTI(I)/ALPHA(J)
220 CONTINUE
    GO TO 50
230 CONTINUE
    DO 330 K=1,NA
    DO 320 I=1,NA
    SUM=0.
    DO 310 J=1,NR
    SUM=SUM+P(I,J)*ALPHA(J)*Q(K,J)
    IF(J.EQ.1)GO TO 310
    SUM=SUM+P(I,J)*BETA(J)*Q(K,J-1)
310 CONTINUE
    IAR(I,K)=IFIX(SUM)
320 CONTINUE
    DO 350 J1=1,250

```

```

DO 330 I1=1,32
K1=(I1-1)*8+1
K2=K1+7
431 WRITE(23,431)(IAR(L,J1),L=K1,K2)
330 FORMAT(1X,8(I9,2X))
CONTINUE
X
ACCEPT 340,JYN
READ(11,340)JYM
340 FORMAT('CONTINUE? (1=YES,0=NO) ',I3)
IF(JYN,EQ,0)GO TO 360
X
ACCEPT 350,NR1
READ(11,350)NR1
350 FORMAT('MATRIX RANK = ',I3)
360 CONTINUE
I2=NR/4
DO 370 I=1,I2
K1=(I-1)*4+1
K2=K1+3
WRITE(24,380)(ALPHA(L),L=K1,K2)
WRITE(24,380)(BETA(LL),LL=K1,K2)
380 FORMAT(1X,4(E12,6,1X))
370 CONTINUE
NR2=NR/4
DO 400 J=1,256
DO 400 I=1,NR2
K1=(I-1)*4+1
K2=K1+3
WRITE(24,380)(P(J,L),L=K1,K2)
WRITE(24,380)(Q(J,LL),LL=K1,K2)
400 CONTINUE
IF(JYN,EQ,H)GO TO 390
NR=NR1
GO TO 230
390 CONTINUE
X
CLOSE(UNIT=21,DISPOSE='DELETE')
X
CLOSE(UNIT=23,DISPOSE='SAVE')
X
CLOSE(UNIT=24,DISPOSE='SAVE')
STOP
END

```

\*\*\*\*\*  
WRTMATAFIN

08/28/81 18:48:17  
CURRENT DIR, YANG

\*\*\*\*\*

```

C
C RUOS FILE NAME: WRTMATAFIN
C WRITES IMAGE FROM VAX
C NOTE: WHEN FORMAT WRITTEN WITH (1X, ) TO VAX
C WORD MUST BE READ WITH NOVA USING (1X, ) FORMAT
C WORD MUST BE READ WITH VAX USING ( ) FORMAT
C I.E. 1X, DELETED FROM FORMAT STATEMENT
C PARAMETER N=512,M=256
C DIMENSION IA(N),IB(M)
C CALL OPEN(1,'MATAFIN',2,IER)
C CALL UPENCT(IER)
C ACCEPT 'TO IMAGE # = ',IOUT
C ACCEPT 'DISPLAY CODE = ',ICODE
C ACCEPT 'MATRIX DIMENSION = ',NA
C CALL DSPL(IER,ICODE)
C DO 20 J=1,256
C DO 10 I=1,32
C K1=(I-1)*8+1
C K2=K1+7

```

```

X READ(1,30)(IA(L),L=K1,K2)
WRITE(10,30)(IA(LL),LL=K1,K2)
30 FORMAT(1X,0(I0,2X))
DO 40 M=K1,K2
IF(IA(M).LT.0)IA(M)=0
IF(IA(M).GT.255)IA(M)=255
40 CONTINUE
10 CONTINUE
CALL PACK(IA,IB,NA)
CALL MTIMAGE(IER,IOUT,J,IB,-NA/2)
20 CONTINUE
CALL CLOSE(1,IER)
STOP
END

```

\*\*\*\*\*  
MATPQTP  
\*\*\*\*\*

08/28/81 10:40:30  
CURRENT DIR. YANG  
\*\*\*\*\*

```

C HDUS FILE NAME:MATPQTP
C IMAGE CONVERSION BY MULTIPLICATION OF P,Q AND D
C MATRIX RANK NR0 RUN ON VAX MUST BE MULTIPLE OF 4
PARAMETER N=1024,M=2048,NN=256,NM=128
DIMENSION P(N),Q(N),ALPHA(NN),BETA(NN),IA(NN),IB(NM)
COMMON/INTS1/IP(M)
COMMON/INTS2/IQ(M)
EQUIVALENCE (IP(1),P(1)),(IQ(1),Q(1))
ACCEPT 'NEW RUN?' (1=YES,0=NO) = ',JYN
ACCEPT 'MAX MATRIX RANK NR0 = ',NR0
ACCEPT 'MATRIX RANK = ',NR
ACCEPT 'IO MT01',IFL
CALL OPEN(3,'MATP',2,IER)
NLines=1024/NR0
NTRANS=NR0/4
NWD5=1024
NBLK5=8
I2=NR0/4
DO 30 I=1,I2
K1=(I-1)*4+1
K2=K1+3
READ(3,20)(ALPHA(L),L=K1,K2)
READ(3,20)(BETA(L),L=K1,K2)
20 FORMAT(1X,4(E13,0,1X))
30 CONTINUE
IF(JYN.EQ.0)GO TO 32
CALL CFILW('PHAT',3,200,IER)
IF(IER.NE.1)TYPE 'FILE ERROR'
CALL CFILW('QMAT',3,200,IER)
IF(IEK.NE.1)TYPE 'FILE ERROR 2'
32 CALL OPEN(1,'PHAT',2,IER)
CALL OPEN(2,'QMAT',2,IER)
IF(JYN.EQ.0)GO TO 52
IMAX=NWD5/4
DO 50 J=1,NTRANS
DO 40 I=1,IMAX
K1=(I-1)*4+1
K2=K1+3
READ(3,20)(P(L),L=K1,K2)
READ(3,20)(Q(LL),LL=K1,K2)
40 CONTINUE
CALL NRBLK(1,(J-1)*NBLK5,IP,NBLK5,IER)
CALL NRBLK(2,(J-1)*NBLK5,IQ,NBLK5,IER)
X TYPE 'IP(I),I=1,32 ',(IP(IXX),IXX=1,32)
X TYPE 'IQ(I),I=1,32',(IQ(IXXX),IXXX=1,32)

```

```

50  CONTINUE
52  CUNTINUE
    CALL RLSE('MTB',IER)
    CALL INIT('MTB',IER)
    IF(IFL.EQ.0)GO TO 200
    CALL SKFLMT(IER,IFL)
200  CONTINUE
    DO 160 K=1,NTRANS
    CALL ROBLK(2,(K-1)*NBLKS,IQ,NBLKS,IER)
    DO 160 K1=1,NLINES
    KJ=(K1-1)*NRB
    I1=0
    DO 150 I=1,NTRANS
    CALL ROBLK(1,(I-1)*NBLKS,IP,NBLKS,IER)
    DO 150 I1=1,NLINES
    IJ=(I1-1)*NRB
    SUM=0.
    DO 140 J=1,NK
    SUM=SUM+P(IJ+J)*ALPHA(J)*U(KJ+J)
    IF(J.EQ.1)GO TO 140
    SUM=SUM+P(IJ+J)*BETA(J)*Q(KJ+J-1)
140  CONTINUE
    II=II+1
    IA(II)=IFIX(SUM)
    IF(IA(II).LT.0)IA(II)=0
    IF(IA(II).GT.255)IA(II)=255
150  CONTINUE
    CALL PACK(IA,IB,256)
    CALL WRITMT(IER,IB,-120)
160  CUNTINUE
    CALL XTENDF(IER)
    CALL CLOSE(1,IER)
    CALL CLOSE(2,IER)
    CALL CLOSE(3,IER)
    CALL RLSE('MTB',IER)
    STOP
    END

```

#### Acknowledgement

We would like to thank Dr. Warren W. Willman for his assistance in running the program MATXVAX on VAX 11/780. Also thanks to Dr. Igor Jurkevich for his helpful suggestions as to the form of this report.

#### References

- [1] H. C. Andrews and C. L. Patterson, Outer product expansion and their uses in Digital Image Processing, Amer. Math. Monthly, Vol. 1, No. 82, June 1975, pp. 1-13.
- [2] C. B. Moler & G. W. Stewart, An Efficient Matrix Factorization for Digital Image Processing, LASL Tech. Report, LA-7637-MS, 1979.

