

AD A109299

LEVEL

12

Office of Naval Research
Contract N00014-76-0060 NR 064-478
Technical Report No. 42

FURTHER STUDIES ON DYNAMIC CRACK CURVING

by

Y.-J. Sun, M. Ramulu, A. S. Kobayashi and B. S.-J. Kang

November 1981

The research reported in this technical report was made possible through support extended to the Department of Mechanical Engineering, University of Washington, by the Office of Naval Research under Contract N00014-76-C-0060 NR 064-478. Reproduction in whole or in part is permitted for any purpose of the United States Government.

Department of Mechanical Engineering
College of Engineering
University of Washington

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

400244
82 01 05 005

DTIC FILE COPY

DTIC
SELECTED
JAN 6 1982
H

FURTHER STUDIES ON DYNAMIC CRACK CURVING

Y.-J. Sun*, M. Ramulu, A. S. Kobayashi and B. S.-J. Kang

University of Washington
Department of Mechanical Engineering
Seattle, Washington 98195

The elasto-dynamic stress field surrounding rapidly propagating cracks in thin polycarbonate, double edged crack tension specimens were analyzed by dynamic photoelasticity using a 16-spark gap Cranz-Schardin camera system. Crack curving was observed in two slanted double edged crack specimens and in two offset parallel double edged crack specimens. In another test, the crack ran straight between two symmetrically located twin cracks. Results of these five tests were used to verify the dynamic crack curving criterion by Ramulu et al. in which a reference distance of

$$r_0 = 1/128 \pi [K_I / \sigma_{max} V(c, c_1, c_2)]^{** 2}$$

from the crack tip is incorporated into the maximum circumferential stress or minimum strain energy density criteria. The critical material property for crack curving in this thin polycarbonate sheet was found to be about $r_c = 0.5$ mm.

Revision For S. GRAXI TIC TAB Unannounced Justification	By Distribution/ Available Lib. Codes Date Rec'd	A
---	---	---

*On leave from Northern Jiao-Tong University, Beijing, Peoples Republic of China.

INTRODUCTION

In a paper in 1963, Erdogan and Sih [1] used the orientation of maximum circumferential stress to predict crack extension of inclined cracks in tension specimens. This mixed mode crack extension criterion, commonly referred to as the maximum circumferential stress criterion, was later advanced among others by Williams and Ewing [2] and Finnie and Saith [3]. More recently, Streit and Finnie [4] incorporated the second order term, $\sigma_{\theta\theta}$, in the crack tip stress field and proposed a crack curving criterion based on the directional stability of a mode I crack propagation. This stability criterion introduced another critical material parameter, r_c , which is the radial distance from the crack tip. The second order term of $\sigma_{\theta\theta}$ was also used by Cotterell and Rice [5] for predicting the crack curving direction of a slightly curved crack. Historically, Yoffe was the first to use the maximum circumferential stress theory to explain surface roughening and crack branching of a rapidly propagating crack in 1951 [6].

As a natural extension of Griffith's energy release rate, Hussain et al. [7], Palaniswamy and Knauss [8] among others predicted the direction of crack kinking based on the maximum energy release criterion. Focusing directly on energy, Sih [9] predicted that the crack would kink in the direction of the minimum strain energy density factor, S . In an early critique of 1976, Swedlow [10] concluded that the difference between the crack kinking angle predicted by the maximum circumferential stress criterion and the minimum strain energy density criterion "are modest at most". Theocaris and Andrianopolous [11] recently modified the S theory and designated the mean value of S , a critical material value for crack extension. Sih [12] also applied the minimum S theory to predict crack kinking of a dynamic crack.

Ramulu et al., in a recent paper [13], incorporated the second order term of $\sigma_{\theta\theta}$ in the dynamic crack tip stress field and then derived the dynamic counterpart of the crack stability model based on the maximum circumferential stress criterion as well as the minimum strain energy density factor. This dynamic crack curving criterion was used to evaluate nine dynamic photoelasticity tests involving curved as well as straight propagating cracks in fracturing Homalite-100 specimens. The critical material property of r_c was found to be 1.3 mm for the Homalite-100 specimens investigated. More importantly, the crack curving directions predicted by either the maximum circumferential stress theory or the minimum strain energy density theory were generally within 1 degree of each other for the relatively low crack velocities observed in these tests. The sign of $\sigma_{\theta\theta}$ was also found to influence significantly the crack angle of a running crack. The purpose of this paper is to provide further evidence in support of the dynamic crack curving criterion advanced by Ramulu et al.

DYNAMIC CRACK CURVING CRITERIA

Maximum Circumferential Stress Criterion

The maximum circumferential stress criterion, as modified by Ramulu et al. [13], assumes that the crack will extend towards the maximum circumferential stress which reached its critical value at a critical distance, r_c , away from the rapidly propagating crack tip. r_c is a characteristic distance derivable from the crack stability criterion

involving the second order term of σ_{max} in the dynamic crack tip stress field. This characteristic distance is [13].

$$r_0 = 1/128/\pi * [K_I / \sigma_{\text{max}} * V(c, c_1, c_2)]^{**2}$$

where K_I is the dynamic stress intensity factor.

σ_{max} is the second order term in the dynamic stress field and is often referred to as the remote stress component.

c , c_1 and c_2 are the crack velocity, dilatational wave velocity and the shear wave velocity, respectively.

$V(c, c_1, c_2)$ is the dynamic correction factor to the static crack instability criterion and is given in Reference [13].

This crack curving criterion which is the dynamic extension of that by Streit and Finnie [3] can be used to predict the crack curving of a crack propagating under pure mode I as well as mixed mode, i.e. modes I and II, conditions.

Minimum Strain Energy Density Criterion

The minimum strain energy density criterion, as modified by Ramulu et al. [13], also incorporates the characteristic distance of r_0 and thus the second order term of σ_{max} in the strain energy density factor, S , of Sih [9]. Unlike the maximum circumferential stress criterion, the minimum S condition yields a relation between the crack curving angle and r_0 in terms of the given σ_{max} and modes I and II stress intensity factors, K_I and K_{II} . Given r_0 , however, the extended minimum strain energy density criterion with the σ_{max} term can be used to predict crack curving of a mode I static crack or a crack propagating at a low crack velocity.

Homalite-100 Fracture Specimens

The validity of the above two dynamic crack curving criteria were assessed through re-evaluated dynamic photoelasticity results of Homalite-100 fracture specimens [14-18]. r_0 for the minimum S criterion was equated to r_c which was found to be about 1.3 mm for the Homalite-100 data used in evaluating the maximum circumferential stress criterion. For the relatively low crack curving angles of -20 to 25 degrees observed in the nine tests, both the maximum circumferential stress and the minimum strain energy density criteria predicted the fracture angles within 1 degree for most of the 81 data points considered in this investigation [13].

POLYCARBONATE FRACTURE SPECIMENS

In order to further verify the above dynamic crack curving criteria, a series of dynamic photoelastic fracture experiments involving thin polycarbonate fracture experiments were conducted. Specimen configurations and the crack paths in five double edged crack tension specimens with either offset parallel cracks, offset slanted cracks and symmetrically located twin cracks, used in this investigation are shown in Figure 1. The annealed thin polycarbonate specimens with blunt starter cracks exhibited brittle fracture with shear lips less than 10 percent of the thickness and an apparent crack tip yield zone of less than 1.5 mm. The dynamic isochromatics surrounding the propagating crack were recorded with a 16 spark gap Craz-Schardin Camera System.

The isochromatic data were reduced by least square fitting to the recorded dynamic isochromatics a theoretical mixed-mode, dynamic crack tip stress field with disposable parameters of K_I , K_{II} and σ_{max} [19]. The characteristic crack tip distance, r_0 , was then computed by Equation (1). With r_0 known, the predicted crack curving angle can be computed by the maximizing condition for the maximum circumferential stress criterion or the minimizing condition for the minimum S criterion. Details of this data reduction procedure can be found in Reference [20].

RESULTS

As shown in Figure 1, crack always propagated from the longer left crack and curved towards the shorter stationary right crack except for Specimen S2-810519 which involved a symmetrically located twin crack. Also the eccentric loading of Specimens S15-810727 and the longer initial crack length of Specimen S5-810530 caused the rapidly propagating upper crack to intersect with the stationary lower crack at its midcrack length.

Figure 2 shows two typical dynamic isochromatic patterns in a fracturing offset, slanted, double edged crack tension specimen. The right edge crack did not propagate during the entire fracture event. Both frames in Figure 2 show the expanding shear wave front which emanated from the original crack tip of the left edged crack when it started to propagate. Figure 3 shows the variations in K_I , K_{II} , σ_{max} and crack velocity of the upper crack in Figure 2. While the crack velocity and K_I remained essentially constant through the relatively straight propagation of the upper crack, σ_{max} oscillated consistent with previous observations [13].

Figure 4 shows two typical dynamic isochromatic patterns in a fracturing offset, parallel double edged crack specimen. Although the upper crack had cut the specimen in half, the stationary lower crack continued to show a high mode II crack tip stress field in Frame No. 10 of this figure. A similar high mode II crack tip stress field was observed in all stationary cracks during the latter part of crack propagation history. Figure 5 shows the variations in K_I , K_{II} , σ_{max} and crack velocity of the upper crack in Figure 4. The larger excursion in K_I in this figure is associated with the curved crack shown in Figure 4. Figure 6 shows the K_I , K_{II} and σ_{max} of the lower stationary crack in Figure 4. While $K_I = 3 \text{ MPa}\sqrt{\text{m}}$ of this crack was close to the estimated fracture toughness of polycarbonate, the small difference in the crack tip bluntness probably prevented crack propagation of the lower right crack. K_{II} of the stationary crack varied from -8.5 to $0.6 \text{ MPa}\sqrt{\text{m}}$ and is about half of the K_I value. This high value, not commonly observed in previous dynamic photoelastic experiments, is due to the load redistribution caused by the decreasing remaining ligament in the fracturing specimen.

Figure 7 shows typical isochromatics of an edge crack propagating between two symmetrically located twin cracks. High mode II crack tip stress fields are noted in the stationary twin cracks in Frame No. 12 of this figure. Figure 8 shows the variations in K_I , K_{II} , σ_{max} and crack velocity of the propagating left crack. Oscillations in σ_{max} are smaller in this straight crack which is propagating at approximately the same crack velocity of $0.2 \cdot c_1$ as the other cracks.

Figure 9 shows the variations in characteristic distance, r_0 , which was computed by Equation (1), for the propagating cracks in the five tests. r_0 for the curved portion of the rapidly propagating crack is larger than the r_0 of the straight crack. Also r_0 , within the scatter band indicated in Figure 9, always dropped to a minimum value at the onset of crack curving. The

scatter band of the minimum value of r_0 yield an average $r_c=0.5$ mm. This value is consistent with the r_c value estimated by Theocaris [21].

Having estimated the r_c for this thin polycarbonate fracture specimens, the crack curving angle was then estimated either by using the maximum circumferential stress or the minimum S criteria. The results, as summarized in Table 1, show that the predicted and experimentally observed crack curving angles for these five tests were mostly within 1 degree of each other regardless of the crack curving criterion used.

CONCLUSIONS

1. Dynamic crack curving angle under pure mode I and mixed mode I and II conditions can be predicted by using either the extended maximum circumferential stress or the minimum strain energy density criteria.
2. The critical characteristic crack tip distance is $r_c=0.5$ mm for the thin polycarbonate fracture specimens considered in this investigation.

ACKNOWLEDGEMENT

The results reported in this paper were obtained through ONR Contract No. 00014-76-C-0600 NR 64-478. The authors wish to thank Drs. N. Perrone and Y. Rajapske, ONR for their support during the course of this investigation.

REFERENCES


1. Erdogan, F. and Sih, G. C., "On the crack extension in plates under plane loading and transverse shear", Trans. ASME J. Basic Engrg., 85(D), 1963, pp. 519-527.
2. Williams, J. G. and Ewing, P. D., "Fracture under complex stress - The angled crack problem", Int. J. Fracture Mech. 8, 1972, pp. 441-446.
3. Finnie, I. and Saith, A., "A note on the angled crack problem and the directional stability of crack", Int. J. Fracture 9, 1973, pp. 484-486.
4. Streit, R. and Finnie, I., "An Experimental Investigation of Crackpath Directional Stability", Experimental Mechanics, Vol. 20, No. 1, January 1980, pp. 17-23.
5. Cotterell, B. and Rice, J. R., "Slightly Curved or Kinked Cracks", Int. J. Frac., Vol. 11, No. 2, 1981, pp. 155-164.
6. Yoffe, E. H., "The Moving Griffith Crack", Philosophical Magazine, Vol. 42, 1951, pp. 739-750.
7. Hussain, M. A., Pu, S. L. and Underwood, J., "Strain-Energy-Release Rate for a Crack Under Combined Mode I and Mode II", ASTM STP 560, 1974, pp. 2-28.

8. Palaniswamy, K. and Knauss, W. G., "On the Problem of Crack Extension in Brittle Solids Under General Loading", Mechanics Today, edited by S. Nemat-Nasser, Pergamon Press, 1978, pp. 87-148.
9. Sih, G.C., "A Special Theory of Crack Propagation", Methods of Analysis and Solutions of Crack Problems, Vol. 1, pp. 21-45, edited by G. C. Sih, Noordhoff International Publishing, Leyden, 1973.
10. Swedlow, J. L., "Criteria for growth of the angled crack", ASTM STP 601, 1976, pp. 506-521.
11. Theocaris, R. S. and Andrianopoulos, N. P., "A Modified Strain Energy Density Criterion Applied to Crack Propagation", to be published in the ASME Journal of Applied Mechanics.
12. Sih, G. C., "Dynamic Crack Problems: Strain Energy Density Fracture Theory", Elastodynamic Crack Problems, Vol. 4, pp. 17-37, edited by G. C. Sih, Noordhoff International Publishing, Leyden, 1977.
13. Ramulu, M. and Kobayashi, A. S., "Dynamic Crack Curving - A Photoelastic Evaluation", submitted to Experimental Mechanics.
14. Bradley, W. B. and Kobayashi, A. S., "Fracture Mechanics - A Photoelastic Investigation", Engineering Fracture Mechanics, Vol. 3, 1971, pp. 317-322.
15. Wade, B. G. and Kobayashi, A. S., "Photoelastic Investigation on the Crack Arrest Capability of Pretensioned Stiffened Panels", Exp. Mechanics, 15, 1, 1975, pp. 1-9.
16. Kobayashi, A. S., Mall, S. and Lee, M. H., "Fracture Dynamics of Wedge-Loaded Double Cantilever Beam Specimen", Cracks and Fracture, ASTM STP, 601, June 1976, pp. 274-290.
17. Kobayashi, A. S. and Chan, C. F., "A Dynamic Photoelastic Analysis of Dynamic-tear-test Specimen", Experimental Mechanics, Vol. 16, No. 5, May 1976, pp. 176-181.
18. Kobayashi, A. S. and Mall, S., "Dynamic Fracture Toughness of Homalite-100", Experimental Mechanics, 18, 1, Jan. 1978, pp. 11-18.
19. Kobayashi, A. S. and Ramulu, M., "Dynamic Stress Intensity Factor for Unsymmetric Dynamic Isochromatics", Experimental Mechanics, Vol. 21, Jan. 1981, pp. 41-48.
20. Ramulu, M. "Dynamic Crack Curving and Branching", a PhD submitted to the University of Washington, March 1982.
21. Theocaris, P. S., "The Caustic as a Means to Define the Core Region in Brittle Fracture", Engineering Fracture Mechanics, Vol. 12, 1980, pp. 235-242.

TABLE 1

SUMMARY OF EXPERIMENTAL AND THEORETICAL RESULTS

Total Number of Experiments:	5
Type of Fracture Specimens:	Double Edged Crack Specimen
Number of Data Points:	114
Crack Velocity, c/c_I :	About 0.2
K_I (MPa $\sqrt{m}$):	1.5 to 3.2
K_{II} (MPa $\sqrt{m}$):	-0.5 to 0.6
σ_{max}/K_I :	-11.1 to 2.5
r_0 (mm):	0.25 to 0.75
Measured Crack Curving Angle:	-20 to 3 degrees
Predicted Crack Curving Angle:	
Maximum Circumferential Stress:	-19 to 5 degrees
Minimum S:	-18 to 5 degrees




(a) SPECIMEN DIMENSIONS

(b) CRACK PATHS

FIG. 1. POLYCARBONATE DOUBLE EDGED CRACK TENSION SPECIMEN.



FIRST FRAME
6 μ SECONDS



SEVENTH FRAME
28 μ SECONDS

FIG. 2. TYPICAL DYNAMIC PHOTOELASTIC PATTERNS IN POLYCARBONATE SLANTED
DOUBLE EDGED CRACK TENSION SPECIMEN. SPECIMEN NO. S14-810717.






FIG. 3. DYNAMIC STRESS INTENSITY FACTOR, CRACK VELOCITY AND σ_{ox} OF UPPER CRACK OF SPECIMEN NO. S14-810717.



SEVENTH FRAME
150 μ SECONDS



TENTH FRAME
225 μ SECONDS

FIG. 4. TYPICAL DYNAMIC ISOCHROMATICS OF A CURVED CRACK IN A POLYCARBONATE
PARALLEL DOUBLE EDGED OFFSET CRACK TENSION SPECIMEN. SPECIMEN NO.
S3-810526.




FIG. 5. DYNAMIC STRESS INTENSITY FACTOR CRACK VELOCITY AND σ_{ox} OF UPPER CRACK OF SPECIMEN NO. S3-810526.




FIG. 6. DYNAMIC STRESS INTENSITY FACTOR AND σ_{ox} OF THE STATIONARY LOWER CRACK OF SPECIMEN NO. S3-810526.



SIXTH FRAME
100 μ SECONDS



TWELFTH FRAME
262 μ SECONDS

FIG. 7. TYPICAL DYNAMIC ISOCHROMATICS OF A STRAIGHT CRACK PASSING THROUGH SYMMETRICALLY LOCATED TWIN CRACKS. SPECIMEN NO. S2-810518.




FIG. 8 . DYNAMIC STRESS INTENSITY FACTORS, CRACK VELOCITY AND σ_{ox} OF THE RUNNING CRACK OF SPECIMEN NO. S2-810518.




FIG.9. CHARACTERISTIC DISTANCE r_0 OF PROPAGATING CRACK IN THE POLYCARBONATE DOUBLE EDGED CRACK TENSION SPECIMENS.

474:NP:716:1ab
78u474-619

Part 1 - Government
Administrative and Liaison Activities

Office of Naval Research
Department of the Navy
Arlington, Virginia 22217
Attn: Code 474 (2)
Code 471
Code 200

Director
Office of Naval Research
Branch Office
646 Summer Street
Boston, Massachusetts 02210

Director
Office of Naval Research
Branch Office
516 South Clark Street
Chicago, Illinois 60605

Director
Office of Naval Research
New York Area Office
715 Broadway - 5th Floor
New York, New York 10003

Director
Office of Naval Research
Branch Office
1030 East Green Street
Pasadena, California 91106

Naval Research Laboratory (A)
Code 167
Washington, D.C. 20375

Defense Documentation Center (12)
Cameron Station
Alexandria, Virginia 22316

NAVY

Undersea Explosion Research Division
Naval Ship Research and Development
Center
Norfolk Naval Shipyard
Portsmouth, Virginia 23709
Attn: Dr. E. Palmer, Code 177

NAVY (Con't.)

Naval Research Laboratory
Washington, D.C. 20375
Attn: Code 8400
8410
8430
8440
8300
8390
8380

David M. Taylor Naval Ship Research
and Development Center
Annapolis, Maryland 21402
Attn: Code 2740
28
281

Naval Weapons Center
China Lake, California 93555
Attn: Code 4062
4320

Commanding Officer
Naval Civil Engineering Laboratory
Code L31
Port Hueneme, California 93041

Naval Surface Weapons Center
White Oak
Silver Spring, Maryland 20910
Attn: Code R-10
G-402
E-82

Technical Director
Naval Ocean Systems Center
San Diego, California 92132

Supervisor of Shipbuilding
U.S. Navy
Newport News, Virginia 23607

Navy Underwater Sound
Reference Division
Naval Research Laboratory
P.O. Box 8337
Orlando, Florida 32806

NAVY (Con't.)

Chief of Naval Operations
Department of the Navy
Washington, D.C. 20350
Attn: Code OP-098

Strategic Systems Project Office
Department of the Navy
Washington, D.C. 20376
Attn: NRP-100

Naval Air Systems Command
Department of the Navy
Washington, D.C. 20361
Attn: Code 3202 (Aerospace and Structures)
504 (Technical Library)
3208 (Structures)

Naval Air Development Center
Warminster, Pennsylvania 18974
Attn: Aerospace Mechanics
Code 606

U.S. Naval Academy
Engineering Department
Annapolis, Maryland 21402

Naval Facilities Engineering Command
200 Stovall Street
Alexandria, Virginia 22332
Attn: Code 03 (Research and Development)
048
043
14114 (Technical Library)

Naval Sea Systems Command
Department of the Navy
Washington, D.C. 20342
Attn: Code 05H
312
322
323
05H
32H

NAVY (Con't.)

Commander and Director
David M. Taylor Naval Ship
Research and Development Center
Bethesda, Maryland 20084
Attn: Code 042
17
172
173
174
1800

1844
012.2
1900
1901
1945
1940
1962

Naval Underwater Systems Center
Newport, Rhode Island 02840
Attn: Dr. R. Trainor

Naval Surface Weapons Center
Dahlgren Laboratory
Dahlgren, Virginia 22448
Attn: Code G04
G20

Technical Director
Naval Island Naval Shipyard
Vallejo, California 94592

U.S. Naval Postgraduate School
Library
Code 0184
Monterey, California 93940

Webb Institute of Naval Architecture
Attn: Librarian
Cranston Beach Road, Glen Cove
Long Island, New York 11542

ARMY

Commanding Officer (2)
U.S. Army Research Office
P.O. Box 12211
Research Triangle Park, NC 27709
Attn: Mr. J. J. Murray, CRD-AA-1P

474:NP:716:1ab
78u474-619

ARMY (Con't.)

Watervliet Arsenal
MAGOS Research Center
Watervliet, New York 12189
Attn: Director of Research

U.S. Army Materials and Mechanics
Research Center
Watertown, Massachusetts 02172
Attn: Dr. R. Shad, DUEEN-T

U.S. Army Missile Research and
Development Center
Redstone Scientific Information
Center
Chief, Document Section
Redstone Arsenal, Alabama 35899

Army Research and Development
Center
Fort Belvoir, Virginia 22060

NASA

National Aeronautics and Space
Administration
Structures Research Division
Langley Research Center
Langley Station
Hampton, Virginia 23365

National Aeronautics and Space
Administration
Associate Administrator for Advanced
Research and Technology
Washington, D.C. 20546

Air Force

Wright-Patterson Air Force Base
Dayton, Ohio 45433
Attn: AFPLD (PB)
(PBR)
(PBR)
(PBR)
AFPL (PBR)

Air Force (Con't.)

Chief Applied Mechanics Group
U.S. Air Force Institute of Technology
Wright-Patterson Air Force Base
Dayton, Ohio 45433

Chief, Civil Engineering Branch
W.R.C. Research Division
Air Force Weapons Laboratory
Kirtland Air Force Base
Albuquerque, New Mexico 87117

Air Force Office of Scientific Research
Bolting Air Force Base
Washington, D.C. 20332
Attn: Mechanics Division

Department of the Air Force
Air University Library
Maxwell Air Force Base
Montgomery, Alabama 36112

Other Government Activities

Commandant
Chief, Testing and Development Division
U.S. Coast Guard
1300 E Street, NW.
Washington, D.C. 20226

Technical Director
Marine Corps Development
and Education Command
Quantico, Virginia 22134

Director Defense Research
and Engineering
Technical Library
Room 3C128
The Pentagon
Washington, D.C. 20301

Other Government Activities (Con't.) PART 2 - Contractors and Other Technical Collaborators

Dr. M. Goss
National Science Foundation
Environmental Research Division
Washington, D.C. 20550

Library of Congress
Science and Technology Division
Washington, D.C. 20540

Director
Defense Nuclear Agency
Washington, D.C. 20305
Attn: DPN3

Mr. Jerome Forsh
Staff Specialist for Materials
and Structures
OOSDRA, The Pentagon
Room 3D1089
Washington, D.C. 20301

Chief, Airframe and Equipment Branch
FA-120
Office of Flight Standards
Federal Aviation Agency
Washington, D.C. 20535

National Academy of Sciences
National Research Council
Ship Hull Research Committee
2101 Constitution Avenue
Washington, D.C. 20418
Attn: Mr. A. B. Lytle

National Science Foundation
Engineering Mechanics Section
Division of Engineering
Washington, D.C. 20550

Piscataway Arsenal
Plastics Technical Evaluation Center
Attn: Technical Information Section
Dover, New Jersey 07801

Maritime Administration
Office of Maritime Technology
16th and Constitution Avenue, NW.
Washington, D.C. 20230

Universities

Dr. J. Timley Odom
University of Texas at Austin
345 Engineering Science Building
Austin, Texas 78712

Professor Julius Mikhlin
California Institute of Technology
Division of Engineering
and Applied Sciences
Pasadena, California 91109

Dr. Harold Liebowitz, Dean
School of Engineering and
Applied Science
George Washington University
Washington, D.C. 20052

Professor Eli Sternberg
California Institute of Technology
Division of Engineering and
Applied Sciences
Pasadena, California 91109

Professor Paul M. Naghd
University of California
Department of Mechanical Engineering
Berkeley, California 94720

Professor A. J. Durelli
Oakland University
School of Engineering
Rochester, Missouri 18065

Professor P. L. Dillig
Columbia University
Department of Civil Engineering
New York, New York 10027

Professor Norman Jones
The University of Liverpool
Department of Mechanical Engineering
P. O. Box 147
Brownlow Hill
Liverpool L69 3BX
England

Professor E. J. Shudrath
Pennsylvania State University
Applied Research Laboratory
Department of Physics
State College, Pennsylvania 16801

Universities (Con't.)

Professor J. Klesner
Polytechnic Institute of New York
Department of Mechanical and
Aerospace Engineering
333 Jay Street
Brooklyn, New York 11201

Professor R. A. Schapery
Texas A&M University
Department of Civil Engineering
College Station, Texas 77843

Professor Walter B. Pilkey
University of Virginia
Research Laboratories for the
Engineering Sciences and
Applied Sciences
Charlottesville, Virginia 22901

Professor E. D. Willmert
Clarkson College of Technology
Department of Mechanical Engineering
Potomac, New York 13676

Dr. Walter E. Mateler
Texas A&M University
Aerospace Engineering Department
College Station, Texas 77843

Dr. Hussein A. Kameel
University of Arizona
Department of Aerospace and
Mechanical Engineering
Tucson, Arizona 85721

Dr. S. J. Pavane
Carnegie-Mellon University
Department of Civil Engineering
Schenley Park
Pittsburgh, Pennsylvania 15213

Dr. Ronald L. Huston
Department of Engineering Analysis
University of Cincinnati
Cincinnati, Ohio 45221

Universities (Con't.)

Professor C. C. M. Shi
Lough University
Institute of Fracture and
Solid Mechanics
Bathlehem, Pennsylvania 18015

Professor Albert E. Kobayashi
University of Washington
Department of Mechanical Engineering
Seattle, Washington 98195

Professor Daniel Frederick
Virginia Polytechnic Institute and
State University
Department of Engineering Mechanics
Blacksburg, Virginia 24061

Professor A. C. Eringen
Princeton University
Department of Aerospace and
Mechanical Sciences
Princeton, New Jersey 08540

Professor E. H. Lee
Stanford University
Division of Engineering Mechanics
Stanford, California 94305

Professor Albert I. King
Wayne State University
Biomechanics Research Center
Detroit, Michigan 48202

Dr. V. R. Hodgson
Wayne State University
School of Medicine
Detroit, Michigan 48202

Dean B. A. Bolay
Northwestern University
Department of Civil Engineering
Evanston, Illinois 60201

Universities (Con't.)

Professor F. G. Hedge, Jr.
University of Minnesota
Department of Aerospace Engineering
and Mechanics
Minneapolis, Minnesota 55455

Dr. B. C. Brucher
University of Illinois
Dean of Engineering
Urbana, Illinois 61801

Professor H. W. Hammark
University of Illinois
Department of Civil Engineering
Urbana, Illinois 61803

Professor E. Reissner
University of California, San Diego
Department of Applied Mechanics
La Jolla, California 92037

Professor William A. Nash
University of Massachusetts
Department of Mechanics and
Aerospace Engineering
Amherst, Massachusetts 01001

Professor G. Herrmann
Stanford University
Department of Applied Mechanics
Stanford, California 94305

Professor J. D. Achenbach
Northwest University
Department of Civil Engineering
Evanston, Illinois 60201

Professor S. B. Dong
University of California
Department of Mechanics
Los Angeles, California 90024

Professor Burt Paul
University of Pennsylvania
Towson School of Civil and
Mechanical Engineering,
Philadelphia, Pennsylvania 19104

Universities (Con't.)

Professor H. W. Liu
Syracuse University
Department of Chemical Engineering
and Metallurgy
Syracuse, New York 13210

Professor S. Sadner
Technion - R&D Foundation
Haifa, Israel

Professor Werner Goldsmith
University of California
Department of Mechanical Engineering
Berkeley, California 94720

Professor E. S. Rivlin
Lough University
Center for the Application
of Mathematics
Bathlehem, Pennsylvania 18015

Professor P. A. Conserelli
State University of New York at
Buffalo
Division of Interdisciplinary Studies
Karr Parker Engineering Building
Chemistry Road
Buffalo, New York 14214

Professor Joseph L. Rose
Drexel University
Department of Mechanical Engineering
and Mechanics
Philadelphia, Pennsylvania 19104

Professor B. E. Donaldson
University of Maryland
Aerospace Engineering Department
College Park, Maryland 20742

Professor Joseph A. Clark
Catholic University of America
Department of Mechanical Engineering
Washington, D.C. 20064

Universities (Con't.)

Dr. Samuel B. Bettorf
University of California
School of Engineering
and Applied Science
Los Angeles, California 90024

Professor Isaac Fried
Boston University
Department of Mathematics
Boston, Massachusetts 02215

Professor E. Krampl
Kammler Polytechnic Institute
Division of Engineering
Engineering Mechanics
Troy, New York 12181

Dr. Jack B. Vinson
University of Delaware
Department of Mechanical and Aerospace
Engineering and the Center for
Composite Materials
Newark, Delaware 19711

Dr. J. Duffy
Brown University
Division of Engineering
Providence, Rhode Island 02912

Dr. J. L. Swedlow
Carnegie-Mellon University
Department of Mechanical Engineering
Pittsburgh, Pennsylvania 15213

Dr. V. E. Varadan
Ohio State University Research Foundation
Department of Engineering Mechanics
Columbus, Ohio 43210

Dr. Z. Hashin
University of Pennsylvania
Department of Metallurgy and
Materials Science
College of Engineering and
Applied Science
Philadelphia, Pennsylvania 19104

Universities (Con't.)

Dr. Jackson C. S. Yang
University of Maryland
Department of Mechanical Engineering
College Park, Maryland 20742

Professor T. Y. Chang
University of Akron
Department of Civil Engineering
Akron, Ohio 44325

Professor Charles W. Bert
University of Oklahoma
School of Aerospace, Mechanical,
and Nuclear Engineering
Norman, Oklahoma 73019

Professor Satva N. Atluri
Georgia Institute of Technology
School of Engineering and
Mechanics
Atlanta, Georgia 30332

Professor Graham P. Carey
University of Texas at Austin
Department of Aerospace Engineering
and Engineering Mechanics
Austin, Texas 78712

Dr. S. S. Wang
University of Illinois
Department of Theoretical and
Applied Mechanics
Urbana, Illinois 61801

Industry and Research Institutes

Dr. Norman Hobbs
Kaman Avidyne
Division of Kaman
Sciences Corporation
Burlington, Massachusetts 01803

Argonne National Laboratory
Library Services Department
9700 South Cass Avenue
Argonne, Illinois 60440

Industry and Research Institutes (Con't.)

Dr. M. C. Junger
Cambridge Acoustical Associates
34 Rindge Avenue Extension
Cambridge, Massachusetts 02140

Dr. V. Gdino
General Dynamics Corporation
Electric Boat Division
Groton, Connecticut 06340

Dr. J. E. Greenapton
J. G. Engineering Research Associates
1831 Henlo Drive
Baltimore, Maryland 21215

Newport News Shipbuilding and
Dry Dock Company
Library
Newport News, Virginia 23607

Dr. W. F. Bosich
McDonnell Douglas Corporation
3301 Bolsa Avenue
Huntington Beach, California 92647

Dr. B. M. Abramson
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas 78284

Dr. R. C. DeHart
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas 78284

Dr. M. L. Baron
Weidinger Associates
110 East 59th Street
New York, New York 10022

Dr. T. L. Geers
Lockheed Missiles and Space Company
3251 Hanover Street
Palo Alto, California 94304

Mr. William Caywood
Applied Physics Laboratory
Johns Hopkins Road
Laurel, Maryland 20810

Industry and Research Institutes (Con't.)

Dr. Robert E. Dunham
Pacifica Technology
P.O. Box 148
Del Mar, California 92014

Dr. M. F. Kanninen
Daimler-Benz Laboratories
505 King Avenue
Columbus, Ohio 43201

Dr. A. A. Hochrein
Dandilean Associates, Inc.
Springlake Research Road
15110 Frederick Road
Woodbine, Maryland 21797

Dr. James W. Jones
Swanson Service Corporation
P.O. Box 5415
Huntington Beach, California 92646

Dr. Robert E. Nickell
Applied Science and Technology
3344 North Torrey Pines Court
Suite 220
La Jolla, California 92037

Dr. Kevin Thomas
Westinghouse Electric Corp.
Advanced Reactors Division
P. O. Box 158
Madison, Pennsylvania 15663

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TR 42	2. GOVT ACCESSION NO. AD-A109249	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Further Studies on Dynamic Crack Curving		5. TYPE OF REPORT & PERIOD COVERED Technical Report
7. AUTHOR(s) Y.-J. Sun, M. Ramulu, A. S. Kobayashi and B. S.-J. Kang		6. PERFORMING ORG. REPORT NUMBER TR 42
9. PERFORMING ORGANIZATION NAME AND ADDRESS University of Washington Dept. of Mechanical Engineering FU-10 Seattle, WA 98195		8. CONTRACT OR GRANT NUMBER(s) N00014-76-C-0060
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Arlington, VA 22217		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 064-478
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE November 11, 1981
		13. NUMBER OF PAGES 18
		15. SECURITY CLASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Unlimited distribution		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Dynamic stress intensity factors, mechanics, crack-curving, dynamic photo-elasticity		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The elasto-dynamic stress field surrounding rapidly propagating cracks in thin polycarbonate, double edged crack tension specimens were analyzed by dynamic photoelasticity using a 16-spark gap Cranz-Schardin camera system. Crack curving was observed in two slanted double edged crack specimens and in two offset, parallel double edged crack specimens. In another test, the crack ran straight between two symmetrically located twin cracks. Results of these five tests were used to verify the dynamic crack curving criterion by Ramulu, et al., in which a reference distance of $r_0 = 1/128 \pi^* [K_I / \sigma_{max} V(c, c_1, c_2)]^{**2}$ from the crack tip		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

20. Continued

is incorporated into the maximum circumferential stress of minimum strain energy density criteris. The critical material property for crack curving in this thin polycarbonate sheet was found to be about $r_0 = 0.5$ mm.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)