MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS 1963 A

LEVEL

✓3

AD A109769

HEC ACTIVITIES
IN RESERVOIR ANALYSIS

by

VERNON R. BONNER

HEC

THE HYDROLOGIC
ENGINEERING CENTER
- research
- training
- application

Water Resources Support Center

U.S. Army Corps of Engineers

01 19 82 015

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Technical Paper No. 75	2. GOVT ACCESSION NO. AD-A109769	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) HEC ACTIVITIES IN RESERVOIR ANALYSIS		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Vernon R. Bonner		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Corps of Engineers The Hydrologic Engineering Center 609 Second Street, Davis, CA 95616		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE June 1980
		13. NUMBER OF PAGES 11
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Distribution of this publication is unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Reservoirs, mathematical models, reservoir operation, water quality,
water resources.

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

Over the last 15 years, The Hydrologic Engineering Center (HEC) has been
developing, applying, and distrbuting computer programs dealing with various
aspects of hydrologic engineering, including reservoir analysis. The Center
has developed several models for the simulation of reservoir operation and
has supported the development of a water quality model for reservoirs and
rivers. This paper presents review of model development and an overview of the
capabilities and types of applications for the most recent computer programs,
"Simulation of Flood Control and Conservation Systems" (Continued)

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE
1 JAN 73

20 (Continued)

(HEC-5) and "Water Quality for River-Reservoir Systems" (WQRRS). Also, current research and development dealing with reservoir analysis are described.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	

By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

HEC ACTIVITIES IN RESERVOIR ANALYSIS[1]

by

Vernon R. Bonner [2]

INTRODUCTION

Over the last 15 years, The Hydrologic Engineering Center (HEC) has been developing, applying, and distributing computer programs dealing with various aspects of hydrologic engineering, including reservoir analysis. The Center has developed several models for the simulation of reservoir operation and has supported the development of a water quality model for reservoirs and rivers. This paper presents a review of model development and an overview of the capabilities and types of applications for the most recent computer programs, "Simulation of Flood Control and Conservation Systems" (HEC-5) and "Water Quality for River-Reservoir Systems" (WQRRS). Also, current research and development dealing with reservoir analysis are described.

PROGRAM DEVELOPMENT

The Hydrologic Engineering Center has been involved with the development, distribution and support of computer programs since its inception in 1964. Early programs were small, single-purpose routines like Gate Regulation Curve (1), Spillway Rating and Flood Routing (2), and Reservoir Yield (3). All three programs were released in 1966.

During the mid-sixties, the computer program, "Reservoir System Analysis for Conservation" (HEC-3) (4) was developed by Leo R. Beard. Program capabilities were expanded and by 1974, the fourth generation model was released with a full range of capabilities to simulate a reservoir system for typical conservation objectives of minimum flows, diversions and hydropower generation. During the early seventies, the HEC-3 program was applied to a number of reservoir studies at the Center. (5,6,7). The program is still actively used and at last count, 200 source decks had been distributed.

Although the HEC-3 program was adequate for conservation studies, there was a need for flood control simulation within the Corps. During the early seventies, Bill S. Eichert developed a model for flood control simulation which was released in 1973 as HEC-5, "Reservoir System

---

Operation for Flood Control." (8) After its release, Mr. Eichert continued to develop the model, adding conservation capabilities that were available within HEC-3. By 1975, a new version labeled HEC-5C was released with both flood control and conservation simulation capabilities. The HEC-5C label was carried by the program until a new release was made in June 1979. Now, HEC-5, "Simulation of Flood Control and Conservation Systems," (9) is our primary reservoir simulation program. Since its June release, 59 copies of the new program have been distributed. Prior to that date, there were 124 copies of earlier versions released.

Program development in the water quality area centered on reservoir temperature models during the sixties. In 1969, the Center released a monthly reservoir temperature stratification model (10) that simulates temperature variations between horizontal strata within a reservoir. During the early seventies, the need for more comprehensive quality analysis led to the development and application of several mathematical computer models. (11) The Center has adopted the ecological model of Drs. Chen and Orlob and has supported the expansion of that model with a river ecological model, developed by Mr. William Norton. Other modifications were made, and in 1974 the Center released the program, "Water Quality for River-Reservoir Systems." (WQRRS) (12) The model was capable of analyzing 18 different physical, chemical and biological water quality parameters.

In 1975, the streamflow routing capability was added to WQRRS, and in 1976 the capability to analyze branched and loop stream systems was added. The current model was created in 1978 when the preprocessors were integrated into the individual modules of the program. Today the program is distributed as three separate but integrable modules: the reservoir module, the stream hydraulics module, and the stream quality module. The stream quality module has no hydraulic computation capability and requires the hydraulic data file generated by the hydraulics module.

PROGRAM CAPABILITIES AND APPLICATIONS

The early studies with HEC-5 were generally flood control planning studies. The program flood control operation is based on maintaining nondamaging discharges at designated downstream locations while observing constraints on outlet capacity, rate of change on releases, and limits on the future foresight of inflow and inflow accuracy. Economic routines provide flood damage estimates for individual floods or expected annual damages based on multiple flood analysis. The expected value of damages is used as a basis for evaluating alternative flood control plans. (13,14,15)

More recently, the conservation capabilities of HEC-5 are being applied to reservoir yield determination problems. The program can simulate reservoir operations for minimum flow requirements, diversions, and hydropower. Hydropower operation can be for individual sites or system power requirements, and pump storage operation can also be simulated. Table 1 lists the systems simulated with HEC-5 in which the Center has had a major role.

TABLE 1

SYSTEMS SIMULATED BY HEC-5

River Basin	Location	Number Reservoirs	Number Control Points (including res)	Time Increment (hrs)
Trinity	Texas	15	28	24
Merrimack	New England	5	11	3
Susquehanna	Pennsylvania	34	75	4
Schuylkill	Pennsylvania	12	26	3
Potomac	VA,MD,PA	26	39	2
Red River-North	Minnesota	13	29	24 & 720
Feather	California	3	4	2
Pajaro	California	3	6	1 & 720
Grand (Neosho)	Oklahoma	24	86	2
James	Virginia	22	35	6
Red River	Texas,Arkansas	14	28	6
Hudson	N.Y.,PA	3	5	720
Morova	Yugoslavia	7	14	4
Little River	Oklahoma	4	9	6 & 720
Marshall Fork	Texas	1	2	24
Catskill Aqueduct	Hudson River	2	5	720
Sacramento River	California	11	16	2
Shasta-Red Bluff	California	2	5	2
Roaring Fork	Colorado	1	4	24
San Joaquin	California	22	56	6
Salt River Basin	Arizona	7	12	2 & 720
Savannah Pumped Storage	Georgia	3	5	1 & 24
White River Pumped Storage	Arkansas	3	4	1 & 24 & 720

A recent operation study (16) analyzed the impact of pump-back operation on hydropower production and recreation usability of a reservoir system on the Savannah River. The total energy requirements were specified for the three tandem reservoir system and the program allocated the energy requirements to the individual projects based on balancing the reservoir storage levels. The system allocation routine also accounts for the pump-back water and the downstream minimum flow requirements.

The need for a water quality evaluation of existing and proposed project conditions on the Trinity River in Texas required the analysis of both reservoir and stream channel conditions. These requirements led to linking of the water quality models described earlier. Existing and project conditions have also been simulated for or by other Corps offices at the proposed Tocks Island Lake, Lake Koocanusa (Libby Dam), and Lincoln Lake using variations of the Chen-Orlob model. (11)

The WQRRS model reflects an attempt by HEC to provide a generalized river-reservoir water quality model which is continuously updated and maintained with the best available concepts. The reservoir module of the program is applicable to aerobic impoundments that can be represented as one-dimensional systems having horizontal isotherms. This approximation is generally satisfactory in medium to moderately large lakes or reservoirs with long residence times. The approximation may be less satisfactory in shallow impoundments or those having a rapid flow-through time. Systems that have a rapid flow-through time are often fully mixed and can be treated as slowly moving streams using the stream quality module. The reservoir model is designed to provide a detailed portrayal of the important processes that determine the thermal and water quality characteristics of lakes and reservoirs. The interdependence of constituents is shown in Figure 1.

The stream hydraulic module provides six hydraulic computation options. They are 1) steady gradually varied flow (backwater), 2) solution to the full St. Venant equations, 3) stage-flow relationship, 4) kinematic wave, 5) Muskingum, and 6) modified Puls.

In the stream quality module, the rate of transport of quality parameters can be represented for aerobic streams. Peak pollutant loads can be routed through steady or unsteady flow conditions using the routing from the stream hydraulic module. If a steady state stream water quality analysis is desired, it can be simulated by holding inputs constant for a few computation periods. Field verification of the river water quality module is currently underway for the Allegheny River.

CURRENT ACTIVITIES

Current reservoir system activities are in three functional areas: hydropower, real-time flood operations, and water quality analysis. The hydropower activity is supported by Corps Research and Development funds as well as by the Department of Energy and the Corps National Hydropower Study.

A Aeration
B Bacterial Decay
C Chemical Equilibrium
E Excreta

G Growth
M Mortality
P Photosynthesis
R Respiration

S Settling
H Harvest

Figure 1. QUALITY AND ECOLOGIC RELATIONSHIPS

An extensive data file system has been developed by the Center for use in the inventory of some 7,000 dams as a part of the National Hydroelectric Power Study. Computer software has also been written to develop HEC-5 input data automatically from the file system. With the developed software, a global request or specific site request can be made to automatically generate HEC-5 input and operate the model to determine dependable capacity, firm annual energy and average annual energy for any storage project in the files. The results are automatically returned to the files and used for economic analysis.

The HEC-5 program is also being used to determine the potential gains from reallocation of flood control storage. Using the program's yield optimization feature, the potential gain in firm and average annual energy is being determined for all existing power projects with significant flood control storage. The program's flood damage routines will provide estimates of the potential cost from loss of flood control storage.

The real-time operation work has focused on flood flow forecasts, improved linkage between forecast model and operation model, and improved interaction between the operation model and the program user. The concept of linking a forecast model with HEC-5 and providing convenient interactive output displays of operation results was demonstrated in 1975 for the Merrimack River Basin. (17) Subsequent software development has provided a new interactive output display package that provides both graphical and tabular displays of simulation results. Included in the package is the capability to create and store menus that can be utilized for input/output requests to the program and an automatic procedure to graphically input hydrographs to the model. The input hydrographs can be forecasted inflows or proposed reservoir release schedules. With the new output routines, it is possible to quickly simulate and display the program's flood operation. The operator can display results, make decisions, and reoperate the model with the new input (e.g., release schedule). The package was demonstrated at the National Workshop on Reservoir System Operations at Boulder, Colorado in August 1979. (18)

Through the Los Angeles District of the Corps of Engineers, the Salt River Project (SRP) of Phoenix, Arizona, heard about the new capabilities and requested assistance in applying the operation model to their system. Earlier planning studies had been performed using HEC-5; therefore, it was easy to develop the data files for a "real-time" operation. In mid-December 1979, a three-day training/work session was provided at the Center to demonstrate how the Salt River System could be modeled and analyzed. The Project staff made arrangements with the National Weather Service to obtain the necessary inflow forecasts. They also contracted with the computer service company where the software was developed so there would be no difficulty in transferring the data files and programs. By January they were operational and began testing the software.

The January-February flood season was a major test for project operations and the computer programs. Mr. Thomas Sands, Senior Engineer with SRP, feels the program has become an important tool during times

6

of critical reservoir operations. As reported in the March 20, 1980 edition of PULSE,* a record 35 computer simulations were made during the storms of February 13 and 22, 1980. The simulations were made not only to assist in reservoir release decisions, but also to provide downstream flow predictions for the bridges in Phoenix. SRP reports the program has extended their ability to analyze the effects of potential storms.

The water quality calculations are being incorporated into the reservoir simulation model HEC-5. The objective is to provide a computer program and methodology for total water management capability for complex systems of reservoirs. The model will evaluate flood control, hydropower, water quality and other project purposes and determine the "best" system regulation to meet all downstream water needs. The resultant model will also provide the first step toward a long-term water quality regulation for large multiple-purpose reservoir systems.

The first phase, completed last year, linked water temperature algorithms to HEC-5. The model, called HEC-5Q, was applied to a single reservoir operation. The second phase is now expanding the model to simulate additional water quality parameters and operate with two parallel reservoirs and two tandem reservoirs. The contract also requires solving a test case and providing appropriate documentation. Next year, the third phase will provide the capability of simulating a comprehensive reservoir system. Example operations and appropriate documentation will also be required. If it appears feasible, the model will be modified to include real-time regulation capability.

CONCLUSIONS

The need for comprehensive models to analyze reservoir-river systems is evident. The program capabilities, wide distribution, and support of HEC-5 and WQRRS make them attractive tools for the analysis of reservoir systems. Past applications of the models to a variety of problems show their worth for planning studies. With the current model development, they may also be useful tools for application to operation problems on a "real-time" basis.

---

*PULSE is a weekly public affairs newsletter published by the Salt River Project.

REFERENCES

1. The Hydrologic Engineering Center, "Gate Regulation Curve," Computer Program Documentation, February 1966.

2. The Hydrologic Engineering Center, "Spillway Rating and Flood Routing," Computer Program Documentation, October 1966.

3. The Hydrologic Engineering Center, "Reservoir Yield," Computer Program Documentation, August 1966.

4. The Hydrologic Engineering Center, "HEC-3 Reservoir System Analysis for Conservation," Users Manual, July 1974.

5. Davis, C. Pat and Fredrich, A.J., "Development of System Operation Rules for an Existing System by Simulation," The Hydrologic Engineering Center Technical Paper No. 31, August 1971.

6. Beard, L.R., Weis, Arden, and Austin, T.A., "Alternative Approaches to Water Resource System Simulation," The Hydrologic Engineering Center Technical Paper No. 32, May 1972.

7. Fredrich, A.J., and Beard, Leo R., "System Simulation for Integrated Use of Hydroelectric and Thermal Power Generation," The Hydrologic Engineering Center Technical Paper No. 33, October 1972.

8. The Hydrologic Engineering Center, "HEC-5 Reservoir System Operation for Flood Control," Users Manual (out of print), May 1973.

9. The Hydrologic Engineering Center, "HEC-5 Simulation of Flood Control and Conservation Systems," Users Manual, June 1979.

10. The Hydrologic Engineering Center, "Reservoir Temperature Stratification," Users Manual, January 1972.

11. Willey, R.G., "Water Quality Evaluation of Aquatic Systems," The Hydrologic Engineering Center Technical Paper No. 38, April 1975.

12. The Hydrologic Engineering Center, "Water Quality for River-Reservoir Systems," Draft Users Manual, October 1978.

13. Eichert, Bill S., "HEC-5C, A Simulation Model for System Formulation and Evaluation," The Hydrologic Engineering Center Technical Paper No. 41, March 1974.

14. Eichert, B.S., "Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems," The Hydrologic Engineering Center Technical Paper No. 43, August 1975.

15. Eichert, B.S., and Davis, D.W., "Sizing Flood Control Reservoir Systems by Systems Analysis," The Hydrologic Engineering Center Technical Paper No. 44, March 1976.

16. McMahon, G.F., Bonner, V.R., and Eichert, B.S., "Operational Simulation of a Reservoir System with Pumped Storage," ASCE Journal of the Water Resources Planning and Management Division, Vol. 106, No. WR1, March 1980.

17. Eichert, B.S., Peters, J.C., and Pabst, A.F., "Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin," The Hydrologic Engineering Center Technical Paper No. 45, November 1975.

18. Eichert, B.S., and Bonner, V.R., "HEC Contribution to Reservoir System Operation," The Hydrologic Engineering Center Technical Paper No. 63, August 1979.

TECHNICAL PAPERS

*Technical papers are written by the staff of the HEC, sometimes in
collaboration with persons from other organizations, for presentation
at various conferences, meetings, seminars and other professional
gatherings.*

Price
$2.00 each

1   Use of Interrelated Records to Simulate Streamflow, Leo R.
       Beard, December 1964, 22 pages.

2   Optimization Techniques for Hydrologic Engineering, Leo R.
       Beard, April 1966, 26 pages.

3   Methods of Determination of Safe Yield and Compensation Water
       from Storage Reservoirs, Leo R. Beard, August 1965,
       21 pages.

4   Functional Evaluation of a Water Resources System, Leo R.
       Beard, January 1967, 32 pages.

5   Streamflow Synthesis for Ungaged Rivers, Leo R. Beard,
       October 1967, 27 pages.

6   Simulation of Daily Streamflow, Leo R. Beard, April 1968,
       19 pages.

7   Pilot Study for Storage Requirements for Low Flow Augmenta-
       tion, A. J. Fredrich, April 1968, 30 pages.

8   Worth of Streamflow Data for Project Design - A Pilot Study,
       D. R. Dawdy, H. E. Kubik, L. R. Beard, and E. R. Close,
       April 1968, 20 pages.

9   Economic Evaluation of Reservoir System Accomplishments,
       Leo R. Beard, May 1968, 22 pages.

#10   Hydrologic Simulation in Water-Yield Analysis, Leo R.
       Beard, 1964, 22 pages.

#11   Survey of Programs for Water Surface Profiles, Bill S.
       Eichert, August 1968, 39 pages.

#12   Hypothetical Flood Computation for a Stream System, Leo
       R. Beard, April 1968, 26 pages.

#13   Maximum Utilization of Scarce Data in Hydrologic Design,
        Leo R. Beard and A. J. Fredrich, March 1969, 20 pages.

#14   Techniques for Evaluating Long-Term Reservoir Yields,
        A. J. Fredrich, February 1969, 36 pages.

#15   Hydrostatistics - Principles of Application, Leo R. Beard,
        July 1969, 18 pages.

#16   A Hydrologic Water Resource System Modeling Techniques,
        L. G. Hulman and D. K. Erickson, 1969, 42 pages.

#17   Hydrologic Engineering Techniques for Regional Water
        Resources Planning, Augustine J. Fredrich and Edward F.
        Hawkins, October 1969, 30 pages.

#18   Estimating Monthly Streamflows Within a Region, Leo R.
        Beard, Augustine J. Fredrich, Edward F. Hawkins, January
        1970, 23 pages.

#19   Suspended Sediment Discharge in Streams, Charles E. Abraham,
        April 1969, 24 pages.

#20   Computer Determination of Flow Through Bridges, Bill S.
        Eichert and John Peters, July 1970, 32 pages.

#21   An Approach to Reservoir Temperature Analysis, L. R. Beard
        and R. G. Willey, April 1970, 31 pages.

#22   A Finite Difference Method for Analyzing Liquid Flow in
        Variably Saturated Porous Media, Richard L. Cooley,
        April 1970, 46 pages.

#23   Uses of Simulation in River Basin Planning, William K.
        Johnson and E. T. McGee, August 1970, 30 pages.

#24   Hydroelectric Power Analysis in Reservoir Systems, Augustine
        J. Fredrich, August 1970, 19 pages.

#25   Status of Water Resource Systems Analysis, Leo R. Beard,
        January 1971, 14 pages.

#26   System Relationships for Panama Canal Water Supply,
        Lewis G. Hulman, April 1971, 18 pages.
        *This publication is not available to countries outside of
        the U.S.*

#27   Systems Analysis of the Panama Canal Water Supply, David C.
Lewis and Leo R. Beard, April 1971, 14 pages.
*This publication is not available to countries outside of
the U.S.*

#28   Digital Simulation of an Existing Water Resources System,
Augustine J. Fredrich, October 1971, 32 pages.

#29   Computer Applications in Continuing Education, Augustine J.
Fredrich, Bill S. Eichert, and Darryl W. Davis, January
1972, 24 pages.

#30   Drought Severity and Water Supply Dependability, Leo R. Beard
and Harold E. Kubik, January 1972, 22 pages.

#31   Development of System Operation Rules for an Existing System
by Simulation, C. Pat Davis and Augustine J. Fredrich,
August 1971, 21 pages.

#32   Alternative Approaches to Water Resource System Simulation,
Leo R. Beard, Arden Weiss, and T. Al Austin, May 1972,
13 pages.

#33   System Simulation for Integrated Use of Hydroelectric and
Thermal Power Generation, Augustine J. Fredrich and Leo R.
Beard, October 1972, 23 pages.

#34   Optimizing Flood Control Allocation for a Multipurpose
Reservoir, Fred K. Duren and Leo R. Beard, August 1972,
17 pages.

#35   Computer Models for Rainfall-Runoff and River Hydraulic
Analysis, Darryl W. Davis, March 1973, 50 pages.

#36   Evaluation of Drought Effects at Lake Atitlan, Arlen D. Feldman,
September 1972, 17 pages.
*This publication is not available to countries outside of
the U.S.*

#37   Downstream Effects of the Levee Overtopping at Wilkes-Barre,
PA, During Tropical Storm Agnes, Arlen D. Feldman, April
1973, 24 pages.

#38   Water Quality Evaluation of Aquatic Systems, R. G. Willey,
April 1975, 26 pages.

#39   A Method for Analyzing Effects of Dam Failures in Design
Studies, William A. Thomas, August 1972, 31 pages.

TECHNICAL PAPERS (Continued)   Price
                                                              $2.00 each

#40   Storm Drainage and Urban Region Flood Control Planning,
       Darryl Davis, October 1974, 44 pages.

#41   HEC-5C, A Simulation Model for System Formulation and
       Evaluation, Bill S. Eichert, March 1974, 31 pages.

#42   Optimal Sizing of Urban Flood Control Systems, Darryl
       Davis, March 1974, 22 pages.

#43   Hydrologic and Economic Simulation of Flood Control Aspects
       of Water Resources Systems, Bill S. Eichert, August
       1975, 13 pages.

#44   Sizing Flood Control Reservoir Systems by Systems Analysis,
       Bill S. Eichert and Darryl Davis, March 1976, 38 pages.

#45   Techniques for Real-Time Operation of Flood Control Reservoirs
       in the Merrimack River Basin, Bill S. Eichert, John C.
       Peters and Arthur F. Pabst, November 1975, 48 pages.

#46   Spatial Data Analysis of Nonstructural Measures, Robert P.
       Webb and Michael W. Burnham, August 1976, 24 pages.

#47   Comprehensive Flood Plain Studies Using Spatial Data Manage-
       ment Techniques, Darryl W. Davis, October 1976, 23 pages.

#48   Direct Runoff Hydrograph Parameters Versus Urbanization,
       David L. Gundlach, September 1976, 10 pages.

#49   Experience of HEC in Disseminating Information on Hydrological
       Models, Bill S. Eichert, June 1977, 12 pages. *(Superseded by TP#56)*

#50   Effects of Dam Removal: An Approach to Sedimentation,
       David T. Williams, October 1977, 39 pages.

#51   Design of Flood Control Improvements by Systems Analysis:
       A Case Study, Howard O. Reese, Arnold V. Robbins, John
       R. Jordan, and Harold V. Doyal, October 1971, 27 pages.

#52   Potential Use of Digital Computer Ground Water Models,
       David L. Gundlach, April 1978, 40 pages.

#53   Development of Generalized Free Surface Flow Models Using
       Finite Element Techniques, D. Michael Gee and Robert C.
       MacArthur, July 1978, 23 pages.

#54   Adjustment of Peak Discharge Rates for Urbanization,
       David L. Gundlach, September 1978, 11 pages.

#55   The Development and Servicing of Spatial Data Management
       Techniques in the Corps of Engineers, R. Pat Webb and
       Darryl W. Davis, July 1978, 30 pages.

#56   Experiences of the Hydrologic Engineering Center in Main-
       taining Widely Used Hydrologic and Water Resource Computer
       Models, Bill S. Eichert, November 1978, 19 pages.

#57   Flood Damage Assessments Using Spatial Data Management
       Techniques, Darryl W. Davis and R. Pat Webb, May 1978,
       30 pages.

#58   A Model for Evaluating Runoff-Quality in Metropolitan
       Master Planning, L. A. Roesner, H. M. Nichandros,
       R. P. Shubinski, A. D. Feldman, J. W. Abbott, and A. O.
       Friedland, April 1972, 85 pages.

#59   Testing of Several Runoff Models on an Urban Watershed,
       Jess Abbott, October 1978, 56 pages.

#60   Operational Simulation of a Reservoir System with Pumped
       Storage, George F. McMahon, Vern Bonner and Bill S.
       Eichert, February 1979, 35 pages.

#61   Technical Factors in Small Hydropower Planning, Darryl W.
       Davis, February 1979, 38 pages.

#62   Flood Hydrograph and Peak Flow Frequency Analysis, Arlen D.
       Feldman, March 1979, 25 pages.

#63   HEC Contribution to Reservoir System Operation, Bill S.
       Eichert and Vernon R. Bonner, August 1979, 32 pages.

#64   Determining Peak-Discharge Frequencies in an Urbanizing
       Watershed: A Case Study, Steven F. Daly and John Peters,
       July 1979, 19 pages.

#65   Feasibility Analysis in Small Hydropower Planning, Darryl
       W. Davis and Brian W. Smith, August 1979, 24 pages.

#66   Reservoir Storage Determination by Computer Simulation of
       Flood Control and Conservation Systems, Bill S. Eichert,
       October 1979, 14 pages.

#67   Hydrologic Land Use Classification Using LANDSAT, Robert J.
       Cermak, Arlen D. Feldman, and R. Pat Webb, October 1979,
       30 pages.