

ADA 111573



NRL Memorandum Report 4731

Recoil Distributions in Some Proton Reactions

J. B. LANGWORTHY


*Radiation Survivability & Detection Branch
Condensed Matter & Radiation Sciences Division*

January 29, 1982

FILE COPY



NAVY RESEARCH LABORATORY
Washington, D.C.



SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NRL Memorandum Report 4731	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) RECOIL DISTRIBUTIONS IN SOME PROTON REACTIONS		5. TYPE OF REPORT & PERIOD COVERED Interim report on a continuing NRL problem.
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) J. B. Langworthy		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Research Laboratory Washington, DC 20375		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62712N; 66-1279-A-2
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE January 29, 1982
		13. NUMBER OF PAGES 18
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Nuclear reaction Recoil distribution Proton reaction Soft upset Energy distribution		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The distributions of recoil products from the two most important double decays of silicon excited by proton absorption are calculated by analytical and numerical methods. The nuclear reactions treated are Si(p,p α) and Si(p,2p) and it is assumed the decays are by evaporation. Conversion of the results to distributions of dose is discussed. The latter distributions are of interest in the soft upset of satellite electronic memories.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

RECOIL DISTRIBUTIONS IN SOME PROTON REACTIONS

Single event upset in electronic memory devices has caused a great deal of concern in the last two or three years.¹ One particular area of concern is upset produced in memories on board spacecraft which operate in the earth's radiation belts. Recent NRL calculations have shown² that upset rates can be very high in spacecraft memories. Though protons do not deposit energy sufficiently fast to produce upsets directly, some of their secondary products are sufficiently heavy and energetic to do so and occur with sufficient frequency to contribute to observed rates. This paper calculates the energy distribution of the recoil nuclei from the two most important proton induced reactions, $\text{Si}(p, \alpha)\text{Mg}$ and $\text{Si}(p, 2p)\text{Al}$. The dose density from the recoil is easily obtained from this and is briefly discussed. It is assumed for each case that the two light products are emitted essentially simultaneously so that the recoil velocities for both steps of the two step decay are calculated using the mass of the residual nucleus.

Manuscript submitted November 16, 1981.



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Special	
A	

An excited nucleus with velocity $\vec{v}_0$ decays first with a recoil velocity distribution, $D_1(v_1)$, spherical relative to $\vec{v}_0$, and again with $D_2(v_2)$, also spherical relative to $\vec{v}_1$. In order to calculate the distribution of the energy deposited by the recoil, it is first necessary to obtain the combined distribution of the two steps in the frame of $\vec{v}_1$. Assuming the decays are by evaporation³

$$D_i(E_i) = c_i (E_i - B_i) e^{-E_i/t_i}, \quad i = 1, 2, \quad E_i \geq B_i \quad (1)$$

where B_i and t_i are reaction constants and c_i is determined by

$$1 = \int dE D_i(E). \quad (2)$$

The energy parameter is center of mass reaction energy so

$$E_i = \frac{1}{2} m_i v_i^2,$$

$$m_i = \frac{M_R}{M_1} (M_R + M_1), \quad M_1 = M_p, \quad M_2 = \begin{cases} M_\alpha \\ M_p \end{cases}, \quad M_R = \begin{cases} M(^{24}\text{Mg}) \\ M(^{27}\text{Al}) \end{cases} \quad (3)$$

Carrying out the normalization, one obtains

$$c_i = t_i^{-2} e^{B_i/t_i}. \quad (4)$$

Since it is our intention to apply the vector convolution theorem in velocity space⁴ it is first necessary to change the given distributions from energy densities to velocity space densities.⁵ From (2)

$$\begin{aligned} 1 &= m \int D(v) v dv \\ &= (4\pi)^{-1} m \int v^{-1} D(v) d^3v. \end{aligned} \quad (5)$$

Thus to convert D to a velocity space density one writes

$$D'(v) = (4\pi v)^{-1} m D(v). \quad (6)$$

Assuming no correlation between D_1 and D_2 , the combined distribution is given as a function of $\vec{u} = \vec{v}_1 + \vec{v}_2$ in the same frame as v_1 by the convolution theorem.

$$\begin{aligned} D'(\vec{u}) &= (4\pi)^{-2} m_1 m_2 \iint v_1^{-1} v_2^{-1} D_1(v_1) D_2(v_2) \delta(\vec{u} - \vec{v}_1 - \vec{v}_2) d^3v_1 d^3v_2 \\ &= (4\pi)^{-2} m_1 m_2 \iint v_1^{-1} v_2^{-1} D_1(v_1) D_2(v_2) d^3v_1, \quad v_2 = |\vec{u} - \vec{v}_1|, \\ &= (4\pi)^{-2} m_1 m_2 \int D_1 D_2 v_1 v_2^{-1} dv_1 d\mu_1 d\phi_1 \\ &= (8\pi)^{-1} m_1 m_2 \int D_1 D_2 v_1 v_2^{-1} dv_1 d\mu_1, \end{aligned} \quad (7)$$

where $\mu_1 = \cos \theta_1$. Note that $v_2 = 0$ does not occur. Since

$$v_2^2 = u^2 - 2uv_1\mu_1 + v_1^2, \quad (8)$$

the entire μ_1 dependence is in $v_2^{-1}D_2$. Also one has from (8), holding u and v_1 fixed,

$$v_2 dv_2 = -uv_1 d\mu_1$$

$$v_2^{-1} d\mu_1 = -(uv_1)^{-1} dv_2. \quad (9)$$

As μ_1 goes from -1 to 1 , v_2 goes from $v^+ = u+v_1$ to $v^- = |u-v_1|$. For the μ_1 integral then one has

$$\begin{aligned} \int_{-1}^1 v_2^{-1} D_2 d\mu_1 &= -(uv_1)^{-1} \int_{v^+}^{v^-} D_2 dv_2 \\ &= -(uv_1 t_2^2)^{-1} \int_{v^+}^{v^-} \left(\frac{1}{2} m_2 v^2 - B_2\right) e^{-(\frac{1}{2} m_2 v^2 - B_2)/t_2} dv \\ &= -(uv_1)^{-1} (2)^{\frac{1}{2}} (t_2 m_2)^{-\frac{1}{2}} e^{B_2/t_2} \int_{w^+}^{w^-} (w^2 - B_2/t_2) e^{-w^2} dw \\ &= (uv_1)^{-1} (2t_2 m_2)^{-\frac{1}{2}} e^{B_2/t_2} \left[w e^{-w^2} \Big|_{w^+}^{w^-} + (2B_2/t_2 - 1) \int_{w^+}^{w^-} e^{-w^2} dw \right] \\ &= (uv_1)^{-1} (2t_2 m_2)^{-\frac{1}{2}} e^{B_2/t_2} \left(w e^{-w^2} + \frac{1}{2} (\pi)^{\frac{1}{2}} (2B_2/t_2 - 1) \operatorname{erf}(w) \right) \Big|_{w^+}^{w^-}. \quad (10) \end{aligned}$$

The point $u = 0$ will not be a problem after changing back to energy density below. Since there is no remaining angular dependence, $D'(\vec{u}) = D'(u)$ and,

$$D'(u) = \frac{m_1}{8\pi u} \left(\frac{m_2}{2t_2} \right)^{\frac{1}{2}} e^{B_2/t_2} \int_{v_m}^{\infty} dv_1 D_1(v_1) F(v_1)$$

where

$$F(v_1) = \left(w e^{-w^2} + \frac{1}{2} (\pi)^{\frac{1}{2}} (2B_2/t_2 - 1) \text{erf}(w) \right) \Big|_{w^+}^{w^-}$$

and

$$w^+ = \left(\frac{m_2}{2t_2} \right)^{\frac{1}{2}} (u + v_1), \quad w^- = \text{Max} \left\{ \left(\frac{m_2}{2t_2} \right)^{\frac{1}{2}} |u - v_1|, \left(\frac{B_2}{t_2} \right)^{\frac{1}{2}} \right\}$$

with

$$v_m = (2B_1/m_1)^{\frac{1}{2}}. \quad (11)$$

For the reactions of interest $B_2 \geq B_1$ and $B_2/m_2 \geq B_1/m_1$ so the lower limit for v_1 includes that for v_2 . Also in evaluating (11), whenever $(B_2/t_2)^{\frac{1}{2}} > w^+$, F , and thus the integrand, vanish at this particular v_1 .

Of course at this point one has only the spherical distribution relative to $\vec{v}_0$. This is a convenient point at which to check normalization. One requires

$$\begin{aligned} 1 &= \int D'(u) d^3u \\ &= 4\pi M_R^{-1} \int D'(E) u dE \end{aligned} \quad (12)$$

so a simple check is just a sum over

$$D(u) = 4\pi M_R^{-1} D'(u) \quad (13)$$

on a grid linear in energy.

In the numerical evaluation it was convenient to program D_1 and F as statement functions. The error function (erf) is a single precision library function and ought to be fairly fast. Still each call of F is roughly equivalent to the evaluation of two one-dimensional integrals. Use of Simpson rule is made so one loop for evaluation and one for integration was written to allow printing one complete integrand for error checking. Another convenient error check was to require the sign of $F(v_1)$ to be positive. The constants are $B_1 = 2.4$, $B_2 = 4.6$, $t_1 = t_2 = 2.45$ in MeV. Units of the D_1 are MeV^{-1} so writing the masses in MeV gives the velocities in units of light velocity, c . Since the integral is in velocity and the normalization check is in energy, the corresponding loops are on different grids designed to evaluate overlapping regions in $D_1(v_1)$ and $D'(u)$. Thus it was convenient to begin each loop with a unitless energy scale using B_1 as the unit. Then, for example, if a range in $E(u)$ from 0 to 10 ($10 B_1$ MeV) gives an adequate evaluation of D_1 the appropriate range for v_1/v_m would be 1 to $10^{1/2}$. While in principle there is a serious complication of upper limits required by numerical evaluation, this is ignorable in practice because of the property of these distributions in having compact support. Thus any accuracy desired within computer precision may be attained simply by extending the upper limits sufficiently.

The program RECOIL (listed in the Appendix) has been written, the first half performing the preceding calculations, and the results from this part

are given in Tables I and II. Upper limits for the unitless energy grids were 49 for (p,p α) and 36 for (p,2p), corresponding to evaporation energies of 117.6 and 86.4 MeV. For comparison the peak of the evaporation distribution is at $B_1 + t_1$, or 7.05 and 4.85 MeV, respectively. The overall sums obtained were 0.996 and 0.989, respectively. It may be seen below that extending the energy range decreases this error still.

Consider now the transformation of these distributions to the frame of $\vec{v}_0$. Assume absorption of a 30 MeV proton in the initial excitation, forming a compound nucleus. One has

$$M_p v_p = M_c v_0$$

$$\frac{1}{2} M_p v_p^2 = \frac{1}{2} M_c v_0^2 + E_x \quad (14)$$

and obtains for the excitation energy

$$E_x = \left(1 - \frac{M_p}{M_c}\right) T, \quad T = \frac{1}{2} M_p v_p^2 \quad (15)$$

Taking $M_c = M(^{28}\text{Si}+p)$ one obtains $E_x = 28.96$ MeV, $E_c = \frac{1}{2} M_c v_0^2 = 1.04$, $v_0 = 0.008945c$. Thus the transformation is in part accomplished by the substitution

$$u^2 = v^2 - 2vv_0 \cos \theta + v_0^2, \quad (16)$$

Table I

PROGRAM RECOIL ON (P,PA)

SPHERICAL ENERGY DISTRIBUTION (PER MEV)

ENERGY DISTRIB.

0.0000	0.000000	1.6444	0.429517	3.2888	0.080470
0.0967	0.028580	1.7411	0.418171	3.3855	0.069456
0.1935	0.092224	1.8378	0.402229	3.4822	0.059784
0.2902	0.173525	1.9346	0.382284	3.5789	0.051331
0.3869	0.246142	2.0313	0.359196	3.6757	0.043968
0.4836	0.302075	2.1280	0.333924	3.7724	0.037581
0.5804	0.343079	2.2247	0.307411	3.8691	0.032056
0.6771	0.372533	2.3215	0.280503	3.9659	0.027292
0.7738	0.393493	2.4182	0.253905	4.0626	0.023196
0.8706	0.408342	2.5149	0.228177	4.1593	0.019682
0.9673	0.418841	2.6117	0.203730	4.2560	0.016673
1.0640	0.426263	2.7084	0.180844	4.3528	0.014104
1.1607	0.431509	2.8051	0.159683	4.4495	0.011916
1.2575	0.435221	2.9018	0.140330	4.5462	0.010053
1.3542	0.437758	2.9986	0.122791	4.6430	0.008471
1.4509	0.438514	3.0953	0.107026	4.7397	0.007129
1.5477	0.436139	3.1920	0.092954		

OVERALL SUM 0.996304.

Table II

PROGRAM RECOIL ON (P,2P)

SPHERICAL ENERGY DISTRIBUTION (PER MEV)

ENERGY DISTRIB.

0.0000	0.000000	1.0797	0.288428	2.1161	0.003285
0.0432	0.923879	1.1228	0.247268	2.1593	0.002670
0.0864	1.042541	1.1666	0.211004	2.2025	0.002168
0.1296	1.079965	1.2092	0.179297	2.2457	0.001760
0.1727	1.093790	1.2524	0.151765	2.2889	0.001427
0.2159	1.099337	1.2956	0.128005	2.3321	0.001156
0.2591	1.101681	1.3388	0.107606	2.3752	0.000935
0.3023	1.102759	1.3820	0.090182	2.4184	0.000757
0.3455	1.103173	1.4251	0.075367	2.4616	0.000612
0.3887	1.103055	1.4683	0.062821	2.5048	0.000494
0.4319	1.099393	1.5115	0.052236	2.5480	0.000399
0.4750	1.087444	1.5547	0.043337	2.5912	0.000322
0.5182	1.063878	1.5979	0.035878	2.6344	0.000259
0.5614	1.027549	1.6411	0.029644	2.6775	0.000209
0.6046	0.979225	1.6843	0.024440	2.7207	0.000168
0.6478	0.920916	1.7274	0.020128	2.7639	0.000135
0.6910	0.855260	1.7706	0.016544	2.8071	0.000109
0.7342	0.785046	1.8138	0.013578	2.8503	0.000088
0.7774	0.712890	1.8570	0.011127	2.8935	0.000070
0.8205	0.641044	1.9002	0.009107	2.9367	0.000056
0.8637	0.571315	1.9434	0.007444	2.9798	0.000045
0.9069	0.505061	1.9866	0.006077	3.0230	0.000036
0.9501	0.443215	2.0298	0.004955	3.0662	0.000029
0.9933	0.386352	2.0729	0.004036	3.1094	0.000023
1.0365	0.334745				

OVERALL SUM 0.988986

redefining θ as the angle between $\vec{v}_0$ and $\vec{v}$. Similarly defining θ_1 , as the angle between $\vec{v}_0$ and $\vec{u}$, one notes that (13) has the form

$$D(u) = \frac{dN}{dE_1 d\Omega_1} \quad (17)$$

where $d\Omega_1 = d\mu_1 d\phi_1$, even though it lacks Ω_1 dependence. The transformation is therefore completed by the Jacobian.

$$\frac{dN}{dE d\Omega} = \frac{\partial(E_1, \Omega_1)}{\partial(E, \Omega)} \frac{dN}{dE_1 d\Omega_1} \quad (18)$$

$$\frac{\partial(E_1, \Omega_1)}{\partial(E, \Omega)} = \frac{v}{u} = \left(\frac{E}{E_1} \right)^{1/2} \quad (19)$$

Calculations of this transformation to the lab have been added to RECOIL, forming the second half. In addition lab solid angle $d\Omega$ is averaged to obtain dN/dE . Further the norm and average energy are obtained. The resulting distributions are in Tables III and IV and Figure 1. These tables show peaks near 1.35 and 0.97 MeV and average energies of 2.55 and 1.55 MeV for (p,pa) and (p,2p) respectively.

Now notice that from (18) one easily obtains an energy deposition distribution, given the recoil energy loss dE/dx ,

$$\frac{dN}{dx d\Omega} = \frac{dE}{dx} \frac{dN}{dE d\Omega} \quad (20)$$

If one assumes constant energy loss (a crude approximation) and sets $dE/dx = \epsilon$, then one recognizes that the multiplication of (18) by a constant is removed by renormalization. One then views (20) as nothing but a unit

Table III

PROGRAM RECOIL ON (P,PA)

SPHERICAL ENERGY DISTRIBUTION:

POINTS: 101 EMAX: 9.6728 DU(EMAX): 0.000000 NORM: 0.999838

LAB ENERGY DISTRIBUTION (PER MEV)

ENERGY DISTRIB.

0.0	0.000000	2.7	0.205211	5.4	0.056298
0.1	0.130652	2.8	0.199989	5.5	0.052009
0.2	0.172869	2.9	0.194539	5.6	0.047918
0.3	0.197031	3.0	0.188982	5.7	0.044043
0.4	0.211857	3.1	0.183269	5.8	0.040391
0.5	0.221444	3.2	0.177499	5.9	0.036955
0.6	0.227709	3.3	0.171649	6.0	0.033732
0.7	0.232417	3.4	0.165780	6.1	0.030732
0.8	0.234863	3.5	0.159883	6.2	0.027945
0.9	0.236755	3.6	0.153986	6.3	0.025345
1.0	0.238050	3.7	0.148091	6.4	0.022955
1.1	0.238933	3.8	0.142218	6.5	0.020765
1.2	0.239413	3.9	0.136371	6.6	0.018728
1.3	0.239595	4.0	0.130555	6.7	0.016858
1.4	0.239563	4.1	0.124777	6.8	0.015186
1.5	0.239294	4.2	0.119041	6.9	0.013638
1.6	0.238761	4.3	0.113350	7.0	0.012211
1.7	0.237857	4.4	0.107706	7.1	0.010944
1.8	0.236575	4.5	0.102119	7.2	0.009793
1.9	0.234942	4.6	0.096583	7.3	0.008737
2.0	0.232771	4.7	0.091130	7.4	0.007792
2.1	0.230124	4.8	0.085754	7.5	0.006946
2.2	0.226993	4.9	0.080484	7.6	0.006177
2.3	0.223400	5.0	0.075342	7.7	0.005487
2.4	0.219371	5.1	0.070323	7.8	0.004873
2.5	0.214957	5.2	0.065477	7.9	0.004321
2.6	0.210242	5.3	0.060790	8.0	0.003824

LAB NORM: 9.94159E-01 EAVE: 2.5550

Table IV

PROGRAM RECOIL ON (P,2P)

SPHERICAL ENERGY DISTRIBUTION:

POINTS: 129 EMAX: 5.5278 DUC(EMAX): 0.000000 NORM: 0.988988

LAB ENERGY DISTRIBUTION (PER MEV)

ENERGY DISTRIB.

0.0	0.000000	1.7	0.352809	3.4	0.063937
0.1	0.157603	1.8	0.332330	3.5	0.053026
0.2	0.231629	1.9	0.312182	3.6	0.044920
0.3	0.287849	2.0	0.292375	3.7	0.037175
0.4	0.334630	2.1	0.272955	3.8	0.030526
0.5	0.374476	2.2	0.253928	3.9	0.024877
0.6	0.407510	2.3	0.235322	4.0	0.020127
0.7	0.431137	2.4	0.217077	4.1	0.016164
0.8	0.439071	2.5	0.199204	4.2	0.012897
0.9	0.442378	2.6	0.181680	4.3	0.010234
1.0	0.442665	2.7	0.164526	4.4	0.008075
1.1	0.441257	2.8	0.147774	4.5	0.006328
1.2	0.438627	2.9	0.131577	4.6	0.004927
1.3	0.431510	3.0	0.116076	4.7	0.003831
1.4	0.412558	3.1	0.101432	4.8	0.002959
1.5	0.393624	3.2	0.087793	4.9	0.002266
1.6	0.373189	3.3	0.075273	5.0	0.001739

LAB NORM: 9.85881E-01 EAVE: 1.5531




Fig. 1 — Recoil distributions

change and accepts the numerical distribution (18) as giving the distribution per $\epsilon^{-1} \mu\text{m}$, the distance in which 1 MeV is lost. Instead of assuming constant energy loss one may utilize the code E-DEP-1⁶ to include straggling effects. A minor change will be required however since the energy-deposited report of E-DEP-1 does not include ionization loss, a significant part of dose. In making this change it will be permissible to ignore radiation loss, a few percent effect. Short of using E-DEP-1 but better than assuming constant dE/dx , one can find expressions giving the variation.

In fact $\epsilon = 1 \text{ MeV}/\mu\text{m}$ is only about twenty percent low when averaged over the first few μm . Thus the implication of Figure 1 is that significant energy, deposited in a spherical region of radius 3 to 4 μm , should be added to that previously considered.

Acknowledgments

The author wishes to thank E. L. Petersen for suggesting this problem and P. Shapiro for helpful conversations and a critical reading.

References

1. C. S. Guenzer, R. G. Allas, A. B. Campbell, J. M. Kidd, E. L. Petersen, N. Seeman and E. A. Wolicki, IEEE Trans. NS-27, 1485 (1980).
2. E. L. Petersen, IEEE Trans. NS-27, 1494 (1980) and E. L. Petersen, IEEE Trans. NS-28 (1981) (to be published).
3. C. K. Cline, Nucl. Phys. A174, 73 (1971) and G. B. Saha and N. T. Porile, Phys. Rev. 149, 880 (1966).

4. H. Cramer, *Mathematical Methods of Statistics*, Princeton (1946), pp. 285, 140.
5. Useful manipulations of vectorial distributions are given in J. B. Langworthy, *Naval Research Laboratory Report 6391* (1966).
6. I. Manning and G. P. Mueller, *Computer Phys. Communication* 7, 85 (1974).

APPENDIX

SOURCE LISTING

ASC FAST FORTRAN COMPILER

CSN

STATEMENT

CP OPTIONS = (M,X)

```

0001      PROGRAM RECOIL
C SET UP FOR SI(P,P ALPHA). FOR (P,2P) SET B2=B1, MA=MP & CHANGE MR
C TRANSFORMATION OF SPHERICAL DISTRIBUTION TO LAB ADDED
0002      IMPLICIT REAL(M)
0003      DIMENSION SG(241),DU(82),EU(82),DV(66),EV(66)
0004      DIMENSION DV2(22),EV2(22),DV3(22),EV3(22)
0005      EQUIVALENCE (DV2,DV(23)),(EV2,EV(23)),(DV3,DV(45)),(EV3,EV(45))
0006      DATA MC,MP,MA,MR/931.5016,938.2796,4.0026,23.98504/,R1,B2,T
      *2.4,4.6,2.45/,DE/1.0/,A/0./,I1,J1,K1/82,241,66/,MT/27.97693/
0007      E1(V)=(V*V*M1-B1)*RT
0008      D1(V)=RT*E1(V)*EXP(-F1(V))
0009      FW(V)=V*EXP(-V*V)+FC*ERF(V)
0010      J2=J1-1
0011      DV1=8./FLOAT(J2)
0012      MA=MA*MC
0013      MR=MR*MC
0014      M0=0.5*(MR+MP)/MP
0015      M1=M0*MR
0016      M2=MR*(MR+MA)*0.5/MA
0017      RT=1.0/T
0018      VW=SQRT(M2*RT)
0019      F=M0*VW*EXP(B2*RT)
0020      P4=ATAN(1.0)
0021      FC=(2.0*B2*RT-1.0)*SQRT(P4)
0022      VU=SQRT(B1/M1)
0023      S1=2.*DV1*VU/3.
0024      VT=SQRT(B2*RT)
0025      PRINT 61
0026      61  FORMAT(' PROGRAM RECOIL ON (P,PA)')
0027      DU(1)=0.
0028      EU(1)=0.
0029      DO 1 I=2,I1
0030      U=SQRT(DF*(I-1))*VU
0031      EU(I)=0.5*MR*U*U
0032      DO 2 J=1,J1
0033      V1=VU*(1.0+DV1*(J-1))
0034      SG(J)=0.
0035      VP=(V1+U)*VW
0036      IF(VP.LE.VT) GOTO 2
0037      VM=ABS(V1-U)*VW
0038      IF(VM.LT.VT) VM=VT
0039      SG(J)=FW(VM)-FW(VP)
0040      IF(SG(J).GT.-1E-6) GOTO 8
0041      PRINT 69,SG(J),V1,U,J,I
0042      69  FORMAT(' ***NEGATIVE INTEGRAND,V1,U,J,I:',1P3E11.2,2I4)
0043      8   SG(J)=F*D1(V1)*SG(J)
0044      2   CONTINUE
0045      S=0.5*(SG(J1)-SG(1))
0046      DO 4 J=2,J2,2
0047      4   S=S+2.*SG(J)+SG(J-1)

```

CSN	STATEMENT	CP OPTIONS = (M,X)
0048	DU(I)=S*S1	
0049	A=A+DU(I)	
0050	A=A*EU(2)	
0051	PRINT 62,I1,EU(I1),DU(I1),A	
0052	62 FORMAT(// " SPHERICAL ENERGY DISTRIBUTION: " POINTS: ".I4, * " EMAX: ",F7.4, " DU(EMAX): ",F9.6, " NORM: ",F9.6)	
0053	MT=MT*MC	
0054	ME=MP+MT	
0055	EP=30.*MP/ME*MR/ME	
0056	EV(1)=0.	
0057	DV(1)=0.	
0058	DO 10 K=2,K1	
0059	EV(K)=0.1*(K-1)	
0060	E2=2.0*SQRT(EV(K)*EP)	
0061	S=0.	
0062	DO 11 J=1,100	
0063	I0=1	
0064	MU=1.0-(2*J-1)/100.	
0065	E0=EV(K)+EP-E2*MU	
0066	F1=SQRT(EV(K)/E0)	
0067	DO 14 I=I0,I1	
0068	IF(E0.LT.EU(I)) GOTO 15	
0069	14 CONTINUE	
0070	GOTO 16	
0071	15 I0=I-1	
0072	D=DU(I0)*(DU(I)-DU(I0))*(E0-EU(I0))/(EU(I)-EU(I0))	
0073	S=S+D*F1	
0074	11 CONTINUE	
0075	16 DV(K)=S*0.01	
0076	10 CONTINUE	
0077	PRINT 64	
0078	64 FORMAT(/// " LAB ENERGY DISTRIBUTION (PER MEV) ", */// " ENERGY DISTRIB. ")	
0079	PRINT 65,(EV(K),DV(K),EV2(K),DV2(K),EV3(K),DV3(K),K=1,22)	
0080	65 FORMAT(3(F10.1,F10.6))	
0081	S=0.	
0082	A=0.	
0083	DO 20 K=1,K1	
0084	S=S+DV(K)	
0085	20 A=A+(EV(K)+0.05)*DV(K)	
0086	A=A/S	
0087	S=S*EV(2)	
0088	PRINT 66,S,A	
0089	66 FORMAT(/// " LAB NORM: ",1PE13.5, " EAVE: ",0PF7.4)	
0090	END	