

AD-A111 930 ARMY ELECTRONICS RESEARCH AND DEVELOPMENT COMMAND WS--ETC F/6 15/2
MUNITION EXPENDITURE MODEL VERIFICATION: KWIK. PHASE I.(U)
DEC 81 S L COHN, R PENA
UNCLASSIFIED ERADCOM/ASL-TR-0102 NL


UNCLASSIFIED

NL .

$$\frac{1}{2} \cdot 1 = \frac{1}{2}$$

A 10x10 grid of 100 squares. The first 48 squares are black, and the remaining 52 squares are white.

END
DATE
FILMED
4 82
DTIC





-TR-0102



AD

Reports Control Symbol
OSD - 1366

ADA111930

MUNITION EXPENDITURE MODEL VERIFICATION:
KWIK PHASE I

DECEMBER 1981

CO-AUTHORED BY
Stephen L. Cohn and Ricardo Peña

DTIC FILE COPY

DTIC
ELECTRONIC

MAR 12 1982

Approved for public release; distribution unlimited.

A



US Army Electronics Research and Development Command

Atmospheric Sciences Laboratory

White Sands Missile Range, NM 88002

82 08 12 017

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.

ASL-TR-0102
ERRATA SHEET

Page 17 - First Paragraph

For the higher windspeeds (figure 8) there is no apparent mean difference between the two methods, although there were wide differences on any given trial between KWIK and the FM method.

Should read:

For the higher windspeeds (figure 8), there is no apparent mean difference between the two sets of meteorological data, although there were wide differences in munition expenditures on any given trial.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ASL-TR-0102	2. GOVT ACCESSION NO. AD-A111930	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) MUNITION EXPENDITURE MODEL VERIFICATION: KWIK PHASE I		5. TYPE OF REPORT & PERIOD COVERED Final Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Stephen L. Cohn and Ricardo Peña		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Atmospheric Sciences Laboratory White Sands Missile Range, NM 88002		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS DA Task 1L161102AH71-A2
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Electronics Research and Development Command Adelphi, MD 20783		12. REPORT DATE December 1981
		13. NUMBER OF PAGES 79
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Munition expenditure High wind screening Smoke screening effectiveness Target area meteorology Target obscuration Visible wavelengths		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The US Army Atmospheric Sciences Laboratory (ASL) at White Sands Missile Range (WSMR), New Mexico, has developed a munition expenditure model called KWIK (a mnemonic derived from crosswind integrated concentration), which uses Gaussian diffusion theory. Phase I of the KWIK Munition Expenditure Model verification test was conducted during the summer of 1980 at Dugway Proving Ground (DPG), Utah, for visible wavelengths, using statically detonated hexacholorethane (HC) smoke sources. Results presented show a mean smoke screening effectiveness of 88 percent and 99 percent of the screen duration time, for		

20. ABSTRACT (cont)

low (< 7 knots) and moderate (7 to 15 knots) windspeeds, respectively. Under satisfactory screening conditions, the KWIK model predicted 5 percent fewer munitions than the Field Manual (FM) method for the low relative humidity (RH $\approx$ 30.5 percent) during the test. Thirty-eight percent fewer rounds would have been used by the KWIK model had high relative humidity (RH $\approx$ 80 percent) occurred during this test. Eight trials, conducted under conditions considered unfavorable by the FM method (winds > 16 knots), produced a 100 percent mean effectiveness in screening the targets. Phase I results also indicate that use of target area meteorology is desirable under low windspeeds or marginal screening conditions, but may not be necessary under high windspeeds resulting from synoptic scale weather systems.

CONTENTS

INTRODUCTION.....	5
DESCRIPTION OF MODEL.....	6
DESCRIPTION OF TRIALS.....	8
Test Objectives.....	8
Meteorological Limitations.....	8
Data Requirements.....	9
Smoke Impact Area.....	9
KWIK Calculations.....	9
EVALUATION OF DATA.....	10
Smoke Screening Assessment.....	10
Munition Expenditure Assessment.....	15
High Wind Screening.....	17
CONCLUSIONS.....	18
Screening Effectiveness.....	18
Munition Expenditure Comparisons.....	19
High Wind Screening.....	19
Target Area Meteorology.....	20
REFERENCES.....	26
APPENDIX A. KWIK MODEL OUTPUT CALCULATIONS.....	27
APPENDIX B. TARGET OBSERVER ASSESSMENTS.....	43
APPENDIX C. PHOTOGRAPHIC DATA.....	57



Approved For	
By	Signature
Date	11
Unauthorized	11
Justification	
By	
Date	
Approved by	
Date	
Dist	
A	

LIST OF FIGURES

1. Test grid for KWIK smoke tests, Phase I, DPG, Utah.....	21
2. Center portion of HC array at smoke impact area.....	21
3. Munition comparison: KWIK vs field manual using Horizontal Grid met (windspeed: 2.0 to 3.5 m/s).....	22
4. Munition comparison: KWIK vs field manual using Horizontal Grid met (windspeed: 3.6 to 7.5 m/s).....	22
5. Munition comparison: KWIK vs field manual using Ditto Met Station data (windspeed: 2.0 to 3.5 m/s).....	23
6. Munition comparison: KWIK vs field manual using Ditto Met Station data (windspeed: 3.6 to 7.5 m/s).....	23
7. Meteorological comparison: Ditto vs Horizontal Grid met data (windspeed: 2.0 to 3.5 m/s).....	24
8. Meteorological comparison: Ditto vs Horizontal Grid met data (windspeed: 3.6 to 7.5 m/s).....	24
9. Meteorological comparison: Ditto vs Horizontal Grid met data (windspeed: > 8.0 m/s).....	25

LIST OF TABLES

1. KWIK SMOKE TRIALS, PHASE I, DPG, UTAH.....	11
2. SMOKE SCREENING ASSESSMENT, WINDSPEED 2.0 - 3.5 M/S.....	12
3. SMOKE SCREENING ASSESSMENT, WINDSPEED 3.6 - 7.5 M/S.....	13
4. MUNITION EXPENDITURE ASSESSMENT.....	16
5A. WINDSPEED (WS) > 8 M/S VS CALCULATED MUNITION EXPENDITURES.....	18
5B. SCREEN CHARACTERISTICS.....	19

INTRODUCTION

The threat imposed by the Soviet bloc tank forces requires that ground level obscuration, for both offensive and defensive planning, must receive the most thorough research and developmental efforts. The possibility of reducing costs for munition expenditures further dictates pursuit of more efficient mechanisms for obtaining obscuration objectives.

The development of munition expenditure algorithms requires the application of hypotheses relating micrometeorology, atmospheric optics, and turbulent diffusion in the surface boundary layer of the atmosphere. Primary criteria for a workable prototype system require that: (1) the algorithm must function reliably in the near-, mid-, and far-infrared as well as in the visible wavelengths of the electromagnetic spectrum; (2) the predicted smoke concentration must obscure the optical path to a predetermined attenuation level; (3) the input parameters must be few in number and readily obtainable; and (4) the model output must include munition expenditure estimates, the impact separation of projectiles from an adjustment point to establish and maintain a smoke screen, and the rate of fire necessary to maintain that smoke screen.

In order to meet the primary criteria, the model must take into account: (1) the effects of relative humidity upon the hygroscopic characteristics of the smoke aerosols; (2) the meteorological limits for practical applications of screen/obscuration on a battlefield; and (3) the relationships between transmittance through the smoke versus concentration over the pathlength as a function of wavelength.

The above criteria were considered in developing the US Army Atmospheric Sciences Laboratory (ASL) KWIK (a mnemonic derived from crosswind integrated concentration) smoke algorithm.¹ KWIK is a hybrid model which produces munition expenditures based on atmospheric optics and turbulent diffusion theory as a function of battlefield meteorological observations.

A large data base from previous experiments exists in the literature, covering chemically generated military smokes. These data have been used to verify and/or evaluate several different approaches to atmospheric diffusion, including the Gaussian formulae. These previous tests have verified the predictability of relatively long average downwind concentrations of some diffusing materials in the atmosphere. However, a deficiency exists in the case of military smokes for which the actual obscuration has not been reliably predicted or verified, especially over short time intervals. This deficiency has made it impossible to evaluate KWIK in all categories of performance without obtaining additional data.

In order to verify the munition expenditure predictions of the KWIK model, an evaluation plan consisting of three phases was devised by ASL. This report

¹Umstead, R. K., R. Pena, and F. V. Hansen, "KWIK: An Algorithm for Calculating Munitions Expenditures for Smoke Screening/Obscuration in Tactical Situations," ASL-TR-0030, US Army Atmospheric Sciences Laboratory, White Sands Missile Range, NM, 1979.

deals only with Phase I, an effectiveness evaluation test for visible wavelengths. This test was conducted using statically detonated hexachloroethane (HC) smoke sources, at Dugway Proving Ground (DPG), Utah, during the summer of 1980.

DESCRIPTION OF MODEL

The KWIK model consists of a blending of meteorological and site parameters, atmospheric optics, and turbulent diffusion theory. Each of these are briefly discussed below.

Meteorological data requirements for the KWIK algorithm are based upon observations that would be available on a modern battlefield (i.e. hourly airway type data obtained from the United States Air Force [USAF] Air Weather Service via the USAF Global Weather Central, or information furnished by the US Army Field Artillery Meteorological Sections).

Observational requirements for the microscale diffusion, atmospheric optics, ambient stability, and wind direction effects upon the obscuring screen were investigated, with the determination being that eight standard meteorological parameters and one terrain characterization index would be sufficient for the KWIK algorithm. The eight meteorological data inputs consist of:

- ceiling height in feet
- cloud cover in percent
- visibility in miles
- precipitation, yes or no
- temperature in degrees F
- dew point temperature in degrees F
- wind direction in degrees (meteorological convention)
- windspeed in knots

The terrain index is the average height, in centimeters, of the surface roughness elements, such as trees, bushes, grasses, or buildings. Relative humidities, which are required for extrapolating yield factors for the smoke munitions, are calculated from the temperatures and dew points.

The stability category scheme used is a composite version developed from the published results of Pasquill,² Turner,³ and Smith.⁴ The composite approach uses Turner's radiation index, ceiling, and cloud modifications to the index, and Smith's windspeeds associated with each Pasquill category. Other inputs related to the calculation of insolation for the determination of the atmospheric stability category, are:

latitude in degrees

direction from equator (north or south)

longitude in degrees

direction from Greenwich (east or west)

altitude above MSL in kilometers

Julian date in three digits

Greenwich civil time in hours

KWIK contains an optics section that is adapted from an approach to atmospheric transmission by Downs.⁵ The transmittance of light at various wavelengths through a path is determined by calculating the attenuation due to (1) absorption by water vapor and (2) scattering by natural atmospheric aerosols.

For a continuous smoke source, such as the HC used in the KWIK phase I trials, the smoke is assumed to have a Gaussian distribution and to diffuse independently in three coordinate directions (X, Y, Z). The crosswind integrated concentration (CWIC) equation used is based on the Gaussian

²Pasquill, F., Atmospheric Diffusion, 2nd edition, Halsted Press, division of John Wiley & Sons, New York, 429 pp, 1974.

³Turner, D. B., "A Diffusion Model for an Urban Area," J Appl Meteorol, 3:83, 1964.

⁴Smith, F. B., "A Scheme for Estimating the Vertical Dispersion of a Plume from a Source Near Ground-Level," (unpublished Meteorological Office note), 1973.

⁵Downs, A. R., "A Review of Atmospheric Transmission Information in the Optical and Microwave Spectral Regions," Report 2710, Ballistic Research Laboratory, Aberdeen Proving Ground, MD, 1976.

distribution function described by Pasquill² and Gifford⁶ and modified by Umstead et al.¹

DESCRIPTION OF TRIALS

Thirty trials were conducted at DPG during July and September of 1980. Groups of three M1 and one M2 HC smoke canisters arranged to simulate dynamically fired 155-mm M116BE projectiles (figure 2) were used.

Test Objectives. The objectives of the KWIK Phase I evaluation test were:

1. To provide an evaluation of the KWIK smoke model by correlating model predictions of obscuration effectiveness with empirical (observer) data.

2. To collect meteorological, photographic, and observer data in order to characterize the meteorological, environmental, and smoke plume behavior for each trial.

3. To compare and evaluate smoke munition expenditure calculations of the KWIK model from successful screens with those obtained by the current method used by the field army.⁷ * *

4. To compare meteorological data from a distant (10 km) source and evaluate its effect on the munition expenditures calculated by the KWIK model.

Meteorological Limitations. No limitations were placed on cloud cover, ambient temperature, or relative humidity. Wind directions were limited to $135^\circ \pm 45^\circ$ or $315^\circ \pm 45^\circ$ (SE or NW winds) to obtain cross-through quartering winds. Desired windspeed range was set at 5 to 17 knots; however, windspeeds

²Pasquill, F., Atmospheric Diffusion, 2nd edition, Halsted Press, division of John Wiley & Sons, New York, 429 pp, 1974.

⁶Gifford, F. A., "An Outline of Theories of Diffusion in the Lower Layers of the Atmosphere," Meteorology and Atomic Energy, D. Slade, editor, US Atomic Energy Commission, Washington, DC, 1968.

¹Umstead, R. K., R. Pena, and F. V. Hansen, "KWIK: An Algorithm for Calculating Munitions Expenditures for Smoke Screening/Obscuration in Tactical Situations," ASL-TR-0030, US Army Atmospheric Sciences Laboratory, White Sands Missile Range, NM, 1979.

⁷JTCG/ME, "Summary Tables of Estimated Ammunition Expenditures to Establish and Maintain Smoke Screens," (unpublished manuscript).

⁸"Field Artillery Smoke," Training Circular 6-20-5, US Army Field Artillery School, Fort Sill, OK, 1975.

⁹FM 6405, "Modern Battlefield Cannon Gunnery," Headquarters, Department of the Army, Washington, DC, 1976.

greater than 17 knots were encountered during the last day of the trials. After reviewing initial results, it was decided to continue the trials under these high wind conditions. Atmospheric stability categories desired for the trials were B, C, D, and E.

Data Requirements. The main data requirements consisted of meteorological, photographic, and visual observational data.

Meteorological data were measured at the test site (horizontal grid) from three different towers (figure 1). Two 10-m towers were located at the southeast and northwest ends of the grid, respectively, and a 32-m tower was located on the northeast side of the grid next to the observation post. Windspeed and wind direction were measured on all three towers at 2 and 10 m, with additional levels at 16 and 32 m on the 32-m tower. Temperature was measured at all four levels of the 32-m tower and at the 2-m level of the 10-m towers. Dew point temperature was measured only at the 2-m level on all meteorological towers. Upper atmospheric data were collected at the Ditto Meteorological Station, located about 10 km east of the test area, at the DPG Ditto Technical Center.

The photographic coverage provided during the trials consisted of three 16-mm color motion picture cameras located as shown in figure 1. The two side cameras were zoomed in on the target area during all trials. The center camera covered the width of the screening area, including smoke sources and target area, for all trials for the duration of the cloud passage.

Color still photographs were taken every 30 seconds during each trial with a camera located near the area of the observation post (figure 1). Also, for all trials, television coverage of the targets was recorded on video tape (taken from behind the target area) during the duration of the cloud passage.

Visible smoke obscuration assessments were made from the observation post. Each observer (with binoculars) was situated in a booth and had an unrestricted view of the target area (figure 1). Separate booths prevented communication between the observers. Each of three observers was assigned one of the three targets, with a fourth observer assigned all three targets. The first three observers activated a recording device when their assigned target was visible. The fourth observer activated a recording device when one or more targets were visible. The signals from each observer were recorded on magnetic tape.

Smoke Impact Area. This area included the screening area plus 30 m to the southeast and to the northwest, for a total of 560 m (figure 1). The required HC smoke canisters for each test were placed on lines a, b, and c (figure 2) along the 115-m length. The munitions along each selected "a" line were ignited simultaneously while the ignition of the "b" and "c" lines were delayed by 2-min time intervals. Each line contained one M2 and three M1 smoke canisters placed lengthwise in a southwest-northeast direction. This arrangement was used to simulate the dispersion pattern of dynamically fired M16 155-mm HC rounds.

KWIK Calculations. An HP85 desktop calculator located at the command post was used to perform the KWIK smoke model munition expenditure calculations. Using the meteorological and site data from the test grid prior

to each trial as inputs, the model produced the outputs that were used for the appropriate trials on a real-time basis (appendix A).

The munition spacing was approximated to the nearest 35 m, in relation to the HC canister array described above. The initial volley was then detonated from the selected "a" lines and the sustaining volleys from the selected "b" and "c" lines, according to the KWIK calculations. Table 1 shows a summary of the 30 trials describing the meteorological inputs used for the calculations, the stability calculated, the munitions expended, and the misfires for each trial.

EVALUATION OF DATA

The evaluation of the data was performed in three parts: (1) the Smoke Screening Assessment, based on the target obscuration data contained in appendix B; (2) the Munition Expenditure Assessment, comparing the KWIK munition expenditures with those obtained using the method in the current FM (FM 6-40-5),⁷ ⁸ and also comparing munition expenditure results using meteorological data collected at the DPG Horizontal Test Grid and at the Ditto Meteorological Station; and (3) High Wind (>8 m/s) Smoke Screening Assessment, based on data from trials 23 through 30. For the purpose of evaluation, all of the test data were grouped according to windspeed as follows: (1) 2.0 to 3.5 m/s, (2) 3.6 to 7.5 m/s, and (3) >8 m/s.

Smoke Screening Assessment. Appendix B contains the target observer assessment data, which was plotted as a function of time. The cross-hashed bars indicate the time when a particular target was scheduled to be visible, and the clear bars represent the time when a particular observer could see his assigned target. These data were analyzed for all trials, except trials 1 through 4, which lacked observer data. Tables 2 and 3 represent the smoke screening assessment for wind groupings 2.0 to 3.5 m/s and 3.6 to 7.5 m/s, respectively. These tables show the total time each target was observed, compared to the time the target was scheduled to be in the field of view. In the case of the fourth observer (labeled "All"), the tables show the total time he viewed any of the targets, compared to the maximum time any target was scheduled to be visible. From this assessment, the percentage of effective screening was obtained. Photographic data from each trial (appendix C) were used to verify the target observer assessment data. The "Initial Time to Screen Target" is the minimum time it took for the screen to completely obscure the target. In some cases, this could not be determined, because wind conditions were variable or because a particular target was not in the field of view until after the screen was completely formed.

Low windspeed screens (2.0 to 3.5 m/s) were successful in four out of six cases, with an average effective screening percentage of 88.3 of the total target time, as shown in table 2. Trial 16 was unsuccessful because of low

⁷JTCG/ME, "Summary Tables of Estimated Ammunition Expenditures to Establish and Maintain Smoke Screens," (unpublished manuscript).

⁸"Field Artillery Smoke," Training Circular 6-20-5, US Army Field Artillery School, Fort Sill, OK, 1975.

TABLE 1. KLIK SMOKE TRIALS, PHASE I DPG, UTAH 1 2

10-M WINDS			HORIZ GRID MET			CLOUD			DITTO MET			MUNITION CALCULATIONS			DITTO MET		
DATE	TRIAL NO.	TO LULU-GMT	DIRECTION (DEGS)	SPEED (KNOTS)	CEILING (K FT)	COVER (%)	TEMP (°F)	DWPT (°F)	STABILITY ³	DIRECTION (DEGS)	SPEED (KNOTS)	STABILITY	EXP. (RDS)	KWIK MISFIRES ⁴ (RDS)	MANUAL (RDS)	KWIK (RDS)	MANUAL (RDS)
7/23/80	1	5 1924:30	160	6	9	20	95	46	B	170	4	A	12	3	22	14	25
	2	5 2052	315	10	7	20	99	43	C	160	5	A	15	5 1/2	8	15	22
	3	5 1838	345	8	15	60	93	43	C	270	6	A	12	1	11	12	12
	4	5 2010	340	8	12	40	96	45	B	300	5	A	18	1 1/2	11	15	21
	5	5 1807	300	10	10	100	68	49	D	260	5	C	9	1 1/4	9	11	11
9/11/80	6	6 1922	300	10	15	100	67	48	D	300	6	C	9	1 1/4	10	8	10
	7	7 2010	310	10	10	90	69	52	D	300	7	C	9	3/4	8	10	10
	8	8 2053	310	12	10	90	70	49	D	300	13	D	9	1 1/2	10	12	12
	9	9 1705	190	12	25	60	76	39	D	150	10	C	18	1 1/2	17	15	9
	10	10 1812	200	14	15	40	77	38	D	160	9	C	27	3	25	12	10
9/15/80	11	11 1954	160	6	15	40	81	40	B	150	7	B	18	1 1/2	22	12	21
	12	12 2050	180	10	5	10	83	36	C	180	6	B	15	1 3/4	12	18	26
	13	13 2202	280	8	15	30	83	34	C	210	2	B	8	1 3/4	14	13	30
	14	14 1438	280	4	10	10	47	32	D	140	2	C	3	3 1/2	8	13	8
	15	15 1339	135	6	2 1/2	0	46	29	D	140	4	F	3	3 1/2	8	13	3
9/16/80	16	16 1427	140	4	2 1/2	0	51	30	D	150	2	C	3	3 1/2	8	10	10
	17	17 1513	130	5	2 1/2	0	59	33	C	120	4	C	3	3 1/2	8	10	10
	18	18 1500	160	6	2 1/2	0	66	34	C	130	2	B	10	1 1/2	10	13	7
	19	19 1314	180	8	2 1/2	0	67	35	E	140	8	E	7	1 1/2	12	7	8
	20	20 1345	150	12	2 1/2	0	68	37	D	150	10	D	12	1 1/2	12	9	9
9/18/80	21	21 1419	160	9	16	10	66	37	D	150	10	D	9	0	10	9	9
	22	22 1451	160	12	16	10	72	38	D	180	14	D	12	1	13	18	18
	23	23 1519	160	16	16	10	72	38	D	180	14	D	18	1 1/2	18	18	18
	24	24 1554	155	17	16	80	79	47	D	180	14(22) 7	D	18	1 1/2	18	18	18
	25	25 1631	160	17	16	80	79	47	D	180	15(22)	D	18	1 1/2	18	18	18
9/25/80	26	26 1707	160	17	15	100	82	47	D	180	14(22)	D	18	2 1/2	High	18	18
	27	27 1746	180	17	15	100	82	47	D	180	14(22)	D	21	1 1/2	Wind	18	18
	28	28 1911	180	19	6	60	85	43	D	180	18(26)	D	27	1 1/2	1 1/2	24	24
	29	29 1955:30	190	17	6	40	88	44	D	170	18(27)	D	27	1 1/2	1 1/2	24	24
	30	30 2053	190	25	6	90	89	42	D	180	15(23)	D	45	4	1 1/2	21	21

NOTES:

1. No precipitation during trials.
2. Visibility for all trials was 30 miles.
3. Calculated by model.
4. Misfires are listed in terms of rounds (4 canisters per round)
5. Data on these trials not usable.
6. Default value for clear sky.
7. () indicates gusts.

TABLE 2. SMOKE SCREENING ASSESSMENT, WIND SPEED: 2.0 - 3.5 m/s

TRIAL NO.	TARGET	INITIAL TIME TO SCREEN TARGET (MIN: SEC)	APPROX. BUILD UP (MIN: SEC)	TARGET SCHEDULE (MIN: SEC)	TIME TARGET OBSERVED (MIN: SEC)	EFFECTIVE SCREENING (%)	MEAN EFFECTIVE SCREENING (%)
11	Tank (T)	*		4:30	0:00	100	
	Jeep (J)	*		2:30	0:00	100	
	Moving (M)	*		5:00	0:45	85	
	All (A)	*	1:00	5:00	1:42	66	88
14	T	*		2:30	0:00	100	
	J	*		(Target down for entire trial)		---	
	M	2:42		5:30	1:50	100	
	A	2:42	2:42	5:30	0:54	100	100
15	T	0:45		6:00	0:45	100	
	J	1:30		6:00	3:30	67	
	M	2:00		6:00	2:15	93	
	A	2:00	2:00	6:00	3:45	67	82
16	T	0:42		6:00	3:18		
	J	5:00		4:00	2:21		
	M	6:00		6:00	4:24		
	A	6:00	*	6:00	4:45	0	0
17	T	*		2:30	0:24	84	
	J	0:48		4:00	0:48	100	
	M	*		5:00	1:36	68	
	A	0:48	0:48	6:00	2:06	78	83
18	T	*		2:00	1:48		
	J	4:00		5:00	2:36		
	M	4:30		6:00	2:12		
	A	6:00	*	6:00	4:18	0	0

* Cannot be determined

TABLE 3. SMOKE SCREENING ASSESSMENT, WINDSPEED 3.6 - 7.5 m/s

TRIAL NO.	TARGET	INITIAL TIME TO SCREEN TARGET (MIN: SEC)	APPROX. BUILD UP (MIN: SEC)	TARGET SCHEDULE (MIN: SEC)	TIME TARGET OBSERVED (MIN: SEC)	EFFECTIVE SCREENING (%)	MEAN EFFECTIVE SCREENING (%)
5	Tank (T)	*		4:30	0:00	100	96
	Jeep (J)	*		2:30	0:12	92	
	Moving (M)	1:12		5:00	0:12	100	
	All (A)	*	1:12	5:00	0:15	95	
6	T	2:00		3:00	2:00	100	98
	J	2:00		5:00	1:18	94	
	M	1:40		3:00	1:40	100	
	A	2:00	2:00	5:00	2:00	100	
7	T	*		2:30	0:00	100	98
	J	1:00		4:00	1:15	94	
	M	*		5:00	0:00	100	
	A	1:00	1:00	6:00	1:00	100	
8	T	*		2:00	0:00	100	100
	J	1:00		5:00	0:00	100	
	M	0:30		6:00	0:30	100	
	A	0:30	1:00	6:00	0:18	100	
9	T	1:00		3:30	0:30	100	100
	J	0:30		3:30	0:00	100	
	M	1:00		5:00	0:00	100	
	A	1:00	1:00	5:00	0:00	100	
10	T	*		3:00	0:00	100	100
	J	0:24		3:00	0:24	100	
	M	0:30		5:30	0:00	100	
	A	0:24	0:30	6:00	0:24	100	

* Cannot be determined

TABLE 3. (cont)

TRIAL NO.	TARGET	INITIAL TIME TO SCREEN TARGET (MIN: SEC)	APPROX. BUILD UP (MIN: SEC)	TARGET SCHEDULE (MIN: SEC)	TIME TARGET OBSERVED (MIN: SEC)	EFFECTIVE SCREENING (%)	MEAN EFFECTIVE SCREENING (%)
12	Tank (T)	0:18		3:00	0:18	100	
	Jeep (J)	1:00		5:00	0:15	95	
	Moving (M)	*		3:00	0:15	92	
	All (A)	0:18	1:00	6:00	0:18	100	97
13	T	1:00		3:00	1:00	100	
	J	1:24		6:00	1:24	100	
	M	0:48		6:00	0:57	97	
	A	1:12	1:24	6:00	1:27	96	98
19	T	0:30		3:30	0:00	100	
	J	0:30		3:30	0:00	100	
	M	1:00		5:00	0:00	100	
	A	1:00	1:00	5:30	0:18	96	99
20	T	*		3:00	0:00	100	
	J	0:42		3:00	0:42	100	
	M	0:50		5:30	0:20	100	
	A	0:50	0:50	5:30	0:50	100	100
21	T	1:30		4:30	0:00	100	
	J	1:00		3:00	0:00	100	
	M	1:25		5:00	0:25	100	
	A	1:25	1:30	5:00	0:25	100	100
22	T	0:24		3:00	0:24	100	
	J	1:00		5:00	0:00	100	
	M	*		3:00	0:00	100	
	A	0:24	1:00	6:00	0:24	100	100

* Cannot be determined

windspeeds (< 2 m/s) which contributed to excessive plume rise, preventing formation of a screen. In trial 18, the windspeeds were also very low (≈ 3 m/s), contributing to excessive plume rise. Significantly, the FM method's predictions for trials 16 and 18 were identical to those produced by KWIK, indicating that both models were unable to predict an effective screen.

Table 3 contains the smoke screening assessment for twelve trials within the wind regime of 3.6 to 7.5 m/s. Most of these trials occurred under neutral atmospheric stability conditions. Two trials (12 and 13) were conducted under slightly unstable conditions and one trial (19) under slightly stable conditions. The overall effective screening assessment for this group was 99 percent.

Munition Expenditure Assessment. Table 4 shows the number of rounds KWIK predicted would obscure the entire 500 m for 6 min for two wind groups under low humidity ($RH \approx 30$ percent) and under high humidity ($RH \approx 80$ percent). The corresponding number of munitions obtained by using the current FM method are also shown for each trial (the same for both humidity levels), as well as the wind direction in relation to the line of sight. For both humidity levels in each wind regime, the net gain or loss in munition expenditures is also indicated. In the case of trial 19, for example, the KWIK model predicted 7 munitions for low humidity and 5 munitions for high humidity, while the FM method predicted 12 munitions. This translates to a munition savings for KWIK of 42 percent and 58 percent, respectively. Munition expenditures cannot be obtained from the FM for windspeeds outside the ranges shown in table 4.

For the lower windspeed group, KWIK produced a net gain in munition savings of 21.4 percent for low humidity and 35.7 percent for high humidity. For the higher windspeed group, KWIK produced a net loss of 2.7 percent for low humidity, but a net gain of 39.4 percent for high humidity. As shown in figure 3, KWIK efficiency in munition expenditures improved as the day progressed when compared to the FM method. This is due to steadily increasing instability from daytime heating. Under the low windspeeds (2.0 to 3.5 m/s), KWIK has the capability of finely describing atmospheric stability while the FM method has only three gross categories. Under the higher windspeeds (3.6 to 7.5 m/s), atmospheric stability tends to remain relatively constant with daytime heating, and therefore little difference in munitions expenditures is noted in figure 4.

The alternating dash-dot curve in figures 3 and 4 represents the number of munitions KWIK calculated to be necessary to screen at a relative humidity of about 80 percent. KWIK's capability of using the hygroscopic properties of HC smoke enables more efficient use of this munition when compared to the FM method. This is demonstrated by the consistently lower munition expenditures calculated for all the plotted trials in figures 3, 4, and 9. A net savings of 35.7 percent during the low windspeeds and 39.4 percent during the higher windspeeds could have been realized under these higher humidities. This higher humidity category ($RH \approx 80$ percent) is a fairly common occurrence in Europe, especially during the predawn and early morning hours. Under these conditions, KWIK could save a significant number of smoke munitions. Figures 5 and 6 represent the same thing as figures 3 and 4, except that meteorological inputs were derived from data collected at the Ditto Meteorological Station. Again, KWIK did better than the FM method as the day progressed in the low windspeed cases, while little or no difference was

TABLE 4. MUNITION EXPENDITURE ASSESSMENT

WINDSPEED: 2.0 - 3.5 m/s

TEST NO.	FIELD MANUAL	KWIK (RH 30%)	% CHANGE (RH 30%)	KWIK (RH 80%)	% CHANGE (RH 80%)	WIND
11	22	12	+45	8	+64	QTR/CROSS
14	14	8	+43	8	+43	QTR/CROSS
15	8	8	0	6	+25	QTR/CROSS
16	8	8	0	8	0	CROSS/QTR
17	8	9	-12.5	7	+12.5	QTR/CROSS
18	10	10	0	8	+20	CROSS/QTR

NET CHANGE	+21.4	NET CHANGE	+35.7
------------	-------	------------	-------

WINDSPEED: 3.6 - 7.5 m/s

5	10	9	+10	7	+30	CROSS/QTR
6	10	9	+10	7	+30	CROSS/QTR
7	8	9	-12.5	7	+12.5	CROSSWIND
8	10	9	+10	6	+40	CROSSWIND
9	17	18	-6	9	+47	QTR/HEAD
10	25	27	-8	15	+40	QTR/HEAD
12	12	18	-50	9	+25	QUARTERING
13	12	15	-25	7	+42	QTR/CROSS
19	12	7	+42	5	+58	QUARTERING
20	11	12	-9	6	+45	CROSS/QTR
21	10	9	+10	7	+30	CROSS/QTR
22	13	12	+8	6	+54	CROSS/QTR

NET CHANGE	-2.7	NET CHANGE	+39.4
------------	------	------------	-------

observed in the higher windspeed cases. If relative humidities had been higher, KWIK's performance would have been greatly enhanced as compared to the FM method.

Figures 7 and 8 compare munition expenditure calculations based on both the horizontal grid meteorology and the Ditto meteorology. For the low windspeeds (figure 7) KWIK consistently calculated lower munition expenditures with the horizontal grid meteorology. This calculation is not entirely unexpected because with low windspeeds local effects caused by terrain features and solar heating tend to dominate the microscale meteorology. For the higher windspeeds (figure 8) there is no apparent mean difference between the two methods, although there were wide differences on any given trial between KWIK and the FM method. One possible explanation for this variation could be Granite Mountain, which is just a few km southwest through southeast of the grid. This might have set up mountain lee waves with a southeast wind flow, resulting in much higher windspeeds at the test grid than at the Ditto Meteorological Station.

High Wind Screening. Trials 23 through 30 were conducted at windspeeds in excess of 16 knots. Army Training Circular TC 6-20-5, entitled "Field Artillery Smoke," indicates that smoke screening at these windspeeds is unfavorable. Nevertheless, it was decided that the testing would continue as long as a successful screen could be deployed, since no other data of this type existed. As shown in table 5A, windspeeds ranged from 18 to 30 knots (8.8 to 15 m/s), with gusts to 40 knots (20 m/s). At these windspeeds a neutral stability was maintained through all trials, as was later verified by examining cloud behavior from photographic records. The number of munitions calculated for the 6-min screens ranged from 18 to 45, with the higher figure calculated during a near gale with a quartering/headwind direction. A typical scenario would involve 1/3 of the total munitions expended initially for establishing the screen and 1/3 every two minutes for maintaining the screen. Figure 9 shows the number of munitions needed to successfully form a screen (from a low of 18 to a high of 27) for trials 23 through 29. The meteorological input from the Ditto Meteorological Station indicated identical munition expenditures during the morning hours, but somewhat lower amounts during the afternoon hours when the winds were higher. Since the higher winds were experienced at the horizontal grid, probably due to mountain lee waves, it was not surprising to see the slight difference in munition expenditures as calculated from data taken at the two meteorological stations.

The smoke screen characteristics for the high wind cases are indicated in table 5B. The build-up time is defined as the time, after T-0, required to obscure all targets from the observers' view. The duration of the screen is the time period from initiation of a test to the instant when a target became visible to one or more of the observers. The total effective screening time is the total time that all targets were continually screened from all observers.

For the eight trials, the mean build-up time was 28.75 s with a mean effective screening time of 6 min and 17 s. In all cases, once the screen had formed there were no apparent holes until the screen began to break up at the end of the trial. It was surprising to note that the best screens in quality and duration, as judged by observer and photographic data, occurred during the higher winds.

TABLE 5A. WIND SPEED (WS) > 8 m/s VS CALCULATED MUNITION EXPENDITURES

<u>TRIAL NO.</u>	<u>WS(M/S)</u>	<u>STABILITY</u>	<u>ROUNDS CALCULATED</u>	<u>ROUNDS DETONATED</u>	<u>DIRECTION</u>
23	9-12	D	18	17	CROSS/QUARTER
24	8.8-12	D	18	16.75	CROSS/QUARTER
25	9.7-13	D	18	17	CROSS/QUARTER
26	8.7-12	D	18	15.75	CROSS/QUARTER
27	11.7-15.5	D	21	20	QUARTER
28	12.8-18	D	27	25.5	QUARTER
29	12.3-19.5	D	27	25.5	QUARTER
30	15-20	D	45*	41	QUARTER/HEAD

*Calculated during near gale.

The similarity of the munition expenditure calculations from both Ditto Meteorological Station and the horizontal grid met station would seem to indicate that under certain synoptic scale events, the target meteorology is similar to the meteorology several km away. These types of large scale weather systems are not unusual in Europe, especially during the winter months. Another common feature during the winter storms is high relative humidity ($RH \approx 80$ percent). Results using such a high relative humidity are plotted in figure 9. All other meteorological parameters are identical. A reduction in munitions of 47.39 percent over the cases with lower humidities illustrates the wide variation possible under varying ambient moisture conditions. This variation is important, considering that the FM method does not have the capability to screen under high winds or to use the ambient moisture to reduce expenditures under high humidities.

CONCLUSIONS

Screening Effectiveness. In this initial phase of testing, KWIK has demonstrated that it not only is more efficient in munition utilization than the FM method, but that it also has the capability to calculate munition expenditures under meteorological conditions which the present FM method considers impractical. For the low windspeed or marginal screening category (2.0 to 3.5 m/s), two trials were unsuccessful in forming a screen because low windspeeds and extreme variability of wind direction. Since calculations for these same two trials using the FM method produced identical munition expenditures, both techniques failed to successfully screen under these meteorological conditions. The remaining four trials in the low wind category produced a mean effective smoke screen during 88.3 percent of the screen

duration time. The few instances during which a target was visible were almost always caused by significant changes in windspeed and wind direction during the course of a trial.

There were twelve trials conducted under favorable screening conditions, with windspeeds ranging from 3.6 to 7.5 m/s. These trials produced a 99 percent mean effective screen. All of these screens would have denied acquisition of a target for the duration of the screen.

Munition Expenditure Comparisons. Phase I was conducted under dry conditions, with an average relative humidity of only 30.5 percent. These dry conditions are important, because hexachloroethane is a hygroscopic smoke whose screen capabilities are greatly enhanced under the higher humidities that are frequently found in Europe. For the marginal screening category, KWIK used 21.4 percent fewer munitions than the FM method. However, under high humidities (RH $\approx$ 80 percent), KWIK could have saved 35.7 percent of the rounds that the FM method required for the same missions.

In the favorable screening category KWIK used 2.7 percent more munitions than the FM method required. However, under high humidities (RH $\approx$ 80 percent), KWIK would have produced a 39.4 percent savings in munitions expenditures. The failure to incorporate the relative humidity effects into the FM method clearly causes an excess expenditure of smoke rounds under the higher humidity conditions.

High Wind Screening. One of the surprises of Phase I was the discovery that it is practical to screen a target during high winds. Eight trials were conducted under high wind (8.0 to 15.0 m/s) or "unfavorable" screening conditions, with a 100 percent mean effective screen. All these screens obscured all targets for more than the required 6 min as seen in table 5B.

TABLE 5B. SCREEN CHARACTERISTICS

TRIAL NO	BUILD-UP TIME (S)	DURATION OF SCREEN (MIN:S)	TOTAL EFFECTIVE SCREENING TIME (MIN:S)
23	30	6:40	6:10
24	30	6:50	6:20
25	40	6:40	6:00
26	42	6:45	6:03
27	15	6:55	6:40
28	28	6:50	6:22
29	30	6:40	6:10
30	15	6:45	6:30
MEAN	28.75	6:46	6:17


There are several possible reasons for the successful screening at high windspeeds. One plausible explanation is that the vegetation flattens as the windspeed increases lowering the effective roughness length. This lowering of the roughness length would change the dispersion parameters, which are critical to the correct calculation of munition expenditures. Examining table 5A, it is noted that the actual number of munitions that successfully detonated was always less than the number calculated. Since all of the screens were successful, this over-prediction of needed munitions could be due to wind-modified roughness length.

Another possibility is the homogeneity of the terrain at DPG. It is possible that for heterogeneous terrain or terrain with extensive vegetation, such as a forest, the increased turbulence at higher windspeeds would preclude the use of smoke.

A third possibility is a change in the efficiency of continuous burning smoke munitions during high winds. An increase in the oxygen available to the munition could conceivably improve the efficiency.

Regardless of the reason or combination of reasons for the high-wind smoke screening, further investigation is clearly warranted. If future experiments confirm that smoke screening at high windspeeds is feasible, then a change in doctrine would be indicated. This could give friendly forces an advantage in future confrontations using smoke.

Target Area Meteorology. Under marginal screening conditions, the winds are variable in both space and time. Even under the relatively uniform terrain of DPG, use of the target area meteorology produced a savings in munition expenditures, as shown in figure 7. As windspeeds increase, local wind circulations disperse and the general flow becomes more uniform (figure 9). During the transition period between low and high windspeeds, tremendous variability can exist over a spatial distance of only 10 km (figure 8). In the wintertime European scenario, major storms covering hundreds of km are quite common. Many of these storms are associated with windspeeds high enough to preclude the necessity of knowing target area meteorology to perform a mission. (This assumes that the terrain features do not dominate the target area meteorology.) Under weaker wind regimes, which occur in Europe during the summer season, local wind circulations would make the availability of target area meteorology desirable or even necessary for the completion of a mission.



**TEST GRID FOR KWIK SMOKE TESTS
PHASE I DPG, UTAH**

Figure 1. Test grid for KWIK smoke tests, Phase I, DPG, Utah.




Figure 2. Center portion of HC array at smoke impact area (sets 8 to 10).




Figure 3. Munition comparison: KWIK vs field manual using Horizontal Grid met (windspeed: 2.0 to 3.5 m/s).




Figure 4. Munition comparison: KWIK vs field manual using Horizontal Grid met (windspeed: 3.6 to 7.5 m/s).




Figure 5. Munition comparison: KWIK vs field manual using Ditto Met Station data (windspeed: 2.0 to 3.5 m/s).




Figure 6. Munition comparison: KWIK vs field manual using Ditto Met Station data (windspeed: 3.6 to 7.5 m/s).




Figure 7. Meteorological comparison: Ditto vs Horizontal Grid met data (windspeed: 2.0 to 3.5 m/s).




Figure 8. Meteorological comparison: Ditto vs Horizontal Grid met data (windspeed: 3.6 to 7.5 m/s).




Figure 9. Meteorological comparison: Ditto vs Horizontal Grid met data (windspeed: > 8.0 m/s).

REFERENCES

1. Umstead, R. K., R. Pena, and F. V. Hansen, "KWIK: An Algorithm for Calculating Munition Expenditures for Smoke Screening/Obscuration in Tactical Situations," ASL-TR-0030, US Army Atmospheric Sciences Laboratory, White Sands Missile Range, NM, 1979.
2. Pasquill, F., Atmospheric Diffusion, 2nd edition Halsted Press, division of John Wiley & Sons, New York, 429 pp, 1974.
3. Turner, D. B., "A Diffusion Model for an Urban Area," J Appl Meteorol, 3:83, 1964.
4. Smith, F. B., "A Scheme for Estimating the Vertical Dispersion of a Plume from a Source Near Ground-Level," (unpublished Meteorological Office note), 1973.
5. Downs, A. R., "A Review of Atmospheric Transmission Information in the Optical and Microwave Spectral Regions," Report 2710, Ballistic Research Laboratory, Aberdeen Proving Ground, MD, 1976.
6. Gifford, F. A., "An Outline of Theories of Diffusion in the Lower Layers of the Atmosphere," Meteorology and Atomic Energy, D. Slade, editor, US Atomic Energy Commission, Washington, DC, 1968.
7. JTCG/ME, "Summary Tables of Estimated Ammunition Expenditures to Establish and Maintain Smoke Screens," (unpublished manuscript).
8. "Field Artillery Smoke," Training Circular 6-20-5, US Army Field Artillery School, Fort Sill, OK, 1975.
9. FM 6405, "Modern Battlefield Cannon Gunnery," Headquarters, Department of the Army, Washington, DC.

APPENDIX A

KWIK MODEL OUTPUT CALCULATIONS

This section contains the HP85 data output run for each of the 30 trials conducted for the KWIK Phase I evaluation tests. The stability category and relative humidity are calculated by the model.

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	1
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	205
ZULU TIME	HR =	19
CEILING	M =	3657.6
CLOUD COVER	% =	20
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	33.3
DEWPOINT	DEG =	7.8
WIND DIRECTION	DEG =	160.0
WIND SPEED	KTS =	6.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY B
RELATIVE HUMIDITY 20.6

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/	SPACING	ROUNDS
	MIN	METERS	
INITIAL:	4	139	
SUSTAIN:	4 .5	142	12

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	2
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	205
ZULU TIME	HR =	21
CEILING	M =	2133.6
CLOUD COVER	% =	20
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	35.6
DEWPOINT	DEG =	6.1
WIND DIRECTION	DEG =	315.0
WIND SPEED	KTS =	10.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY C
RELATIVE HUMIDITY 16.3

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/	SPACING	ROUNDS
	MIN	METERS	
INITIAL:	5	113	
SUSTAIN:	5 .5	113	15

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	3
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	206
ZULU TIME	HR =	18
CEILING	M =	4572.0
CLOUD COVER	% =	60
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	33.9
DEWPOINT	DEG =	8.9
WIND DIRECTION	DEG =	345.0
WIND SPEED	KTS =	8.0
ROUGHNESS ELEMENT CM	=	27.0

PASQUILL STABILITY CATEGORY C
RELATIVE HUMIDITY 21.6

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	4
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	206
ZULU TIME	HR =	20
CEILING	M =	3657.6
CLOUD COVER	% =	40
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	35.6
DEWPOINT	DEG =	7.2
WIND DIRECTION	DEG =	340.0
WIND SPEED	KTS =	8.0
ROUGHNESS ELEMENT CM	=	27.0

PASQUILL STABILITY CATEGORY B
RELATIVE HUMIDITY 17.5

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/	SPACING	ROUNDS
	MIN	METERS	
INITIAL:	4	139	
SUSTAIN:	4 .5	139	12

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/	SPACING	ROUNDS
	MIN	METERS	
INITIAL:	6	99	
SUSTAIN:	6 .5	99	18

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	5
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	255
ZULU TIME	HR =	18
CEILING	M =	3048.0
CLOUD COVER	% =	100
VISIBILITY	KM =	32.2
PRECIPITATION	=	NO
TEMPERATURE	DEG =	20.0
DEWPOINT	DEG =	9.4
WIND DIRECTION	DEG =	300.0
WIND SPEED	KTS =	10.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 50.6

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	6
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	255
ZULU TIME	HR =	19
CEILING	M =	4572.0
CLOUD COVER	% =	100
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	19.4
DEWPOINT	DEG =	8.9
WIND DIRECTION	DEG =	300.0
WIND SPEED	KTS =	10.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 50.4

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	3		232	
SUSTAIN:	3	.5	233	9

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	3		227	
SUSTAIN:	3	.5	227	9

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	7
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	255
ZULU TIME	HR =	20
CEILING	M =	3048.0
CLOUD COVER	% =	90
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	20.6
DEWPOINT	DEG =	11.1
WIND DIRECTION	DEG =	310.0
WIND SPEED	KTS =	10.0
ROUGHNESS ELEMENT CM	=	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 54.6

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	8
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	255
ZULU TIME	HR =	21
CEILING	M =	3048.0
CLOUD COVER	% =	90
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	21.1
DEWPOINT	DEG =	9.4
WIND DIRECTION	DEG =	310.0
WIND SPEED	KTS =	12.0
ROUGHNESS ELEMENT CM	=	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 47.2

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	3	232	
SUSTAIN:	3 .5	246	9

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	3	180	
SUSTAIN:	3 .5	180	9

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	9
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	259
ZULU TIME	HR =	17
CEILING	M =	7620.0
CLOUD COVER	% =	60
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	23.9
DEWPOINT	DEG =	2.8
WIND DIRECTION	DEG =	190.0
WIND SPEED	KTS =	12.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 25.2

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	6		90	
SUSTAIN:	6	.5	90	18

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	10
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	259
ZULU TIME	HR =	18
CEILING	M =	4572.0
CLOUD COVER	% =	40
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	25.0
DEWPOINT	DEG =	3.3
WIND DIRECTION	DEG =	200.0
WIND SPEED	KTS =	14.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 24.5

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	9		58	
SUSTAIN:	9	.5	58	27

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	11
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	259
ZULU TIME	HR =	20
CEILING	M =	4572.0
CLOUD COVER	% =	40
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	27.2
DEWPOINT	DEG =	4.4
WIND DIRECTION	DEG =	160.0
WIND SPEED	KTS =	6.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY B
RELATIVE HUMIDITY 23.2

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL: 4		139	
SUSTAIN: 4	.5	145	12

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	12
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	259
ZULU TIME	HR =	21
CEILING	M =	7620.0
CLOUD COVER	% =	10
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	28.3
DEWPOINT	DEG =	1.7
WIND DIRECTION	DEG =	180.0
WIND SPEED	KTS =	10.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY C
RELATIVE HUMIDITY 17.9

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL: 6		84	
SUSTAIN: 6	.5	84	18

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 13
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 259
ZULU TIME HR = 22
CEILING M = 4572.0
CLOUD COVER % = 30
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 28.3
DEWPOINT DEG = 1.1
WIND DIRECTION DEG = 280.0
WIND SPEED KTS = 8.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY C
RELATIVE HUMIDITY 17.2

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	5		123	
SUSTAIN:	5	.5	123	15

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 14
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 260
ZULU TIME HR = 14
CEILING M = 3048.0
CLOUD COVER % = 10
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 8.3
DEWPOINT DEG = 0.0
WIND DIRECTION DEG = 280.0
WIND SPEED KTS = 4.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 55.7

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	6		93	
SUSTAIN:	1	.5	643	8

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	15
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	261
ZULU TIME	HR =	14
CEILING	M =	7620.0
CLOUD COVER	% =	0
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	7.8
DEWPOINT	DEG =	-1.7
WIND DIRECTION	DEG =	105.0
WIND SPEED	KTS =	6.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 50.3

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	4		139	
SUSTAIN:	2	.5	383	8

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	16
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	261
ZULU TIME	HR =	14
CEILING	M =	7620.0
CLOUD COVER	% =	0
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	10.6
DEWPOINT	DEG =	-1.1
WIND DIRECTION	DEG =	140.0
WIND SPEED	KTS =	4.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 43.7

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	6		93	
SUSTAIN:	1	.5	679	8

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 17
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 261
ZULU TIME HR = 15
CEILING M = 7620.0
CLOUD COVER % = 0
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 15.0
DEWPOINT DEG = .6
WIND DIRECTION DEG = 130.0
WIND SPEED KTS = 5.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY C
RELATIVE HUMIDITY 37.3

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 18
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 261
ZULU TIME HR = 16
CEILING M = 7620.0
CLOUD COVER % = 0
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 18.3
DEWPOINT DEG = 1.1
WIND DIRECTION DEG = 160.0
WIND SPEED KTS = 6.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY C
RELATIVE HUMIDITY 31.4

VISIBLE:

METERS MIN
SCREEN LENGTH/DURATION: 500 6

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	5		116	
SUSTAIN:	2	.5	314	9

VISIBLE:

METERS MIN
SCREEN LENGTH/DURATION: 500 6

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	4		139	
SUSTAIN:	3	.5	221	10

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 19
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 262
ZULU TIME HR = 13
CEILING M = 7620.0
CLOUD COVER % = 0
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 19.4
DEWPOINT DEG = 1.7
WIND DIRECTION DEG = 180.0
WIND SPEED KTS = 8.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY E
RELATIVE HUMIDITY 30.5

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	3		185	
SUSTAIN:	2	.5	357	7

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 20
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 262
ZULU TIME HR = 14
CEILING M = 7620.0
CLOUD COVER % = 0
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 20.0
DEWPOINT DEG = 2.8
WIND DIRECTION DEG = 150.0
WIND SPEED KTS = 12.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 31.9

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	4		151	
SUSTAIN:	4	.5	151	12

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 21
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 262
ZULU TIME HR = 14
CEILING M = 7620.0
CLOUD COVER % = 0
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 20.0
DEWPOINT DEG = 2.8
WIND DIRECTION DEG = 160.0
WIND SPEED KTS = 9.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 31.9

VISIBLE:

SCREEN LENGTH/DURATION: METERS MIN
500 6

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	3		204	
SUSTAIN:	3	.5	204	9

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 22
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 262
ZULU TIME HR = 14
CEILING M = 4876.8
CLOUD COVER % = 10
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 22.2
DEWPOINT DEG = 3.3
WIND DIRECTION DEG = 160.0
WIND SPEED KTS = 12.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 29.0

VISIBLE:

SCREEN LENGTH/DURATION: METERS MIN
500 6

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	4		139	
SUSTAIN:	4	.5	139	12

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	23
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	262
ZULU TIME	HR =	15
CEILING	M =	4876.8
CLOUD COVER	% =	10
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	22.2
DEWPOINT	DEG =	3.3
WIND DIRECTION	DEG =	160.0
WIND SPEED	KTS =	16.0
ROUGHNESS ELEMENT CM	=	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 29.0

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	24
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	262
ZULU TIME	HR =	16
CEILING	M =	4876.8
CLOUD COVER	% =	80
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	26.1
DEWPOINT	DEG =	8.3
WIND DIRECTION	DEG =	155.0
WIND SPEED	KTS =	17.0
ROUGHNESS ELEMENT CM	=	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 32.4

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL: 6		97	
SUSTAIN: 6	.5	97	18

VISIBLE:

SCREEN LENGTH/DURATION: 500 6 METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL: 6		97	
SUSTAIN: 6	.5	97	18

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 25
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 262
ZULU TIME HR = 16
CEILING M = 4876.8
CLOUD COVER % = 80
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 26.1
DEWPOINT DEG = 8.3
WIND DIRECTION DEG = 160.0
WIND SPEED KTS = 17.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 32.4

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 26
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 262
ZULU TIME HR = 17
CEILING M = 4572.0
CLOUD COVER % = 100
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 27.8
DEWPOINT DEG = 8.3
WIND DIRECTION DEG = 160.0
WIND SPEED KTS = 17.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 29.4

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	6		93	
SUSTAIN:	6	.5	93	18

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	6		91	
SUSTAIN:	6	.5	91	18

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	27
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	262
ZULU TIME	HR =	18
CEILING	M =	4572.0
CLOUD COVER	% =	100
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	27.8
DEWPOINT	DEG =	8.3
WIND DIRECTION	DEG =	180.0
WIND SPEED	KTS =	17.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 29.4

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	7		73	
SUSTAIN:	7	.5	73	21

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER	=	28
ID	=	DPG
LATITUDE	DEG = N	40.2
LONGITUDE	DEG = W	112.7
ALTITUDE	KM =	1.3
JULIAN DATE	DAY =	262
ZULU TIME	HR =	19
CEILING	M =	1828.8
CLOUD COVER	% =	60
VISIBILITY	KM =	48.3
PRECIPITATION	=	NO
TEMPERATURE	DEG =	29.4
DEWPOINT	DEG =	6.1
WIND DIRECTION	DEG =	180.0
WIND SPEED	KTS =	19.0
ROUGHNESS ELEMENT	CM =	27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 22.9

VISIBLE:

SCREEN LENGTH/DURATION: 500 6
METERS MIN

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY	GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL:	9		59	
SUSTAIN:	9	.5	59	27

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 29
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 262
ZULU TIME HR = 20
CEILING M = 1828.8
CLOUD COVER % = 40
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 30.6
DEWPOINT DEG = 6.7
WIND DIRECTION DEG = 190.0
WIND SPEED KTS = 17.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 22.4

MUNITION EXPENDITURES
FOR HC SMOKE
DPG TESTS

TRIAL NUMBER = 30
ID = DPG
LATITUDE DEG = N 40.2
LONGITUDE DEG = W 112.7
ALTITUDE KM = 1.3
JULIAN DATE DAY = 262
ZULU TIME HR = 21
CEILING M = 1828.8
CLOUD COVER % = 90
VISIBILITY KM = 48.3
PRECIPITATION = NO
TEMPERATURE DEG = 31.7
DEWPOINT DEG = 5.6
WIND DIRECTION DEG = 190.0
WIND SPEED KTS = 25.0
ROUGHNESS ELEMENT CM = 27.0

PASQUILL STABILITY CATEGORY D
RELATIVE HUMIDITY 19.4

VISIBLE:

SCREEN LENGTH/DURATION: METERS MIN
500 6

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL: 9		57	
SUSTAIN: 9	.5	57	27

VISIBLE:

SCREEN LENGTH/DURATION: METERS MIN
500 6

HC SMOKE SCREEN

155MM HOWITZER

VOLLEY GUNS	RATE/ MIN	SPACING METERS	ROUNDS
INITIAL: 15		34	
SUSTAIN: 15	.5	34	45


APPENDIX B

TARGET OBSERVER ASSESSMENTS

The target observer assessments for trials 5 through 30 are given. No observer data were available for trials 1 through 4. Even though all trials were run for 8 min, the KWIK model calculations were based on a 6-min screening period, as indicated by the dashed line on the graphs.


DATE: 11 SEP 80
 To: 1807Z
 WS: 5.5 m/sec
 WD: 275 deg
 STABILITY: D
 RH: 51%
 MUNITION EXP: 9

● : Target never seen by observer 18% scoring




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 5

DATE: 11 SEP 80
 To: 1922Z
 WS: 4.5 m/sec
 WD: 285 deg
 STABILITY: D
 MUNITION EXP: 9




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 6
 DPG, UTAH

DATE: 11 SEP 80
 To: 2010Z
 WS: 5.5 m/sec
 WD: 302 deg.
 STABILITY: D
 RH: 55%
 MUNITION EXP: 9




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 7
 DPG, UTAH

DATE: 11 SEP 80
 To: 2053Z
 WS: 5.2 m/sec
 WD: 317 deg
 STABILITY: D
 MUNITION EXP: 9




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 8
 DPG, UTAH

DATE: 15 SEP 80
 To: 1705Z
 WS: 6.3 m/sec
 WD: 193 deg
 STABILITY: D
 MUNITION EXP: 18




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 9
 DPG, UTAH

DATE: 15 SEP 80
 To: 1812Z
 WS: 6.0 m/sec
 WD: 187 deg
 STABILITY: D
 RH: 25%
 MUNITION EXP: 27




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 10
 DPG, UTAH

DATE: 15 SEP 80
 To: 2050Z
 WS: 3.3 m/sec
 WD: 185 deg.
 STABILITY: C
 RH: 18%
 MUNITION EXP: 18




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 12
 DPG, UTAH

DATE: 15 SEP 80
 To: 1954Z
 WS: 2.8 m/sec
 WD: 213 deg
 STABILITY: B
 MUNITION EXP: 12



TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 11
 DPG, UTAH


DATE: 15 SEP 80
 To: 2202Z
 WS: 2.8 m/sec
 WD: 237 deg
 STABILITY: C
 MUNITION EXP: 15



TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 13
 DPG, UTAH


DATE: 16 SEP 80
 To: 1438Z
 WS: 1.7 m/sec
 WD: 275 deg
 STABILITY: D
 MUNITION EXP: 7

● : Target never seen by observer




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 14
 DPG, UTAH

DATE: 17 SEP 80
 To: 1339Z
 WS: 3.8 m/sec
 WD: 90 deg.
 STABILITY: D
 RH: 50%
 MUNITION EXP: 8




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 15
 DPG, UTAH

DATE: 17 SEP 80
 To: 1427Z
 WS: 1.7 m/sec
 WD: 142 deg
 STABILITY: D
 MUNITION EXP: 7




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 16
 DPG, UTAH

DATE: 17 SEP 80
 To: 1513Z
 WS: 2.5 m/sec
 WD: 145 deg
 STABILITY: C
 MUNITION EXP: 9



TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 17
 DPG, UTAH

DATE: 17 SEP 80
 To: 1600Z
 WS: 2.8 m/sec
 WD: 152 deg
 STABILITY: C
 MUNITION EXP: 10



TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 18
 DPG, UTAH

DATE: 16 SEP 80

To: 1314Z

WS: 6.2 m/sec


WD: 158 deg.

STABILITY: E

RH: 31%

MUNITION EXP: 7

•: TARGET NOT SEEN BY OBSERVER



TARGET OBSERVER ASSESSMENT

KWIK I TEST TRIAL No. 19

DPG, UTAH

DATE: 18 SEP 80

To: 1345Z

WS: 6.5 m/sec


WD: 145 deg.

STABILITY: D

RH: 32%

MUNITION EXP: 12

•: TARGET NOT SEEN BY OBSERVER



TARGET OBSERVER ASSESSMENT

KWIK I TEST TRIAL No. 20

DPG, UTAH

DATE: 18 SEP 80

TO: 1419

WS: 6 m/sec

WD: 148 deg

STABILITY: D

RH:

MUNITION EXP: 9

●: Target never seen by observer

ALL TARGETS OBSERVER

JEEP OBSERVER

JEEP SCHEDULE

MOVING TARGET OBSERVER

MOVING TARGET SCHEDULE

TANK OBSERVER

TANK SCHEDULE

☐

●

|||||

☐

|||||

☐

|||||

ALL TARGETS OBSERVER

JEEP OBSERVER

JEEP SCHEDULE

MOVING TARGET OBSERVER

MOVING TARGET SCHEDULE

TANK OBSERVER

TANK SCHEDULE

☐

☐

|||||

☐

|||||

☐

|||||

DATE: 18 SEP 80

TO: 1451

WS: 6.8 /sec, 9.0 m/sec gust

WD: 145 deg

STABILITY: D

RH:

MUNITION EXP: 12

ALL TARGETS OBSERVER

JEEP OBSERVER

JEEP SCHEDULE

MOVING TARGET OBSERVER

MOVING TARGET SCHEDULE

TANK OBSERVER

TANK SCHEDULE

☐

☐

|||||

☐

|||||

☐

|||||

T-0 +2 +4 +6 +8
TIME, MINUTES

TARGET OBSERVER ASSESSMENT

KWIK I TEST TRIAL No. 21

DPG, UTAH

T-0 +2 +4 +6 +8
TIME, MINUTES


TARGET OBSERVER ASSESSMENT

KWIK I TEST TRIAL No. 22

DPG, UTAH

DATE: 18 SEP 80
 To: 1519Z
 WS: 9-12 m/sec
 WD: 145 deg.


STABILITY: D
 MUNITION EXP: 18 (MISFIRE: 1)



TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 23
 DPG, UTAH


DATE: 18 SEP 80
 To: 1554Z
 WS: 8.8 - 12 m/sec
 WD: 142 deg.

STABILITY: D
 MUNITION EXP: 18 (MISFIRE: 1)




TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 24
 DPG, UTAH

DATE: 18 SEP 80
 To: 1631Z
 WS: 9.7-13 m/sec
 WD: 138 deg.
 STABILITY: D
 MUNITION EXP: 18 (MISFIRES: 1)



TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 25
 DPG, UTAH

DATE: 18 SEP 80
 To: 1707Z
 WS: 8.7-12 m/sec
 WD: 112 deg.
 STABILITY: D
 MUNITION EXP: 18 (MISFIRES: 2)



TARGET OBSERVER ASSESSMENT
 KWIK I TEST TRIAL No. 26
 DPG, UTAH

DATE: 18 SEP 80


To: 1746Z

WS: 11.7-15.5 m/sec

WD: 188 deg.

STABILITY: D

MUNITION EXP: 21 (MISFIRES: 1)



TARGET OBSERVER ASSESSMENT

KWIK I TEST TRIAL No. 27

DPG, UTAH

DATE: 18 SEP 80


To: 1911Z

WS: 12.8-18 m/sec

WD: 192 deg.

STABILITY: D

MUNITION EXP: 27 (MISFIRES: 1)




TARGET OBSERVER ASSESSMENT

KWIK I TEST TRIAL No. 28


DPG, UTAH

MUNITION EXP: 27 (MISFIRES: 1'2)



DPG, UTAH

MUNITION EXP: 15 (MISFIRES: 1)



DPG, UTAH

APPENDIX C


PHOTOGRAPHIC DATA

Photographs are shown of five trials representative of different atmospheric stability conditions encountered during the 30 trials. Each photograph shows a 30-s time sequence from $T + 0$ to $T + 240$.

The windspeed and wind direction are shown as an average value during the trial. Trial 25 shows the average wind and gust experienced.

KWIK TRIAL 11 1954 GMT 15 SEP 80

WS : 5 KNOTS WD : 213° STAB. CAT. : B MUN. EXP. : 12



T+0 SEC




T+30



T+60



T+90



T+120




T+150



T+180




T+210



T+240

KWIK TRIAL 12 2050 GMT 15 SEP 80
WS : 6 KNOTS WD : 185° STAB. CAT. : C MUN. EXP. : 18




T+60



T+150



T+240




T+30



T+120



T+210



T+0 SEC



T+90



T+180


KWIK TRIAL 15 1339 GMT 17 SEP 80
WS : 7 KNOTS WD : 90 STAB. CAT: D MUN. EXP. : 8




T+60



T+30



T+0 SEC



T+150



T+120



T+90



T+240




T+210



T+180

KWIK TRIAL 19 1314 GMT 18 SEP 80

WS : 12 KNOTS WD : 158° STAB. CAT. : E MUN. EXP. 7




T+60



T+150



T+240




T+30




T+120



T+210



T+0 SEC



T+90



T+180


KWIK TRIAL 25 1631 GMT 18 SEP 80
WS : 20/26 KNOTS WD : 138° STAB. CAT. : D MUN. EXP. : 18



T+0 SEC




T+30



T+60



T+90



T+120



T+150



T+180



T+210



T+240

DISTRIBUTION LIST

Commander
US Army Aviation Center
ATTN: ATZQ-D-MA
Fort Rucker, AL 36362

John M. Hobbie
c/o Kentron International
2003 Byrd Spring Road
Huntsville, AL 35807

Chief, Atmospheric Sciences Div
Code ES-81
NASA
Marshall Space Flight Center, AL 35812

Commander
US Army Missile Command
ATTN: DRDMI-RR/Dr. O. M. Essenwanger
Redstone Arsenal, AL 35809

Commander
US Army Missile Command
ATTN: DRSMI-OG (B. W. Fowler)
Redstone Arsenal, AL 35809

Commander
US Army Missile R&D Command
ATTN: DRDMI-TEM (R. Haraway)
Redstone Arsenal, AL 35809

Redstone Scientific Information Center
ATTN: DRSMI-RPRD (Documents)
US Army Missile Command
Redstone Arsenal, AL 35809

Commander
HQ, Fort Huachuca
ATTN: Tech Ref Div
Fort Huachuca, AZ 85613

Commander
US Army Intelligence
Center & School
ATTN: ATSI-CD-MD
Fort Huachuca, AZ 85613

Commander
US Army Yuma Proving Ground
ATTN: Technical Library
Bldg 2105
Yuma, AZ 85364

Dr. Frank D. Eaton
Geophysical Institute
University of Alaska
Fairbanks, AK 99701

Naval Weapons Center
Code 3918
ATTN: Dr. A. Shlanta
China Lake, CA 93555

Commanding Officer
Naval Envir Prediction Rsch Facility
ATTN: Library
Monterey, CA 93940

Sylvania Elec Sys Western Div
ATTN: Technical Reports Lib
PO Box 205
Mountain View, CA 94040

Tetra Tech Inc.
ATTN: L. Baboolal
630 N. Rosemead Blvd.
Pasadena, CA 91107

Geophysics Officer
PMTC Code 3250
Pacific Missile Test Center
Point Mugu, CA 93042

Commander
Naval Ocean Systems Center
(Code 4473)
ATTN: Technical Library
San Diego, CA 92152

Meteorologist in Charge
Kwajalein Missile Range
PO Box 67
APO San Francisco, CA 96555

Director
NOAA/ERL/APCL R31
RB3-Room 567
Boulder, CO 80302

Library-R-51-Tech Reports
NOAA/ERL
320 S. Broadway
Boulder, CO 80303

National Center for Atmos Rsch
Mesa Library
P. O. Box 3000
Boulder, CO 80307

Dr. B. A. Silverman D-1200
Office of Atmos Resources Management
Water and Power Resources Service
PO Box 25007
Denver Federal Center, Bldg. 67
Denver, CO 80225

Hugh W. Albers (Executive Secretary)
CAO Subcommittee on Atmos Rsch
National Science Foundation Room 510
Washington, DC 2055

Dr. Eugene W. Bierly
Director, Division of Atmos Sciences
National Science Foundation
1800 G Street, N.W.
Washington, DC 20550

Commanding Officer
Naval Research Laboratory
Code 2627
Washington, DC 20375

Defense Communications Agency
Technical Library Center
Code 222
Washington, DC 20305

Director
Naval Research Laboratory
Code 5530
Washington, DC 20375

Dr. J. M. MacCallum
Naval Research Laboratory
Code 1409
Washington, DC 20375

HQDA (DAMI-ISP/H. Tax)
Washington, DC 20314

HQDA (DAEN-RDM/Dr. de Percin)
Washington, DC 20314

The Library of Congress
ATTN: Exchange & Gift Div
Washington, DC 20540

2

Mil Asst for Atmos Sci Ofc of
the Undersecretary of Defense
for Rsch & Engr/E&LS - RM 3D129
The Pentagon
Washington, DC 20301

Dr. John L. Walsh
Code 6534
Navy Research Lab
Washington, DC 20375

AFATL/DLODL
Technical Library
Eglin AFB, FL 32542

Naval Training Equipment Center
ATTN: Technical Information Center
Orlando, FL 32813

Technical Library
Chemical Systems Laboratory
Aberdeen Proving Ground, MD 21010

US Army Materiel Systems
Analysis Activity
ATTN: DRXSY-MP
APG, MD 21005

Commander
ERADCOM
ATTN: DRDEL-PA/ILS/-ED
2800 Powder Mill Road
Adelphi, MD 20783

Commander
ERADCOM
ATTN: DRDEL-PAO (M. Singleton)
2800 Powder Mill Road
Adelphi, MD 20783

Commander
ERADCOM
ATTN: DRDEL-ST-T (Dr. B. Zarwyn)
2800 Powder Mill Road
Adelphi, MD 20783
02

Commander
Harry Diamond Laboratories
ATTN: DELHD-CO
2800 Powder Mill Road
Adelphi, MD 20783

Chief
Intel Mat Dev & Spt Ofc
ATTN: DELEW-WL-I
Bldg 4554
Fort George G. Mead, MD 20755

Acquisitions Section, IRDB-D823
Library & Info Svc Div, NOAA
6009 Executive Blvd.
Rockville, MD 20752

Naval Surface Weapons Center
White Oak Library
Silver Spring, MD 20910

Air Force Geophysics Laboratory
ATTN: LCC (A. S. Carten, Jr.)
Hanscom AFB, MA 01731

Air Force Geophysics Laboratory
ATTN: LYD
Hanscom AFB, MA 01731

Meteorology Division
AFGL/LY
Hanscom AFB, MA 01731

The Environmental Research
Institute of MI
ATTN: IRIA Library
PO Box 8618
Ann Arbor, MI 48107

Mr. William A. Main
USDA Forest Service
1407 S. Harrison Road
East Lansing, MI 48823

Dr. A. D. Belmont
Research Division
PO Box 124
Control Data Corp
Minneapolis, MN 55440

Commander
Naval Oceanography Command
Bay St. Louis, MS 39529

Commanding Officer
US Army Armament R&D Command
ATTN: DRDAR-TSS Bldg 59
Dover, NJ 07801

Commander
ERADCOM Scientific Advisor
ATTN: DRDEL-SA
Fort Monmouth, NJ 07703

Commander
ERADCOM Tech Support Activity
ATTN: DELSD-L
Fort Monmouth, NJ 07703

Commander
HQ, US Army Avionics R&D Actv
ATTN: DAVAA-O
Fort Monmouth, NJ 07703

Commander
USA Elect Warfare Lab
ATTN: DELEW-DA (File Cy)
Fort Monmouth, NJ 07703

Commander
US Army Electronics R&D Command
ATTN: DELCS-S
Fort Monmouth, NJ 07703

Commander
US Army Satellite Comm Agency
ATTN: DRCPM-SC-3
Fort Monmouth, NJ 07703

Commander/Director
US Army Combat Survl & Target
Acquisition Laboratory
ATTN: DELCS-D
Fort Monmouth, NJ 07703

Director
Night Vision & Electro-Optics Laboratory
ATTN: DELNV-L (Dr. R. Buser)
Fort Belvoir, VA 22060

Project Manager
FIREFINDER/REMBASS
ATTN: DRCPM-FFR-TM
Fort Monmouth, NJ 07703

6585 TG/WE
Holloman AFB, NM 88330

AFWL/Technical Library (SUL)
Kirtland AFB, NM 87117

AFWL/WE
Kirtland, AFB, NM 87117

TRASANA
ATTN: ATAA-SL (D. Anguiano)
WSMR, NM 88002

Commander
US Army White Sands Missile Range
ATTN: STEWS-PT-AL
White Sands Missile Range, NM 88002

Rome Air Development Center
ATTN: Documents Library
TSLD (Bette Smith)
Griffiss AFB, NY 13441

Environmental Protection Agency
Meteorology Laboratory, MD 80
Rsch Triangle Park, NC 27711

US Army Research Office
ATTN: DRXRO-PP
PO Box 12211
Rsch Triangle Park, NC 27709

Commandant
US Army Field Artillery School
ATTN: ATSF-CD-MS (Mr. Farmer)
Fort Sill, OK 73503

Commandant
US Army Field Artillery School
ATTN: ATSF-CD-MS
Fort Sill, OK 73503

Commandant
US Army Field Artillery School
ATTN: Morris Swett Library
Fort Sill, OK 73503

Commander
US Army Dugway Proving Ground
ATTN: STEDP-MT-DA-M
(Mr. Paul Carlson)
Dugway, UT 84022

Commander
US Army Dugway Proving Ground
ATTN: MT-DA-L
Dugway, UT 84022

US Army Dugway Proving Ground
ATTN: STEDP-MT-DA-T
(Dr. W. A. Peterson)
Dugway, UT 84022

Inge Dirmhirn, Professor
Utah State University, UMC 48
Logan, UT 84322

Defense Technical Information Center
ATTN: DTIC-DDA-2
Cameron Station, Bldg. 5
Alexandria, VA 22314
12

Commanding Officer
US Army Foreign Sci & Tech Cen
ATTN: DRXST-IS1
220 7th Street, NE
Charlottesville, VA 22901

Naval Surface Weapons Center
Code G65
Dahlgren, VA 22448

Commander
US Army Night Vision
& Electro-Optics Lab
ATTN: DELNV-D
Fort Belvoir, VA 22060

Commander
USATRADOC
ATTN: ATCD-FA
Fort Monroe, VA 23651

Commander
USATRADOC
ATTN: ATCD-IR
Fort Monroe, VA 23651

Dept of the Air Force
5WW/DN
Langley AFB, VA 23665

US Army Nuclear & Cml Agency
ATTN: MONA-WE
Springfield, VA 22150

Director
US Army Signals Warfare Lab
ATTN: DELSW-OS (Dr. Burkhardt)
Vint Hill Farms Station
Warrenton, VA 22186

Commander
US Army Cold Regions Test Cen
ATTN: STECR-OP-PM
APO Seattle, WA 98733

ATMOSPHERIC SCIENCES RESEARCH REPORTS

1. Lindberg, J. D. "An Improvement to a Method for Measuring the Absorption Coefficient of Atmospheric Dust and other Strongly Absorbing Powders," ECOM-5565, July 1975.
2. Avara, Elton P., "Mesoscale Wind Shears Derived from Thermal Winds," ECOM-5566, July 1975.
3. Gomez, Richard B., and Joseph H. Pierluissi, "Incomplete Gamma Function Approximation for King's Strong-Line Transmittance Model," ECOM-5567, July 1975.
4. Blanco, A. J., and B. F. Engebos, "Ballistic Wind Weighting Functions for Tank Projectiles," ECOM-5568, August 1975.
5. Taylor, Fredrick J., Jack Smith, and Thomas H. Pries, "Crosswind Measurements through Pattern Recognition Techniques," ECOM-5569, July 1975.
6. Walters, D. L., "Crosswind Weighting Functions for Direct-Fire Projectiles," ECOM-5570, August 1975.
7. Duncan, Louis D., "An Improved Algorithm for the Iterated Minimal Information Solution for Remote Sounding of Temperature," ECOM-5571, August 1975.
8. Robbiani, Raymond L., "Tactical Field Demonstration of Mobile Weather Radar Set AN/TPS-41 at Fort Rucker, Alabama," ECOM-5572, August 1975.
9. Miers, B., G. Blackman, D. Langer, and N. Lorimier, "Analysis of SMS/GOES Film Data," ECOM-5573, September 1975.
10. Manquero, Carlos, Louis Duncan, and Rufus Bruce, "An Indication from Satellite Measurements of Atmospheric CO₂ Variability," ECOM-5574, September 1975.
11. Petracca, Carmine, and James D. Lindberg, "Installation and Operation of an Atmospheric Particulate Collector," ECOM-5575, September 1975.
12. Avara, Elton P., and George Alexander, "Empirical Investigation of Three Iterative Methods for Inverting the Radiative Transfer Equation," ECOM-5576, October 1975.
13. Alexander, George D., "A Digital Data Acquisition Interface for the SMS Direct Readout Ground Station - Concept and Preliminary Design," ECOM-5577, October 1975.
14. Cantor, Israel, "Enhancement of Point Source Thermal Radiation Under Clouds in a Nonattenuating Medium," ECOM-5578, October 1975.

15. Norton, Colburn, and Glenn Hoidale, "The Diurnal Variation of Mixing Height by Month over White Sands Missile Range, NM," ECOM-5579, November 1975.
16. Avara, Elton P., "On the Spectrum Analysis of Binary Data," ECOM-5580, November 1975.
17. Taylor, Fredrick J., Thomas H. Pries, and Chao-Huan Huang, "Optimal Wind Velocity Estimation," ECOM-5581, December 1975.
18. Avara, Elton P., "Some Effects of Autocorrelated and Cross-Correlated Noise on the Analysis of Variance," ECOM-5582, December 1975.
19. Gillespie, Patti S., R. L. Armstrong, and Kenneth O. White, "The Spectral Characteristics and Atmospheric CO₂ Absorption of the Ho⁺³:YLF Laser at 2.05 μ m," ECOM-5583, December 1975.
20. Novlan, David J., "An Empirical Method of Forecasting Thunderstorms for the White Sands Missile Range," ECOM-5584, February 1976.
21. Avara, Elton P., "Randomization Effects in Hypothesis Testing with Autocorrelated Noise," ECOM-5585, February 1976.
22. Watkins, Wendell R., "Improvements in Long Path Absorption Cell Measurement," ECOM-5586, March 1976.
23. Thomas, Joe, George D. Alexander, and Marvin Dubbin, "SATTEL - An Army Dedicated Meteorological Telemetry System," ECOM-5587, March 1976.
24. Kennedy, Bruce W., and Delbert Bynum, "Army User Test Program for the RDT&E-XM-75 Meteorological Rocket," ECOM-5588, April 1976.
25. Barnett, Kenneth M., "A Description of the Artillery Meteorological Comparisons at White Sands Missile Range, October 1974 - December 1974 ('PASS' - Prototype Artillery [Meteorological] Subsystem)," ECOM-5589, April 1976.
26. Miller, Walter B., "Preliminary Analysis of Fall-of-Shot From Project 'PASS'," ECOM-5590, April 1976.
27. Avara, Elton P., "Error Analysis of Minimum Information and Smith's Direct Methods for Inverting the Radiative Transfer Equation," ECOM-5591, April 1976.
28. Yee, Young P., James D. Horn, and George Alexander, "Synoptic Thermal Wind Calculations from Radiosonde Observations Over the Southwestern United States," ECOM-5592, May 1976.

29. Duncan, Louis D., and Mary Ann Seagraves, "Applications of Empirical Corrections to NOAA-4 VTPR Observations," ECOM-5593, May 1976.
30. Miers, Bruce T., and Steve Weaver, "Applications of Meteorological Satellite Data to Weather Sensitive Army Operations," ECOM-5594, May 1976.
31. Sharenow, Moses, "Redesign and Improvement of Balloon ML-566," ECOM-5595, June 1976.
32. Hansen, Frank V., "The Depth of the Surface Boundary Layer," ECOM-5596, June 1976.
33. Pinnick, R. G., and E. B. Stenmark, "Response Calculations for a Commerical Light-Scattering Aerosol Counter," ECOM-5597, July 1976.
34. Mason, J., and G. B. Hoidale, "Visibility as an Estimator of Infrared Transmittance," ECOM-5598, July 1976.
35. Bruce, Rufus E., Louis D. Duncan, and Joseph H. Pierluissi, "Experimental Study of the Relationship Between Radiosonde Temperatures and Radiometric-Area Temperatures," ECOM-5599, August 1976.
36. Duncan, Louis D., "Stratospheric Wind Shear Computed from Satellite Thermal Sounder Measurements," ECOM-5800, September 1976.
37. Taylor, F., P. Mohan, P. Joseph, and T. Pries, "An All Digital Automated Wind Measurement System," ECOM-5801, September 1976.
38. Bruce, Charles, "Development of Spectrophones for CW and Pulsed Radiation Sources," ECOM-5802, September 1976.
39. Duncan, Louis D., and Mary Ann Seagraves, "Another Method for Estimating Clear Column Radiances," ECOM-5803, October 1976.
40. Blanco, Abel J., and Larry E. Taylor, "Artillery Meteorological Analysis of Project Pass," ECOM-5804, October 1976.
41. Miller, Walter, and Bernard Engebos, "A Mathematical Structure for Refinement of Sound Ranging Estimates," ECOM-5805, November 1976.
42. Gillespie, James B., and James D. Lindberg, "A Method to Obtain Diffuse Reflectance Measurements from 1.0 and 3.0 μ m Using a Cary 17I Spectrophotometer," ECOM-5806, November 1976.
43. Rubio, Roberto, and Robert O. Olsen, "A Study of the Effects of Temperature Variations on Radio Wave Absorption," ECOM-5807, November 1976.

44. Ballard, Harold N., "Temperature Measurements in the Stratosphere from Balloon-Borne Instrument Platforms, 1968-1975," ECOM-5808, December 1976.
45. Monahan, H. H., "An Approach to the Short-Range Prediction of Early Morning Radiation Fog," ECOM-5809, January 1977.
46. Engebos, Bernard Francis, "Introduction to Multiple State Multiple Action Decision Theory and Its Relation to Mixing Structures," ECOM-5810, January 1977.
47. Low, Richard D. H., "Effects of Cloud Particles on Remote Sensing from Space in the 10-Micrometer Infrared Region," ECOM-5811, January 1977.
48. Bonner, Robert S., and R. Newton, "Application of the AN/GVS-5 Laser Rangefinder to Cloud Base Height Measurements," ECOM-5812, February 1977.
49. Rubio, Roberto, "Lidar Detection of Subvisible Reentry Vehicle Erosive Atmospheric Material," ECOM-5813, March 1977.
50. Low, Richard D. H., and J. D. Horn, "Mesoscale Determination of Cloud-Top Height: Problems and Solutions," ECOM-5814, March 1977.
51. Duncan, Louis D., and Mary Ann Seagraves, "Evaluation of the NOAA-4 VTPR Thermal Winds for Nuclear Fallout Predictions," ECOM-5815, March 1977.
52. Randhawa, Jagir S., M. Izquierdo, Carlos McDonald, and Zvi Salpeter, "Stratospheric Ozone Density as Measured by a Chemiluminescent Sensor During the Stratcom VI-A Flight," ECOM-5816, April 1977.
53. Rubio, Roberto, and Mike Izquierdo, "Measurements of Net Atmospheric Irradiance in the 0.7- to 2.8-Micrometer Infrared Region," ECOM-5817, May 1977.
54. Ballard, Harold N., Jose M. Serna, and Frank P. Hudson, Consultant for Chemical Kinetics, "Calculation of Selected Atmospheric Composition Parameters for the Mid-Latitude, September Stratosphere," ECOM-5818, May 1977.
55. Mitchell, J. D., R. S. Sagar, and R. O. Olsen, "Positive Ions in the Middle Atmosphere During Sunrise Conditions," ECOM-5819, May 1977.
56. White, Kenneth O., Wendell R. Watkins, Stuart A. Schleusener, and Ronald L. Johnson, "Solid-State Laser Wavelength Identification Using a Reference Absorber," ECOM-5820, June 1977.
57. Watkins, Wendell R., and Richard G. Dixon, "Automation of Long-Path Absorption Cell Measurements," ECOM-5821, June 1977.

58. Taylor, S. E., J. M. Davis, and J. B. Mason, "Analysis of Observed Soil Skin Moisture Effects on Reflectance," ECOM-5822, June 1977.
59. Duncan, Louis D., and Mary Ann Seagraves, "Fallout Predictions Computed from Satellite Derived Winds," ECOM-5823, June 1977.
60. Snider, D. E., D. G. Murcray, F. H. Murcray, and W. J. Williams, "Investigation of High-Altitude Enhanced Infrared Background Emissions," (U), SECRET, ECOM-5824, June 1977.
61. Dubbin, Marvin H., and Dennis Hall, "Synchronous Meteorological Satellite Direct Readout Ground System Digital Video Electronics," ECOM-5825, June 1977.
62. Miller, W., and B. Engebos, "A Preliminary Analysis of Two Sound Ranging Algorithms," ECOM-5826, July 1977.
63. Kennedy, Bruce W., and James K. Luers, "Ballistic Sphere Techniques for Measuring Atmospheric Parameters," ECOM-5827, July 1977.
64. Duncan, Louis D., "Zenith Angle Variation of Satellite Thermal Sounder Measurements," ECOM-5828, August 1977.
65. Hansen, Frank V., "The Critical Richardson Number," ECOM-5829, September 1977.
66. Ballard, Harold N., and Frank P. Hudson (Compilers), "Stratospheric Composition Balloon-Borne Experiment," ECOM-5830, October 1977.
67. Barr, William C., and Arnold C. Peterson, "Wind Measuring Accuracy Test of Meteorological Systems," ECOM-5831, November 1977.
68. Ethridge, G. A., and F. V. Hansen, "Atmospheric Diffusion: Similarity Theory and Empirical Derivations for Use in Boundary Layer Diffusion Problems," ECOM-5832, November 1977.
69. Low, Richard D. H., "The Internal Cloud Radiation Field and a Technique for Determining Cloud Blackness," ECOM-5833, December 1977.
70. Watkins, Wendell R., Kenneth O. White, Charles W. Bruce, Donald L. Walters, and James D. Lindberg, "Measurements Required for Prediction of High Energy Laser Transmission," ECOM-5834, December 1977.
71. Rubio, Robert, "Investigation of Abrupt Decreases in Atmospherically Backscattered Laser Energy," ECOM-5835, December 1977.
72. Monahan, H. H., and R. M. Cionco, "An Interpretative Review of Existing Capabilities for Measuring and Forecasting Selected Weather Variables (Emphasizing Remote Means)," ASL-TR-0001, January 1978.

73. Heaps, Melvin G., "The 1979 Solar Eclipse and Validation of D-Region Models," ASL-TR-0002, March 1978.
74. Jennings, S. G., and J. B. Gillespie, "M.I.E. Theory Sensitivity Studies - The Effects of Aerosol Complex Refractive Index and Size Distribution Variations on Extinction and Absorption Coefficients, Part II: Analysis of the Computational Results," ASL-TR-0003, March 1978.
75. White, Kenneth O., et al, "Water Vapor Continuum Absorption in the 3.5 μ m to 4.0 μ m Region," ASL-TR-0004, March 1978.
76. Olsen, Robert O., and Bruce W. Kennedy, "ABRES Pretest Atmospheric Measurements," ASL-TR-0005, April 1978.
77. Ballard, Harold N., Jose M. Serna, and Frank P. Hudson, "Calculation of Atmospheric Composition in the High Latitude September Stratosphere," ASL-TR-0006, May 1978.
78. Watkins, Wendell R., et al, "Water Vapor Absorption Coefficients at HF Laser Wavelengths," ASL-TR-0007, May 1978.
79. Hansen, Frank V., "The Growth and Prediction of Nocturnal Inversions," ASL-TR-0008, May 1978.
80. Samuel, Christine, Charles Bruce, and Ralph Brewer, "Spectrophone Analysis of Gas Samples Obtained at Field Site," ASL-TR-0009, June 1978.
81. Pinnick, R. G., et al., "Vertical Structure in Atmospheric Fog and Haze and its Effects on IR Extinction," ASL-TR-0010, July 1978.
82. Low, Richard D. H., Louis D. Duncan, and Richard B. Gomez, "The Microphysical Basis of Fog Optical Characterization," ASL-TR-0011, August 1978.
83. Heaps, Melvin G., "The Effect of a Solar Proton Event on the Minor Neutral Constituents of the Summer Polar Mesosphere," ASL-TR-0012, August 1978.
84. Mason, James B., "Light Attenuation in Falling Snow," ASL-TR-0013, August 1978.
85. Blanco, Abel J., "Long-Range Artillery Sound Ranging: 'PASS' Meteorological Application," ASL-TR-0014, September 1978.
86. Heaps, M. G., and F. E. Niles, "Modeling of Ion Chemistry of the D-Region: A Case Study Based Upon the 1966 Total Solar Eclipse," ASL-TR-0015, September 1978.

87. Jennings, S. G., and R. G. Pinnick, "Effects of Particulate Complex Refractive Index and Particle Size Distribution Variations on Atmospheric Extinction and Absorption for Visible Through Middle-Infrared Wavelengths," ASL-TR-0016, September 1978.
88. Watkins, Wendell R., Kenneth O. White, Lanny R. Bower, and Brian Z. Sojka, "Pressure Dependence of the Water Vapor Continuum Absorption in the 3.5- to 4.0-Micrometer Region," ASL-TR-0017, September 1978.
89. Miller, W. B., and B. F. Engebos, "Behavior of Four Sound Ranging Techniques in an Idealized Physical Environment," ASL-TR-0018, September 1978.
90. Gomez, Richard G., "Effectiveness Studies of the CBU-88/B Bomb, Cluster, Smoke Weapon," (U), CONFIDENTIAL ASL-TR-0019, September 1978.
91. Miller, August, Richard C. Shirkey, and Mary Ann Seagraves, "Calculation of Thermal Emission from Aerosols Using the Doubling Technique," ASL-TR-0020, November 1978.
92. Lindberg, James D., et al, "Measured Effects of Battlefield Dust and Smoke on Visible, Infrared, and Millimeter Wavelengths Propagation: A Preliminary Report on Dusty Infrared Test-I (DIRT-I)," ASL-TR-0021, January 1979.
93. Kennedy, Bruce W., Arthur Kinghorn, and B. R. Hixon, "Engineering Flight Tests of Range Meteorological Sounding System Radiosonde," ASL-TR-0022, February 1979.
94. Rubio, Roberto, and Don Hooch, "Microwave Effective Earth Radius Factor Variability at Wiesbaden and Balboa," ASL-TR-0023, February 1979.
95. Low, Richard D. H., "A Theoretical Investigation of Cloud/Fog Optical Properties and Their Spectral Correlations," ASL-TR-0024, February 1979.
96. Pinnick, R. G., and H. J. Auvermann, "Response Characteristics of Knollenberg Light-Scattering Aerosol Counters," ASL-TR-0025, February 1979.
97. Heaps, Melvin G., Robert O. Olsen, and Warren W. Berning, "Solar Eclipse 1979, Atmospheric Sciences Laboratory Program Overview," ASL-TR-0026, February 1979.
98. Blanco, Abel J., "Long-Range Artillery Sound Ranging: 'PASS' GR-8 Sound Ranging Data," ASL-TR-0027, March 1979.
99. Kennedy, Bruce W., and Jose M. Serna, "Meteorological Rocket Network System Reliability," ASL-TR-0028, March 1979.

100. Swingle, Donald M., "Effects of Arrival Time Errors in Weighted Range Equation Solutions for Linear Base Sound Ranging," ASL-TR-0029, April 1979.
101. Umstead, Robert K., Ricardo Pena, and Frank V. Hansen, "KWIK: An Algorithm for Calculating Munition Expenditures for Smoke Screening/Obscuration in Tactical Situations," ASL-TR-0030, April 1979.
102. D'Arcy, Edward M., "Accuracy Validation of the Modified Nike Hercules Radar," ASL-TR-0031, May 1979.
103. Rodriguez, Ruben, "Evaluation of the Passive Remote Crosswind Sensor," ASL-TR-0032, May 1979.
104. Barber, T. L., and R. Rodriguez, "Transit Time Lidar Measurement of Near-Surface Winds in the Atmosphere," ASL-TR-0033, May 1979.
105. Low, Richard D. H., Louis D. Duncan, and Y. Y. Roger R. Hsiao, "Micro-physical and Optical Properties of California Coastal Fogs at Fort Ord," ASL-TR-0034, June 1979.
106. Rodriguez, Ruben, and William J. Vechione, "Evaluation of the Saturation Resistant Crosswind Sensor," ASL-TR-0035, July 1979.
107. Ohmstede, William D., "The Dynamics of Material Layers," ASL-TR-0036, July 1979.
108. Pinnick, R. G., S. G. Jennings, Petr Chylek, and H. J. Auvermann, "Relationships between IR Extinction Absorption, and Liquid Water Content of Fogs," ASL-TR-0037, August 1979.
109. Rodriguez, Ruben, and William J. Vechione, "Performance Evaluation of the Optical Crosswind Profiler," ASL-TR-0038, August 1979.
110. Miers, Bruce T., "Precipitation Estimation Using Satellite Data," ASL-TR-0039, September 1979.
111. Dickson, David H., and Charles M. Sonnenschein, "Helicopter Remote Wind Sensor System Description," ASL-TR-0040, September 1979.
112. Heaps, Melvin G., and Joseph M. Heimerl, "Validation of the Dairchem Code, I: Quiet Midlatitude Conditions," ASL-TR-0041, September 1979.
113. Bonner, Robert S., and William J. Lentz, "The Visioceilometer: A Portable Cloud Height and Visibility Indicator," ASL-TR-0042, October 1979.
114. Cohn, Stephen L., "The Role of Atmospheric Sulfates in Battlefield Obscurations," ASL-TR-0043, October 1979.

115. Fawbush, E. A., et al., "Characterization of Atmospheric Conditions at the High Energy Laser System Test Facility (HELSTF), White Sands Missile Range, New Mexico, Part I, 24 March to 8 April 1977," ASL-TR-0044, November 1979.
116. Barber, Ted L., "Short-Time Mass Variation in Natural Atmospheric Dust," ASL-TR-0045, November 1979.
117. Low, Richard D. H., "Fog Evolution in the Visible and Infrared Spectral Regions and its Meaning in Optical Modeling," ASL-TR-0046, December 1979.
118. Duncan, Louis D., et al., "The Electro-Optical Systems Atmospheric Effects Library, Volume I: Technical Documentation," ASL-TR-0047, December 1979.
119. Shirkey, R. C., et al., "Interim E-O SAEL, Volume II, Users Manual," ASL-TR-0048, December 1979.
120. Kobayashi, H. K., "Atmospheric Effects on Millimeter Radio Waves," ASL-TR-0049, January 1980.
121. Seagraves, Mary Ann, and Louis D. Duncan, "An Analysis of Transmittances Measured Through Battlefield Dust Clouds," ASL-TR-0050, February 1980.
122. Dickson, David H., and Jon E. Ottesen, "Helicopter Remote Wind Sensor Flight Test," ASL-TR-0051, February 1980.
123. Pinnick, R. G., and S. G. Jennings, "Relationships Between Radiative Properties and Mass Content of Phosphoric Acid, HC, Petroleum Oil, and Sulfuric Acid Military Smokes," ASL-TR-0052, April 1980.
124. Hinds, B. D., and J. B. Gillespie, "Optical Characterization of Atmospheric Particulates on San Nicolas Island, California," ASL-TR-0053, April 1980.
125. Miers, Bruce T., "Precipitation Estimation for Military Hydrology," ASL-TR-0054, April 1980.
126. Stenmark, Ernest B., "Objective Quality Control of Artillery Computer Meteorological Messages," ASL-TR-0055, April 1980.
127. Duncan, Louis D., and Richard D. H. Low, "Bimodal Size Distribution Models for Fogs at Meppen, Germany," ASL-TR-0056, April 1980.
128. Olsen, Robert O., and Jagir S. Randhawa, "The Influence of Atmospheric Dynamics on Ozone and Temperature Structure," ASL-TR-0057, May 1980.

129. Kennedy, Bruce W., et al, "Dusty Infrared Test-II (DIRT-II) Program," ASL-TR-0058, May 1980.
130. Heaps, Melvin G., Robert O. Olsen, Warren Berning, John Cross, and Arthur Gilcrease, "1979 Solar Eclipse, Part I - Atmospheric Sciences Laboratory Field Program Summary," ASL-TR-0059, May 1980
131. Miller, Walter B., "User's Guide for Passive Target Acquisition Program Two (PTAP-2)," ASL-TR-0060, June 1980.
132. Holt, E. H., editor, "Atmospheric Data Requirements for Battlefield Obscuration Applications," ASL-TR-0061, June 1980.
133. Shirkey, Richard C., August Miller, George H. Goedecke, and Yugal Behl, "Single Scattering Code AGAUSX: Theory, Applications, Comparisons, and Listing," ASL-TR-0062, July 1980.
134. Sojka, Brian Z., and Kenneth O. White, "Evaluation of Specialized Photoacoustic Absorption Chambers for Near-Millimeter Wave (NMMW) Propagation Measurements," ASL-TR-0063, August 1980.
135. Bruce, Charles W., Young Paul Yee, and S. G. Jennings, "In Situ Measurement of the Ratio of Aerosol Absorption to Extinction Coefficient," ASL-TR-0064, August 1980.
136. Yee, Young Paul, Charles W. Bruce, and Ralph J. Brewer, "Gaseous/Particulate Absorption Studies at WSMR using Laser Sourced Spectrophones," ASL-TR-0065, June 1980.
137. Lindberg, James D., Radon B. Loveland, Melvin Heaps, James B. Gillespie, and Andrew F. Lewis, "Battlefield Dust and Atmospheric Characterization Measurements During West German Summertime Conditions in Support of Grafenwohr Tests," ASL-TR-0066, September 1980.
138. Vechione, W. J., "Evaluation of the Environmental Instruments, Incorporated Series 200 Dual Component Wind Set," ASL-TR-0067, September 1980.
139. Bruce, C. W., Y. P. Yee, B. D. Hinds, R. G. Pinnick, R. J. Brewer, and J. Minjares, "Initial Field Measurements of Atmospheric Absorption at 9 μ m to 11 μ m Wavelengths," ASL-TR-0068, October 1980.
140. Heaps, M. G., R. O. Olsen, K. D. Baker, D. A. Burt, L. C. Howlett, L. L. Jensen, E. F. Pound, and G. D. Allred, "1979 Solar Eclipse: Part II Initial Results for Ionization Sources, Electron Density, and Minor Neutral Constituents," ASL-TR-0069, October 1980.
141. Low, Richard D. H., "One-Dimensional Cloud Microphysical Models for Central Europe and their Optical Properties," ASL-TR-0070, October 1980.

142. Duncan, Louis D., James D. Lindberg, and Radon B. Loveland, "An Empirical Model of the Vertical Structure of German Fogs," ASL-TR-0071, November 1980.
143. Duncan, Louis D., "EOSAEL 80, Volume I, Technical Documentation," ASL-TR-0072, January 1981.
144. Shirkey, R. C., and S. G. O'Brien, "EOSAEL 80, Volume II, Users Manual," ASL-TR-0073, January 1981.
145. Bruce, C. W., "Characterization of Aerosol Nonlinear Effects on a High-Power CO₂ Laser Beam," ASL-TR-0074, February 1981.
146. Duncan, Louis D., and James D. Lindberg, "Air Mass Considerations in Fog Optical Modeling," ASL-TR-0075, February 1981.
147. Kunkel, Kenneth E., "Evaluation of a Tethered Kite Anemometer," ASL-TR-0076, February 1981.
148. Kunkel, K. E., et al, "Characterization of Atmospheric Conditions at the High Energy Laser System Test Facility (HELSTF) White Sands Missile Range, New Mexico, August 1977 to October 1978, Part II, Optical Turbulence, Wind, Water Vapor Pressure, Temperature," ASL-TR-0077, February 1981.
149. Miers, Bruce T., "Weather Scenarios for Central Germany," ASL-TR-0078, February 1981.
150. Cogan, James L., "Sensitivity Analysis of a Mesoscale Moisture Model," ASL-TR-0079, March 1981.
151. Brewer, R. J., C. W. Bruce, and J. L. Mater, "Optoacoustic Spectroscopy of C₂H₂ at the 9 μ m and 10 μ m C¹⁸O₂ Laser Wavelengths," ASL-TR-0080, March 1981.
152. Swingle, Donald M., "Reducible Errors in the Artillery Sound Ranging Solution, Part I: The Curvature Correction" (U), SECRET, ASL-TR-0081, April 1981.
153. Miller, Walter B., "The Existence and Implications of a Fundamental System of Linear Equations in Sound Ranging" (U), SECRET, ASL-TR-0082, April 1981.
154. Bruce, Dorothy, Charles W. Bruce, and Young Paul Yee, "Experimentally Determined Relationship Between Extinction and Liquid Water Content," ASL-TR-0083, April 1981.
155. Seagraves, Mary Ann, "Visible and Infrared Obscuration Effects of Ice Fog," ASL-TR-0084, May 1981.

156. Watkins, Wendell R., and Kenneth O. White, "Wedge Absorption Remote Sensor," ASL-TR-0085, May 1981.
157. Watkins, Wendell R., Kenneth O. White, and Laura J. Crow, "Turbulence Effects on Open Air Multipaths," ASL-TR-0086, May 1981.
158. Blanco, Abel J., "Extending Application of the Artillery Computer Meteorological Message," ASL-TR-0087, May 1981.
159. Heaps, M. G., D. W. Hoock, R. O. Olsen, B. F. Engebos, and R. Rubio, "High Frequency Position Location: An Assessment of Limitations and Potential Improvements," ASL-TR-0088, May 1981.
160. Watkins, Wendell R., and Kenneth O. White, "Laboratory Facility for Measurement of Hot Gaseous Plume Radiative Transfer," ASL-TR-0089, June 1981.
161. Heaps, M. G., "Dust Cloud Models: Sensitivity of Calculated Transmittances to Variations in Input Parameters," ASL-TR-0090, June 1981.
162. Seagraves, Mary Ann, "Some Optical Properties of Blowing Snow," ASL-TR-0091, June 1981.
163. Kobayashi, Herbert K., "Effect of Hail, Snow, and Melting Hydrometeors on Millimeter Radio Waves," ASL-TR-0092, July 1981.
164. Cogan, James L., "Techniques for the Computation of Wind, Ceiling, and Extinction Coefficient Using Currently Acquired RPV Data," ASL-TR-0093, July 1981.
165. Miller, Walter B., and Bernard F. Engebos, "On the Possibility of Improved Estimates for Effective Wind and Temperature," (U), SECRET, ASL-TR-0094, August 1981.
166. Heaps, Melvin G., "The Effect of Ionospheric Variability on the Accuracy of High Frequency Position Location," ASL-TR-0095, August 1981.
167. Sutherland, Robert A., Donald W. Hoock, and Richard B. Gomez, "An Objective Summary of US Army Electro-Optical Modeling and Field Testing in an Obscuring Environment," ASL-TR-0096, October 1981.
168. Pinnick, R. G., et al, "Backscatter and Extinction in Water Clouds," ASL-TR-0097, October 1981.
169. Cole, Henry P., and Melvin G. Heaps, "Properties of Dust as an Electron and Ion Attachment Site for Use in D Region Ion Chemistry," ASL-TR-0098, October 1981.

170. Spellicy, Robert L., Laura J. Crow, and Kenneth O. White, "Water Vapor Absorption Coefficients at HF Laser Wavelengths Part II: Development of the Measurement System and Measurements at Simulated Altitudes to 10 KM," ASL-TR-0099, November 1981.
171. Cohn, Stephen L., "Transport and Diffusion Solutions for Obscuration Using the XM-825 Smoke Munition," ASL-TR-0100, November 1981.
172. Pinnick, R. G., D. M. Garvey, and L. D. Duncan, "Calibration of Knollenberg FSSP Light-Scattering Counters for Measurement of Cloud Droplets," ASL-TR-0101, December 1981.
173. Cohn, Stephen L. and Ricardo Pena, "Munition Expenditure Model Verification: KWIK Phase I," ASL-TR-0102, December 1981.
174. Blackman, George R., "Cloud Geometry Analysis of the Smoke Week III Obscuration Trials," ASL-TR-0103, January 1982.

EN

DAT
FILM

4-8

DTI