


AD-A111 937 ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND WATER--ETC F/6 13/13  
EFFECT OF SUPPORT CONDITIONS ON BEAM VIBRATIONS SUBJECTED TO NO--ETC(U)

UNCLASSIFIED  
JAN 82 J J WU  
ARLCB-TR-82002

NL

1 of 1  
AD-A  
11247

END
DATE
FILMED
04-82
DTIC



MICROCOPY RESOLUTION TEST CHART

ANSI #10-1983 (3.00) 25X

12

AD


ADA111937

TECHNICAL REPORT ARLCB-TR-82002

EFFECT OF SUPPORT CONDITIONS ON BEAM  
VIBRATIONS SUBJECTED TO MOVING LOADS

Julian J. Wu

January 1982



US ARMY  
ARRADCOM

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND  
LARGE CALIBER WEAPON SYSTEMS LABORATORY  
BENÉT WEAPONS LABORATORY  
WATERVLIET, N. Y. 12189

AMCMS No. 611102H600011

PRON No. 1A1283121A1A

DTIC  
EXTRACTED  
MAR 12 1982  
H

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

DTIC FILE COPY

82 03 11 153

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.


The use of trade name(s) and/or manufacture(s) does not constitute an official indorsement or approval.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ARLDB TR 82007	2. GOVT ACCESSION NO. AD-A114937	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) EFFECT OF SUPPORT CONDITIONS ON BEAM VIBRATIONS SUBJECTED TO MOVING LOADS	5. TYPE OF REPORT & PERIOD COVERED TR	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Julian J. Wu	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Armament Research & Development Command Benet Weapons Laboratory, DRDAR-LCB-FL Watervliet, NY 12189	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS AMMS NO. 611102H00011 DDOY NO. 1A1285121A1A	
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command Large Caliber Weapon Systems Laboratory Dover, NJ 07301	12. REPORT DATE January 1982	13. NUMBER OF PAGES 17
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	15a. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES  Presented at 27th Conference of Army Mathematicians, 10-12 June 1981 at U.S. Military Academy, West Point, NY. Published in proceedings of the conference.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  Support Conditions Beam Vibrations Moving Loads Finite Elements <u>Initial Boundary Value Problems</u>		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  Solutions of beam vibrations under moving loads are presented with a variety of support conditions. The purpose is to demonstrate how the support conditions will effect such beam motions. The solution method and mathematical background will be reviewed including the introduction of various support parameters. By slightly modifying an existing computational scheme, the desired results have been obtained and presented in several tables and plots showing the effect of support stiffness on beam motions.		

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)



SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

STATEMENT OF THE PROBLEM

AN EQUIVALENT VARIATIONAL PROBLEM


OUTLINE OF SOLUTION FORMULATION

RESULTS OF COMPUTATIONS

REFERENCES

LIST OF ILLUSTRATIONS

1. Beam deflections under a moving load for fixed-fixed supports ( $\gamma = 10.0$ ).
2. Beam deflections under a moving load for fixed-simply supported end conditions ( $\gamma = 10.0$ ).
3. Beam deflections under a moving load for fixed-free supports ( $\gamma = 10.0$ ).
4. Beam deflections under a moving load for free-free end conditions ( $\gamma = 10.0$ ).
5. Beam deflections under a moving load for free-fixed supports ( $\gamma = 10.0$ ).



<b>Accession For</b>	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
<b>By</b>	
<b>Distribution/</b>	
<b>Availability Codes</b>	
Dist	Avail and/or
A	

STATEMENT OF THE PROBLEM

The dynamic equation of Euler-Bernoulli beam subjected to a moving force can be written as the following equation

$$EIv'''' + \rho Ay = P\delta(x-\bar{x}), \quad 0 \leq x \leq L, \quad (1)$$

$$0 \leq t \leq T$$

where  $v = v(x,t)$  denotes the beam deflection as a function of the spatial coordinates  $x$  and the time  $t$ . The letters  $E$ ,  $I$ ,  $A$ ,  $\rho$ , and  $L$  denote elastic modulus, second moment of the cross-sectional area, and the area itself, the length, and the material density of the beam, respectively. A Dirac delta function is denoted by  $\delta$ ,  $\bar{x} = \bar{x}(t)$  is the location of the force  $P$ .  $T$  denotes some finite time of interest. As usual, a prime (') denotes differentiation with respect to  $x$  and a dot ( $\dot{\phantom{x}}$ ), differentiation with respect to  $t$ .

The boundary conditions are written as

$$EIy'''(0,t) + k_1y(0,t) = 0$$

$$EIy''(0,t) - k_2y'(0,t) = 0$$

$$EIy'''(L,t) - k_3y(L,t) = 0$$

$$EIy''(L,t) + k_4y'(L,t) = 0$$
(2)

where  $k_i$ ,  $i = 1, 2, 3$ , and  $4$  are the spring constant which model the support characteristics. The initial conditions are

$$v(x, 0) = \bar{v}_0(x)$$

$$\dot{v}(x, 0) = \bar{v}_1(x)$$
(3)

Equations (1) through (3) will be written in dimensionless form for the sake of generality and simplicity. This is accomplished by the introduction of dimensionless parameters. In the following an arrow ( $\bar{\phantom{x}}$ ) will be read as "replaces":

$$y \rightarrow \frac{y}{\lambda}, \quad x \rightarrow \frac{x}{\lambda}, \quad t \rightarrow \frac{t}{T}$$

$$k_1 \rightarrow \frac{k_1 \lambda^3}{EI}, \quad k_2 \rightarrow \frac{k_2 \lambda}{EI}$$

$$k_3 \rightarrow \frac{k_3 \lambda^3}{EI}, \quad k_4 \rightarrow \frac{k_4 \lambda}{EI}$$

$$y_1 \rightarrow Ty_1, \quad P \rightarrow \frac{P \lambda^3}{EI}$$

With these new dimensionless parameters, Eqs. (1) through (3) become:

$$y'''' + \gamma^2 y = P \delta(x-x) \quad , \quad \begin{matrix} 0 \leq x \leq 1 \\ 0 \leq t \leq 1 \end{matrix} \quad (1')$$

$$\begin{aligned} y''(0,t) + k_1 y(0,t) &= 0 \\ y''(0,t) - k_2 y'(0,t) &= 0 \\ y''(1,t) - k_3 y(1,t) &= 0 \\ y''(1,t) + k_4 y(1,t) &= 0 \end{aligned} \quad \begin{matrix} \\ \\ 0 \leq t \leq 1 \\ \end{matrix} \quad (2')$$

and

$$\begin{aligned} y(x,0) &= \bar{y}_0(x) \\ y(x,0) &= y_1(x) \end{aligned} \quad \begin{matrix} \\ 0 \leq x \leq 1 \end{matrix} \quad (3')$$

where in Eq. (1'), we have

$$\gamma = \frac{c}{T} \quad (5a)$$

which is dimensionless, with

$$c = \left( \frac{\rho A \lambda^4}{EI} \right)^{1/2} \quad (5b)$$

which has the dimension of the physical time.

Hence then, we shall obtain solutions for the problem defined by Eqs.

(1') through (3') for various values of  $k_i$ ,  $i = 1, 2, 3$ , and 4.

## AN EQUIVALENT VARIATIONAL PROBLEM

The problem of solving the equation (1') through (3') in the previous section will be transformed into a variational problem. Consider

$$\delta I = 0 \quad (5a')$$

with

$$\begin{aligned} I = & \int_0^1 \int_0^1 \{ \frac{1}{2} \rho \dot{y}^{*2} + \frac{1}{2} \rho \dot{y}^2 + \frac{1}{2} (k_1 - k_2) y^* y \} dx dt \\ & + \int_0^1 dt \{ k_1 y(0, t) y^*(0, t) + k_2 y^*(0, t) y(0, t) \\ & + k_3 y(1, t) y^*(1, t) + k_4 y^*(1, t) y(1, t) \} \\ & + k_5 \int_0^1 dx \{ k_5 [y(x, 0) - \bar{y}_0(x)] y^*(x, 1) - \bar{y}_1(x) y^*(x, 0) \} \end{aligned} \quad (5b')$$

where  $y^*(x, t)$  is called the adjoint function of  $y(x, t)$ . If one takes the first variation of  $I$  considering  $y(x, t)$  to be fixed and  $\delta y^*$  to be completely arbitrary, it is easy to see that the differential equation (1') and boundary condition (2') will be recovered and the initial condition becomes

$$\begin{aligned} \dot{y}^*(x, 1) - k_5 [y(x, 0) - \bar{y}_0(x)] &= 0 \\ \dot{y}^*(x, 0) - \bar{y}_1(x) &= 0 \end{aligned} \quad (3'')$$

In Eq. (3''), it is seen that if one let  $k_5 \rightarrow \infty$  in the limit, the initial condition of (3') will also be recovered. The use of a large parameter such as  $k_5$  is known as the penalty function method or the method of large spring constant.<sup>1</sup>

<sup>1</sup>Wu, J. J., "Vibrations of a Beam Under Moving Loads by a Finite Element Formulation Consistent in Spatial and Time Coordinates," The 51st Shock and Vibration Bulletin, Part 3; Analytical Methods, Dynamics, and Vehicle Systems, pp. 111-130 (1981).

### OUTLINE OF SOLUTION FORMULATION

To derive the finite element matrix equations, one begins with (1) and (2) and writes

$$\begin{aligned} \kappa \text{Div}_x \gamma &= 0 \\ &= \int_0^1 \int_0^1 \{y'' \delta v^* - y' \delta v \delta x' + \delta y' (x-c) \delta x\} dx dt \\ &= \int_0^1 \{ \delta y [ \kappa y'(0,t) \delta v^*(1,t) + \kappa y'(1,t) \delta v^*(0,t) \\ &\quad - \kappa y(1,t) \delta v^*(1,t) + \kappa y(0,t) \delta v^*(0,t) ] \\ &\quad - \int_0^1 \delta x [ \kappa y(x,t) \delta v^*(x,t) - \kappa y(x,t) \delta v^*(x,t) ] \} dx dt \end{aligned}$$

The element local variables are now introduced

$$\begin{aligned} \xi &= \frac{(i)}{K} = Kx - i + 1 \\ \eta &= \frac{(j)}{L} = Lt - j + 1 \end{aligned} \quad (14)$$

or

$$\begin{aligned} x &= \frac{1}{K} (\xi + i - 1) \\ t &= \frac{1}{L} (\eta + j - 1) \end{aligned}$$

where  $K$  is the number of divisions in  $x$  and  $L$  in  $y$ . A typical grid scheme is shown in Figure 6). Equation (6b) can now be written as

$$\begin{aligned}
 & \sum_{j=1}^K \sum_{i=1}^L \left[ \frac{1}{K} \frac{1}{L} \frac{K^2}{L} y''(1j) \delta y^{*i}(1j) - \frac{r-L}{K} y(1j) y^{*i}(1j) \right] d\xi dn \\
 & + \sum_{j=1}^K \int_0^1 d\xi \left[ \frac{K_1}{L} y(1j) y^{*i}(1j)(0,0) + K_2 \frac{r}{L} y(1j) y^{*i}(1j) \delta y^{*i}(1j)(0,0) \right. \\
 & \quad \left. + \sum_{i=1}^L \int_0^1 d\xi \left[ \frac{1}{K} \frac{1}{L} \frac{1}{K} \{ r^2 k_5 (y(1j)(\xi, 0) y^{*i}(1j)(\xi, 1)) \} \right. \right. \\
 & \quad \left. \left. + \sum_{i=1}^L \int_0^1 d\xi \int_0^1 d\eta \frac{1}{K} \frac{1}{L} \frac{1}{K} \{ (x-\xi) y^{*i}(1j)(\xi, \eta) \} \right] d\eta \right. \\
 & \quad \left. + \sum_{i=1}^K \frac{r-k_5}{K} \int_0^1 d\xi [y_0(1)(\xi) \delta y^{*i}(1j)(\xi, 1)] \right. \\
 & \quad \left. + \sum_{i=1}^K \frac{r}{K} \int_0^1 d\xi [y_1(1)(\xi) \delta y^{*i}(1j)(\xi, 0)] \right] \quad (8)
 \end{aligned}$$

The shape function vector is now introduced. Let

$$y(1j)(\xi, \eta) = \underline{a}^T(\xi, \eta) \underline{Y}(1j)$$

$$y^{*i}(1j)(\xi, \eta) = \underline{a}^T(\xi, \eta) \underline{Y}^{*i}(1j) = \underline{Y}^{*i}(1j) \underline{a}(\xi, \eta) \quad (9)$$

Equation (8) then becomes

$$\begin{aligned}
 & \sum_{i=1}^K \sum_{j=1}^L \delta Y^{*T}(ij) \left( \frac{K^2}{L} A + \frac{\gamma^2 L}{K} B_1 \right) Y(ij) \\
 & + \sum_{i=1}^L \delta Y^{*T}(ij) \left( \frac{k_1}{L} B_1 + \frac{k_2 K^2}{L} B_2 \right) Y(ij) \\
 & + \sum_{i=1}^L \delta Y^{*T}(ij) \left( \frac{k_3}{L} B_3 + \frac{k_4 K^2}{L} B_4 \right) Y(ij) \\
 & + \sum_{i=1}^K \delta Y^{*T}(iL) \left( \frac{\gamma^2 k_5}{K} B_5 \right) Y(iL) \\
 = & \sum_{i=1}^K \sum_{j=1}^L \delta Y^{*T}(ij) \frac{P}{L} F(ij) + \sum_{i=1}^K \delta Y^{*T}(iL) \frac{\gamma^2 k_5}{K} G(i) \\
 & + \sum_{i=1}^K \delta Y^{*T}(iL) \frac{\gamma^2}{K} H(i) \tag{10}
 \end{aligned}$$

where, as it can be seen readily, that

$$\begin{aligned}
 A &= \int_0^1 \int_0^1 a_{i,j} a_{i,j}^T d\xi d\eta \\
 B &= \int_0^1 \int_0^1 a_{i,n} a_{i,n}^T d\xi d\eta \\
 B_1 &= \int_0^1 a_{i,n} a_{i,n}^T d\eta, \quad B_2 = \int_0^1 a_{i,n} a_{i,n}^T d\xi d\eta \\
 B_3 &= \int_0^1 a_{i,n} a_{i,n}^T d\eta, \quad B_4 = \int_0^1 a_{i,n} a_{i,n}^T d\xi d\eta \\
 B_5 &= \int_0^1 a_{i,1} a_{i,1}^T d\xi \\
 F(ij) &= \int_0^1 \int_0^1 a_{i,n} \bar{s}(ij)(\xi-\eta) d\xi d\eta, \quad G(i) = \int_0^1 a_{i,1} \bar{y}_0(i)(\xi) d\xi
 \end{aligned}$$

and

$$H_i = \int_0^1 a_{i,0} \bar{y}_1(i)(\xi) d\xi \tag{11}$$

Now Eq. (10) can be assembled in a global matrix equation

$$SY^*T^T K Y = SY^* F \quad (11)$$

by virtue of the fact that  $SY^*$  is not subjected to any constrained conditions, one has

$$Y = T^{-1} SY^{*T} K^{-1} SY^* F \quad (12)$$

which can be solved routinely. More details can be found in reference 1.

#### RESULTS AND CONCLUSIONS

Appropriate values of physical parameters must be assigned for obtaining numerical results. Let

$$v = \frac{L}{T} \quad (13)$$

be the velocity of the travelling force. Only constant velocity will be considered in this report. Thus  $T$  becomes the time required for the force to move from one end of the beam to the other end. As  $T$  varies from  $\infty$  to 0, the velocity  $v$  varies from 0 to  $\infty$  as  $L$  is always finite. Since we have normalized all the parameters in length with respect to  $L$ , it is not necessary to specify  $L$  in numerical computations. Instead, the beam's length is considered to be unity. The real value in length can be recovered simply by a multiplication of  $L$  to the normalized (dimensionless) ones. Then it will be helpful if  $v$  in Eq. (13) can be related to some reference velocity associated with the beam's characteristics. We shall select the velocity of the first mode of vibration (standing waves) of a cantilevered beam as this reference velocity and call it

---

<sup>1</sup>Wu, J. J., "Vibrations of a Beam Under Moving Loads by a Finite Element Formulation Consistent in Spatial and Time Coordinates," The 51st Shock and Vibration Bulletin, Part 3; Analytical Methods, Dynamics, and Vehicle Systems, pp. 111-130 (1981).

$v_1$ . Hence the normalized velocity is defined by

$$\bar{v} = \frac{v}{v_1} \quad (15)$$

Now, we shall relate this  $\bar{v}$  with the parameters defined earlier in this report. It is known in many textbooks on vibrations (for example, see reference 3) that for a cantilevered beam, the first mode of vibrations has a circular frequency

$$\omega_1 = (1.875)^2 / c = 3.5166 / c \quad (16)$$

where  $c$  is given in (5b). The corresponding frequency and period are then respectively

$$f_1 = \frac{\omega_1}{2\pi} = 0.560 / c \quad (\text{in cycles per seconds})$$

$$T_1 = \frac{1}{f_1} = 1.79 \quad (\text{in seconds}) \quad (16)$$

Hence

$$v_1 = \frac{2E}{T_1} = 2\pi f_1 = 1.12 \frac{c}{c} \quad (17)$$

and

$$\bar{v} = \frac{v}{v_1} = \frac{\gamma/T}{1.12 \gamma/c} = 0.895 \frac{c}{T} = 0.895 \gamma \quad (18)$$

where  $\gamma = c/T$ , as defined in Eq. (5b).

For the results computed in this report,  $\gamma$  is set to be ten. Hence  $\bar{v} = 8.95$  or  $v$  is about nine times  $v_1$ . At this load velocity, the dynamic effect of the moving force on the beam vibration is quite evident as shown in Figures 1 through 5. This is also approximately a typical speed at which a projectile

---

<sup>3</sup>Fryba, L. Vibration of Solids and Structures Under Moving Loads, Noordhoff International, Groningen, 1971, p. 91.

moves down a cannon tube (see, for example, reference 1). Figure 1 shows the deflection curves for a beam with fixed-fixed supports. Curves numbered I, II, III, and IV are at the moment when  $P$  is at  $1/4$ ,  $2/4$ ,  $3/4$ , and  $4/4$  of support. Figures 2 through 5 are the same curves for the support conditions of fixed-simple supported, fixed-free, free-free, and free-fixed respectively.

It should be noted that the load  $P$  is assumed to move from the left toward the right. The beam motions from fixed-free supports are quite different from those of free-fixed supports as demonstrated, for example, in Figures 1 and 5. This dynamic behavior has also been noted by Fryba.<sup>3</sup> In fact, the deflection curves for the case of free-fixed supports resemble closely to those of free-free supports than the fixed-free ones.

The values of the "spring constants" in Eqs. (2') and (5b) are as follows. For a fixed rigid support the  $k_1$  is taken to be  $10^{10}$ ; for no support at all, it is assigned a zero. The value of  $k_5$  in Eq. (5b) is also assigned to be  $10^{10}$ .

Results presented above are based on a grid scheme of  $5 \times 8$  elements. A typical grid scheme is shown in Figure 6). Numerical convergence of these data should be fairly good as discussed previously in Reference 1.

1Wu, J. J., "Vibrations of a Beam Under Moving Loads by a Finite Element Formulation Consistent in Spatial and Time Coordinates," The 51st Shock and Vibration Bulletin, Part 3; Analytical Methods, Dynamics, and Vehicle Systems, pp. 111-130 (1981).

3Fryba, Vibration of Solids and Structures Under Moving Loads, Noordhoff International, Groningen, 1971, p. 91.

4Wu, J. J., "Vibrations of a Beam Under Moving Loads by a Finite Element Formulation Consistent in Spatial and Time Coordinates," The 51st Shock and Vibration Bulletin, Part 3; Analytical Methods, Dynamics, and Vehicle Systems, pp. 126 (1981).

#### REFERENCES

1. Wu, J. J., "Vibrations of a Beam Under Moving Loads by a Finite Element Formulation Consistent in Spatial and Time Coordinates," The 51st Shock and Vibration Bulletin, Part 3; Analytical Methods, Dynamics, and Vehicle Systems, pp. 111-130 (1981).
2. Tong, K. N., Theory of Mechanical Vibration, John Wiley, New York, 1960, p. 256.
3. Fryba, L., Vibration of Solids and Structures Under Moving Loads, Noordhoff International, Groningen, 1971, p. 91.
4. Wu, J. J., "Vibrations of a Beam Under Moving Loads by a Finite Element Formulation Consistent in Spatial and Time Coordinates," The 51st Shock and Vibration Bulletin, Part 3; Analytical Methods, Dynamics, and Vehicle Systems, pp. 126 (1981).




Figure 1. Beam deflections under a moving load for fixed-fixed supports ( $\gamma = 10.0$ ).




Figure 2. Beam deflections under a moving load for fixed-simply supported end conditions ( $\nu = 10.0$ ).




Figure 3. Beam deflections under a moving load for fixed-free supports ( $\gamma = 10.0$ ).




Figure 4. Beam deflections under a moving load for free-free end conditions ( $\gamma = 10.0$ ).




Figure 5. Beam deflections under a moving load for a free-fixed supports ( $\gamma = 10.0$ ).

$\Delta t$




Figure 6

A Typical Grid of Finite Elements

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
COMMANDER	1
CHIEF, DEVELOPMENT ENGINEERING BRANCH	1
ATTN: DRDAR-LCB-DA	1
-DM	1
-DP	1
-DR	1
-DS	1
-DC	1
CHIEF, ENGINEERING SUPPORT BRANCH	1
ATTN: DRDAR-LCB-SE	1
-SA	1
CHIEF, RESEARCH BRANCH	1
ATTN: DRDAR-LCB-RA	1
-RC	1
-RM	1
-RP	1
CHIEF, LWC MORTAR SYS. OFC.	1
ATTN: DRDAR-LCB-M	
CHIEF, IMP. 81MM MORTAR OFC.	1
ATTN: DRDAR-LCB-I	
TECHNICAL LIBRARY	5
ATTN: DRDAR-LCB-TL	
TECHNICAL PUBLICATIONS & EDITING UNIT	2
ATTN: DRDAR-LCB-TL	
DIRECTOR, OPERATIONS DIRECTORATE	1
DIRECTOR, PROCUREMENT DIRECTORATE	1
DIRECTOR, PRODUCT ASSURANCE DIRECTORATE	1

NOTE: PLEASE NOTIFY ASSOC. DIRECTOR, BENET WEAPONS LABORATORY, ATTN:  
DRDAR-LCB-TL, OF ANY REQUIRED CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
ASST SEC OF THE ARMY RESEARCH & DEVELOPMENT ATTN: DEP FOR SCI & TECH THE PENTAGON WASHINGTON, D.C. 20315	1	COMMANDER US ARMY TANK-AUTMV R&D COMD ATTN: TECH LIB - DRDTA-UL MAT LAB - DRDTA-RK WARREN, MICHIGAN 48090	1 1
COMMANDER US ARMY MAT DEV & READ. COMD ATTN: DRUDE 5001 EISENHOWER AVE ALEXANDRIA, VA 22333	1	COMMANDER US MILITARY ACADEMY ATTN: CHMN, MECH ENGR DEPT WEST POINT, NY 10996	1
COMMANDER US ARMY ARRADCOM ATTN: DRDAR-LC -LCA (PLASTICS TECH EVAL CEN) -LCE -LCM -LCS -LCW -TSS (STINFO) DOVER, NJ 07801	1 1 1 1 1 2	US ARMY MISSILE COMD REDSTONE SCIENTIFIC INFO CEN ATTN: DOCUMENTS SECT, BLDG 4484 REDSTONE ARSENAL, AL 35898  COMMANDER REDSTONE ARSENAL ATTN: DRSMI-RRS -RSM ALABAMA 35809	2
COMMANDER US ARMY ARRCOM ATTN: DRSAR-LEP-L ROCK ISLAND ARSENAL ROCK ISLAND, IL 61299	1	COMMANDER ROCK ISLAND ARSENAL ATTN: SARRI-ENM (MAT SCI DIV) ROCK ISLAND, IL 61202	1
DIRECTOR US ARMY BALLISTIC RESEARCH LABORATORY ATTN: DRDAR-TSB-S (STINFO) ABERDEEN PROVING GROUND, MD 21005	1	COMMANDER HQ, US ARMY AVN SCH ATTN: OFC OF THE LIBRARIAN FT RUCKER, ALABAMA 36362	1
COMMANDER US ARMY ELECTRONICS COMD ATTN: TECH LIB FT MONMOUTH, NJ 07703	1	COMMANDER US ARMY FGN SCIENCE & TECH CEN ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	1
COMMANDER US ARMY MOBILITY EQUIP R&D COMD ATTN: TECH LIB FT BELVOIR, VA 22060	1	COMMANDER US ARMY MATERIALS & MECHANICS RESEARCH CENTER ATTN: TECH LIB - DRXMR-PL WATERTOWN, MASS 02172	2

NOTE: PLEASE NOTIFY COMMANDER, ARRADCOM, ATTN: BENET WEAPONS LABORATORY, DRDAR-LCB-TL, WATERVLIET ARSENAL, WATERVLIET, N.Y. 12189, OF ANY REQUIRED CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT)

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
COMMANDER US ARMY RESEARCH OFFICE P.O. BOX 12511 RESEARCH TRIANGLE PARK, NC 27709	1	COMMANDER DEFENSE TECHNICAL INFO CENTER ATTN: DTIA-TCA CAMERON STATION ALEXANDRIA, VA 22314	12
COMMANDER US ARMY HARRY DIAMOND LAB ATTN: TECH LIB 2800 POWDER MILL ROAD ADELPHIA, ME 20783	1	METALS & CERAMICS INFO CEN BATTELLE COLUMBUS LAB 505 KING AVE COLUMBUS, OHIO 43201	1
DIRECTOR US ARMY INDUSTRIAL BASE ENG ACT ATTN: DRXPE-MT ROCK ISLAND, IL 61201	1	MECHANICAL PROPERTIES DATA CTR BATTELLE COLUMBUS LAB 505 KING AVE COLUMBUS, OHIO 43201	1
CHIEF, MATERIALS BRANCH US ARMY R&S GROUP, EUR BOX 65, FPO N.Y. 09510	1	MATERIEL SYSTEMS ANALYSIS ACTV ATTN: DRXSY-MP ABERDEEN PROVING GROUND MARYLAND 21005	1
COMMANDER NAVAL SURFACE WEAPONS CEN ATTN: CHIEF, MAT SCIENCE DIV DAHLGREN, VA 22448	1		
DIRECTOR US NAVAL RESEARCH LAB ATTN: DIR, MECH DIV CODE 26-27 (DOC LIB) WASHINGTON, D. C. 20375	1 1		
NASA SCIENTIFIC & TECH INFO FAC. P. O. BOX 3757, ATTN: ACQ BR BALTIMORE/WASHINGTON INTL AIRPORT MARYLAND 21240	1		

NOTE: PLEASE NOTIFY COMMANDER, ARRADCOM, ATTN: BENET WEAPONS LABORATORY,  
DRDAF-ICB-TL, WATERVLIET ARSENAL, WATERVLIET, N.Y. 12189, OF ANY  
REQUIRED CHANGES.

FILMED  
4-8