







110000



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Technical Report No. 333	2. GOVT ACCESSION NO. AD-A112 368	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Sound Ranging Effectiveness Model (SREM)		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) William J. Hughes Henry C. Dubin		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Materiel Systems Analysis Activity Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS DA Project No. 1R665706M541
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Materiel Development & Readiness Command 5001 Eisenhower Avenue Alexandria, VA 22333		12. REPORT DATE December 1981
		13. NUMBER OF PAGES 118
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) DTIC NOTE MAR 23 1982		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Sound Ranging Acoustic Loading Acquisition of Targets via Sound Ranging		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The Sound Ranging Effectiveness Model (SREM), was developed in order to examine the loading effects of different firing rates on present sound ranging systems as well as to help establish criteria for future system requirements. The model uses artillery missions generated in a division level wargame (DIVLEV) to simulate the associated sounds and the times they reach the sound base as well as their relative intensities. Performance estimates for various sound ranging capabilities, based on 3 1/2 hours day and 3 1/2 hours night combat simulation are given.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

TABLE OF CONTENTS

	Page
1. INTRODUCTION	7
2. BACKGROUND	7
3. SREM DESCRIPTION	8
3.1 SREM Inputs	14
3.2 Generation of Sound Event Times	15
3.2.1 Indirect Fire Times	15
3.2.2 Direct Fire Times	15
3.2.3 Air Support Time	17
3.3 Generation of Sound Intensities	17
3.4 SREM Bookkeeping	17
3.5 Outputs	23
3.6 Sample Results	23
3.7 Sample Scenario	23
3.8 Sample Outputs	26
4. SUMMARY	38
APPENDIX A - SREM USER'S GUIDE	47
APPENDIX B - SAMPLE RUN	57
APPENDIX C - PROGRAM LISTING	81
DISTRIBUTION LIST	117

Accession, Per
 1915 1916
 1917 1918
 1919 1920
 1921 1922
 1923 1924
 1925 1926
 1927 1928
 1929 1930
 1931 1932
 1933 1934
 1935 1936
 1937 1938
 1939 1940
 1941 1942
 1943 1944
 1945 1946
 1947 1948
 1949 1950
 1951 1952
 1953 1954
 1955 1956
 1957 1958
 1959 1960
 1961 1962
 1963 1964
 1965 1966
 1967 1968
 1969 1970
 1971 1972
 1973 1974
 1975 1976
 1977 1978
 1979 1980
 1981 1982
 1983 1984
 1985 1986
 1987 1988
 1989 1990
 1991 1992
 1993 1994
 1995 1996
 1997 1998
 1999 2000
 2001 2002
 2003 2004
 2005 2006
 2007 2008
 2009 2010
 2011 2012
 2013 2014
 2015 2016
 2017 2018
 2019 2020
 2021 2022
 2023 2024
 2025 2026
 2027 2028
 2029 2030
 2031 2032
 2033 2034
 2035 2036
 2037 2038
 2039 2040
 2041 2042
 2043 2044
 2045 2046
 2047 2048
 2049 2050
 2051 2052
 2053 2054
 2055 2056
 2057 2058
 2059 2060
 2061 2062
 2063 2064
 2065 2066
 2067 2068
 2069 2070
 2071 2072
 2073 2074
 2075 2076
 2077 2078
 2079 2080
 2081 2082
 2083 2084
 2085 2086
 2087 2088
 2089 2090
 2091 2092
 2093 2094
 2095 2096
 2097 2098
 2099 2100
 2101 2102
 2103 2104
 2105 2106
 2107 2108
 2109 2110
 2111 2112
 2113 2114
 2115 2116
 2117 2118
 2119 2120
 2121 2122
 2123 2124
 2125 2126
 2127 2128
 2129 2130
 2131 2132
 2133 2134
 2135 2136
 2137 2138
 2139 2140
 2141 2142
 2143 2144
 2145 2146
 2147 2148
 2149 2150
 2151 2152
 2153 2154
 2155 2156
 2157 2158
 2159 2160
 2161 2162
 2163 2164
 2165 2166
 2167 2168
 2169 2170
 2171 2172
 2173 2174
 2175 2176
 2177 2178
 2179 2180
 2181 2182
 2183 2184
 2185 2186
 2187 2188
 2189 2190
 2191 2192
 2193 2194
 2195 2196
 2197 2198
 2199 2200
 2201 2202
 2203 2204
 2205 2206
 2207 2208
 2209 2210
 2211 2212
 2213 2214
 2215 2216
 2217 2218
 2219 2220
 2221 2222
 2223 2224
 2225 2226
 2227 2228
 2229 2230
 2231 2232
 2233 2234
 2235 2236
 2237 2238
 2239 2240
 2241 2242
 2243 2244
 2245 2246
 2247 2248
 2249 2250
 2251 2252
 2253 2254
 2255 2256
 2257 2258
 2259 2260
 2261 2262
 2263 2264
 2265 2266
 2267 2268
 2269 2270
 2271 2272
 2273 2274
 2275 2276
 2277 2278
 2279 2280
 2281 2282
 2283 2284
 2285 2286
 2287 2288
 2289 2290
 2291 2292
 2293 2294
 2295 2296
 2297 2298
 2299 2300
 2301 2302
 2303 2304
 2305 2306
 2307 2308
 2309 2310
 2311 2312
 2313 2314
 2315 2316
 2317 2318
 2319 2320
 2321 2322
 2323 2324
 2325 2326
 2327 2328
 2329 2330
 2331 2332
 2333 2334
 2335 2336
 2337 2338
 2339 2340
 2341 2342
 2343 2344
 2345 2346
 2347 2348
 2349 2350
 2351 2352
 2353 2354
 2355 2356
 2357 2358
 2359 2360
 2361 2362
 2363 2364
 2365 2366
 2367 2368
 2369 2370
 2371 2372
 2373 2374
 2375 2376
 2377 2378
 2379 2380
 2381 2382
 2383 2384
 2385 2386
 2387 2388
 2389 2390
 2391 2392
 2393 2394
 2395 2396
 2397 2398
 2399 2400
 2401 2402
 2403 2404
 2405 2406
 2407 2408
 2409 2410
 2411 2412
 2413 2414
 2415 2416
 2417 2418
 2419 2420
 2421 2422
 2423 2424
 2425 2426
 2427 2428
 2429 2430
 2431 2432
 2433 2434
 2435 2436
 2437 2438
 2439 2440
 2441 2442
 2443 2444
 2445 2446
 2447 2448
 2449 2450
 2451 2452
 2453 2454
 2455 2456
 2457 2458
 2459 2460
 2461 2462
 2463 2464
 2465 2466
 2467 2468
 2469 2470
 2471 2472
 2473 2474
 2475 2476
 2477 2478
 2479 2480
 2481 2482
 2483 2484
 2485 2486
 2487 2488
 2489 2490
 2491 2492
 2493 2494
 2495 2496
 2497 2498

LIST OF TABLES

Table Number		Page
1	Sound Ranging AN/TNS-10 Characteristics	12
2	Sustained Rates of Fire for Weapons Used in Sample Scenario	16
3	Equivalent Bare TNT Charges Used to Simulate Initial Sound Intensities	18
4	Force Composition in Sample Scenario	25

LIST OF FIGURES

Figure No.		Page
1	Sound Base Deployment Schematic	9
2	Typical Sound Breaks on a Paper Tape for a Low Rate of Fire	10
3	Correlation of Sound Breaks	11
4	Sound Ranging Effectiveness Model Basic Flow Diagram . . .	13
5	Sample SREM Outputs	20
6	Sound Ranging Capabilities	22
7A	Potential Target Production for CT=6 System With a 2- Minute Processing Time	24
7B	Potential Target Production for a CT=12 System With a Negligible Target Processing Time	24
8	Rate of Fire as a Function of Percent of Game Time (Daytime)	27
9	Rate of Fire as a Function of Percent of Game Time (Night time)	28
10	Unique Targets Located by a Manual System in the Sample High Intensity Scenario	29
11	Unique Targets Located by an Automatic System in the Sample High Intensity Scenario	30
12	Unique Targets Located by a Manual System in the Sample Moderate Intensity Scenario	31
13	Unique Targets Located by an Automatic System in the Sample Moderate Intensity Scenario	32
14	Summary of Unique Sound Ranging Acquisitions.	33
15	Rate of Unique Target Production as a Function of the Rates of Fire in the Sample Moderate Intensity Scenario.	34
16	Rate of Unique Target Production as a Function of the Rates of Fire in the Sample High Intensity Scenario. . .	35
17	Rate of Unique Target Production as a Function of the Rates of Fire in the Sample Moderate Intensity Scenario. .	36

LIST OF FIGURES (continued)

Figure No.		Page
18	Rate of Unique Target Production as a Function of the Rates of Fire in the Sample High Intensity Scenario.	37
19	Total Targets Located by a Manual System in the Sample High Intensity Scenario	39
20	Total Targets Located by an Automatic System in the Sample High Intensity Scenario	40
21	Total Targets Located by a Manual System in the Sample Moderate Intensity Scenario	41
22	Total Targets Located by an Automatic System in the Sample Moderate Intensity Scenario	42
23	Rate of Unique Target Production as a Function of the Rate of Fire in the Sample High Intensity Scenario (Manual System)	43
24	Rate of Unique Target Production as a Function of the Rate of Fire in the Sample High Intensity Scenario (Automatic System)	44
25	Rate of Unique Target Production as a Function of the Rate of Fire in the Sample Moderate Intensity Scenario (Manual System)	45
26	Rate of Unique Target Production as a Function of the Rate of Fire in the Sample Moderate Intensity Scenario (Automatic System)	46

SOUND RANGING EFFECTIVENESS MODEL (SREM)

1. INTRODUCTION

Recently, there has been a resurgence of interest in sound ranging as a target acquisition system. This resurgence of interest may be attributed to several factors:

(a) Cost -- when compared to other target acquisition systems sound ranging is relatively inexpensive.

(b) Detectability -- while radars must transmit intermittently and move periodically to avoid detection, a sound base is passive and may remain operative continuously.

(c) Commonality -- presently, sound ranging is the most common system for locating hostile indirect fire weapons among the NATO countries.

(d) Historical success -- during both World War II and the Korean War, sound ranging was the most productive target acquisition system available.

In support of this increased interest, AMSAA has developed a sound ranging effectiveness model (SREM). This model, which is keyed to a two-sided division level wargame, was developed to examine the loading effects of different firing rates on present manual sound ranging systems, as well as to help establish criteria for future system requirements.

The model uses artillery missions generated in the division level wargame to simulate the associated sounds and the times they reach the sound base as well as their relative intensities.

Performance estimates for various sound ranging capabilities, based on 3 1/2 hour-day and 3 1/2-hour night combat simulation, are given. Results show that although sound ranging will often be saturated at the high firing rates associated with an intense break-through scenario, there are still many opportunities to locate hostile indirect fire positions.

Appendix A contains a User's Guide on how to set up an input file and run the program. Appendix B contains a listing of SREM along with sample inputs and sample outputs.

2. BACKGROUND

The French initiated experiments in sound ranging in September 1914. These experiments led to the organization of sound ranging sections within the French Army and subsequently, sound ranging sections were rapidly adopted by all of the Allies.

By 1934, the first US observation battalion, under the Field Artillery, was activated. Improvements made at this time included modifications to permit the use of standard field wire, more sensitive microphones, improved designs of recording instruments, more accurate plotting equipment, and adaptation of procedures to improve tactics.

During World War II, the US sound ranging community was expanded to 25 full observation battalions for approximately 75 percent of all confirmed targets located during World War II.

By 1950, when the Korean War started, the 1st Observation Battalion was the only organization of its kind in the US Army, and it was only at 60 percent full strength. By the end of the Korean conflict, there were four observation battalions, two of which were in Korea. During the Korean War, sound ranging, on the average, located 4 percent of all active batteries on a given day, this represented 59 percent of all locations made.

In Vietnam, due to the long emplacement time and the large amounts of wire necessary, sound bases were deployed only along the DMZ, but due to the poor condition of the equipment (the equipment was World War II vintage) and the lack of experience of the operators, sound ranging was deemed to be of little use.

Figure 1 illustrates the typical deployment of a sound base. The sound observers, labeled O.P. initiate a paper tape strip recorder, which is located at the command post, when they detect incoming sounds. The paper tape records the low frequency responses of the six microphones on six separate channels as typified in Figure 2. A three foot strip of tape, corresponding to about six seconds, is activated by the sound observer. The command post crew would then try to correlate the six breaks, one on each channel, which resulted from the same sound source. By determining the differences in times of arrival for any two channels, a bearing to the sound source can be manually plotted. When the five independent bearings all intersect closely, the weapon location has been determined. Figure 3 demonstrates which of the sound "breaks" in Figure 2 could be correlated to give sound locations. Table 1 lists the basic characteristics of the current US sound ranging system. Near-term improvements to this system include replacement of wire by radio data links and a computer and CRT to assist in plotting the sound locations.

Although Figure 2 depicts a strip of tape with a relatively low rate of sound events, about 25 sound events per minute, one can see that the art of reading and correlating the breaks requires a high level of skill and proficiency. In particular, it has long been known that high rates of fire can completely saturate a reader's ability to resolve any targets on a tape in a timely manner.

To date, no study has been found which addresses the loading problems a sound ranging system will face in a mid-to-high-intensity scenario. The sound ranging effectiveness model was developed in order to determine how often a sound ranging system will be saturated, and what target producing capabilities it will have in such a scenario.

3. SREM DESCRIPTION

Figure 4 shows the basic flow diagram for the sound ranging effectiveness model (SREM).




FIGURE 1. SOUND BASE DEPLOYMENT SCHEMATIC




FIGURE 2. TYPICAL SOUND BREAKS ON A PAPER TAPE FOR A LOW RATE OF FIRE




FIGURE 3. CORRELATION OF SOUND BREAKS

TABLE 1. SOUND RANGING SET AN/TNS-10 CHARACTERISTICS

AN/TNS-10 IS A PRODUCT IMPROVED AN/GR-8 (FULLY TRANSISTORIZED)

NUMBER OF RECORDING CHANNELS	-	6
METHOD OF RECORDING	-	DRY, ELECTROSTATIC
RECORD MEDIUM	-	TELEDELTO PAPER
CHART SPEED	-	6 INCHES/SECOND
TIMING MARKS	-	0.01, 0.1, 1.0 SECOND
DIGITAL TIME PRINTOUT	-	1-SECOND INTERVALS
POWER REQUIREMENTS	-	STANDBY: 12 VOLTS; 125 MA OPERATING: 12 VOLTS; 7.5 AMP
SIZE	-	TRANSIT CASE: 13.5" x 16.5" x 26.5" OPERATIONAL: 12.4" x 21.9" x 10.3"
WEIGHT (INCLUDING TRANSIT CASE)	-	100 LBS

SOUND RANGING EFFECTIVENESS MODEL




FIGURE 4 BASIC FLOW DIAGRAM

type of ordnance delivered
amount of ordnance delivered

This output file which is generated by the wargame is then used as the input file for SREM.

3.2 Generation of Sound Event Times.

Sound event times are generated based on the times that sounds would arrive at the sound ranging microphone. Initial times for each sound event, that is, the time the sound events were created, are based on the mission start time (from the input file), and the sustained rate of fire for that weapon. Initial times for impacts are based on the firing time for the weapon involved and the flight time of the projectile (which is dependent on the weapon-to-target distance).

Once an initial time for a sound event is determined, the time required for the sound to propagate to the sound ranging microphone must be calculated. The propagation time in SREM is calculated using a constant speed of sound (assuming a homogeneous standard atmosphere) over the distance from the sound event to the microphone.¹

3.2.1 Indirect Fire Times. At the start of each indirect fire mission, the initial firing time for each weapon is distributed normally about the mission start time in order to simulate crew reaction time. Subsequent firing times for each weapon are based on a normal distribution about the mean firing rate for that weapon. Table 2 gives the standard rates of fire for the various indirect fire weapons which were played. A standard deviation of one tenth the time between firings was used, and a minimum firing time of one third the standard time between rounds was imposed. Firing times for each weapon in that battery continue to be generated for the entire length of the mission.

3.2.2 Direct Fire Times. For direct fire engagements, the initial firing times and the subsequent firing times are calculated using the same rules used for direct fire missions. However, the rate of fire for these engagements is determined by the number of rounds fired by that unit in that minute; this is obtained from the input file. Two engagements of the same unit, therefore, will not necessarily have the same rate of fire. The number of rounds fired is dependent on the individual engagement and is determined by the wargame. For direct fire missions consisting of tanks and anti-tank guided missiles (ATGM) only the muzzle blast from the tank main armament, and only the impact sound from an ATGM are considered as sound sources which would register on the sound ranging microphone. The impact from a tank round and the launch of an ATGM are mostly high frequency sound events which tend to be discriminated out at the microphone.

¹ The reader is reminded that the purpose of SREM is to investigate only the loading effects on sound ranging systems; the details of sound propagation through moving and inhomogeneous atmospheres, although required for accuracy calculation, is not warranted by the one second time resolution of SREM.

TABLE 2. SUSTAINED RATES OF FIRE

<u>WEAPON</u>	<u>ROUNDS/MIN</u>
155 MM HOWITZER.	1.0
8 INCH	.5
81 MM MORTAR	8
4.2 INCH MORTAR.	3
120 MM MORTAR.	3
152 MM GUN/HOWITZER.	1
122 MM MULTIPLE RAIL LAUNCHER.	40
130 MM GUN	1
122 MM HOWITZER.	1.5

3.2.3 Air Support Times. Air support missions have the number and type of ordnance to be delivered specified. The ordnance is delivered uniformly over the time period indicated by the mission duration time.

3.3 Generation of Sound Intensities.

The firing charge used for each mission is determined by first computing the range to the target; then from the weapon firing tables one of the top three charges available for firing that range is selected randomly. The peak over pressure detected at the sound ranging microphone is calculated using the equation:

$$P = 210(W^{1/3}/R)1.047$$

where P = pressure in pounds per square inch,
W = equivalent charge weight in pounds of TNT, and
R = range in feet from the sound source to the microphone.

This equation was developed by curve fitting to data collected by the Ballistic Research Laboratories (BRL) and reported in BRL Report #1240. SREM converts this pressure to amplitude in db for printout and storage. Table 3 shows the TNT charges used for approximating both muzzle and impact blasts. The charges are those used for the various missions fired in the wargame. The equivalent TNT charge weights have already been taken to the 1/3 power as used in the propagation formula. It should be noted that these equivalent TNT charges are matched to far field peak overpressures and are not intended to reflect the destructive force from the actual muzzle or impact blast.

3.4 SREM Bookkeeping.

Sound events are grouped by amplitude and then ordered based on their arrival times at the sound ranging microphone. Figure 5 is a sample output available from SREM. "MIN" is the minute of the wargame being displayed. "SEC" is the second in the minute under consideration. "TOT" is the total number of sound events in that second which could be detected. The numbers across the top indicate the amplitudes at which the sounds arrived. Sounds arriving below 70db in amplitude were considered too low to be detected and were, therefore, not included in the total. The numbers to the right of the slash indicate how many of the total number of sound events are Red indirect fire muzzle events.

One of the purposes of this model, given the loading effects of a scenario, is to evaluate parametrically the target production potential of sound systems based on the capability to discern sound sources whose sounds overlap in time at the various microphones in the sound base. Therefore, an input parameter was included which allows the user to arbitrarily define when a sound ranging system is no longer capable of discerning targets due to saturation. As the rate of sound events reaching the sound ranging microphone increases, the capability of the system to discern targets initially increases proportionally then levels off and finally decreases due to both the overlapping of arriving sound signatures and the increased difficulty in associating which of the several sound breaks on each channel corresponds to the same source. Within the expected area of coverage of a

TABLE 3. EQUIVALENT BARE TNT CHARGES USED TO
SIMULATE INITIAL SOUND INTENSITIES

<u>WEAPON TYPE</u>	<u>CHARGE</u>	<u>EQUIVALENT TNT CHARGE $W^{1/3}$ (IN LBS$^{1/3}$)</u>	<u>EQUIVALENT TNT CHARGE USED FOR DETONATION OF HE ROUND (IN LBS$^{1/3}$)</u>
155mm howitzer	3w	1.46	2.605
	4w	1.59	
	5w	1.90	
	6w	2.13	
	7w	3.04	
8 inch howitzer	1	1.63	3.311
	2	1.87	
	4	2.34	
	5	2.50	
	6	2.81	
	7	3.04	
81mm mortar	6	.524	1.341
	7	.555	
	9	.617	
4.2 inch mortar	19	.745	1.983
	20	.763	
	25	.839	
	39	.921	
	40	.927	
120mm mortar	1	.355	1.728
	2	.427	
	3	.479	
	4	.530	
	5	.575	
	6	.618	
122mm howitzer	4	.538	2.089
	3	1.37	
	2	1.67	
	1	2.02	
	Partial	2.34	
	Full	2.82	
152mm howitzer	12	1.48	1.934
	10	1.68	
	8	1.90	
	5	2.28	
	3	2.50	
	1	2.56	
	Full	2.63	

TABLE 3. CONTINUED

WEAPON TYPE	CHARGE	EQUIVALENT TNT CHARGE $W^{1/3}$ (IN LBS $^{1/3}$)	EQUIVALENT TNT CHARGE USED FOR DETONATION OF HE ROUND (IN LBS $^{1/3}$)
122mm MRL		.073	2.089
130mm gun	4	.186	2.089
	3	.280	
	2	.401	
	1	.629	
	Full	1.05	
125mm tank gun		2.50	
175mm gun	1	2.90	3.288
	2	3.43	
	3	3.95	
105mm tank gun .		2.29	
CBU-24			4.54
Rockeye			4.10
Maverick			3.50
RBK-500			4.54
RBK-250			4.10
500 lb bomb			5.76

MIN = 0713		AMPLITUDE IN DB										
SEC	TOT	> 110	105-110	100-105	95-100	92-95	89-92	87-89	84-87	80-84	70-80	< 70
1	2	/	/	1/	/	/	/	/	/	/	1/1	10/10
2	2	/	/	/	/	/	/	/	/	1/1	1/1	/
3	5	/	1/	/	1/	/	/	/	1/1	/	2/2	/
4	12	/	2/	/	4/	/	/	/	3/2	2/1	1/	/
5	3	/	1/	/	/	/	/	/	/	/	2/2	8/8
6	3	/	1/	/	/	/	/	/	/	1/1	1/1	/
7	4	/	1/	/	/	/	/	/	/	/	3/3	7/6
8	4	/	1/	/	/	/	1/	/	1/	/	1/1	/
9	2	/	/	1/	/	/	/	/	/	/	1/1	/
10	4	/	/	/	2/	/	/	/	2/1	/	/	/
11	1	/	/	/	/	/	/	/	/	/	1/1	/
12	3	1/	/	/	/	/	/	/	/	1/1	1/1	/
13	/	/	/	/	/	/	/	/	/	/	/	6/6
14	/	/	/	/	/	/	/	/	/	/	/	5/4
15	/	/	/	/	/	/	/	/	/	/	/	/
16	4	1/	/	1/	/	/	/	/	/	1/1	1/1	/
17	4	1/	/	/	1/	/	/	/	1/	1/1	/	/
18	5	/	1/	/	1/	/	/	/	/	/	3/2	/
19	/	/	/	/	/	/	/	/	/	/	/	/
20	3	/	1/	/	/	/	/	/	/	1/1	/	/

FIGURE 5 . SAMPLE SREM OUTPUT

linear sound base (In a linear sound base the microphone are placed 1 sound sec apart), the arrival times at six microphones from a single sound source will usually occur within 6 seconds. This input parameter, therefore, is defined in terms of the number of sound events arriving in a 6-second window at a single point. The point chosen for measuring the number of sound events should represent the center of the sound base deployed. In this way sound events have already traversed three microphones by the time the model detects them. A location can be made with information from 3 channels (accuracy improves with additional information from other channels). Therefore, using a six second window insures that a sound event has or will have traversed at least three sound ranging microphones during that 6 second period and that a location can be determined for each sound event detected in a six second window where the CT has not been exceeded.


This input parameter, which we call the critical threshold (CT), is defined as the maximum number of sound events that may occur during a 6-second period in which it is still possible to discern targets. By varying the critical threshold, various sound ranging capabilities can be modeled. The user should take care to identify all the variables which will reduce the point at which a particular system will saturate (the CT), since the results obtained are very dependent on this parameter.

Once all the sound events are generated, the output is scanned with a 6-second window. If the total number of sound events in the window is less than CT then all the Red muzzle events in that 6-second window are counted as discernible. The number of discernible Red muzzle events in that window is then used to increment how often that number of targets could be detected at the current rate of fire. The Combat Surveillance and Target Acquisition Lab at Ft. Monmouth, NJ performed an analysis on the capabilities of sound ranging; part of their results are summarized in Figure 6.

Figure 6¹ represents the resolvable combinations per minute for a given number of arrivals per minute. This would represent the limiting capabilities of a completely automated system in a steady state condition. This also represents the physical limitations on sound ranging. For example, the curve labeled "5 of 6" is the theoretical limit, assuming that the interarrival times on each channel are distributed exponentially and independently, that at least five out of six channels will have sound breaks which do not overlap any of the other breaks on each of those channels. Another way of understanding the curves displayed in Figure 6 is to assume a limiting capability on a particular system. For example, if a system had 6 channels and required unmasked sound breaks on at least 4 channels then the curve "< 4 of 6" would represent its capabilities, however, if that same system required unmasked sound breaks on at least 5 channels then its capability would be reduced to that labeled "< 5 of 6." This figure also demonstrates that if you have a large number of microphones, then the probability of having unmasked sound breaks on at least 5 channels is much higher, which is only logical. It is noted that the abscissa for these

¹ Figure 6 was provided by the Combat Surveillance and Target Acquisition Laboratory, Fort Monmouth, NJ.

"SOUND RANGING CAPABILITIES"



RANDOM ARRIVALS-RESOLUTION = .125 SEC.

FIGURE 6. SOUND RANGING CAPABILITIES (Figure provided by Combat Surveillance and Target Acquisition Laboratory, Ft. Monmouth, NJ)

curves is the average number of sound events arriving per minute - not the rate of fire - and that the ordinate shows how many of these events could be resolved.

3.5 Outputs.

SREM provides the user with:

- a time history of when and how many targets were acquired as well as the number of these that would be unique targets
- percent of game time a sound ranging system would be able to locate 1,2,3,..... etc. Red muzzle events for all rates of fire in the game
- based on results obtained at the different rates of fire, SREM computes what percent of game time a sound ranging system would be able to locate 1,2,3,..... etc. Red muzzle events assuming the rate of fire was held constant
- percent of game time for each rate of fire

3.6 Sample Results.

For the purposes of this analysis, it was assumed that a critical threshold (CT) of 6 was equivalent to the capabilities of a present day manual system comparable to that of an AN/TNS-10. A CT of 12 was assumed to be equal to the capabilities of an achievable, automated system. The limiting potentials of these two systems are shown in Figures 7A and 7B. For the manual system (Figure 7A) the potential for locating sound events increases linearly as a function of total battlefield rounds per minute to a maximum of 30 locations per hour at 30 rounds per minute. Beyond 30 rounds per minute the capability decays rapidly until slightly above 100 rounds per minute the system becomes saturated and no sound event locations could be discerned. However, due to the processing time involved in reading the charts, plotting the sound breaks and calculating the locations, this system is saturated at 30 locations per hour. For the automatic system (Figure 7B) the potential for locating sound events increases linearly as a function of total battlefield rounds per minute to a maximum of 60 locations per minute at 60 rounds per minute, the automatic system's capability also decays rapidly until at approximately 200 rounds per minute this system also becomes saturated and can produce no locations.

3.7 Sample Scenario.

A sample scenario consisting of 3 1/2 hours of daytime and 3 1/2 hours of nighttime combat was exercised using DIVLEV, AMSAA's two-sided division level wargame. The artillery force composition is listed in Table 4. All the required inputs were extracted from both scenarios and SREM was executed, modeling the capabilities of both a manual and an automatic system as mentioned above.




FIGURE 7A. Potential Target Production for a CT=6 System with a 2 Minute Target Processing Time




FIGURE 7B. Potential Target Production for a CT=12 System with a Negligible Target Processing Time

FORCE COMPOSITION

BLUE 1 ARMORED DIV + 2 EXTRA BRIGADES
 1 ARMORED CAVALRY REGIMENT

2E - 4.2 MORT PLTS
5 - 155 BNS
2 - 155 BTRYs
3 - 8" BNS
1 - 175 BN

RED 4 TANK DIVISIONS
 1 MOTORIZED RIFLE DIV

21 - 120 MORT BTRYs
17 - 122 BNS
14 - 152 BNS
7 - MRL BNS
7 - 130 BNS

TABLE 4

For the 3 1/2 hours of daytime combat (a covering force scenario), Figure 8 shows the distribution of rates of fire by percent of game time. Applying the capabilities of both a manual and automatic system as described above, a manual system (which is only operable at rates of fire below 100 rounds per minute) would be capable of making locations less than 1 percent of the game time. An automatic system (operable below 200 rounds per minute) would be capable of making locations approximately 9 percent of the game time.

Figure 9 shows the distribution of rates of fire by percent of game time for the 3 1/2 hours of night combat (which is nearer to the main battle area). Again applying the two different capabilities, a manual system would still be limited in the amount of time it could be productive to less than 4 percent; however, an automatic system in this scenario would remain operable approximately 33 percent of the game time.

3.8 Sample Outputs.

The capabilities of both a manual and an automatic sound ranging system were modeled in SREM for both 3 1/2 hour segments of game time. Figure 10 shows for the daytime 3 1/2 hours of combat, the cumulative number of unique Red artillery batteries located as a function of game time for capabilities representing a manual system. During the first hour there was a relative lull during which five targets could be located. For the next 2 hours, the system was totally saturated until just past seven when one more location was made. Figure 11 gives the cumulative unique Red artillery batteries located as a function of game time for the capabilities representing an automatic system. During the early lull that the manual system was capable of making five locations, the automatic system was able to make nine locations. For the next 90 minutes this system was also saturated. When the next lull in the firing occurred, the automatic system was able to locate 19 additional Red artillery batteries, compared to one additional location for the manual system for the same time period.

Figure 12 is a manual system's capabilities during the 3 1/2-hour nighttime segment of the battle. During the first hour there was enough activity left from the daytime to saturate this system; there was then a half hour lull during which 10 Red artillery batteries could be located, but for the rest of the scenario this system was totally saturated. Figure 13 shows the automatic system's capabilities during the same time period. The automatic system was able to take advantage of the slightly lower rates of fire for the first hour and 45 minutes. During the next hour, there was an attempted river crossing during which the rates of fire increased to the point where they saturated the automated system. During the last 45 minutes, the system was again capable of producing targets at a usable rate. Figure 14 is a summary showing the total number of unique Red batteries located during both 3 1/2-hour segments of game time by the manual and automatic systems. This shows that increasing sound ranging capabilities to even a modest automated system increases the number of locations four to five times.

Figures 15-18 show the target production capability as a function of rate of fire for both the manual and automated systems. The rate of fire in these graphs was based on continuous fire at rates generated by DIVLEV.




FIGURE 8. RATE OF FIRE AS A FUNCTION OF PERCENT OF GAME TIME (DAYTIME)




FIGURE 9. RATE OF FIRE AS A FUNCTION OF PERCENT OF GAME TIME (NIGHT-TIME)

MANUAL SYSTEM (CT = 6)
DAYTIME SCENARIO (HIGH INTENSITY)




FIGURE 10. UNIQUE TARGETS LOCATED BY A MANUAL SYSTEM
IN THE SAMPLE HIGH INTENSITY SCENARIO

AUTOMATIC SYSTEM (CT=12)
DAYTIME SCENARIO (HIGH INTENSITY)




FIGURE 11. UNIQUE TARGETS LOCATED BY AN AUTOMATIC SYSTEM IN THE SAMPLE
HIGH INTENSITY SCENARIO

MANUAL SYSTEM (CT = 6)
NIGHT TIME SCENARIO (MODERATE INTENSITY)




FIGURE 12. UNIQUE TARGETS LOCATED BY A MANUAL SYSTEM IN THE SAMPLE MODERATE INTENSITY SCENARIO.

AUTOMATIC SYSTEM (CT = 12)
NIGHTTIME SCENARIO (MODERATE INTENSITY)




FIGURE 13. UNIQUE TARGETS LOCATED BY AN AUTOMATIC SYSTEM
IN THE SAMPLE MODERATE INTENSITY SCENARIO.

SCENARIO SR CAPABILITY	DAY (COVERING FORCE)	NIGHT (MBA)
PRESENT MANUAL	6	10
MODEST AUTOMATIC	25	55

RED ARTILLERY BATTERIES LOCATED

FIGURE 14. SUMMARY OF UNIQUE SOUND RANGING ACQUISITIONS

MANUAL SYSTEM* (CT=6)
STEADY STATE CONDITIONS
(MID INTENSITY)




FIGURE 15 RATE OF UNIQUE TARGET PRODUCTION AS A FUNCTION
OF THE RATES OF FIRE IN THE SAMPLE MODERATE INTENSITY SCENARIO

MANUAL SYSTEM (CT=6)
STEADY STATE CONDITIONS
(HIGH INTENSITY)




FIGURE 16 RATE OF UNIQUE TARGET PRODUCTION AS A FUNCTION OF THE RATES OF FIRE IN THE SAMPLE HIGH INTENSITY SCENARIO

AUTOMATIC SYSTEM (CT=12)
STEADY STATE CONDITION
(MID INTENSITY)




FIGURE 17 RATE OF UNIQUE TARGET PRODUCTION AS A FUNCTION OF THE RATES OF FIRE IN THE SAMPLE MODERATE INTENSITY SCENARIO

**AUTOMATIC SYSTEM (CT=12)
STEADY STATE CONDITION
(HIGH INTENSITY)**




FIGURE 18 RATE OF UNIQUE TARGET PRODUCTION AS A FUNCTION OF THE RATES OF FIRE IN THE SAMPLE HIGH INTENSITY SCENARIO

Figures 19-22 show the cumulative number of red indirect artillery weapons capable of being located as a function of game time. When compared to the unique number of batteries capable of being located it can be seen that many batteries could have been located several times.

In a tactical situation, however, rates of fire rarely remain constant for more than a few seconds. When the average rate of fire is high it may be possible to still locate some targets during lulls in the firing. For the purpose of giving the reader a feel for these tactical fluctuations, the resolvable targets displayed in Figures 15-18 are also given in Figures 23-26, where in the latter figures the rates of fire are averaged over a five minute period around the six second window used for determining the number of discernable targets. In Figures 23-26, the potential of the hypothetical sound systems to locate hostile indirect fire weapons depends on the tactical fluctuations in the overall rates of fire as well as the sound system resolving capability.

4. SUMMARY

The Sound Ranging Effectiveness model was not designed to model any one system. SREM provides the distribution of sound events down to a 1-second resolution as would be expected in a tactical situation. The use in SREM of a critical threshold (CT) is a simplified parametric approach to modeling various sound ranging capabilities. In the event the user wishes to model a specific system in greater detail, SREM has been set up to allow the user to easily add subroutines reflecting their system model. The program will provide a sliding 6-second window which may be examined by any subroutines. The 6-second window will contain the amplitude and type of every sound event occurring in this window.

SREM has been developed to address the problems of loading and saturation of sound ranging systems. As such, it can provide to the analyst estimates of sound ranging performance on to the designer, future system requirements based on various scenarios. The authors feel that the passive operation and relatively low cost make future automatic sound ranging systems viable candidates for helping to satisfy the Army's counterbattery target acquisition needs. Although not addressed in this model, improved meteorological data acquisition systems and numerical plotting solutions are being developed which significantly improve sound ranging accuracy as compared with past capabilities. Accuracies better than 50 meters can be expected under favorable conditions such as nighttime or fog (utilizing short base subarrays and cross correlation techniques). It is also clear that future sound systems for the fast moving European scenarios will have to use radio links and automatic positioning systems which are under development to greatly enhance mobility over what has been achievable in the past.

In short, with improved accuracy and mobility on the horizon, the use of microprocessors for signal processing and mini computers for numerical plotting solutions would make automatic sound ranging a considerable target acquisition asset as illustrated in SREM example scenario.

MANUAL SYSTEM (CT-6)
DAYTIME SCENARIO (HIGH INTENSITY)




FIGURE 19 TOTAL TARGETS LOCATED BY A MANUAL SYSTEM IN
THE SAMPLE HIGH INTENSITY SCENARIO

AUTOMATIC SYSTEM (CT=12)
DAYTIME SCENARIO (HIGH INTENSITY)




FIGURE 20 TOTAL TARGETS LOCATED BY AN AUTOMATIC SYSTEM IN THE
SAMPLE HIGH INTENSITY SCENARIO

MANUAL SYSTEM (CT=6)
NIGHTTIME SCENARIO (MODERATE INTENSITY)




FIGURE 21 TOTAL TARGETS LOCATED BY A MANUAL SYSTEM
IN THE SAMPLE MODERATE INTENSITY SCENARIO

AUTOMATIC SYSTEM (CT=12)
NIGHTTIME SCENARIO (MODERATE INTENSITY)




FIGURE 22 TOTAL TARGETS LOCATED BY AN AUTOMATIC SYSTEM
IN THE SAMPLE MODERATE INTENSITY SCENARIO

MANUAL SYSTEM (CT=6) IN A TACTICAL SITUATION
(DAY COVERING FORCE ACTION)




FIGURE 23 RATE OF UNIQUE TARGET PRODUCTION AS A FUNCTION
OF THE RATE OF FIRE IN THE SAMPLE HIGH INTENSITY
SCENARIO

AUTOMATIC SYSTEM (CT=12) IN A TACTICAL SITUATION (DAYTIME COVERING FORCE ACTION)




FIGURE 24 RATE OF UNIQUE TARGET PRODUCTION AS A FUNCTION OF
THE RATE OF FIRE IN THE SAMPLE HIGH INTENSITY SCENARIO

MANUAL SYSTEM (CT=6) IN A TACTICAL SITUATION

(NIGHTIME MBA)




FIGURE 25 RATE OF UNIQUE TARGET PRODUCTION AS A FUNCTION OF THE RATE OF FIRE IN THE SAMPLE MODERATE INTENSITY SCENARIO

AUTOMATIC SYSTEM (CT-12) IN A TACTICAL SITUATION




FIGURE 26 RATE OF UNIQUE TARGET PRODUCTION AS A FUNCTION OF THE RATE OF FIRE IN THE SAMPLE MODERATE INTENSITY SCENARIO

APPENDIX A
SREM USER'S GUIDE

Next page is blank.

APPENDIX A
THE SOUND RANGING EFFECTIVENESS MODEL (SREM)
USER'S GUIDE

SREM is designed to examine the loading problems a sound ranging system will experience in a given scenario. To do this, SREM receives as input both Red and Blue, direct and indirect firing missions and Close Air Support missions. Sound events are generated for each of these missions to account for the muzzle blast for artillery, and the impact sound event for artillery, direct fire and Close Air Support missions. These sound events are then time ordered based on the time they would reach the sound base and are then examined to see when the sound ranging system being modeled would be capable of making locations. SREM also keeps track of Red muzzle events so that when the sound system is capable of making locations, it counts the number of unique Red muzzle events which would be available to be located.

SREM requires the initialization of the sound base location, start and stop times, one parameter describing the saturation limit if the system being modeled, and one describing the resolution in terms of rate of fire you wish to have in the results. The initialization procedure and where to locate the required data statements are described in detail in this guide.

The Sound Ranging Effectiveness Model is presently configured to receive its inputs from DIVLEV, a two-sided division level wargame; DIVLEV generates an input file which is later read by SREM. In the event the user wishes to generate an input file, the format required for this file is included.

The sound ranging effectiveness model was written on a CDC 7600 computer and contains some coding peculiar to that system. The following are CDC unique and will have to be changed if the program is run on a different system.

1. The first line of the program is a program statement which declares how files are to be used.
2. Several large arrays are found in "LEVEL 2" statements, this places these arrays in an auxiliary portion of memory. These are large arrays and some provision may be required in order to handle them.

Required initialization inputs for SREM

- o Location of sound base to nearest 100 meters*

* The user should be careful to note if any special coordinate systems are being used to create the input. SREM assumes all coordinates are given to the nearest 100 meters.

ESNDBS = Easting
NSNDBS = Northing

3 Digit UTM coordinate
3 Digit UTM coordinate

- Starting time =

MASTIM - standard military time.

The starting time need not agree with the starting time of the input file. The program will step through the input file until a time equal to MASTIM is reached.

- Stop time =

MAXTIM - Standard military time.

If the simulated time step reaches this time before it reaches the end of file SREM treats it as an end of file.

- Critical threshold

CT = Maximum number of sound events occurring in a 6-second period during which all sound events in that window could be located. (Max = 18)

- Method of calculating Rate of Fire

SYS = 1, Rate of fire is calculated by the 5-minute average rate of fire immediately preceding the 6-second window in question.

= 2, Rate of fire is calculated by taking the number of muzzle events in the 6-second window and extrapolating it to 1 minute.

- Resolution of Summary output

ROF = Increment of rate of fire for summary outputs. (i.e.,

ROF=25 will display all outputs on rate of fire steps of 25.)

All the required inputs for initialization can be found in data statements in the main routine. The locations of the various data statements are in Table 1.

The input file must be unformatted records eight words per record. Records are read into array MISHUN one at a time. The records for indirect fire missions must follow the format found in Table 2, for a direct fire mission Table 3, and for a close air support mission Table 4.

TABLE 1
LOCATION OF DATA STATEMENTS FOR INITIALIZATION

- Sound Base location
 - Easting (ESNDBS) = line 30 main routine
 - Northing (NSNDBS) = line 31 main routine
- Starting time
 - MASTIM = line 32 main routine
- Stop time
 - MAXTIM = line 33 main routine
- Critical threshold
 - CT = line 34 main routine
- Method of calculating rate of fire
 - SYS = line 35 main routine
- Resolution of outputs
 - ROF = line 36 main routine

TABLE 2
SREM INPUT FILE (MISHUN (I), I = 1,8)

● Artillery Missions (indirect fire)

MISHUN (1) = Number of weapons in this battery.

MISHUN (2) = Time this artillery mission will begin.

MISHUN (3) = Easting coordinate of target to nearest 100 meters.

MISHUN (4) = Northing coordinate of target to nearest 100 meters.

MISHUN (5) = Duration of this mission.

MISHUN (6) = Easting coordinate of firing weapon to nearest 100 meters.

MISHUN (7) = Northing coordinate of firing weapon to nearest 100 meters.

MISHUN (8) = Coded number;

First 3 digits = unique 3 digit identifier for this battery.

Second 2 digits = resource number (See Table 5)

Last digit = force; 1 = Blue

2 = Red

TABLE 3

● Direct Fire Missions

MISHUN (1) = Number of rounds fired in this minute by this weapon.

MISHUN (2) = Time this direct fire mission began.

MISHUN (3) and MISHUN (4) = Zero (0)

MISHUN (5) = Duration of this firing mission (in minutes).

MISHUN (6) = Easting coordinate of weapon firing to nearest 100 meters.

MISHUN (7) = Northing coordinate of weapon firing to nearest 100 meters.

MISHUN (8) = Coded number (same as indirect fire).

TABLE 4

● Close Air Support Mission

MISHUN (1) = Coded number;

First digit = type of ordnance as follows:

BLUE	TYPE #	RED
CBU - 24	1	RBK - 500
Rockeye	2	RBK - 250
Maverick	3	500 LB Bomb

Last 2 digits = number of sticks of this type ordnance.

A stick is as follows:

CBU-24	}	8 each
Rockeye		
RBK-500		
RBK-250		

Maverick - 2 each
500 lb Bomb - 2 each

MISHUN (2) = Time this ordnance was delivered.

MISHUN (3) = Easting coordinate for this target to the nearest 100 meters.

MISHUN (4) = Northing coordinate for this target to the nearest 100 meters.

MISHUN (5) = One (1)

MISHUN (6) and MISHUN (7) = Zero (0)

MISHUN (8) = Coded number (same as direct fire).

TABLE 5

Resource	
Blue Weapon	Red Weapon
M60A3 Tank w/105mm gun	2 T72 tank w/125mm gun
	3 APC, BMP w/Sagger
Cobra/tow	5 HIND-A w/Sagger
Mortar, 81mm (M29A1)	6 Mortar, 120mm (m1938-43)
	9 BRDM w/Sagger
155mm Howitzer SP (M109A1)	11 122mm Howitzer (D-30)
8-inch Howitzer SP (M110E2)	12 152mm G/H (D-20)
175mm Gun SP (M107)	13 122mm MRL (BM-21)
M113A1 w/tow	20 Sagger, Manpack
Tow, Ground Mounted	21 122mm Howitzer, SP(M1974)
	22 152mm G/H, SP (M1973)
Mortar, 4.2-inch SP	28 130mm Gun (M-46)
	36 240mm MRL
Jet Aircraft, CAS	37 Jet Aircraft, CAS

Next page is blank.

APPENDIX B
SAMPLE RUN

APPENDIX B

SAMPLE RUN

A 10-minute simulation was set up for demonstration purposes. The initialization values used are in Table B-1. The input records used are in Table B-2. Figures B-1 through B-11 contain the minute by minute record available as an output of all the sound events. This output is described in detail on page of the main report. Figure B-12 is an output which provides the average number of Red muzzle events when the total number of sound events was 1,2,3, etc. Figures B-13 and B-14 are outputs which provide for each minute of the game the total number of potential targets and the total number of unique targets respectively.

Figure B-15 provides for each rate of fire band, what percentages of the total game time a sound ranging system would be capable of locating 0,1,2,3, ... etc. weapons. For example, the rate of fire was between 25 and 50 rounds per minute and it was possible to locate 2 Red muzzle events 14.44 percent of the total game time. Also, the rate of fire was between 25 and 50 rounds per minute and no Red muzzle events occurred during 22.5 percent of the total game time.

The "LOST" column indicates what percentage of the game time there were Red muzzle events but the threshold was exceeded and no locations could be made. The "TOT" column indicates what percentage of game time the rate of fire fell within that band.

Based on the previous outputs, it was determined what percentage of the time it was possible to locate 1,2,3, ... etc. Red muzzle events when the rate of fire was within a specific band.

For example, in Figure B-16 under the column marked "2" and in row marked "25 - 50" you will find the number 15.07. This indicates that 15.07 percent of the time that the rate of fire was within the 25 - 50 rounds per minute band, it was possible to locate 2 Red muzzle events.

Figure B-17 is a 5-minute moving average of the rate of fire by bands. Since this was a very short run, all the rates of fire fell within 25 - 50 rounds per minute.

SAMPLE INPUTS

Below are the inputs for the sample run.

ESNDBS = 460

NSNDBS = 230

The sound base is located at 460 east, 230 north, (SREM assumes 100 meter accuracy.)

MASTIM - 10430

The start time for this run will be day 1 at 0430. (SREM has a 1 minute time resolution.)

MAXTIM = 10441

The stop time for this run will be day 1 at 0441. (SREM stops when it reaches this time, any inputs with this time will be ignored.)

CT = 6

The system being modeled in this run has the capability of discerning targets when there are no more than 6 overlapping sound events in a six second window.

SYS = 1

For this output we wish to have the rates of fire calculated based on the 5 minutes immediately preceding the six second window.

ROF = 25

All the outputs for this run will be displayed in rate of fire steps of 25.

TABLE B-1

SEC	PIP # 10431	119	105-110	100-105	91-100	92-95	IN	D B	87-89	84-87	80-84	70-80	< 70
1		/	/	/	/	/	/	/	/	/	/	/	/
2		/	/	/	/	/	/	/	/	/	/	/	/
3		/	/	/	/	/	/	/	/	/	/	/	/
4		/	/	/	/	/	/	/	/	/	/	/	/
5		/	/	/	/	/	/	/	/	/	/	/	/
6	4	/	/	/	/	/	/	/	/	/	1/	3/	/
7	4	/	/	/	/	/	/	1/	/	/	2/	/	/
8		/	/	/	/	/	/	/	/	/	/	/	/
9		/	/	/	/	/	/	/	/	/	/	/	/
10	1	/	/	/	/	/	/	/	/	/	/	1/	/
11	2	/	/	/	/	/	/	/	/	/	2/	/	/
12		/	/	/	/	/	/	/	/	/	/	/	/
13		/	/	/	/	/	/	/	/	/	/	/	/
14		/	/	/	/	/	/	/	/	/	/	/	/
15		/	/	/	/	/	/	/	/	/	/	/	/
16		/	/	/	/	/	/	/	/	/	/	/	/
17		/	/	/	/	/	/	/	/	/	/	/	/
18		/	/	/	/	/	/	/	/	/	/	/	/
19		/	/	/	/	/	/	/	/	/	/	/	/
20		/	/	/	/	/	/	/	/	/	/	/	/
21		/	/	/	/	/	/	/	/	/	/	/	/
22		/	/	/	/	/	/	/	/	/	/	/	/
23		/	/	/	/	/	/	/	/	/	/	/	/
24		/	/	/	/	/	/	/	/	/	/	/	/
25		/	/	/	/	/	/	/	/	/	/	/	/
26		/	/	/	/	/	/	/	/	/	/	/	/
27		/	/	/	/	/	/	/	/	/	/	/	/
28		/	/	/	/	/	/	/	/	/	/	/	/
29		/	/	/	/	/	/	/	/	/	/	/	/
30		/	/	/	/	/	/	/	/	/	/	/	/
31		/	/	/	/	/	/	/	/	/	/	/	/
32		/	/	/	/	/	/	/	/	/	/	/	/
33		/	/	/	/	/	/	/	/	/	/	/	/
34		/	/	/	/	/	/	/	/	/	/	/	/
35		/	/	/	/	/	/	/	/	/	/	/	/
36		/	/	/	/	/	/	/	/	/	/	/	/
37	1	/	/	/	/	/	1/	1	2/	1	2/	1	2/
38	12	/	/	/	/	/	1/	1	1/	1	5/	2	1/
39	12	/	/	/	/	/	/	/	3/	2	8/	2	1/
40	4	/	/	/	/	/	/	/	/	/	1/	/	/
41		/	/	/	/	/	/	/	/	/	/	/	/
42		/	/	/	/	/	/	/	/	/	/	/	/
43		/	/	/	/	/	/	/	/	/	/	/	/
44		/	/	/	/	/	/	/	/	/	/	/	/
45		/	/	/	/	/	/	/	/	/	/	/	/
46		/	/	/	/	/	/	/	/	/	/	/	/
47		/	/	/	/	/	/	/	/	/	/	/	/
48		/	/	/	/	/	/	/	/	/	/	/	/
49		/	/	/	/	/	/	/	/	/	/	/	/
50		/	/	/	/	/	/	/	/	/	/	/	/
51	2	/	/	/	/	/	/	/	1/	/	1/	1	/
52		/	/	/	/	/	/	/	/	/	/	/	/
53		/	/	/	/	/	/	/	/	/	1/	1	/
54	1	/	/	/	/	/	/	/	/	/	1/	1	/
55	1	/	/	/	/	/	/	/	/	/	1/	1	/
56		/	/	/	/	/	/	/	/	/	/	/	/
57		/	/	/	/	/	/	/	/	/	/	/	/
58		/	/	/	/	/	/	/	/	/	/	/	/
59		/	/	/	/	/	/	/	/	/	/	/	/
60		/	/	/	/	/	/	/	/	/	/	/	/

FIGURE B-2

[illegible]

FIGURE B-3

FIGURE B-4

SEC	MP - 10434	TOT	> 110	100-110	100-100	65-100	92-95	89-92	87-89	84-87	90-84	70-80	< 70
1													
2													
3													
4							1/1						
5													
6							1/1						
7													
8													
9													
10													
11													
12													
13													
14													
15													
16													
17													
18													
19													
20													
21													
22													
23													
24													
25													
26													
27													
28													
29													
30													
31													
32													
33													
34													
35													
36													
37													
38													
39													
40													
41													
42													
43													
44													
45													
46													
47													
48													
49													
50													
51													
52													
53													
54													
55													
56													
57													
58													
59													
60													

FIGURE B-5

SEC	WPA 1042	100-110	100-100	95-100	92-95	89-92	87-89	84-87	80-84	70-80	< 70
1		/	/	/	/	/	/	/	/	/	/
2		/	/	/	/	/	/	/	/	/	/
3		/	/	/	/	/	/	/	/	/	/
4		/	/	/	/	/	/	/	/	/	/
5		/	/	/	/	/	/	/	/	/	/
6	2	/	/	/	/	/	/	/	/	/	/
7		/	/	/	/	/	/	/	/	/	/
8	2	/	/	/	/	/	/	/	/	/	/
9		/	/	/	/	/	/	/	/	/	/
10		/	/	/	/	/	/	/	/	/	/
11		/	/	/	/	/	/	/	/	/	/
12	5	/	/	/	/	/	/	/	/	/	/
13		/	/	/	/	/	/	/	/	/	/
14	6	/	/	/	/	/	/	/	/	/	/
15	1	/	/	/	/	/	/	/	/	/	/
16		/	/	/	/	/	/	/	/	/	/
17	2	/	/	/	/	/	/	/	/	/	/
18		/	/	/	/	/	/	/	/	/	/
19	2	/	/	/	/	/	/	/	/	/	/
20	1	/	/	/	/	/	/	/	/	/	/
21	1	/	/	/	/	/	/	/	/	/	/
22		/	/	/	/	/	/	/	/	/	/
23		/	/	/	/	/	/	/	/	/	/
24		/	/	/	/	/	/	/	/	/	/
25		/	/	/	/	/	/	/	/	/	/
26		/	/	/	/	/	/	/	/	/	/
27	3	/	/	/	/	/	/	/	/	/	/
28	1	/	/	/	/	/	/	/	/	/	/
29		/	/	/	/	/	/	/	/	/	/
30		/	/	/	/	/	/	/	/	/	/
31		/	/	/	/	/	/	/	/	/	/
32		/	/	/	/	/	/	/	/	/	/
33	4	/	/	/	/	/	/	/	/	/	/
34	1	/	/	/	/	/	/	/	/	/	/
35		/	/	/	/	/	/	/	/	/	/
36		/	/	/	/	/	/	/	/	/	/
37	2	/	/	/	/	/	/	/	/	/	/
38	2	/	/	/	/	/	/	/	/	/	/
39	2	/	/	/	/	/	/	/	/	/	/
40	3	/	/	/	/	/	/	/	/	/	/
41	2	/	/	/	/	/	/	/	/	/	/
42		/	/	/	/	/	/	/	/	/	/
43	1	/	/	/	/	/	/	/	/	/	/
44		/	/	/	/	/	/	/	/	/	/
45		/	/	/	/	/	/	/	/	/	/
46		/	/	/	/	/	/	/	/	/	/
47		/	/	/	/	/	/	/	/	/	/
48		/	/	/	/	/	/	/	/	/	/
49		/	/	/	/	/	/	/	/	/	/
50	1	/	/	/	/	/	/	/	/	/	/
51		/	/	/	/	/	/	/	/	/	/
52		/	/	/	/	/	/	/	/	/	/
53		/	/	/	/	/	/	/	/	/	/
54		/	/	/	/	/	/	/	/	/	/
55		/	/	/	/	/	/	/	/	/	/
56	3	/	/	/	/	/	/	/	/	/	/
57		/	/	/	/	/	/	/	/	/	/
58	2	/	/	/	/	/	/	/	/	/	/
59	2	/	/	/	/	/	/	/	/	/	/
60		/	/	/	/	/	/	/	/	/	/

FIGURE B-6

SFC	REP. 10-26	112	10-110	10-100	45-100	42-45	49-52	D. B.	67-69	84-87	80-84	70-80	< 70
1													
2													
3													
4													
5													
6													
7													
8													
9													
10													
11													
12													
13													
14													
15													
16													
17													
18													
19													
20													
21													
22													
23													
24													
25													
26													
27													
28													
29													
30													
31													
32													
33													
34													
35													
36													
37													
38													
39													
40													
41													
42													
43													
44													
45													
46													
47													
48													
49													
50													
51													
52													
53													
54													
55													
56													
57													
58													
59													
60													

FIGURE B-7

SIC	MIN - 11437	110	105-110	107-105	A M P L I T U D E	91-100	92-95	I N	U F	84-87	80-84	70-80	< 70
1	1	/	/	/	/	/	/	/	/	/	/	/	/
2	2	/	/	/	/	/	/	/	/	/	/	/	/
3	3	/	/	/	/	/	/	/	/	/	/	/	/
4	4	/	/	/	/	/	/	/	/	/	/	/	/
5	5	/	/	/	/	/	/	/	/	/	/	/	/
6	6	/	/	/	/	/	/	/	/	/	/	/	/
7	7	/	/	/	/	/	/	/	/	/	/	/	/
8	8	/	/	/	/	/	/	/	/	/	/	/	/
9	9	/	/	/	/	/	/	/	/	/	/	/	/
10	10	/	/	/	/	/	/	/	/	/	/	/	/
11	11	/	/	/	/	/	/	/	/	/	/	/	/
12	12	/	/	/	/	/	/	/	/	/	/	/	/
13	13	/	/	/	/	/	/	/	/	/	/	/	/
14	14	/	/	/	/	/	/	/	/	/	/	/	/
15	15	/	/	/	/	/	/	/	/	/	/	/	/
16	16	/	/	/	/	/	/	/	/	/	/	/	/
17	17	/	/	/	/	/	/	/	/	/	/	/	/
18	18	/	/	/	/	/	/	/	/	/	/	/	/
19	19	/	/	/	/	/	/	/	/	/	/	/	/
20	20	/	/	/	/	/	/	/	/	/	/	/	/
21	21	/	/	/	/	/	/	/	/	/	/	/	/
22	22	/	/	/	/	/	/	/	/	/	/	/	/
23	23	/	/	/	/	/	/	/	/	/	/	/	/
24	24	/	/	/	/	/	/	/	/	/	/	/	/
25	25	/	/	/	/	/	/	/	/	/	/	/	/
26	26	/	/	/	/	/	/	/	/	/	/	/	/
27	27	/	/	/	/	/	/	/	/	/	/	/	/
28	28	/	/	/	/	/	/	/	/	/	/	/	/
29	29	/	/	/	/	/	/	/	/	/	/	/	/
30	30	/	/	/	/	/	/	/	/	/	/	/	/
31	31	/	/	/	/	/	/	/	/	/	/	/	/
32	32	/	/	/	/	/	/	/	/	/	/	/	/
33	33	/	/	/	/	/	/	/	/	/	/	/	/
34	34	/	/	/	/	/	/	/	/	/	/	/	/
35	35	/	/	/	/	/	/	/	/	/	/	/	/
36	36	/	/	/	/	/	/	/	/	/	/	/	/
37	37	/	/	/	/	/	/	/	/	/	/	/	/
38	38	/	/	/	/	/	/	/	/	/	/	/	/
39	39	/	/	/	/	/	/	/	/	/	/	/	/
40	40	/	/	/	/	/	/	/	/	/	/	/	/
41	41	/	/	/	/	/	/	/	/	/	/	/	/
42	42	/	/	/	/	/	/	/	/	/	/	/	/
43	43	/	/	/	/	/	/	/	/	/	/	/	/
44	44	/	/	/	/	/	/	/	/	/	/	/	/
45	45	/	/	/	/	/	/	/	/	/	/	/	/
46	46	/	/	/	/	/	/	/	/	/	/	/	/
47	47	/	/	/	/	/	/	/	/	/	/	/	/
48	48	/	/	/	/	/	/	/	/	/	/	/	/
49	49	/	/	/	/	/	/	/	/	/	/	/	/
50	50	/	/	/	/	/	/	/	/	/	/	/	/
51	51	/	/	/	/	/	/	/	/	/	/	/	/
52	52	/	/	/	/	/	/	/	/	/	/	/	/
53	53	/	/	/	/	/	/	/	/	/	/	/	/
54	54	/	/	/	/	/	/	/	/	/	/	/	/
55	55	/	/	/	/	/	/	/	/	/	/	/	/
56	56	/	/	/	/	/	/	/	/	/	/	/	/
57	57	/	/	/	/	/	/	/	/	/	/	/	/
58	58	/	/	/	/	/	/	/	/	/	/	/	/
59	59	/	/	/	/	/	/	/	/	/	/	/	/
60	60	/	/	/	/	/	/	/	/	/	/	/	/

FIGURE B-8

SEC	MIN - 1043-	110	100-110	AMP 111 UDE	IN	DB	84-87	84-87	84-87	70-80	< 70
1	1	/	/	/	/	/	/	/	/	/	/
2	1	/	/	/	/	/	/	/	/	/	/
3	1	/	/	/	/	/	/	/	/	/	/
4	1	/	/	/	/	/	/	/	/	/	/
5	2	/	/	/	/	/	/	/	/	/	/
6	1	/	/	/	/	/	/	/	/	/	/
7	1	/	/	/	/	/	/	/	/	/	/
8	1	/	/	/	/	/	/	/	/	/	/
9	1	/	/	/	/	/	/	/	/	/	/
10	6	/	/	/	/	/	/	/	/	/	/
11	6	/	/	/	/	/	/	/	/	/	/
12	4	/	/	/	/	/	/	/	/	/	/
13	2	/	/	/	/	/	/	/	/	/	/
14	2	/	/	/	/	/	/	/	/	/	/
15	2	/	/	/	/	/	/	/	/	/	/
16	4	/	/	/	/	/	/	/	/	/	/
17	4	/	/	/	/	/	/	/	/	/	/
18	1	/	/	/	/	/	/	/	/	/	/
19	1	/	/	/	/	/	/	/	/	/	/
20	1	/	/	/	/	/	/	/	/	/	/
21	2	/	/	/	/	/	/	/	/	/	/
22		/	/	/	/	/	/	/	/	/	/
23		/	/	/	/	/	/	/	/	/	/
24		/	/	/	/	/	/	/	/	/	/
25		/	/	/	/	/	/	/	/	/	/
26	2	/	/	/	/	/	/	/	/	/	/
27	2	/	/	/	/	/	/	/	/	/	/
28		/	/	/	/	/	/	/	/	/	/
29		/	/	/	/	/	/	/	/	/	/
30	1	/	/	/	/	/	/	/	/	/	/
31	2	/	/	/	/	/	/	/	/	/	/
32		/	/	/	/	/	/	/	/	/	/
33		/	/	/	/	/	/	/	/	/	/
34		/	/	/	/	/	/	/	/	/	/
35		/	/	/	/	/	/	/	/	/	/
36	2	/	/	/	/	/	/	/	/	/	/
37		/	/	/	/	/	/	/	/	/	/
38		/	/	/	/	/	/	/	/	/	/
39		/	/	/	/	/	/	/	/	/	/
40		/	/	/	/	/	/	/	/	/	/
41	1	/	/	/	/	/	/	/	/	/	/
42	2	/	/	/	/	/	/	/	/	/	/
43	4	/	/	/	/	/	/	/	/	/	/
44		/	/	/	/	/	/	/	/	/	/
45		/	/	/	/	/	/	/	/	/	/
46		/	/	/	/	/	/	/	/	/	/
47		/	/	/	/	/	/	/	/	/	/
48		/	/	/	/	/	/	/	/	/	/
49		/	/	/	/	/	/	/	/	/	/
50		/	/	/	/	/	/	/	/	/	/
51		/	/	/	/	/	/	/	/	/	/
52		/	/	/	/	/	/	/	/	/	/
53		/	/	/	/	/	/	/	/	/	/
54		/	/	/	/	/	/	/	/	/	/
55		/	/	/	/	/	/	/	/	/	/
56	1	/	/	/	/	/	/	/	/	/	/
57	1	/	/	/	/	/	/	/	/	/	/
58		/	/	/	/	/	/	/	/	/	/
59		/	/	/	/	/	/	/	/	/	/
60		/	/	/	/	/	/	/	/	/	/

FIGURE B-9

SEC	MIP - 1940	100-110	100-105	A P P L I T U C E	I A	D R	84-97	80-84	70-80	< 70
1										/
2										/
3										/
4										/
5										/
6									1/1	/
7										/
8										/
9										/
10										/
11										/
12										/
13										/
14										/
15										/
16										/
17										/
18										/
19										/
20										/
21										/
22										/
23										/
24										/
25										/
26										/
27										/
28										/
29										/
30										/
31										/
32										/
33										/
34										/
35										/
36										/
37										/
38										/
39										/
40										/
41										/
42										/
43										/
44										/
45										/
46										/
47										/
48										/
49										/
50										/
51										/
52										/
53										/
54										/
55										/
56										/
57										/
58										/
59										/
60										/

FIGURE B-11

FIGURE B-12

TOT
EVENTS

RED
MUZZLES

0	0.00
1	.56
2	.55
3	.94
4	1.12
5	1.20
6	1.00
7	2.00
8	.67
9	4.00
10	4.00
11	0.00
12	6.00
13	6.00
14	0.00
15	0.00
16	0.00
17	0.00
18	0.00
19	0.00
20	0.00
21	0.00
22	0.00
23	0.00
24	0.00
25	0.00
26	0.00
27	0.00
28	0.00
29	0.00
30	0.00
31	0.00
32	0.00
33	0.00
34	0.00
35	0.00
36	0.00
37	0.00
38	0.00
39	0.00
40	0.00
41	0.00
42	0.00
43	0.00
44	0.00
45	0.00
46	0.00
47	0.00
48	0.00
49	0.00
50	0.00

51	0.00
52	0.00
53	0.00
54	0.00
55	0.00
56	0.00
57	0.00
58	0.00
59	0.00
60	0.00
61	0.00
62	0.00
63	0.00
64	0.00
65	0.00
66	0.00
67	0.00
68	0.00
69	0.00
70	0.00
71	0.00
72	0.00
73	0.00
74	0.00
75	0.00
76	0.00
77	0.00
78	0.00
79	0.00
80	0.00
81	0.00
82	0.00
83	0.00
84	0.00
85	0.00
86	0.00
87	0.00
88	0.00
89	0.00
90	0.00
91	0.00
92	0.00
93	0.00
94	0.00
95	0.00
96	0.00
97	0.00
98	0.00
99	0.00

MIN OF GAME	NO. OF TGTS
-------------------	-------------------

1	0
2	0
3	0
4	0
5	0
6	53
7	81
8	76
9	51
10	33
11	19

FIGURE B-13

MIN OF GAME	NO. OF UNIQUE TGTS
-------------------	-----------------------------

1	0
2	0
3	0
4	0
5	0
6	3
7	0
8	0
9	0
10	1
11	2

FIGURE B-14

TROF		0	1	2	3	4	5	6	LOST	TOT
0- 25		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
25- 50		22.50	18.89	14.44	8.33	2.22	0.00	0.00	20.44	95.83
50- 75		0.00	.28	2.50	0.00	0.00	0.00	0.00	0.00	4.17
75- 100		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100- 125		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125- 150		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150- 175		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175- 200		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
200- 225		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
225- 250		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
250- 275		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
275- 300		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
300- 325		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
325- 350		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
350- 375		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
375- 400		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
400- 425		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
425- 450		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
450- 475		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
475- 500		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
500- 525		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
525- 550		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
550- 575		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
575- 600		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
600- 625		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
625- 650		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
650- 675		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
675- 700		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
700- 725		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
725- 750		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
750- 775		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
775- 800		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
800- 825		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
825- 850		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
850- 875		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
875- 900		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
900- 925		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
925- 950		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
950- 975		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
975-1000		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1000-1025		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1025-1050		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1050-1075		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1075-1100		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1100-1125		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1125-1150		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1150-1175		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1175-1200		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1200-1225		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1225-1250		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1250-1275		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1275-1300		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1300-1325		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1325-1350		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1350-1375		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

FIGURE B-15

1375-1400	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1400-1425	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1425-1450	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1450-1475	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1475-1500	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1500-1525	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1525-1550	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1550-1575	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1575-1600	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1600-1625	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1625-1650	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1650-1675	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1675-1700	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1700-1725	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1725-1750	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1750-1775	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1775-1800	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1800-1825	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1825-1850	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1850-1875	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1875-1900	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1900-1925	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1925-1950	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1950-1975	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1975-2000	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
TOT =	100.0000								

FIGURE B-15

TROF		0	1	2	3	4	5	6	LOST	TOT
0- 25		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
25- 50	23.48	19.71	15.07	8.70	2.32	0.00	0.00	0.00	50.72	100.00
50- 75	0.00	6.67	0.00	0.00	0.00	0.00	0.00	0.00	33.33	100.00
75- 100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100- 125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125- 150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150- 175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175- 200	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
200- 225	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
225- 250	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
250- 275	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
275- 300	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
300- 325	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
325- 350	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
350- 375	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
375- 400	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
400- 425	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
425- 450	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
450- 475	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
475- 500	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
500- 525	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
525- 550	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
550- 575	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
575- 600	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
600- 625	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
625- 650	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
650- 675	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
675- 700	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
700- 725	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
725- 750	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
750- 775	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
775- 800	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
800- 825	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
825- 850	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
850- 875	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
875- 900	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
900- 925	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
925- 950	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
950- 975	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
975-1000	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1000-1025	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1025-1050	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1050-1075	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1075-1100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1100-1125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1125-1150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1150-1175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1175-1200	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1200-1225	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1225-1250	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1250-1275	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1275-1300	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1300-1325	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1325-1350	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

FIGURE B-16

1350-1375	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1375-1400	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1400-1425	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1425-1450	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1450-1475	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1475-1500	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1500-1525	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1525-1550	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1550-1575	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1575-1600	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1600-1625	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1625-1650	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1650-1675	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1675-1700	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1700-1725	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1725-1750	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1750-1775	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1775-1800	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1800-1825	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1825-1850	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1850-1875	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1875-1900	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1900-1925	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1925-1950	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1950-1975	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1975-2000	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

FIGURE B-16

FIGURE B-17

ROF		PRCNT OF GAME
0-	25	0.0000
25-	50	100.0000
50-	75	0.0000
75-	100	0.0000
100-	125	0.0000
125-	150	0.0000
150-	175	0.0000
175-	200	0.0000
200-	225	0.0000
225-	250	0.0000
250-	275	0.0000
275-	300	0.0000
300-	325	0.0000
325-	350	0.0000
350-	375	0.0000
375-	400	0.0000
400-	425	0.0000
425-	450	0.0000
450-	475	0.0000
475-	500	0.0000
500-	525	0.0000
525-	550	0.0000
550-	575	0.0000
575-	600	0.0000
600-	625	0.0000
625-	650	0.0000

APPENDIX C

PROGRAM LISTING

Next page is blank.

```

PROGRAM SKEM(INPUT,OUTPUT,TAPE5=INPUT,TAPE6=OUTPUT,DEBUG=OUTPUT)
IMPLICIT INTEGER (A-Z)
REAL R
COMMON/BLK1/MISHUN(60)/BLK2/ESNDBS,NSNDBS/BLK7/NC/BLK9/MASTIM
COMMON / BLK12/CT,SYS,RDF
DIMENSION AKTIL(9)
DATA ESNDFS/2240/
*      ,NSNDBS/2230/
*      ,MASTIM/10437/
*      ,MASTIM/10441/
*      ,CT      / 6/
*      ,SYS     /11/
*      ,RDF     /25/

C
C   TYP = 1 - 155MM HOWITZER-----21
C           = 2 - 8 INCH -----22
C           = 3 - 81MM MORTAR -----23
C           = 4 - 4.2 INCH MORTAR-----24
C           = 5 - 120MM MORTAR -----25
C           = 6 - 122MM HOWITZER -----26
C           = 7 - 152MM G/H -----27
C           = 8 - 122 MRL -----28
C           = 9 - 130MM GUN -----29
C           = 10 - T72-125MM -----30
C           = 11 - SAGGER -----31
C           = 12 - 240MM MRL -----32
C           = 13 - M60A3 W/105MM -----33
C           = 14 - TOW -----34
C           = 15 - 175 MM GUN -----35
C           = 16 - CAS MISSION-----36
C
C   NC=1
C   ICALL = 1
C   CALL NRAN31(RAND,Z,NC)
C
C   READ IN SOUND BASE LOCATION
C
C   100 FORMAT(2I3,I5)
C   ICNT=1
C
C   READ IN ARTILLERY MISSION
C
C   200 READ(5) (MISHUN(I),I = 1,8)
C   IF(EOF(5))1100,250
C   250 CONTINUE
C   IF(MISHUN(2) .LT. MASTIM) GO TO 200
C   IF(MISHUN(1) .EQ. 0) GO TO 200
C   CALL TYPE(MISHUN,ITYPE,IFORCE,IPFS)
C   IF(ITYPE .EQ. 0) GO TO 200
C   CALL UNIQID
C   110 CONTINUE
C
C   IF THIS IS THE FIRST MISSION SKIP COMPARISON
C   A=1
C   IF(ICNT .EQ. 1) GO TO 300
C
C   COMPARE THIS TIME TO LAST MISSION

```

```

C      IF(MISHUN(2) .EQ. MASTIM ) GO TO 300
      GO TO 350
300    CALL FIRETM(A)
      ICNT=ICNT+1
      DO 310 L=1,8
310    ARTIL(L) = MISHUN(L)
      GO TO 200

C
C      STORE THIS MISSION
C
350    DO 355 I = 1,8
355    ARTIL(I)=MISHUN(I)
      A=2
      CALL FIRETM(A)
      MASTIM = MASTIM+1
      IB = MASTIM/100.
      TM = MASTIM - (IB * 100)
      IF(TM .NE. 59) GO TO 356
      MASTIM = MASTIM + 41
356    CONTINUE
      GO TO 790

C
C      GET FINETIMES FOR STORED MISSION
C
358    DO 360 I = 1,8
360    MISHUN(I)=ARTIL(I)
      GO TO 110
790    CONTINUE
      CALL RDRDF(MASTIM)
      CALL OUTSUP(MASTIM,ICALL)
      ICALL = ICALL + 1
      CALL PRINT (MASTIM)
      B = MASTIM
      R = B/100.
      IB = B
      TM = MASTIM - (IB * 100)
      IF(TM .NE. 59) GO TO 795
      MASTIM = MASTIM + 40
795    CONTINUE
      MASTIM = MASTIM+1
      IF(MASTIM .EQ. MAXTIM) GO TO 1100
1000   GO TO 350
1100   CONTINUE
      MASTIM = 999
      CALL RDRDF(MASTIM)
      CALL OUTSUP(MASTIM,ICALL)
      STOP
      END

```

SYMBOLIC REFERENCE MAP (R=2)

```

SUBROUTINE FIRETM(K)
IMPLICIT INTEGER (A-Z)
REAL RNG

```

```

C*****
C
C   THIS SUBROUTINE COMPUTES AND STORES IN AN ARRAY
C   THE FIRETIMES FOR EACH GUN IN A BATTERY.
C   IF A BATTERY WILL FIRE FOR MORE THAN ONE MINUTE
C   THIS ROUTINE STORES THAT MISSION FOR THE NEXT
C   MINUTE, ALONG WITH THE FIRST FIRING TIME IN
C   THAT MINUTE
C   K = 1 - ARTIL MISSION
C   K = 2 - END OF MINUTE, PROCESS MISSIONS FROM LAST MINUTE
C   FOR STORE(J,K,L)
C   J = 1 - OLD ARTIL MISSION
C   J = 2 - NEW ART MISSION
C
C   COMMON / BLK1/MISHUN(60)
C   *       / BLK4/NMISS
C   *       / BLK6/RNG
C   *       / BLK2/ESNDBS,NSNDBS
C   *       / BLK9/MASTIM
C   DIMENSION STORE(2,60,300)
C
C   SET PARAMETERS AND CALL RANGE TO COMPUTE THE
C   RANGE FROM THE ARTILERY AND THE SOUND BASE.
C*****
C
C   X=ESNDBS
C   Y=NSNDBS
C   A=MISHUN(6)
C   R=MISHUN(7)
C   CALL RANGE(X,Y,A,B)
C   IF(K.EQ.2.) GO TO 250
C
C   CALL BATTFIRE TO GET FIRING TIME FOR EACH
C   GUN IN A BATTERY. SET NMISS=1 FOR NEW MISSION
C
C   JJ = MISHUN(1)
C   IF(MISHUN(3).EQ.0) JJ = 1
C   DO 200 J= 1,JJ
C   NMISS=1
C   CALL BATTFR
C   MISHUN(9+J)= MISHUN(9)
200  CONTINUE
C
C   IF MISSION WILL LAST MORE THAN 1 MINUTE
C   STORE IT AND INCREMENT COUNTER TO TEL
C   YOU HOW MANY MISSIONS HAVE BEEN STORED
C
C   IF(MISHUN(5) .EQ. 1) GO TO 230
C   MISHUN(5) = MISHUN(5)+ 1
C   NCNT=NCNT+1
C   DO 225 J = 1,60
C   L = 2

```

```

225 STORE(L,J,NCNT) = MISHUN(J)
230 CONTINUE
    RETURN
250 DCNT = ARTIL
    IF(DCNT .EQ. 0) GO TO 425
C
C   RECALL MISSIONS WHICH BEGAN FIRING IN THE
C   LAST MIN AND LASTED LONGER THAN 1 MINUTE
C
    K = 1
    DO 420 M=1,DCNT
        DO 310 I = 1,60
            MISHUN(I) = STORE(K,I,M)
310 STORE(K,I,M) = 0
            IF (MISHUN(1) .EQ. 0 ) GO TO 425
C
C   COMPUTE RANGE AND CALL BATTFIRE FOR FIRE TIMES
C
    A=MISHUN(6)
    B=MISHUN(7)
    CALL RANGE (X,Y,A,B)
    JJ = MISHUN(1)
    IF(MISHUN(3).EQ. 0) JJ = 1
    DO 320 J=1,JJ
C
C   SET NMISS=2 FOR A MISSION WHICH IS CONTINUED
C   FROM LAST MIN
C
    NMISS=2
    MISHUN(9) = MISHUN(9+J)
    CALL BATTFR
    MISHUN (9+J) = MISHUN(9)
320 CONTINUE
C
C   IF MISSION WILL LAST MORE THAN 1 MINUTE
C   STORE IT AND KEEP COUNT HOW MANY YOU HAVE STORED
C
    IF (MISHUN(5) .EQ. 1) GO TO 410
    MISHUN(5) = MISHUN(5)-1
    NCNT=NCNT + 1
    L = 2
    DO 400 J=1,60
400 STORE(L,J,NCNT) = MISHUN(J)
410 CONTINUE
420 CONTINUE
425 CONTINUE
    IF( NCNT .EQ. 0) GO TO 460
    L = 2
    DO 450 I= 1,NCNT
    DO 450 J= 1,60
        STORE(1,J,I) = STORE(2,J,I)
        STORE(2,J,I) = 0
450 CONTINUE
460 CONTINUE
    ARTIL = NCNT
    NCNT=0
    RETURN

```

SUBROUTINE BATTFR

```

C
C*****
C
C    THIS SUBROUTINE COMPUTES THE FIRING TIMES FOR
C    EACH GUN OR TANK, IT CALLS RATE TO COMPUTE
C    RATE OF FIRE, IT CALLS IMPACT FOR IMPACT TIMES,
C    AND IT CALLS ARRAY TO STORE THE SCUD EVENTS.
C    NMISS = 1 MEANS THIS IS A NEW MISSION
C    NMISS = 2 MEANS THIS MISSION IS CONTINUED FROM
C             A PREVIOUS MINUTE
C*****
C
C    INTEGER TYP,TIMLFT,FT,FTT,TIMEO
C    COMMON / BLK1/MISHUN(60)
C    *      / BLK4/NMISS
C    *      / BLK5/TYP,IAMP
C    *      / BLK6/PNG
C
C    PICM = FRACTION OF ICM
C
C    DATA PICM/.333/
C    CALL TYPE(MISHUN,ITYPE,IFORCE,IRES)
C    IF(NMISS .EQ.1) GO TO 500
C
C    GET LAST FIRING TIME FOR THIS GUN
C
C    ICNT = 0
C    FT = MISHUN(9)
C    MAXTIM = 60
C    GO TO 600
500  CALL RATE(RCF)
C    TIMEO = .1*RCF
C    FT = TIMEO
C    IF(ITYPE .EQ. 8) TIMEO = 1
C    IF(ITYPE .EQ. 12) TIMEO = 1
C    MAXTIM = 60
C    GO TO 600
C
C    GET RATE OF FIRE FOR THIS GUN
C
C    550  CALL RATE(RCF)
C    IF(ITYPE .EQ. 12) GO TO 560
C    IF(ITYPE .NE. 8) GO TO 590
C    560  CONTINUE
C    ICNT = ICNT + 1
C    IF(ICNT .EQ. 17 .AND. ITYPE .EQ. 12) GO TO 570
C    IF(ICNT .NE. 41) GO TO 590
C    570  CONTINUE
C    FT = 60
C    TIMLFT = 0
C    GO TO 830
C    590  FT = TIMEO + RCF
C    600  TIMLFT = MAXTIM - FT
C    IF(TIMLFT .LE. 0) GO TO 800
C

```

```

C      CALCULATE THE TIME FOR THE SOUND TO
C      REACH THE SOUND BASE
C
      IRNG=(RNG/.338)
      FTT = FT+ IRNG
      TYP = ITYPE
      IF(FTT .EQ. 0) FTT = 1
      KEY=1

C
C      COMPUTE WHAT BAND OF AMPLITUDE THIS
C      SOUND EVENT IS IN
C
      MISH = ITYPE
      CALL AMPL(MISH,RNG,IAMP)
      CONTINUE

C
C      STORE THIS SOUND EVENT IN MASTER ARRAY
C
      CALL ARRAY(FTT,TYP,IAMP)
      CONTINUE

C
C      CALL IMPACT TO DETERMINE IMPACT TIMES
C
      CALL TGTARY(FTT)
      IF(KANF(Z) .GT. PICM .AND.
*  ITYPE .LE. 2) GO TO 750
      IF(ITYPE .EQ. 3) GO TO 750
      IF(ITYPE .EQ. 10) GO TO 750
      IF(ITYPE .EQ. 11) GO TO 750
      IF(ITYPE .EQ. 13) GO TO 750
      IF(ITYPE .EQ. 14) GO TO 750
      IF(ITYPE .EQ. 16) GO TO 750
      CALL IMPACT(MISHUN,FT)
750  CONTINUE
      TIMEO = 60-TIMLFT
      GO TO 550
800  MISHUN(9)=FT-60
      RETURN
      END

```

```

SUBROUTINE ARRAY(SEC,TYP,IAMP)
IMPLICIT INTEGER (A-Z)
COMMON /BLKR/SOUND(240,40,11)
LEVEL 2,SOUND
C THIS SUBROUTINE STORES SOUND EVENTS IN A
C 3 DIMENSIONAL ARRAY ACCORDING TO THE FOLLOWING
C ARFAY(SEC,TYP,AMP)
C
C INTEGER SEC,TYP
C SEC = TIME OF SOUND EVENT (1-240)
C TYP = TYPE OF WEAPON OR IMPACT (1-18)
C AMP = RANGE OF AMPLITUDE (1-11)
C
C MUZZLE                      IMPACT
C EVENT                      EVENT
C
C TYP = 1 - 155MM HOWITZER-----21
C       2 - 8 INCH -----22
C       3 - 81MM MORTAR -----23
C       4 - 4.2 INCH MORTAR-----24
C       5 - 120MM MORTAR -----25
C       6 - 122MM HOWITZER -----26
C       7 - 152MM G/H -----27
C       8 - 122 MRL -----28
C       9 - 130MM GUN -----29
C      10 - T72-125MM -----30
C      11 - SAGGER -----31
C      12 - 240MM MRL -----32
C      13 - M60A3 W/105MM -----33
C      14 - TOW -----34
C      15 - 175 MM GUN -----35
C      16 - CAS MISSION-----36
C
C SEC = SEC + 1
C SOUND(SEC,TYP,IAMP) = SOUND(SEC,TYP,IAMP) + 1
C RETURN
C END

```

```

SUBROUTINE IMPACT(MISHUN,FT)
IMPLICIT INTEGER (A-Z)
REAL RNG
C
C THIS SUBROUTINE COMPUTES THE TIME THE IMPACT
C SOUND WILL REACH THE SOUND BASE.
C
  DIMENSION MISHUN(60)
  COMMON/BLK2/ESNDBS,NSNDRS/
1BLK4/NMISS/BLK5/TYP,IAMP/BLK6/RNG
C
C GET RANGE FROM GUN TO TARGET
C
  X=MISHUN(6)
  Y=MISHUN(7)
  A=MISHUN(3)
  B=MISHUN(4)
  CALL RANGE(X,Y,A,B)
  IF(MISHUN(3) .EQ. 0) RNG = .5
C
C COMPUTE FLIGHT TIMES
C
  FLGT = 4. * RNG
C
C COMPUTE TARGET RANGE FROM THE SOUND BASE
C
  IF(MISHUN(3) .NE. 0) GO TO 100
  A = MISHUN(6)
  B = MISHUN(7)
100 CONTINUE
  X = ESNDBS
  Y = NSNDRS
  CALL RANGE(X,Y,A,B)
  SBRNG = RNG/.336
C
C SET KEY FOR COMPUTING AMPLITUDE OF IMPACT
C FROM THIS GUN
C
  KEY = 2
  CALL TYPE(MISHUN,ITYPE,IFORCE,IRES)
  TYP = ITYPE + 20
  CALL AMPL(TYP,RNG,IAMP)
  SE = SBRNG + FLGT + FT
  IF (SE .GE. 240) SE = 240
C
C STORE THIS SOUND EVENT IN THE MASTER ARRAY
C
  CALL AARRAY(SE,TYP,IAMP)
600 CONTINUE
  RETURN
  END

```

```
SUBROUTINE RANGE(X,Y,A,B)
INTEGER A,B,X,Y
COMMON/BLK6/RNG
```

C
C
C
C

```
THIS SUBROUTINE CALCULATES THE RANGE BETWEEN
THE TWO COORDINATES GIVEN BY XY AND AB
```

```
C=((X-A)**2+(Y-B)**2)
RNG = SQRT(C)/10.
RETURN
END
```

```

SUBROUTINE RATE(ROF)
C
C THIS SUBROUTINE COMPUTES A RATE OF FIRE
C FOR INDIVIDUAL SHOTS. THE SUSTAINED RATES
C OF FIRE ARE IN ARRAY RAOF
C
COMMON/BLK1/MISHUN(60)/BLK7/NC
COMMON /BLK9/MASTIM
C
RAOF(I) I=1--155MM
      =2--RINCH
      =3--81MM MOPTAR
      =4--4.2 INCH MOPTAR
      =5--120MM
      =6--122MM
      =7--152MM G/H
      =8--MRL
      =9--130MM GUN
      =10-T72-125MM
      =11-SAGGER
      =12-240 MRL
      =13-M60A3 W/105MM
      =14-TOW
      =15-175 MM GUN
      =16-CAS MISSION
C
DIMENSION RAOF(20)
      DIMENSION NBOM(2,10)
DATA RAOF/ 1.0, .5, 8., 3., 3., 1., 1., 40., 1., 0.0,
*          0.0, 16., 0., 0.0, 0.5, 0., 0.0, 0.0, 0.5, 0.0/
DATA (NBOM(1,J),J=1,10)/
*      8, 8, 1, 0, 0, 0, 0, 0, 0, 0/
DATA (NBOM(2,J),J=1,10)/
*      8, 8, 2, 0, 0, 0, 0, 0, 0, 0/
CALL TYPE(MISHUN,ITYPE,IFORCE,IRES)
I = ITYPE
IF(MISHUN(3).EQ. 0) GO TO 200
      IF(MISHUN(6) .EQ. 0) GO TO 300
IF(RAOF(I) .NE. 0.0) GO TO 100
ROF = 0.0
RETURN
100 CONTINUE
RTE=(1./RAOF(I))*60.
SIGMA=.1*RTE
CALL NRAN31(RAND,Z,NQ)
ROF=RTE + RAND * SIGMA
MIN =.33 * RTE
IF(ROF .LE. MIN) ROF = MIN
IF(I .EQ. 8) ROF = 1.5
RETURN
200 CONTINUE
RTE = MISHUN(1)
RTE = RTE/100. + .5
ROF = (1./RTE) * 60.
RETURN
300 CONTINUE

```

C
C
C

THIS IS A CAS MISSION THE RATE WILL BE THE NUMBER
OF BOMBS DROPPED

```
LDS = MISHUN(1) - ((MISHUN(1)/100)*100)
  NTYPE = MISHUN(1)/100
  RTE = NBOM(IFORCE,NTYPE) * LDS
IF(IFORCE .EQ. 1 .AND. NTYPE. .EQ. 3) RTE = RTE/30.
  ROF = (1./RTE) * 60.
IF(NTYPE .EQ. 3 .AND.
*   IFORCE .EQ. 1 .AND.
*   MISHUN(5) .EQ. 1 .AND.
*   MASTIM .EQ. MISHUN(2)) MISHUN(5) = 30
  RETURN
END
```

```

SUBROUTINE AMPL (MISH,RNG,IAMP)
*****
C
C   IN THIS SUBROUTINE THE AMPLITUDE OF EACH SOUND
C   IS CALCULATED IN DB (REF .0002 UBARs).
C   THE INITIAL AMPLITUDE IS CALCULATED USING EQUIVALENT
C   BARE TNT CHARGES , THESE CHARGES ARE EQUIVALENT
C   COMPUTATIONALLY AT THE ONE THIRD POWER.
C   ARRAY TNT CONTAINS THE EQUIVALENT CHARGES FOR
C   3 DIFFERENT FIRING CHARGES FOR EACH RANGE BEING
C   FIRED. THE CHARGE USED FOR EACH SHOT IS DETERMINED
C   BY A RANDOM NUMBER DRAW FOR THE THREE AVAILABLE
C   FIRING CHARGES. CHARGES IN BOTH TNT AND HE ARE ALREADY
C   TO THE ONE THIRD POWER
C   IF THIS EVENT IS AN IMPACT THEN THE EQUIVALENT
C   CHARGE IS OBTAINED FROM ARRAY HE
C
C   AFTER CALCULATING THE AMPLITUDE OF THE SOUND EVENT
C   IT IS PLACED IN AN AMPLITUDE BIN AS FOLLOWS.
C
C       AMPL      AMPL
C       IN        BIN
C       DB
C   > 110        1
C   105-110      2
C   100-105      3
C   95-100       4
C   92-95        5
C   89-92        6
C   87-89        7
C   84-87        8
C   80-84        9
C   70-80       10
C   < 70        11
C
C   A= AMPL IN UBARs
C   RNG=  RANGE IN KM
C
C   TNT(I,J,K)
C       I = TYPE OF GUN (1-20)
C       J = RANGE (1-30)
C       K = FIRING CHARGE (1-3)
C
C   HE(I)
C       I = TYPE OF GUN WHICH
C           FIRED THIS ROUND
C
C       I= TYPE OF GUN
C       1 = 155MM
C       2 = 8 INCH
C       3 = 81MM MORTAR
C       4 = 4.2 INCH MORTAR
C       5 = 120MM
C       6 = 122MM
C       7 = 152MM G/H
C       8 = MRL
C       9 = 130MM GUN
C      10 = T72 - 125MM
C      11 = SAGGER
C      12 = 240 MRL
C      13 = M60A3 W/105MM
C      14 = TOW
C      15 = 175MM GUN
C      16 = REDEYE
*****

```

C

```

DIMENSION TNT(20,30,3),
*      HE(40)
*      ,CASBM(2,10)
COMMON /BLK1/MISHUN(60)
COMMON /BLK7/NQ
DATA (TNT(1,K,1),K=1,30)/
* 1.46, 1.46, 1.59, 1.90, 2.13, 25*2.36/
DATA (TNT(1,K,2),K=1,30)/
* 3*1.46, 1.59, 1.90, 7*2.13, 18*2.36/
DATA (TNT(1,K,3),K=1,30)/
* 4*1.46, 1.59, 4*1.90, 3*2.13, 18*2.36/
DATA (TNT(2,K,1),K=1,30)/
* 1.63, 1.87, 2.34, 2.50, 2.81, 2.81, 24*3.04/
DATA (TNT(2,K,2),K=1,30)/
* 1.63, 1.63, 2.34, 2.34, 2.50, 2.50, 8*2.81, 16*3.04/
DATA (TNT(2,K,3),K=1,30)/
* 1.63, 1.63, 1.87, 1.87, 2*2.34, 5*2.50, 3*2.81, 16*3.04/
DATA (TNT(3,K,1),K=1,30)/
* .555, 29*.617/
DATA (TNT(3,K,2),K=1,30)/
* .524, 3*.555, 26*.617/
DATA (TNT(3,K,3),K=1,30)/
* .524, 3*.555, 26*.617/
DATA (TNT(4,K,1),K=1,30)/
* .745, .763, .763, .839, 26*.927/
DATA (TNT(4,K,2),K=1,30)/
* .745, .745, .763, .839, .921, 25*.927/
DATA (TNT(4,K,3),K=1,30)/
* 3*.745, .839, .921, 25*.927/
DATA (TNT(5,K,1),K=1,30)/
* .355, .427, .479, .530, 26*.618/
DATA (TNT(5,K,2),K=1,30)/
* .427, .479, .530, .575, 26*.618/
DATA (TNT(5,K,3),K=1,30)/
* .479, .530, .575, 27*.618/
DATA (TNT(6,K,1),K=1,30)/
* 2*.538, 1.37, 1.67, 2.02, 2*2.34, 23*2.82/
DATA (TNT(6,K,2),K=1,30)/
* 3*.538, 1.37, 1.67, 2*2.02, 5*2.34, 18*2.82/
DATA (TNT(6,K,3),K=1,30)/
* 4*.538, 1.37, 2*1.67, 4*2.02, 2.34, 18*2.82/
DATA (TNT(7,K,1),K=1,30)/
* 2*1.46, 1.68, 1.90, 2.28, 2.50, 2.56, 23*2.63/
DATA (TNT(7,K,2),K=1,30)/
* 3*1.46, 1.68, 1.90, 2.28, 2.50, 8*2.56, 15*2.63/
DATA (TNT(7,K,3),K=1,30)/
* 4*1.46, 1.68, 1.90, 2.28, 8*2.50, 2.56, 14*2.63/
DATA (TNT(8,K,1),K=1,30)/
* 30*1.37/
DATA (TNT(8,K,2),K=1,30)/
* 30*1.37/
DATA (TNT(8,K,3),K=1,30)/
* 30*1.37/
DATA (TNT(9,K,1),K=1,30)/
* 7*.298, 6*2.75, 17*3.08/
DATA (TNT(9,K,2),K=1,30)/

```

```

*      7*.298, 2*.353, 4*.415, 9*2.75, 8*3.08/
DATA (TNT(9,K,3),K=1,30)/
*      9*.298, 4*.353, 6*.415, 3*2.75, 8*3.08/
DATA (TNT(10,K,1),K=1,30)/
*      30*2.50/
DATA (TNT(10,K,2),K=1,30)/
*      30*2.50/
DATA (TNT(10,K,3),K=1,30)/
*      30*2.50/
DATA (TNT(11,K,1),K=1,30)/
1      30*1.825/
DATA (TNT(11,K,2),K=1,30)/
1      30*1.825/
DATA (TNT(11,K,3),K=1,30)/
1      30*1.825/
DATA (TNT(12,K,1),K=1,30)/
*      30*1.56/
DATA (TNT(12,K,2),K=1,30)/
*      30*1.56/
DATA (TNT(12,K,3),K=1,30)/
*      30*1.56/
DATA (TNT(13,K,1),K=1,30)/
*      30*2.29/
DATA (TNT(13,K,2),K=1,30)/
*      30*2.29/
DATA (TNT(13,K,3),K=1,30)/
*      30*2.29/
DATA (TNT(14,K,1),K=1,30)/
1      30*1.825/
DATA (TNT(14,K,2),K=1,30)/
1      30*1.825/
DATA (TNT(14,K,3),K=1,30)/
1      30*1.825/
DATA (TNT(15,K,1),K=1,30)/
*      12*2.90, 6*3.43, 12*3.95/
DATA (TNT(15,K,2),K=1,30)/
*      18*3.43, 12*3.95/
DATA (TNT(15,K,3),K=1,30)/
*      30*3.95/
DATA (HE(I),I=1,20)/
*      2.605, 3.311, 1.341, 1.983, 1.726,
*      2.089, 1.934, 2.089, 2.089, 0.0,
*      0.0, 2.089, 0.0, 0.0, 3.288,
*      0.0, 0.0, 0.0, 0.0, 0.0/
DATA (CASBM(1,J),J=1,10)/
*      4.54,4.10,3.50, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0/
DATA (CASBM(2,J),J=1,10)/
*      4.54,4.10,5.76, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0/
IF(MISH .GT.20) GO TO 500

C
C
C
SELECT THE CHARGE TO BE USED FOR THIS SHOT

B = RANF(Z)
K = 2
IF( B .LE. .33) K = 1
IF( P .GE. .67) K = 3
J = RNG + .5

```

```

      IF ( J .LE. 1) J = 1
      IF ( J .GE. 30) J = 30
      I = MISH
      BANG = TNT(I,J,K)
      GO TO 600

C
C      IF THIS IS AN IMPACT EVENT GET THE EXPLOSIVE
C      CHARGE WEIGHT.
C
500      INDEX = MISH -20
      CALL TYPE(MISHUN,ITYPE,IFORCE,IRES)
      IF(ITYPE .NE. 16) GO TO 550
      ICRD = MISHUN(5)/100
      BANG = CASBM(IFORCE,ICRD)
      GO TO 600
550      CONTINUE
      BANG = HE(INDEX)
600      CONTINUE

C
C      CALCULATE THE AMPLITUDE OF THE SOUND IN PSI
C
      R = RNG * 3280.84
      IF(R .NE. 0.) GO TO 700
      WRITE(6,900) MISH,RNG,IAMP
900      FORMAT(1X,I4,F10.4,I4,/)
700      CONTINUE
      PSI = 210. * ((BANG/R)**1.407)

C
C      NOW CONVERT TO UBARS AND THEN TO DB
C
      PUBAR = PSI * 1000000. / 14.5

C
      DB = 20. * ALOG10(PUBAR / .0002)
      DB = DB - 10
      CALL NRAN31(RAND,Z,RNG)
      DB = DB + ( 8.0 * RAND)

C      SELECT THE RANGE BIN FOR THIS AMPLITUDE
      IDB = DB
      IF(ITYPE .GE. 5 .OR.
      * ITYPE.LE.9) CALL AVG(IDB,ICALL)
      IF (DB .GE. 110.) IAMP = 1
      IF (DB .LT. 110.) IAMP = 2
      IF (DB .LT. 105.) IAMP = 3
      IF (DB .LT. 100.) IAMP = 4
      IF (DB .LT. 95.) IAMP = 5
      IF (DB .LT. 92.) IAMP = 6
      IF (DB .LT. 89.) IAMP = 7
      IF (DB .LT. 87.) IAMP = 8
      IF (DB .LT. 84.) IAMP = 9
      IF (DB .LT. 80.) IAMP = 10
      IF (DB .LT. 70.) IAMP = 11
      RETURN
      END

```

```

SUBROUTINE AVG(IAMP,ICALL)
IF(ICALL .EQ. 999) GO TO 500
ITOT = ITOT + IAMP
ICNT = ICNT + 1
RETURN
500 CONTINUE
IAVG = ITOT/ICNT
WRITE(6,900) IAVG
900 FORMAT(1H1,//////////20X,112,1H1)
RETURN
END

```

SUBROUTINE PRINT(MASTIM)

```

C
C*****
C
C      SOUND(SEC,TYP,AMP)
C
C      SEC = TIME OF SOUND EVENT (1-240)
C      TYP = TYPE OF WEAPON OR IMPACT (1-40)
C      AMP = RANGE OF AMPLITUDE (1-11)
C
C      MUZZLE                      IMPACT
C      EVENT                      EVENT
C
C      TYP = 1 - 155MM HOWITZER-----21
C             2 - 8 INCH -----22
C             3 - 81MM MORTAR -----23
C             4 - 4.2 INCH MORTAR-----24
C             5 - 120MM MORTAR -----25
C             6 - 122MM HOWITZER -----26
C             7 - 152MM G/H -----27
C             8 - 122 MRL -----28
C             9 - 130MM GUN -----29
C            10 - T72-125MM -----30
C            11 - SAGGER -----31
C            12 - 240MM MRL -----32
C            13 - M60A3 W/105MM -----33
C            14 - TOW -----34
C            15 - 175 MM GUN -----35
C            16 - CAS MISSION-----36
C
C*****
C

```

```

      IMPLICIT INTEGER (A-Z)
      COMMON/BLK8/SOUNC(240,40,11)
      COMMON / BLK11/IDARAY(240,300)
      LEVEL 2,IDARAY
      LEVEL 2,SOUND
      DIMENSION BLANK(100)
      INTEGER AMP(12,12)
      DATA BLANK/' ', '1', '2', '3', '4', '5', '6', '7', '8', '9', '10',
1'11', '12', '13', '14', '15', '16', '17', '18', '19', '20',
*'21', '22', '23', '24', '25', '26', '27', '28', '29', '30',
*'31', '32', '33', '34', '35', '36', '37', '38', '39', '40',
*'41', '42', '43', '44', '45', '46', '47', '48', '49', '50',
*'51', '52', '53', '54', '55', '56', '57', '58', '59', '60',
*'61', '62', '63', '64', '65', '66', '67', '68', '69', '70',
*'71', '72', '73', '74', '75', '76', '77', '78', '79', '80',
*'81', '82', '83', '84', '85', '86', '87', '88', '89', '90',
*'91', '92', '93', '94', '95', '96', '97', '98', '99'/'

```

```

      THIS SUBROUTINE WILL PRINT OUT THE SOUND
      EVENTS AND UPDATE THE ARRAY

```

```

      AMP(12)=0
      WRITE(6,910) MASTIM
75 CONTINUE

```

```

      DD 200 N=1,60
      DC 400 J=1,11
      DD 400 K = 1,40
      AMP(1,J) = AMP(1,J) + SOUND(N,K,J)
      IF( K . LT. 5 ) GO TO 390
      IF( K .GT. 9 ) GO TO 390
      AMP(2,J) = AMP(2,J) + SOUND(N,K,J)
390  CONTINUE
400  CONTINUE
      DD 500 J=1,10
500  AMP(1,12) = AMP(1,12) + AMP(1,J)
      WRITE(6,900) N,BLANK(AMP(1,12)+1),((BLANK(AMP(I,J)+1),I=1,2),
      *J=1,11)
502  CONTINUE
C
C      ZERO FILL ARRAY AMP
C
      DD 510 M = 1,2
      DC 510 J = 1,12
510  AMP(M,J) = 0
200  CONTINUE
900  FORMAT(2X,12,6X,A2,7X,11(A2,'/',A2,3X))
C
C      MOVE ALL THE SOUND EVENTS DOWN ONE MINUTE IN ARRAY SOUND
C
      DD 1000 N = 1,180
      DD 1000 K = 1,40
      DD 1000 J=1,11
      NN= N+60
      SOUND(N,K,J) = SOUND(NN,K,J)
1000 CONTINUE
      DD 1500 N = 181,240
      DD 1500 K = 1,40
      DD 1500 J = 1,11
      SOUND(N,K,J) = 0
1500 CONTINUE
      DD 2000 N = 1,180
      NN = N + 60
      DD 2000 K = 1,300
      IDARAY(N,K) = IDARAY(NN,K)
2000 CONTINUE
      DD 3000 I = 61,240
      DD 3000 J = 1,300
      IDARAY(I,J) = 0
3000 CONTINUE
      RETURN
910  FORMAT(1H1,8X,'MIN = ',I5,
      *20X,'A M P L I T U D E      I N      C R ',/
      *1X,'SEC',8X,'TOT', 6X,'> 110  105-110 100-105  95-100  92-95  89
      *92  87-89  84-87  80-84  70-80  < 70',/)
      END

```

AD-A112 366

ARMY MATERIEL SYSTEMS ANALYSIS ACTIVITY ABERDEEN PROV--ETC F/G 17/1
SOUND RANGING EFFECTIVENESS MODEL (SREM). (U)

DEC 81 W J HUGHES, H C DUBIN


UNCLASSIFIED

AMSAA-TR-333

NL

2-2
2-2
2-2





```

SUBROUTINE RORCF (MASTIM)
IMPLICIT INTEGER (A-Z)
REAL ROF,CUMROF(100),NUMRED(100)
COMMON /BLK8/SOUND(240,40,11)
LEVEL 2,SOUND

```

```

C
C*****
C
C      THIS SUBROUTINE EXTRACTS FROM ARRAY SOUND THE
C      CUMULATIVE RATE OF FIRE ( THE INDEX FOR CUMROF(I)).
C      IT THEN STORES IN THAT LOCATION THE RED RATE OF FIRE.
C
C      TOT = CUMULATIVE RATE OF FIRE + IMPACTS
C      RED = CUMULATIVE RATE OF RED MUZZLE EVENTS
C*****
C
      IF (MASTIM .EQ. 999) GO TO 700
      TOT=0
      DO 500 N=1,60
      DO 400 J=1,11
      DO 300 K = 1,40
      TOT=TOT+SOUND(N,K,J)
      IF(K .GT. 9) GO TO 300
      IF(K .LT. 5) GO TO 300
      RED=RED+SOUND(N,K,J)
300  CONTINUE
400  CONTINUE
      IF(TOT .GE. 99) TOT = 99
      CUMROF(TOT+1) = CUMROF(TOT+1) + RED
      NUMRED(TOT+1) = NUMRED(TOT+1)+1
      RED = 0
      TOT = 0
500  CONTINUE
      RETURN
700  CONTINUE
      WRITE(6,900)
      DO 800 I = 1,100
      IF(NUMRED(I) .NE. 0.) GO TO 750
      ROF = 0.
      GO TO 760
750  CONTINUE
      ROF = CUMROF(I)/NUMRED(I)
760  CONTINUE
      II =I-1
      WRITE (6,910) II,ROF
800  CONTINUE
900  FORMAT(1H1,10X,'TOT',7X,'RED',/9X'EVENTS  MUZZLES'//)
910  FORMAT (10X,I2,7X,F6.2)
      RETURN
      END

```

```

      SUBROUTINE EVENTS (ROF5,MASTIM, ICALL,ROF)
      IMPLICIT INTEGER (A-Z)
      REAL PRCNT
      COMMON /BLK8/SOUND(240,40,11)
      LEVEL 2,SOUND
      DIMENSION SEC(300)
      C   SEC(I) I = 1-100
      C   STORED IS THE NUMBER OF SECS DURING WHICH
      C   THE EVENTS PER SECOND = I
      IF(MASTIM.EQ. 999) GO TO 700
      ICNT = ICNT + 1
      TOT = (ROF5 * .2) / ROF
      SEC(TOT+1) = SEC(TOT + 1) + 1
      RETURN
700  CONTINUE
      WRITE(6,905)
905  FORMAT(1H1)
      WRITE(6,910)
      ICALL = ICALL - 10
      DO 800 I = 1,100
      PRCNT = (SEC(I)*100.)/(ICNT + 1.0)
      II = I*ROF
      JJ = (I*ROF)-ROF
      WRITE (6,900) JJ,II,PRCNT
800  CONTINUE
900  FORMAT (16X,16,'-',I6,10X,F6.4/)
910  FORMAT (40X,'PRCNT',/21X,'ROF',18X,'OF',/40X,'GAME',/)
      RETURN
      END

```

```

C      SUBROUTINE OUTSUM(MASTIM,ICALL)
C
C      IMPLICIT INTEGER (A-Z)
C
C      COMMON / BLK8/SOUND(240,40,11)
C      COMMON /BLK12/CT,SYS,ROF
C      LEVEL 2,SOUND
C
C      REAL PRCNT
C      *      ,ROF1
C      *      ,LINTOT
C      *      ,FACTOR
C      *      ,JACK(80)
C      *      ,ROF3(80)
C      *      ,OUTSM2(20)
C      *      ,OUTSM1(20,20)
C
C      DIMENSION  ALPH(20)
C      *      ,FMT1(5)
C      *      ,FMT2(7)
C      *      ,SUM1(6)
C      *      ,ROF5F(300)
C      *      ,RUNTOT(500)
C      *      ,ROM5(300)
C      *      ,DIST(6,3,11)
C
C      DATA  FMT1  /'1X,I4,'
C      *      , '1H-,I4,'
C      *      , '
C      *      , 'F6.2,'
C      *      , 'F8.2)'
C      *      /
C
C      DATA  FMT2  /'2X,4HTROF'
C      *      , '8X,'
C      *      , '
C      *      , 'A6,4HLOST,'
C      *      , '2X,'
C      *      , '3HTOT'
C      *      , '//'
C      *      /
C
C      DATA  DASH  /'6H  ---,/'
C
C      DATA  BLANK  /'
C      *      /
C
C      DATA  NMBR  /'F6.2,'
C      *      /
C
C      DATA  NMBR2 /'F8.2,'
C      *      /
C
C      DATA  ALPH  /'1','2','3','4','5',
C      *      , '6','7','8','9','10',
C      *      , '11','12','13','14','15',
C      *      , '16','17','18','19','20'
C      *      /
C
C      DATA  ALPH1 /'0'/

```

```

C *****
C
C THIS SUBROUTINE CALCULATES THE RATE OF FIRE OVER A FIVE MINUTE
C PERIOD (ROF5) AND THEN CONSIDERS ALL SOUND EVENTS IN THE
C NEXT SIX SECOND PERIOD
C   CT = CRITICAL THRESHOLD
C       THIS IS THE NUMBER OF EVENTS THAT MAY OCCUR IN A SIX SECOND
C WINDOW AND STILL BE DISTINGUISHABLE
C
C SUM1(I) I=1,6 = NO. OF MUZZLE EVENTS PER SEC(I)
C               IN THE SIX SECOND WINDOW
C ROM5(I) I=1,300 TOTAL MUZZLE EVENTS IN SEC I OF 5 MIN WINDOW
C
C ROF5F(I) I=1,300 TOTAL NO. OF SOUND EVENTS IN SECOND I OF
C               THE 5 MIN WINDOW
C ROF5 = TOTAL NO. OF SOUND EVENTS IN 5 MIN WINDOW
C
C ROM = TOTAL NO. OF MUZZLE EVENTS IN 5 MIN WINDOW
C
C IRDF = COUNTER FOR SECOND OF 5 MIN WINDOW
C
C IDIST = COUNTER FOR SECOND OF 6 SEC WINDOW
C
C THRESH = TOTAL NO. OF SOUND EVENTS IN 6 SEC WINDOW
C
C REDSUM = TOTAL RED MUZZLES IN 6 SEC WINDOW
C
C MUZSUM = TOTAL MUZZLE EVENTS IN 6 SEC WINDOW
C ROFBIN = RATE OF FIRE BIN BASED ON
C           1 RATE OF FIRE FOR 5 MIN
C           2 RATE OF FIRE FOR 6 SEC
C
C ROF3(I) = NO. OF TIMES RATE OF FIRE = (I * ROF)
C
C RINTOT(I) I =1,500 TOT NO. OF DETECTABLE RED MUZZLE EVENTS
C FOR MIN I OF GAME
C
C REDSUM = NUMBER OF RED MUZZLE EVENTS
C GLTSM1(I,J,K)
C   I = 1,80 RATE OF FIRE BINS IN INCREMENTS OF ROF
C   ROF = INCREMENTS FOR I
C   J = NUMBER OF RED MUZZLE EVENTS
C
C STORED IS THE NUMBER OF TIMES CONDITIONS I,J ARE MET.
C
C DIST(I,J,K) THIS IS THE SIX SECOND WINDOW UNDER CONSIDERATION
C   I = 1,6 SECOND
C   J = 1,2 1 = ALL SOUND EVENTS
C           2 = RED MUZZLE EVENTS
C   K = 1,11 AMPLITUDE BINS
C *****
C
C THE FOLLOWING ARE INPLTS FOR THIS SUBROUTINE
C ROF = INCREMENT FOR GLTSM1
C

```

```

C      CT = CRITICAL THRESHOLD (MAX = 18)
C      ISYS = TYPE OF SYSTEM REPORTING
C           1 - AUTOMATED
C           2 - MANUAL
C
C*****
C
C      IF THIS IS THE END OF INPUT GO TO PRINTOUT
C
C      IF(MASTIM .EQ. 999) GO TO 500
C      IF(ICALL .GT. 5) GO TO 190
C
C      UP TO STATEMENT 190 IS ONLY TO INITIATE THE FIRST FIVE MINUTES
C      DURING WHICH WE WILL CONSIDER THE RATE OF FIRE
C*****
C
50  CONTINUE
      ICNT = ICNT + 1
      DO 120 I = 1,60
        DO 110 J = 1,40
          DO 100 K = 1,11
            II = 60 * (ICALL - 1) + I
            ROF5F(II) = ROF5F(II) + SOUND(I,J,K)
            IF(J .GE. 21) GO TO 90
            ROM5(II) = ROM5(II) + SOUND(I,J,K)
          90  CONTINUE
        100  CONTINUE
      110  CONTINUE
    120  CONTINUE
      IF(ICALL .NE. 5) GO TO 180
      DO 160 I = 1,6
        DO 150 K = 1,11
          DO 140 J = 1,40
            DIST(I,1,K) = DIST(I,1,K) + SOUND((54+I),J,K)
            IF(J .LT. 5 .OR.
              *      J .GT. 9 .AND.
              *      J .NE. 12) GO TO 130
            DIST(I,2,K) = DIST(I,2,K) + SOUND((54+I),J,K)
          130  CONTINUE
        140  CONTINUE
      150  CONTINUE
    160  CONTINUE
C
      IROF = 1
      IOIST = 1
      ROF5 = 0
      ROM = 0
      DO 170 I = 1,300
        POM = POM + ROM5(I)
        ROF5 = ROF5 + ROF5F(I)
      170  CONTINUE
    180  CONTINUE
      RETURN
    190  CONTINUE
C

```

```

C*****
C
C      THE 5 MINUTE INITIALIZATION IS OVER CONTINUE.
C
C*****
C
C      SUBTRACT THE RATE OF EVENTS FOR THE LAST SECOND
C      FROM ROF5 AND SUBTRACT THE RATE OF FIRE FROM
C      ROM FOR THE LAST SECOND
C
DO 380 TIM = 1,60
  OLDROF = ROF5/ROF
  ROF5 = ROF5 - ROF5F(IROF)
  TEMROF = C
  TEMROM = 0
  ROM = ROM - ROM5(IROF)

C
C      REMOVE THE OLDEST SECOND FROM DIST(I,J,K) AND
C      REPLACE IT WITH THE NEXT SECOND FROM SOUND(I,J,K)
C
DO 210 I = 1,11
  DO 200 J = 1,3
    DIST(IDIST,J,I) = 0
  CONTINUE
200 CONTINUE
210 SUM1(IDIST) = 0
  DO 270 K = 1,11
    DO 260 J = 1,40

C
C      TOTAL EVENTS FOR 1 SEC
C      TEMPOF = TEMROF + SOUND(TIM,J,K)
C      IF(J .GE. 21) GO TO 230

C
C      TOTAL MUZ EVENTS FOR 1 SEC
C      TEMROM = TEMROM + SOUND(TIM,J,K)
230 CONTINUE

C
C      TOTAL EVENTS / SEC / AMP
C      DIST(IDIST,1,K) = DIST(IDIST,1,K) + SOUND(TIM,J,K)
C      IF(J .GE.21) GO TO 250

C
C      TOT MUZ EVENTS / SEC
C      SUM1(IDIST) = SUM1(IDIST) + SOUND(TIM,J,K)
C      IF(J .LT. 5 .OR.
*      J .GT. 9 .AND.
*      J .NE. 12) GO TO 240

C
C      RED MUZ EVENTS / SEC / AMP
C      DIST(IDIST,2,K) = DIST(IDIST,2,K)
*      + SOUND(TIM,J,K)

C
C      RED MUZ EVENTS / SEC / AMP
C      DIST(IDIST,3,K) = DIST(IDIST,3,K)
*      + SOUND(TIM,J,K)
240 CONTINUE
250 CONTINUE
260 CONTINUE

```

```

270      CONTINUE
C
C      ROF5 = TOTAL EVENTS CVER 5 MIN PERIOD
C      ROM  = TOTAL MUZZLE EVENTS OVER 5 MIN PERIOD
C
C      ADD THE RATE OF FIRE FOR THE NEWEST SECOND
C
C      ROF5 = ROF5 + TEMROF
C      PDF5F(IROF) = TEMROF
C      ROM  = ROM + TEMROM
C      ROM5(IROF) = TEMROM
C      IROF = IROF + 1
C
C      IF THIS IS THE END OF A 5 MIN PERIOD, SUBROUTINE
C      EVENTS WILL RECIEVE THE PRESENT 5MIN TOTAL EVENTS
C
C      IF(IROF .NE. 300) GO TO 280
C      CALL EVENTS (ROM,MASTIM,ICALL,RCF)
C      IROF = 1
280      CONTINUE
C      NEWRCF = ROF5/ROF
C
C      IF THE PATE OF SOUND EVENTS HAS CHANGED CONSIDER
C      ALL TARGETS IN THE SIX SECOND WINDOW
C
C      IF(OLOPDF .EQ. NEWROF) GO TO 310
C      DO 300 I = 1,11
C      DO 290 J = 1,6
C      DIST(J,3,I) = DIST(J,2,I)
290      CONTINUE
300      CONTINUE
310      CONTINUE
C      IDIST = IDIST + 1
C      IF(IDIST .GT. 6) ICIST = 1
C      REDSUM = 0
C      JAKSM  = 0
C      THRESH = 0
C
C      ADD UP ALL SOUND EVENTS IN 6 SEC WINDOW
C
C      DO 330 SEC = 1,6
C      DO 320 AMP = 1,10
C      THRESH = THRESH + DIST(SEC,1,AMP)
320      CONTINUE
330      CONTINUE
C
C      IF THE THRESHOLD HAS NOT BEEN EXCEEDED ADD UP ALL
C      THE RED MUZZLE EVENTS IN THAT WINDOW
C      REDSUM = CT + 1
C      IF(THRESH .GT. CT) GO TO 360
C      REDSUM = 0
C      DO 350 SEC = 1,6
C      DO 340 AMP = 1,10
C      REDSUM = REDSUM + DIST(SEC,2,AMP)
C      JAKSM = JAKSM + DIST(SEC,3,AMP)
C      DIST(SEC,3,APP) = 0
340      CONTINUE

```

```

350          CONTINUE
          NTOT = NTOT + REDSUM
C
C          CALL OTSUM2 TO SEE IF ANY OF THESE TARGETS
C          ARE UNIQUE
C
          CALL OTSUM2(TIM,ICNT)
360        CONTINUE
C
C          CALCULATE THE RATE OF FIRE BIN THAT THESE EVENTS
C          GO TO
C          ROFBN1 WILL CONTAIN THE RATE OF MUZZLE EVENTS
C          AVERAGED OVER THE 5 MIN WINDOW
C          ROFBN2 WILL CONTAIN THE RATE OF MUZZLE EVENTS
C          IN THE 6 SECOND WINDOW EXTRAPOLATED
C          TO 1 MIN
C
          ROFBN1 = ((RCM/5)/RCF) + 1
          MUZSUM = 0
          DO 370 M1 = 1,6
            MUZSUM = MUZSUM + SUM1(M1)
370        CONTINUE
          ROFBN2 = (MUZSUM * 10 / PCF) + 1
C
          IF(SYS .EQ. 1) ROFBIN = ROFBN1
          IF(SYS .EQ. 2) ROFBIN = ROFBN2
C
          IF(ROFBIN .GE. 80) RCFBIN = 60
C
C          STORE IN OUTSM1 HOW OFTEN YOU WERE ABLE TO DETECT
C          THIS MANY RED MUZZLES AT THIS RATE OF FIRE
C
          OUTSM1(ROFBIN,(REDSUM+1)) = OUTSM1(ROFBIN,REDSUM+1) + 1
          JACK(ROFBIN) = JACK(ROFBIN) + JAKSM
          ROF3(ROFBIN) = ROF3(ROFBIN) + 1
380      CONTINUE
          ICNT = ICNT + 1
          CALL OTSUM2(TIM,ICNT)
          RNTOT(ICNT) = NTOT
          NTOT = 0
          ITOT = 0
          RETURN
C
C *****
C
C          THE END OF THE INPUT HAS BEEN REACHED
C          THIS IS THE BEGINING OF ALL THE SUMMARY PRINTOUTS
C *****
C
500      CONTINUE
          CALL OTSUM2(TIM,ICNT)
          WRITE(6,900)
          WRITE(6,960)
          DO 510 I = 1,ICNT
            WRITE(6,950) I

```

```

      *                               , RUNTOT(1)
510  CONTINUE
      II = CT + 2
      FACTOR = (ICALL - 6) * (60./100.)
C
C      NOW CALCULATE THE PERCENT OF GAME TIME
C      CONDITIONS (X,Y) WERE MET IN OUTSM1(X,Y)
C
      DO 530 I = 1,80
        DO 520 J = 1,II
          OUTSM1(I,J) = OUTSM1(I,J) / FACTOR
520  CONTINUE
530  CONTINUE
      WRITE(6,900)
      WRITE(6,940)
      IMAX = CT
      FMT2(3) = ALPH(CT+1)
      WRITE(6,FMT2) ALPH1,(ALPH(JX),JX=1,IMAX)
      DO 550 R = 1,80
        DO 540 M = 1,II
          LINTOT = LINTOT + CUTSM1(R,M)
540  CONTINUE
          FMT1(3) = ALPH(II)
          N1 = (P * ROF) - ROF
          N2 = (K * ROF)
          WRITE(6,FMT1)
            *                               N1
            *                               ,N2
            *                               ,(CUTSM1(R,I),I=1,II)
            *                               ,LINTOT
          LINTOT = 0.
550  CONTINUE
      DO 570 I = 1,80
        DO 560 J = 1,II
          PRCNT = PRCNT + OUTSM1(I,J)
560  CONTINUE
570  CONTINUE
      WRITE(6,920) PRCNT
      WRITE(6,930)
      WRITE(6,940)
C
      WRITE(6,FMT2)
      *                               ALPH1
      *                               ,(ALPH(JX),JX = 1,IMAX)
      N1 = 0
      N2 = 0
      DO 620 I = 1,80
        ROF1 = OUTSM1(I,1)
        DO 580 J = 2,II
          ROF1 = ROF1 + OUTSM1(I,J)
580  CONTINUE
C
C      OUTSM2 WILL CONTAIN THE NORMALIZED DISTRIBUTION
C      FOR ROF = 1* 50
C
      DO 600 J = 1,II
        OUTSM2(J) = C

```



```

      *          /)
C 940  FORMAT(T4+
      *          , 'R E D   M U Z Z L E   E V E N T S'
      *          , /)
C 950  FORMAT(T11
      *          , I3
      *          , T17
      *          , I4
      *          , /)
C 960  FORMAT(T10
      *          , 'MIN      NO.' /
      *          , T10
      *          , 'OF      OF' /
      *          , T10
      *          , 'GAME ' /
      *          , T16
      *          , 'TGTS' //
      *          )
C
      RETURN
      END

```

```

SUBROUTINE GTSUM2(TIM,ICNT)
INTEGER TIM
COMMON / BLK9/MASTIM
*      / BLK11/IDARAY(240,300)
*      / BLK10/IDTGT(1000,4)
LEVEL 2, IDARAY
DIMENSION IUNEK(500)
*      ,ITEM(6,300)
IF(MASTIM.EQ. 999) GO TO 500C
IF(ICNT.EQ. 0) ICNT = 1
ITIM = TIM - 6
IF( ICNT.NE. NCNT) GO TO 1000
100 IF (TIM.LT. 6) GO TO 3000
C
C CHECK THE SIX SECOND WINDOW
C
DO 500 I = 1,6
C
C CHECK EACH UNIQUE TARGET
C
DO 400 J = 1,300
IF(IDARAY(ITIM+I,J).EQ. 0) GO TO 450
DO 300 K = 1,500
C
C IDTGT CONTAINS A LIST OF UNIQUE TARGETS AND WHETHER
C THEY HAVE BEEN LOCATED
C
IF(IDARAY(ITIM+I,J).NE. IDTGT(K,1)) GO TO 250
IF (IDTGT(K,2).NE. 0) GO TO 350
ITOT = ITOT + 1
IDTGT(K,2) = 1
IDTGT(K,4) = MASTIM
GO TO 350
250 CONTINUE
300 CONTINUE
350 CONTINUE
400 CONTINUE
450 CONTINUE
500 CONTINUE
RETURN
1000 CONTINUE
IUNEK(ICNT) = ITOT
ITOT = 0
C
C STORE THE LAST SIX SECONDS OF THIS MINUTE IN CASE
C TIM IS LESS THAN SIX ON THE NEXT CALL
C
DO 1100 I = 1,6
DO 1100 J = 1,300
1100 ITEM(I,J) = IDARAY(54+I,J)
NCNT = ICNT
RETURN
3000 CONTINUE
DO 4000 I = 1,TIM
DO 4000 J = 1,300
ITEM(I,J) = IDARAY(I,J)
4000 CONTINUE

```

C
C
C

SINCE TIM IS LESS THAN SIX ITEM WILL CONTAIN THE SIX SECOND WIN

```
DO 4500 I = 1,6
DO 4400 J = 1,300
IF(ITEM(I,J) .EQ. 0) GO TO 4450
DO 4300 K = 1,500
IF(ITEM(I,J) .NE. IDTGT(K,1)) GO TO 4250
IF(IDTGT(K,2) .NE. 0) GO TO 4350
ITOT = ITOT +1
IDTGT(K,2) = 1
IDTGT(K,4) = MASTIM
GO TO 4350
4250 CONTINUE
4300 CONTINUE
4350 CONTINUE
4400 CONTINUE
4450 CONTINUE
4500 CONTINUE
RETURN
5000 CONTINUE
WRITE(6,9105)
9105 FORMAT(1H1)
WRITE(6,9100)
DO 6000 I = 1,ICNT
6000 WRITE (6,9000) I, ILNEEK(I)
9000 FORMAT(10X,13,3X,14/)
9100 FORMAT(9X,'MIN NO. '//
19X,'OF OF'//
29X,'GAME UNIQUE'//
315X,'TGTS'//)
END
```

```

SUBROUTINE UNIQID
IMPLICIT INTEGER (A-Z)
COMMON / BLK1/MISHUN(60)
*      / BLK10/IDTGT(1000,4)

C
C      IDTGT(I,J) WILL CONTAIN A LIST OF UNIQUE
C      TARGETS (RED MUZZLE EVE
C      IF J=1 THEN THIS TARGET HAS BEEN LOCATED.
C

CALL TYPE(MISHUN,ITYPE,IFORCE,IRES)
IF(IFORCE .EQ. 1) GO TO 1400
IF(MISHUN(3) .EQ. 0) GO TO 1300
IUNIQ = IRES * 100000000 + MISHUN(6) * 10000 + MISHUN(7)
1000  CONTINUE
      I = I + 1
      IF(IDTGT(I,1) .NE. 0) GO TO 1200
      IDTGT(I,1) = IUNIQ
      IDTGT(I,3) = MISHUN(2)
1200  CONTINUE
      IF(IDTGT(I,1) .NE. IUNIQ) GO TO 1000
1300  CONTINUE
1400  CONTINUE
      RETURN
END

```

```

SUBROUTINE TGTARY(FTT)
COMMON / BLK1/MISHUN(60)
*      / BLK11/IDARAY(240,300)
LEVEL 2, IDARAY
INTEGER FTT

C
C      IDARAY CONTAINS A LIST OF TIMES SOUND EVENTS
C      REACHED THE SOUND BASE (1-240)
C      AND THE UNIQUE IDENTIFIER (1-300)
C

CALL TYPE(MISHUN, ITYPE, IFORCE, IRES)
I = 0
IUNEK = IRES * 100000000 + MISHUN(6) * 10000 + MISHUN(7)
IF(ITYPE .LT. 5) GO TO 1300
IF(ITYPE .GT. 12 .AND. ITYPE .NE. 15) GO TO 1200
1000   CONTINUE
      I = I + 1
      IF(IDARAY(FTT, I) .NE. 0) GO TO 1100
      IDARAY(FTT, I) = IUNEK
1100   CONTINUE
      IF(IDARAY(FTT, I) .NE. IUNEK) GO TO 1000
1200   CONTINUE
1300   CONTINUE
END

```

```

SUBROUTINE TYPE(MISHUN, ITYPE, IFORCE, IRES)
DIMENSION MISHUN(60)
DIMENSION NTYPE(2,40)

```

```

      ARRAY NTYPE(I,J) CONTAINS ALL THE WPN TYPES

```

```

      I= 1,2  FORCE NO.
      J= 1,40  RESOURCE NO.

```

```

      DATA (NTYPE(1,J),J=1,40)/

```

```

*      0, 13, 0, 0, 14, 3, 0, 0, 0, 0,
*      1, 2, 15, 0, 0, 0, 0, 0, 0, 14,
*      14, 0, 0, 0, 0, 0, 0, 4, 0, 0,
*      0, 0, 0, 0, 0, 0, 16, 0, 0, 0/

```

```

      DATA (NTYPE(2,J),J=1,40)/

```

```

*      0, 10, 11, 0, 11, 5, 0, 0, 11, 0,
*      6, 7, 8, 0, 0, 0, 0, 0, 0, 11,
*      6, 7, 0, 0, 0, 0, 0, 9, 0, 0,
*      0, 0, 0, 0, 0, 12, 16, 0, 0, 0/

```

```

      MISHUN(8) IS UNIT ID * 1000 + RESOURCE * 10 + FORCE

```

```

      IFORCE = MISHUN(8) - ((MISHUN(8)/10) * 10)

```

```

      IRES = (MISHUN(8) - ((MISHUN(8)/1000) * 1000))/10

```

```

      ID = MISHUN(8)/1000

```

```

      ITYPE = NTYPE(IFORCE, IRES)

```

```

      RETURN

```

```

      END

```

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commandant US Army Field Artillery School ATTN: ATSF-CD-R (Mr. Farmer) ATSF-CF-R Fort Sill, OK 73503	1	Commandant Naval Surface Weapons Center Code G65 Dahlgren, VA 22448
1	Commander/Director US Army Combat Surveillance & Target Acquisition Laboratory ATTN: DELCS-D Fort Monmouth, NJ 07703	1	Project Manager, FIREFINDER/REMBASS ATTN: DRCPM-FF-R Fort Monmouth, NJ 07703
1	Commander Atmospheric Sciences Lab ATTN: W. Miller White Sands Missile Range NM 88002	1	Commander US Army Intelligence Center & School ATTN: ATSI-CD-MD Fort Huachuca, AZ 85613
1	Commander US Army Materiel Development & Readiness Command ATTN: DRCPA-P 5001 Eisenhower Avenue Alexandria, VA 22333	12	Commander Defense Technical Information ATTN: TCA Cameron Station Alexandria, VA 22333
1	Commander US Army Concepts Analysis Agency 8120 Woodmont Avenue Bethesda, MD 20014	2	Chief Defense Logistics Studies Information Exchange US Army Logistics Manage- ment Center ATTN: DRSMC-D Fort Lee, VA 23801
2	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL ATAA-T White Sands Missile Range NM 88002	1	Reliability Analysis Center ATTN: Mr. I. L. Krulac Griffiss AFB, NY 13441

DISTRIBUTION LIST (continued)

Aberdeen Proving Ground

- 1 Director, BRL, Bldg 328
- 2 Cdr, USATECOM
ATTN: DRSTE
DRSTE-CS-A
Bldg 314
- 1 Dir, BRL
ATTN: DRDAR-TSB-S (STINFO BRANCH)
Bldg 305
- 1 Dir, HEL, Bldg 520

