

MEMORANDUM REPORT ARBRL-MR-03160

(Supersedes IMR No. 705)

EFFECT OF GUN TUBE EVACUATION ON FREE
FIELD BLAST PRESSURES AND
COMPARISON WITH
PROPOSED MODELS

TECHNICAL
LIBRARY

Raymond E. Gordnier

March 1982



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR- 03160	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) EFFECT OF GUN TUBE EVACUATION ON FREE FIELD BLAST PRESSURES AND COMPARISON WITH PROPOSED MODELS		5. TYPE OF REPORT & PERIOD COVERED Final
7. AUTHOR(s) Raymond E. Gordnier		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Ballistic Research Laboratory (ATTN: DRDAR-BLL) Aberdeen Proving Ground, MD 21005		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory (DRDAR-BL) Aberdeen Proving Ground, MD. 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS RDT&E 1L161102AH43
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE March 1982
		13. NUMBER OF PAGES 33
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES This report supersedes Interim Memorandum Report No. 705 dated March 1981.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Muzzle Blast Shock Waves Aerodynamic Interactions Unsteady Flow		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) (ner) Since excessive muzzle blast overpressures are adversely affecting artillery crew safety and performance, there is interest in developing a detailed understanding of the blast from guns, so that accurate computations may be performed and blast prediction techniques may be developed. The objective of this paper is to examine the influence of the precursor flow upon the propellant gas blast. To investigate the precursor effect, a 20mm cannon is evacuated to eliminate the air column forward of the projectile. (Continued)		

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

Data taken from these rounds are compared with that from firings at ambient conditions. The precursor-propellant gas interaction is demonstrated to influence the blast wave development in the near field forward of the muzzle; however, beyond a distance of 25 calibers from the muzzle, the two cases are indistinguishable.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES.	5
I. INTRODUCTION	7
II. TEST INSTRUMENTATION AND TECHNIQUE	8
III. MUZZLE FLOW ANALYSIS	8
IV. BLAST FIELD ANALYSIS	9
V. MUZZLE BLAST MODELING	10
VI. CONCLUSIONS.	12
ACKNOWLEDGMENT	12
REFERENCES	25
LIST OF SYMBOLS.	27
DISTRIBUTION LIST.	29

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Flow Field Schematics.	13
2. Experimental Instrumentation	13
3. Comparison of Muzzle Flow Development - Example 1.	14
4. Comparison of Muzzle Flow Development - Example 2.	15
5. Comparison of Muzzle Flow Development - Example 3.	16
6. Comparison of Muzzle Flow Development - Example 4.	17
7. Peak Overpressure Along a $\phi = 10^\circ$ Radial	18
8. Peak Overpressure Along a $\phi = 45^\circ$ Radial	19
9. Peak Overpressure Along a $\phi = 90^\circ$ Radial	20
10a. Comparison of the Predictions of Erdos and DelGuidice with Experimental Results for the Peak Overpressure Along a $\phi = 10^\circ$ Radial.	21
10b. Comparison of the Predictions of Erdos and DelGuidice with Experimental Results for the Peak Overpressure Along a $\phi = 90^\circ$ Radial.	22
11. Comparison of the Predictions of Schmidt with Experimental Results for the Peak Overpressure Along a $\phi = 90^\circ$ Radial. . .	23
12. Comparison of the Predictions of Fansler with Experimental Results for the Peak Overpressure Along a $\phi = 90^\circ$ Radial. . .	24

I. INTRODUCTION

Excessive blast overpressures at crew stations presently restrict the use of several Army weapons systems. Similarly, proving grounds often have to curtail operation during certain atmospheric conditions which allow blast focusing on populated areas. Many gun systems have muzzle devices whose use and effectiveness are influenced by their muzzle flow. Recently, an interest has arisen in the study of muzzle flash and secondary flash. These problems lead to the need for a more detailed understanding of the muzzle flow and the blast overpressure fields.

The flow from the muzzle of a gun consists of two impulsive jets (Figure 1). The air being forced out ahead of the projectile creates the first flow, called the precursor flow. As the projectile exits the gun tube, the high pressure, propellant gases are released creating a second, propellant gas flow. This flow rapidly overtakes and effectively consumes the much weaker precursor flow.

A variety of research projects have already been carried out to investigate the previously mentioned problems. In a series of optical experiments, Schmidt and Shear¹ characterized the muzzle flow around small caliber weapons. Erdos and Del Guidice² have developed a spherically symmetric model which calculates flow properties along the axis of symmetry. Their model assumes a core flow that is predicted by a steady method of characteristics calculation and then uses a finite difference technique to calculate the propagation of the shock layer between the jet Mach disk and the blast wave. Westine³, Smith⁴, and Schmidt⁵ have each presented a scaling law used to predict overpressures in the muzzle blast field. Fansler⁶ extends the scaling law of Smith to incorporate a more general range of weapons.

-
1. E. M. Schmidt and D. D. Shear, "Optical Measurements of Muzzle Blast," *AIAA Journal*, Vol. 13, No. 8, August 1975, pp. 1086-1091.
 2. J. Erdos and P. Del Guidice, "Calculations of Muzzle Blast Flow Fields," *AIAA Journal*, Vol. 13, No. 8, August 1975, pp. 1048-1056.
 3. P. Westine, "The Blast Field About the Muzzle of Guns," *Shock and Vibration Bulletin*, Vol. 39, Part 6, March 1969.
 4. F. Smith, "A Theoretical Model of the Blast from Stationary and Moving Guns," 1st International Symposium on Ballistics, Orlando, FL, November 1974, sponsored by American Defense Preparedness Association, Washington, D.C. 20005.
 5. E. M. Schmidt, G. D. Kahl, and D. D. Shear, "Gun Blast: Its Propagation and Control," AIAA Paper 80-1060, June 1980.
 6. K. S. Fansler and G. Keller, "Variation of Free-Field Muzzle-Blast with Propellant Type," 6th International Symposium on Ballistics, Orlando, FL, October 1981, sponsored by American Defense Preparedness Association, Washington, D.C. 20005.

In a paper by Schmidt, Kahl, and Shear⁵, it is suggested that the precursor flowfield affects the development of the propellant blast field. The present report presents a more detailed look at the interaction between the precursor and the propellant gas flows. By evacuating the gun tube ahead of the projectile, the precursor is eliminated. Comparison of these firings with normal or ambient conditions permits the isolation of the influence of the precursor flow. The near field is observed through a series of spark shadowgraphs while far-field data is acquired with static or side-on pressure transducers. The experimental results are compared with the scaling relations of Schmidt⁵ and Fansler⁶. Additionally, a separate development is presented which extends the results of Erdos² away from the axis of symmetry.

II. TEST INSTRUMENTATION AND TECHNIQUE

The weapon fired in this program is a 20mm cannon (Figure 2) which has a barrel length of 1.52m, a chamber volume of 41.7cm³ and a twist of rifling of one turn in 25 calibers. An M55A2 training round weighing 98g and having a L/D of 3.75 is used. The propellant fired is WC870 which has the following properties:

$$RT_{ad} = 9.87 \times 10^5 \text{ m}^2/\text{s}^2$$

$$\gamma = 1.24$$

Rounds are fired at reduced charges to obtain a range of exit conditions, summarized below:

m_c (g)	V_e (m/s)
3.6	280
17.8	610
38.9	1060

To investigate the effects of the tube gases ejected prior to projectile separation, the gun tube is evacuated before firings, thus effectively eliminating the precursor flow. Placing a mylar diaphragm across the muzzle and an "O" ring around the projectile forward of the rotating band allows the gun tube to be evacuated to below 50 μ m of Hg before firing.

Static pressure transducers placed along rays of 10°, 45°, 90°, 135°, and 170° measure the pressure pulses in the blast field. A spark shadow-graph technique¹ permits the observation of the muzzle flowfield. However, optical and transducer surveys are made separately to minimize the effect of reflecting from the Fresnel lens. Approximately three rounds are fired at each set of pressure transducer locations. Data is acquired for both the ambient and evacuated tube cases.

III. MUZZLE FLOW ANALYSIS

As previously mentioned, the muzzle flow development is observed through a series of spark shadowgraphs. The early development of the flow is

portrayed in Figure 3. The projectile has just separated from the gun bore and the high pressure propellant gases are escaping. For the atmospheric case (Figure 3a), the precursor flow is clearly portrayed and the development of the blast caused by the propellant gases has been slowed due to its submergence in the hot and turbulent gases of the precursor flow. By contrast, the evacuated case (Figure 3b), shows that the precursor has been almost completely eliminated. What remains appears to have little influence on the development of the main blast.

In Figures 4 and 5, the development of the blast wave can be seen. The atmospheric case, Figures 4a and 5a, clearly shows the effect of the precursor on the development of the blast in the axial direction. The blast wave is propagating into a preconditioned medium with a high velocity and a higher temperature, which allows the forward portion of blast to move out more rapidly than the lateral portions. This creates a nonspherical shape as opposed to the more spherically symmetric blast for the evacuated case (Figures 4b and 5b).

Finally, in Figure 6 the blast wave is fairly well developed and for the atmospheric case the blast wave is about to overtake the precursor wave (Figure 6a). As the blast wave overtakes the precursor wave it becomes fully developed and rapidly approaches the shape corresponding to the evacuated case (Figure 6b).

IV. BLAST FIELD ANALYSIS

The effect of evacuating the tube can be seen in Figure 7. The peak overpressures along a $\phi = 10^\circ$ radial described by

$$\overline{\Delta p} = (p - p_\infty) / p_\infty \quad (1)$$

are plotted for both atmospheric and evacuated conditions fired at a projectile velocity, $V_p = 1060\text{m/s}$. At locations near the muzzle, higher overpressures are obtained for rounds fired from an evacuated gun tube. Indicating that, in the ambient firings, interactions between the expanding propellant gas and the precursor flow cause an attenuation in the strength of the air shock. Further from the muzzle ($R/D \geq 30$), the overpressure levels are indistinguishable.

The pressure data taken with the ambient tube (Figure 7) displays a number of interesting features which may be correlated with properties of the flow field through observation of the spark shadowgraph sequences. Between 5 and 10 calibers from the muzzle, the overpressure profile has a local minimum. At 5 calibers the propellant gas wave is still immersed in the supersonic core of the precursor jet; however by 7.5 calibers, the blast wave moves outside of the supersonic core. Within the precursor jet, the propellant gas is expanding into an ambient with a high wave speed in the axial direction. This reduced the strength of the shock developed ahead of the propellant gas/air interface. However, once the propellant gas expands through the precursor jet, the nature of the surroundings change. The expansion now occurs in a relatively quiescent, lower wave speed ambient with a resultant increase in shock strength as the interface is penetrated.

Beyond 10 calibers, the pressures for the atmospheric case become larger than those for the evacuated case. A possible explanation for this behavior is that at this location, the blast generated by the release of the propellant gases coalesces with the precursor blast. In both the evacuated and ambient data, a local maximum in overpressure is observed at $R/D = 22.5$. This is due to an interaction between the air blast and projectile shock system as the round moves free of the decelerating blast.

Figure 8 presents a similar set of data for a $\phi = 45^\circ$ radial. The precursor has little effect on the blast overpressures. Peak overpressures along a $\phi = 90^\circ$ radial are presented in Figure 9. In this case, effects of the precursor do not appear significant. The data indicates that, as would be expected, the influence of the precursor flow is greatest near the line of fire and confined to the region close to the muzzle. However, since most existing analytical and numerical treatments of the muzzle flow do not include the precursor/propellant gas interaction, it is important to be aware of this phenomena when making comparisons between theory and experiment. Theory would produce a description of a flow field more nearly corresponding to the current evaluated tube data and should tend to over-predict blast pressure in the near field. Such over-predictions may not be a serious problem. If used to describe peak pressure levels on a muzzle device, the analysis would produce a built-in safety factor for the estimation of stress levels. In the far field, where crew members are present, the analysis and experiment should show minimal sensitivity to precursor effects.

V. MUZZLE BLAST MODELING

In this section, the measured blast overpressure properties of the 20mm cannon are compared with existing analyses^{2,5,6}. The numerical calculations of Erdos and Del Guidice² describe the muzzle flow in a region close to the axis of symmetry. In the present comparison, the predicted variation of pressure along the axis is swung to different rays by using the scaling law of Smith⁴.

Smith presents the following expression for the variation of scale length with the azimuthal angle, ϕ :

$$\frac{c'}{c} = f \cos \phi + (1 - f^2 \sin^2 \phi)^{\frac{1}{2}} \quad (2)$$

Smith develops this relationship from an analogy between the blast from a gun and that from a moving explosion. The value c' is in effect a stretched reference length, whereas c is the representative length of the gun. The parameter f is calculated from the best fit between c' and ϕ . The values of c' were calculated from data given by Schmidt⁵ and the following equation given by Smith⁴.

$$\overline{\Delta p} \propto (c')^{4/3} \quad (3)$$

For the 20mm gun used in these tests, f is determined to be 0.79.

The results of these calculations along a 10° ray are presented in Figure 10a. The predictions give reasonable results for locations greater than 12.5 calibers. Also, as expected, the predictions in the near field tend to agree with the evacuated tube data since the numerical calculation does not account for the effects of the precursor. Figure 10b presents a similar set of results for a 90° ray. In this instance, the procedure results in predictions which are reasonable for the reduced velocity cases but do not agree well for $V_m = 1060\text{m/s}$.

Schmidt⁵ suggests method for predicting the blast overpressure which uses the stabilized position of the Mach disk, x_{ns} , as a reference length. Schmidt gives the following equation for the variation in overpressure

$$\overline{\Delta p} = 0.975 \phi / r^{-1.1} \quad (4)$$

where

$$\phi = .8 \cos \phi + (1 - .64 \sin^2 \phi)^{\frac{1}{2}} \quad (5)$$

$$\overline{r} = r/x_{ns} \quad (6)$$

A comparison of Schmidt's predictions using the measured position of the Mach disc⁵ is presented in Figure 11. While obtaining general agreement with measurement, the scaling technique tends to over-predict pressure levels.

Fansler and Keller⁶ have developed a predictive scheme based on the work of Smith⁴ which permits calculation of blast overpressure contours once the interior ballistic performance of the weapon is determined. The basic relation describing overpressure is

$$\overline{\Delta p} = F (c'/c)/(r/\ell)^n \quad (7)$$

where c'/c is given by Smith's expression for the variation in scale length with polar angle, Equation (2), and, for best agreement, F and n are found to be 1.65 and 1 respectively. The scale length is given as

$$\frac{\ell}{D} = \sqrt{\frac{EM_p}{100 (U - \eta c) p_\infty [1+c/3m_1]}} \quad (8)$$

where $M_p = V_p/a_e$, U is the volume of the chamber plus bore volume, c is the mass of the propellant charge, and m_1 is the mass of the projectile if friction is taken into account. The covolume, η , is approximated by the value $1.2 \times 10^{-3} \text{ m}^3/\text{kg}$. Further, the quantity E , the original internal energy minus the kinetic energy of the projectile and propellant and the heat losses to the surroundings is

$$E = \frac{BCRT_a}{\gamma-1} - \frac{1}{2} (m_1 + c/3) (1+x) V_p^2 \quad (9)$$

where B is the percent of propellant burnt and x is the ratio of heat losses to the kinetic energy. Combining these expressions with Equation (7), yields the final equations for overpressure with sonic exit flow

$$\overline{\Delta p} = \frac{0.165[0.8 \cos \theta + (1-0.64 \sin^{-2} \theta)^{\frac{1}{2}}]}{r/D} \frac{EM_p}{(U-\eta c) p_{\infty}[1+c/(3m_1)]} \quad (10)$$

and with supersonic exit flow

$$\overline{p}_s = 0.94 \overline{p} \sqrt{\{1 + [1+c/(3m_1)] c V_p^2\}/(2E)} \quad (11)$$

Comparison of the predictions with experimental data shows that good agreement is obtained although the predicted rate of decay of overpressure in the far field is somewhat greater than measurements.

VI. CONCLUSIONS

A set of data has been taken to investigate the precursor/propellant gas interactions. It is shown that the precursor seems to have a significant effect on the muzzle flow near the gun bore axis, but this effect decreases with azimuthal angle. In the far field, the precursor has no measured effect on the blast field.

Three techniques for predicting blast overpressures are compared with experimental results. The method proposed by Fansler gives good agreement with the data, requires minimal effort, and is sensitive to changes in weapon ballistics.

ACKNOWLEDGMENT

The author wishes to thank Donald McClellan, William Thompson, and Gary Rumley for their aid in the preparation and operation of this test program. This writer also acknowledges the guidance of Drs. E. M. Schmidt and K. S. Fansler in the development of this research effort.




FIGURE 1 FLOW FIELD SCHEMATICS






Figure 2. Experimental Instrumentation




a. Atmospheric Tube




b. Evacuated Tube

Figure 3. Comparison of Muzzle Flow Development - Example 1




a. Atmospheric Tube




b. Evacuated Tube

Figure 4. Comparison of Muzzle Flow Development - Example 2




a. Atmospheric Tube




b. Evacuated Tube

Figure 5. Comparison of Muzzle Flow Development - Example 3



a. Atmospheric Tube



b. Evacuated Tube

Figure 6. Comparison of Muzzle Flow Development - Example 4




Figure 7. Peak Overpressure Along a $\phi = 10^\circ$ Radial




Figure 8. Peak Overpressure Along a $\phi = 45^\circ$ Radial




Figure 9. Peak Overpressure Along a $\phi = 90^\circ$ Radial




Figure 10a. Comparison of the Predictions of Erdos and DelGuidice with Experimental Results for the Peak Overpressure Along a $\phi = 10^\circ$ Radial




Figure 10b. Comparison of the Predictions of Erdos and DelGuidice with Experimental Results for the Peak Overpressure Along a $\phi = 90^\circ$ Radial




Figure 11. Comparison of the Predictions of Schmidt with Experimental Results for the Peak Overpressure Along a $\phi = 90^\circ$ Radial




Figure 12. Comparison of the Predictions of Fansler with Experimental Results for the Peak Overpressure Along a $\phi = 90^\circ$ Radial

REFERENCES

1. E. M. Schmidt and D. D. Shear, "Optical Measurements of Muzzle Blast," *AIAA Journal*, Vol. 13, No. 8, August 1975, pp. 1086-1091.
2. J. Erdos and P. Del Guidice, "Calculations of Muzzle Blast Flow Fields," *AIAA Journal*, Vol. 13, No. 8, August 1975, pp. 1048-1056.
3. P. Westine, "The Blast Field about the Muzzle of Guns," *Shock and Vibration Bulletin*, Vol. 39, Part 6, March 1969.
4. F. Smith, "A Theoretical Model of the Blast from Stationary and Moving Guns," 1st International Symposium on Ballistics, Orlando, FL, November 1974, sponsored by American Defense Preparedness Association, Washington, D.C. 20005.
5. E. M. Schmidt, G. D. Kahl, and D. D. Shear, "Gun Blast: Its Propagation and Control," AIAA Paper 80-1060, June 1980.
6. K. S. Fansler and G. Keller, "Variation of Free-Field Muzzle-Blast with Propellant Type," 6th International Symposium on Ballistics, Orlando, FL, October 1981, sponsored by American Defense Preparedness Association, Washington, D.C. 20005.

LIST OF SYMBOLS

c	scale length
c'	stretched scale length
e	specific energy
p	pressure
p_{∞}	atmospheric pressure
$\overline{\Delta p}$	overpressure
r	radial location
R	gas constant
T_{ad}	adiabatic flame temperature
x_{ns}	stabilized location of Mach disk
γ	ratio of specific heats
ϕ	azimuthal angle

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Technical Info Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	1	Commander US Army Communications Rsch and Development Command ATTN: DRDCO-PPA-SA Fort Monmouth, NJ 07703
2	HQDA (DAMA-CSM, MAJ Tobin, Mr. Lippe) Pentagon Washington, DC 20310	5	Commander US Army Missile Command ATTN: DRDMI-R DRDMI-RBL DRSMI-TLH (Ricks) DRDMI-RDK DRDMI-YDL Redstone Arsenal, AL 35809
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Tank Automotive Research & Development Cmd ATTN: DRDTA-UL Warren, MI 48090
2	Commander US Army Materiel Development and Readiness Command ATTN: DRCDL DRCDE-R, Mr. Lockert 5001 Eisenhower Avenue Alexandria, VA 22333	3	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib (2 cys) Deputy for Life Cycle Management (Mr. Ambrosini) Rock Island, IL 61299
3	Commander US Army Aviation Research and Development Command ATTN: DRDAV-E DRCPM-AAH Product Manager, AH-1 4300 Goodfellow Boulevard St. Louis, MO 63166	10	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS (2 cys) DRDAR-TDS, Mr. Lindner DRDAR-TDA, Mr. Blick DRDAR-LC-F, Mr. A. Loeb DRDAR-SCA, Mr. N. Ford DRDAR-LCW, Mr. M. Salsbury DRDAR-LCE, Dr. H. Fair DRDAR-LCE, Mr. Einstein DRDAR-SEM, (W. Bielauskas) Dover, NJ 07801
1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035	1	ODCSI, USAREUR & 7A ATTN: AEAGB-PDN(S&E) APO, NY 09403
1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
6	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCV, (Mr. Reisman) DRDAR-SCN, (Mr. Kahn) DRDAR-LC, (Dr. Frasier) DRDAR-SCW, (Mr. Townsend) DRDAR-SG (Dr. T. Hung) PM, 30mm Ammo, (LTC Logan) Dover, NJ 07801	2	HQDA (DAMA-CSM, MAJ Tobin, Mr. Lippe) Pentagon Washington, DC 20310
6	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Mr. W. Dock Dr. G. Carofano Dr. C. Andrade DRDAR-LCB, Mr. T. Allen Mr. R. Billington Watervliet, NY 12189	1	Commander US Army Research Office ATTN: CRD-AA-EH P. O. Box 12211 Research Triangle Park NC 27709
1	Commander US Army Jefferson Proving Ground ATTN: STEJP-TD-D Madison, IN 47251	3	Commander US Army Ballistic Missile Defense Systems Command Huntsville, AL 35804
1	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL Watertown, MA 02172	3	Commander Naval Air Systems Command ATTN: AIR-604 Washington, DC 20360
1	Commander US Army Natick Research and Development Command ATTN: DRXRE, Dr. D. Sieling NATICK, MA 01762	3	Commander Naval Ordnance Systems Cmd ATTN: ORD-9132 Washington, DC 20360
2	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL, Tech Lib ATAA-S White Sands Missile Range NM 88002	2	Commander David W. Taylor Naval Ship Research & Development Cmd ATTN: Lib Div, Code 522 Aerodynamic Lab Bethesda, MD 20084
		3	Commander Naval Surface Weapons Center ATTN: Code 6X Mr. F. H. Maille Dr. J. Yagla Dr. G. Moore Dahlgren, VA 22448
		1	Commander Naval Surface Weapons Center ATTN: Code 730, Tech Lib Silver Spring, MD 20910

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Commander Naval Weapons Center ATTN: Code 553, Tech Lib China Lake, CA 93555	1	Director NASA Scientific & Technical Information Facility ATTN: SAK/DL P. O. Box 8757 Baltimore/Washington International Airport, MD 21240
1	Commander Naval Research Laboratory ATTN: Tech Info Div Washington, DC 20375	1	AAI Corporation ATTN: Dr. T. Stastny Cockeysville, MD 21030
1	Commander Naval Ordnance Station ATTN: Code FS13A, P. Sewell Indian Head, MD 20640	1	Advanced Technology Labs ATTN: Mr. J. Erdos Merrick & Steward Avenues Westbury, NY 11590
1	AFRPL/LKCB, Dr. Horning Edwards AFB, CA 93523	1	Aerospace Corporation ATTN: Dr. G. Widhopf P. O. Box 92957 Los Angeles, CA 90009
2	AFATL (DRDL, Dr. D. C. Daniel Tech Lib) Eglin AFB, FL 32542	1	ARO, Inc. ATTN: Tech Lib Arnold AFS, TN 37389
1	AFWL/SUL Kirtland AFB, NM 87117	1	ARTEC Associates, Inc. ATTN: Dr. S. Gill 26046 Eden Landing Road Hayward, CA 94545
1	ASD/XRA (Stinfo) Wright-Patterson AFB, OH 45433	1	Battelle Columbus Laboratories ATTN: J. E. Backofen, Jr. 505 King Avenue Columbus, OH 43201
1	Director National Aeronautics and Space Administration George C. Marshall Space Flight Center ATTN: MS-I, Lib Huntsville, AL 38512	1	Technical Director Colt Firearms Corporation 150 Huyshope Avenue Hartford, CT 14061
1	Director Jet Propulsion Laboratory ATTN: Tech Lib 2800 Oak Grove Drive Pasadena, CA 91103	2	ARO, Inc. ATTN: Dr. J. Lewis Mr. W. D. Williams Arnold AFS, TN 37389

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	General Electric Corporation Armaments Division ATTN: Mr. R. Whyte Lakeside Avenue Burlington, VT 05401	1	Director Applied Physics Laboratory The Johns Hopkins University Johns Hopkins Road Laurel, MD 20810
1	Honeywell, Inc. ATTN: Mail Station MN 112190 (G. Stilley) 600 Second Street, North Hopkins, MN 55343	1	Massachusetts Institute of Technology Dept of Aeronautics and Astronautics ATTN: Tech Lib 77 Massachusetts Avenue Cambridge, MA 02139
3	Hughes Helicopter Company Bldg. 2, MST22B ATTN: Mr. R. Forker Mr. L. Johnson Mr. R. Flood Centinella and Teel Streets Culver City, CA 90230	1	Ohio State University Dept of Aeronautics and Astronautical Engineering ATTN: Tech Lib Columbus, OH 43210
1	Martin Marietta Corp. ATTN: Mr. A. J. Culotta P. O. Box 5387 Orlando, FL 32805	3	Polytechnic Institute of New York Graduate Center ATTN: Tech Lib Prof. S. Lederman Dr. G. Moretti Route 110 Farmingdale, NY 11735
1	Olin Corporation Winchester-Western Division 275 Winchester Avenue New Haven, CT 06504	1	Director Forrestal Research Center Princeton University Princeton, NJ 08540
1	Sandia Laboratories ATTN: Aerodynamics Dept Org 5620, R. Maydew Albuquerque, NM 87115	1	Kaman Tempo ATTN: Mr. J. Hindes 715 Shamrock Road, Suite UL-1 Bel Air, MD 21014
1	Guggenheim Aeronautical Lab California Institute of Tech ATTN: Tech Lib Pasadena, CA 91104	1	Southwest Research Institute ATTN: Mr. Peter S. Westine 8500 Culebra Road San Antonio, TX 78228
1	Franklin Institute ATTN: Tech Lib Race & 20th Streets Philadelphia, PA 19103		

DISTRIBUTION LIST

Aberdeen Proving Ground

Dir, USAMSAA
ATTN: DRXSY-D
DRXSY-MP, H. Cohen

Cdr, USATECOM
ATTN: DRSTE-TO-F

Cdr, USACSL, Bldg. E3516, EA
ATTN: DRDAR-CLB-PA

Dir, USAHEL
ATTN: Dr. Weisz
Dr. Cummings

Cdr, USATECOM
ATTN: MTD, Mr. S. Walton

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____

2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

