

AD-A118 809

RAND CORP SANTA MONICA CA

F/G 22/2

TRANSMISSION AND ORBITAL CONSTRAINTS IN SPACE-RELATED PROGRAMS:--ETC(11)

NOV 81 A L HIEBERT

UNCLASSIFIED

RAND/P-6713

NL

10-1  
RAND

END
DATE
FORMED
9 82
DIA

AD A118809



TRANSMISSION AND ORBITAL CONSTRAINTS IN SPACE-RELATED PROGRAMS:  
BRIEFING SUMMARY

A. L. Hiebert

November 1981

DTIC FILE COPY

DTIC  
ELECTE  
SEP 1 1982  
S D  
D

P-6713

DISTRIBUTION STATEMENT A

Approved for public release;  
Distribution Unlimited

82 08 30 192

PREFACE

This briefing summary is an addendum to a Rand Note on "Transmission and Orbital Constraints in Space-Related Programs: Project Description," N-1536-AF, August 1980, prepared for the United States Air Force. Essential components of the project include development of a comprehensive Space Environment Data Base and Analysis Codes and Computer Programs. This capability will provide a resource for evaluating engineering and architectural designs, identifying and analyzing the impact of intentional and unintentional electromagnetic (EM) interference, and predicting probable saturation conditions in spectrum usage of space and earth segments, and satellite/orbital positions. Assessments of ways of accommodating anticipated growth are included in the program.

The briefing was presented at a joint conference on "Space Systems Data Bases and Analysis Capabilities," which was organized to assist Rand and the ECAC in defining the items for inclusion in the data base, its subsequent updating, and evaluating existing and needed analysis programs. Representatives from industry and government agencies were asked to participate. The conference was conducted and hosted by ECAC, on November 17-19, 1981 at Annapolis, MD. ECAC will compile a report on the Proceedings.

<b>Accession For</b>	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
<b>By</b>	
<b>Distribution/</b>	
<b>Availability Codes</b>	
<b>Dist</b>	<b>Avail and/or</b>
A	Special



CONTENTS

PREFACE .....	iii
Section	
I. INTRODUCTION .....	1
II. PROJECT OBJECTIVES .....	3
III. TECHNICAL REQUIREMENTS .....	6
SPACE ENVIRONMENT DATA BASE .....	6
ANALYSIS CODES AND COMPUTER PROGRAMS .....	9
IV. PROJECT STATUS AND FUTURE EFFORTS .....	13
Appendix A: SPACE SYSTEMS DATA RECORD--Electromagnetic Characteristics and Operational Information for Space Systems and Related Earth Segments .....	17

I. INTRODUCTION

The United States Air Force has a leadership role in the development and operation of space systems for the Department of Defense. Planning for future space-related programs needs to include anticipated growth in number of space systems, including ground networks, large multifunction satellites, increased data-transmission rates, and effects on future requirements for spectrum allocations and orbital positions.

A study project,\* sponsored by the Air Force, was initiated to develop a capability for predicting and analyzing the spectrum/orbital geometry requirements of current and projected U.S. and international space-related systems. Essential components of the project include development of a comprehensive space environment data base and computer analysis programs. This capability will provide a resource for evaluating engineering and architectural designs, identifying and analyzing the impact of intentional and unintentional electromagnetic (EM) interference, and predicting probable saturation conditions in spectrum usage and satellite/orbital positions. Assessments of means for accommodating the anticipated growth are also an important part of the study project.

The Directorate of Space Systems and Command, Control, Communications (AF/RDS), Headquarters, United States Air Force is providing support for this project within the Air Force through the

---

\* A. L. Hiebert and A. F. Brewer, Transmission and Orbital Constraints in Space-Related Programs: Project Description, The Rand Corporation, N-1536-AF, August 1980.

Program Management Directive (PMD) of the Advanced Space Communications Program (PE634431F). AF/RDS is the Office of Primary Responsibility (OPR) for the Rand effort and will assist in requesting the support and participation of other DoD organizations, the FCC, NASA, NTIA, and space-related industries. Rand's work will be coordinated with these agencies. The project will be structured for a continuing analysis program that will comply with technical criteria, rules and regulations, and coordination procedures established by the national and international spectrum management agencies. As projected, the analysis program will be designed to be accessible to the space community as operational capabilities are acquired.

## II. PROJECT OBJECTIVES

Projected advances in the use of space by the military and other organizations for communications, navigation, surveillance, and other mission capabilities--coupled with the prospect of substantial increases in launch rates by U.S. military, intelligence, and civil agencies, as well as by international agencies--will add substantially to data link traffic and data-processing requirements in ground-to-satellite, satellite-to-satellite, and satellite-to-ground communications and relay systems. Data transmission requirements could expand by several orders of magnitude as new and larger spacecraft are developed; LANDSAT-D, for example, proposed that resolution be increased from 1.2 acres to 0.2 acre (4850 M<sup>2</sup> to 810 M<sup>2</sup>) and that the IR data rate be increased from 1000 to 1,000,000 bits/sec. Such expansion could severely tax the data-handling capacities of current equipment and affect the frequency spectrum allocations and orbit assignments of satellite systems. Available spectrum, and the useful orbital positions as defined by today's capabilities, may be inadequate. This could negate the operational advantage of the increased sensing capabilities now being sought in spacecraft, and the increased demand in time of crisis could result in disruption of critical data transmission.

The future growth in both commercial and military space systems will be constrained by technical problems associated with the frequency spectrum, orbital congestion, and costs stemming from proliferated terminals. The seriousness of these constraints is shown in an assessment of the useful areas and coverage of the geostationary

circle;\* these areas are essentially full at current assignments with communications satellites at C-band and are expected to reach saturation at X and K<sub>u</sub>-bands in the future. The military UHF and SHF frequency bands are also almost saturated because large portions of them are shared with terrestrial links.

Future deep-space-based exploration systems may also be characterized by high-data-rate-mission sensors and thus will create additional problems in the use of the frequency spectrum and in data transmission. The high data rates are based on the demand for timely and accurate sensor information covering wide spatial areas and are generated by fast detectors with high sensitivity and resolution. Deep-space exploration sensors are expected to exhibit data rates that will exceed the data transmission capacity of the currently planned communication links and ground-processing equipment.

7 This briefing outlines the project objectives and tasks required to develop a continuing program for predicting and analyzing the spectrum and orbital requirements of current and future space-related systems, and for predicting potential saturation conditions. → p. 5

---

\* The FCC has acknowledged that additional steps must be taken to meet the continued demand for satellite capacity and to provide for new entry. To address this matter, the FCC has issued a "Notice of Inquiry and Proposed Rulemaking," Docket No. 81-704, November 18, 1981, on the "Licensing of Space Stations in the Domestic Fixed-Satellite Service and Related Revisions of Part 25 of the Rules and Regulations." A reduction in the geostationary orbital space from 4 degrees to 2 degrees between satellites operating in the 4/6 GHz bands, and in spacing from 3 degrees to 2 degrees between satellites operating in the 12/14 GHz bands, is proposed. A 3-dB improvement in earth station antenna sidelobe gain standards and a 10-dB cross-polarization isolation standard for small off-axis angles are also proposed. These changes should provide spacing for 37 U.S. satellites in each of the bands listed.

→ The project objectives are to design and develop a capability for :

- (1) Predicting and analyzing spectrum/orbital requirements of current and projected U.S. and international space-related programs,
- (2) Evaluating engineering and architectural designs,
- (3) Identifying and analyzing intentional/unintentional EMI,
- (4) Predicting saturation in spectrum usage/orbital positions,
- (5) Assessing means to accommodate growth, *and*
- (6) Supporting preparations for space services <sup>f</sup>-WARC. *g*

### III. TECHNICAL REQUIREMENTS

To accomplish the project objectives, it will be necessary to design and develop a comprehensive Space Environment Data Base and Analysis Codes and Computer Programs.

#### SPACE ENVIRONMENT DATA BASE

The proposed Space Environment Data Base should consist of a file on electromagnetic and operational characteristics and a file on the deployment status of currently active and projected U.S. and international space systems, related earth segments, and network systems. The Electromagnetic and Operational Characteristics File should include three levels of information:

1. Level 1 - minimum data.
2. Level 2 - nominal and expanded data.
3. Documentation, reports, measured data.

The Deployment Status File should include four time-related information categories:

1. Current and active-deployed systems.
2. Approved-for-launch systems and scheduled dates.
3. Firm and funded development space system programs.
4. Future development plans and schedules.

A proposed data collection format has been designed by Rand and ECAC/IITRI and is intended for use in developing the Electromagnetic and Operational Characteristics File on Level 1.\* The data will support preliminary interference analyses and will provide indications of the operational usage of systems. The format applies to communications, navigation, relay, sensor satellites, space transportation systems, their related earth segments, launch operations, and TT C operations. Technical characteristics of the hardware involved and operational characteristics of the system are to be reported. Other types of satellites, such as radar and solar power satellites, require additional data to describe the system adequately. Formats to accommodate these systems are being designed and will be published at a later date.

The data collection format (Appendix A) proposed by Rand and ECAC was designed to accommodate current and active deployed systems. The same format should be used to report known or projected data on systems in other categories of the Deployment Status File. Estimates or projections should be identified as such.

The proposed format is currently being tested and evaluated on Air Force space systems in cooperation with the Air Force Space Division Program Offices and the Communications Electronics Support Office (CSD/DC). It will be reviewed with NTIA, the FCC, Frequency Management Offices of the Department of Defense, and participants in the conference.

---

\* Appendix A: SPACE SYSTEMS DATA RECORD--Electromagnetic Characteristics and Operational Information for Space Systems and Related Earth Segments.

Design and modification of the Space Environment Data Base should be conducted as a continuing joint effort by The Rand Corporation, the DoD Electromagnetic Compatibility Analysis Center (ECAC), the DoD Frequency Management Agencies, NTIA, FCC, and other participating agencies. Responsibility for constructing and maintaining the Data Base and developing an analysis capability for space-systems planning has been assigned to the ECAC at Annapolis, Maryland.\* ECAC already has the necessary computer and data-processing equipment, the trained personnel, and a substantial portion of the required space-environment data and associated analysis codes and programs. Additional facilities may be needed to process highly classified and proprietary data.

ECAC also maintains an extensive and active data base on the electromagnetic and operational characteristics of terrestrial and earth environment equipment that may affect some of the space-related programs.

Preliminary discussions have been initiated with NORAD, ADCOM (SPADOC), and other agencies about the acquisition and processing of needed data on the operational condition and status of space systems. Since these data will be at various levels of security and in some cases will include proprietary information, appropriate means for processing proprietary and classified information will need to be developed and approved by the cognizant agencies. A preliminary list of agencies and contacts was published in the Rand Report mentioned earlier and is being updated as the project develops.

---

\* Memorandum: "Electromagnetic Compatibility Analysis Center Support for Space Systems Planning," 25 June 1981, Office of the Under Secretary of Defense, Research and Engineering, Assistant Deputy Under Secretary (Technical Policy and Operations).

The Data Base should be made available--as needed, and under appropriate security procedures--to Rand space studies, to DoD, and to Government agencies and sponsored contractors conducting analyses in the subject areas.\* The Data Base should be updated for satellite launches/decays and changes in space systems development plans to provide a continuing source of information for analyzing current and future space systems.

Prediction and analysis of probability of spacecraft collision and/or physical impact with space objects will not be addressed in this project. However, the Data Base should provide useful information on the ephemerides of current and future satellites, which is essential to such investigations.

#### ANALYSIS CODES AND COMPUTER PROGRAMS

The objectives are to devise analytic codes and computer programs for interrogating the Space Environment Data Base so that current and projected usage/saturation levels and impact of EM interference can be determined for the spectrum allocation, orbital positions of space systems, and related earth segments.

It may be necessary to develop new analysis techniques and usage/saturation criteria for each type of space communications, navigation relay, or sensor service. Since the results depend on space, time, frequency, message length, and scenario, usage and saturation

---

\* "Accessibility to the Data Base" will be discussed by J. Atkinson of ECAC in a separate briefing, and will be published in The Proceedings of the Conference.

levels will have to be determined for each elemental space volume of the system at various times and frequencies, at mean message lengths, and under different scenarios for different levels of usage. Space, even useful portions of space, is a very large volume. Conditions prevailing in one portion (or elemental volume) tend to be different from those prevailing in another.

For each authorized frequency band and/or channel, completely defined emissions, partially defined emissions (random in space or time), and undefined emissions (random in space and time) will have to be statistically combined and compared with receiver sensitivity, antenna gain, and system losses in order to derive a measure of band usage.

This correlation will provide a basis for projecting future demands on each allocated band in terms of the anticipated increase for users or frequency of use. After "saturation" is defined for each type of service, it should be possible to determine which usage rates are approaching saturation in an assigned frequency band and orbital position and how soon this is likely to occur.

Limits of orbital spacing are based on beamwidths of the earth station/terminal (may include mobile) antennas, electromagnetic interference criteria, and adherence to the ITU Radio Regulations. Hence, intentional and unintentional interference situations and their impact on usage/saturation levels should be assessed. Analysis of system vulnerability to intentional EM interference is an additional and essential requirement for hardened and secure systems.

Once suitable criteria have been determined and analyzed and programs have been developed, they will be applied to the Data Base to answer questions such as

1. What are the usage and saturation rates of existing and planned space communication systems?
2. Can a new system be added to the existing space environment and function as required? What will a new system (assuming it became operational) do to the existing systems?
3. What are intentional/unintentional interference situations, sources, and effects?
4. What will defined jamming situations do to a specified military data link that is already X percent saturated?
5. Which systems are the least conservative of spectrum?
6. Which systems approach orbital congestion?

Answers to questions such as these should make it possible to recommend communication practices, band allocations, and orbital assignments that will permit transmission of essential information within the available finite spectrum.

A list of proposed analysis codes and computer programs have been compiled to provide the capabilities for performing the types of analysis discussed and for meeting the overall project objectives (Table 1).

This list is based on a series of joint Rand/ECAC technical surveys and reviews of existing programs and those recommended for development. It will be augmented as the surveys and project activities continue and as user requirements are identified.

Table 1

Proposed Analysis Codes and Computer Programs

Title	Organization
1. Cull and coordination models: Space and earth segments ITU Radio Regulation Appendix 28, 29--Automation Ground mobile satellite terminals	ECAC ECAC, NTIA ECAC
2. Co-site analysis: space segment	ECAC
3. Co-site analysis: earth stations, fixed/mobile	ECAC
4. Intrasystem EMC Analysis: AF/IAP	RADC
5. Engineering and architectural design analysis: MITRE Interactive Communication Analysis Program (MICAP) Interference Analysis in Satellite Communications	MITRE MITRE
6. Intersystem EMC and vulnerability analysis: Geostationary orbit: Spectrum-Orbit Utilization Program (SOUP) Satellite Link Interference Prediction Nongeostationary orbits and fixed/mobile stations Environmental Analysis Model: frequency planning Deep Space RFI Prediction Program (DSIP-II) MILSATCOM vulnerability analysis	NTIA, NASA, ORI Rand Rand ECAC JPL AF/ESC, Bell
7. Saturation prediction and analysis: System capacity Usage rate/efficiency Orbital positions	Rand

IV. PROJECT STATUS AND FUTURE EFFORTS

During the formative period of the Rand project, and in subsequent Air Force/Rand reviews, we were advised to develop concepts and plans for listing the uses of the analysis programs and for accessing the data base, as required. It was assumed that ECAC would be assigned the responsibility of developing a data base and analysis capability with respect to military space systems for the purpose of improving EMC planning and minimizing the potential intersystem harmful EM interference. Other related space efforts, as listed in the Rand project objectives, may require the development and use of analysis capabilities by other DoD and government agencies and possibly by Air Force aerospace contractors.

Examples of such efforts would include capabilities for

1. EMC intrasystem analysis of space systems.
2. Assessments and analysis of Blue/Grey Forces interference or intentional Red Forces jamming.
3. Analysis of special space systems requiring compartmental data bases and 24-hour operational support.
4. Engineering analysis of architectural formulations of proposed space systems.
5. Determination of the transmission capacity of space systems, their usage rate and efficiency of use, and the predicted saturation of spectrum utilization and orbital positions.
6. Technical preparations space services WARC.

This extended support will require access to the ECAC data base and selected analysis computer programs. A joint conference on Space Systems Data Bases and Analysis Capabilities was organized to assist us and the ECAC in defining the items for inclusion in the data base and its subsequent updating, and in reviewing and evaluating existing and needed analysis programs. Representatives from industry and government agencies were asked to participate. The conference was conducted and hosted by ECAC, on November 17-19, 1981 at Annapolis, MD. ECAC will compile a report on the Proceedings.

Rand will be requesting the assistance of ECAC, the Aerospace Corporation, and other participating agencies in conducting assessments of the data base items and analysis programs required to meet the overall objectives outlined in this briefing. We hope to continue the design and development of analysis programs and to assist in determining the Air Force technical analysis and support requirements.

Among the objectives of the project is that it be timed to provide a usable capability for the technical development of Air Force positions on spectrum usage and orbital location issues for Space Services WARC. Attaining this objective will require the combined effort of and coordination with agencies outside Rand.

Study efforts aimed at assessing means to accommodate the growth of space systems and related proliferated earth terminals have not been discussed in this briefing. However, candidate techniques that may offer ways of accommodating increased proliferation of space data are being monitored and assessed as the project develops. Examples of such techniques include:

- o Current and potential developments in data processing and compression, multibeam antennas, etc..
- o Use of higher frequencies.
- o Added spectrum allocations.
- o More efficient energy dispersal.
- o Improved side lobes of earth station antennas.
- o Satellite data relay systems.

Appendix A

SPACE SYSTEMS DATA RECORD

Electromagnetic Characteristics and Operational Information  
for Space Systems and Related Earth Segments

Prepared by

The Rand Corporation  
1700 Main Street  
Santa Monica, CA 90406

and

IIT Research Institute for  
DoD Electromagnetic Compatibility Analysis Center  
North Severn  
Annapolis, MD 21402

September 30, 1981

PRECEDING PAGE

INTRODUCTION

This data collection format is intended for use in developing the Electromagnetic and Operational Characteristics File on Level 1. The data will support preliminary interference analyses and will provide indications of operational usage of systems. The format applies to communications, navigation, relay, sensor satellites, space transportation systems, their related earth segments, launch operations, and TT&C operations. Technical characteristics of the hardware involved and operational characteristics of the system are to be reported. Other types of satellites, such as radar and solar power satellites, require additional data to adequately describe the system. Formats to accommodate these systems are being designed and will be published at a later date.

This data collection format was designed to accommodate current and active deployed systems. The same format will be used to report known or projected data on systems in the other Deployment Status File categories. Estimates or projections will be identified as such.

The number of forms to be completed will vary with the system being described. A space segment form will be completed for each satellite associated with the system and an earth segment form will be completed for each earth station associated with the system. Transmitter data and receiver data forms will be completed for each operating mode of each equipment nomenclature associated with the system.

If additional data items are required for systems being reported, please attach to the form as supplemental information with appropriate identifiers. Comments and suggestions on the data collection format are requested.

DATA SOURCES AND REFERENCES

Form Completed by:  
Organization \_\_\_\_\_  
Address \_\_\_\_\_  
  
Point of Contact \_\_\_\_\_  
Telephone Commercial: \_\_\_\_\_  
Autovon: \_\_\_\_\_

Reference Documents (list by title, date, document number, and classification).

SUBMIT DATA TO:

Department of Defense  
Electromagnetic Compatibility Analysis Center  
North Severn, Annapolis, MD 21402  
Attn: H. F. Mezzack XM

Class/  
Release/  
Source

I. SYSTEM DATA

A. General

1. Mission Title/Common Name \_\_\_\_\_
2. Associated Satellite Names \_\_\_\_\_
3. Associated Terminal Names \_\_\_\_\_
4. Responsible Agency/Country \_\_\_\_\_
  - a. Research and Development of System \_\_\_\_\_
  - b. Acquisition \_\_\_\_\_
  - c. Control \_\_\_\_\_
  - d. User \_\_\_\_\_
5. Control Center Names and Locations \_\_\_\_\_
6. System Function/Type \_\_\_\_\_  
(ex: data, DBS, comm, passive reflector, etc.)
7. Average Usage Factor  
Current \_\_\_\_\_  
Projected \_\_\_\_\_
8. Link Data
  - a. Uplink Margin \_\_\_\_\_
  - b. Uplink Maximum Possible Signalling Rate  
or Bandwidth \_\_\_\_\_
  - c. Uplink Maximum Data Rate  
or Capacity \_\_\_\_\_
  - d. Downlink Margin \_\_\_\_\_
  - e. Downlink Maximum Possible Signalling Rate  
or Bandwidth \_\_\_\_\_
  - f. Downlink Maximum Possible Signalling Rate  
or Bandwidth \_\_\_\_\_
  - g. Lowest Equivalent Satellite Link Noise  
Temperature \_\_\_\_\_
9. GMF S Note \_\_\_\_\_
10. Operating Modes \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Class/  
Release/  
Source

II. EARTH STATION

A. Administrative

1. Licensee/Organization/Unit \_\_\_\_\_
2. City or Base (Station Name) \_\_\_\_\_
3. Manufacturer \_\_\_\_\_
4. Station Class \_\_\_\_\_

II. EARTH STATION PARAMETERS

Class/  
Release/  
Source

B. Physical

- 1. Site Name, Country \_\_\_\_\_
  
- 2. Location
  - a. Latitude \_\_\_\_\_
  - Longitude \_\_\_\_\_
  - b. UTM Grid Reference
    - Northing \_\_\_\_\_
    - Easting \_\_\_\_\_
    - Grid Zone \_\_\_\_\_
    - Spheriod \_\_\_\_\_
  
- 3. Antenna Azimuth \_\_\_\_\_  
(if geosynchronous satellite)
  
- 4. Fixed/Mobile \_\_\_\_\_
  
- 5. Platform Type \_\_\_\_\_
  
- 6. Radius of Movement\* \_\_\_\_\_
  
- 7. a. Rain-Climatic Zone \_\_\_\_\_  
b. Radio-Climatic Zone \_\_\_\_\_  
(A, B, C)\* \_\_\_\_\_  
c. Horizon Elevation \_\_\_\_\_  
Profile\* \_\_\_\_\_
  
- 8. Refractivity \_\_\_\_\_

\*Attach Information

Class/  
Release/  
Source

II. EARTH STATION TRANSMITTERS

C. Technical

0. Equipment Nomenclature/Operating Mode

- 1. Bandwidth \_\_\_\_\_
- 2. Frequency Range \_\_\_\_\_
- 3. Modulation \_\_\_\_\_
- 4. Power \_\_\_\_\_
- 5. Power Type \_\_\_\_\_
- 6. Harmonic Attenuation \_\_\_\_\_
- 7. Spurious Attenuation \_\_\_\_\_
- 8. RF Filter, Filter Type \_\_\_\_\_  
3 dB Bandwidth/Number of Poles/Q \_\_\_\_\_  
or Off-Frequency/Relative Level \_\_\_\_\_

- 9. Noise Floor \_\_\_\_\_
- 10. Data Rate/Number of Voice or Video Circuits \_\_\_\_\_
- 11. Emissions Description: \_\_\_\_\_  
(if different from RF filter spectrum) \_\_\_\_\_  
3 dB Bandwidth/Roll-Off \_\_\_\_\_  
Frequency/Relative Attenuation \_\_\_\_\_

- 12. Access Mode \_\_\_\_\_
- 13. Link Type \_\_\_\_\_
- 14. Output Device \_\_\_\_\_

Electrooptic (e-o) Transmitter

- 1. Nomenclature \_\_\_\_\_
- 2. Wavelength \_\_\_\_\_
- 3. Output Device \_\_\_\_\_
- 4. Power Output \_\_\_\_\_
- 5. Emissions Spectrum \_\_\_\_\_  
Off-Frequency/Relative Level \_\_\_\_\_
- 6. Data Rate \_\_\_\_\_

II. EARTH STATION RECEIVER

D. Technical

Class/  
Release/  
Source

0. Equipment Nomenclature/Operating Mode

- 1. RF Bandwidth \_\_\_\_\_
- 2. Frequency Range \_\_\_\_\_
- 3. Modulation \_\_\_\_\_
- 4. RF Filter Type \_\_\_\_\_  
3 dB Bandwidth/Number of Poles (Roll-off)/Q \_\_\_\_\_  
or Off Frequency/Relative Level \_\_\_\_\_

5. Number of IF Stages

- 6. For Each IF Stage: \_\_\_\_\_  
IF Frequency \_\_\_\_\_  
3 dB Bandwidth/# Poles (Roll-off)/Q \_\_\_\_\_  
or Frequency/Relative Level \_\_\_\_\_

LO Frequency

- 7. Spurious Rejection \_\_\_\_\_
- 8. Harmonic Rejection \_\_\_\_\_
- 9. Image Rejection \_\_\_\_\_
- 10. Required Signal-to-Noise Ratio \_\_\_\_\_

- 11. Noise Figure \_\_\_\_\_
- 12. Noise Equivalent Power/Responsivity \_\_\_\_\_

13. Sensitivity/Sensitivity Criterion

- 14. Baseband Bandwidth \_\_\_\_\_
- 15. Access Mode \_\_\_\_\_
- 16. G/T \_\_\_\_\_
- 17. Effective Receiver Noise Temperature \_\_\_\_\_

e-o Receiver

- 1. Nomenclature \_\_\_\_\_
- 2. Wavelength \_\_\_\_\_
- 3. Detector Type \_\_\_\_\_
- 4. Sensitivity and Basis \_\_\_\_\_
- 5. RF Susceptibility \_\_\_\_\_
- 6. Coherent/Incoherent \_\_\_\_\_
- 7. Detector Noise Voltage \_\_\_\_\_

III. SPACE SEGMENT

Class/  
Release/  
Source

A. Administrative

- |                                     |       |       |
|-------------------------------------|-------|-------|
| 1. Mission Title/Common Name        | _____ | _____ |
| 2. International Designator         | _____ | _____ |
| 3. NORAD-Space Object Number        | _____ | _____ |
| 4. Inter-Range Operations Number    | _____ | _____ |
| 5. Satellite Launch/Expiration Date | _____ | _____ |
| 6. Bringing Into Use Date           | _____ | _____ |
| 7. Manufacturer                     | _____ | _____ |

III. SATELLITE ORBITAL PARAMETERS

Class/  
Release/  
Source

B. Physical

1. Orbit Type \_\_\_\_\_

Elliptical Orbits

2. Orbit Inclination \_\_\_\_\_

3. Right Ascension of Ascending Node \_\_\_\_\_

4. Orbital Eccentricity \_\_\_\_\_

5. Argument of Perigee \_\_\_\_\_

6. Mean Motion Rate \_\_\_\_\_

7. Epoch \_\_\_\_\_

8. Inclination \_\_\_\_\_

9. Semi-latus Rectum \_\_\_\_\_

10. Time of Perigee Passage \_\_\_\_\_

11. Apogee \_\_\_\_\_

12. Perigee \_\_\_\_\_

13. Nodal Period \_\_\_\_\_

14. Mean Anomaly \_\_\_\_\_

15. Eccentric Anomaly \_\_\_\_\_

16. Active Portion of Orbit \_\_\_\_\_

17. First Time Derivative of Mean Motion Rate

( $n_0/2$ ) \_\_\_\_\_

18. Second Time Derivative of Mean Motion Rate

( $n_0/6$ ) \_\_\_\_\_

19. Drag Coefficient \_\_\_\_\_

( $B^*$ ) \_\_\_\_\_

20. Element Set Number \_\_\_\_\_

Geosynchronous Orbits

2. Longitude of Station in Orbit \_\_\_\_\_

3. Station Keeping Limits \_\_\_\_\_

4. Inclination \_\_\_\_\_

Class/  
Release/  
Source

III. SPACE STATION TRANSMITTER

C. Technical

0. Equipment Nomenclature/Operating Mode		
1. Bandwidth	_____	_____
2. Frequency Range	_____	_____
3. Modulation	_____	_____
4. Power	_____	_____
5. Power Type	_____	_____
6. Harmonic Attenuation	_____	_____
7. Spurious Attenuation	_____	_____
8. RF Filter	_____	_____
3 dB Bandwidth/Number of Poles/Q	_____	_____
Off-Frequency/Relative Attenuation	_____	_____
9. Modulation Type	_____	_____
10. Data Rate/Number of Voice or Video Circuits	_____	_____
11. Emissions Descriptions	_____	_____
3 dB Bandwidths/Roll-Off	_____	_____
Frequency/Relative Attenuation	_____	_____
	_____	_____
	_____	_____
12. Noise Floor	_____	_____
13. Access Mode	_____	_____
14. Downlink Mode	_____	_____
15. Output Device	_____	_____
e-o Transmitter		
1. Nomenclature	_____	_____
2. Wavelength	_____	_____
3. Output Device	_____	_____
4. Power Output	_____	_____
5. Emissions Spectrum	_____	_____
3 dB Bandwidth/Roll-off	_____	_____
Off-Frequency/Relative Level	_____	_____
	_____	_____
	_____	_____
6. Data Rate	_____	_____

III. SPACE STATION RECEIVER

Class/  
Release/  
Source

D. Technical

- 0. Equipment Nomenclature/Operating Mode
- 1. RF Bandwidth \_\_\_\_\_
- 2. Frequency Range \_\_\_\_\_
- 3. Modulation \_\_\_\_\_
- 4. RF Filter Type \_\_\_\_\_  
3 dB Bandwidth/Number of Poles (Roll-off) \_\_\_\_\_  
or Off-Frequency/Relative Level \_\_\_\_\_
- 5. Number of IF Stages \_\_\_\_\_
- 6. For Each IF Stage: \_\_\_\_\_  
IF Frequency \_\_\_\_\_  
3 dB Bandwidth/# Poles (Roll-off) \_\_\_\_\_  
or Frequency/Relative Level \_\_\_\_\_  
LO Frequency \_\_\_\_\_
- 7. Spurious Rejection \_\_\_\_\_
- 8. Harmonic Rejection \_\_\_\_\_
- 9. Image Rejection \_\_\_\_\_
- 10. Required Signal-to-noise Ratio \_\_\_\_\_
- 11. Noise Figure \_\_\_\_\_
- 12. Noise Equivalent Power/Responsivity \_\_\_\_\_
- 13. Sensitivity/Sensitivity Criterion \_\_\_\_\_
- 14. Baseband Bandwidth \_\_\_\_\_
- 15. Access Mode \_\_\_\_\_
- 16. Effective Receiver Noise Temperature \_\_\_\_\_
- 17. G/T \_\_\_\_\_

e-o Receiver

- 1. Nomenclature \_\_\_\_\_
- 2. Wavelength \_\_\_\_\_
- 3. Detector Type \_\_\_\_\_
- 4. Sensitivity and Basis \_\_\_\_\_
- 5. RF Susceptibility \_\_\_\_\_
- 6. Coherent/Incoherent \_\_\_\_\_
- 7. Detector Noise Voltage \_\_\_\_\_

IV. EARTH STATION ANTENNA

Class/  
Release/  
Source

A. Administrative

1. Equipment Nomenclature

\_\_\_\_\_

\_\_\_\_\_

2. Operating Agency

\_\_\_\_\_

\_\_\_\_\_

3. Transmit Mode

\_\_\_\_\_

\_\_\_\_\_

4. Receive Mode

\_\_\_\_\_

\_\_\_\_\_

5. Manufacturer

\_\_\_\_\_

\_\_\_\_\_

IV. EARTH STATION ANTENNA

Class/  
Release/  
Source

B. Physical

- |                             |       |       |
|-----------------------------|-------|-------|
| 1. Antenna Type             | _____ | _____ |
| 2. Antenna Dimensions       | _____ | _____ |
| 3. Horizontal Arc Scanned   | _____ | _____ |
| 4. Vertical Arc Scanned     | _____ | _____ |
| 5. Feedpoint Height         | _____ | _____ |
| 6. Azimuth Pointing Angle   | _____ | _____ |
| 7. Elevation Pointing Angle | _____ | _____ |

IV. EARTH STATION ANTENNA

Class/  
Release/  
Source

C. Technical

- |   |       |       |
|---|-------|-------|
| 1. Gain                                     | _____ | _____ |
| 2. Gain Pattern (Use figure if available)   | _____ | _____ |
| Angle Off Boresight/Relative Level          | _____ | _____ |
| 3. Polarization/Polarization Discrimination | _____ | _____ |
| 4. Type of Illumination                     | _____ | _____ |
| 5. Efficiency                               | _____ | _____ |
| 6. Antenna Noise Temperature                | _____ | _____ |
| 7. Horizontal Beamwidth                     | _____ | _____ |
| 8. Vertical Beamwidth                       | _____ | _____ |
| 9. Optics:                                  |       |       |
| Tranmittance                                | _____ | _____ |
| Aperture Diameter                           | _____ | _____ |
| Field of View                               | _____ | _____ |
| Beam Divergence                             | _____ | _____ |

V. SPACE STATION ANTENNA

Class/  
Release/  
Source

A. Administrative

1. Equipment Nomenclature
2. Operating Agency
3. Transmit Mode
4. Receive Mode
5. Manufacturer

_____	_____
_____	_____
_____	_____
_____	_____
_____	_____

V. SPACE STATION ANTENNA

Class/  
Release/  
Source

B. Physical

- |                                      |       |       |
|--------------------------------------|-------|-------|
| 1. Antenna Type                      | _____ | _____ |
| 2. Antenna Dimensions                | _____ | _____ |
| 3. Beam Type (spot, global,<br>etc.) | _____ | _____ |
| 4. Position in X,Y,Z<br>Coordinates  | _____ | _____ |
| 5. Antenna Feed                      | _____ | _____ |

Class/  
Release/  
Source

V. SPACE STATION ANTENNA

C. Technical

- |   |       |       |
|---|-------|-------|
| 1. Gain                                     | _____ | _____ |
| 2. Gain Pattern (Use figure if available)   | _____ | _____ |
| Angle Off Boresight/Relative Level          | _____ | _____ |
| 3. Polarization/Polarization Discrimination | _____ | _____ |
| 4. Type of Illumination                     | _____ | _____ |
| 5. Efficiency                               | _____ | _____ |
| 6. Antenna Noise Temperature                | _____ | _____ |
| 7. Horizontal Beamwidth                     | _____ | _____ |
| 8. Vertical Beamwidth                       | _____ | _____ |
| 9. Optics:                                  |       |       |
| Transmittance                               | _____ | _____ |
| Aperture Diameter                           | _____ | _____ |
| Field of View                               | _____ | _____ |
| Beam Divergence                             | _____ | _____ |

VI. MODULATION DESCRIPTION

Class/  
Release/  
Source

A. Analog

- |   |       |       |
|---|-------|-------|
| 1. Modulation Type  | _____ | _____ |
| 2. Baseband Signal Description                              | _____ | _____ |
| 3. FM   | _____ | _____ |
| a. Peak Deviation   | _____ | _____ |
| b. Freq. Limits of Modulating Signal                        | _____ | _____ |
| c. Pre-emphasis/De-emphasis                                 | _____ | _____ |
| 4. FDM/FM   | _____ | _____ |
| a. Number of Voice Channels                                 | _____ | _____ |
| b. Frequency Limits of FDM Baseband                         | _____ | _____ |
| c. Peak Carrier Deviation                                   | _____ | _____ |
| d. Pre-emphasis/De-emphasis                                 | _____ | _____ |
| e. RMS Deviation  | _____ | _____ |
| 5. TV   | _____ | _____ |
| a. Baseband Modulation (TV System) (e.g., PAL, SECAM, NTSC) | _____ | _____ |
| 6. AM   | _____ | _____ |
| a. Modulation Index   | _____ | _____ |

VI. MODULATION DESCRIPTION

Class/  
Release/  
Source

B. Digital

- |                                |       |       |
|--------------------------------|-------|-------|
| 1. Modulation Type             | _____ | _____ |
| 2. Baseband Signal Description | _____ | _____ |
|                                | _____ | _____ |
|                                | _____ | _____ |
|                                | _____ | _____ |
| 3. Information Rate            | _____ | _____ |
| 4. Signalling Rate             | _____ | _____ |
| 5. Applied Coding              | _____ | _____ |



VI. MODULATION DESCRIPTION

Class/  
Release/  
Source

D. Pulsed Systems

- |                                |       |       |
|--------------------------------|-------|-------|
| 1. Pulse Width                 | _____ | _____ |
| 2. Pulse Rise Time             | _____ | _____ |
| 3. Pulse Fall Time             | _____ | _____ |
| 4. Pulse Repetition Rate       | _____ | _____ |
| 5. Frequency Deviation on Rise | _____ | _____ |
| 6. Frequency Deviation on Fall | _____ | _____ |
| 7. Chirped Frequency Shift     | _____ | _____ |

Class/  
Release/  
Source

VII. ACCESS MODES

A. TDMA

- 1. Frame Rate \_\_\_\_\_
- 2. Preamble Length \_\_\_\_\_
- 3. Preamble Rate \_\_\_\_\_
- 4. Slot Length \_\_\_\_\_
- 5. Number of Slots \_\_\_\_\_
- 6. Guardband \_\_\_\_\_

B. FDMA\*

- 1. Number of Channels \_\_\_\_\_
- 2. Channel Bandwidth \_\_\_\_\_
- 3. Channel Spacing \_\_\_\_\_

C. CDMA or SSMA

- 1. Code Length \_\_\_\_\_
- 2. Number of Users (nets) \_\_\_\_\_
- 3. Code Rate \_\_\_\_\_
- 4. Code Type \_\_\_\_\_

D. OTHER TYPE

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

\* If channel bandwidths and spacing are not uniform, attach description

GLOSSARY  
TRANSMITTER PARAMETERS

Access Mode - method by which a communications satellite accommodates multiple network users, i.e., TDMA, FDMA, etc.

Average Power - the power delivered to the transmitter output averaged over a modulation cycle.

Bandwidth - difference between the frequencies at which attenuation is less than a specified amount.

Baseband - the band of frequencies occupied by the signal before it modulates the carrier frequency to form the transmitted radio signal.

Chirp Frequency Shift - difference between the maximum and minimum frequencies of a chirped pulse.

Data Rate - baseband digital information rate (bits per second).

Downlink Mode - spot beams, b'cast, etc.

Emissions Description - a set of relative power levels at frequencies offset from the carrier frequency.

Filter Type - generic circuit type used in filter construction (for example: Butterworth, Elliptical, etc.).

Frequency Limits of Modulating Signal - baseband bandwidth of input signal.

Harmonic Attenuation - relative level of emissions (amount of suppression of output signal) at multiples of the desired output frequency.

Margin - excess of received signal levels beyond that needed for proper operation.

Modulation - method of modifying some characteristics(s) (phase, frequency, or amplitude) of a wave to correspond to some other wave or data.

Noise Floor - minimum noise output of a system.

Operating Mode - designation to identify a method in which the system can be used.

Output Device - final stage power amplification device (for example: travelling wave tube).

Peak Power - (for pulsed systems) mean output power during pulse duration.

Pole - value for which the network function of a circuit is infinite.

Pre-Emphasis - a process that emphasizes the magnitude of some frequency components in order to reduce adverse affects such as noise.

Pulse Repetition Frequency - rate (in Hz or pps) at which pulses are transmitted.

Pulsewidth - time interval between points on the leading and trailing edge of a pulse which are  $\frac{1}{2}$  the peak pulse amplitude.

Q - quality factor, ratio of resonant frequency to 3 dB bandwidth.

RF Filter - final filter at the output of the transmitter.

Rise Time (fall time) - time interval required for the pulse to rise (fall) from 10% to 90% (90% to 10%) of its peak amplitude.

Roll-Off (fall-off) - rate of increasing attenuation of an emissions spectrum with frequency.

Signalling Rate - actual rate of transmitting modulated pulses. (Symbols per second.)

Spurious Attenuation - amount of suppression of output signal (relative level of emissions) outside the bandwidth sufficient to ensure the desired transmission (excluding harmonics).

Stretched Compression Pulse Width Indicator - (RADAR) coding and processing of a single pulse of long duration to one of short duration and high range resolution.

Symbol - a transmitted, modulated, pulse.

System Data Rate - total throughput of satellite system given in either bps, equivalent video circuits, or equivalent voice channels.

Usage Factor - communications systems: ratio of utilized information transmission capability to that available. Other systems: fraction of utilized operational time.

#### RECEIVER PARAMETERS

Access Mode - method by which a communications satellite accommodates multiple network users, i.e., TDMA, FDMA, etc.

Baseband Bandwidth - frequency difference between the 3 dB points of the information bearing signal.

Equivalent Satellite Link Noise Temperature - noise temperature at the input of the earth station receiver. Corresponds to the RF noise power which produces the total observed noise at the output of the satellite link.

G/T - radio station figure-of-merit. Ratio of antenna gain-to-equivalent noise temperature of receiver system.

IF Stage - frequency translation and filtering circuit.

Image Rejection - rejection at a frequency separated from the tuned frequency by twice the IF frequency. The image frequency may be above or below the tuned frequency depending on whether the local oscillator frequency is above or below the tuned frequency.

Modulation - method of wave modification that an equipment is designed to receive.

Noise Equivalent Power - the value of radiation which produces, in the detector, an RMS S/N ratio of one.

Noise Figure - measure of the noise added to an input signal by a receiver.

Off-Frequency - a given frequency separation from the tuned frequency.

Pole - value for which the network function of a circuit is infinite.

Processing - on-board signal manipulation.

Processing Mode - description of on-board signal handling (for example: regenerative repeater).

Required Signal-to-Noise (S/N) Ratio - S/N needed for proper signal processing at a specific point.

Relative Level - rejection compared to minimum (in-band) case.

RF Bandwidth - difference between the frequencies at which RF filter rejection is less than 3 dB.

Roll-Off (fall-off) - rate of increasing signal rejection of receiver selectivity, with respect to frequency.

Sensitivity - minimum input signal level required to produce an output having a given S/N. Lower limit of useful input signal power.

Sensitivity Criteria - method or threshold used to determine receiver sensitivity.

Spurious Rejection - relative rejection level for signals outside the bandwidth sufficient to ensure the desired reception.

System Bandwidth - total bandwidth of all on-board receivers.

Transmittance - ratio of flux emerging to flux incident.

#### ORBITAL PARAMETERS

Active Portion of Orbit - for non-geosynchronous satellites, the amount of time during each orbit when RF links(s) are active.

Anomaly - angle from the focus of the orbital ellipse between the line of the apsides of the orbit and the point of closest approach to the focus, in the direction of travel. Also, true anomaly.

Apogee - orbital point most distant from center of earth.

Argument of the Perigee - angle from the ascending node to the perigee along the path of the orbit in the direction of spacecraft motion.

Ascending Node - point (longitude) where the satellite crosses the equatorial plane from the southern to the northern hemisphere.

Epoch - time at which specified orbital parameters are valid.

Geostationary Orbit - nominally circular satellite orbit having a period of one day and an orbital inclination of zero.

Geosynchronous Orbit - satellite orbit where the period is one day.

Longitude (for Geosynchronous satellites) - longitude in degrees referenced to the prime meridian of the point on the equator directly beneath the satellite (also "orbital slot").

Longitude of Ascending Node - see ascending node.

Mean Anomaly - angle that would be described by the radius vector had it moved uniformly at the average angular motion.

Mean Motion Rate - average angular velocity of satellite ( $360^\circ$  divided by the satellite period).

Nodal Period - time to complete one orbit.

Non-Geosynchronous or Non-Geostationary Orbit - orbit where the period does not equal one day.

Orbital Eccentricity - for elliptical orbits, a measure of the "flatness" of the ellipse. The ratio of the distance from the center of the ellipse to the focus and the length of the semi-major axis.

Orbital Inclination - angle between the orbital plane and the earth's equatorial plane. Measured at point where satellite passes from southern to northern hemisphere.

Perigee - orbital point closest to center of earth.

Right Ascension of Ascending Node - angular distance along the celestial equator from the vernal equinox eastward to the point where the satellite passes from the southern to northern hemisphere.

Semi-Latus Rectum - distance, on a line perpendicular to the major axis, from the focus to the orbital ellipse.

Station Keeping Limits (for Geosynchronous Satellites) - tolerance of the satellites's position in the North/South and East/West directions.

Time of Perigee Passage - epoch when satellite passes through the perigee.

#### MODULATION PARAMETERS

Channel Spacing - separation between center frequencies of FH channels.

Chirp (Pulsed FM) Spread Spectrum - sweeping of an FM carrier over a wide frequency band during a pulse interval.

Code Length - block length of PN code.

De-Emphasis - process of restoring pre-emphasized signals.

Direct Sequence Spread Spectrum - modulation of a carrier by a digital code sequence whose chirp rate is much higher than the information bandwidth.

Frequency Division Multiplexing/Frequency Modulation (FDM/FM) - FM transmission of a group of voice channels multiplexed together.

Frequency Hopping Spread Spectrum - shifting of the carrier frequency to preset channels in a pattern set by a code sequence.

Frequency Modulation (FM) - modulation of a sine-wave carrier so that its instantaneous frequency differs from the carrier frequency by an amount proportional to the instantaneous amplitude of the modulating signal.

Frequency Sweep - difference in frequency limits through which a chirped pulse is swept.

Gate Length - period during which system is turned on.

Hop Rate - rate at which FH system jumps from one channel to another.

Modulation - method of modifying some characteristic(s) (phase, frequency, or amplitude) of a wave to correspond to some other wave or data.

Peak Deviation - maximum frequency difference in FM systems between the instantaneous frequency and the carrier frequency.

Period - time between successive gates or pulses.

Pre-Emphasis - a process that emphasizes the magnitude of some frequency components to reduce adverse effects such as noise.

Pseudonoise (PN) Code - a binary sequence with a desirable trans-orthogonal auto-correlation property.

Processing Gain - improvement in S/N obtained by decoding spread spectrum mode transmissions.

Spread Spectrum - transmission of an information-bearing signal over a bandwidth wider than necessary.

ANTENNA PARAMETERS

Antenna Noise Temperature - the average temperature of all noise sources in the antenna pattern.

Beamwidth - angle between which the antenna gain is within a given amount relative to the maximum gain.

Divergence - rate of beam spreading.

Efficiency - ratio of total power output by the antenna to the power received.

Gain - ratio of output power radiated (or received) in a given direction to that which would be radiated (or received) by an isotropic antenna.

Polarization - description of the electric vector transmitted from an antenna (or which an antenna is designed to receive).

ACCESS MODE PARAMETERS

Code Division Multiple Access (CDMA) - communication through use of difference codes at a common carrier frequency.

Frame Rate - in TDMA systems, time between bursts of a given user.

Frequency Division Multiple Access (FDMA) - communication through use of difference frequency bands within a common repeater.

Guardband - in TDMA, time between slots; in FDMA, unused frequency between channels.

Preamble - in TDMA systems, synchronization, acquisition, and bit timing information.

Slot Length - in TDMA systems, burst times for individual system users.

Time Division Multiple Access (TDMA) - communication through non-overlapping time-sequenced bursts of transmissions through a common repeater.

Symbol Rate - channel output signaling rate.

Synchronization Type - method of acquiring and maintaining synchronization.

Sweep Time - pulse time in a chirped system.

Time Hopping Spread Spectrum - pulsing of output signal controlled by a PN code.

SOURCES FOR DEFINITIONS

Space Flight Handbooks, Volume 1: Orbital Flight Handbook, NASA SP33,  
Washington DC, 1963, (NTIS # N63-21101).

Bate, R., Mueller, D., White, J., Fundamentals of Astrodynamics, Dover Inc.,  
1971.

Rocca, R., Jr., Satellite Handbook, ECAC-HDBK-78-17, March 1978.

International Telecommunication Union, Radio Regulations, Geneva, Switzerland,  
rev 1981.

Jay, F., Ed., IEEE Standard Dictionary of Electrical and Electronics Terms,  
Second Edition, ANSI/IEEE Std 100-1977, Wiley-Interscience, 1978.

National Telecommunications and Information Administration, Manuel of  
Regulations and Procedures for Federal Radio Frequency Management, Washington,  
DC, 1980.

Lapedes, D., Ed., Dictionary of Scientific and Technical Terms, McGraw-Hill,  
1978.

Grat, R., Modern Dictionary of Electronics, Howard W. Sams & Co., Inc., 1970.

ATE  
LMED  
8