

AD A121669

AD-F 300/28

AD

TECHNICAL REPORT ARBRL-TR-02438

FORM-FUNCTIONS FOR THE IBHYG CODE

Franz R. Lynn

November 1982

DTIC
ELECTE
NOV 19 1982
A



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

DTIC FILE COPY

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U. S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute endorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Technical Report ARBRL-TR- 02438	2. GOVT ACCESSION NO. AD-A121669	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Form-Functions for the IBHVG Code		5. TYPE OF REPORT & PERIOD COVERED Technical Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Franz R. Lynn		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Ballistic Research Laboratory ATTN: DRDAR-BLI Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L162618AH80
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory Aberdeen Proving Ground, MD. 21005		12. REPORT DATE November 1982
		13. NUMBER OF PAGES 52
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		16. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Interior Ballistic Calculations Form-Functions Propellant Grain Geometries		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) mab The form-functions, methods of calculating the mass fraction burned given the depth burned, are developed for the ten propellant grain geometries available in the IBHVG code, a frequently used interior ballistic computer program. The FORTRAN coding embodying the computations is included.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	5
I. INTRODUCTION.	7
II. SUBROUTINE ORGANIZATION	8
III. GRAIN TYPE 1: SEVEN-PERFORATED CYLINDER.	8
IV. GRAIN TYPE 2: SINGLE-PERFORATED CYLINDER	12
V. GRAIN TYPE 3: CORD	13
VI. GRAIN TYPE 4: RECTANGULAR STRIP.	14
VII. GRAIN TYPE 5: SPHERE	15
VIII. GRAIN TYPE 6: SLOTTED TUBE	15
IX. GRAIN TYPES 7, 8, AND 10: ROUNDED-HEXAGONAL.	18
X. GRAIN TYPE 9: NINETEEN-PERFORATED CYLINDER	25
REFERENCES.	28
APPENDIX A: LISTING OF FORM-FUNCTION SUBROUTINES . . .	29
APPENDIX B: LIST OF SYMBOLS.	39
DISTRIBUTION LIST	43



Acquisition For	
DTIC GRAAL	☒
DTIC TAB	☐
Unannounced	☐
Justification	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

LIST OF ILLUSTRATIONS

Figure	Page
1. Seven-Perforated Grain -- End View	9
2. Slotted Tube Grain -- End View	16
3. One-Sixth of Hex Grain -- End View	19
4. Hex Grain -- Inner Sliver	21
5. Hex Grain -- Outer Sliver	22
6. Nineteen-Perforated Grain -- End View	26

I. INTRODUCTION

This report documents the form-functions developed for the interior ballistics computer code Interior Ballistics of High-Velocity Guns (IBHVG), a FORTRAN program used in the Interior Ballistics Division of the Ballistic Research Laboratory. IBHVG, based on the Baer-Frankle code¹, will itself be the subject of a forthcoming report.

A "form-function" is any computational scheme for determining either surface area, volume, or fraction burned for a burning propellant grain at any instant from ignition to extinction based on initial dimensions and depth burned. Either surface area or fraction burned is generally required in interior ballistic calculations. The IBHVG code does not use surface area so the form-functions described below omit area derivation. Also, the traditional assumptions are made that all grain surfaces erode at the same rate and all the perforations are of equal diameter.

A variety of approaches to a number of grain geometries have been taken in the past^{2,3}. Stals, for example, not only deals with detailed analyses of different grain types, but contains a wealth of background information, history of attacks to the problem, and an extensive bibliography. While this report does not attempt to supplant previous efforts, it presents some novel treatments which may prove applicable to codes other than IBHVG. For example, the analyses of the seven- and nineteen-perforated cases are based on a method of dealing with general cylindrical grains⁴. This method enables handling grains with unequal webs.

The FORTRAN coding embodying the methods of calculations will be discussed in parallel with the development of all algorithms for ease of

¹P. G. Baer, and J. M. Frankle, "The Simulation of Interior Ballistic Performance of Guns by Digital Computer Program," USA Ballistic Research Laboratories Report 1183, USA Ballistic Research Laboratories, APG, MD, December 1962.

²J. Corner, "Theory of the Interior Ballistics of Guns," John Wiley & Sons, New York, 1950, pp. 30-35.

³J. Stals, "Form-Functions for Multicomponent Propellant Charges Including Inhibited Grains and Sliver Burn," Materials Research Laboratories Technical Note 371, Materials Research Laboratories, Maribyrnong, Victoria, Australia, September 1976.

⁴F. R. Lynn, "Development of General Form-Functions for Multiperforated Cylindrical Propellant Grains," Ballistic Research Laboratory Memorandum Report ARBRLMR03014, Ballistic Research Laboratory, USA ARRADCOM, APG, MD, March 1980.

understanding. Also, FORTRAN computational hierarchy is followed throughout the text. A comprehensive listing of the referenced subroutines will be found in APPENDIX A.

II. SUBROUTINE ORGANIZATION

The result of the form-function calculations in IBHVG is the fractions burned, at any instant, for the M propellants comprising the charge, where $1 < M < 5$. At each time step, a call is made to a single subroutine, FORMT, which either performs the required operations or, in the case of seven- or nineteen-perforated grains, calls auxiliary routines GENIS and GENOS. APPENDIX A contains listings for these three subroutines.

APPENDIX B notes all important input, output, and control variables used. Most are passed through COMMON, although a few are local. No other COMMON variables pertain to FORMT operation.

Subroutine FORMT is called whenever the calling program requires the fractions burned, the Z array, of the M propellants being burned. A glance at the listing reveals that FORMT is essentially one large loop, processing each of the M propellants in turn. All computations for the Jth propellant are bypassed if either it is entirely consumed, that is,

$$Z(J) \geq 1$$

or if logic elsewhere in IBHVG dictates that the condition flag

$$ICFLAG(J) = 0$$

which signifies that the ignition criterion for the Jth propellant has not been met. However, if the propellant has ignited but is not yet completely burned, execution continues. The depth burned for propellant J is extracted from the Y array, having been calculated elsewhere prior to entrance to FORMT, and twice this value is stored in U. Next, N(J), the grain code for propellant J in Table 1 is examined, and a branch taken to the appropriate area of FORMT. There, the fraction burned, Z(J), is determined based on U, initial grain dimensions, and various control variables, followed by a jump to the bottom of the loop. After all M propellants have been processed, a return is made from FORMT to the calling routine.

As Table 1 notes, there are ten different grain types dealt with by IBHVG. The remainder of the report will be concerned with considering the types in turn, devising a method of finding Z for them at any instant, and developing the FORMT coding based on these calculations.

III. GRAIN TYPE 1: SEVEN-PERFORATED CYLINDER

An end view of this grain appears in Figure 1. It is a cylinder pierced longitudinally by seven cylindrical holes arranged at the center




Figure 1. Seven-Perforated Grain -- End View

TABLE 1. IBHVG GRAIN GEOMETRIES AND CODES

<u>GRAIN CODE</u>	<u>GEOMETRY</u>
1	7-perforated cylinder
2	1-perforated cylinder
3	cord
4	rectangular strip
5	sphere
6	slotted tube
7	37-perforated hexagonal
8	19-perforated hexagonal
9	19-perforated cylinder
10	7-perforated hexagonal

and vertices of a regular hexagon. Initially, suppose the grain to have length $GL(J)$, diameter $D(J)$, perforation diameter $PD(J)$, inner web $WI(J)$, and outer web $WO(J)$.

On the first call to FORMT, i.e., at the beginning of the first time step, COMMON variable I is set to 0. On succeeding passes, I will be greater than zero, thereby forcing a branch to line 50, bypassing the initialization section which is described next.

First, the middle web, $WM(J)$ is zeroed as it is not used by this grain type. Then the diameter is recomputed to absorb any inconsistencies in grain dimensions. Figure 1 makes the calculation

$$D(J) = 3 \cdot PD(J) + 2 \cdot (WI(J) + WO(J)), \quad (1)$$

clear. Next, the initial grain volume is determined and stored in $VO(J)$. The end area, E , of the grain is given by

$$E = \pi/4 \cdot D(J)^2 - 7 \cdot \pi/4 \cdot PD(J)^2, \quad (2)$$

so the initial volume is

$$\begin{aligned} VO(J) &= GL(J) \cdot E \\ &= .25 \cdot \pi \cdot GL(J) \cdot (D(J)^2 - 7 \cdot PD(J)^2). \end{aligned} \quad (3)$$

Note that we assume π is passed through COMMON Variable PI.

The method developed in Reference 4 is employed and, in what follows, its notation and nomenclature are used freely. For purposes of calculating the end-area of the grain, it is partitioned into one class of

outer slivers congruent to ABDC and one class of inner slivers congruent to OAB.

Array IFLAG is the branch-flag array and two positions are initialized to -1 for this, the Jth propellant.

Array SF is the "side" array. Letting

$$WW = WI(J) + PD(J) \quad (4)$$

represent the distance between centers of adjacent perforations, all three sides of each sliver in both classes are set to length WW.

The last calculation in the initialization section is the determination of the grain's web, the shortest distance through the grain to be broached as the grain burns. This is given by

$$WEBC(J) = \min (WO(J), WI(J), GL(J)), \quad (5)$$

the length being included to account for very short grains.

The post-initialization coding starts at line 50. The reduced grain length, reduced grain diameter, and increased perforation diameter are

$$\begin{aligned} GRL &= \max (GL(J) - U, 0) \\ OD &= D - U \\ PRFD &= PD + U, \end{aligned} \quad (6)$$

respectively, the maximum being taken to guarantee a non-negative grain length. If

$$0 \leq U \leq WEBC(J),$$

the web is not broached and we determine end-area of the grain, E, by the same method as in the initialization section, so

$$E = \pi/4 \cdot OD^2 - 7 \cdot \pi/4 \cdot PRFD^2 \quad (7)$$

yielding

$$Z(J) = 1 - GRL \cdot E/VO(J). \quad (8)$$

However, if

$$\text{WEBC}(J) < U,$$

we branch to line 60 and employ routines GENIS and GENOS as described in Reference 4 with one minor modification. Since IBHVG does not use grain surface area, the argument to return that quantity is not present in the call and the coding in GENIS and GENOS which yields sliver surface area is commented out as can be seen from APPENDIX A. The AW array is the work array and sliver volumes for the inner and outer slivers of the Jth propellant are returned through the appropriate cells in array GV. Total sliver volume of a given class is six times the volume of each sliver, yielding

$$Z(J) = 1 - 6 \cdot (GV(1,J) + GV(2,J))/VO(J). \quad (9)$$

A branch is then made to the bottom of the loop.

IV. GRAIN-TYPE 2: SINGLE-PERFORATED CYLINDER

Initially, this grain is a cylinder of length $GL(J)$ and diameter $D(J)$ pierced by a cylindrical hole of diameter $PD(J)$, the centers of the two cylinders coinciding. Let the web be $WI(J)$.

As with the case of the seven-perforated cylinder, an initialization section is processed if $I = 0$. The middle web, $WM(J)$, and outer web, $WO(J)$, are zeroed as they are unused and the diameter recalculated as

$$D(J) = PD(J) + 2 \cdot WI(J), \quad (10)$$

to absorb any error in grain dimensions. Then

$$\text{WEBC}(J) = \min(WI(J), GL(J)) \quad (11)$$

is twice the depth burned at grain extinction. Letting E represent the initial end area of the grain, we have

$$E = \pi/4 \cdot D(J)^2 - \pi/4 \cdot PD(J)^2, \quad (12)$$

and the initial volume is

$$\begin{aligned} VO(J) &= GL(J) \cdot E \\ &= \pi/4 \cdot GL(J) \cdot (D(J)^2 - PD(J)^2). \end{aligned} \quad (13)$$

The factor $\pi/4$ is not present in the coding as it will cancel in the calculation of $Z(J)$.

The post-initialization coding starts at line 190. The end-area, E , of the grain burned to a depth of $1/2 U$ must be determined. First, it is cleared by

$$E = 0.$$

If

$$0 \leq U \leq WEBC(J),$$

then we override this value of zero for E . The reduced grain length, reduced grain diameter, and increased perforation diameter are

$$\begin{aligned} GL(J) - U \\ D(J) - U \\ PD(J) + U, \end{aligned}$$

respectively, so, as above,

$$\begin{aligned} E &= \pi/4 \cdot (D(J) - U)^2 - \pi/4 \cdot (PD(J) + U)^2 \\ &= \pi/4 \cdot ((D(J) - U)^2 - (PD(J) + U)^2), \end{aligned} \quad (14)$$

and fraction burned is

$$Z(J) = 1 - E \cdot (GL(J) - U) / VO(J). \quad (15)$$

Note that the factor $\pi/4$ in the calculation of E is absent in the coding as it would cancel in the $Z(J)$ calculation.

V. GRAIN TYPE 3: CORD

Initially, this grain is a solid cylinder with length $GL(J)$ and diameter $D(J)$.

If COMMON variable I=0, indicating the first call to FORMT, an initialization section is processed. The perforation diameter and inner, middle, and outer webs are zeroed for this, the Jth propellant, as these quantities are unused. The initial volume

$$VO(J) = GL(J) \cdot \pi/4 \cdot D(J)^2 \quad (16)$$

is that of a right circular cylinder. In the coding, the $\pi/4$ is omitted because it will cancel in the calculation of Z(J).

Post-initialization code starts at line 220. The reduced grain dimensions

GL(J)-U
D(J)-U

are used to produce the fraction burned

$$Z(J) = 1 - \max(GL(J)-U, 0) \cdot \max(D(J)-U, 0)^2 / VO(J) \quad (17)$$

where the $\pi/4$ factor is absent, having cancelled with a like factor in VO(J).

VI. GRAIN TYPE 4: RECTANGULAR STRIP

Initially, this grain is a solid rectangular parallelepiped with length GL(J) width D(J), and depth WI(J).

As above, variable I = 0 signals processing of an initialization section. First, all grain dimensions not used are zeroed and the initial grain volume

$$VO(J) = GL(J) \cdot D(J) \cdot WI(J), \quad (18)$$

is determined.

The post-initialization code starts at line 440. The reduced grain dimensions, namely,

GL(J)-U
D(J)-U
WI(J)-U,

are multiplied together to produce the volume. And thus the fraction burned is

$$Z(J) = 1 - \max(GL(J)-U) \cdot \max(D(J)-U) \cdot \max(WI(J)-U)/VO(J) \quad (19)$$

where the maxima are taken with 0 to guarantee a non-negative grain volume.

VII. GRAIN TYPE 5: SPHERE

Initially, this grain is a solid sphere of diameter $D(J)$.

On the initialization pass, signaled by $I = 0$, all grain dimensions except grain diameter are zeroed because they are unused.

The reduced grain diameter is

$$D(J)-U.$$

Thus fraction burned is

$$\begin{aligned} Z(J) &= 1 - 1/6 \cdot \pi \cdot \max(D(J) - U, 0)^3 / (1/6 \cdot \pi \cdot D(J)^3) \quad (20) \\ &= 1 - (\max(D(J) - U, 0)/D(J))^3, \end{aligned}$$

where the maximum is taken to guarantee a non-negative reduced grain diameter.

VIII. GRAIN TYPE 6: SLOTTED TUBE

An end view of this grain appears in Figure 2. It is an ordinary single-perforated grain with a slot, the sides of which are parallel. Initially, suppose the grain to have length $GL(J)$, diameter $D(J)$, web $WI(J)$, perforation diameter $PD(J)$, and slot width $WM(J)$.

As with the other grain types, an initialization section is processed if COMMON variable $I = 0$. First, the unused dimension $WO(J)$ zeroed. Let

$$PRFD = .5 \cdot WM(J), \quad (21)$$

be half the slot width,




Figure 2. Slotted Tube Grain -- End View

$$SO = .5 \cdot D(J), \quad (22)$$

be the grain radius, and

$$SI = .5 \cdot PD(J), \quad (23)$$

be the perforation radius. In right triangles OBD and OAC we have

$$\begin{aligned} \theta &= \pi/2 - \arccos(PRFD/SO) \\ \alpha &= \pi/2 - \arccos(PRFD/SI), \end{aligned} \quad (24)$$

respectively. As before, the code assumes PI contains π . Denote by E the end-area of the grain; then

$$\begin{aligned} E &= \text{area reflex sector BOF} \\ &\quad - \text{area reflex sector AOE} \\ &\quad - 2 \cdot \text{area triangle AOB} \\ &= 1/2 \cdot (2\pi - 2\theta) \cdot SO^2 - 1/2 \cdot (2\pi - 2\alpha) \cdot SI^2 \\ &\quad - 2 \cdot 1/2 \cdot PRFD \cdot (SO \cdot \cos(\theta) - SI \cdot \cos(\alpha)) \\ &= (\pi - \theta) \cdot SO^2 - (\pi - \alpha) \cdot SI^2 \\ &\quad - PRFD \cdot (SO \cdot \cos(\theta) - SI \cdot \cos(\alpha)). \end{aligned} \quad (25)$$

Thus initial volume is

$$VO(J) = GL(J) \cdot E. \quad (26)$$

Finally,

$$WEBC(J) = \min(GL(J), WI(J)), \quad (27)$$

is twice the depth burned at grain extinction.

The post-initialization section of coding starts at line 510. The end-area of the grain, E, is cleared by

$$E = 0.$$

If

$$WEBC(J) < U,$$

then the grain is extinguished and a branch is taken to line 520, producing a fraction burned of 1. Otherwise, let

$$PRFD = .5 \cdot (WM(J) + U), \quad (28)$$

be half the new slot width,

$$SO = .5 \cdot (D(J) - U), \quad (29)$$

be reduced grain radius,

$$SI = .5 \cdot (PD(J) + U) \quad (30)$$

be perforation radius, and

$$GRL = GL(J) - U, \quad (31)$$

be reduced grain length. Then θ , α , and E are calculated as done in the initialization section and fraction burned is

$$Z(J) = 1 - E \cdot GRL/VO(J). \quad (32)$$

IX. GRAIN TYPES 7, 8, AND 10: ROUNDED-HEXAGONAL

Figure 3 depicts one-sixth of a rounded-hexagonal grain with nineteen perforations. Let grain length be $GL(J)$, all inner webs be $WI(J)$, the outer web $WO(J)$, and perforation diameter $PD(J)$. Note that the rounded "corners" are bounded by inside and outside circular arcs of radii $1/2 \cdot PD(J)$ and $WO(J) + 1/2 \cdot PD(J)$, respectively, as shown in sector CDE.

The 7-, 19- and 37-perforated hexagonal grains are but special members of a family. By induction on K, the number of hexagonal rings of perforations, we have

$$\begin{aligned} NP &= \text{number of perforations} = 3K^2 + 3K + 1 \\ SI &= \text{number of inner slivers} = 6K^2 \\ SO &= \text{number of outer slivers} = 6K \\ &\quad \text{number of corner slivers} = 12, \end{aligned} \tag{33}$$

for $K > 0$. The inner slivers are all congruent to the area within ABC, the outer slivers to the area within BCEF, and the corners to CDE. Routine FORMT currently handles cases $K = 1, 2$, and 3 yielding, respectively, $NP = 7, 19$, and 37 , $SI = 6, 24$, and 54 , and $SO = 6, 12$, and 18 .

Entry for hex grains is made at statements 240, 250, or 600 in FORMT where SO and SI are set to the appropriate values and a branch taken to line 260. Here WW is the distance between centers of adjacent perforations and WW2 is its square, PRFD is the increased perforation diameter and PRFD2 its square, GRL is the reduced grain length, and WOD is the outer web. The end area of the grain, E, is initially cleared to zero.

Figure 4 shows an inner sliver during burning. By definition of cosines,

$$\begin{aligned} \theta &= 2 \cdot \text{acos}(\min(1, CL/CJ)) \\ &= 2 \cdot \text{acos}(\min(1, WW/PRFD)), \end{aligned} \tag{34}$$

where the minimum is taken with 1 in case θ is degenerate. Figure 5 shows an outer sliver burning. By definition of cosines,

$$\begin{aligned} \alpha &= \text{acos}(\min(1, EC/CM)) \\ &= \text{acos}(\min(1, (PD(J) + 2 \cdot WOD - U)/PRFD)), \end{aligned} \tag{35}$$

where the minimum is taken with 1 in case α is degenerate. These angles are sufficient to calculate E.

Consider the twelve corners. If

$$WOD \leq U,$$

they are completely consumed and their contribution to E is zero.




Figure 4. Hex Grain -- Inner Sliver




Figure 5. Hex Grain -- Outer Sliver

Otherwise, by subtracting the area of concentric circular sectors, and recalling that π is in PI,

$$\begin{aligned}
 E &= 12 \cdot (1/2 \cdot \pi/6 \cdot (1/2 \cdot PD(J) + WOD - 1/2 \cdot U)^2 \quad (36) \\
 &\quad - 1/2 \cdot \pi/6 \cdot (PRFD/2)^2 \\
 &= .25 \cdot \pi \cdot ((PD(J) + 2 \cdot WOD - U)^2 - PRFD^2).
 \end{aligned}$$

Consider now the inner slivers. A DATA statement provides values of square root of 3 in RT and $\pi/3$ in PI3, variables required for the remainder of this analysis. If

$$\pi/3 \leq \theta,$$

then all inner slivers are consumed so a branch is taken to line 270. Otherwise, the area contribution of the SI inner slivers must be added to E. Hence, referring to Figure 4,

$$\begin{aligned}
 E &= E + SI \cdot (\text{area inner sliver}) \quad (37) \\
 &= E + SI \cdot (\text{area triangle ABC} - 3 \cdot \text{area triangle JBC} \\
 &\quad - 3 \cdot \text{area sector JCK}) \\
 &= E + SI \cdot (1/2 \cdot WW \cdot (1/2 \cdot WW \sqrt{3}) \\
 &\quad - 3 \cdot 1/2 \cdot WW \cdot (1/2 \cdot PRFD \cdot \sin(\theta/2)) \\
 &\quad - 3 \cdot 1/2 \cdot (\pi/3 - \theta) \cdot (PRFD/2)^2).
 \end{aligned}$$

Then, by substitution in the line with $\sin(\theta/2)$ using

$$WW = PRFD \cdot \cos(\theta/2), \quad (38)$$

and recalling the half-angle formula for $\sin$,

$$E = E + SI \cdot .25 \cdot (WW^2 \cdot \sqrt{3} - 1.5 \cdot PRFD^2 \cdot (\sin(\theta) + \pi/3 - \theta)). \quad (39)$$

Lastly, consider the outer slivers. When

$$\alpha + \theta/2 \geq \pi/2,$$

or, equivalently

$$\alpha \geq 1/2 (\pi - \theta),$$

then the outer slivers are extinguished and a branch is taken to line 280. Otherwise, the area contribution of the SO outer slivers must be added to E. Hence,

$$\begin{aligned} E &= E + SO \cdot (\text{area outer sliver}) & (40) \\ &= E + SO \cdot (\text{area rectangle BCFE} - \text{area triangle BCF} \\ &\quad - 2 \cdot \text{area triangle MEC} - 2 \cdot \text{area sector MCP}) \\ &= E + SO \cdot (WW \cdot (PD(J) + 2 \cdot WOD - U)/2 \\ &\quad - 1/2 \cdot WW \cdot (1/2 \cdot PRFD \cdot \sin(\theta/2)) \\ &\quad - 2 \cdot 1/2 \cdot (PD(J) + 2 \cdot WOD - U)/2 \cdot (1/2 \cdot PRFD \cdot \sin(\alpha)) \\ &\quad - 2 \cdot 1/2 \cdot (\pi/2 - \alpha - \theta/2) \cdot (PRFD/2)^2) \\ &= E + SO \cdot .125 \cdot (2 \cdot (2 \cdot WOD + PD(J) - U) \cdot (2 \cdot WW - PRFD \cdot \sin(\alpha)) \\ &\quad - PRFD^2 \cdot (\sin(\theta) + \pi - 2 \cdot \alpha - \theta)). \end{aligned}$$

This concludes the calculation of E. If variable I > 0, then the initialization section is bypassed and Z = 1 - E · GRL/VO(J). Otherwise, the grain diameter D(J) is recalculated for printout purposes. As in the case of the other grain types, the initial grain volume must be computed.

Initially, we have

$$\begin{aligned} U &= 0 \\ \alpha &= 0 \\ \theta &= 0 \\ PRFD &= PD(J), \end{aligned}$$

and all slivers and corners are present. This implies

$$\begin{aligned} E &= .25 \cdot \pi \cdot ((PD(J) + 2 \cdot WOD)^2 - PD(J)^2) & (41) \\ &\quad + SI \cdot .25 \cdot (WW^2 \cdot \sqrt{3} - 1.5 \cdot PD(J)^2 \cdot \pi/3) \\ &\quad + SO \cdot .125 \cdot (2 \cdot (2 \cdot WOD + PD(J)) \cdot 2 \cdot WW - PD(J)^2 \cdot \pi) \end{aligned}$$

$$= \pi \cdot WOD \cdot (WOD + PD(J)) + .25 \cdot SI \cdot WW^2 \cdot \sqrt{3} \\ - .125 \cdot \pi \cdot (SO + SI) \cdot PD(J)^2 + SO \cdot WW \cdot (WOD + 1/2 PD(J)),$$

and

$$VO(J) = GL(J) \cdot E. \quad (42)$$

Finally, a check must be made to see whether the outer sliver remains within its original bounds, for if it does not, the above analysis is invalid. That is, the point P in Figure 5 must not reach the midpoint of $\overline{BC}$ before the perforation centered at C does. Equivalently, we must have

$$\overline{EC} \geq 1/2 \overline{CB} - 1/2 PD(J) \quad (43)$$

$$WOD + 1/2 PD(J) \geq 1/2 WI(J)$$

$$2 \cdot WOD + PD(J) \geq WI(J),$$

and conversely. Otherwise, FORMT will stop with an error message.

X. GRAIN TYPE 9: NINETEEN-PERFORATED CYLINDER

Initially, this grain is a cylinder pierced by nineteen uniform cylindrical perforations. An end view is shown in Figure 6. Its length is $GL(J)$, diameter $D(J)$, and perforation diameter $PD(J)$. It is characterized by three webs: inner, $WI(J)$; middle, $WM(J)$; and outer, $WO(J)$.

If COMMON variable I is greater than zero, the initialization section is bypassed by a branch to line 320. Otherwise, the grain diameter is recalculated to absorb any inconsistencies as

$$D(J) = 5 \cdot PD(J) + 2 \cdot (WI(J) + WM(J) + WO(J)), \quad (44)$$

and the grain volume is computed by

$$VO(J) = GL(J) \cdot (\pi/4 \cdot D(J)^2 - 19 \cdot \pi/4 \cdot PD(J)^2) \\ + .25 \cdot \pi \cdot GL(J) \cdot (D(J)^2 - 19 \cdot PD(J)^2). \quad (45)$$




Figure 6. Nineteen-Perforated Grain -- End View

The remainder of the initialization section and the whole of the post-initialization coding is drawn directly from the worked example, Section IV, in Reference 4 with IFLAG, SF, AW, GV being the flag, side, work, and volume arrays. The only novelties are the addition of an additional subscript for the Jth propellant and the removal of the surface area computation. The latter was discussed in the case of the seven-perforated grain, above.

REFERENCES

1. P. G. Baer and J. M. Frankle, "The Simulation of Interior Ballistic Performance of Guns by Digital Computer Programs," USA Ballistic Research Laboratories Report 1183, USA Ballistic Research Laboratories, APG, MD, December 1962.
2. J. Corner, "Theory of the Interior Ballistics of Guns," John Wiley & Sons, New York, 1950, pp. 30-35.
3. J. Stals, "Form-Functions for Multicomponent Propellant Charges Including Inhibited Grains and Sliver Burn," Materials Research Laboratories Technical Note 371, Materials Research Laboratories, Maribyrnong, Victoria, Australia, September 1975.
4. Franz R. Lynn, "Development of General Form-Functions for Multi-perforated Cylindrical Propellant Grains," Ballistic Research Laboratory Memorandum Report ARBRLMR03014, Ballistic Research Laboratory, USA ARRADCOM, APG, MD, April 1980.

APPENDIX A
LISTING OF FORM-FUNCTION SUBROUTINES

```

C      FORMT.007      29-APR-82
      SUBROUTINE FORMT
      COMMON/IGNITE/ICFLAG(5)
      COMMON/RUNBLK/XC(20),PR(20),M(5),GT(5),C(5),
      BF(5),TO(5),ALP(5),BET(5),GA(5),COV(5),RHO(5),
      SGL(5),D(5),PD(5),WI(5),WM(5),WO(5),G1,G2(2),
      XH(2),VO,TV,DG,DL,CLR,CV,DT,WP,NPR,M,LVSPK,ICODE(5),
      SYHRES(5),IBRHO(5),BRMP(5,5),BRMR(5,5),AVWEB(5)
      COMMON/XTRA/PT(2),PB(2),KLST,PRLST,DEN2,H(2),RES,AGW,
      BI,CT,AP,PH,PBR(2),DEN1,HCL,AC(5),BC(5),CC(5),DC(5),
      SEC(5),Z(5),PDV,FHL,PTPP,PBPP,HPP,PBRPP,TPP,VPP,XPP,APP,
      BAPK,Z1PP,Z2PP,Z3PP,Z4PP,Z5PP,COEFF,DEN3,CTM,PI,VO(5),
      XKR,MH,Y(5),DY(5)
      DIMENSION WEBC(5),SF(3,4,5),AW(4,4,5),IFLAG(4,5),GV(4,5)
      DATA RT/1.732050808/,PI3/1.047197551/

C
C+++  FIND FRACTIONS BURNED Z(J) FOR J=1,2,...,M PROPELLANTS
      DO 1000 J=1,M
C
C+++  BYPASS IF JTH PROPELLANT UNIGNITED OR EXTINGUISHED
      IF(Z(J).GE.1..OR.ICFLAG(J).EQ.0) GOTO 1000
C
C+++  SET U = 2 X DEPTH BURNED & BRANCH ON GRAIN TYPE
      U=2.*Y(J+3)
      GOTO (20,180,210,430,450,500,250,240,310,600),N(J)
C
C+++  CODE 1: 7-PERF GRAIN
20  IF(1.GT.0) GOTO 50
      W(1)=0.
      D(J)=3.*PD(J)+2.*(WI(J)+WO(J))
      VO(J)=.25*PI*(GL(J)+D(J)**2-7.*PD(J)**2)
      IFLAG(1,J)=-1
      IFLAG(2,J)=-1
      WM=WI(J)+PD(J)
      DO 30 K=1,3
      SF(K,1,J)=WM
      SF(K,2,J)=WM
30  CONTINUE
      WEBC(J)=AMIN1(WO(J),WI(J),GL(J))
50  GRL=AMAX1(GL(J)-U,0.)
      DD=D(J)-U
      PRFD=PD(J)+U
      IF(U.GT.WEBC(J)) GOTO 60
      E=.25*PI*(DD**2-7.*PRFD**2)
      Z(J)=1.-GRL*E/VO(J)
      GOTO 1000
60  CALL GENIS(SF(1,1,J),AW(1,1,J),PRFD,GRL,IFLAG(1,J),GV(1,J))
      CALL GENOS(SF(1,2,J),AW(1,2,J),PRFD,GRL,.5*DD,IFLAG(2,J),GV(2,J))
      Z(J)=1.-6.*(GV(1,J)+GV(2,J))/VO(J)
      GOTO 1000
C
C+++  CODE 2: 1-PERF GRAIN
180 IF(1.GT.0) GOTO 190
      W(1)=0.
      VO(J)=U.
      D(J)=PD(J)+2.*WI(J)
      WEBC(J)=AMIN1(GL(J),WI(J))

```

```

190 VO(J)=GL(J)+(D(J)**2-PD(J)**2)
   E=0.
   IF(U.LE.WERC(J)) E=(D(J)-U)**2-(PD(J)+U)**2
   Z(J)=1.-E*(GL(J)-U)/VO(J)
   GOTO 1000

C
C*** CODE 3: CURD GRAIN
210 IF(I.GT.0) GOTO 220
   PD(J)=0.
   WI(J)=0.
   WO(J)=0.
   WM(J)=0.
   VO(J)=GL(J)+D(J)**2
   Z(J)=1.-AMAX1(GL(J)-J,0.)*(AMAX1(D(J)-U,0.))**2/VO(J)
   GOTO 1000

C
C*** CODE 9: ROUNO-HEX 19-PERF GRAIN
240 SO=17.
   SI=24.
   GOTO 260

C
C*** CODE 7: ROUNO-HEX 37-PERF GRAIN
250 SO=16.
   SI=34.
   WM=WI(J)+PD(J)
   WZ=WM**2
   PRFD=PD(J)+U
   PRF02=PRFD**2
   SRL=AMAX1(GL(J)-U,0.)
   WOO=WO(J)
   E=U.
   THETA=2.*ACOS(AMIN1(WM/PRFD,1.))
   ALPHA=ACOS(AMIN1((2.*WOO+PD(J)-U)/PRFD,1.))
   IF(U.LE.WOO) E=.25*PI*((2.*WOO+PD(J)-U)**2-PRF02)
   IF(THETA.GE.PI) GOTO 270
   E=E+SI*.25*(WZ+RT-1.5*PRF02*(SIN(THETA)+PI-THETA))
270 IF(ALPHA.GE.5*(PI-THETA)) GOTO 280
   E=E+SO*.125*(2.*(2.*WOO+PD(J)-U)*(2.*WM-PRFD*SIN(ALPHA))-PRF02+
   (SIN(THETA)+PI-2.*ALPHA-THETA))
280 IF(I.GT.0) GOTO 290
   WM(J)=WI(J)
   IF(N(J).EQ.10) D(J)=3.*PD(J)+2.*WI(J)+2.*WOO
   IF(N(J).EQ.8) D(J)=5.*PD(J)+4.*WI(J)+2.*WOO
   IF(N(J).EQ.7) D(J)=7.*PD(J)+6.*WI(J)+2.*WOO
   VO(J)=E+GL(J)
   IF(2.*WOO+PD(J).GE.WI(J)) GOTO 290
   CALL ERRMSG('FORMT BAD HEX PROP')
290 Z(J)=1.-E*SRL/VO(J)
   GOTO 1000

C
C*** CODE 9: 19-PERF GRAIN
310 IF(I.GT.0) GOTO 320
   D(J)=5.*PD(J)+2.*(WI(J)+WM(J)+WO(J))
   VO(J)=.25*PI*GL(J)*(D(J)**2-19.*PD(J)**2)
   ON 315 K=1,4
   IFLAG(K,J)=-1
315 CONTINUE

```

```

SF(1,1,J)=WI(J)+PD(J)
SF(2,1,J)=SF(1,1,J)
SF(3,1,J)=SF(1,1,J)
SF(1,2,J)=.5*SQRT(2.+(WI(J)+PD(J))^2+(WI(J)+PD(J))^2)
SF(2,2,J)=SF(1,2,J)
SF(3,2,J)=SF(1,2,J)
SF(1,3,J)=PD(J)+.5*(WI(J)+WM(J))
SF(2,3,J)=SF(1,3,J)
SF(3,3,J)=WM(J)+PD(J)
SF(1,4,J)=SF(1,3,J)
SF(2,4,J)=2.*SF(1,3,J)
SF(3,4,J)=SF(1,3,J)*RT
WESC(J)=AMIN1(WO(J),WM(J),WI(J),SF(1,3,J)-PD(J),SF(1,2,J)-PD(J),
GL(J))
320 GRL=AMAX1(GL(J)-U,0.)
OD=D(J)-U
PRFD=PD(J)+U
IF(U.GT.WESC(J)) GOTO 330
E=.25*PI*(OD**2-19.*PRFD**2)
Z(J)=1.-GRL+E/VO(J)
GOTO 1000
330 DO 340 K=1,2
CALL GENIS(SF(1,K,J),AM(1,K,J),PRFD,GRL,IFLAG(K,J),GV(K,J))
340 CONTINUE
CALL GENIS(SF(1,4,J),AM(1,4,J),PRFD,GRL,.5*OD,IFLAG(4,J),GV(4,J))
Z(J)=1.-(6.*(GV(1,J)+GV(2,J))+12.*(GV(3,J)+GV(4,J)))/VO(J)
GOTO 1000
C
C*** CODE 4: RECTANGULAR STRIP GRAIN
430 IF(I.GT.0) GOTO 440
PD(J)=0.
WO(J)=0.
WM(J)=0.
VO(J)=GL(J)+D(J)+WI(J)
440 Z(J)=1.-AMAX1(GL(J)-U,0.)*AMAX1(D(J)-U,0.)*
AMAX1(WI(J)-U,0.)/VO(J)
GOTO 1000
C
C*** CODE 5: SPHERICAL GRAIN
450 IF(I.GT.0) GOTO 460
GL(J)=0.
PD(J)=0.
WI(J)=0.
WO(J)=0.
WM(J)=0.
460 Z(J)=1.-(AMAX1(D(J)-U,0.)/D(J))^3
GOTO 1000
C
C*** CODE 6: SLOTTED-TUBE GRAIN
500 IF(I.GT.0) GOTO 510
WI(J)=0.
PRFD=.5*WM(J)
SD=.5*D(J)
SI=.5*PD(J)
THETA=.5*PI-ACOS(PRFD/SD)
ALPHA=.5*PI-ACOS(PRFD/SI)
VO(J)=GL(J)+((PI-THETA)*SD**2-(PI-ALPHA)*SI**2-

```

```

      PRFD*(SD*COS(THETA)-SI*COS(ALPHA))
      WEC(J)=AMIN1(OL(J),VI(J))
910  E=0.
      IF(U.GT.WEC(J)) GOTO 920
      PRFD=.5*(WH(J)+U)
      SD=.5*(D(J)-U)
      SI=.5*(PD(J)+U)
      ORL=OL(J)-U
      THETA=.5*PI-ACOS(PRFD/SD)
      ALPHA=.5*PI-ACOS(PRFD/SI)
      E=(PI-THETA)*SD**2-(PI-ALPHA)*SI**2-PRFD*(SD+
      COS(THETA)-SI*COS(ALPHA))
920  Z(J)=1.-E*ORL/VO(J)
      GOTO 1000
C
C*** CODE 10: ROUND-MEX 7-PERF GRAIN
600  SD=6.
      SI=6.
      GOTO 260
C
1000 CONTINUE
      RETURN
      END

```

```

C      GENIS.001      11-DEC-78
C      SUBROUTINE GENIS(S,A,PRFD,GRL,IFLAG,VOL)
C
C      SUBROUTINE *GENIS*: CALCULATE SURFACE AREA AND VOLUME FOR A
C      GENERAL INNER SLIVER OF A BURNING GRAIN
C      WITH LENGTH = GRL & PERF DIAM = PRFD.
C
C      DIMENSION S(3),A(4)
C      DATA PI2/ 1.5707963 /
C
C      IF(IFLAG) 10,20,30
C
C      INITIAL PASS: IFLAG WAS SET NEGATIVE BY CALLING ROUTINE.
C      STORE ANGLES A1,A2,A3 AND AREA OF TRIANGLE
C      WITH SIDES S(1),S(2),S(3) INTO A(1),...,A(4)
C
10  A(1) = ACOS((S(2)**2+S(3)**2-S(1)**2)/(2.*S(2)*S(3)))
C      A(2) = ACOS((S(1)**2+S(3)**2-S(2)**2)/(2.*S(1)*S(3)))
C      A(3) = ACOS((S(1)**2+S(2)**2-S(3)**2)/(2.*S(1)*S(2)))
C
C      A(4) = .5*S(1)*S(2)*SIN(A(2))
C
C      ...CHECK FOR ERROR CONDITION: FIND IF TRIANGLE ACCEPTABLE...
C
C      J = 0
C      DO 19 I = 1,3
C      IF(A(I).LT..9*PI2) J = J+1
19  CONTINUE
C      IF(J.GT.1) CALL ERRMSG(*GENIS* ERROR      )
C
C      IF OK, SET FLAG TO ZERO TO BYPASS INITIALIZATION HEREFTER.
C
C      IFLAG = 0
C
C      SUCCEEDING PASSES UNTIL BURNOUT: FIND AUXILIARY ANGLES
C
20  TAU12 = ACOS(AMIN1(1.,S(3)/PRFD))
C      TAU13 = ACOS(AMIN1(1.,S(2)/PRFD))
C      TAU23 = ACOS(AMIN1(1.,S(1)/PRFD))
C
C      ...AND BRANCH IF SLIVER FAILS BURNOUT CRITERIA.
C
C      IF(TAU12+TAU13+TAU23.LT.PI2 .AND. GRL.GT.0.) GOTO 25
C
C      SLIVER JUST BURNED OUT: SET FLAG TO BYPASS AREA & VOLUME CALCULATIONS
C
C      IFLAG = 1
C      GOTO 30
C
C      SLIVER NOT BURNED OUT: DETERMINE END AREA, VOLUME, AND SURFACE AREA
C
25  H = A(4)-.25*PRFD*(S(1)*SIN(TAU23)+S(2)*SIN(TAU13)
C      +S(3)*SIN(TAU12)+PRFD*(PI2-TAU12-TAU13-TAU23))
C
C      VOL = H*GRL
C
C      SURF = 2.*H*GRL+PRFD*(PI2-TAU12-TAU13-TAU23)

```

C ...AND RETURN.

C RETURN

C SLIVER IS BURNED OUT: RETURN WITH ZERO VOLUME AND SURFACE AREA.

C 30 VOL = 0.
C SURF = 0.
C RETURN

C 840

```

C      GENOS.OU2      09-JUN-80
C      SUBROUTINE GENOS(S,A,PRFD,GRL,RAD,IFLAG,VOL)
C
C      SUBROUTINE *GENOS*: CALCULATE SURFACE AREA AND VOLUME FOR A
C      GENERAL OUTER SLIVER OF A BURNING GRAIN
C      WITH LENGTH = GRL, RADIUS = RAD, AND
C      PERF DIA = PRFD.
C
C      DIMENSION S(3),A(4)
C
C      IF(IFLAG) 10,20,30
C
C      INITIAL PASS: IFLAG WAS SET NEGATIVE BY CALLING ROUTINE.
C      STORE ANGLES A1,A2,A3 AND AREA OF TRIANGLE
C      WITH SIDES S(1),S(2),S(3) INTO A(1),...,A(4)
C
10  A(1) = ACOS((S(2)**2+S(3)**2-S(1)**2)/(2.*S(2)*S(3)))
    A(2) = ACOS((S(1)**2+S(3)**2-S(2)**2)/(2.*S(1)*S(3)))
    A(3) = ACOS((S(1)**2+S(2)**2-S(3)**2)/(2.*S(1)*S(2)))
C
    A(4) = .5*S(1)*S(3)*SIN(A(2))
C
    ...AND SET FLAG TO ZERO TO BYPASS INITIALIZATION HEREFTER.
C
    IFLAG = 0
C
C      SUCCEEDING PASSES UNTIL BURNDOUT: FIRST DETERMINE AUXILIARY ANGLES
C
20  TAU1 = ACOS(AMINI(1.,(S(2)**2+RAD**2-.25*PRFD**2)/(2.*S(2)*RAD)))
    TAU2 = ACOS(AMINI(1.,(S(3)**2+RAD**2-.25*PRFD**2)/(2.*S(3)*RAD)))
    TAU3 = ACOS(AMAXI(-1.,(S(2)**2-RAD**2+.25*PRFD**2)/(S(2)*PRFD)))
    TAU4 = ACOS(AMAXI(-1.,(S(3)**2-RAD**2+.25*PRFD**2)/(S(3)*PRFD)))
C
    SIG = ACOS(AMINI(1.,S(1)/PRFD))
C
    ...AND BRANCH IF SLIVER FAILS BURNDOUT CRITERIA.
C
    IF(TAU1+TAU2.LT.A(1) .AND. GRL.GT.0.) GOTO 25
C
C      SLIVER JUST BURNED OUT: SET FLAG TO BYPASS AREA & VOLUME CALCULATIONS
C
    IFLAG = 1
    GOTO 30
C
C      SLIVER NOT BURNED OUT: FIRST CHECK ERROR CONDITIONS...
C
25  IF(TAU3.LT.A(3) .OR. TAU4.LT.A(2))
    * CALL ERRMSG(*GENOS* ERROR *)
C
    ...IF OK, DETERMINE END AREA, VOLUME, AND SURFACE AREA
C
    E = .5*RAD*(S(2)*SIN(TAU1)+RAD*(A(1)-TAU1-TAU2)+S(3)*SIN(TAU2))
    *-A(4)-.25*PRFD*(S(1)*SIN(SIG)+.5*PRFD*(TAU3+TAU4-2.*SIG
    *-A(2)-A(3)))
C
    VOL = E*GRL
C

```

```

C      SURF = 2.*B*GRL*(RAD*(A(1)-TAU1-TAU2)+.5*PRFD*(TAU3+TAU4-2.*SIG
C      & -A(2)-A(3)))
C
C      ...AND RETURN.
C
C      RETURN
C
C      SLIVER IS BURNED OUT: RETURN WITH ZERO VOLUME AND SURFACE AREA.
C
C      10 VOL = 0.
C      SURF = 0.
C      RETURN
C
C      END

```

APPENDIX B
LIST OF SYMBOLS

LIST OF SYMBOLS

Symbol	Array	Description
M	N (NO)	Number of propellants
Z	Y (YES)	Fractions burned
ICFLAG	Y	Ignition threshold flags
N	Y	Grain codes
U	N	Twice depth burned
I	N	Flag, equals 0 on initial pass
VO	Y	Initial grain volumes
IFLAG	Y	Slivering flags
GV	Y	Sliver volumes
WEBC	Y	Overall grain webs
SF	Y }	Work arrays
AW	Y }	
RT	N	3
PI	N	π
PI3	N	$\pi/3$
GL	Y	Grain lengths: all codes except 5
D	Y	{ Grain diameters: all codes except 4 Grain widths: code 4
PD	Y	Perforation diameters: codes 1,2,6,7,8,9
WI	Y	{ Inner webs: codes 1,2,6,7,8,9 Grain thicknesses: code 4
WM	Y	{ Middle webs: code 9 Slot widths: code 6
WO	Y }	Outer webs: codes 1,7,8,9
WOD	N }	

LIST OF SYMBOLS (cont'd)

Symbol	Array	Description
WW	N	Distance between perforation centers
WW2	N	$WW \cdot WW$
GRL	N	Grain length - U
OD	N	Grain diameter - U
PRFD	N	Perforation diameter + U
PRFD2	N	$PRFD \cdot PRFD$
E	N	End-area of grain
ALPHA } THETA }	N	Various angles

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22314	3	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST DCRSF-E, Safety Office DRCDE-DW 5001 Eisenhower Avenue Alexandria, VA 22333
1	Office of the Under Secretary of Defense Research & Engineering ATTN: R. Thorkildsen Washington, DC 20301	14	Commander US Army Armament R&D Command ATTN: DRDAR-TSS (2 cys) DRDAR-TCD Dr. D. Gyrog DRDAR-LCA K. Russell A. Moss J. Lannon A. Beardell D. Downs S. Einstein L. Schlosberg S. Westley S. Bernstein P. Kemmey C. Heyman Dover, NJ 07801
1	HQDA/SAUS-OR, D. Hardison Washington, DC 20301		
1	HQDA/DAMA-ZA Washington, DC 20310		
2	HQDA, DAMA-CSM, A. German E. Lippi Washington, DC 20310		
1	HQDA/SARDA Washington, DC 20310		
1	Commander US Army War College ATTN: Library-FF229 Carlisle Barracks, PA 17013	10	US Army Armament R&D Command ATTN: DRDAR-SCA, L. Stiefel B. Brodman DRDAR-LCE-I, D. Spring DRDAR-LCE, R. Walker L. Avrami DRDAR-LCU-CT E. Barriera R. Davitt DRDAR-LCU-CV C. Mandala E. Moore DRDAR-LCM-E S. Kaplowitz Dover, NJ 07801
1	Commander Ballistic Missile Defense Advanced Technology Center P. O. Box 1500 Huntsville, AL 35804		
1	Chairman DOD Explosives Safety Board Room 856-C Hoffman Bldg. 1 2461 Eisenhower Avenue Alexandria, VA 22331		

15 DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
5	Commander US Army Armament R&D Command ATTN: DRDAR-QAR, J. Rutkowski G. Allen J. Donner P. Seroa D. Adams Dover, NJ 07801	5	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib DRSAR-LC, L. Ambrosini DRSAR-IRC, G. Cowan DRSAR-LEM, W. Fortune R. Zastrow Rock Island, IL 61299
5	Project Manager Cannon Artillery Weapons System ATTN: DRCPM-CAWS, F. Menke DRCPM-CAWS-WS H. Noble DRCPM-CAWS-SI M. Fisette DRCPM-CAWS-AM R. DeKleine H. Hassmann Dover, NJ 07801	1	Commander US Army Watervliet Arsenal ATTN: SARWV-RD, R. Thierry Watervliet, NY 12189
		1	Director US Army ARFADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Watervliet, NY 12189
		1	Commander US Army Aviation Research and Development Command ATTN: DRDAV-E 4300 Goodfellow Blvd. St. Louis, MO 63120
3	Project Manager Munitions Production Base Modernization and Expansion ATTN: DRCPM-PMB, J. Ziegler M. Lohr A. Sikloski Dover, NJ 07801	1	Commander US Army TSARCOM 4300 Goodfellow Blvd. St. Louis, MO 63120
3	Project Manager Tank Main Armament System ATTN: DRCPM-TMA, D. Appling DRCPM-TMA-105 DRCPM-TMA-120 Dover, NJ 07801	1	Director US Army Air Mobility Research And Development Laboratory Ames Research Center Moffett Field, CA 94035
4	Commander US Army Armament R&D Command ATTN: DRDAR-LCW-A M. Salisbury DRDAR-LCS DRDAR-LCU, A. Moss DRDAR-LC, J. Frasier Dover, NJ 07801		

23

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Commander US Army Communications Research and Development Command ATTN: DRDCO-PPA-SA Fort Monmouth, NJ 07703	1	Project Manager Improved TOW Vehicle ATTN: DRCPM-ITV US Army Tank Automotive Research & Development Command Warren, MI 48090
1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703	2	Program Manager M1 Abrams Tank System ATTN: DRCPM-GMC-SA, J. Roossien Warren, MI 48090
1	Commander US Army Harry Diamond Lab. ATTN: DELHD-TA-L 2800 Powder Mill Road Adelphi, MD 20783	1	Project Manager Fighting Vehicle Systems ATTN: DRCPM-FVS Warren, MI 48090
2	Commander US Army Missile Command ATTN: DRSMI-R DRSMI-YDL Redstone Arsenal, AL 35898	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL, Tech Lib White Sands Missile Range, NM 88002
1	Commander US Army Natick Research and Development Command ATTN: DRDNA-T, D. Sieling Natick, MA 01762	1	Project Manager M-60 Tank Development ATTN: DRCPM-M60TD Warren, MI 48090
1	Commander US Army Tank Automotive Research and Development Command ATTN: DRDTA-UL Warren, MI 48090	1	Commander US Army Training & Doctrine Command ATTN: ATCD-MA/ MAJ Williams Fort Monroe, VA 23651
1	US Army Tank Automotive Materiel Readiness Command ATTN: DRSTA-CG Warren, MI 48090	2	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL Tech Library Watertown, MA 02172

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Commander US Army Research Office ATTN: Tech Library P. O. Box 12211 Research Triangle Park, NC 27709	1	Commander US Army Foreign Science & Technology Center ATTN: DRXST-MC-3 220 Seventh Street, NE Charlottesville, VA 22901
1	Commander US Army Mobility Equipment Research & Development Command ATTN: DRDME-WC Fort Belvoir, VA 22060	1	President US Army Artillery Board Ft. Sill, OK 73504
1	Commander US Army Logistics Mgmt Ctr Defense Logistics Studies Fort Lee, VA 23801	2	Commandant US Army Field Artillery School ATTN: ATSF-CO-MW, B. Willis Ft. Sill, OK 73503
2	Commandant US Army Infantry School ATTN: Infantry Agency Fort Benning, GA 31905	3	Commandant US Army Armor School ATTN: ATZK-CD-MS/M. Falkovitch Armor Agency Fort Knox, KY 40121
1	US Army Armor & Engineer Board ATTN: STEBB-AD-S Fort Knox, KY 40121	1	Chief of Naval Materiel Department of the Navy ATTN: J. Amlic Washington, DC 20360
1	Commandant US Army Aviation School ATTN: Aviation Agency Fort Rucker, AL 36360	1	Office of Naval Research ATTN: Code 473, R. S. Miller 800 N. Quincy Street Arlington, VA 22217
1	Commandant Command and General Staff College Fort Leavenworth, KS 66027	2	Commander Naval Sea Systems Command ATTN: SKA-62R, J. W. Murrin, R. Beauregard Navy Department Washington, DC 20362
1	Commandant US Army Special Warfare School ATTN: Rev & Tng Lit Div Fort Bragg, NC 28307	1	Commander Naval Air Systems Command ATTN: NAIR-954-Tech Lib Washington, DC 20360
1	Commandant US Army Engineer School ATTN: ATSE-CD Ft. Belvoir, VA 22060		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Strategic Systems Project Office Dept. of the Navy Room 901 ATTN: J. F. Kincaid Washington, DC 20376	4	Commander Naval Weapons Center ATTN: Code 388, R. L. Darr C. F. Price T. Boggs Info. Sci. Div. China Lake, CA 93555
1	Assistant Secretary of the Navy (R, E, and S) ATTN: R. Reichenbach Room 5E787 Pentagon Bldg. Washington, DC 20350	2	Superintendent Naval Postgraduate School Dept. of Mechanical Engineering ATTN: A. E. Fuhs Code 1424 Library Monterey, CA 93940
1	Naval Research Lab Tech Library Washington, DC 20375	6	Commander Naval Ordnance Station ATTN: P. L. Stang C. Smith S. Mitchell C. Christensen D. Brooks Tech Library Indian Head, MD 20640
5	Commander Naval Surface Weapons Center ATTN: Code G33, J. L. East D. McClure W. Burrell J. Johndrow Code DX-21, Tech Lib Dahlgren, VA 22448	1	HQ AFSC Andrews AFB Washington, DC 20331
2	Commander US Naval Surface Weapons Center ATTN: J. P. Consaga C. Gotzmer Indian Head, MD 20640	1	Program Manager AFOSR Directorate of Aerospace Sciences ATTN: L. H. Caveny Bolling AFB, DC 20332
4	Commander Naval Surface Weapons Center ATTN: S. Jacobs/Code 240 Code 730 K. Kim/Code R-13 R. Bernecker Silver Spring, MD 20910	6	AFRPL (DYSC) ATTN: D. George J. N. Levine B. Goshgarian D. Thrasher N. Vander Hyde Tech Library Edwards AFB, CA 93523
2	Commanding Officer Naval Underwater Systems Center Energy Conversion Dept. ATTN: CODE 5B331, R. S. Lazar Tech Lib Newport, RI 02840		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	AFFTC ATTN: SSD-Tech Lib Edwards AFB, CA 93523	1	AVCO Everett Resch Lab ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149
1	AFATL ATTN: DLYV Eglin AFB, FL 32542	2	Calepan Corporation ATTN: E. B. Fisher Tech Library P. O. Box 400 Buffalo, NY 14225
1	AFATL/DL DL ATTN: O. K. Hainey Eglin AFB, FL 32542	1	Foster Miller Associates, ATTN: A. Erickson 135 Second Avenue Waltham, MD 02154
1	ADTC ATTN: DLODL Tech Lib Eglin AFB, FL 32542	1	BMD Corporation ATTN: T. P. Goddard P. O. Box 2019 Monterey, CA 93940
1	AFDDL ATTN: TST-Lib Wright-Patterson AFB, OH 45433	1	General Applied Sciences Lab ATTN: J. Erdos Merrick & Stewart Avenues Westbury Long Island, NY 11590
1	HO NASA 600 Independence Avenue, SW ATTN: Code JMW, Tech Lib. Washington, DC 20546	1	General Electric Company Armament Systems Dept. ATTN: M. J. Bulman, Room 1311 Lakeside Avenue Burlington, VT 05412
1	NASA/Lyndon B. Johnson Space Center ATTN: NHS-22, Library Section Houston, TX 77058	1	Hercules Powder Co. Allegheny Ballistics Laboratory ATTN: R. B. Miller P. O. Box 210 Cumberland, MD 21501
1	Aerodyne Research, Inc. Bedford Research Park ATTN: V. Yousefian Bedford, MA 01730	1	Hercules, Inc Bacchus Works ATTN: K. P. McCarty Magna, UT 84044
1	Aerojet Solid Propulsion Co. ATTN: P. Michali Sacramento, CA 95813		
1	Atlantic Research Corporation ATTN: M. K. King 5390 Chesapeake Avenue Alexandria, VA 22314		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Hercules, Inc. Eglin Operations AFATL DLDL ATTN: R. L. Simmons Eglin AFB, FL 32542	2	Rockwell International Rocketdyne Division ATTN: BA08 J. E. Flanagan J. Gray 6633 Canoga Avenue Canoga Park, CA 91304
1	IITRI ATTN: M. J. Klein 10 W. 35th Street Chicago, IL 60616	1	Science Applications, INC. ATTN: R. E. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364
2	Lawrence Livermore Laboratory ATTN: M. S. L-355, A. Buckingham M. Finger P. O. Box 808 Livermore, CA 94550	1	Scientific Research Assoc., Inc. ATTN: H. McDonald P. O. Box 498 Glastonbury, CT 06033
1	Olin Corporation Badger Army Ammunition Plant ATTN: R. J. Thiede Baraboo, WI 53913	1	Shock Hydrodynamics, Inc. ATTN: W. H. Andersen 4710-16 Vineland Avenue North Hollywood, CA 91602
1	Olin Corporation Smokeless Powder Operations ATTN: R. L. Cook P. O. Box 222 St. Marks, FL 32355	3	Thiokol Corporation Huntsville Division ATTN: D. Flanigan R. Glick Tech Library Huntsville, AL 35807
1	Paul Gough Associates, Inc. ATTN: P. S. Gough P. O. Box 1614 Portsmouth, NH 03801	2	Thiokol Corporation Wasatch Division ATTN: J. Peterson Tech Library P. O. Box 524 Brigham City, UT 84302
1	Physics International Company 2700 Merced Street Leandro, CA 94577	2	Thiokol Corporation Elkton Division ATTN: R. Biddle Tech Lib. P. O. Box 241 Elkton, MD 21921
1	Princeton Combustion Research Lab., Inc. ATTN: M. Summerfield 1041 US Highway One North Princeton, NJ 08540		
1	Pulsepower Systems, Inc. ATTN: L. G. Elmore 815 American Street San Carlos, CA 94070		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organisation</u>	<u>No. Of Copies</u>	<u>Organisation</u>
2	United Technologies Chemical Systems Division ATTN: R. Brown Tech Library P. O. Box 358 Sunnyvale, CA 94086	1	California Institute of Tech 204 Karman Lab Main Stop 301-46 ATTN: F. E. C. Culick 1201 E. California Street Pasadena, CA 91125
1	Universal Propulsion Company ATTN: H. J. McSpadden Black Canyon Stage 1 Box 1140 Phoenix, AZ 85029	1	Director Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, CA 91103
1	PMC Corporation Northern Ordnance Division ATTN: J. E. Alexander 4800 East River Road Minneapolis, MN 55421	1	University of Illinois Dept of Mech Engineering ATTN: R. Krier 144 MEB, 1206 W. Green St. Urbana, IL 61801
2	AAI Corporation ATTN: J. Herbert R. L. Kachinski P. O. Box 6767 Baltimore, MD 21204	1	University of Massachusetts Dept. of Mechanical Engineering ATTN: K. Jakus Amherst, MA 01002
1	Honeywell, Inc Defense Systems Division ATTN: J. Kennedy Edina, MN 75524	1	University of Minnesota Dept. of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455
1	Ares Inc. ATTN: J. Moldenhauer Port Clinton, Ohio 43452	1	Case Western Reserve University Division of Aerospace Sciences ATTN: J. Tien Cleveland, OH 44135
1	Southwest Research Institute ATTN: Robert E. White 8500 Culebra Road San Antonio, TX 78228	3	Georgia Institute of Tech School of Aerospace Eng. ATTN: B. T. Zinn E. Price W. C. Strahle Atlanta, GA 30332
1	Battelle Memorial Institute ATTN: Tech Library 505 King avenue Columbus, OH 43201	1	Institute of Gas Technology ATTN: D. Gidaspo 3424 S. State Street Chicago, IL 60616
1	Brigham Young University Dept. of Chemical Engineering ATTN: M. Beckstead Provo, UT 84601		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organisation</u>	<u>No. Of Copies</u>	<u>Organisation</u>
1	Johns Hopkins University Applied Physics Laboratory Chemical Propulsion Information Agency ATTN: T. Christian Johns Hopkins Road Laurel, MD 20707	1	SRI International Propulsion Sciences Division ATTN: Tech Library 333 Ravenswood Avenue Menlo Park, CA 94025
1	Massachusetts Institute of Tech Dept of Mechanical Engineering ATTN: T. Toong Cambridge, MA 02139	1	Stevens Institute of Technology Davidson Laboratory ATTN: R. McAlamy, III Hoboken, NJ 07030
1	Pennsylvania State University Applied Research Lab ATTN: G. M. Faeth P. O. Box 30 State College, PA 16801	2	Los Alamos National Lab ATTN: T. D. Butler, MS B216 M. Division, B. Craig P. O. Box 1663 Los Alamos, NM 87545
1	Pennsylvania State University Dept. Of Mechanical Engineering ATTN: K. Kuo University Park, PA 16802	1	University of Southern California Mechanical Engineering Dept. ATTN: ONE200, M. Gerstein Los Angeles, CA 90007
1	Purdue University School of Mechanical Engineering ATTN: J. R. Osborn TSPC Chaffee Hall West Lafayette, IN 47907	2	University of Utah Dept. of Chemical Engineering ATTN: A. Baer G. Flandro Salt Lake City, UT 84112
1	Rensselaer Polytechnic Inst. Department of Mathematics Troy, NY 12181	1	Washington State University Dept. of Mechanical Engineering ATTN: C. T. Crowe Pullman, WA 99164
1	Rutgers University Dept. of Mechanical and Aerospace Engineering ATTN: S. Tenkin University Heights Campus New Brunswick, NJ 08903		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organisation</u>	<u>No. Of Copies</u>	<u>Organisation</u>
<u>Aberdeen Proving Ground</u>			
	Dir, USAMSAA		
	ATTN: DRXSY-D		
	DRXSY-MP, H. Cohen		
	Cdr, USATECOM		
	ATTN: DRSTE-TO-F		
	STEAP-MT, S. Walton		
	G. Rice		
	D. Lacey		
	C. Herud		
	Dir, HEL		
	ATTN: J. Weiss		
	Dir, USACSL, Bldg. E3516, EA		
	ATTN: DRDAR-CLB-PA		
	Dir, MTD		
	Bldg. 400		

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____
2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

----- FOLD HERE -----

Director
JS Army Ballistic Research Laboratory
Aberdeen Proving Ground, MD 21005




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-TSB -S
Aberdeen Proving Ground, MD 21005



----- FOLD HERE -----