

AD-A122 905

MODEL FOR THE PROPAGATION OF PULSED SURFACE POLARITONS 1/1
WITH QUASI-SELF-IN. (U) ROCHESTER UNIV NY DEPT OF
CHEMISTRY X HUANG ET AL. DEC 82 UROCHESTER/DC/82/TR-27
UNCLASSIFIED N00014-80-C-0472 9/a 29/8


END

DATE

FILED

283

11



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

12

AL A 122905

OFFICE OF NAVAL RESEARCH

Contract N00014-80-C-0472

Task No. NR 056-749

TECHNICAL REPORT No. 27

Model for the Propagation of Pulsed Surface
Polaritons with Quasi-Self-Induced Transparency

by

Xi-Yi Huang, Jui-teng Lin and Thomas F. George

Prepared for Publication

in

Zeitschrift für Physik B

University of Rochester
Department of Chemistry
Rochester, New York 14627

December, 1982

Reproduction in whole or in part is permitted for any purpose
of the United States Government.

This document has been approved for public release and sale;
its distribution is unlimited.

DTIC FILE COPY

JAN 03 1983

E

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER UROCHESTER/DC/82/TR-27	2. GOVT ACCESSION NO. AD-A122	3. RECIPIENT'S CATALOG NUMBER 905
4. TITLE (and Subtitle) Model for the Propagation of Pulsed Surface Polaritons with Quasi-Self-Induced Transparency		5. TYPE OF REPORT & PERIOD COVERED Interim Technical Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Xi-Yi Huang, Jui-teng Lin and Thomas F. George		8. CONTRACT OR GRANT NUMBER(s) N00014-80-C-0472
9. PERFORMING ORGANIZATION NAME AND ADDRESS University of Rochester Department of Chemistry Rochester, New York 14627		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 056-749
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research Chemistry Program Code 472 Arlington, Virginia 22217		12. REPORT DATE December 1982
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 23
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) This document has been approved for public release and sale; its distribution is unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Prepared for publication in Zeitschrift für Physik B, in press.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) PULSED LASER-SURFACE INTERACTIONS SLAB (TWO-INTERFACE) CONFIGURATION PULSED SURFACE POLARITONS HYPERBOLIC SECANT PULSES QUASI-SELF-INDUCED TRANSPARENCY TRANSVERSE PHASE OSCILLATIONS GAS-SOLID INTERFACE OPTICAL BLOCH AND MAXWELL EQUATIONS		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The possibility of quasi-self-induced transparency for the propagation of pulsed surface polaritons on a gas-solid interface is investigated. A theoretical model combining the optical Bloch and Maxwell equations is presented. The boundary conditions of the interface system lead to a closed relation between the laser pulse velocities in each of the two media. The behavior of transverse phase oscillations in hyperbolic secant pulses, due to the properties of the interface and the restriction of the pulse duration, are discussed. The treatment is extended to a slab (two-interface) configuration, where there is no restriction on the envelope of the pulsed		

DD FORM 1 JAN 73 1473

Unclassified


SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

slab mode such that quasi-self-induced transparency is no longer observed.

Appendix For	
1. Title	☒
2. Author	☐
3. Subject	☐
4. Date	☐
5. Location	☐
6. Distribution	☐
7. Other	☐
Dist	☐
A	



Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

Model for the Propagation of Pulsed Surface Polaritons
with Quasi-Self-Induced Transparency

Xi-Yi Huang,^{†‡} Jui-teng Lin^{*} and Thomas F. George[†]

[†]Department of Chemistry, University of Rochester
Rochester, New York 14627 USA

^{*}Laser Physics Branch, Optical Sciences Division,
Naval Research Laboratory, Washington, D.C. 20375 USA

The possibility of quasi-self-induced transparency for the propagation of pulsed surface polaritons on a gas-solid interface is investigated. A theoretical model combining the optical Bloch and Maxwell equations is presented. The boundary conditions of the interface system lead to a closed relation between the laser pulse velocities in each of the two media. The behavior of transverse phase oscillations in hyperbolic secant pulses, due to the properties of the interface and the restriction of the pulse duration, are discussed. The treatment is extended to a slab (two-interface) configuration, where there is a restriction on the envelope of the pulsed slab mode such that quasi-self-induced transparency is no longer observed.

[‡]Also with the Department of Physics, University of Rochester.
Permanent address: Institute of Physics, Academia Sinica,
Beijing (Peking), The People's Republic of China.

I. Introduction

The development of sources of pulsed coherent radiation (laser) has prompted investigations of the behavior of coherent traveling waves interacting with media which have absorption bands near or at the frequency of the applied pulse. Of particular interest are resonant absorbing media characterized by two-level transitions which are induced by optical radiation.¹ At the same time, increasing attention has been paid to the problem of surface polaritons (SP), which, in a simple case, occur at a single interface between two media, one having a negative dielectric (or magnetic) permeability and the other a positive one. The SP propagate along the interface and decay exponentially for directions normal to the interface.² Under usual conditions, due to radiation absorption or relaxation of the media, the SP propagating on the interface would decay rapidly, where the traveling distance for infrared SP are on the order of a cm.³

It is established that an optical pulse propagating through an absorbing gas medium would be resonantly absorbed according to Beer's law when its intensity is low. As the intensity of the (coherent) laser radiation increases, the pulse may propagate through the absorber gas as if it were transparent. This phenomenon, called self-induced transparency, was predicted and demonstrated by McCall and Hahn^{4,5} and experimentally refined later.⁶

In the present paper, we shall study an interface system comprised of a gas medium and a solid medium. In the next section we predict and present an analysis of quasi-self-induced transparency (quasi-SIT) for the propagation of SP on the interface of

a two-level atomic gas and an unspecified "surface-active" medium, which is a solid material possessing a dielectric constant $\epsilon_m(\omega)$ whose real part is negative near the frequency ω of interest. The term "quasi" is used as a prefix to SIT since there is decay in the solid medium through the imaginary part of ϵ_m . For the gas medium, the imaginary part of ϵ_g plays a negligible role in the saturated propagation governed by the nonlinear Bloch and Maxwell equations, so that the propagation is lossless. The relation between the laser pulse velocities in each media, which must match at the interface, and phase oscillations associated with hyperbolic secant pulses are revealed. In Section III the treatment is extended to a slab (two-interface) configuration, where there is a restriction on the envelope of the pulsed slab mode whereby quasi-SIT is no longer seen. Section IV contains some final remarks.

II. Quasi-SIT Propagation of Pulsed SP in a Semi-Infinite Medium

Consider an interface system with two media separated at $z = 0$ (see Fig. 1). Let a gas of two-level absorbers with dielectric constant $\epsilon_g(\omega)$ occupy the upper-half space $z > 0$. The lower-half space $z < 0$ is filled by a second unspecified dielectric medium characterized by an isotropic frequency-dependent dielectric function $\epsilon_m(\omega)$. For SP to exist, we require $\text{Re}\epsilon_m(\omega) < -\text{Re}\epsilon_g(\omega) (\approx -1)$

We shall consider plane waves propagating in the xz -plane as shown in Fig. 1. The pulsed electromagnetic (EM) waves $\vec{E}_g$ and $\vec{E}_m$ propagating in the two media can be written as

$$\vec{E}_{g,m} = \hat{e}_{g,m} E_{g,m}(x_{g,m}, t) \exp[i(k_{g,m} x_{g,m} - \omega t)] + \text{c.c.}, \quad (2.1)$$

where ω is the frequency, $x_{g,m}$ is a space coordinate, $\vec{k}_{g,m}$ is the wave vector and $\hat{e}_{g,m}$ is the unit polarization vector perpendicular to $\vec{k}_{g,m}$. $E_{g,m}$ denotes the amplitude of the EM wave in the media and is assumed to be a slowly-varying function in space and time,

$$\partial E_{g,m} / \partial x_{g,m} \ll k_{g,m} E_{g,m}, \quad (2.2)$$

$$\partial E_{g,m} / \partial t \ll \omega E_{g,m}. \quad (2.3)$$

This assumption is justified on the basis that the shortest laser pulses one might work with in experiments are on the time scale of a fraction of a picosecond, whereas the carrier waves have frequencies on the order of 10^{14} to 10^{15} sec^{-1} for the infrared and visible region of the spectrum.

We shall discuss separately the propagation behavior in each of the two media, beginning with the gas medium. The one-dimensional wave equation describing a plane wave propagating along the x_g -direction is

$$\left[\frac{\partial^2}{\partial x_g^2} - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} \right] E_g(x_g, t) = \frac{4\pi}{c^2} \frac{\partial^2}{\partial t^2} P_g(x_g, t), \quad (2.4)$$

where c is the vacuum speed of light and $P_g(x_g, t)$ is the polarization density. This density, characterized by the ensemble-averaged dipoles of the two-level atoms, can be obtained by solving the optical Bloch equations.¹ For a short pulse propagating in a dilute gas medium, we may neglect the damping rates in the Bloch equations.^{1,4,5} The resulting lossless Bloch equations provide us with an interesting coherent pulse which is area- and shape-stable in propagation,^{4,5}

$$E_g(\zeta_g) = \frac{2}{\kappa\tau} \text{sech}(\zeta_g/\tau). \quad (2.5)$$

τ is the pulse duration, $\kappa = 2d/\hbar$ where d is the magnitude of the transition dipole of the absorber and

$$\zeta_g \equiv t - x_g/v_g. \quad (2.6)$$

v_g is the constant velocity of the laser pulse in the gas medium and can be evaluated by^{1,4,5}

$$\frac{1}{v_g} - \frac{1}{c} = \frac{\alpha}{2\pi g(0)} \int d\Delta \frac{g(\Delta)}{\Delta^2 + (1/\tau)^2}, \quad (2.7)$$

where α is the absorption coefficient, $g(\Delta)$ is a normalized inhomogeneous broadening spectral density function and $\Delta = \omega_0 - \omega$ is the detuning of the laser with respect to the absorption frequency ω_0 .

For the solid medium, the wave equation describing a plane wave propagating in the x_m -direction can be written as

$$\left[\frac{\partial^2}{\partial x_m^2} - \frac{\epsilon_m(\omega)}{c^2} \frac{\partial^2}{\partial t^2} \right] E_m(x_m, t) = 0, \quad (2.8)$$

where for a pulse with a slowly-varying amplitude

$$E_m(x_m, t) = E_m(x_m, t) e^{i(k_m x_m - \omega t)} + \text{c.c.} \quad (2.9)$$

$E_m(t, x_m)$ is the pulse envelope, ω is the wave frequency and k_m is the wave vector. Imposing the slowly-varying assumptions (2.2) and (2.3) on E_m , we obtain the reduced Maxwell equation

$$k_m \frac{\partial E(x_m, t)}{\partial x_m} + \frac{\omega \epsilon_m(\omega)}{c^2} \frac{\partial E_m(x_m, t)}{\partial t} = 0 \quad (2.10)$$

One of the solutions of Eq.(2.10) is

$$E(x_m, t) = E(\zeta_m) \quad (2.11)$$

where $E(\zeta_m)$ is any smooth function of ζ_m ,

$$\zeta_m = t - x_m/v_m \quad (2.12)$$

and v_m is the pulse velocity.

The infinite plane waves given by Eqs. (2.1) and (2.5) can be expressed in the xz -plane as

$$\vec{E}_{g,m} = \hat{e}_{g,m} E_{g,m}(\zeta_{g,m}) \exp[i(k_{(g,m)x}x + k_{(g,m)z}z - \omega t)] + c.c., \quad (2.13)$$

where

$$\zeta_g = t - (k_{gx}x + k_{gz}z)/(k_g v_g), \quad (2.14)$$

$$\zeta_m = t - (k_{mx}x - k_{mz}z)/(k_m v_m), \quad (2.15)$$

and $k_{(g,m)x}$ and $k_{(g,m)z}$ are the x - and z -components of the wave vectors $\vec{k}_{g,m}$. We then impose the following boundary conditions at the interface defined by $z=0$ (supposing no charge and current on the interface):

$$\hat{n} \cdot [\epsilon_g(\omega) \vec{E}_g - \epsilon_m(\omega) \vec{E}_m] = 0 \quad (2.16)$$

$$\hat{n} \times [\vec{E}_g - \vec{E}_m] = 0, \quad (2.17)$$

where $\hat{n}$ is the unit vector along the positive z -axis as shown in Fig. 1. This gives the form of the dispersion relation for the pulsed SP as

$$k_x(\omega) \equiv k_{gx}(\omega) = k_{mx}(\omega) = \frac{\omega}{c} \left[\frac{\epsilon_g(\omega) \epsilon_m(\omega)}{\epsilon_g(\omega) + \epsilon_m(\omega)} \right]^{1/2}, \quad (2.18)$$

and quite interesting to note, there is a closed relation between the pulse velocities in the two media given as

$$v_g k_g / k_x = v_m k_m / k_x. \quad (2.19)$$

We define $v_x \equiv v_g k_g / k_x$, the x- and z-components of the amplitudes of the EM waves in the two media as

$$E_{gx}(t-x/v_x) = E_{mx}(t-x/v_x) \quad (2.20)$$

$$E_{gz}(t-x/v_x) = - \frac{\epsilon_m(\omega)}{\epsilon_g(\omega)} E_{mz}(t-x/v_x). \quad (2.21)$$

Eqs.(2.20) and (2.21) mean that once the hyperbolic secant pulse is prepared in the gas medium, the envelope of the field amplitude in the solid medium will be a hyperbolic secant profile as well.

Eqs.(2.12) and (2.19) lead to a restriction on the constant pulse velocity of the hyperbolic secant pulse in the gas medium, namely,

$$v_g = \omega/k_g \approx c. \quad (2.22)$$

This requirement is different from what one usually expects of SIT pulses in homogeneous gas media, where the pulse velocity v_g can be much smaller than c .^{4,5,6} For a short laser pulse with duration τ much less than the inhomogeneous lifetime T^* , Eq.(2.7) takes the form

$$\frac{1}{v_g} - \frac{1}{c} = \frac{\alpha \tau^2}{2T^*} \quad (2.23)$$

The requirement of $v_g \approx c$ leads to the restriction on the pulse duration that

$$\tau < (2T^*/\alpha)^{1/2}, \quad (2.24)$$

which is a much milder condition than $\tau \ll T^*$. A typical value of T^* in the gas medium, originating from the Doppler effect, would be around a nanosecond.⁶ Hence, a laser pulse which could generate quasi-SIT propagation for SP on the interface (i.e., lossless propagation in the gas medium but decay in the solid medium) must be substantially less than a nanosecond.

We can now write the EM fields in the two media, obtained by combining the Maxwell and Bloch equations, as

$$\vec{E}_g = \frac{2}{\kappa\tau} \left(-\frac{k_{gz}}{k_g}, 0, \frac{k_x}{k_g} \right) \text{sech} \left(\frac{t-x/v_x - z/v_{gz}}{\tau} \right) \exp[i(k_x x + k_{gz} z - \omega t)] + \text{c.c.} \quad (2.25)$$

$$\vec{E}_m = \frac{2}{\kappa\tau} \left(-\frac{k_{mz}}{k_m}, 0, -\frac{k_x}{k_m} \right) \text{sech} \left(\frac{t-x/v_x + z/v_{mz}}{\tau} \right) \exp[i(k_x x - k_{mz} z - \omega t)] + \text{c.c.} \quad (2.26)$$

When $\text{Re}\epsilon_m < -\text{Re}\epsilon_g$, $\vec{E}_{g,m}$ decays in the direction normal to the interface, and

$$v_x \equiv v_g k_g / k_x = v_m k_m / k_x \quad (2.27)$$

$$v_{gz} \equiv v_g k_g / k_{gz} \quad (2.28)$$

$$v_{mz} \equiv v_m k_m / k_{mz} \quad (2.29)$$

It is interesting to note from the above expressions for the EM fields that the quasi-SIT propagation of SP occurs along the interface with a constant velocity v_x (less than c), but that exponential decay with an oscillatory phase behavior occurs normal to the interface. Such oscillations would be a unique feature for a heterogeneous system (with $\text{Re}\epsilon_m < -\text{Re}\epsilon_g$) and cannot be found in a homogeneous system.

In order to understand the effect of the dielectric constants on these oscillations, we consider the z-components of the SP as derived from Eqs.(2.27) and (2.28),

$$E_{gz} = \frac{8}{\kappa\tau} \frac{e^{-\alpha_g z}}{(1-\epsilon_g/|\epsilon_m|)^{1/2}} [e^T \cos(\beta_g z - \Omega) + e^{-T} \cos(\beta_g z + \Omega)] / D_g \quad (2.30)$$

$$E_{mz} = \frac{8}{\kappa\tau} \frac{e^{-\alpha_m |z|}}{(|\epsilon_m|/\epsilon_g - 1)^{1/2}} [e^{-T} \sin(\beta_m |z| - \Omega) + e^T \sin(\beta_m |z| + \Omega)] / D_m, \quad (2.31)$$

where $\alpha_{g,m}$ is the imaginary part of $k_{(g,m)z}$ and

$$T = (t - x/v_x) / \tau \quad (2.32)$$

$$\beta_{g,m} = 1/(\tau |v_{(g,m)z}|) \quad (2.33)$$

$$\Omega = k_x x - \omega t \quad (2.34)$$

$$D_{g,m} = e^{2T} + e^{-2T} + 2 \cos(2\beta_{g,m} z). \quad (2.35)$$

The propagation of the above z-components, normalized to the peak value of E_{gz} with $\epsilon_g = 1$ and $\epsilon_m = -10$, is shown in Fig. 2 (we are taking the dielectric constants to be real). The large $|\epsilon_m|$ cases in Parts (A) and (B) correspond, for example, to SP propagating along a diatomic cubic crystal surface with frequency near the transverse optical phonon frequency, $\omega \gtrsim \omega_{t0}$, or a metal surface with frequency far less than the plasma frequency, $\omega \ll \omega_p$. The smaller $|\epsilon_m|$ cases in Parts (C) and (D) correspond to SP propagating along a diatomic cubic surface with frequency near the longitudinal optical phonon frequency of the crystal, $\omega \lesssim \omega_{l0}$, or a metal surface

with frequency near the plasma frequency, $\omega \lesssim \omega_p$.⁷ We note that the behavior of the SP is characterized not only by the phase factor Ω [compare Parts (A) and (B)], but also by the dielectric constant ϵ_m [compare Parts (C) and (D)]. The decay of the SP in the solid medium is faster than in the gas medium, since $|\epsilon_m| > \epsilon_g$ and $\alpha_m = |\epsilon_m| \alpha_g$.

III. Propagation of Pulsed SP in a Slab (Two-Interface) Configuration

We now extend our treatment to the situation of two interfaces, where for simplification we assume each dielectric media to be optically isotropic and hence neglect any effects of spatial dispersion. We restrict ourselves to a symmetric slab configuration, i.e., where the media adjoining the slab are identical, although the extension to non-symmetric cases is straightforward. We also take the point of view that there is one EM wave in each of the media adjoining the slab, and hence two EM waves in the slab medium, i.e., a pair of EM waves associated with each interface between the optically-isotropic media (see Fig. 3).

Let us consider a pulsed interface mode propagating in the x-direction along a slab of thickness d parallel to the xz-plane. As seen in Fig. 3, the interface between medium 1 and the slab (medium 2) is located at $z = 0$, and the interface between medium 3 and the slab is at $z = d$. Invoking the assumption of a slowly-varying pulse envelope, (2.2) and (2.3), we can express the electric fields in the three media as

$$\vec{E}_1 = \hat{e}_1 E_1(z_1) \exp[i(k_{1x}x - k_{1z}z - \omega t)], \quad z < 0 \quad (3.1)$$

$$\begin{aligned}
\vec{E}_2 &= E_2^a + E_2^b \\
&= \hat{e}_2^a E_2^a(\zeta_2^a) \exp[i(k_{2x}x + k_{2z}z - \omega t)] \\
&\quad + \hat{e}_2^b E_2^b(\zeta_2^b) \exp[i(k_{2x}x - k_{2z}z' - \omega t)], \\
0 < z < d, \quad z' = z - d < 0
\end{aligned} \tag{3.2}$$

$$\begin{aligned}
\vec{E}_3 &= \hat{e}_3 E_3(\zeta_3) \exp[i(k_{3x}x + k_{3z}z' - \omega t)] \\
z' &> 0.
\end{aligned} \tag{3.3}$$

$E_1(\zeta_1)$ and $E_2(\zeta_2^a)$ are the amplitudes of $\vec{E}_1$ and $\vec{E}_2$, respectively, at the $z=0$ interface, E_2^b and E_3 are the amplitudes of $\vec{E}_2^b$ and $\vec{E}_3$ at the $z=d$ interface and

$$\zeta_1 = t - (x \cos \alpha_1 - z \sin \alpha_1)/v_1, \quad z < 0 \tag{3.4}$$

$$\zeta_2^a = t - (x \cos \alpha_2 + z \sin \alpha_2)/v_2, \quad 0 < z < d \tag{3.5}$$

$$\zeta_2^b = t - (x \cos \alpha_2 - z' \sin \alpha_2)/v_2, \quad -d < z' < 0 \tag{3.6}$$

$$\zeta_3 = t - (x \cos \alpha_3 + z' \sin \alpha_3)/v_3, \quad z' > 0 \tag{3.7}$$

k_{ix} and k_{iz} ($i=1,2,3$) are the wave vector components parallel and perpendicular to the interfaces, respectively. For surface wave (polariton) propagation, the real part of ϵ_1 must be negative while the real part of ϵ_2 is positive, or vice versa.

Imposing the boundary conditions of Eqs.(2.16) and (2.17) at each interface, we arrive at the following relations:

$$-\frac{\epsilon_1}{k_1} E_1(t - \frac{xk_x}{v_1 k_1}) = \frac{\epsilon_2}{k_2} [E_2(t - \frac{xk_x}{v_2 k_2}) - E_2(t - \frac{xk_x + dk_{2z}}{v_2 k_2}) \exp(ik_{2z}d)] \tag{3.8}$$

$$-\frac{k_{1z}}{k_1} E_1(t - \frac{xk_x}{v_1 k_1}) = \frac{k_{2z}}{k_2} [E_2(t - \frac{xk_x}{v_2 k_2}) + E_2(t - \frac{xk_x + dk_{2z}}{v_2 k_2}) \exp(ik_{2z}d)], \tag{3.9}$$

where

$$k_x = k_{1x} = k_{2x} = k_{3x}. \quad (3.10)$$

As compared to the case of continuous wave operation,^{2,8} Eqs.(3.8) and (3.9) lead to an extra condition for the matching of waves at the interfaces, namely,

$$\frac{\epsilon_2 k_{1z} + \epsilon_1 k_{2z}}{\epsilon_2 k_{1z} - \epsilon_1 k_{2z}} \frac{E_2(t-x/v_{2x})}{E_2(t-x/v_{2x} - d/v_{2z})} = e^{ik_{2z}d}, \quad (3.11)$$

where

$$v_{1x} \equiv \frac{v_1}{k_x/k_1} \quad (3.12)$$

$$v_{2x} \equiv \frac{v_2}{k_x/k_2} \quad (3.13)$$

$$v_{2z} \equiv \frac{v_2}{k_{2z}/k_2}. \quad (3.14)$$

To satisfy Eq.(3.11) at any time t ($t > 0$) and any spatial point x on the interfaces, the pulse envelope for the slab mode, E_2 , must be prepared as

$$E_2(t-x/v_{2x} - d/v_{2z}) = E_2(t-x/v_{2x}) f(d/v_{2z}), \quad (3.15)$$

where $f(d/v_{2z})$ is independent of x and t . For example, for an exponentially decaying pulse (i.e., a field which is turned on quickly and then decays exponentially) given as

$$E_2(t-x/v_{2x}) = e^{-(t-x/v_{2x})}, \quad (t > 0) \quad (3.16)$$

Eq.(3.11) reduces to the dispersion relation

$$\frac{\epsilon_2 k_{1z} + \epsilon_1 k_{2z}}{\epsilon_2 k_{1z} - \epsilon_1 k_{2z}} = e^{i(k_{2z} + 1/v_{2z})d}. \quad (3.17)$$

Combining Eqs.(3.8), (3.9) and (3.15), we see another requirement for pulsed surface mode propagation in the symmetric slab configuration,

$$v_{1x} = v_{2x}, \quad (3.18)$$

which is similar to Eq.(2.19) for the single-interface case.

Let us suppose the slab to be filled by a two-level atomic gas, wherein the hyperbolic secant envelope $E_2(\zeta) = \text{sech}(\zeta) = 2/(e^{-\zeta} + e^{\zeta})$ does not satisfy Eq.(3.15). The condition of (3.15) means that the pulses coming from the two interfaces inside the slab must combine to create a single pulse to match the pulses propagating in the media surrounding the slab (see Fig. 4). This is a strong restriction on the pulse envelope, and hence quasi-SIT does not exist as in the case of a single interface.

In the limit of continuous-wave operation, i.e., $E_1 \approx \text{constant}$ and $E_2 \approx \text{constant}$, Eq.(3.11) reduces to a well-known dispersion for the slab configuration,^{2,8}

$$\frac{\epsilon_2 k_{1z} + \epsilon_1 k_{2z}}{\epsilon_2 k_{1z} - \epsilon_1 k_{2z}} = e^{ik_{2z}d}. \quad (3.19)$$

For a very thick slab [$d \gg I_m(1/k_{2z})$], the above expression reduces to a single-interface relation,

$$\frac{k_{1z}}{k_{2z}} = - \frac{\epsilon_1}{\epsilon_2}. \quad (3.20)$$

IV. Summary and Final Remarks

Through a model consisting of a single gas-solid interface, we have considered the possible existence of SP with quasi-SIT. For generating such SP, the velocities of hyperbolic secant pulses must match on the interface. In this regard, it is suggested that

the pulse duration of the coherent light has to be substantially less than a nanosecond. An interesting behavior of transverse phase oscillations in the hyperbolic secant waves, caused by the interface effect, is revealed. Such a new phenomenon is not found in a homogeneous gas medium.

To experimentally check the existence of SP with quasi-SIT, the SF_6 -Al interface with CO_2 laser pulses might be a good candidate. Using 10.6- μm CO_2 laser pulses, Patel and Slusher^{9,10} have observed SIT in SF_6 . Since the dielectric constant of Al in this frequency region is negative, we anticipate SP with quasi-SIT.

Concerning the rising intensity of a coherent EM wave, it is interesting to note that as the field energy has been confined to a thin region near the surface, the intensity of SP should increase by a factor of 10 to 100 compared to that of the incident laser beam.^{3,11} Based on the optical "area theorem" in SIT,^{1,4,5} SP with quasi-SIT may be further increased by the choice of an appropriate "pulse area". For example, if an intense short pulse with area $A = 3\pi$ is injected into a gas medium, it will tend toward $A = 2\pi$ as it propagates and the pulse intensity will be amplified by the absorbing medium by a factor of 9/4.

The extension of pulsed SP propagation to a slab (two-interface) configuration has been considered. For the pulsed slab mode to occur, in addition to the pulse velocity matching requirement there is a restriction on the pulse envelope function of the slab mode so that quasi-SIT is no longer observed. Such a restriction is peculiar to pulsed surface wave propagation and does not apply to the continuous-wave case.

Acknowledgments

This work was supported in part by the Office of Naval Research, the Air Force Office of Scientific Research (AFSC), the United States Air Force, under Grant AFOSR-82-0046, and the U. S. Army Research Office. The United States Government is authorized to reproduce and distribute reprints for governmental purposes notwithstanding any copyright notation hereon. TFG acknowledges the Camille and Henry Dreyfus Foundation for a Teacher-Scholar Award (1975-84).

References

1. L. Allen and J. H. Eberly, Optical Resonance and Two-Level Atoms (Wiley, New York, 1975).
2. See, for example, the review article by G. Borstel and H. J. Falge, *Appl. Phys.* 16 (1978) 211.
3. C. R. Huo and X. Y. Huang, *Acta Phys. Sin.* 29 (1980) 1581.
[The English version is *Chinese Physics* 1 (1981) 601.]
4. S. L. McCall and E. L. Hahn, *Phys. Rev. Lett.* 18 (1967) 908.
5. S. L. McCall and E. L. Hahn, *Phys. Rev.* 183 (1969) 457.
6. See, for example, the review article by R. E. Slusher in *Progress in Optics*, Vol. XII, Ed. E. Wolf (North-Holland, Amsterdam, 1974), pp. 55-100.
7. C. Kittel, Introduction to Solid State Physics (Wiley, New York, 1976).
8. See, for example, E. Burstein, A. Hartstein, J. Schoenwald, A. A. Maradudin, D. L. Mills and R. F. Wallis in Polaritons, Ed. E. Burstein and F. DeMartini (Pergamon, New York, 1974) pp. 89-108.
9. C. K. N. Patel and R. E. Slusher, *Phys. Rev. Lett.* 19 (1967) 1019.
10. C. K. N. Patel, *Phys. Rev. A* 1 (1970) 979.
11. C. R. Chen, A. R. B. de Castro, Y. R. Shen and F. DeMartini, *Phys. Rev. Lett.* 43 (1979) 946.

Figure Captions

1. SP propagation on an interface. The wave vectors $\vec{k}_{g,m}$ and unit vectors $\hat{e}_{g,m}$ and $\hat{n}$ are indicated. When $\text{Re}\epsilon_m(\omega) < -\text{Re}\epsilon_g(\omega)$ and $\text{Re}\epsilon_g > 0$, SP will occur on the interface.
2. The propagation of normalized SP [Eqs.(2.32) and (2.33)] in the gas ($z > 0$) and solid ($z < 0$) media for real dielectric constants, where $\epsilon_g = 1$ and $(\epsilon_m, \Omega) = (A) (-10, 0)$, (B) $(-10, \pi/2)$, (C) $(-5, 0)$ and (D) $(-2, \pi/2)$. Here we have used $T = 0.5$, $\tau = 2$ picoseconds and z in units of c/ω .
3. SP propagation in a slab configuration. The wave vectors $\vec{k}_i$ and unit vectors $\hat{e}_i$ ($i = 1, 2, 3$) in the three media are indicated.
4. Schematic diagram of the conditions of Eqs.(3.8) and (3.9), where pulses from both interfaces must combine to form a single pulse to match the pulses in the media surrounding the slab. For a thin enough slab, there is a delay between the pulses given by $\zeta_d = d/v_{2z}$. The quantities ζ_1 and ζ_2 are defined as $\zeta_i = t - x/v_{ix}$.




Fig. 1




Fig. 2 (A)(B)






Fig. 2 (C) (D)






Fig. 4.

TECHNICAL REPORT DISTRIBUTION LIST, GEN

	<u>No. Copies</u>		<u>No. Copies</u>
Office of Naval Research Attn: Code 413 800 North Quincy Street Arlington, Virginia 22217	2	Naval Ocean Systems Center Attn: Mr. Joe McCartney San Diego, California 92152	1
ONR Pasadena Detachment Attn: Dr. R. J. Marcus 1030 East Green Street Pasadena, California 91106	1	Naval Weapons Center Attn: Dr. A. B. Amster, Chemistry Division China Lake, California 93555	1
Commander, Naval Air Systems Command Attn: Code 310C (H. Rosenwasser) Department of the Navy Washington, D.C. 20360	1	Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko Port Hueneme, California 93401	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12	Dean William Tolles Naval Postgraduate School Monterey, California 93940	1
Dr. Fred Saalfeld Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375	1	Scientific Advisor Commandant of the Marine Corps (Code RD-1) Washington, D.C. 20380	1
U.S. Army Research Office Attn: CRD-AA-IP P. O. Box 12211 Research Triangle Park, N.C. 27709	1	Naval Ship Research and Development Center Attn: Dr. G. Bosmajian, Applied Chemistry Division Annapolis, Maryland 21401	1
Mr. Vincent Schaper DTNSRDC Code 2803 Annapolis, Maryland 21402	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 19112	1
Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1	Mr. A. M. Anzalone Administrative Librarian PLASTEC/ARRADCOM Bldg 3401 Dover, New Jersey 07801	1
Dr. David L. Nelson Chemistry Program Office of Naval Research 800 North Quincy Street Arlington, Virginia 22217	1		

TECHNICAL REPORT DISTRIBUTION LIST, 056

	<u>No. Copies</u>		<u>No. Copies</u>
Dr. G. A. Somorjai Department of Chemistry University of California Berkeley, California 94720	1	Dr. W. Kohn Department of Physics University of California (San Diego) La Jolla, California 92037	1
Dr. J. Murday Naval Research Laboratory Surface Chemistry Division (6170) 455 Overlook Avenue, S.W. Washington, D.C. 20375	1	Dr. R. L. Park Director, Center of Materials Research University of Maryland College Park, Maryland 20742	1
Dr. J. B. Hudson Materials Division Rensselaer Polytechnic Institute Troy, New York 12181	1	Dr. W. T. Peria Electrical Engineering Department University of Minnesota Minneapolis, Minnesota 55455	1
Dr. Theodore E. Madey Surface Chemistry Section Department of Commerce National Bureau of Standards Washington, D.C. 20234	1	Dr. Chia-wei Woo Department of Physics Northwestern University Evanston, Illinois 60201	1
Dr. J. M. White Department of Chemistry University of Texas Austin, Texas 78712	1	Dr. Robert M. Hexter Department of Chemistry University of Minnesota Minneapolis, Minnesota 55455	1
Dr. Keith H. Johnson Department of Metallurgy and Materials Science Massachusetts Institute of Technology Cambridge, Massachusetts 02139	1	Dr. R. P. Van Duyne Chemistry Department Northwestern University Evanston, Illinois 60201	1
Dr. J. E. Demuth IBM Corporation Thomas J. Watson Research Center P. O. Box 218 Yorktown Heights, New York 10598	1	Dr. S. Sibener Department of Chemistry James Franck Institute 5640 Ellis Avenue Chicago, Illinois 60637	1
Dr. C. P. Flynn Department of Physics University of Illinois Urbana, Illinois 61801	1	Dr. M. G. Lagally Department of Metallurgical and Mining Engineering University of Wisconsin Madison, Wisconsin 53706	1

TECHNICAL REPORT DISTRIBUTION LIST, 056

	<u>No. Copies</u>		<u>No. Copies</u>
Dr. Robert Gomer Department of Chemistry James Franck Institute 5640 Ellis Avenue Chicago, Illinois 60637	1	Dr. K. G. Spears Chemistry Department Northwestern University Evanston, Illinois 60201	1
Dr. R. G. Wallis Department of Physics University of California, Irvine Irvine, California 92664	1	Dr. R. W. Plummer University of Pennsylvania Department of Physics Philadelphia, Pennsylvania 19104	1
Dr. D. Ramaker Chemistry Department George Washington University Washington, D.C. 20052	1	Dr. E. Yeager Department of Chemistry Case Western Reserve University Cleveland, Ohio 41106	1
Dr. P. Hansma Physics Department University of California, Santa Barbara Santa Barbara, California 93106	1	Professor D. Hercules University of Pittsburgh Chemistry Department Pittsburgh, Pennsylvania 15260	1
Dr. J. C. Hemminger Chemistry Department University of California, Irvine Irvine, California 92717	1	Professor N. Winograd The Pennsylvania State University Department of Chemistry University Park, Pennsylvania 16802	1
Dr. Martin Fleischmann Department of Chemistry Southampton University Southampton SO9 5NH Hampshire, England	1	Professor T. F. George The University of Rochester Chemistry Department Rochester, New York 14627	1
Dr. G. Rubloff IBM Thomas J. Watson Research Center P. O. Box 218 Yorktown Heights, New York 10598	1	Professor Dudley R. Herschbach Harvard College Office for Research Contracts 1350 Massachusetts Avenue Cambridge, Massachusetts 02138	1
Dr. J. A. Gardner Department of Physics Oregon State University Corvallis, Oregon 97331	1	Professor Horia Metiu University of California, Santa Barbara Chemistry Department Santa Barbara, California 93106	1
Dr. G. D. Stein Mechanical Engineering Department Northwestern University Evanston, Illinois 60201	1	Professor A. Steckl Rensselaer Polytechnic Institute Department of Electrical and Systems Engineering Integrated Circuits Laboratories Troy, New York 12181	1

TECHNICAL REPORT DISTRIBUTION LIST, 056

	<u>No. Copies</u>	<u>No. Copies</u>
Dr. John T. Yates Department of Chemistry University of Pittsburgh Pittsburgh, Pennsylvania 15260	1	
Professor G. H. Morrison Department of Chemistry Cornell University Ithaca, New York 14853	1	
Captain Lee Myers AFOSR/NC Bolling AFB Washington, D.C. 20332	1	
Dr. David Squire Army Research Office P. O. Box 12211 Research Triangle Park, NC 27709	1	
Professor Ronald Hoffman Department of Chemistry Cornell University Ithaca, New York 14853	1	

DATE
ILME