


AD-A124 798


EFFECT OF FREQUENCY-DEPENDENT SOIL PARAMETERS ON
REFLECTION COEFFICIENTS(U) HARRY DIAMOND LABS ADELPHI
MD N V HILL DEC 82 HDL-TR-2004

1/1

UNCLASSIFIED

F/G 20/14 NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

12

HDL-TR-2004

December 1982

Effect of Frequency-Dependent Soil Parameters on Reflection Coefficients

Norman V. Hill



DTIC
ELECTE
FEB 23 1983
S D

U.S. Army Electronics Research
and Development Command
Harry Diamond Laboratories
Adelphi, MD 20783

B

Approved for public release; distribution unlimited.

FILE COPY

83 02 022 087

6

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER HDL-TR-2004	2. GOVT ACCESSION NO. AD-A14 798	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Effect of Frequency-Dependent Soil Parameters on Reflection Coefficients		5. TYPE OF REPORT & PERIOD COVERED Technical Report
7. AUTHOR(s) Norman V. Hill		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Materiel Development and Readiness Command Alexandria, VA 22333		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Element: 62120A DA: 1L162120AH25
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE December 1982
		13. NUMBER OF PAGES 34
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES HDL Project No. X751E2 DRCMS Code: 612120H250011		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Universal network model Multiply reflected wave Varying regional parameter Spectral density Primary reflected wave		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The degree with which electromagnetic pulse (EMP) energy is predicted above a reflecting plane is strongly dependent on the nature of the plane. The reflection of electromagnetic energy from a surface can be accurately described mathematically, and equations which predict these fields are common knowledge to the EMP community. Although this is the case, some predictive analysis uses models for the earth's surface which are independent of frequency and considers only an average soil moisture content.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

1

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

20. ABSTRACT (Cont'd)

→ This report describes the varieties of electrical properties with frequency and moisture content. It applies these variations to a reflected EMP and assesses the energy difference between models which use parameters independent of frequency and those which use varying parameters. Finally, it discusses the variation of soil properties with depth and predicts the magnitude of energy, above the ground, which may result from this variation. ←

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

CONTENTS

	<u>Page</u>
1. INTRODUCTION	7
2. SOIL PARAMETERS	7
3. REFLECTION COEFFICIENTS FROM SOILS	12
3.1 Single Reflection	12
3.2 Multiple Reflection	18
4. ERROR ANALYSIS	24
5. CONCLUSION	27
LITERATURE CITED	27
DISTRIBUTION	29

FIGURES

1. Universal network model	8
2. Relative dielectric constant versus frequency at sample points between 0.5 and 600 MHz.	11
3. Conductivity versus frequency at sample points between 0.5 and 600 MHz	11
4. Polarization normal to plane of incidence	12
5. Polarization parallel to plane of incidence	12
6. Magnitude of reflection coefficients (R_H) using varying- parameter model at 5-, 10-, 15-, and 20-percent moisture	15
7. Phase of reflection coefficients (R_H) using varying parameter model at 5-, 10-, 15-, and 20-percent moisture	16
8. Magnitude of reflection coefficients (R_V) using varying- parameter model at 5-, 10-, 15-, and 20-percent moisture	16
9. Phase of reflection coefficients (R_V) using varying-parameter model at 5-, 10-, 15-, and 20-percent moisture	17

FIGURES (Cont'd)

	<u>Page</u>
10. Singly reflected wave	17
11. Multiply reflected wave	18
12. Magnitude of multiple reflection coefficient (R_H) for a two-layer earth. Varying-parameter model is used for upper layer (0.5 m thick), and network model is used for lower layer (infinite half plane)	21
13. Magnitude of multiple reflection coefficient (R_H) for a two-layer earth. Varying-parameter model is used for upper layer (1 m thick), and network model is used for lower layer (infinite half plane)	22
14. Magnitude of multiple reflection coefficient (R_H) for a two-layer earth. Varying-parameter model is used for upper layer (2 m thick), and network model is used for lower layer (infinite half plane)	22
15. Magnitude of multiple reflection coefficient (R_V) for a two-layer earth. Varying-parameter model is used for upper layer (0.5 m thick), and network model is used for lower layer (infinite half plane)	23
16. Magnitude of multiple reflection coefficient (R_V) for a two-layer earth. Varying-parameter model is used for upper layer (1 m thick), and network model is used for lower layer (infinite half plane)	23
17. Magnitude of multiple reflection coefficient (R_V) for a two-layer earth. Varying-parameter model is used for upper layer (2 m thick), and network model is used for lower layer (infinite half plane)	24
18. Comparison between reflection coefficient as predicted by varying regional parameter model, network model (both at 10-percent moisture), and constant-parameter model (conductivity = 7 mmho/m, dielectric constant = 15)	26

TABLES

	<u>Page</u>
1. Coefficient a_n for Universal Soil	9
2. Percentage of Error for Variable-Parameter Model (Standard) and Network Model for Various Moisture Contents	25
3. Percentage of Error for Variable-Parameter Model (Standard) and Constant-Parameter Model for Various Moisture Contents	26

DTIC
ELECTE
S FEB 23 1983 **D**
B



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
PER CALL JC	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

1. INTRODUCTION

If the conductivity and dielectric constant of two distinct media are known, the amount of electromagnetic energy which will be reflected at their interface can be related to the incident energy through the Fresnel equations. On a large scale, the earth-air boundary is an example of such an interface. In comparison to the earth, the electrical properties of the air can be considered relatively independent of regional variations. Therefore, obtaining typical electrical properties of the soil in a particular region becomes a primary objective if the reflection coefficients are desired.

With regional values, the reflection of electromagnetic energy, such as that encountered after a high-altitude nuclear burst, can be calculated. Without regional values, however, the spectrum of energy reflected may be inadequately predicted. Any method of approximating conductivity and dielectric constant will produce an error if it excludes regional variables such as structure or mineral content, or if it excludes frequency and moisture content. To determine whether this error should cause significant concern, the actual values for conductivity and dielectric constant can be measured and compared with predicted values. In this way, the reflected energy spectrum can be more accurately predicted.

2. SOIL PARAMETERS

In order to determine the energy of a pulse wave reflected from the surface of the earth, the electrical properties of this soil/air boundary must be known. The Fresnel equations, which describe the reflection of electromagnetic energy, require that the conductivity, permittivity, and permeability of both the air and the soil be known. Under normal conditions, and in comparison to soil, the electrical properties of air are approximately equal to those of free space. Therefore, determining the electrical properties of the earth becomes a primary concern.

Several studies have been conducted concerning the electrical properties of the soil. The results of these studies state that the conductivity (σ) and permittivity (ϵ) can be predicted at a specified frequency, if the moisture content is known. The permeability (μ), which is a function of the ferrous mineral content, deviates slightly from that of free space in most regions.

Scott¹ measured numerous samples over the frequency range of 10^2 to 10^6 Hz. After averaging his data, he produced a set of curves for

¹J. H. Scott, *Electrical and Magnetic Properties of Rock and Soil*, U.S. Geological Survey, Note 18 (1966).

conductivity and dielectric constant as functions of frequency. These curves, which have become known as Scott's universal curves, have been curve fit with a second-order surface fit and are mathematically represented in equations (1) and (2).

Scott's curve fit for conductivity is

$$K = -0.604 + 1.640W - 0.062F + 0.062W^2 - 0.070FW + 0.021F^2; \quad (1)$$

the curve fit for relative dielectric constant is

$$D = 4.905 + 1.308W - 0.971F + 0.111W^2 - 0.160FW + 0.059F^2, \quad (2)$$

where

$K = \log_{10}$ of conductivity (mmho/m),
 $D = \log_{10}$ of dielectric constant (ϵ/ϵ_0),
 $W = \log_{10}$ of water content (percent by volume), and
 $F = \log_{10}$ of frequency (Hz).

Since Scott's work encompasses a large variety of laboratory-measured soil samples (samples which correlated well with field measurements), equations (1) and (2) give an average of conductivity and dielectric constant over various regions.

C. L. Longmire² developed a time-domain representation called the universal RC network model (fig. 1). The basic assumption of this model is that the soil can be regarded electrically as an equivalent network of resistors and capacitors. Longmire made no laboratory measurements, but by using Scott's curves and data that he received by private consultation with Wilkenfeld,² he extended the expected validity of his model over the frequency range of 10^0 to 3×10^{12} Hz.




Figure 1. Universal network model.

²C. L. Longmire, *A Universal Impedance for Soils*, Defense Nuclear Agency, DNA 3788T (1975).

Longmire's model states that

$$C_{\infty} = \epsilon_0 \epsilon_{\infty} \quad , \quad C_n = \epsilon_0 a_n \quad ,$$

$$R_0 = \sigma_0^{-1} \quad , \quad R_n = \frac{1}{2\pi f_n C_n} \quad ,$$

where

C is capacitance,

a is a constant,

R is resistance,

R_0 is the resistance of the circuit that is asymptotically approached as frequency is decreased,

σ is conductivity,

f is frequency, and

the subscript ∞ indicates a value which is asymptotically approached as frequency is increased.

The relative dielectric constant of the soil is

$$\epsilon_r = \epsilon/\epsilon_0 = \epsilon_{\infty} + \sum_{n=1}^N \frac{a_n}{1 + (f/f_n)^2} \quad , \quad (3)$$

and the conductivity is

$$\sigma = \sigma_0 + 2\pi\epsilon_0 \sum_{n=1}^N a_n f_n \frac{(f/f_n)^2}{1 + (f/f_n)^2} \text{ (mho/m)} \quad , \quad (4)$$

where f_n accounts for moisture content. Table 1 gives coefficients for universal soil as derived by Longmire's model.

TABLE 1. COEFFICIENT a_n FOR UNIVERSAL SOIL

n	a_n	n	a_n	n	a_n
1	3.40×10^6	6	1.33×10^2	11	9.80×10^{-1}
2	2.74×10^5	7	2.72×10	12	3.92×10^{-1}
3	2.58×10^4	8	1.25×10	13	1.73×10^{-1}
4	3.38×10^3	9	4.80		
5	5.26×10^2	10	2.17		

To obtain a standard for evaluating the error which might be incurred by applying the results of this network model in a region which does not follow the typical soil parameters, laboratory measurements were made of ϵ_r and σ for five samples of soil taken from the Harry Diamond Laboratories, Woodbridge Research Facility, Woodbridge, VA. The National Bureau of Standards conducted these measurements over the frequency range of 5×10^6 to 6×10^8 Hz. Following Scott's work, a second-order surface fit was made for these data as given in equations (5) and (6):

$$D = 5.886 - 1.045F - 2.055W + 0.077FW + 0.056F^2 + 1.180W^2, \quad (5)$$

$$K = -3.233 + 0.6453F - 0.448W - 0.105FW - 0.0113F^2 + 0.8876W^2. \quad (6)$$

Equations (5) and (6) are henceforth referred to as the varying regional parameter equations.

The averaged values at 5-, 10-, 15-, 20-, and 25-percent moisture content for conductivity and dielectric constant are shown in figures 2 and 3. Also shown are the values predicted by the Longmire universal network model for 10-percent moisture content (eq (3) and (4)).

As can be seen from figure 3, averaged values for conductivity are considerably below the values predicted by the network model. Since these data were obtained in a region of higher than average rainfall, and taken from the uppermost soil, it is believed that their values indicate only that the surface soil possesses a low conductivity. Several other field measurements were taken near the laboratory, measurements which indicate that the conductivity of the soil increases sharply a few feet below the surface of the earth. Unfortunately, the samples were too few to determine where the sharp increase took place nor what conductivity the soil might possess in the lower strata.

When either conductivity or dielectric constant changes from one homogeneous medium to another, as is the case at the Woodbridge Research Facility, a second medium for reflection is provided. Because these boundaries are close to each other, the energy which is transmitted through the primary boundary will undergo a second reflection at the secondary boundary. The wave which will ultimately be seen by an observer will be a combination of an incident wave, a primary reflected wave, and a series of multiply reflected waves. This problem is discussed briefly after the reflection from the primary boundary is discussed.




Figure 2. Relative dielectric constant versus frequency at sample points between 0.5 and 600 MHz. Longmire's curve for 10-percent moisture is also shown for comparison.




Figure 3. Conductivity versus frequency at sample points between 0.5 and 600 MHz. Longmire's curve for 10-percent moisture is also shown for comparison.

3. REFLECTION COEFFICIENTS FROM SOILS

3.1 Single Reflection

Soils, like most common materials, fall in the category of lossy dielectrics. Fresnel's equations (as discussed in many electromagnetics texts³) describe the reflection/transmission process of electric and magnetic components of an electromagnetic field across the boundaries of two distinct media. The following equations relate to figures 4 and 5.

For the E field normal to the plane of incidence,

$$E_1 = \frac{\mu_2 k_1 (\cos \theta_2 + \cos \theta_0)}{\mu_2 k_1 \cos \theta_2 + \mu_1 k_2 \cos \theta_1} E_0 \quad (7)$$

$$E_2 = \frac{\mu_2 k_1 \cos \theta_0 - \mu_1 k_2 \cos \theta_1}{\mu_2 k_1 \cos \theta_2 + \mu_1 k_2 \cos \theta_1} E_0 \quad (8)$$




Figure 4. Polarization normal to plane of incidence.




Figure 5. Polarization parallel to plane of incidence.

³J. A. Stratton, *Electromagnetic Theory*, McGraw-Hill Book Co. (1941).

For the H field normal to the plane of incidence,

$$H_1 = \frac{\mu_1 k_2 (\cos \theta_2 + \cos \theta_0)}{\mu_1 k_2 \cos \theta_2 + \mu_2 k_1 \cos \theta_1} H_0 , \quad (9)$$

$$H_2 = \frac{\mu_1 k_2 \cos \theta_0 - \mu_2 k_1 \cos \theta_1}{\mu_1 k_2 \cos \theta_0 + \mu_2 k_1 \cos \theta_1} H_0 , \quad (10)$$

where θ is angle of incidence, and k_i is the complex propagation constant defined by

$$k_i^2 = j\omega\mu_i(\sigma_i - j\omega\epsilon_i) ,$$

where $\omega = 2\pi f$.

Through Snell's law

$$\sin \theta_0 = \sin \theta_2 , \text{ and}$$

$$k_2 \sin \theta_0 = k_1 \sin \theta_1 .$$

The reflection coefficients can be written

$$R_H = \frac{E_2}{E_0} = \frac{\mu_2 k_1 \cos \theta_0 - \mu_1 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}}{\mu_2 k_1 \cos \theta_0 + \mu_1 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}}$$

for E normal to the plane of incidence, and

$$R_V = \frac{H_2}{H_0} = \frac{\mu_1 k_2^2 \cos \theta_0 - \mu_2 k_1 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}}{\mu_1 k_2^2 \cos \theta_0 + \mu_2 k_1 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}}$$

for H normal to the plane of incidence.

By considering a typical air/earth interface, these formulas can be further simplified. Medium 2 (characterized by σ_2 , μ_2 , ϵ_2) is that of the earth, and medium 1 (characterized by σ_1 , μ_1 , ϵ_1) is that of air; since

$$\mu_1 \approx \mu_2 \approx \mu_0 ,$$

$$\epsilon_1 \approx \epsilon_0 ,$$

$$\sigma_1 \approx 0 ,$$

the reflection coefficients can be simplified to

$$R_H = \frac{\cos \theta_0 - \sqrt{\left(\epsilon_r - j \frac{\sigma_2}{\epsilon_0 \omega}\right) - \sin^2 \theta_0}}{\cos \theta_0 + \sqrt{\left(\epsilon_r - j \frac{\sigma_2}{\epsilon_0 \omega}\right) - \sin^2 \theta_0}} \quad (11)$$

and

$$R_V = \frac{\left(\epsilon_r - j \frac{\sigma_1}{\epsilon_0 \omega}\right) \cos \theta_0 - \sqrt{\left(\epsilon_r - j \frac{\sigma_1}{\epsilon_0 \omega}\right) - \sin^2 \theta_0}}{\left(\epsilon_r - j \frac{\sigma_1}{\epsilon_0 \omega}\right) \cos \theta_0 + \sqrt{\left(\epsilon_r - j \frac{\sigma_1}{\epsilon_0 \omega}\right) - \sin^2 \theta_0}} , \quad (12)$$

where $\epsilon_r = \epsilon_1/\epsilon_0$ and subscripts H and V refer to horizontal and vertical components.

Figures 6, 7, 8, and 9 show the magnitudes and phases of reflection coefficients R_H and R_V using varying regional parameter equations. The angle of incidence is 60° .

The incident and reflected waves combine to form what is generally referred to as the total wave. These equations have been developed in other texts⁴ and are restated here:

⁴M. A. Messier, *The Effects of Ground Reflection on Observed EMP Waveforms*, Defense Nuclear Agency, DNA 3370T (1974).

$$E_H = E_0 \left[1 + R_H e^{-j(h/\lambda)} \right] \cos \phi , \quad (13)$$

$$E_V = E_0 \left[1 + R_V e^{-j(h/\lambda)} \right] \sin \phi \cos \theta , \quad (14)$$

$$E_R = E_0 \left[1 + R_V e^{-j(j/\lambda)} \right] \sin \phi \cos \theta , \quad (15)$$

where

$\lambda \equiv$ wavelength,
 $h \equiv$ distance between point of reflection and observer,
 $\phi \equiv$ polarization of E vector, parallel to vector n,
 $E_R \equiv$ radial wave, and
 $E_0 \equiv$ incident wave.

These equations apply to the geometry of figure 10 and assume that the distance between the source of the pulse and either the observer or the earth is much greater than the distance between the earth and the observer.




Figure 6. Magnitude of reflection coefficients (R_H) using varying-parameter model at 5-, 10-, 15-, and 20-percent moisture.




Figure 7. Phase of reflection coefficients (R_H) using varying-parameter model at 5-, 10-, 15-, and 20-percent moisture.




Figure 8. Magnitude of reflection coefficients (R_V) using varying-parameter model at 5-, 10-, 15-, and 20-percent moisture.




Figure 9. Phase of reflection coefficients (R_V) using varying-parameter model at 5-, 10-, 15-, and 20-percent moisture.




Figure 10. Singly reflected wave.

3.2 Multiple Reflection

If there is a marked increase in soil conductivity at some depth, as is the case for most of the eastern seaboard,⁵ a transmitted pulse will undergo a primary reflection and a series of multiple reflections. Figure 11 depicts this process. The total wave seen by an observer just above the earth will be composed of an incident wave, a primary reflected wave, and a series of multiply reflected waves.⁶

The multiply reflected pulse is a geometric series:

$$E_r = E_0 \left[1 + e^{j\Delta_1} (\rho + \tau\tau'\rho' e^{j\Delta_2} + \tau\tau'\rho'^{-2}\rho'' e^{j2\Delta_2} + \tau\tau'\rho'^{-3}\rho''^2 e^{j3\Delta_2} \dots) \right] \quad (16)$$

(for zero polarization)

where

E_r = resultant E field,
 ρ = reflection coefficient,
 τ = transmission coefficient,
 Δ_1 and Δ_2 account for phase delay and attenuation in medium 1 and medium 2, respectively, and
 primes indicate the number of times the wave has been reflected.




Figure 11. Multiply reflected wave.

⁵E. D. Sunde, *Earth Conduction Effects in Transmission Systems*, D. Van Nostrand Co. Inc. (1968).

⁶M. V. Klein, *Optics*, T. Wiley and Sons Inc. (1970).

Equation (16) can be reduced to the closed-form equivalent:

$$E_r = E_0 \left[\tau \tau' \rho' e^{j\Delta_1} \left(\frac{1}{1 + \rho \rho' e^{j\Delta_1}} \right) \right] . \quad (17)$$

Phase delay and attenuation can be found by

$$\Delta_1 = \frac{2h\omega}{\cos \theta_1} \left| \frac{\mu_2 \epsilon_2}{2} \sqrt{1 + \left(\frac{\sigma_2}{\omega \epsilon_2} \right)^2} - 1 \right|^{1/2} ,$$

$$\Delta_2 = \Delta_1 + \frac{2h\omega}{\cos \theta_1} \left| \frac{\mu_2 \epsilon_2}{2} \sqrt{1 + \left(\frac{\sigma_2}{\omega \epsilon_2} \right)^2} + 1 \right|^{1/2} ,$$

with

$$\rho_H = \frac{k_1 \cos \theta_0 - \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}}{k_1 \cos \theta_0 + \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}} , \quad (18)$$

$$\rho'_H = \frac{\sqrt{k_2^2 - k_1^2 \sin^2 \theta} - \sqrt{k_3^2 - k_1^2 \sin^2 \theta}}{\sqrt{k_2^2 - k_1^2 \sin^2 \theta} + \sqrt{k_3^2 - k_1^2 \sin^2 \theta}} , \quad (19)$$

$$\tau_H = \frac{2k_1 \cos \theta_0}{k_1 \cos \theta_0 + \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}} , \quad (20)$$

$$\tau'_H = \frac{2\sqrt{k_2^2 - k_1^2 \sin^2 \theta}}{\sqrt{k_2^2 - k_1^2 \sin^2 \theta} + \sqrt{k_3^2 - k_1^2 \sin^2 \theta}} , \quad (21)$$

for E-field normal to plane of incidence, and

$$\rho_V = \frac{k_2^2 \cos \theta_0 - k_1 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}}{k_2^2 \cos \theta_0 + k_1 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}}, \quad (22)$$

$$\rho'_V = \frac{k_3^2 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_1} - k_2^2 \sqrt{k_3^2 - k_1^2 \sin^2 \theta_1}}{k_3^2 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_1} + k_2^2 \sqrt{k_3^2 - k_1^2 \sin^2 \theta_1}}, \quad (23)$$

$$\tau_V = \frac{2k_2^2 \cos \theta_0}{k_2^2 \cos \theta_0 + k_1 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_0}}, \quad (24)$$

$$\tau'_V = \frac{2k_2^2 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_1}}{k_3^2 \sqrt{k_2^2 - k_1^2 \sin^2 \theta_1} + k_2^2 \sqrt{k_3^2 - k_1^2 \sin^2 \theta_1}}, \quad (25)$$

for E-field parallel to plane of incidence.

The reflection coefficients (R_H) for multiply reflected waves in a stratified medium are shown in figures 12, 13, and 14 (eq (18) through (21)). Figures 15, 16, and 17 show R_V for multiply reflected waves (eq (22) through (25)). Here, the depth of medium 2 is 1/2, 1, and 2 m, respectively. Media 1 and 3 are considered infinite. The propagation constant k_1 is that of free space. Constant k_2 was generated from the variable regional parameter equation and k_3 was generated using the network model. The angle of incidence is 60°.

As can be expected, for the multiply reflected wave, the lower frequency components are more readily transmitted through the soil/soil boundary. At higher frequencies, a declining magnitude is due to increased attenuation in addition to increased soil conductivity.

Since the properties of the upper stratification below 10^5 Hz are not known, and the properties of the lower stratification are only conjectured to follow the universal network model, this analysis is not included in the final analysis of the reflected pulse; however, it is discussed here to show how a homogeneous model which uses either the universal network model or the variable regional parameter model may deviate from a possible real situation.




Figure 12. Magnitude of multiple reflection coefficient (R_H) for a two-layer earth. Varying-parameter model is used for upper layer (0.5 m thick), and network model is used for lower layer (infinite half plane).




Figure 13. Magnitude of multiple reflection coefficient (R_H) for a two-layer earth. Varying-parameter model is used for upper layer (1 m thick), and network model is used for lower layer (infinite half plane).




Figure 14. Magnitude of multiple reflection coefficient (R_H) for a two-layer earth. Varying-parameter model is used for upper layer (2 m thick), and network model is used for lower layer (infinite half plane).




Figure 15. Magnitude of multiple reflection coefficient (R_V) for a two-layer earth. Varying-parameter model is used for upper layer (0.5 m thick), and network model is used for lower layer (infinite half plane).




Figure 16. Magnitude of multiple reflection coefficient (R_V) for a two-layer earth. Varying-parameter model is used for upper layer (1 m thick), and network model is used for lower layer (infinite half plane).




Figure 17. Magnitude of multiple reflection coefficient (R_v) for a two-layer earth. Varying-parameter model is used for upper layer (2 m thick), and network model is used for lower layer (infinite half plane).

4. ERROR ANALYSIS

A convenient way to represent the total energy on a per ohm basis is by integrating the magnitude of the spectral density over the range of frequencies of interest:

$$E = \frac{1}{2\pi} \int_{-\infty}^{\infty} |E(\omega)|^2 d\omega . \quad (26)$$

The energy difference between two real spectra is

$$\frac{1}{\pi} \int_0^{\infty} |E(\omega)|^2 - |\bar{E}(\omega)|^2 d\omega . \quad (27)$$

Here, $E(\omega)$ represents the spectrum of the total E field of the signal used as the basis for analysis, and $\bar{E}(\omega)$ is the approximating signal. The percentage of error (P_e) is

$$P_e = \frac{\int_0^\infty \{ |E(\omega)|^2 - |\bar{E}(\omega)|^2 \} d\omega}{\int_0^\infty |E(\omega)|^2 d\omega} \times 100\% \quad (28)$$

Since it is not possible to numerically integrate over the entire spectrum, the analysis will include the extrapolated spectrum of 10^5 to 10^9 Hz in which the variable parameter model is valid. Also, to eliminate the confusion or cancellation due to phase shift caused by the delay of the reflected wave, the observer is placed an incremental distance above the earth's surface. Here also, the analysis is done for zero polarization (i.e., R_v is not used). Table 2 lists the percentages of error between the total energies of waves above soil modeled by the variable-parameter model and soil modeled by the network model with the variable-parameter model as the standard.

The values show that the spectra $E(\omega)$ and $\bar{E}(\omega)$ are displaced from each other and will probably give values for P_e which will be no less than 50 percent.

Another model which is often used for calculating propagation constants and reflection coefficients is the constant-parameter model. This model, as the name implies, assumes that the conductivity and dielectric constant are constant over the entire spectrum of frequencies and range of possible moisture contents. Typical values for these parameters are $\sigma = 7$ mmho/m and $\epsilon_r = 15$ for the Woodbridge Research Facility. The values for the percentage of error are listed in table 3.

These values indicate that by judicious selection of σ and ϵ_r the percentage of error can be reduced. However, some error is inevitable because the spectrum predicted by the constant-parameter model will have a sharper roll-off, as demonstrated in the comparison of the three models given in figure 18.

TABLE 2. PERCENTAGE OF ERROR FOR VARIABLE-PARAMETER MODEL (STANDARD) AND NETWORK MODEL FOR VARIOUS MOISTURE CONTENTS

Moisture content (%)	Percentage of error (%)
5	59.0
10	-75.2
15	-80.4
20	-82.7

TABLE 3. PERCENTAGE OF ERROR FOR VARIABLE-
PARAMETER MODEL (STANDARD) AND CONSTANT-
PARAMETER MODEL FOR VARIOUS MOISTURE CONTENTS

Moisture content (%)	Percentage of error (%)
5	68.9
10	63.0
15	54.4
20	43.8




Figure 18. Comparison between reflection coefficient as predicted by varying regional parameter model, network model (both at 10-percent moisture), and constant-parameter model (conductivity = 7 mmho/m, dielectric constant = 15).

5. CONCLUSION

The percentage of error for the energy difference between two signals was minimized by using the constant-parameter model. This, however, does not mean that the constant-parameter model is the best possible method. The spectra of the reflected wave had a sharper roll-off than either the variable-parameter model or the network model. This means that there will be some minimum error which cannot be eliminated.

If there were data between 10^2 and 10^6 Hz, the network model could be altered to more closely approximate the true nature of the soil. A convenient method for obtaining the soil parameter at any frequency and moisture content would then exist. It could conceivably minimize the percentage error below 10 percent.

However, the problem generated by the multiple reflection from a stratified medium would still remain. The only solution for this would be to follow the stated equations for multiple reflections after the lower stratification has been characterized by extensive field measurements.

LITERATURE CITED

- (1) J. H. Scott, Electrical and Magnetic Properties of Rock and Soil, U.S. Geological Survey, Note 18 (1966).
- (2) C. L. Longmire, A Universal Impedance for Soils, Defense Nuclear Agency, DNA 3788T (1975).
- (3) J. A. Stratton, Electromagnetic Theory, McGraw-Hill Book Co. (1941).
- (4) M. A. Messier, The Effects of Ground Reflection on Observed EMP Waveforms, Defense Nuclear Agency, DNA 3370T (1974).
- (5) E. D. Sunde, Earth Conduction Effects in Transmission Systems, D. Van Nostrand Co. Inc. (1968).
- (6) M. V. Klein, Optics, T. Wiley and Sons Inc. (1970).

DISTRIBUTION

ADMINISTRATOR
DEFENSE TECHNICAL INFORMATION CENTER
ATTN DTIC-DDA (12 COPIES)
CAMERON STATION, BUILDING 5
ALEXANDRIA, VA 22314

DIRECTOR
US ARMY MATERIEL SYSTEMS ANALYSIS
ACTIVITY
ATTN DRXS-MP
ABERDEEN PROVING GROUND, MD 21005

DIRECTOR
US ARMY BALLISTIC RESEARCH
LABORATORY
ATTN DRDAR-TSB-S (STINFO)
ABERDEEN PROVING GROUND, MD 21005

US ARMY ELECTRONICS TECHNOLOGY
& DEVICES LABORATORY
ATTN DELET-DD
ATTN DELSD-L
FT MONMOUTH, NJ 07703

HQ, USAF/SAMI
WASHINGTON, DC 20330

TELEDYNE BROWN ENGINEERING
CUMMINGS RESEARCH PARK
ATTN DR. MELVIN L. PRICE, MS-44
HUNTSVILLE, AL 35807

DIRECTOR
DEFENSE ADVANCED RSCH PROJ AGENCY
ARCHITECT BUILDING
1400 WILSON BLVD
ATTN TIO
ARLINGTON, VA 22209

FEDERAL EMERGENCY MANAGEMENT AGENCY
500 C STREET SW
ATTN JAMES W. KERR
MITIGATION & RESEARCH
WASHINGTON, DC 20472

DIRECTOR
DEFENSE COMMUNICATIONS AGENCY
ATTN CODE C312
ATTN CODE C313
WASHINGTON, DC 20305

DEFENSE COMMUNICATIONS ENGINEERING
CENTER
1860 WIEHLE AVENUE
ATTN CODE R720, C. STANSBERRY
ATTN CODE R123, RSCH LIB
ATTN CODE R400
RESTON, VA 22090

DIRECTOR
DEFENSE INTELLIGENCE AGENCY
ATTN RDS-3A
ATTN RDS-3A4, POMPONIO PLAZA
WASHINGTON, DC 20301

DIRECTOR
DEFENSE NUCLEAR AGENCY
ATTN RAEV, ELECTRONICS VULNERABILITY
DIV
ATTN TITL, TECHNICAL LIBRARY DIV
ATTN RAE, EMP EFFECTS DIV
WASHINGTON, DC 20305

COMMANDER
FIELD COMMAND
DEFENSE NUCLEAR AGENCY
ATTN FCPR
ATTN FCSPM, J. SMITH
ATTN FCLMC
KIRKLAND AFB, NM 87115

NATIONAL COMMUNICATIONS SYSTEM
OFFICE OF THE MANAGER
DEPARTMENT OF DEFENSE
ATTN NCS-TS, CHARLES D. BODSON
WASHINGTON, DC 20305

DIRECTOR
NATIONAL SECURITY AGENCY
DEPARTMENT OF DEFENSE
ATTN R-52, O. VAN GUNTEN
ATTN S232, D. VINCENT
FT MEAD, MD 20755

UNDER SECRETARY OF DEF FOR RSCH & ENGRG
DEPARTMENT OF DEFENSE
ATTN G. BARSE
ATTN S & SS (OS)
WASHINGTON, DC 20301

COMMANDER
BMD SYSTEM COMMAND
DEPARTMENT OF THE ARMY
PO BOX 1500
ATTN BMDSC-AOLIB
HUNTSVILLE, AL 35807

COMMANDER
ERADCOM TECHNICAL SUPPORT ACTIVITY
DEPARTMENT OF THE ARMY
ATTN TECHNICAL LIBRARY DIV
FT MONMOUTH, NJ 07703

COMMANDER
US ARMY COMM-ELEC ENGRG INSTAL
AGENCY
ATTN CCC-PRSO-S
ATTN CCC-CED-SES
FT HUACHUCA, AZ 85613

COMMANDER
US ARMY COMMUNICATIONS COMMAND
COMBAT DEVELOPMENT DIVISION
ATTN ATSI-CD-MD
FT HUACHUCA, AZ 85613

DISTRIBUTION (Cont'd)

CHIEF
US ARMY COMMUNICATIONS
SYS AGENCY
ATTN CCM-RD-T
ATTN CCM-AD-SV
FT MONMOUTH, NJ 07703

PROJECT MANAGER
US ARMY COMMUNICATIONS RES
& DEV COMMAND
ATTN DRCPM-ATC
ATTN DRCPM-TDS-BSI
FT MONMOUTH, NJ 07703

US ARMY INTEL THREAT
ANALYSIS DETACHMENT
ROOM 2201, BLDG A
ARLINGTON HALL STATION
ATTN RM 2200, BLDG A
ARLINGTON, VA 22212

COMMANDER
US ARMY TEST & EVALUATION COMMAND
ATTN DRSTE-FA
ABERDEEN PROVING GROUND, MD 21005

COMMANDER
WHITE SANDS MISSILE RANGE
DEPARTMENT OF THE ARMY
ATTN STEWS-TE-AN, J. OKUMA
WHITE SANDS MISSILE RANGE, NM 88002

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
ATTN PME 117-215
WASHINGTON, DC 20360

COMMANDER
NAVAL OCEAN SYSTEMS CENTER
ATTN CODE 015, C. FLETCHER
ATTN CODE 7240, S. W. LICHTMAN
SAN DIEGO, CA 92152

DIRECTOR
NAVAL RESEARCH LABORATORY
ATTN CODE 4104, EMANUAL L. BRANCATO
ATTN CODE 2627, DORIS R. FOLEN
ATTN CODE 6623, RICHARD L. STATLER
ATTN CODE 6624
WASHINGTON, DC 20375

COMMANDER
NAVAL SURFACE WEAPONS CENTER
ATTN CODE WA51RH, RM 130-108
ATTN CODE F32, EDWIN R. RATHBURN
WHITE OAK, SILVER SPRING, MD 20910

COMMANDER
NAVAL SURFACE WEAPONS CENTER
DAHLGREN LABORATORY
ATTN CODE DF-56
DALHGREN, VA 22448

AF WEAPONS LABORATORY, AFSC
ATTN NTN
ATTN NT
ATTN EL, CARL E. BAUM
ATTN ELXT
ATTN SUL
ATTN CA
ATTN ELA, J. P. CASTILLO
ATTN ELP
ATTN ELT, W. PAGE
ATTN NXS
KIRTLAND AFB, NM 87117

UNIVERSITY OF CALIFORNIA
LAWRENCE LIVERMORE LABORATORY
PO BOX 808
ATTN TECH INFO DEPT
ATTN L-06, T. DONICH
ATTN L-545, D. MEEKER
ATTN L-156, E. MILLER
ATTN L-10, H. KRUGER
ATTN FCPRL
ATTN H. S. CABAYAN
LIVERMORE, CA 94550

LOS ALAMOS SCIENTIFIC LABORATORY
PO BOX 1663
ATTN BRUCE W. NOEL
ATTN CLARENCE BENTON
LOS ALAMOS, NM 87545

SANDIA LABORATORIES
PO BOX 5800
ATTN C. N. VITTITOE
ATTN R. L. PARKER
ATTN ELMER F. HARTMAN
ALBUQUERQUE, NM 87115

AEROSPACE CORP
PO BOX 92957
ATTN C. B. PEARLSTON
ATTN IRVING M. GARFUNKEL
ATTN JULIAN REINHEIMER
ATTN LIBRARY
ATTN CHARLES GREENHOW
LOS ANGELES, CA 90009

AGABIAN ASSOCIATES
250 NORTH NASH STREET
ATTN LIBRARY
EL SEGUNDO, CA 90245

AVCO RESEARCH & SYSTEMS GROUP
201 LOWELL STREET
WILMINGTON, MA 01887

BATTELLE MEMORIAL INSTITUTE
505 KING AVENUE
ATTN EUGENE R. LEACH
COLUMBUS, OH 43201

DISTRIBUTION (Cont'd)

BDM CORP
7915 JONES BRANCH DR
ATTN CORPORATE LIBRARY
MCLEAN, VA 22102

BDM CORP
PO BOX 9274
ALBUQUERQUE INTERNATIONAL
ATTN LIB
ALBUQUERQUE, NM 87119

BENDIX CORP
RESEARCH LABORATORIES DIVISION
BENDIX CENTER
ATTN MAX FRANK
SOUTHFIELD, MI 48075

BOEING COMPANY
PO BOX 3707
ATTN HOWARD W. WICKLEIN
ATTN D. E. ISBELL
ATTN DAVID KEMLE
ATTN B. C. HANRAHAN
ATTN KENT TECH LIB
SEATTLE, WA 98124

BROWN ENGINEERING COMPANY, INC
CUMMINGS RESEARCH PARK
ATTN FRED LEONARD
HUNTSVILLE, AL 35807

BURROUGHS CORP
FEDERAL & SPECIAL SYSTEMS GROUP
CENTRAL AVE & ROUTE 252
PO BOX 517
ATTN ANGELO J. MAURIELLO
PAOLI, PA 19301

CALSPAN CORP
PO BOX 400
ATTN TECH LIBRARY
BUFFALO, NY 14225

CINCINNATI ELECTRONICS CORP
2630 GLENDALE - MILFORD ROAD
ATTN LOIS HAMMOND
CINCINNATI, OH 45241

COMPUTER SCIENCES CORP
6565 ARLINGTON BLVD
ATTN RAMONA BRIGGS
FALLS CHURCH, VA 22046

COMPUTER SCIENCES CORP
1400 SAN MATEO BLVD, SE
ATTN LIBRARY
ATTN ALVIN SCHIFF
ALBUQUERQUE, NM 87108

CONTROL DATA CORP
PO BOX 0
ATTN JACK MEEHAN
MINNEAPOLIS, MN 55440

DIKEWOOD CORP
1613 UNIVERSITY BLVD, NE
ATTN TECH LIB
ATTN L. WAYNE DAVIS
ALBUQUERQUE, NM 87102

DIKEWOOD CORP
2716 OCEAN & PARK BLVD, SUITE 3000
ATTN K. LEE
SANTA MONICA, CA 90405

E-SYSTEMS, INC
GREENVILLE DIVISION
PO BOX 1056
ATTN JOLETA MOORE
GREENVILLE, TX 75401

EFFECTS TECHNOLOGY, INC.
5383 HOLLISTER AVENUE
ATTN S. CLOW
SANTA BARBARA, CA 93111

EG&G WASHINGTON ANALYTICAL SERVICES
CENTER, INC
PO BOX 10218
ATTN C. GILES
ALBUQUERQUE, NM 87114

FAIRCHILD CAMERA & INSTRUMENT CORP
464 ELLIS STREET
ATTN DAVID K. MYERS
MOUNTAIN VIEW, CA 94040

FORD AEROSPACE & COMMUNICATIONS CORP
3939 FABIAN WAY
ATTN TECH LIB
PALO ALTO, CA 94303

FORD AEROSPACE & COMMUNICATIONS
OPERATIONNS
FORD & JAMBOREE ROADS
ATTN KEN C. ATTINGER
NEWPORT BEACH, CA 92663

GENERAL DYNAMICS CORP
ELECTRONICS DIVISION
PO BOX 81127
ATTN RSCH LIB
SAN DIEGO, CA 92138

GENERAL DYNAMICS CORP
INTER-DIVISION RESEARCH LIBRARY
KEARNY MESA
PO BOX 80986
ATTN RSCH LIB
SAN DIEGO, CA 92138

GENERAL ELECTRIC CO.-TEMPO
CENTER FOR ADVANCED STUDIES
816 STATE STREET (PO DRAWER QQ)
ATTN DASAC
ATTN ROYDEN R. RUTHERFORD
ATTN WILLIAM MCNAMERA
SANTA BARBARA, CA 93102

DISTRIBUTION (Cont'd)

GENERAL ELECTRIC COMPANY
AEROSPACE ELECTRONICS SYSTEMS
FRENCH ROAD
ATTN CHARLES M. HEWISON
UTICA, NY 13503

GENERAL ELECTRIC COMPANY
PO BOX 5000
ATTN TECH LIB
BINGHAMTON, NY 13902

GENERAL ELECTRIC CO.-TEMPO
ALEXANDRIA OFFICE
HUNTINGTON BUILDING, SUITE 300
2560 HUNTINGTON AVENUE
ATTN DASIAAC
ALEXANDRIA, VA 22303

GENERAL RESEARCH CORP
SANTA BARBARA DIVISION
PO BOX 6770
ATTN TECH INFO OFFICE
SANTA BARBARA, CA 93111

GEORGIA INSTITUTE OF TECHNOLOGY
OFFICE OF CONTRACT ADMINISTRATION
ATTN RSCH SECURITY COORDINATOR
FOR HUGH DENNY
ATLANTA, GA 30332

GRUMMAN AEROSPACE CORP
SOUTH OYSTER BAY ROAD
ATTN L-01 35
BETHPAGE, NY 11714

GTE SYLVANIA, INC
ELECTRONICS SYSTEMS GRP-EASTERN DIV
77 A STREET
ATTN CHARLES A. THORNHILL, LIBRARIAN
ATTN LEONARD L. BLAISDELL
NEEDHAM HEIGHTS, MA 02194

GTE SYLVANIA, INC
189 B STREET
ATTN CHARLES H. RAMSBOTTOM
ATTN DAVID D. FLOOD
ATTN EMIL P. MOTCHO
ATTN H & V GROUP, A. NUREFORA
ATTN J. WALDRON
NEEDHAM HEIGHTS, MA 02194

HARRIS CORP
HARRIS SEMICONDUCTOR DIVISION
PO BOX 883
ATTN V PRES & MCG PRGMS DIV
MELBOURNE, FL 32901

HAZELTINE CORP
PULASKI ROAD
ATTN TECH INFO CTR, M. WAITE
GREENLAWN, NY 11740

HONEYWELL INC
AVIONICS DIVISION
2600 RIDGEWAY PARKWAY
ATTN S & RC LIB
ATTN RONALD R. JOHNSON
MINNEAPOLIS, MN 55413

HONEYWELL INC
AVIONICS DIVISION
13350 U.S. HIGHWAY 19 NORTH
ATTN MS 725-5, STACEY H. GRAFF
ATTN W. E. STEWART
ST PETERSBURG, FL 33733

HUGHES AIRCRAFT COMPANY CENTINELA & TEALE
ATTN JOHN B. SINGLETARY
ATTN CTDC 6/E110
ATTN KENNETH R. WALKER
CULLVER CITY, CA 90230

IIT RESEARCH INSTITUTE
10 WEST 35TH STREET
ATTN IRVING N. MINDEL
ATTN JACK E. BRIDGES
CHICAGO, IL 60616

INTL TEL & TELEGRAPH CORP
500 WASHINGTON AVENUE
ATTN TECHNICAL LIBRARY
ATTN ALEXANDER T. RICHARDSON
NUTLEY, NJ 07110

IRT CORP
PO BOX 81087
ATTN C. B. WILLIAMS
ATTN DENNIS SWIFT
SAN DIEGO, CA 92138

JAYCOR
11011 TORREYANA ROAD
PO BOX 85154
ATTN ERIC P. WENAAS
ATTN RALPH H. STAHL
SAN DIEGO, CA 92138

JAYCOR
205 S. WHITTING STREET, SUITE 500
ATTN LIB
ALEXANDRIA, VA 22304

KAMAN SCIENCES CORP
1500 GARDEN OF THE GODS ROAD
ATTN ALBERT P. BRIDGES
ATTN W. FOSTER RICH
ATTN WALTER E. WARE
ATTN FRANK H. SHELTON
ATTN JERRY I. LUBELL
ATTN PHIL TRACY
COLORADO SPRINGS, CO 80907

LITTON SYSTEMS, INC
DATA SYSTEMS DIVISION
8000 WOODLEY AVENUE
ATTN EMC GP

DISTRIBUTION (Cont'd)

LITTON SYSTEMS, INC (Cont'd)
ATTN M848-61
VAN NUYS, CA 91409

LITTON SYSTEMS, INC
AMERCOM DIVISION
5115 CALVERT ROAD
ATTN J. SKAGGS
COLLEGE PARK, MD 20740

LOCKHEED MISSILES & SPACE CO, INC
PO BOX 504
ATTN I. ROSSI
ATTN SAMUEL I. TAIMUTY
ATTN H. E. THAYN
ATTN GEORGE F. HEATH
ATTN BENJAMIN T. KIMURA
SUNNYVALE, CA 94086

LOCKHEED MISSILE & SPACE CO, INC
3251 HANOVER STREET
ATTN TECH INFO CTR D/COLL
PALO ALTO, CA 94304

MARTIN MARIETTA CORP
ORLANDO DIVISION
PO BOX 5837
ATTN MONA C. GRIFFITH
ORLANDO, FL 32805

MCDONNELL DOUGLAS CORP
PO BOX 516
ATTN TOM ENDER
ST LOUIS, MO 63166

MCDONNELL DOUGLAS CORP
5301 BOLSA AVENUE
ATTN STANLEY SCHNEIDER
ATTN TECH LIBRARY SERVICES
HUNTINGTON BEACH, CA 92647

MISSION RESEARCH CORP
PO DRAWER 719
ATTN EMP GROUP
ATTN WILLIAM C. HART
ATTN C. LONGMIRE
SANTA BARBARA, CA 93102

MISSION RESEARCH CORP
PO BOX 7816
ATTN WERNER STARK
ATTN ROY STRAYER, JR
COLORADO SPRINGS, CO 80933

MITRE CORP
PO BOX 208
ATTN M. F. FITZGERALD
BEDFORD, MA 01730

NORDEN SYSTEMS, INC
HELEN STREET
ATTN TECHNICAL LIBRARY
NORWALK, CT 06856

NORTHROP RESEARCH TECHNOLOGY CENTER
ONE RESEARCH PARK
ATTN LIBRARY
PALOS VERDES PENN, CA 90274

NORTHROP CORP
ELECTRONIC DIVISION
2301 WEST 120TH STREET
ATTN LEW SMITH
ATTN RAD EFFECTS GRP
HAWTHORNE, CA 90250

PHYSICS INTERNATIONAL COMPANY
2700 MERCED STREET
ATTN DOC CON
SAN LEANDRO, CA 94577

R&D ASSOCIATES
PO BOX 9695
ATTN S. CLAY ROGERS
ATTN CHARLES MO
ATTN RICHARD R. SCHAEFER
ATTN DOC CON
ATTN M. GROVER
ATTN C. MACDONALD
MARINA DEL REY, CA 90291

RAND CORP
1700 MAIN STREET
ATTN LIB-D
ATTN W. SOLLFREY
SANTA MONICA, CA 90406

RAYTHEON COMPANY
HARTWELL RD
ATTN GAJANAN H. JOSHI
BEDFORD, MA 01730

RAYTHEON COMPANY
528 BOSTON POST ROAD
ATTN HAROLD L. FLESCHER
SUDBURY, MA 01776

RCA CORP
CAMDEN COMPLEX
FRONT & COOPER STREETS
ATTN OLIVE WHITEHEAD
ATTN R. W. ROSTROM
CAMDEN, NJ 08012

ROCKWELL INTERNATIONAL CORP
PO BOX 3105
ATTN J. L. MONROE
ATTN V. J. MICHEL
ATTN D/243-068, 031-CA31
ANAHEIM, CA 92803

SANDERS ASSOCIATES, INC
95 CANAL STREET
ATTN 1-6270, R. G. DESPATHY, SR P E
NASHUA, NH 03060

DISTRIBUTION (Cont'd)

SCIENCE APPLICATIONS, INC
PO BOX 277
ATTN FREDERICK M. TESCHE
BERKELEY, CA 94701

SINGER COMPANY
1150 MC BRIDE AVENUE
ATTN TECH INFO CTR
LITTLE FALLS, NJ 07424

SPERRY RAND CORP
SPERRY MICROWAVE ELECTRONICS
PO BOX 4648
ATTN MARGARET CORT
CLEARWATER, FL 33518

SPERRY RAND CORP
SPERRY DIVISION
MARCUS AVENUE
ATTN TECH LIB
GREAT NECK, NY 11020

SRI INTERNATIONAL
333 RAVENSWOOD AVENUE
ATTN ARTHUR LEE WHITSON
MENLO PARK, CA 94025

SYSTEMS, SCIENCE & SOFTWARE, INC
PO BOX 1620
ATTN ANDREW R. WILSON
LA JOLLA, CA 92038

TEXAS INSTRUMENTS, INC
PO BOX 6015
ATTN TECH LIB
ATTN DONALD J. MANUS
DALLAS, TX 75265

TRW DEFENSE & SPACE SYS GROUP
ONE SPACE PARK
ATTN O. E. ADAMS
ATTN J. PENAR
ATTN W. GARGARO
REDONDO BEACH, CA 90278

UNITED TECHNOLOGIES CORP
HAMILTON STANDARD DIVISION
BRADLEY INTERNATIONAL AIRPORT
ATTN CHIEF ELEC DESIGN
WINDSOR LOCKS, CT 06069

WESTINGHOUSE ELECTRIC CORP
ADVANCED ENERGY SYSTEMS DIV
PO BOX 10864
ATTN TECH LIB
PITTSBURGH, PA 15236

US ARMY ELECTRONICS RESEARCH
& DEVELOPMENT COMMAND
ATTN TECHNICAL DIRECTOR, DRDEL-CT
ATTN R. HARMAN, DRDEL-MA

HARRY DIAMOND LABORATORIES
ATTN CO/TD/TSO/DIVISION DIRECTORS
ATTN RECORD COPY, 81200
ATTN HDL LIBRARY, 81100 (3 COPIES)
ATTN HDL LIBRARY, 81100 (WOODBIDGE)
ATTN TECHNICAL REPORTS BRANCH, 81300
ATTN LEGAL OFFICE, 97000
ATTN CHAIRMAN, EDITORIAL COMMITTEE
ATTN CHIEF, 13000
ATTN CHIEF, 21000
ATTN CHIEF, 21100
ATTN CHIEF, 21200
ATTN CHIEF, 21300 (10 COPIES)
ATTN CHIEF, 21400
ATTN CHIEF, 21500
ATTN CHIEF, 22000
ATTN CHIEF, 22100
ATTN CHIEF, 22300
ATTN CHIEF, 22800
ATTN CHIEF, 22900
ATTN CHIEF, 20240
ATTN CHASE, R., 21100
ATTN VALLIN, J., 22100
ATTN LEPOER, K., 21100
ATTN REYZER, R., 21300
ATTN CUNEO, A., 21100
ATTN HILL, N., 21300

END