

AD-A127 612

USE OF INDUCED SPATIAL INCOHERENCE FOR UNIFORM
ILLUMINATION ON LASER FUSION TARGETS(U) NAVAL RESEARCH
LAB WASHINGTON DC R H LEHMBERG ET AL. 11 APR 83

1/1


UNCLASSIFIED

NRL-MR-5829

F/G 20/5

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A



SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NRL Memorandum Report 5029	2. GOVT ACCESSION NO. 90 4127612	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) USE OF INDUCED SPATIAL INCOHERENCE FOR UNIFORM ILLUMINATION OF LASER FUSION TARGETS		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) R. H. Lehmberg and S. P. Obenschain		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Research Laboratory Washington, DC 20375		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Department of Energy Washington, DC 20545		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS DOE AI08-79DP 40092(172) 47-0859-0-3
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE April 11, 1983
		13. NUMBER OF PAGES 13
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Uniform illumination Spatial incoherence Echelon Temporal averaging		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) We report a technique to achieve very uniform illumination of laser irradiated targets by inducing a controlled amount of transverse spatial incoherence in the output beam of a broadband laser. The spatial incoherence is created by imposing different optical delays upon different transverse sections of the beam, and choosing the delay increments to be larger than the laser coherence time $t_c = 1/\Delta\nu$. This technique may allow easy attainment of the pellet illumination uniformity required for laser fusion. —		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

USE OF INDUCED SPATIAL INCOHERENCE FOR UNIFORM ILLUMINATION OF LASER FUSION TARGETS

High gain laser fusion requires a very uniform ablation pressure at the pellet surface.^{1,2} For the case of directly illuminated pellets, this in turn requires a high degree of uniformity in the incident intensity. Even at $\lambda = 1 \mu\text{m}$, where significant lateral smoothing can take place in the ablating plasma,^{3,4} illumination uniformities to within $\pm 10\%$ are likely to be required. At shorter wavelengths, where the smaller absorption-ablation distance of the plasma provides only minimal lateral smoothing,⁴ illumination uniformities to within $\pm 1\%$ may be required.

Efforts to achieve uniform illumination have been frustrated by imperfections in the high power laser systems. The cumulative effect of small phase aberrations (both linear and nonlinear) introduced by each optical element of a multistage laser produces large random intensity nonuniformities at the output, and these can only be partially controlled at great expense by using ultra high quality optics and extensive beam relaying.⁵ In order to obtain the desired intensity and focal diameter with a lens of reasonable focal length, one normally places the pellet in the quasi near field of the lens, rather than at best focus. With this configuration, however, the nonuniformities at the laser output tend to be mapped onto the pellet. Random nonuniformities may be statistically smoothed by overlapping many independent beams at the pellet, but the large number of beam lines required to do this in a conventional way may be prohibitive.

In this letter, we report a simple and novel technique that allows a high degree of illumination uniformity with modest quality laser beams. This technique induces a controlled amount of transverse spatial incoherence in the output beam of a broadband laser, whose coherence time $t_c = 1/\Delta\nu$ is short in comparison to the pulsewidth t_p . The spatial incoherence is achieved by imposing different optical delays upon different transverse sections of the beam, and choosing the delay increments to be larger than t_c . A wide aperture beam is thus broken up into a large number N of independent beamlets. At the focus of a lens, these overlap to produce a complicated interference pattern modulated by a smooth envelope that characterizes the diffraction of an individual beamlet. On time scales long in comparison to t_c , the interference pattern averages out, leaving only the smooth diffraction profile. The pellet will effectively ignore the rapidly shifting interference pattern if its hydrodynamic response time t_h satisfies $t_h \gg t_c$. The diffraction profile is relatively insensitive to amplitude and phase nonuniformities in the incident beam; in fact, the beam need only be approximately uniform over the small width of each beamlet. We estimate that laser bandwidths as small as 0.2% should be adequate to implement this scheme for laser fusion.

The concept described here bears some similarity to a technique recently proposed by Mima and Kato,⁶ in which the beam is broken up by a random phase mask. In that proposal, however, the random phase relationship among the beamlets would remain fixed in time; i.e., the incident beam becomes aberrated, but not really incoherent. The focal interference pattern therefore persists throughout the pulse, and it invariably contains longer scalelength components that would be deleterious to the pellet implosion uniformity. Similar considerations apply to optical beam integrating devices that are designed to produce a "top hat" spatial profile.⁷

The induced incoherence concept is illustrated for one transverse dimension in Fig. 1. The incident laser beam amplitude is

$$E_L(x, z, t) = A(x)F(t - z/c) \exp[-i\omega(t - z/c)], \quad (1)$$

where the complex amplitudes $A(x)$ and $F(t)$ describe the transverse nonuniformities and slow time dependence, respectively. For a Q -switched pulse in a broad bandpass laser medium, $F(t)$ can be approximated by a quasi-stationary stochastic variable satisfying Gaussian statistics. The correlation function $\langle F(t)F^*(t + \tau) \rangle$ will exhibit a smooth localized τ dependence of width $t_c = 2\pi/\Delta\omega$, so that $\langle F(t)F^*(t + \tau) \rangle \approx 0$ for $|\tau| > t_c$, while the mean square amplitude $\langle |F(t)|^2 \rangle$ varies negligibly within interval t_c if $t_c \ll t_p$. (Here, the brackets denote an ensemble average.) This beam propagates through the transparent echelon structure, which introduces time delays t_n that increase with each step. If the beam is nearly uniform over scalelength D_1 (i.e., if $|\partial A/\partial x|D_1 \ll |A|$), then the output field is approximately

$$\sum_{n=1}^N \epsilon(x - nD_1) A_n F(t - t_n) \exp[i\omega(t_n - t)], \quad (2)$$

where $A_n \equiv A(nD_1)$, and $\epsilon(x)$ is a "top hat" function equal to unity for $|x| \leq D_1/2$ and zero elsewhere. Without loss of generality, one can normalize the amplitudes so that $\sum_n |A_n|^2 = 1$. To produce nearly complete transverse spatial incoherence within times of order t_c , the delay increments $t_{n+1} - t_n$ must be larger than t_c , and ωt_n must vary randomly (over at least 2π) from step to step. The latter requirement ensures that phase relationships among nearby beamlets will not be duplicated among lower beamlets as the emerging wavefront shears its way down the echelon.

In the focal plane of the lens, the instantaneous intensity profile $I(x, t) = |E_f(x, t)|^2$ of the overlapping beamlets is

$$I(x, t) = C \operatorname{sinc} \left(\frac{2\pi x}{d} \right) \sum_{m=1-N}^{N-1} J_m(t) \exp \left[i \frac{2\pi x}{\Lambda_m} \right], \quad (3)$$

where $\operatorname{sinc}(2\pi x/d) = \sin^2(2\pi x/d)/(2\pi x/d)^2$ is the diffraction envelope of width $d = 2\lambda f/D_1$ (zero-to-zero), $C \equiv D_1^2/f\lambda$, $\Lambda_m = \lambda f/m D_1$ is the m th transverse mode wavelength, and

$$J_m(t) = \sum_n A_n A_{n+m}^* F(t - t_n) F^*(t - t_{n+m}) \exp[i\omega(t_n - t_{n+m})] \quad (4)$$

is the m th transverse mode amplitude, assuming for simplicity that the maximum delay time difference satisfies $t_N - t_1 \ll t_p$. The spatial profile of $I(x, t)$ is generally a complicated random pattern, as shown on the right hand side of Fig. 1. If $t_c > t_N - t_1$, then the beamlets remain coherent (although randomly phased), and this pattern will persist throughout the pulse. This corresponds to the case discussed in Ref. (6). If $t_c < t_{n+1} - t_n$, however, the beamlets become effectively incoherent with respect to one another, and the pattern averages out in times $T \gg t_c$. The time-averaged intensity $\bar{I}(x, t, T)$ over interval $(t, t + T)$ thus approaches the ensemble average value

$$\langle I(x, t) \rangle = C \langle |F(t)|^2 \rangle \operatorname{sinc}(2\pi x/d) \quad (5)$$

when $t_c \ll T \ll t_p$. This spatial profile, which is indicated by the smooth curve in Fig. 1, contains over 90% of the energy in its central lobe $|x| \leq d/2$. As a numerical example, let $\lambda = 1 \mu\text{m}$, $f = 5 \text{ m}$, and $D_1 = 5 \text{ mm}$; then $d = 2 \text{ mm}$.

To estimate the residual random nonuniformities of $\bar{I}(x, t, T)$, we examine the ensemble fluctuations in the time-averaged mode amplitudes $\bar{J}_m(t, T)$ for $m \neq 0$. Since $\langle \bar{J}_m(t, T) \rangle = \delta_{m,0} \langle |F(t)|^2 \rangle$, the relative magnitude of the RMS energy fluctuations in all off-axis modes up to $|m| = M \leq N - 1$ is given by the ratio

$$R_M = \left[\sum_{|m|=1}^M \langle |\bar{J}_m(t, T)|^2 \rangle \right]^{1/2} / \langle \bar{J}_0(t, T) \rangle \quad (6a)$$

LASER BEAM OF
BANDWIDTH

$$\Delta\nu = 1/t_c$$




Fig. 1 — Use of spatial incoherence induced by a transparent echelon to smooth the focal spot irradiance of a broadband laser.



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

$$= \bar{\gamma} \left(\frac{t_c}{T} \right)^{1/2} \left[\sum_{|m|=1}^M \sum_n |A_n|^2 |A_{n+m}|^2 \right]^{1/2}, \quad (6b)$$

where $T \gg t_c$, and

$$\bar{\gamma}^2 = \int_{-\infty}^{\infty} \left| \frac{\langle F(t) F^*(t + \tau) \rangle}{\langle |F(t)|^2 \rangle} \right|^2 \frac{d\tau}{t_c} \leq 1. \quad (7)$$

In deriving expression (6b), we have assumed Gaussian statistics for $F(t)$ and random phases for ωt_n . Expression (6b) reduces to $\bar{\gamma} (t_c/T)^{1/2}$ when $M = N - 1$; however, for laser fusion, the most dangerous off-axis modes are those with long transverse wavelengths $|\Lambda_m| > \Lambda_M = d/2M$ where $M < N - 1$, and Λ_M is comparable to the absorption-ablation distance in the ablating plasma.¹⁻³ If $M \ll N - 1$, then the n summation in (6b) can be approximated by $N(1/N^2)$, and

$$R_M \approx \bar{\gamma} (t_c/T)^{1/2} (d/N\Lambda_M)^{1/2}. \quad (8)$$

The concepts introduced here can be extended to two transverse dimensions in any one of several ways, such as the use of two perpendicular echelons, or a structure in which the steps consist of squares, closely packed hexagonals, or concentric circles. If two perpendicular echelons are used, the time delay increments on the second one should be as large as the total $t_N - t_1$ on the first. The average intensity at focus then becomes proportional to $\text{sinc}(2\pi x/d) \text{sinc}(2\pi y/d)$ (which contains 82% of the energy in the center lobes), while expression (8) becomes

$$R_M \approx \bar{\gamma} (t_c/T)^{1/2} \pi^{1/2} d/2N\Lambda_M. \quad (9)$$

From expressions (8) and (9), we see that two factors contribute to the beam smoothing. The $d/N\Lambda_M$ term arises because part of the energy has been channeled into (presumably) less dangerous modes at shorter transverse wavelengths. This is the smoothing mechanism proposed in Ref. (6). For a pellet of diameter d , a maximum allowable Λ_M of $d/10$, and $N = 40$ steps in each echelon, one obtains $d/N\Lambda_M = 1/4$. The $(t_c/T)^{1/2}$ term (which suppresses *all* off-axis modes) arises from the temporal averaging, where T/t_c represents the effective number of independent random intensity distributions contributing to the irradiance within interval T . For $t_c \sim 1$ psec and an averaging time $T = 400$ psec, this factor alone will effect a 20-fold reduction of R_M .

The use of induced incoherence for beam smoothing was tested with a transparent echelon-lens combination similar to the one shown in Fig. 1. A laser beam of variable coherence time is produced by an actively Q -switched Nd-glass oscillator. The oscillator bandwidth, which is monitored by a spectrograph, is adjusted by intracavity etalons, and by varying the gain to loss ratio in the cavity. Pulses widths are typically 30 nsec. The beam from the oscillator is expanded to a 20 mm diameter and transmitted through the echelon, which consists of overlapped 1 mm thick glass slides cemented together to minimize losses. This echelon breaks the beam into ~ 1 mm wide beamlets with a 1.7 psec delay increment between adjacent beamlets. The beamlets then pass through a slit perpendicular to the echelon steps to achieve a one-dimensional geometry, and are focused onto a Vidicon camera by a 1 meter focal length lens. The vidicon measures the focal profile averaged over the laser pulsewidth.

Figure 2 shows the effect of the echelon on the focal distribution with a narrow band HeNe laser in place of the glass oscillator. The echelon broadens the focus due to diffraction, and produces a complicated pattern due to interference among the coherent beamlets.

Figure 3 shows the focal distributions with the echelon and the variable bandwidth glass oscillator. When the laser is adjusted for a narrow bandwidth, one obtains a complicated interference pattern, as with the HeNe laser. At the intermediate bandwidth shown, the coherence time $t_c = 1/\Delta\nu \approx 4.6$ psec is longer than the delay between nearby beamlets, but shorter than that of the widely spaced beamlets. Here the shorter scalelength interference pattern produced by the widely spaced beamlets (that intersect




Fig. 2 — Far-field focal profiles obtained using a HeNe laser with and without the echelon. The vidicon camera employed for the measurements has a $25\text{ }\mu\text{m}$ spatial resolution.

LASER SPECTRUM FOCAL PROFILE




Fig. 3 — Far-field focal profiles obtained with the echelon as the bandwidth of the glass oscillator is varied.

at larger angles) is smoothed, while the longer scalelength pattern produced by adjacent beamlets persists. Finally, when t_c becomes short enough (~ 1.6 psec for the case shown) the interference among adjacent beamlets averages out, and one obtains the smooth focal distribution shown.

We have also tested the ability of the induced incoherence technique to smooth out nonuniformity in the incident laser beam. Figure 4(a) shows the illumination obtained in the quasi-near field (2.5 cm closer to the lens than best focus) when a large amplitude nonuniformity was impressed on the incident laser beam without the echelon. In Fig. 4(b), where the echelon has been inserted in the beam, the nonuniformity is eliminated. The temporal incoherence of the laser was the same in both cases. The echelon was found to provide a significant smoothing effect over a distance $\pm \Delta z$ (from best focus) given by $\Delta z \approx d/\theta$, where θ is the convergence angle of the outermost beamlets.

The induced incoherence smoothing technique is applicable to high power glass laser systems. In measurements of gain vs. wavelength, we found the gain coefficient for phosphate glass (Q-98), to be within 97% of the peak value over the 0.2% bandwidth used in these experiments. Thus, with a modest increase in the gain, a high power system could accommodate the bandwidths used in the above experiments. Other lasers, such as KrF, with similar bandwidth capabilities should also be applicable to the technique.


The smallest laser bandwidth that can be used will be determined by the required number of beamlets N^2 and the pulsewidth t_p . The delay increment of the echelon ($t_{n+1} - t_n > t_c$) limits the rise-time at focus to $\geq N^2 t_c$; hence, for $N^2 \approx 1000$ and $t_c \approx 1$ psec, the total delay across the beam would be ≥ 1 nsec. Since fusion reactor pellets will involve pulsewidths > 10 nsec, this should not be a serious restriction. Aside from this consideration, a lower bound on $\Delta \nu$ may be determined by the onset of plasma instabilities produced in the interference intensity maxima. At high irradiances, this may require that t_c be less than the instability growth time.

In this paper, we have demonstrated both theoretically and experimentally the use of programmed spatial incoherence to achieve a smooth illumination profile on flat targets. This technique has a marked advantage over other techniques involving a coherent laser, such as the random phase plate or the Spawr integrator, in that (1) virtually unlimited degrees of uniformity can be achieved, and (2) the focal spot irradiance is uniform even on short spatial scalelengths. The second feature may be important for avoiding instabilities in laser plasma interactions, such as small scale self-focusing and stimulated Brillouin scattering. For the fusion application, one needs uniform illumination of a spherical surface. Earlier studies have shown that if the incident laser profiles are smooth, one can achieve uniform illumination of a spherical surface by overlapping a relatively small (≥ 20) number of beams.⁸⁻¹¹ The problem prior to the availability of this technique has been in achieving a smooth and reproducible focal profile in a single beam.


The smoothing technique appears highly promising for the fusion application. It should also be applicable to other processes, such as shock wave generation, which require uniform illumination by a concentrated laser beam.

We gratefully acknowledge the valuable discussions and suggestions by Dr. S. E. Bodner, and the technical assistance of M. Fink, J. Kosakowski, H. Hellfeld and N. Nocerino. This work was supported jointly by the Office of Naval Research and the U.S. Department of Energy.

(a)
MODULATED BEAM
NO ECHELON



(b)
MODULATED BEAM
WITH ECHELON



1 mm

Fig. 4 — Quasi-near field focal profiles obtained without (a) and with (b) the echelon. In both cases the laser beam at the lens had the same structured profile.

REFERENCE

1. John H. Nuckolls et. al. in Proceedings of the European Conference on Laser Interaction with Matter, Oxford, England (1977) (unpublished).
2. S.E. Bodner, *J. Fusion Energy* **1**, 221 (1981).
3. S.P. Obenschain, J. Grun, B.H. Ripin and E.A. McLean, *Phys. Rev. Lett.* **46**, 1402 (1981), and **48**, 709 (1982).
4. J.H. Gardner and S.E. Bodner, *Phys. Rev. Lett.* **47**, 1137 (1981).
5. Special Issue on Lasers for Fusion, M.D. Richardson, ed.; *IEEE J. Quantum Electron.* **QE-17** (Sept. 1981).
6. K. Mima and Y. Kato, ILE Progress Report on Inertial Fusion Program for Jan-March 1982 (Institute of Laser Engineering, Osaka University, May 1982); Y. Kato and K. Mima, *Appl. Physics* (Springer) **B29**, 186 (1982).
7. Spawr Optical Research, Inc. (Corona, CA); U.S. Patent No. 4195913.
8. James E. Howard, *Appl. Optics* **16**, 2764 (1977).
9. J.B. Trenholme and E.J. Goodwin, "Nova Target Illumination Studies," Laser Program Annual Report—1979, Vol. 1, pp. 2-139, UCRL-50021-79 (1980).
10. J.M. McMahon and R.H. Lehmberg, 1981 Topical Conference on Symmetry Aspects of Inertial Confinement Implosions, S.E. Bodner, ed. (to be published).
11. S. Skupsky and K. Lee, Sixth International Workshop on Laser Interaction and Related Phenomena (Plenum Publishing Co., 1983).

DOE DISTRIBUTION LIST FOR REPORTS

University of California
Lawrence Livermore National Lab
Post Office Box 808
Livermore CA 94550

H.G. Ahlstrom, L-481
J.L. Emmett L-448
J.F. Holzrichter, L-481
M.J. Monsler, L-479
J.H. Nuckolls, L-477
L.W. Coleman, L-473
J.T. Hunt, L-481
A.B. Langdon L-477

U.S. Department of Energy
Office of Inertial Fusion
Washington DC 20545

L.E. Killian
G. Gibbs
T.F. Godlove
S.L. Kahalas
J.E. Lewis
R.L. Schriever
T.H. Walsh
S.J. Barish

U.S. Dept. of Energy (194 cys)
Technical Information Center
P.O. Box 62
Oak Ridge, TN 37830

Defense Tech. Information Ctr. (2 cys)
Cameron Station
5010 Duke Street
Alexandria, VA 22314

R. McCrory
University of Rochester
250 East River Road
Rochester, NY 14623

Robert T. Duff
U.S. Department of Energy
Office of Classification
Washington, DC 20545

Rex B. Purcell (2 cys)
U.S. Department of Energy
Nevada Operations Office
Post Office Box 14100
Las Vegas, NV 89114

Z.N. Zafiris/R. Bredderman
U.S. Department of Energy
San Francisco Operations Office
1333 Broadway
Oakland, CA 94512

Los Alamos National Laboratory
Post Office Box 1663
Los Alamos, NM 87545
S.D. Rockwood, ICF Prog. Mgr.
DAD/IF, M/S527 (6 cys)

G. Yonas (4 cys)
Sandia National Laboratories
Post Office Box 5880
Albuquerque, NM 87185

S. Bodner
Naval Research Laboratory
Code 4730
Washington, DC 20375

T. Coffey
Naval Research Laboratory
Code 1001
Washington DC 20375

Alexander Glass
KMS Fusion, Inc.
3941 Research Park Drive
P.O. Box 1567
Ann Arbor, MI 48106

NRL Code 4700 (26 cys)

NRL Code 4730 (100 cys)

NRL Code 2628 (20 cys)

DOE OPTIONAL LIST FOR REPORTS

Lawrence Livermore Natl. Laboratory
P.O. Box 808
Livermore, CA 94551

Dr. W. Kruer, L-545
Dr. B. Laskinski, L-32
Dr. J. Lindl L-32
Dr. C. Max L-545
Dr. D. Phillion
Dr. W. Mead
Dr. R. Kidder
Dr. Roger Haas
Dr. E.M. Campbell

KMS Fusion
3941 Research Park Drive
Post Office Box 1567
Ann Arbor, MI 48106

Dr. F. Mayer
Dr. R. Johnson
Dr. R. Berger
Dr. T. Spieziali
Dr. D. Slater

TRW Corporation
1 Space Park
Redondo Beach, CA 90278

Dr. D. Arnush
Dr. J. Thompson

Physics International
2700 Merced Street
San Leandro, CA 94577
G. Dahlbacka

Institut fur Plasmaphysik
8046 Garching
Bei Munchen
West Germany
Dr. R. Sigel
Dr. K. Eidmann

National Research Council
Division of Physics
100 Sussex Drive
Ottawa K1A-0R6, Canada
Dr. J. Alcock
Dr. N. Burnett

University of Quebec
INRS Energie
Case Postale 1020
Varenes, Quebec
Dr. T. Johnston
Dr. R. Decoste
Dr. H. Pepin

Laboratoire de Physique des
Milieux Ionises
Ecole Polytechnique
17, Rue Descartes
75230 Paris Cedex 05
France
Dr. E. Fabre

Institute for Laser Engineering
Osaka University
Suita Osaka, 565, Japan
Dr. C. Yamanaka
Dr. K. Mima

Los Alamos Scientific Laboratory
P.O. Box 1663
Los Alamos, NM 87545
Dr. Alan Saxman
Dr. D. Forslund
Dr. S. Gitomer
Dr. J. Kindel
Dr. D. Giovanelli
Dr. S. Singer
Dr. P. Goldstone

Sandia Laboratory
P.O. Box 5800
Albuquerque, NM 87115
Dr. K. Matzen

Maxwell Laboratory Inc.
9935 Balboa Avenue
San Diego, CA 92123
Dr. J. Pearlman

Kirkland Air Force Base
Air Force Weapons Laboratory
Albuquerque, NM 87117
Dr. A. Guenther

University of Maryland
Dept. of Physics & Astronomy
College Park, MD 20740
Dr. H. Griem

University of Rochester
Laboratory for Laser Energetics
Rochester, NY 14627
Dr. B. Yaakobi
Dr. J. Soures
Dr. M. Richardson
Dr. S. Craxton
Dr. W. Seka
Dr. S. Skupsky

University of California
Department of Physics
Los Angeles, CA 90024
Dr. N. Luhmann

North Carolina State University
Department of Physics
Raleigh, NC 27607
Dr. Carter Armstrong

AWRE
Aldermaston, England
Dr. J. Weale
Dr. P. Flynn

Rutherford Laboratory
Chilton, Didcot
Oxon, OX11 0QX
England
Dr. M. Key
Dr. T. Raven
Dr. P. Rumsby
Dr. R. Evans

INTERNAL DISTRIBUTION

Code 4740
V. Granatstein
Code 4040
D. Book
J. Boris
M. Emery
J. Gardner
Code 4770
G. Cooperstein
Code 4790
D. Colombant
W. Manheimer
Code 4720
J. Davis
D. Duston
Code 6680
D. Nagel
R. Whitlock
P. Burkhalter

END

FILMED

6-83

DTIC