

AD-A127 810

COMPOSITE COAXIAL TELECOMMUNICATIONS CABLE(U) FOREIGN
TECHNOLOGY DIV WRIGHT-PATTERSON AFB OH T LAPINSKI
02 MAR 83 FTD-ID(RS)T-1795-82

1/1


UNCLASSIFIED

F/G 9/1

NL



END
DATE
FILMED
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

2

FTD-ID(RS)T-1795-82

FOREIGN TECHNOLOGY DIVISION



COMPOSITE COAXIAL TELECOMMUNICATIONS CABLE

by

Tadeusz Lapinski



DTIC
ELECTE
MAY 10 1983
S E D

Approved for public release;
distribution unlimited.

A 127810

DTIC FILE COPY



88 05 09-046

EDITED TRANSLATION

FTD-ID(RS)T-1795-82

2 March 1983

MICROFICHE NR: FTD-83-C-000341

COMPOSITE COAXIAL TELECOMMUNICATIONS CABLE

By: Tadeusz Lapinski

English pages: 2

Source: Wiadomosci Elektrotechniczne, Nr. 19(522),
1 October 1979, pp. 528


Country of origin: Poland

Translated by: LEO KANNER ASSOCIATES
F33657-81-D-0264

Requester: RCA

Approved for public release; distribution unlimited.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	



<p>THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.</p>	<p>PREPARED BY: TRANSLATION DIVISION FOREIGN TECHNOLOGY DIVISION WP-AFB, OHIO.</p>
---	---

GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc. merged into this translation were extracted from the best quality copy available.

COMPOSITE COAXIAL TELECOMMUNICATIONS CABLE

Author: Tadeusz Łapiński

At the end of 1978 the Cable Factory im. M. Buczek in Ożarów in Masuria began the production of long-distance composite telecommunications cable with coaxial pairs and quads having expanded polyethylene insulation, developed by the ENERGOKABEL Research and Development Center.

The small-dimension type 1.2/4.4 coaxial pairs with insulation in the form of cyclically clamped polyethylene tubing are specified for the transmission of analog signals at frequencies up to 12.5 MHz (2700-channel telephone transmission) and up to 108 kHz, as well as for the transmission of digital signals up to 2 Mbit/sec.

This long-distance composite cable is used as a replacement for coaxial cable and symmetrical cable. Lines constructed using this cable are smaller than lines constructed with the two kinds of cable mentioned here.

Four kinds of composite cable profiles can be realized using this cable: with two, four, six, and eight pairs. One layer of quads numbering respectively for a 0.9 mm conductor 12, 14, 18, and 20, and for a 1.2 mm conductor, 10, 12, 14, and 16, is set up as the core for cables formed from coaxial pairs and three auxiliary bundles.

The structure of small-dimension coaxial pairs and their characteristics are in conformance with WT-78/K-094 Technical Specifications, and the structure

of the star quads according to WT-77/K-093.

A rippled aluminum shield, protected from corrosion by means of a bitumen covering and an extruded polyethylene jacket, is placed around the center of the cables.

The nominal value of the actual capacitance of side circuit quads is 38.5 nF/km. The results of measurements have shown that actual capacitance is included within the range 36.69 to 37.96 nF/km.

Average near-end crosstalk attenuation between side circuits within the quads of composite cable 500 m long at a frequency of 100 kHz is 74.31 dB. Between side circuits with adjacent quads 86.42 dB, between side circuits separated from each other by a single separating quad 97.86 dB, and separated from each other by two quads 106.79 dB.

The average far-end crosstalk attenuation between side circuits within the quads of composite cable 500 m long at a frequency of 100 kHz is 80.6 dB, between side circuits with adjacent quads 96.74 dB, between side circuits separated from each other by a single separating quad 98.95 dB, and separated from each other by two quads 112.89 dB.

Relationship between constituent wave impedance (W_0) and wave attenuation (α) in a symmetrical line, and frequency (f).

f	W_0	α
kHz	Ω	dB/km
1	261.26	0.004
2	200.91	1.04
10	127.16	1.50
20	124.08	2.32
100	122.26	2.92
211	121.06	4.00
507	120.04	6.00
1001	120.04	11.00

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

<u>ORGANIZATION</u>	<u>MICROFICHE</u>
A205 DMAHTC	1
A210 DMAAC	1
B344 DIA/RTS-2C	9
C043 USAMIIA	1
C500 TRADOC	1
C509 BALLISTIC RES LAB	1
C510 R&T LABS/AVRADCOM	1
C513 ARRADCOM	1
C535 AVRADCOM/TSARCOM	1
C539 TRASANA	1
C591 FSTC	4
C619 MIA REDSTONE	1
D008 NISC	1
E053 HQ USAF/INET	1
E403 AFSC/INA	1
E404 AEDC/DOF	1
E408 AFWL	1
E410 AD/IND	1
E429 SD/IND	1
P005 DOE/ISA/DDI	1
P050 CIA/OCR/ADD/SD	2
AFIT/LDE	1
FTD	
CCN	1
NIA/PHS	1
NIIS	2
LLNL/Code L-389	1
NASA/NST-44	1
NSA/1213/TDL	2