

AD-A137 888


LARGE ENHANCEMENT OF THE SAGNAC EFFECT BASED ON
NONLINEARLY INDUCED NONRE. (U) PURDUE UNIV LAFAYETTE IN
SCHOOL OF ELECTRICAL ENGINEERING A KAPLAN 30 MAY 83
AFOSR-TR-83-1295 AFOSR-82-0126 F/G 20/6

1/1

UNCLASSIFIED

NL

END



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

2

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER AFOSR-TR- 83 - 1295	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) LARGE ENHANCEMENT OF THE SAGNAC EFFECT BASED ON NONLINEARLY INDUCED NONRECIPROCITY		5. TYPE OF REPORT & PERIOD COVERED FINAL REPORT 01 April 82 - 31 MARCH 83
7. AUTHOR(s) Professor Alexander Kaplan		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS School of Electrical Engineering Purdue University West Lafayette, IN 47907		8. CONTRACT OR GRANT NUMBER(s) AFOSR-82-0126
11. CONTROLLING OFFICE NAME AND ADDRESS Air Force Office of Scientific Research/NE Building 410 Bolling AFB, DC 20332		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 61102F 2305/B2
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE May 30, 1983
		13. NUMBER OF PAGES 16
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Sagnac Effect, Gyro, rotation Sensor		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) On Back		

DTIC
ELECTE
S **D**
JAN 20 1984
E

AD A137080

DTIC FILE COPY

➤ A substantial enhancement (by orders of magnitude) of the Sagnac effect in a passive ring resonator can be attained by using a nonreciprocal feedback. This feedback is based on the nonreciprocal element controlled by the signal proportional to the difference between intensities of counterpropagating waves, and is an opto-electronic analog of nonlinear nonreciprocity proposed by us early. Under some critical conditions, this system can exhibit directional bistability and directional switching of the counterpropagating waves.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



AFOSR-TR. 83-1295

Grant AFOSR-82-0126

Final Scientific Report

B J F
MAY 20 1983 *Dec*
/ cy only


"Large Enhancement of The Sagnac
Effect Based on Nonlinearly Induced Nonreciprocity"

Submitted to

U.S. Air Force Office of Scientific Research
Bolling Air Force Base, Washington, DC 20332
Attention: Dr. B. Feldman

by

School of Electrical Engineering
Purdue University
West Lafayette, IN 47907


Professor Alexander Kaplan
Principal Investigator

May 30, 1983

cc: MIT/Mr. Duff
NE/Dr. Haraldsen

84 01 19 128

Approved for public release;
distribution unlimited.

The research under this grant started on April 1, 1982, at M.I.T. The initially proposed period for this research was 1 year, with initial budget \$79,626. At the Fall 1982, the grant was transferred from M.I.T. to Purdue University. This was done in the form of subcontract, which results in loss of approximately \$13,000 in research funding due to indirect costs related with the subcontract procedure. This corresponds to approximately 2 months of research lost as far as the term of grant is concerned. During the remaining period of time, a number of novel results were obtained which were published in 12 papers (see list attached).

The research progressed basically in these directions:

- i) Enhancement of the sagnac effect in ring resonator and directionally asymmetric bistability based on nonlinear nonreciprocity [2, 4, 10].
- ii) Nonlinear optic modes at nonlinear interfaces [1, 6]. This portion of the research was aimed to start a study of excitation of modes at the bent nonlinear surfaces; it was based on the research by the principal investigator under previous grant AFOSR-80-0188 and done in collaboration with researchers in Bell Labs, Holmdel, NJ.
- iii) Nonlinear (and particularly bistable) cyclotron resonance based on relativistic nonlinearity of electron in vacuum and in semiconductors [3, 8, 11]; this is to continue a research started under previous grant AFOSR-80-0188.
- iv) Enhancing of laser gyroscopes by nonreciprocal feedback [5, 7]; this work is to start a novel modification of initial concept by using electro-optical means.
- v) General theory of light-induced (nonlinear) nonreciprocity and its various applications [9, 10, 12] (in particular, theory of nonlinear eigenpolarizations of counterpropagating beams and its application to nonlinear "nonreciprocal" spectroscopy [12]).

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH
NOTICE OF TRANSMITTAL TO FILE
This technical report is being submitted to the
approved for distribution to the public.
Distribution is unlimited.
MATTHEW J. KEEPER
Chief, Technical Information Division

Grant AFOSR-82-0126
List of Publications

1. W. J. Tomlinson, J. P. Gordon, P. W. Smith (Bell Labs.) and A. E. Kaplan (MIT), "Reflection of a Gaussian beam at nonlinear interfaces," Applied Optics, 21:2041-2051 (1 June 1982).
2. A. E. Kaplan and P. Meystre, "Nonlinear Sagnac effect," Appl. Phys., B28:24 (June - July 1982).
3. A. E. Kaplan, "Bistable cyclotron resonance based on relativistic nonlinearity," Appl. Phys., B28:166-167 (June - July 1982).
4. A. E. Kaplan and P. Meystre, "Large enhancement of the Sagnac effect in a nonlinear ring resonator and related effects," in Fiber-Optic Rotational Sensors and Related Technologies, ed. S. Ezekiel, and H. J. Arditty, Springer Verlag, 1982, pp. 375-385.
5. A. E. Kaplan, "Enhancement of laser gyro by nonreciprocal feedback," paper at 1982 Ann. Meeting of Opt. Soc. Am., Tucson, Arizona, Oct. '82, paper TuV3, Techn. Rep. p. 31.
6. A. E. Kaplan (M.I.T.), P. W. Smith, and W. J. Tomlinson (Bell Labs), "Switching of reflection of light at nonlinear interfaces," in Integrated Optics and Millimeter and Microwave Integrated Circuits, SPIE Vol. 317, pp. 305-310 (1982).
7. A. E. Kaplan, "Electro-optic enhancement of the Sagnac effect in ring resonator and related effect of directional bistability," Appl. Phys. Lett. 42:479-481 (March 15, 1982).
8. A. E. Kaplan, A. Elci, "Cyclotron Optical bistability in semiconductors," presented at 1983 Conference on Lasers and Opto-Electronics, CLEO'83, Baltimore, Maryland, May 17-20, 1983.
9. A. E. Kaplan, "Nonlinear nonreciprocity: Theory and feasible applications," presented at Los Alamos National Lab. Conference on Optics '83, Los Alamos, NM, April 11-15, 1983.
10. A. E. Kaplan, "Directional bistability and related nonlinear nonreciprocal effects in rotating and moving medium and systems," submitted for presentation at Topical Meeting on Optical Bistability, Rochester, NY, June 15-18, 1983.
11. A. E. Kaplan, "Cyclotron hysteresis of electrons in vacuum and semiconductors," submitted for presentation at Topical Meeting on Optical Bistability, Rochester, NY, June 15-18, 1983.
12. A. E. Kaplan, "Light-induced nonreciprocity and anisotropy, field invariants and nonlinear eigen-polarizations," to be published.

to be published
in "Appl. Phys. Lett."
15 March '83

**Opto-electronic Enhancement of the Sagnac Effect in
a Ring Resonator and Related Effect of Directional Bistability**

A. E. Kaplan

School of Electrical Engineering

Purdue University

West Lafayette, IN 47907

Abstract

A substantial enhancement (by orders of magnitude) of the Sagnac effect in a passive ring resonator can be attained by using a nonreciprocal feedback. This feedback is based on the nonreciprocal element controlled by the signal proportional to the difference between intensities of counterpropagating waves, and is an opto-electronic analog of nonlinear nonreciprocity proposed by us early. Under some critical conditions, this system can exhibit directional bistability and directional switching of the counterpropagating waves.

The Sagnac effect¹ is an underlying phenomenon for optical rotational sensors (laser gyroscopes as well as passive interferometers and ring resonators) which provide an opportunity to measure extremely small rotation rates² and could be applied for geophysical research, inertial navigation systems and related techniques³. In our previous work⁴, a novel way to dramatically enhance the Sagnac effect was proposed which is based on nonlinearly induced nonreciprocity. (Under some conditions the nonlinear nonreciprocity can result also in directional bistability⁵).

In this paper, we propose an opto-electronic analog of the nonlinear system^{4,5} which imitates nonlinear nonreciprocity by using the signal proportional to the difference between intensities of counterpropagating waves in the ring resonant (see Fig. 1) to control the nonreciprocal element (e.g. Faraday rotator⁶) which is incorporated in the resonator and causes a differential change of total optical path lengths of both of the waves. The Faraday rotator may comprise, e.g. of a Faraday cell or Faraday mirror⁶ (which might be even preferable because it does not disturb a wave propagation inside the ring resonators) driven by an external magnet field.

We consider a passive ring resonator (Fig. 1) which is pumped in opposite directions by the laser beams having the same intensity $|E_{in}|^2$ and frequency ν tuned in such a way that it is close to one of the eigenfrequencies ν_0 of the resonator. Then, in the presence of rotation, the Sagnac effect causes an initial differential change of the optical paths of the waves. In turn, this results in differential changes of the intensities of both of the waves because of the splitting of the eigenfrequencies seen by both of beams (one of the beams moves toward a resonance while another moves away from it). This small intensity difference can be detected and amplified by differential amplifier. The output signal of this amplifier is used to drive the nonreciprocal element (e.g. via controlled magnet field in the Faraday cell) which provides further splitting of the eigenfrequencies and further increase of the difference between the intensities. In a way, such a system is an opto-electronic analog of nonlinear-optic passive gyroscope

proposed in Ref[4,5], i.e. nonreciprocal feedback could be considered as "artificial" nonlinear nonreciprocity. Another system, based on the same idea of nonreciprocal feedback, was recently proposed⁷ by us for a laser gyroscope in which case the feedback signal is proportional directly to the frequency splitting of oscillations in laser gyro.

Suppose that the nonreciprocal response (e.g. the nonreciprocal shift of each eigenfrequency, $\Delta\nu_{nr}$) provided by the feedback is proportional to the difference between the partial intensities of the waves:

$$\Delta\nu_{nr}/\nu_o = \alpha(|E_1|^2 - |E_2|^2) \quad (1)$$

where $\alpha = \text{const}$ is a coefficient determined by the parameters of the amplifier, the Faraday cell, etc. (We assume as well, that the detecting and amplifying system can distinguish the sign of difference between the intensities). Then the steady-state amplitudes E_j ($j = 1, 2$) of each of the two waves transmitted through the output semi-transparent mirror are:

$$E_j = \frac{E_{in}\sqrt{\gamma_c/\gamma}}{1 + i\gamma^{-1}\{\nu - \nu_o + (-1)^j[\omega_s + \alpha\nu_o(|E_1|^2 - |E_2|^2)]\}} \quad (2)$$

Here E_{in} is an amplitude of the incident (pumping) field, γ_c is the empty cavity bandwidth (i.e. that caused by mirrors only), γ is the total bandwidth of the system ($\gamma = \gamma_c + \gamma_m$, where γ_m gives the linear losses of medium inside the cavity), and

$$\omega_s = 4S\omega_r\nu_o/Lc \quad (3)$$

is the "Sagnac frequency splitting", where ω_r is rotational rate, S is the area of the ring resonator, and L is its total optic path length. Note that Eq. (2) is an approximate form valid for the good finesse case, that is $\gamma \ll c/L$. We introduce the dimensionless resonance detuning $\Delta = (\nu - \nu_o)/\gamma$ and the dimensionless rotational rate $\Omega = \omega_s/\gamma$, as well as the dimensionless intensities:

$$I_j = \alpha \nu_o |E_j|^2 / \gamma; (j=1,2); I_{in} = \alpha \nu_o \gamma_c |E_{in}|^2 / \gamma^2 \quad (4)$$

(Note that I_j and I_{in} change sign if $\alpha < 0$). The equations for the intensities I_j are readily obtained by multiplying Eq. (3) by its complex conjugate:

$$I_{in} = I_1 [1 + (\Delta - \Omega - I_1 + I_2)^2] = I_2 [1 + (\Delta + \Omega + I_1 - I_2)^2] \quad (5)$$

We assume that in the absence of rotation ($\Omega=0$), the intensities I_1 and I_2 are equal:

$$I_1 = I_2 = I_o \equiv I_{in} / (1 + \Delta^2) \quad (6)$$

Then, in the most interesting case of small rotations ($\Omega \ll 1$), one can assume that the perturbations $\zeta_j = I_j - I_o$ are small ($\zeta_j \ll I_o$). Under this condition, Eqs. (5) immediately yields for ζ_j :

$$\zeta_1 = -\zeta_2 = \Omega(\eta - 1)/2 \quad (7)$$

where

$$\eta = [1 - 4I_{in}\Delta / (1 + \Delta^2)^2]^{-1} \quad (8)$$

Without any nonreciprocal feedback, the Sagnac effect is determined by the term ω_s in Eq. (2) with $\alpha = 0$. It can be seen now from Eq. (5,7) that with the feedback, the total phase difference between the two counterpropagating waves is determined by $\eta\omega_s$ instead of by ω_s . Hence the result of the nonreciprocal feedback is to scale the Sagnac effect by a factor of η which is to be considered as an enhancement factor. Its behavior as a function of the resonant detuning Δ for various pumping intensities I_{in} is shown at Fig. 2. If $I_{in} < 4/3\sqrt{3}$, the maximum and minimum of η , namely $\eta_m = (1 \pm 3I_{in}\sqrt{3/4})^{-1}$, occurs at $\Delta = \pm 1/\sqrt{3}$. It is seen from Eq. (8) that at the boundary

$$I_{in} = I_{th} \equiv \frac{(1 + \Delta^2)^2}{4\Delta} \quad (9)$$

enhancement becomes infinitely large ($\eta \rightarrow \infty$), i.e. Eq. (9) defines the boundary of the domain of instability (domain 1 at Fig. 3). The enhancement increases dramatically as one approaches the boundary (9) from the outside of this domain (i.e. $0 < I_{th} - I_{in} \ll I_{th}$). Let us make quantitative estimates. We assume that stability of the pumping intensity $|E_{in}|^2$ (as well as that of the feedback circuit) is of order of 10^{-4} (e.g. for stabilized argon laser⁸), while the stability of the resonant detuning ($\omega - \omega_0$) is even much better⁸. It can then be seen from Eq. (8) with $\Delta \approx 1/\sqrt{3}$ that the enhancement of $\eta \sim 1.5 \times 10^2$ with stability of 10^{-2} can readily be attained. The difference between the partial intensities $|E_1|^2 - |E_2|^2$, which is to be monitored by the differential detector, is sufficiently large even for very small rotation rates. We assume that $L \sim 1m$, $S \sim 1m^2$, $\lambda_0 \sim 0.5\mu$, $\gamma \sim \gamma_c \sim cT/L$ (T -transmission of a mirror; we assume $T \sim 10^{-2}$). Eq. (7) then gives $(I_1 - I_2)/I_0 \sim 10^2 \eta \omega_r / 2\pi$ where ω_r is expressed in sec^{-1} . Therefore, if $\eta \sim 100$ and $\omega_r \sim 2\pi \cdot 10^{-8} sec^{-1}$, then $(I_1 - I_2)/I_0 \sim 10^{-2}$ which can be easily detected and still is by two orders of magnitude larger than the intensity deviations associated with the stability 10^{-4} . For the considered case, the limitation on the lowest measured rotation rate (with enhancement ~ 100) imposed by the stability of intensity 10^{-4} is $\omega_r \approx 2\pi \cdot 10^{-8} sec^{-1} \approx 10^{-3}$ earth rotation.

Inside the domain of instability (domain 1 at Fig. 3), any small initial difference between I_1 and I_2 grows up exponentially such that steady state $I_1 = I_2$, Eq. (6), becomes unstable. This results in formation of asymmetric oscillation: the amplitude of clockwise wave is different from that of counterclockwise wave, even in the absence of rotation, with the sign of this difference determined by noise or initial conditions. Therefore, the stable regimes with $I_1 > I_2$ and $I_1 < I_2$ are equally probable, and could be switched from one into another, which could be considered as a directional bistability. This kind of bistability is again analogous to that studied in Ref. 5.

To find out the characteristics of the asymmetrical regime, one can use again Eqs. (2) and (5) with $\Omega = 0$, looking now for solutions with $I_1 \neq I_2$. (except from a

symmetrical solution (6)). Eq. (5) readily yields:

$$I_{1,2} = \frac{1}{2} \left[\Delta \pm \frac{1}{\Delta} \sqrt{\Delta(I_{in} - \Delta)} \pm \sqrt{\Delta^2 - 1 \pm 2\sqrt{\Delta(I_{in} - \Delta)}} \right] \quad (10)$$

Here, for each set (I_1, I_2) , the sign in the front of radicals $\sqrt{\Delta(I_{in} - \Delta)}$ should be the same; both signs in the front of large radical give one set (I_1, I_2) . Behavior of the intensities I_1 and I_2 as function of the pumping intensity I_{in} for fixed detunings Δ is shown at Fig. 4. It is seen that for $\Delta < 0$ (curve 1) the oscillations are always symmetric ($I_1 = I_2$). For $0 < \Delta < 1$ (curve 2), one can see that above the threshold ($I_{in} > I_{th}$) intensities of oscillation become different ($I_1 \neq I_2$) which corresponds to the asymmetric regime or the directional bistability ($I_1 > I_2$ or $I_1 < I_2$). Note that I_1 and I_2 play completely symmetrical roles in Eqs. (5), so that which of them becomes larger is determined only by noise or initial conditions.

Furthermore, it follows from Eq. (10) that for $I_{in} > 1$ and $\Delta > 1$, the asymmetrical regime can itself become multivalued (curve 3 at Fig. 4). In such a case, Eq. (10) provides 4 possible solutions; two of them, which satisfy condition $d(I_1 + I_2)/dI_{in} > 0$, are stable (i.e. those with upper sign in the front of radicals $\sqrt{\Delta(I_{in} - \Delta)}$), while two others are unstable. This provides an opportunity for the existence of a triple-stable regime (the third state is the symmetric regime $I_1 = I_2$ which remains stable in this case). By requiring that $dI_j/dI_{in} = \infty$ at the border, we find readily, that the multivalued domain in the plane of the parameters I_{in} and Δ is defined as $I_{th} > I_{in} > \Delta$ where I_{th} is as given by Eq. (9) (i.e. domain 2 at Fig. 3). Therefore, when increasing the pump intensity I_{in} from a zero value, the system exhibits a discontinuous jump to the asymmetrical regime at $I_{in} = I_{th}$. If now one decreases I_{in} , there is a backward jump into the symmetric regime at $I_{in} = \Delta < I_{th}$, such that one covers an hysteretic cycle.

In conclusion, we propose the use of nonreciprocal opto-electronic feedback to dramatically enhance the Sagnac effect in a passive ring resonator. The feedback is comprised of the nonreciprocal element driven by the signal proportional to the splitting of intensities of counterpropagating waves in the resonator. To some extent, this system provides an opto-electronic analog of the nonlinear enhancement of the Sagnac effect proposed in Ref [4], and therefore, can be used to model the latter. On the other hand, the proposed system is of considerable interest for gyro applications on its own. This basically is due to the fact that the main disadvantage (which consists in slow relaxation time of the feedback) of the system is not substantially important for the gyroscope because the required response time is usually fairly large.

It is shown that the factor of enhancement η becomes large in the proximity of the threshold of asymmetrical instability of oscillation. An estimate shows that if the stability of the feedback and the pumping intensity is maintained with accuracy of $\sim 10^{-4}$, the enhancement of $\eta \sim 100$ with stability of 1% can be attained and rotation rates as low as 10^{-3} earth rotation can be measured for typical parameters of the resonator. Inside the domain of instability of symmetrical regime, a new, asymmetric regime establishes with dominant mode (clockwise or anticlockwise) determined by initial conditions. This regime corresponds to the directional bistability⁵ and therefore could be used for directional switching of radiation.

This work was supported by the U.S. Air Force Office of Scientific Research.


References

1. For a comprehensive review, see E. Post, Rev. Mod. Phys. 39, 475 (1967); J. Anandan, Phys. Rev. D. 24, 338 (1981).
2. F. Aronowitz, Proc. SPIE, 157, 2 (1978); T. A. Dorschner, H. Haus, M. Holz, I. W. Smith and H. Statz, IEEE J. Quant. Electr. QE-16, 1376 (1980); G. A. Sanders, M. G. Prentiss and S. Ezekiel, Opt. Lett. 6, 589 (1981).
- 3.(a) Proc. Soc. Photo-Opt. Instrum. Eng., 157 "Laser Inertial Rotation Sensors", 1978, San Diego, CA.
(b) Proc. Conf. on Fiber-Optic Rotational Sensors, M.I.T., (November 1981, Cambridge, MA), to be published.
4. A. E. Kaplan and P. Meystre, Opt. Lett., 6, 590 (1981); also in Ref. 3b.
5. A. E. Kaplan and P. Meystre, Opt. Comm., 40, 229 (1982); also in Ref. 3b.
6. The use of Faraday rotators of various kinds in application to bias in laser gyro was discussed by I. W. Smith and T. A. Dorschner, Proc. SPIE, 157, 21 (1978).
7. A. E. Kaplan, to be published.
8. L. A. Hackel, R. P. Hackel, and S. Ezekiel, Metrologia 13, 141 (1977).

Figure Captions

- Fig. 1.** Schematic of ring resonator gyroscope using an imitation of nonlinear nonreciprocity for substantially enhancing the Sagnac effect; the resonator is pumped in both directions by laser beams with equal intensity and frequency. Nr - nonreciprocal element which may comprise, e.g. of a Faraday cell or a Faraday mirror driven by an external magnet field; D-detecting system providing measurement of phase difference between both of the beams; A-differential amplifier. The signal proportional to the intensity difference controls the nonreciprocal element.
- Fig. 2.** The enhancement factor η vs the dimensionless resonant detuning Δ for various pumping intensity I_{in} . Curves: 1 - $I_{in} = 0$; 2 - $I_{in}/I_{cr} = 0.7$ (where $I_{cr} = 4/3\sqrt{3}$); 3 - $I_{in}/I_{cr} = 0.9$; 4 - $I_{in}/I_{cr} = 0.97$; 5 - $I_{in} = I_{cr}$.
- Fig. 3.** Domains of operation in the plane of parameters I_{in} and Δ : 1 - domain of instability of the symmetric solution $I_1 = I_2$ and existence of directional bistability (with the asymmetric solution $I_1 \neq I_2$); 2 - domain of multistable solution; 3 - domain of significant ($\eta > 2$) enhancing the Sagnac effect.
- Fig. 4.** Dimensionless intensities I_1 and I_2 of the counterpropagating waves vs pumping intensity I_{in} for various resonant detunings Δ . The dotted part of the curves indicate unstable regimes. The curves labeled by $I_1 = I_2$ correspond to the symmetric solution. Curves: 1 - $\Delta = 0$; 2 - $\Delta = 0.6$; 3 - $\Delta = 2$.

Fig. 1






Fig. 2

Fig. 3





Fig. 4



END

FILMED

2-84

DTIC