

12

DOCUMENT 370-83

BARKING SANDS, HAWAII

RANGE REFERENCE ATMOSPHERE
0-70 KM ALTITUDE

DECEMBER 1983

METEOROLOGY GROUP
RANGE COMMANDERS COUNCIL

WHITE SANDS MISSILE RANGE
KWAJALEIN MISSILE RANGE
YUMA PROVING GROUND

PACIFIC MISSILE TEST CENTER
NAVAL WEAPONS CENTER
ATLANTIC FLEET WEAPONS TRAINING FACILITY
NAVAL AIR TEST CENTER

EASTERN SPACE AND MISSILE CENTER
ARMAMENT DIVISION
WESTERN SPACE AND MISSILE CENTER
AIR FORCE SATELLITE CONTROL FACILITY
AIR FORCE FLIGHT TEST CENTER
AIR FORCE TACTICAL FIGHTER WEAPONS CENTER

DTIC
S E
1 FEB 01 1984

AD A 137406

DTIC FILE COPY

MG

This document is approved
for public release, its
distribution is unlimited.

84 01 31 092

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER DOCUMENT 370-83	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) "Barking Sands, Hawaii, Range Reference Atmosphere, 0-70 Km Altitude"		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Meteorology Group Range Commanders Council White Sands Missile Range, NM 88002		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Same as Block 7.		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Range Commanders Council ATTN: STEWS-SA-R White Sands Missile Range, NM 88002		12. REPORT DATE December 1983
		13. NUMBER OF PAGES 201
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Same as block 11.		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for Public Release; Distribution Unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Supersedes Document 104-63, "Lihue, Kauai, Hawaii, Part 1" AD782653.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Range reference atmosphere, data quality control, coordinate system, computation of statistical parameters, statistical models, orthogonal axes, thermodynamic quantities, data samples, altitude levels, derived monthly mean, annual mean model atmospheres.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) FOREWORD -see attached.		

DOCUMENT 370-83

BARKING SANDS, HAWAII

RANGE REFERENCE ATMOSPHERE
0-70 KM ALTITUDE

December 1983

Prepared by

Range Reference Atmosphere Committee
Meteorology Group
Range Commanders Council

Published by

Secretariat
Range Commanders Council
White Sands Missile Range, New Mexico 88002

APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED

TABLE OF CONTENTS

	<u>PAGE</u>
LIST OF ORGANIZATION ACRONYMS	v
FOREWORD	vii
CHAPTER I. INTRODUCTION	1
A. Definition and Purpose of the Range Reference Atmosphere	1
B. Scope of the Range Reference Atmosphere and Arrangement of Tables.	1
C. Data Quality Control Procedures.	2
D. Organization of the Chapters	3
CHAPTER II. WIND STATISTICS AND MODELS.	5
A. General Considerations	5
B. Coordinate System and Computation of Statistical Parameters	8
C. Statistical Wind Models.	10
D. Statistical Parameters With Respect to Any Orthogonal Axes	25
CHAPTER III. STATISTICS OF THERMODYNAMIC QUANTITIES AND MODELS	29
A. General Considerations	29
B. Establishing Data Samples at the Required Altitude Levels.	32
C. Computation of Statistical Parameters for Tables II and III.	36
D. Derived Monthly Mean and Annual Mean Model Atmospheres.	39
E. Thermodynamic Quantities Derivable from the Basic Tables.	40
CHAPTER IV. CONCLUSIONS AND RECOMMENDATIONS	47
REFERENCES	49
CONVERSION UNITS	53
APPENDIX A	109
APPENDIX B	175

LIST OF ORGANIZATION ACRONYMS

AD	Armament Division
AFFTC	Air Force Flight Test Center
AFSC	Air Force Systems Command
AFSC/AFGL	AFSC/Air Force Geophysics Laboratory
AFSC/SD	AFSC/Space Division
AFSCF	Air Force Satellite Control Facility
AFTFWC	Air Force Tactical Fighter Weapons Center
AWS	Air Weather Service
BMD	Ballistic Missile Division
DOD	Department of Defense
DOE	Department of Energy
DOE/NTS	DOE/Nevada Test Site
DPG	Dugway Proving Ground
ESMC	Eastern Space and Missile Center
ETR	Eastern Test Range
KMR	Kwajalein Missile Range
NASA	National Aeronautics and Space Administration
NASA/MSFC	NASA/Marshall Space Flight Center
NASA/WFC	NASA/Wallops Flight Center
NOAA	National Oceanic and Atmospheric Administration
NWC	Naval Weapons Center
PMTC	Pacific Missile Test Center
USA/DTC	U.S. Army/Deseret Test Center
USAECON	U.S. Army Electronics Command
USAFETAC	United States Air Force Environmental Technical Applications Center



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

UTTR	Utah Test and Training Range
WSMC	Western Space and Missile Center
WSMR	White Sands Missile Range
WTR	Western Test Range
YPG	Yuma Proving Ground
6585TG	6585th Test Group
TSCF	Targeting Systems Characterization Facility

FOREWORD

Atmospheric parameters are essential to the research and development of missiles and aerospace vehicles. In the early 1960's, the need was recognized for realistic atmospheric models derived in a consistent manner for each of the several major test ranges. An atmospheric model derived from statistical data for a particular geographical location is referred to as a reference atmosphere.

The first Range Reference Atmosphere (RRA) was issued in 1963 by the Inter-Range Instrumentation Group (IRIG) for Cape Kennedy, Florida, and was followed by additional publications for several ranges up to 1974. Since that time, improved upper air data bases have become available from which to develop the RRA. These resulted from the extended period of records and from improvement in the upper air measuring program by rocketsondes for altitudes above the rawinsonde ceiling of 30 km. Revised and improved RRAs are justified for the following reasons:

- 1) Needs for more definitive statistical atmospheric models have arisen because of changes and advances in aerospace technology. The Space Transportation System (Space Shuttle) is one example.
- 2) Most ranges now have an extended and improved upper air data base from which to develop a more definitive RRA.
- 3) There are requirements for RRAs for new ranges and range sites.
- 4) There have been scientific advances in understanding the upper atmospheric structure and physical relationships.
- 5) Advances in statistical modeling techniques have been made because of the general availability of high-speed electronic computers. These have led to the adoption of advanced concepts in atmospheric modeling.

For these reasons, the Range Reference Atmosphere Committee (RRAC) was tasked by the Range Commanders Council Meteorology Group (RCC MG) to establish new and improved RRAs. The purpose, scope, and objectives of this task are outlined in the following paragraphs.

Purpose: This committee, Task MG-1, establishes RRAs for the several ranges as provided by the RCC. An RRA is a model of the Earth's atmosphere over a geographical location of interest, for use by DOD and other U.S. Government range users. The RRA is used to provide planning data for evaluating environmental constraints for the particular configurations of environment-sensitive systems and components being developed or undergoing tests.

Scope: Using the best available upper atmosphere data base to include rawinsonde, rocketsonde and possibly other high-altitude data sources for the range location, the task is to establish a model of certain statistics for wind and thermodynamic quantities derived in a uniform manner and published in a standardized format.

Objectives: The wind statistics shall be, insofar as practical, modeled to be consistent with rigorous mathematical probability properties of the multivariate normal probability theory. The thermodynamic quantities statistics shall be, insofar as practical, modeled to be consistent with the hydrostatic equation, the equation of state, and the probability principles that are related through these physical equations. The document shall serve as an authoritative source of information and as an atmospheric model for a particular range. The first in the series of revised RRAs to be published is for Kwajalein Missile Range (KMR) (publication date December 1982). The altitude range required for KMR is 0 to 70 km. The order of priority for the subsequent publications is:

<u>Range</u>	<u>Altitude Range Required</u>
1. AFFTC/Edwards AFB, CA	0 - 70 km ^a
2. ESMC/Cape Canaveral AFS, FL	0 - 70 km
3. WSMC/Vandenberg AFB, CA	0 - 70 km ^a
4. WSMR/White Sands, NM	0 - 70 km
5. PMTC/Point Mugu, CA	0 - 70 km
6. UTTR/Dugway (Michael AAF), UT	0 - 30 km ^b
7. AD/Eglin AFB, FL	0 - 30 km
8. ESMC/Ascension Island	0 - 70 km (Terminates at 66 km because of insufficient data)
9. NASA/Wallops Flight Center, VA	0 - 70 km
10. Taquac (Guam)	0 - 30 km
11. PMTC/Barking Sands, HI	0 - 70 km

In keeping with the RCC's objective of standardization, the modeling techniques, basic text, and tabulation format are to be the same for all RRAs. These new and revised RRAs present not only the mean values of the thermodynamic quantities (pressure, temperature, virtual temperature, and density), but also include statistical measures for the dispersion (i.e., standard deviations and skewness coefficients). New quantities presented are water vapor pressure and dewpoint temperature. The statistical modeling for the wind is entirely new. The new approach uses the properties of the bivariate normal probability distribution function.

- a. Use rocketsonde data from PMTC/Point Mugu for altitudes above 30 km.*
b. Consider augmenting data base from Ely or Salt Lake City.

All final computations were performed by the United States Air Force Environmental Technical Applications Center (USAFETAC) in response to a task from Eastern Space and Missile Center (ESMC).

The text was prepared jointly by USAFETAC and the NASA/George C. Marshall Space Flight Center's Space Sciences Laboratory, Atmospheric Sciences Division. The editing and preparation of the draft manuscript were performed by the NASA/MSFC organization.

The cochairmen express their gratitude to all RRAC members and their respective colleagues who have made significant technical contributions to the establishment of these RRAs.

Special thanks are tendered to Lt. B. Novograd for his diligence in forming the many computations and the development of the primary tables, I through IV. Special thanks goes to Lt. F. Wirsing for editing and formulating the equations for the derivable thermodynamic equations. These gentlemen performed this outstanding work under the direction of Major B. Lilius, USAFETAC.

Grateful acknowledgment goes to Mrs. Annette Tingle, NASA/MSFC, for editing the draft manuscript.

The RRAC consists of representatives from the U.S. Air Force, U.S. Army, National Aeronautics and Space Administration, U.S. Navy, and National Oceanic and Atmospheric Administration. The committee members for the RRA for the first publication are:

G. G. Boire, WSMC
O. H. Daniel, ESMC
R. de Violini, PMTC
F. G. Finger, NOAA/NWS
E. E. Fisher, HQ AFSC
B. R. Hixon, PMTC
J. M. Hobbie, KMR
E. J. Keppel, AD
S. F. Kubinski, WSMR
F. J. Schmidlin, NASA/WFC

O. E. Smith
Cochairman, NASA/MSFC

Maj. B. W. Galusha
Cochairman, USAF/ETAC

CHAPTER I. INTRODUCTION

A. Definition and Purpose of the Range Reference Atmosphere

A.1 Definition

A reference atmosphere is a statistical model of the Earth's atmosphere derived from upper air measurements over a particular geographical location. Hence, these Range Reference Atmospheres (RRAs) are atmospheric models developed by the Range Reference Atmosphere Committee (RRAC) in response to a task by the Range Commanders Council Meteorology Group (RCC MG) and published by the RCC Secretariat. The RCC MG, formerly called the Inter-Range Instrumentation Group/Meteorology Working Group (IRIG/MWG), published a series of RRAs during the period 1963 through 1974.

A.2 Purpose

A series of revised and expanded RRAs are to be published for locations of interest to the RCC. These publications are to serve as authoritative reference sources on certain upper air statistics and as atmospheric models for particular range sites. The technical usefulness of these documents for the ranges, range users, U.S. aerospace industries, and the scientific community is recognized because of the standardization of the development techniques and the presentation of the tabulations.

B. Scope of the Range Reference Atmosphere and Arrangement of Tables

B.1 Scope

The RRA contains tabulations for monthly and annual means, standard deviations, and skewness coefficients for windspeed, pressure, temperature, density, water vapor pressure, virtual temperature, and dewpoint temperature; the means and standard deviations for the zonal (U) and meridional (V) wind components; and the linear (product moment) correlation coefficient between the wind components. These statistical parameters are tabulated at the station elevation, at 1-km intervals from sea level to 30 km, and at 2-km intervals from 30 to 90 km. The wind statistics are given at approximately 10 m above the station elevations and at altitudes with respect to mean sea level thereafter. For those range sites without rocketsonde measurements, the RRAs terminate at 30 km altitude, or they are extended, if required, when rocketsonde data from a nearby launch site are available. There are four sets of tables for each of the 12 monthly reference periods and the annual reference period.

B.2 Arrangement of Tables

The statistical parameters for the RRA models are presented in four tables, as outlined in the following paragraphs.

Table I contains all the wind statistical parameters. This table gives the monthly and annual means and standard deviations of the U and V wind components and the linear (product moment) correlation coefficient between these

two components; the mean, standard deviation and skewness coefficient of the windspeed; and the number of wind observations (sample size).

Table II contains the monthly and annual means, standard deviations, and skewness values of pressure, temperature, and density, and the number of observations used for each of these thermodynamic quantities.

Table III contains the monthly and annual means, standard deviations and skewness values of the water vapor pressure, virtual temperature and dewpoint, and the number of observations for each of these moisture-related quantities. The statistical parameters for water vapor pressure and dewpoint terminate at 15 km altitude. Above 15 km the statistical parameters for virtual temperature are considered to be the same as those for temperature.

Table IV contains the monthly and annual mean atmospheric models for the thermodynamic variables: pressure, virtual temperature, and density. This table is derived from the monthly and annual mean virtual temperature versus altitude (geometric) using the hydrostatic equation and the equation of state. Also presented is the geopotential height corresponding to the tabulated geometric altitudes.

The physical unit for all wind parameters is meters per second. The physical unit for pressure is millibars; for temperature and virtual temperature, degrees Kelvin; for density, grams per cubic meter; and for water vapor pressure, millibars. In all cases the skewness coefficient and the correlation coefficient between wind components are unitless. All reference to altitude is geometric altitude and is expressed in kilometers. All reference to height is geopotential height and has the unit geopotential meters or kilometers. All geometric altitudes and geopotential heights are with respect to mean sea level.

C. Data Quality Control Procedures

A small portion (less than 10 percent) of the soundings in the data base used to calculate the RRA tables contained erroneous data values. The soundings which contained these erroneous values were eliminated from the data base using the following procedures:

- 1) Soundings containing gaps in their height data greater than 200 mb were rejected. This step was taken because some soundings only contained height values at their "mandatory" pressure levels, which were occasionally missing, resulting in soundings with no height information at all.

- 2) An initial set of RRA statistics was computed using all the remaining soundings. This initial set of statistics was used to determine data limits for the temperature, pressure, U and V components of the wind, and the dewpoint (for the 0- to 30-km portion of the RRA) or the density (for the 30- to 90-km portion of the RRA). The lower (upper) data limits were set at the mean value for a specific parameter, minus (plus) six standard deviations of that quantity. One pair of data limits was computed for each of these parameters: month of the year and data level.

3) This initial set of data limits was then used to screen the data base. All the soundings that contained values outside these data limits were rejected. A new RRA was then computed using the screened data base. This second RRA was used to generate a second set of data limits.

4) The second set of data limits was then used to screen the data base further. A new RRA was again generated. The skewness values in this RRA were then evaluated, according to empirical criteria specified in section II.A.3 of this document for the winds, and according to criteria in section III.A.3 for the thermodynamic quantities. If these criteria were satisfied, the new RRA was then used to generate a final set of data limits, which were used to control the quality of the data base for the final version of the RRA.

5) Occasionally, the third RRA that was generated did not satisfy all of the skewness criteria. This indicated that some incorrect values were still present in the data base. To complete quality control, steps 3 and 4 were repeated for additional iterations (usually one or two) until the resulting RRA satisfied the skewness criteria. At that point, a final set of data limits was generated. This final set of data limits was then used to control the quality of the data base and generate the final RRA.

D. Organization of the Chapters

Because there are plans to publish a series of RRAs, comments on the special organization of the document are in order. The RRA document is arranged in four chapters. Chapter I is the introduction. Chapter II, Wind Statistics and Models, contains the techniques used to arrive at the wind statistical parameters, table I, and the probability functions that are to be used as wind models to derive several wind statistics. Chapter III, Statistics of Thermodynamic Quantities and Models, contains the techniques used to arrive at the thermodynamic and moisture-related statistical parameters given in tables II and III and the atmospheric thermodynamic model presented in table IV. This chapter also contains sets of equations to calculate several atmospheric properties. Chapter IV contains the general conclusions and recommendations. These four chapters are reprinted without change for each documented RRA to assure consistency and for expediency in preparing the documentation. To account for variations particular to a specific RRA, two appendixes have been included. Appendix A, Examples of Wind Statistics, is designed to give a few illustrative examples of wind statistics for the specific RRA and cursory observations, comparisons, or comments on wind statistics. Appendix B, Range Specific Information, is designed to present specific information particular to the range, such as geographical location, data base, etc., and any cursory observations or comments on the thermodynamic quantities.

Read these appendixes! They are located as the last two units in the document because they may vary in length depending on the circumstances. Appendixes A and B and tables I, II, III, and IV are the only differences among the RRA documents published in this new RRA series.

CHAPTER II. WIND STATISTICS AND MODELS

A. General Considerations

A.1. Objectives

An objective of the RRA is to furnish minimum tabulation for the wind statistics. To meet this objective, the bivariate normal probability distribution was adopted as a statistical model for the wind treated as a vector quantity at the RRA data levels. Only five statistical parameters are required to completely describe this probability function. In Cartesian coordinates these parameters are the means and standard deviations of the two orthogonal components and the correlation coefficient between the two components. These five statistical parameters for the U and V (meteorological coordinates) components are given in table I. The statistical properties of the bivariate normal probability distribution are used to derive many wind statistics that are of interest to the ranges and range users. This procedure produces consistent wind statistics that are connected through rigorous mathematical probability functions. By using these functions, extensive tabulations of wind statistics are avoided.

The statistical properties of the bivariate normal probability distribution presented for the vector wind statistical model are:

- 1) The wind components are univariate normally distributed.
- 2) The conditional distribution of one component given a value of the other component is univariate normally distributed.
- 3) The windspeed is of the form of a generalized Rayleigh distribution.
- 4) The frequency distribution of wind direction can be derived.
- 5) The conditional distribution of windspeed given a value of wind direction (wind rose) can be derived.
- 6) The five tabulated wind statistical parameters with respect to the meteorological U and V coordinate system can be derived for any arbitrary rotation of the orthogonal axes.

The probability distribution functions and sets of equations to derive wind statistics for the previously stated properties of the vector wind model are presented in this chapter. Symbols used are summarized in table A. Illustrative examples are presented in appendix A. No attempt is made to give the derivation of the probability functions. The reader is referred to Smith (1976) for some derivations and several applications of the probability distribution properties for wind statistics.

A.2. Data Quality Control

The U and V components of the wind were used to generate data limits set at plus and minus six standard deviations from the mean for each of the

TABLE A. LIST OF SYMBOLS USED IN CHAPTER II

N	- The number of wind measurements in table I
r	- A general variable for the bivariate normal probability distribution in polar coordinates
R	- A generalized Rayleigh variable used for derived windspeed probability distribution
R (U, V)	- The linear (product moment) correlation coefficient between the zonal and meridional wind components in table I
SK (W)	- Skewness parameter for windspeed in table I
S (U)	- The standard deviation of the zonal wind component in table I
S (V)	- The standard deviation of the meridional wind component in table I
S (W)	- The standard deviation of windspeed in table I
t	- A standardized normal variate used in text table B
U	- The zonal wind component
UBAR	- The mean value of the zonal wind component in table I
V	- The meridional wind component
VBAR	- The mean value of the meridional wind component in table I
W	- Windspeed or modulus of wind vector, a scalar quantity
WBAR	- The mean value of windspeed in table I
X	- A general component variable or coordinate axis
Y	- A general component variable or coordinate axis
$\bar{X}$	- A general component mean value in the [x,y] coordinate system
$\bar{Y}$	- A general component mean value in the [x,y] coordinate system
α (alpha)	- Rotation angle for the [x,y] coordinate system

TABLE A. (concluded)

θ (theta) - Wind direction in the polar coordinate system

λ () (Lambda) - A parameter in the bivariate normal probability distribution in text table C

ξ (Xi) - The mean value in the standardized normal probability distribution used in text table B

π (Pi) - Constant = 3.14159 ...

ρ (Rho) - The general linear correlation coefficient between the two component variables in the [x,y] coordinate system

σ_x, σ_y - The general standard deviations of the x and y component variables in the [x,y] coordinate system.

quantities. These data limits were used to screen the wind data base, as described in section I.C. The data base was considered to be free from errors under the following conditions:

- 1) The skewness of the windspeed was below 4.0 at data levels where the mean windspeed was less than 15 m/s, and

- 2) The skewness of the windspeed was below 2.5 at data levels where the mean windspeed was greater than 15 m/s.

A.3 Limitations

For the wind statistics, the correlation coefficients for like wind components and unlike wind components between altitude levels were not computed. Therefore, wind statistics with respect to altitude (profile) cannot be derived from the RRA statistics. For wind profile modeling techniques the user is referred to Smith (1976). However, the wind statistics at discrete altitudes are valid; all of the probability distribution functions given in chapter II can be derived from the five wind component statistical parameters contained in table I, and the derived distributions can be considered as wind models at discrete altitudes.

By convention, in the statistical literature Greek letters are used for population or theoretically known parameters, and sample estimates are denoted by English alphabetical letters or with a "hat" (^) over the Greek letters. In chapter II Greek letters are used for the variances and the linear correlation coefficient, and the means are denoted by $\bar{X}$ and $\bar{Y}$ when dealing with the bivariate normal distribution. It will always be understood that table I contains sample estimates of the statistical parameters and they are with respect to the meteorological U and V coordinate system.

B. Coordinate System and Computation of Statistical Parameters

B.1. Coordinate System

Wind measurements are recorded in terms of magnitude and direction. The wind direction is measured in degrees clockwise from true north and is the direction from which the wind is blowing. The wind magnitude (the modulus of the vector) is the scalar quantity and is referred to as windspeed or scalar wind. A statistical description that accounts for the wind as a vector quantity is appropriate and requires a coordinate system.

For the RRA the standard meteorological coordinate system has been chosen for the wind statistics, all tables of statistical parameters, and related discussions because the coordinate system used in aerospace and related applied fields has not always been consistent.

Using figure 1, the polar and Cartesian forms for the meteorological coordinate system are defined:

W = windspeed, scalar wind, or magnitude of the wind vector in meters per second.

θ = wind direction. θ is measured in degrees clockwise from true north and is the direction from which the wind is blowing.

U = zonal wind component, positive west to east, in meters per second.

V = meridional wind component, positive south to north, in meters per second.

The components θ and W define the polar form, and the U - V components define the Cartesian forms:

$$U = -W \sin \theta, \quad 0 \leq \theta \leq 360^\circ \quad (1)$$

$$V = -W \cos \theta. \quad (2)$$




Figure 1. The meteorological coordinate system.

It is helpful to note the difference between the mathematical convention for a vector direction and the meteorological convention for wind direction:

$$\theta_{\text{met}} = 270 - \theta_{\text{math}} \quad (3)$$

when $0 \leq \theta_{\text{math}} \leq 270^\circ$

$$\theta_{\text{met}} = 360 + (270 - \theta_{\text{math}})$$

when $270 \leq \theta_{\text{math}} \leq 360^\circ$

B.2 Computation of Statistical Parameters

The wind statistical parameters in table I for the means and standard deviations of the U and V wind components and windspeed and the skewness parameter of windspeed were computed using the sums technique presented in chapter III.C.3. In addition, the linear (product moment) correlation coefficient between the U and V wind components, $r(u,v)$ in table I, was computed. This correlation coefficient is defined as

$$r(u,v) = \frac{\sum_{i=1}^n (U_i - \bar{U})(V_i - \bar{V})}{N s(u) \cdot s(v)} \quad (4)$$

These statistical parameters are with respect to the Standard Meteorological Coordinate System.

C. Statistical Wind Models

C.1. Wind Component Statistics

The univariate normal (Gaussian) probability distribution function is used to obtain wind component statistics. In generalized notations, this probability density function (pdf) is

$$f(t) = \frac{e^{-\frac{t^2}{2}}}{\sqrt{2\pi}} \quad (5)$$

where $t = (X - \xi)/\sigma_x$ is the standardized variate, with ξ defining the mean and σ_x the standard deviation. The probability distribution function (PDF) is

$$F(X) = \int_{-\infty}^X f(t) dt \quad (6)$$

Because this integral cannot be obtained in closed form, it is widely tabulated for zero mean and unit standard deviation. For a convenient reference for the RRA, selected values of $F(X)$ are given in table B. To emphasize the connotation of probability, $F(X)$ is shown in table B as $P\{X\}$. The t values in table B are used as multiplier factors to the standard deviation to express the probability that a normally distributed variable, X , is less than or equal to a given value as

$$P\{X \leq \text{mean} + t \sigma_x\} = \text{probability, } p \quad (7)$$

For example, when $t = 1.6449$, the probability that X is less than or equal to the mean plus 1.6449 standard deviations is 0.95. That value of X that is less than or equal to the mean plus 1.6449 standard deviations is called the 95th percentile value of X . Also given in table B are the numerical values to express the probability that X falls in the interval X_1 and X_2 ; i.e.,

$$P\{X_1 \leq X \leq X_2\} = \text{Interpercentile Range} \quad (8)$$

where

$$X_1 = \bar{X} - t \sigma_x$$

$$X_2 = \bar{X} + t \sigma_x$$

For $t = 1.9602$ the probability that X lies in the interval X_1 and X_2 is 0.95. The values of X_1 and X_2 in this example comprise the 95th interpercentile range.

For a normally distributed variable, the mode (most frequent value) and the median (50th percentile value) are the same as the mean value. The means and standard deviations of the U and V wind components from table 1 are used in equations (7) and (8) to compute the percentile values and interpercentile ranges of the U and V wind components. When equation (7) is illustrated on a normal probability graph, a straight line is formed.

C.2. The Vector Wind Model

Because wind is a vector quantity having direction and magnitude that can be expressed as two components in an orthogonal coordinate system, a probability model that describes the joint relationship is the bivariate normal probability distribution. In general component notation, the bivariate normal probability density function (BNpdf) is

TABLE B. VALUES OF t FOR STANDARDIZED NORMAL
(UNIVARIATE) DISTRIBUTION FOR PERCENTILES
AND INTERPERCENTILE RANGES

t	$P(X)$	X	$P\{X_1 \leq X \leq X_2\} (\%)$
-3.0000	0.00135	$\xi - 3.0000 \sigma$	
-2.5758	0.00500	$\xi - 2.5758 \sigma$	
-2.3263	0.01000	$\xi - 2.3263 \sigma$	
-2.2365	0.01266	$\xi - 2.2365 \sigma$	
-2.0000	0.02275	$\xi - 2.0000 \sigma$	
-1.9602	0.02500	$\xi - 1.9602 \sigma$	
-1.6449	0.05000	$\xi - 1.6449 \sigma$	
-1.2816	0.10000	$\xi - 1.2816 \sigma$	
-1.0000	0.15866	$\xi - 1.0000 \sigma$	
-0.8416	0.20000	$\xi - 0.8416 \sigma$	
-0.6745	0.25000	$\xi - 0.6745 \sigma$	
-0.2533	0.40000	$\xi - 0.2533 \sigma$	
0.0000	0.50000	ξ	
0.2533	0.60000	$\xi + 0.2533 \sigma$	
0.6745	0.75000	$\xi + 0.6745 \sigma$	
0.8416	0.80000	$\xi + 0.8416 \sigma$	
1.0000	0.84134	$\xi + 1.0000 \sigma$	
1.2816	0.90000	$\xi + 1.2816 \sigma$	
1.6449	0.95000	$\xi + 1.6449 \sigma$	
1.9602	0.97502	$\xi + 1.9602 \sigma$	
2.0000	0.97725	$\xi + 2.0000 \sigma$	
2.2365	0.98734	$\xi + 2.2365 \sigma$	
2.3263	0.99000	$\xi + 2.3263 \sigma$	
2.5758	0.99500	$\xi + 2.5758 \sigma$	
3.0000	0.99865	$\xi + 3.0000 \sigma$	

where $X_1 = \xi - t\sigma$
and $X_2 = \xi + t\sigma$

$$f(X,Y) = \frac{1}{2\pi\sigma_x\sigma_y\sqrt{1-\rho^2}} \left[\exp \frac{-1}{2(1-\rho^2)} \left\{ \frac{(X-\bar{X})^2}{\sigma_x^2} - \frac{2\rho(X-\bar{X})(Y-\bar{Y})}{\sigma_x\sigma_y} + \frac{(Y-\bar{Y})^2}{\sigma_y^2} \right\} \right] -\infty \leq X \leq \infty \text{ and}$$

$$-\infty \leq Y \leq \infty , \quad (9)$$

where the five parameters are $\bar{x}, \bar{y}$, the component means; σ_x, σ_y , the component standard deviations; and ρ , the correlation coefficient between the two component variables, X and Y .

For many applications the interest is in determining the probability that a point $\{X, Y\}$ will fall within a contour of equal probability density. The exponential terms of equation (9), when set equal to a constant, λ^2 , give a family of ellipses depending on the value of the constant. The ellipses have a common center at the point $\{\bar{X}, \bar{Y}\}$. Integration of equation (9) over the region bounded by the contours of equal probability density gives

$$P(\lambda) = 1 - e^{\frac{-\lambda^2}{2(1-\rho^2)}} \quad (10)$$

Solving for λ^2 and replacing $P(\lambda)$ by p gives

$$\lambda^2 = -2(1-\rho^2) \ln(1-p) \quad (11)$$

Now define

$$\lambda_e = \sqrt{2} \sqrt{-\ln(1-p)} \quad (12)$$

For ready reference and comparisons, λ_e is shown in table C for selected values of p .

TABLE C. VALUES OF λ FOR BIVARIATE NORMAL
DISTRIBUTION ELLIPSES AND CIRCLES

P(%)	λ_e (ellipse)	λ_c (circle)	P(%)	λ_e (ellipse)	λ_c (circle)
0.000	0.0000	0.0000	65.000	1.4490	1.0246
5.000	0.3203	0.2265	68.268	1.5151	1.0713
10.000	0.4590	0.3246	70.000	1.5518	1.0973
15.000	0.5701	0.4031	75.000	1.6651	1.1774
20.000	0.6680	0.4723	80.000	1.7941	1.2686
25.000	0.7585	0.5363	85.000	1.9479	1.3774
30.000	0.8446	0.5972	86.466	2.0000	1.4142
35.000	0.9282	0.6563	90.000	2.1460	1.5175
39.347	1.0000	0.7071	95.000	2.4477	1.7308
40.000	1.0108	0.7147	95.450	2.4860	1.7579
45.000	1.0935	0.7732	98.000	2.7971	1.9778
50.000	1.1774	0.8325	98.168	2.8284	2.0000
54.406	1.2533	0.8862	98.889	3.0000	2.1213
55.000	1.2637	0.8936	99.000	3.0348	2.1460
60.000	1.3537	0.9572	99.730	3.4393	2.4320
63.212	1.4142	1.0000	99.9877	4.2426	3.0000
$\lambda_e = \sqrt{2} \sqrt{-\ln(1-P)}$ $\lambda_c = \sqrt{-\ln(1-P)}$					

The probability ellipse that contains p-percent of the wind vectors expressed in the most general form is the conic defined by

$$AX^2 + BXY + CY^2 + DX + EY + F = 0 \quad , \quad (13)$$

where

$$A = \sigma_y^2$$

$$B = -2\rho\sigma_x\sigma_y$$

$$C = \sigma_x^2$$

$$D = 2\sigma_x\sigma_y \rho\bar{Y} - 2\sigma_y^2\bar{X} = - (B\bar{Y} + 2A\bar{X})$$

$$E = 2\sigma_x\sigma_y \rho\bar{X} - 2\sigma_x^2\bar{Y} = - (B\bar{X} + 2C\bar{Y})$$

$$F = A\bar{X}^2 + C\bar{Y}^2 + B\bar{X}\bar{Y} - AC (1 - \rho^2) \lambda_e^2 \quad ,$$

and

$$\lambda_e = \sqrt{2} \sqrt{-\ln (1 - p)} \quad .$$

For graphical presentations, the range of the variable is important in order to arrange the scale. The largest and smallest values of X and Y for a given probability ellipse, p, are given by

$$X_{L,S} = \bar{X} \pm \sigma_x \lambda_e \quad (14)$$

$$Y_{L,S} = \bar{Y} \pm \sigma_y \lambda_e \quad , \quad (15)$$

where, as, before, $\lambda_e = \sqrt{2} \sqrt{-\ln (1 - p)}$.

Although there are several approaches to graphing the probability ellipses, the following procedure is advantageous for electronic computer plotting. In establishing the computer plotting program, the sample estimates for $\bar{X}, \bar{Y}, \sigma_x, \sigma_y$, and ρ are constants in equation (13). The user makes the choice of probability ellipses desired. Thus, p in equation (12) is programmed as a parameter. The largest and smallest values for X and Y are computed by equations (14) and (15) for the largest probability ellipse selected. This sets the graphical scale. Values of X within the range of "X smallest" to "X largest" are obtained by incrementing X between these limits. Using the quadratic equation, a solution for Y of equation (13) is made and plotted for each value of X . The centroid $(\bar{X}, \bar{Y})$ for the family of probability ellipses is plotted as a point. Labeling and other identification complete the plotting program.

For a given probability, equation (13) defines an ellipse that contains p -percent of the points X, Y . Since the entire area under the bivariate normal density function [equation (9)] is unity, upon integration for a given probability ellipse, that given ellipse contains p -percent of the total area. In the wind statistics, p -percent of the wind vectors fall within the specified probability ellipse. From this point of view, a specified probability ellipse gives the joint probability that p -percent of the U - V components lie within the given ellipse.

When $\sigma_x^2 = \sigma_y^2 = \sigma^2$ and $\rho = 0$ in the bivariate normal distribution, the probability ellipses of equation (13) reduce to circles whose centers are at the means $\bar{X}, \bar{Y}$. The radii of the probability circles are $\sigma_{V1} \lambda_c$, where

$$\sigma_{V1} = \sqrt{2\sigma^2} \quad (16)$$

and

$$\lambda_c = \sqrt{-\ln (1 - p)} \quad (17)$$

Values for λ_c for selected probabilities, p , are given in table C.

Because this function is simple, it can easily be graphed manually. However, the generalized plotting technique for electronic computer plotters, as represented by equation (13), can be advantageously used.

C.3. Derived Distributions for Wind Statistics

In this subsection the probability distribution functions and sets of equations are presented to derive certain probability distribution functions for wind statistics. These derived probability distributions are:

- 1) The conditional distribution of wind components
- 2) The generalized Rayleigh distribution for windspeed
- 3) The distribution for wind direction
- 4) The conditional distribution of windspeed given a wind direction (wind rose).

The required five statistical parameters for these derived distributions for wind statistics are given in table I.

C.3.1 The Conditional Distribution of Wind Components

Given that two random variables X and Y are bivariate normally distributed, the conditional distribution $f(Y|X)$ is read as $f(Y)$ given X , and likewise $f(X|Y)$ is read as $f(X)$ given Y . The conditional probability distribution function $F(Y|X)$ has the mean $E(Y|X)$ and variance $\sigma^2_{(Y|X)}$, where

$$E(Y|X^*) = \bar{Y} + \rho \left(\frac{\sigma_Y}{\sigma_X} \right) (X^* - \bar{X}) \quad (18)$$

and

$$\sigma^2_{(Y|X^*)} = \sigma_Y^2 (1 - \rho^2) \quad (19)$$

The conditional standard deviation is

$$\sigma_{(Y|X^*)} = \sigma_Y \sqrt{1 - \rho^2} \quad (20)$$

By interchanging the variables and parameters, the conditional distribution function for $F(X|Y^*)$ has the conditional mean

$$E(X|Y^*) = \bar{X} + \rho \left(\frac{\sigma_x}{\sigma_y} \right) (Y^* - \bar{Y}) \quad , \quad (21)$$

conditional variance

$$\sigma^2_{(x|y^*)} = \sigma_x^2 (1 - \rho^2) \quad , \quad (22)$$

and conditional standard deviation

$$\sigma_{(x|y^*)} = \sigma_x \sqrt{1 - \rho^2} \quad . \quad (23)$$

The preceding conditional probability distribution functions are univariate normal distributions for a (fixed) given value for one of the bivariate normal variables. Thus, the t-values given in table B are applicable for conditional probability statements. For example,

$$F(Y|X^*) = E(Y|X^*) + t\sigma_{(y|x^*)} \quad . \quad (24)$$

For $t = 1.6449$ there is a 95 percent chance that Y is less than or equal to $\bar{Y} + 1.6449 \sigma_{(y|x^*)}$ given that $X = X^*$. In symbols this statement reads

$$P \left\{ Y \leq E(Y|X^*) + 1.6449 \sigma_{(y|x^*)} \mid X = X^* \right\} = 0.9500 \quad . \quad (25)$$

Interval probability statements can also be made; namely,

$$P \left\{ Y_1 = E(Y|X^*) - t\sigma_{(y|x^*)} \leq Y \leq Y_2 = E(Y|X^*) + t\sigma_y \mid X = X^* \right\}$$

where X^* can take on any fixed value of X , but a convenient arrangement is to let $X^* = \bar{X} \pm t\sigma_x$.

The close connection of the regression function of Y on X to the conditional mean for the bivariate normal distribution is noted; namely,

$$Y = \bar{Y} + \rho \left(\frac{\sigma_Y}{\sigma_X} \right) (X - \bar{X}) \quad (26)$$

Similarly, the regression function of X on Y is

$$X = \bar{X} + \rho \left(\frac{\sigma_X}{\sigma_Y} \right) (Y - \bar{Y}) \quad (27)$$

These are linear functions and express the same results as would be obtained from a least-squares regression line.

C.3.2. The Generalized Rayleigh Distribution for Windspeed

If two random variables, X and Y, are bivariate normally distributed, then the probability distribution for the modulus, R, can be derived in terms of the five parameters that define the bivariate normal distribution.

$$R = \sqrt{X^2 + Y^2} \quad (28)$$

The distribution of R so derived is called a generalized Rayleigh distribution because there are no restrictions on the parameters. For applications to the RRA, the variable R is recognized as windspeed or the modulus of the wind vector.

The probability density function for R is expressed as

$$f(R) = a_0 R e^{-a_1 R^2} \left[I_0(a_2 R^2) I_0(a_3 R) + 2 \sum_{k=1}^{\infty} I_k(a_2 R^2) I_{2k}(a_3 R) \cos 2k\psi \right] R \geq 0 \quad (29)$$

The functions, $I_0(\cdot)$, $I_k(\cdot)$, and $I_{2k}(\cdot)$ are the modified Bessel functions of the first kind for zero order, kth order, and 2kth order. The coefficients are

$$a_0 = \exp \left[-\frac{1}{2} \left\{ \frac{\bar{X}^2}{\sigma_a^2} + \frac{\bar{Y}^2}{\sigma_b^2} \right\} \right] / \sigma_a \sigma_b ,$$

where σ_a^2 and σ_b^2 are the rotated variances to produce zero correlation between X and Y . σ_a and σ_b are the positive and negative roots¹ of the expression

$$\sigma_{(+,-)}^2 = \frac{1}{2} \left\{ \sigma_x^2 + \sigma_y^2 \pm \left[(\sigma_x^2 + \sigma_y^2)^2 - 4\sigma_x^2 \sigma_y^2 (1 - \rho^2) \right]^{1/2} \right\} ,$$

$$a_1 = (\sigma_x^2 + \sigma_y^2) / 4(1 - \rho^2) \sigma_x^2 \sigma_y^2 ,$$

$$a_2 = \frac{\left[(\sigma_x^2 - \sigma_y^2)^2 + 4\rho^2 \sigma_x^2 \sigma_y^2 \right]^{1/2}}{4(1 - \rho^2) \sigma_x^2 \sigma_y^2} ,$$

$$a_3 = \left[\left(\frac{\bar{X}}{\sigma_a^2} \right)^2 + \left(\frac{\bar{Y}}{\sigma_b^2} \right)^2 \right]^{1/2} ,$$

1. This computational form is obtained from the determinant

$$\begin{vmatrix} \sigma_x^2 - K & \sigma_x \sigma_y \rho \\ \sigma_x \sigma_y \rho & \sigma_y^2 - K \end{vmatrix} ,$$

where K is $\sigma_{(+,-)}^2$, and σ_a and σ_b are analogous to the standard deviation of the major and minor axes of the bivariate normal probability ellipse.

and

$$\tan \psi = \frac{\bar{Y}}{\bar{X}} \frac{\sigma_a^2}{\sigma_b^2} .$$

Since this density function cannot be integrated in closed form from zero to R , numerical integration is used to obtain practical results for the probability distribution function; i.e.,

$$F(R) = \int_0^R f(R) dR . \quad (30)$$

A number of special cases can be obtained from the general Rayleigh distribution [equation (29)], the simplest of which is to let $\sigma_x \equiv \sigma_y = \sigma$ and $\bar{X} = \bar{Y} = 0$ with independent variables X and Y . This gives

$$f(R) = \frac{R}{\sigma^2} e^{-R^2/2\sigma^2} , \quad (31)$$

which is recognized as the classical Rayleigh probability density function. The density function, equation (31), can be integrated in closed form over any range of the variable R . Hence, the probability distribution function, $F(R)$, for equation (31) is

$$F(R) = 1 - \exp \left\{ \frac{-R^2}{2\sigma^2} \right\} . \quad (32)$$

C.3.3. The Derived Distribution of Wind Direction

Considering the wind as a vector quantity and bivariate normally distributed, the wind direction can be derived. This is done by first writing the bivariate normal probability density function in polar coordinates whose variables are

$$g(r, \theta) = r d_1 e^{-\frac{1}{2} (a^2 r^2 - 2br + c^2)} , \quad (33)$$

(see footnote 2)

where

$$a^2 = \frac{1}{(1 - \rho^2)} \left[\frac{\sin^2 \theta}{\sigma_x^2} - \frac{2\rho \cos \theta \sin \theta}{\sigma_x \sigma_y} + \frac{\cos^2 \theta}{\sigma_y^2} \right] ,$$

$$b = \frac{-1}{(1 - \rho^2)} \left[\frac{\bar{x} \sin \theta}{\sigma_x^2} - \frac{\rho(\bar{x} \cos \theta + \bar{y} \sin \theta)}{\sigma_x \sigma_y} + \frac{\bar{y} \cos \theta}{\sigma_y^2} \right] ,$$

$$c^2 = \frac{1}{(1 - \rho^2)} \left[\frac{\bar{x}^2}{\sigma_x^2} - \frac{2\rho \bar{x} \bar{y}}{\sigma_x \sigma_y} + \frac{\bar{y}^2}{\sigma_y^2} \right] ,$$

$$d_1 = \frac{1}{2\pi \sigma_x \sigma_y \sqrt{1 - \rho^2}} ,$$

$r = \sqrt{x^2 + y^2}$ is the modulus of the vector or speed, and θ is the direction of the vector. After integrating $g(r, \theta)$ over $r = 0$ to ∞ , the probability density function of θ is

$$g(\theta) = \frac{d_1}{a^2} e^{-\frac{1}{2} c^2} \left[1 + \sqrt{2\pi} \left(\frac{b}{a} \right) e^{\frac{1}{2} \left(\frac{b}{a} \right)^2} \phi \left(\frac{b}{a} \right) \right] , \quad (34)$$

2. This expression, equation (33), in Smith (1976) is given with respect to the mathematical convention for a vector direction.

where a^2 , b , c^2 , and d_1 are as previously defined in equation (33) and

$$\Phi\left(\frac{b}{a}\right) = \Phi(x) = \frac{1}{\sqrt{2\pi}} \int_{-\infty}^x e^{-\frac{1}{2}t^2} dt$$

is taken from tables of normal distribution functions or made available through a computer subroutine.

If desired, equation (34) can be integrated numerically over a chosen range of θ to obtain the probability that the vector direction will lie within the chosen range; i.e.,

$$F(\theta) = \int_{\theta_2}^{\theta_1} g(\theta) d\theta \quad (35)$$

One application may be to obtain the probability that the wind will flow from a given quadrant or sector as, for example, onshore.

C.3.4. The Derived Conditional Distribution of Windspeed Given the Wind Direction (Wind Rose)

Continuing with the considerations in section C.3.3. of this chapter, the conditional probability density function (pdf) for windspeed, r , given a specified value for the wind direction, θ , can be expressed as

$$f(r|\theta) = \frac{a^2 r e^{-\frac{1}{2}(a^2 r^2 - br)}}{1 + \sqrt{2\pi} \left(\frac{b}{a}\right) e^{\frac{1}{2}\left(\frac{b}{a}\right)^2} \Phi\left\{\frac{b}{a}\right\}} \quad (36)$$

where the coefficients, a and b and the function $\Phi\left\{\frac{b}{a}\right\}$ are as previously defined in equation (33) and in equation (34).

From equation (36) the mode (most frequent value) of the conditional windspeed given a specified value of the wind direction is the positive solution of the quadratic equation,

$$a^2 r^2 - br - 1 = 0 \quad (37)$$

which is

$$(\tilde{r}|\theta) = \frac{1}{2a} \left[\left(\frac{b}{a} \right) + \sqrt{4 + \left(\frac{b}{a} \right)^2} \right] \quad (38)$$

The locus of the conditional modal values of windspeed when plotted in polar form versus the given wind directions forms an ellipse.

The noncentral moment for equation (36) is expressed as

$$\mu'_n = \int_0^{\infty} r^n f(r|\theta) dr \quad (39)$$

Now the first noncentral moment is identical to the first central moment or the expected value, $E(r|\theta)$. The integration of equation (39) for the first moment is sufficiently simple to yield practical computations and can be expressed as

$$E(r|\theta) = \frac{\left(\frac{b}{a} \right) + \left[1 + \left(\frac{b}{a} \right)^2 \right] \sqrt{2\pi} e^{\frac{1}{2} \left(\frac{b}{a} \right)^2} \phi \left\{ \frac{b}{a} \right\}}{a \left[1 + \left(\frac{b}{a} \right) \sqrt{2\pi} e^{\frac{1}{2} \left(\frac{b}{a} \right)^2} \phi \left\{ \frac{b}{a} \right\} \right]} \quad (40)$$

Hence, equation (40) gives the conditional mean value of the windspeed given a specified value for the wind direction.

The integration of equation (36) for the limits $r = 0$ to $r = r^*$ gives the probability that the conditional windspeed is $\leq r^*$ given a value for the wind direction, θ . This conditional probability distribution (PDF) can be written as

$$\Pr \left\{ r \leq r^* \mid \theta = \theta_0 \right\} = 1 - \left[\frac{e^{-\frac{1}{2} r_s^2} + \sqrt{2\pi} \left(\frac{b}{a} \right) \left\{ 1 - \phi(r_s) \right\}}{e^{-\frac{1}{2} \left(\frac{b}{a} \right)^2} + \sqrt{2\pi} \left(\frac{b}{a} \right) \phi \left\{ \frac{b}{a} \right\}} \right] \quad (41)$$

where

$$r_s = \left[a r^* - \left(\frac{b}{a} \right) \right]$$

By definition, equation (41) is an expression for a "wind rose." Empirical wind rose statistics are often tabulated or graphically illustrated giving the frequency that the windspeed is not exceeded for those windspeed values that lie within assigned class intervals of the wind direction. After evaluation of equation (41) for various values of windspeed, r^* , and the given wind directions, θ , interpolations can be performed to obtain various percentile values of the conditional windspeed.

For the special case when $\bar{b}$ in equation (33) equals zero (i.e., for $\bar{x} \equiv \bar{y} = 0$), the conditional modal values of windspeeds [equation (38)], the conditional mean values of windspeeds [equation (40)], and the fixed conditional percentile values of windspeeds [interpolated from evaluations of equation (41)], when plotted in polar form versus the given wind directions, produce a family of ellipses.

For the special case when $\bar{x} = \bar{y} = 0$, equation (36) reduces to the following simple case:

$$\Pr \left\{ r \leq r^* \mid \theta = \theta_0 \right\} = 1 - e^{-\frac{a^2 r^{*2}}{2}} \quad (42)$$

There is a special significance of equation (42) when related to the bivariate normal probability distribution. If r^* and θ are measured from the centroid of the probability ellipse, then the probability that $r \leq r^*$ is the same as the given probability ellipse. Further, solving equation (42) for r^* , gives

$$r^* = \frac{1}{a} \sqrt{-2 \ln (1 - P)} \quad (43)$$

If a probability ellipse P is chosen, equation (42) gives the distance of r along any θ from the centroid of the ellipse to the intercept of the specified probability ellipse. If there is an interest in conditional probability of winds for a given θ relative to the monthly means, equation (43) is applicable. If it is desired to find the magnitude of the wind along any θ relative to the monthly mean to the intercept of a given probability ellipse, equation (43) is applicable.

D. Statistical Parameters With Respect To Any Orthogonal Axes

The five wind statistical parameters presented in table I are given with respect to the standard meteorological coordinate system; i.e., these parameters are for the U and V components. For many aerospace vehicles and range applications, there is a need for wind statistics with respect to orthogonal axes other than west to east and south to north. For example, it may be required to present wind statistics with respect to a flight azimuth of an

aerospace vehicle whose flight azimuth is α degrees from true north measured in a clockwise direction. The following sets of equations are presented to compute the five parameters for the new coordinate axes rotated α degrees clockwise from true north.

a. Rotation of the means through α degrees:

$$\bar{X}_\alpha = \bar{X} \cos (90 - \alpha) + \bar{Y} \sin (90 - \alpha) \quad (44)$$

$$\bar{Y}_\alpha = \bar{Y} \cos (90 - \alpha) - \bar{X} \sin (90 - \alpha) \quad (45)$$

b. Rotation of the variances through α degrees:

$$\begin{aligned} \sigma_{x_\alpha}^2 &= \sigma_x^2 \cos^2 (90 - \alpha) + \sigma_y^2 \sin^2 (90 - \alpha) \\ &\quad + 2\rho\sigma_x\sigma_y \cos (90 - \alpha) \sin (90 - \alpha) \end{aligned} \quad (46)$$

$$\begin{aligned} \sigma_{y_\alpha}^2 &= \sigma_y^2 \cos^2 (90 - \alpha) + \sigma_x^2 \sin^2 (90 - \alpha) \\ &\quad - 2\rho\sigma_x\sigma_y \cos (90 - \alpha) \sin (90 - \alpha) \end{aligned} \quad (47)$$

c. Rotation of the linear correlation coefficient through α degrees:

$$\rho_\alpha = \frac{\text{cov} (X,Y)_\alpha}{\sigma_{x_\alpha}\sigma_{y_\alpha}} \quad (48)$$

where $\text{cov} (X,Y)_\alpha$ is the rotated covariance,

$$\begin{aligned} \text{cov} (X,Y)_\alpha &= \text{cov} (X,Y) [\cos^2 (90 - \alpha) - \sin^2 (90 - \alpha)] \\ &\quad + \cos (90 - \alpha) \sin (90 - \alpha) (\sigma_y^2 - \sigma_x^2) \end{aligned}$$

and

$$\text{cov}(X,Y) = \rho \sigma_x \sigma_y \quad .$$

By using these rotational equations, the bivariate normal distribution with respect to any desired rotated coordinates can be obtained from sample estimates that have been computed with respect to a specific axis. The marginal distributions after rotation are also normally (univariate) distributed. Using the rotational equations greatly reduces computational efforts for applications requiring statistics with respect to several coordinate axes.

Appendix A presents some illustrative examples for the wind statistics of the specific RRA.

CHAPTER III. STATISTICS OF THERMODYNAMICS QUANTITIES AND MODELS

A. General Considerations

A.1. Objectives

The objective inherent in developing the thermodynamic section of the RRA was to describe the thermodynamic characteristics of the atmosphere using a minimum of data tabulations. A set of parameters was selected which, together, thermodynamically describe the climatological state of the atmosphere. These parameters are the pressure, temperature, density, dewpoint, virtual temperature, and water vapor pressure. Used together, these parameters permit the calculation of a large number of derived quantities. (Symbols used in the calculations in this chapter are summarized in table D.) Some of these quantities, such as the speed of sound, are dealt with in section III.E.

The probability distribution of each of the six thermodynamic RRA parameters is described by its mean value, its standard deviation, and its skewness. Several of these parameters (temperature, pressure, dewpoint and density) have probability distributions that are close to a univariate normal distribution; the others do not. The skewness parameter gives an estimate of the asymmetrical departures of a probability distribution.

Hydrostatically modeled mean values of pressure and density were calculated (table IV), so that users may determine the departure of the actual climatological values of these parameters from hydrostatic conditions. This was done by hydrostatically integrating the pressure from the lowest RRA data level to the termination altitude of the particular RRA.

A.2. Data Quality Control

Data limits derived from the following parameters were used to screen the thermodynamic portion of the RRA data base: temperature, pressure, dewpoint (for the 0- to 30-km portion only), and density (for the 30- to 70-km portion only). These limits were set to plus and minus six standard deviations from the mean values of each of these quantities. These limits were used to screen the thermodynamic portion of the RRA data base, according to the procedures described in section I.C. The data base used to generate the thermodynamic portion of the RRA (tables I, II, and IV) was considered to be free from errors under the following conditions:

- a) The skewness values of the pressure and temperature were between -2.5 and 2.5 at all data levels.
- b) The skewness values of the density were between -3.5 and 3.5 at data levels between 0 and 30 km.
- c) The skewness values of the density were between -3.0 and 3.0 at data levels between 30 and 70 km.
- d) The skewness values of the dewpoint were between -2.5 and 2.5 at all data levels with more than 10 data values.



TABLE D. LIST OF SYMBOLS USED IN CHAPTER III

C_s	- Speed of sound
C_d	- Collision diameter
E	- Vapor pressure
g_ϕ	- Gravity at latitude ϕ
H	- Geopotential height
H_m	- Geopotential height at a mandatory radiosonde data level
H_s	- Geopotential height at a significant radiosonde data level
K_t	- Coefficient of thermal conductivity
L	- Mean free path length
M	- Mean molecular weight of air at sea level
$M3Q$	- Annual or monthly third moment of quantity Q
n	- Refractive modulus
N	- Refractive index
NA	- Avogadro's constant
N_Q	- Number of values of quantity Q
P	- Pressure
P_m	- Pressure at a mandatory radiosonde data level
P_s	- Pressure at a significant radiosonde data level
P_h	- Hydrostatically integrated mean monthly or annual pressure
Q	- Any tabulated RRA quantity
R^*	- Universal gas constant
R'	- Specific gas constant of dry air
r', r^*	- Parameters used in converting z to h and vice versa

TABLE D. (concluded)

S	- Sutherland's constant, used in the calculation of dynamic viscosity
T	- Temperature
T_d	- Dew point
T_v	- Virtual temperature
T_{vm}	- Virtual temperature at a mandatory radiosonde data level
T_{vs}	- Virtual temperature at a significant radiosonde data level
V	- Mean air particle speed
V_c	- Mean collision frequency
w	- Parameter used in the hydrostatic interpolation of pressure and density
Z	- Geometric altitude
λ	- Wavelength
α_Q	- Skewness of quantity Q
β	- Constant used in the equation for viscosity
γ	- Ratio of specific heat at constant pressure to specific heat at constant volume
η	- Kinematic coefficient of viscosity
μ	- Dynamic coefficient of viscosity
ρ	- Density
ρ_h	- Mean monthly or annual density derived from pressure height
σ	- Standard deviation of the quantity Q

A.3 Limitation of Thermodynamic Statistics

The correlation coefficients between the thermodynamic quantities and the moisture-related quantities were not calculated at discrete altitudes, nor were any of the correlations between altitudes. Therefore, valid statistical dispersion models that require the relationship between two or more of these quantities at the same altitude or between altitudes cannot be derived. Approximations for the correlation coefficients between pressure, virtual temperature, and density at discrete altitudes may be obtained from the coefficients of variation as developed by Buell (1970). The coefficient of variation is the standard deviation divided by the mean. The mean values and the standard deviations are taken from table II. A model for the profile of monthly and annual mean pressure, virtual temperature, and density that is in excellent agreement with the respective statistical mean values is given by table IV. This agreement results because the physical relationships, given by the hydrostatic equation and the equation of state, were used to derive table IV. When only the monthly or annual mean values for pressure, virtual temperature, and density are required, it is recommended that table IV be used.

B. Establishing Data Samples at the Required Altitude Levels

This section describes the computational procedures used to establish data samples of the thermodynamic RRA parameters at the RRA data levels. References are cited only when an equation given is one of many available in the literature or when an equation is stated in an unusual form.

B.1. Conversion of Data Recorded in Geopotential Heights to Geometric Altitude

The upper-air rocketsonde observations used to obtain the table values above 30 km were recorded in terms of geometric altitude and can be interpolated directly to the altitude intervals shown in the tables. However, the radiosonde observations used to obtain the tabular values below 30 km were recorded in terms of geopotential heights. The change of coordinates from geopotential heights to geometric altitudes (h to z) is accomplished by calculating a table of geopotential heights that correspond exactly to the geometric altitudes at which the atmospheric parameters are tabulated. The radiosonde observations are then interpolated to these geopotential heights. The relationship used to calculate geometric altitude from geopotential height is

$$H = (r'z)/(r^*z) \quad , \quad (49)$$

where

$$r' = gr^*/9.80665$$

and

$$r^* = -2g_\phi / (\partial g_\phi / \partial z_0) \quad .$$

g_ϕ is the sea-level gravity at the latitude ϕ corresponding to the proper location. This value is given by (List, 1968)

$$g_\phi = 9.780356 (1 + 5.2885 \times 10^{-3} \sin^2 \phi - 5.9 \times 10^{-6} \sin^2 (2\phi)). \quad (50)$$

$\frac{\partial g_\phi}{\partial z_0}$ is the rate of change of gravity at the sea level. This quantity is given

by the equation

$$\frac{\partial g_\phi}{\partial z_0} = -3.085462 \times 10^{-6} + 2.27 \times 10^{-9} \cos (2\phi) - 2 \times 10^{-12} \cos (4\phi). \quad (51)$$

The units used for gravity are meters per square second, while the units for $\frac{\partial g_\phi}{\partial z_0}$ are per square second.

The resulting table of values of H obtained by using even increments of 2 in equation (49) is shown in table IV of the RRA. The values of H above 30 km are not used in the interpolation of original data, but are included for the convenience of the user.

B.2. Calculations on the Original Rawinsonde Data Records

It was necessary to interpolate the information from the original rawinsonde data records to the geometric altitudes specified as the RRA data levels. The parameters for which this interpolation was required were the temperature, dewpoint, and pressure. The other parameters were calculated from the interpolated values at each RRA data level. These "derived" parameters were the water vapor pressure, density, and virtual temperature.

B.2.1. Calculation of the Geopotential Height at Significant Levels

Two somewhat different interpolation procedures were used to obtain data from radiosonde and rocketsonde observations at the levels shown in the tables. The procedure used to interpolate radiosonde observations began with the calculation of virtual temperature at each data level in a sounding. The virtual temperature was computed by

$$T_v = T / (1 - 0.379 (e/p)) \quad (52)$$

where T_v and T are in degrees Kelvin and e and p are in millibars.

The radiosonde soundings contain a mix of data taken at "mandatory" and "significant" levels. Pressure, temperature, and dewpoint information was given in these soundings at both types of levels. However, geopotential height information was only given at the mandatory levels. The heights at the significant levels were "filled in" (calculated) hydrostatically using pressure and temperature data from these levels. This procedure permitted the use of most of the significant level data in the calculation of the RRA tables. The equation used for this process was

$$H_s = H_m + 29.2712617 \frac{(T_{vs} - T_{vm})}{2} \ln(P_s/P_m) , \quad (53)$$

where the subscripts s and m denote quantities at significant and mandatory levels. This equation was not used if the difference between two adjacent mandatory levels was greater than 200 mb. All soundings with such data gaps were rejected for use in compiling the RRA.

B.2.2. Temperature

Radiosonde temperatures were interpolated logarithmically with respect to pressure using the equation

$$T = T_U + (T_L - T_U) \frac{\ln p - \ln p_L}{\ln p_U - \ln p_L} , \quad (54)$$

where the subscripts U and L indicate values at the nearest data levels in the actual sounding above and below the interpolated level.

B.2.3. Pressure

The pressure values in each radiosonde sounding were interpolated to the RRA data levels using the equation

$$p = p_L \exp\left(\frac{H_L - H_U}{29.2712617 (0.5) (T_{vU} + T_{vL})}\right) \quad (55)$$

where the subscript L indicates virtual temperature, geopotential height, and pressure values at the data level below and closest to the level at which data were required.

B.2.4. Dewpoint Temperature

Dewpoint values were interpolated logarithmically with respect to pressure using the equation

$$T_d = T_{dU} + (T_{dL} - T_{dU}) \left(\frac{\ln p - \ln p_L}{\ln p_U - \ln p_L} \right) . \quad (56)$$

The subscripts U and L indicate data at the nearest upper and lower data levels in a sounding.

B.2.5. Derived Water Vapor Pressure

The water vapor pressure was calculated from the interpolated dewpoint values at the RRA data levels using Tetten's approximation:

$$e = 6.11 \text{ mb} \times 10^{7.5(T_d - 273.15)/(T_d - 35.86)} \quad (57)$$

B.2.6. Derived Density

The density values derived from radiosonde observations were calculated at the RRA data levels using the equation

$$\rho = 348.36787 p/T_v \quad (58)$$

B.2.7. Derived Virtual Temperature

The virtual temperature values were calculated at the RRA data levels for each sounding using the equation

$$T_v = T/(1 - 0.379(e/p)) \quad (59)$$

where T_v and T are in degrees Kelvin, and p and e are the pressure and vapor pressure, respectively, in millibars.

B.3. Calculations on the Original Rocketsonde Data Records

The rocketsonde data records used to calculate the RRA table values above 30 km were given in terms of geometric altitude. For this reason, slightly different calculations were required to convert the recorded data values to values at the RRA data levels. The pressure, temperature, and density were all interpolated to the RRA data levels; moisture-related parameters (virtual temperature, water vapor pressure, and dewpoint) were not calculated, since atmospheric moisture at altitudes above 30 km was considered to be negligible.

No interpolation was done across gaps in the pressure or temperature data within a sounding larger than 7,000 m. Data values at the RRA levels within such a gap were set to missing.

B.3.1. Temperature

Rocketsonde temperatures were interpolated linearly with respect to geometric altitude using the equation

$$T = T_U + (T_L - T_U) \frac{Z - Z_L}{Z_U - Z_L}, \quad (60)$$

where the subscripts U and L indicate values at the nearest data level in the actual sounding above and below the interpolated level.

B.3.2. Pressure

The pressure values in each rocketsonde sounding were interpolated to the RRA data levels using the equation

$$P = P_L \exp \left(- \frac{g_\phi}{R^*} \frac{M(Z - Z_L)}{\bar{T}_v} \cdot W^2 \right), \quad (61)$$

where $\bar{T}_v = \frac{T_{vU} + T_{vL}}{2}$ and $W = \frac{r^*}{\left(r^* + Z + \frac{Z - Z_L}{2} \right)}$.

B.3.3. Density

Rocketsonde density values were interpolated using the equation

$$\rho = \rho_L \exp \left(- \frac{g_\phi M}{R^*} \frac{(Z - Z_L)}{\bar{T}_v} \cdot W^2 \right), \quad (62)$$

where W is specified in section III.B.3.2.

C. Computation of Statistical Parameters for Tables II and III

A three-step procedure was used for computing the monthly and annual means, standard deviations, and skewness values from the data values at the RRA data levels. Initially, certain statistical sums were calculated and stored as the soundings in the data base were processed. These sums were then used to calculate the monthly statistics given in the RRA tables. The annual statistics were then calculated from these stored sums and the monthly statistics.

C.1. Stored Statistical Sums

The sums calculated were

$$\sum Q, \sum Q^2, \text{ and } \sum Q^3 ,$$

where Q is any one of the quantities given in the thermodynamic part of the RRA.

C.2. Calculation of the Monthly Statistics

C.2.1. Monthly Means

The mean monthly values of the thermodynamic RRA quantities were calculated using the equation

$$\bar{Q} = \sum Q / N_Q ,$$

where N_Q is the number of observed values of the quantity Q for a given month.

C.2.2. Monthly Standard Deviations

The monthly standard deviations of the thermodynamic RRA quantities were calculated using the equation

$$\sigma_Q = \sqrt{\frac{(N_Q \sum Q^2) - (\sum Q)^2}{N_Q \cdot (N_Q - 1)}} . \quad (63)$$

C.2.3. Monthly Skewness Values

The monthly skewness values of the windspeed and of the thermodynamic RRA quantities were calculated using the equation

$$\alpha_Q = \frac{M_{3Q}}{\sigma_Q^3} ,$$

where M_{3Q} is the third moment of the quantity Q, σ_Q is its standard deviation, and

$$M_{3Q} = \left[\frac{\sum Q^3}{N_Q} - \frac{3 \sum Q \sum Q^2}{N_Q^2} - \frac{2 \sum Q^3}{N_Q^3} \right] \cdot \frac{N_Q^2}{(N_Q - 1)(N_Q - 2)} . \quad (64)$$

C.3. Calculation of the Annual Statistics

Equations (63) and (64), used to calculate the monthly values of the standard deviations and skewness values, involve taking the differences between two pairs of large sums containing Q^2 and Q^3 , where Q is the thermodynamic RRA quantity. Using these equations to compute the annual statistics would have resulted in a substantial loss of precision, as these sums become larger by several orders of magnitude in such a case. This problem was avoided by calculating the annual means, standard deviations, and skewness values from the monthly statistics.

C.3.1 Annual Mean Values

The annual mean values of the thermodynamic RRA quantities were calculated using the equation

$$Q_{ANN} = Q_A / N_Q ,$$

where Q_A is the total of all observed values of Q and N_Q is the total number of observations of Q .

C.3.2. Annual Standard Deviations

The annual standard deviations of the thermodynamic RRA quantities were calculated using the equation

$$\sigma_{Q_{ANN}} = \sqrt{\frac{1}{N_Q} \sum_{i=1}^{12} (N_{Qi} \sigma_{Qi}^2) + \frac{1}{N_Q} \sum_{i=1}^{12} (N_{Qi} \bar{Q}_i^2) - Q_{ANN}^2} , \quad (65)$$

where N_{Qi} = the number of data values for Q in month i ($i = 1$ to 12), Q_i = the monthly mean of Q , and σ_{Qi} = the standard deviation of quantity Q in month i .

C.3.3. Annual Skewness Values

The annual skewness values of the thermodynamic RRA quantities were calculated using the equation

$$\begin{aligned}
M_{3Q_{ANN}} = & \frac{1}{N} \sum_{i=1}^{12} (N_{Q_i} M_{3Q_i}) + \frac{3}{N Q_{ANN}} \sum_{i=1}^{12} (N_{Q_i} \bar{Q}_i \sigma_{Q_i}^2) \\
& + \frac{1}{N Q_{ANN}} \sum_{i=1}^{12} (N_{Q_i} Q_i^3) - \frac{3 \bar{Q}_{ANN}}{N Q_{ANN}} \sum_{i=1}^{12} (N_{Q_i} Q_i^2) \\
& - \frac{3 \bar{Q}_{ANN}}{N Q_{ANN}} \sum_{i=1}^{12} (N_{Q_i} \sigma_{Q_i}^2) + 2 \bar{Q}_{ANN}^3, \quad (66)
\end{aligned}$$

where M_{3Q_i} = the third moment about the mean of quantity Q in month i and $M_{3Q_{ANN}}$ = the annual third moment about the mean of the quantity Q .

D. Derived Monthly Mean and Annual Mean Model Atmospheres

A set of modeled monthly mean and annual mean hydrostatic values of pressure and density was calculated from the lowest RRA data level (0 km, mean sea level) upwards to 30 km, and from 30 km upwards to 70 km. The integration from 0 to 30 km was computed independently of the integration from 30 to 70 km because of the difference in data sources. The two different values for 30 km are provided for comparison. When 30-km data are required, the values given in the 0- to 30-km table should be used. These hydrostatically modeled mean values, which are given in table IV, are useful as a check on the validity of the pressure and density values given in table II. In most cases, the values in tables II and IV for any given data level are within 1 percent of each other. The hydrostatic pressure values in table IV were calculated using the equation

$$p_1 = p_0 \exp \left(- \frac{0.034162 (H_1 - H_0)}{0.5 (T_{v_1} + T_{v_0})} \right), \quad (67)$$

where $H_1 - H_0$ is in meters and a "0" subscript refers to values at the RRA data level immediately below the level being checked. p_0 at the lowest data level is set equal to the RRA mean pressure; p_1 , calculated for the next highest data level, is taken as p_0 for the level above that. This process is repeated for all the other RRA data levels. The hydrostatic density corresponding to the hydrostatic pressures is calculated from these pressures and the RRA virtual temperature values using the formula

$$\rho_H = 348.36786 P_H / T_v, \quad (68)$$

where ρ_H and P_H are the hydrostatic density and pressure shown in table IV of the RRA.

E. Thermodynamic Quantities Derivable from the Basic Tables

Several other quantities can be calculated from the statistics listed in tables I and II. Primary physical constants used in these calculations are listed in table E. The equations given in this section can be used to calculate the approximate mean values of these quantities at each RRA data level. It is not possible to infer or derive any information concerning the standard deviation or skewness values of these quantities from the data in tables II and III of the RRA.

E.1. Mean Air Particle Speed

The mean air particle speed, V , is the arithmetic average of the speeds of all air particles in the volume element being considered. For a valid average to occur, there must be a sufficient number of particles involved to represent mean conditions. The equation for V for dry air is

$$V = \sqrt{\frac{8}{\pi} \cdot \frac{R \cdot T}{M}} \quad (69)$$

A computational form for dry air, using tabulated values, is

$$V = \sqrt{7.3094 \times 10^2 \times T} \text{ (meters per second)} \quad (70)$$

where T is the temperature in degrees Kelvin from table II. Equation (69), when corrected for moist air, becomes

$$V = \sqrt{\frac{8}{\pi} \cdot R' \cdot T_v} \quad (71)$$

The computational form for moist air is

$$V = \sqrt{7.3094 \cdot 10^2 \cdot T_v} \text{ (meters per second)} \quad (72)$$

where T_v is the virtual temperature in degrees Kelvin from table III.

TABLE E. LIST OF PRIMARY PHYSICAL CONSTANTS

P_o	= standard atmospheric pressure at sea level = 1.013250×10^5 Newton/m ² = 2116.22 lb/ft ²
ρ_o	= standard atmospheric density at sea level = 1.2250 kg/m ³ = 0.076474 lb/ft ³
T_o	= standard temperature at sea level = 288.15 K = 15.0°C = 59.0°F
g_o	= standard gravity at sea level at latitude 45°32'33" = 9.80665 m/s ²
s	= Sutherland's constant used in calculation of dynamic viscosity = 110.4 K
T_i	= ice-point temperature at P_o = 273.15 K
β	= constant used in calculation of dynamic viscosity = 1.458×10^{-6} kg/s m K ^{1/2} = 7.3025×10^{-7} lb/s ft R ^{1/2}
γ	= ratio of specific heat of air at constant pressure to specific heat of air at constant volume = 1.4
C_D	= mean effective collision diameter of air molecules = 3.65×10^{-10} m = 1.1975×10^{-9} ft
N_a	= Avogadro's constant = 6.022169×10^{26} /kg mol = 2.73179×10^{26} /lb mol
R^*	= gas constant = 8.31432 J/mol K
R'	= gas constant for dry air = 2.8704×10^2 J/kg K
M	= molecular weight of dry air = 28.966 g/mol

E.2 Mean Free Path

The mean free path, L , is the mean value of the distance traveled by each neutral air particle in a selected air parcel, between successive collisions with other particles in that parcel. A meaningful average requires that the selected parcel be large enough to contain a substantial number of particles. The equation for L is given by

$$L = \left(\frac{\sqrt{2}}{2\pi} \right) \left(\frac{R^*T}{N_a C_d^2 P} \right) , \quad (73)$$

where C_d is the effective collision diameter of the mean air molecules. The 1976 standard atmosphere value of 3.65×10^{-10} is valid for the range of altitudes in the RRA.

A computational form for moist air, using tabulated values, is

$$L = 2.335 \times 10^{-7} \frac{T}{P} \text{ (meters)} , \quad (74)$$

where T is the temperature in degrees Kelvin from table II and P is the pressure in millibars from table II.

A form of (73) to correct L for moist air is

$$L = \left(\frac{\sqrt{2}}{2\pi} \right) \frac{R^*MT_v}{N_a C_d^2} . \quad (75)$$

The computational form for moist air is

$$L = 2.3325 \times 10^{-7} \frac{T_v}{P} \text{ (meters)} , \quad (76)$$

where T_v is the virtual temperature in degrees Kelvin from table III and P is the pressure in millibars from table II.

E.3. Mean Collision Frequency

The mean collision frequency, V_c , is considered to be the average speed of air particles contained in an air parcel, divided by the mean free path of the particles inside that parcel. Computationally this is equivalent to

$$V_c = \frac{V}{L} \text{ (sec}^{-1}\text{)} \quad (77)$$

To determine V_c for dry air, use V and L from equations (70) and (74).
To determine V_c for moist air, use V and L from equations (72) and (76).

E.4. Speed of Sound

The expression for the speed of sound, C_s , in meters per second in dry air, is

$$C_s = \sqrt{\frac{\gamma R T}{M}} \quad (78)$$

To compute C_s for dry air from tabulated values, use

$$C_s = \sqrt{4.0185 \times 10^2 \times T} \text{ (meters per second)} \quad (79)$$

where T is the temperature in degrees Kelvin from table II. One form for the speed of sound in moist air is

$$C_s \approx \sqrt{\gamma R' T_v} \quad (80)$$

where T_v is the virtual temperature from table III. A computational form for moist air is

$$C_s \approx \sqrt{4.0185 \times 10^2 T_v} \text{ (meters per second)} \quad (81)$$

E.5. Dynamic Coefficient of Viscosity

The coefficient of dynamic viscosity, μ , is defined as a coefficient of internal friction developed where gas regions move adjacent to each other at different velocities. The following expression is taken from the U.S. Standard Atmosphere (1976):

$$\mu = \frac{\beta \cdot T^{3/2}}{T + S} \quad (82)$$

The computational form is

$$\mu = \frac{(1.458 \times 10^{-6}) T^{3/2}}{T + 110.4} \quad \left(\begin{array}{l} \text{kilograms per second} \\ \text{per meter} \end{array} \right), \quad (83)$$

where T is the temperature in degrees Kelvin from table II.

E.6. Kinematic Coefficient of Viscosity

The kinematic coefficient of viscosity, designated as η , is defined to be the ratio of the dynamic coefficient of viscosity of a gas to its density, or

$$\eta = \mu / \rho \quad (84)$$

The computational form is

$$\eta = 1.0 \times 10^3 \mu / \rho \quad \left(\begin{array}{l} \text{square meters} \\ \text{per second} \end{array} \right), \quad (85)$$

where μ is the dynamic coefficient of viscosity from equation (83) and ρ is the density in grams per cubic meter from table II.

E.7. Coefficient of Thermal Conductivity

The empirical expression used for the coefficient of thermal conductivity, designated as K_t , is given in the 1976 Standard Atmosphere as

$$K_t = \frac{2.65019 \times 10^{-3} \cdot T^{3/2}}{T + 245.4 \times 10^{-(12/T)}} \quad \left(\begin{array}{l} \text{watts per meter} \\ \text{per degree Kelvin} \end{array} \right), \quad (86)$$

where T is in degrees Kelvin.

E.8. Refractive Modulus and Refractive Index

The refractive modulus or refractivity (Selby and McClatchey, 1975; Smith and Weintraub, 1953) is defined as N, where

$$N = (n - 1) \cdot 10^6 \quad (87)$$

and n is the refractive index.

For microwave frequencies below approximately 30 GHz (equivalent to wavelengths above 1 cm), N , the refractive modulus, is given by the empirical equation

$$N = 77.6 \frac{P}{T_d} + 3.73 \times 10^5 \frac{e}{T^2} \text{ (dimensionless)}, \quad (88)$$

where E and P are in millibars and T and T_d are in degrees Kelvin.

The following expression is valid for the visible and infrared wavelengths shorter than approximately 30 μm (0.03 mm).

$$N = 77.6 \frac{P}{T} + 0.584 \frac{P}{T\lambda} \text{ (dimensionless)}, \quad (89)$$

where λ is the wavelength in microns and T is in degrees Kelvin.

The expression for N for the wavelength from 0.03 mm to 1 cm is an extremely complex function of wavelength.

CHAPTER IV. CONCLUSIONS AND RECOMMENDATIONS

Conclusions

This document satisfies the technical objectives established for the RRAC by the RCC MG. Upper air statistics and models for wind and thermodynamic quantities for the specific site have been derived in a consistent and uniform manner, which will be used in publications for all other assigned site locations. These RRAs represent an improvement over the previously published RRAs because of the availability of more extensive upper air data bases and the adaptation of more advanced statistical techniques. A statistical measure of central tendency (mean values) and a measure of dispersion (standard deviation with respect to the mean values) for monthly and annual reference periods have been tabulated for all variables in a consistent manner from data bases that have been edited and quality-controlled in the same manner. Further, a statistical measure for symmetry (skewness coefficient that involves the third statistical moment) has been tabulated for all variables except the U and V wind components. Even with these improvements, the user of these RRAs must recognize certain limitations of the statistical tabulations:

- 1) The wind profile structure with respect to altitude cannot be modeled from the RRA statistics because the interlevel and crosslevel correlations were not computed.

- 2) The profile structure with respect to altitude for any of the thermodynamic variables or any quantities derivable from these variables cannot be modeled because the prerequisite correlations were not computed. However, the profiles of monthly and annual means for pressure, virtual temperature, and density are in agreement (table IV) with the hydrostatic equation and the equation of state.

The preceding limitations are cited to prevent a misuse of the RRAs. More extensive statistical tabulations were beyond the scope of this committee's task. As greater insight is gained through usage of these RRAs, many adaptations of the statistical tabulations for specific engineering and scientific applications are envisioned.

Recommendations

It is recommended that the wind and thermodynamic statistical tabulations and attendant models contained in the RRAs be used as a standard reference source, as may be appropriate, by the ranges and range users. It is further recommended that the respective Range Staff Meteorologist or responsible agency staff member be consulted for the applicability of the RRAs for specific engineering applications.

REFERENCES

Buell, Eugene C.: "Statistical Relations in a Perfect Gas." Journal of Applied Meteorology, 9, 1970, pp. 729-731.

List, R. J., Editor: Acceleration of Gravity, Smithsonian Meteorological Tables, Sixth Ed. Smithsonian Institution, Washington, D.C., 1968, pp. 488.

Selby, J.E.A.; and McClatchey, R.A.: AFCRL-TR-75-0255, Atmospheric Transmittance from 0.25 to 28.5 μ m - Computer Code Lowtran 3, Air Force Cambridge Research Laboratories. Available through the National Technical Information Service, Washington, D.C., 1975.

Smith, E.K.; and Weintraub, S.: "The Constants in the Equation for Atmospheric Refractive Index at Radio Frequencies," Proceedings of the Institute of Radio Engineers, 41, 8, August 1953, pp. 1035-1037.

Smith, O.E.: NASA TM X-73319, Vector Wind and Vector Wind Shear Models at 0-27 km Altitude for Cape Kennedy, Florida, and Vandenberg AFB, California. Prepared under sponsorship of the National Aeronautics and Space Administration. Available through the National Technical Information Service, Washington, D.C., July 1976.

U.S. Standard Atmosphere, 1976. Prepared under the sponsorship of the National Aeronautics and Space Administration, United States Air Force, and United States Weather Bureau. Available through U.S. Government Printing Office, Washington, D.C., October 1976.

PREVIOUS RANGE REFERENCE ATMOSPHERES PUBLISHED BY IRIG

Atlantic Missile Range Reference Atmosphere for Cape Kennedy, Florida (Part I), Document 104-63, April 16, 1963. (AD451780)

White Sands Missile Range Reference Atmosphere (Part I), Document 104-63, June 28, 1964. (AD451781)

Fort Churchill Missile Range Reference Atmosphere for Fort Churchill, Manitoba, Canada (Part I), Document 104-63, August 7, 1964. (AD634727)

Pacific Missile Range Reference Atmosphere for Eniwetok, Marshall Islands (Part I), Document 104-63, September 1, 1964. (AD479264)

Fort Greely Missile Range Reference Atmosphere (Part I), Document 104-63, October 6, 1964. (AD634726)

Eglin Gulf Test Range Atmosphere for Eglin AFB, Florida (Part I), Document 104-63, January 25, 1965. (AD472601)

Pacific Missile Range Atmosphere for Point Arguello, California (Part I), Document 104-63, April 1965. (AD472602)

Wallops Island Test Range Reference Atmosphere (Part I), Document 104-63, July 10, 1965. (AD474071)

Eastern Test Range Reference Atmosphere for Ascension Island, South Atlantic (Part I), Document 104-63, July 1966. (AD645591)

Johnston Island Test Site Reference Atmosphere (Part I), Document 104-63, January 1970. (AD782652)

Lihue, Kauai, Hawaii Reference Atmosphere (Part I), Document 104-63, January 1970. (AD782653).

Cape Kennedy, Florida Reference Atmosphere (Part II), Document 104-63, September 1971. (AD751581)

White Sands Missile Range Reference Atmosphere (Part II), Document 104-63, September 1971. (AD782654)

Wallops Island Test Range Reference Atmosphere (Part II), Document 104-63, September 1971. (ADA040280)

Fort Greely Missile Range Reference Atmosphere (Part II), Document 104-63, September 1971. (ADA040281)

Edwards Air Force Base Reference Atmosphere (Part I), Document 104-63, September 1972. (AD782651)

Kwajalein Missile Range Reference Atmosphere for Kwajalein, Marshall Islands (Part I), Document 104-63, October 1974. (ADA002664)

Pacific Missile Test Center Reference Atmosphere for Point Arguello, California (Part II), Document 104-63, November 1975. (ADA040279)

REVISED RANGE REFERENCE ATMOSPHERES PUBLISHED BY THE RCC

Kwajalein Missile Range, Kwajalein, Marshall Islands, Range Reference Atmosphere, 0-70 Km Altitude, Document 360-82, December 1982. (AD123424)

Cape Canaveral, Florida, Range Reference Atmosphere, 0-70 Km Altitude, Document 361-83, February 1983. (ADA125553)

Vandenberg Air Force Base, California, Range Reference Atmosphere, 0-70 Km Altitude, Document 362-83, April 1983.

Dugway, Utah, Range Reference Atmosphere, 0-30 Km Altitude, Document 363-83, June 1983.

Wallops Island, Virginia, Range Reference Atmosphere, 0-70 Km Altitude, Document 364-83, July 1983.

White Sands Missile Range, New Mexico, Range Reference Atmosphere, 0-70 Km Altitude, Document 365-83, August 1983.

Edwards AFB, California, Range Reference Atmosphere, 0-70 Km Altitude, Document 366-83, August 1983.


Eglin AFB, Florida, Range Reference Atmosphere, 0-30 Km Altitude, Document 367-83, September 1983.

Taguac, Guam Island, Range Reference Atmosphere, 0-30 Km Altitude, Document 368-83, September 1983.

Point Mugu, California, Range Reference Atmosphere, 0-70 Km Altitude, Document 369-83, September 1983.

In addition to the documents above and the present RRA for Barking Sands, Hawaii, the revised series will include an RRA for the following location:

Ascension Island, South Atlantic



CONVERSION UNITS

Physical Constants and Conversion Factors

Numerical values in this document are given in the International System of Units (SI, *Système International d'Unités*). The values in parentheses are equivalent U.S. Customary Units, which are English units adapted for use by the United States of America. The SI and U.S. Customary Units provided in table F are those normally used for measuring and reporting atmospheric data.

By definition, the following fundamental conversion factors are exact:

<u>Type</u>	<u>U.S. Customary Units</u>	<u>Metric</u>
Length	1 U.S. yard (yd)	0.9144 meter (m)
Mass	1 avoirdupois pound (lb)	453.59237 gram (g)
Time	1 second (s)	1 second (s)
Temperature	1 degree Rankine (°R)	9/5 degree Kelvin (K)

To aid in the conversion of units, conversion factors based on the above fundamental conversion factors are given in table F.

TABLE F. FACTORS FOR CONVERSION UNITS

U. S. CUSTOMARY							
METRIC		CONVERSION					
Type of Data	Unit	Abbreviation	Unit	Abbreviation	Multiply	By	To Get
TEMPERATURE	degree Celsius	C	degree Fahrenheit	F	$F - 32$	0.5556	C
	degree Kelvin	K	degree Rankine	R	R	1.8*	F
					$^{\circ}R$	1.00*	F + 459.67
					$^{\circ}R - 459.67$	1.00*	F
					K	1.00*	C + 273.15
Temperature Change	degree Celsius	C	degree Fahrenheit	F	K - 273.15	1.00*	C
	degree Kelvin	K	degree Rankine	R	F or K	1.8*	temp. change F or R
					R	0.5556	temp. change C or F
DENSITY	gram per cubic meter	$g\ m^{-3}$	gram per cubic foot	gr ft ⁻³		0.43700	gr ft ⁻³
	gram per cubic centimeter	$g\ cm^{-3}$				2.2883	$g\ m^{-3}$
						10^{-6} *	$g\ cm^{-3}$
						4.370×10^{-5}	gr ft ⁻³
						2.288×10^{-6}	$g\ cm^{-3}$
WIND	meter per second	$m\ s^{-1}$	mile per hour	mph	$m\ s^{-1}$	2.2369	mph
			knots	knots	$m\ s^{-1}$	0.44704*	$m\ s^{-1}$
			feet per second	$ft\ s^{-1}$	$m\ s^{-1}$	1.0936	knots
					knots	0.51444	$m\ s^{-1}$
					mph	0.868976	knots
DISTANCE	meter	m	feet	ft	m	3.2808	ft
	micron	μ	inch	in.	m	0.3048*	in.
	Angstrom unit	$\text{\AA}$			m	2.54×10^{-4} *	μ
					m	2.54×10^{-8} *	$\text{\AA}$
					m	10^{-6} *	μ
				m	10^{-10} *	$\text{\AA}$	

* Defined exact conversion factor

TABLE F. (continued)

Type of Data	METRIC					U. S. CUSTOMARY					CONVERSION	
	Unit	Abbreviation	Unit	Abbreviation	Multiply	By	To Get					
DISTANCE (Continued)												
MASS												
Weight	gram	g	gram	g			kg					
	kilogram	kg	pound	lb			lb					
							g					
							oz					
							g					
PRESSURE												
Atmospheric	newton per square meter	newton m ⁻²	pound force per square inch	lb in. ⁻²			lb					
	millimeter of Mercury	mmHg	inch of Mercury	in. Hg			in					
	bar	bar					bar					
	millibar	mb					mb					
	dyne per square centimeter (microbar)	dyne cm ⁻²					dyne cm ⁻²					
	kilogram force per square meter	kg m ⁻²					kg m ⁻²					

defined as: conversion factor

TABLE I-1. WIND STATISTICAL PARAMETERS

JANUARY

STATION - 911620 BARKING SANDS, HI									
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS	NOBS
KM	M/S	M/S		M/S	M/S	M/S	M/S		
.005	-1.48	1.84	-.1367	-.14	3.07	2.67	2.44	1.29	339.
1.000	.31	4.60	.0999	.80	5.55	6.00	4.08	.81	337.
2.000	1.88	7.30	.2296	.84	5.29	7.78	4.98	.90	337.
3.000	4.59	8.42	.2866	.49	5.64	9.15	6.34	1.29	337.
4.000	6.97	9.44	.2794	-.43	6.62	11.46	7.07	1.06	337.
5.000	9.76	10.20	.2039	-1.60	7.65	14.03	7.96	.63	337.
6.000	12.19	11.25	.2232	-2.13	9.19	16.74	9.14	.52	335.
7.000	14.73	12.08	.2037	-3.38	11.06	19.83	10.03	.56	333.
8.000	18.10	13.59	.1855	-5.54	13.04	24.28	11.09	.50	331.
9.000	21.91	15.21	.2489	-7.63	14.87	29.04	12.10	.31	331.
10.000	25.29	16.18	.3418	-9.10	16.19	33.05	12.36	.10	326.
11.000	28.00	16.88	.4116	-10.40	17.01	36.08	12.77	.07	319.
12.000	29.62	17.41	.4202	-11.09	16.39	37.30	13.37	.47	319.
13.000	29.66	16.77	.4146	-10.33	14.84	35.21	13.25	.48	318.
14.000	27.27	15.12	.3578	-9.52	12.62	32.72	12.29	.36	315.
15.000	23.26	13.30	.3478	-7.79	10.92	28.00	10.63	.17	314.
16.000	18.17	11.19	.3098	-5.80	9.10	22.00	9.36	.26	308.
17.000	12.39	9.44	.2140	-4.17	7.16	15.67	8.11	.43	308.
18.000	6.60	7.67	.1512	-2.34	5.45	10.12	5.92	.93	307.
19.000	1.72	5.55	.1317	-1.34	3.83	6.11	3.59	.65	303.
20.000	-1.01	4.42	.1235	-1.08	2.88	4.71	2.79	.81	293.
21.000	-2.28	4.57	.1464	-1.05	2.49	4.96	2.97	.80	283.
22.000	-2.79	5.11	.0479	-.83	2.74	5.56	3.34	.76	287.
23.000	-3.04	5.44	.0999	-.65	2.43	5.80	3.38	.70	278.
24.000	-3.02	6.49	.0954	-.39	2.84	6.54	4.07	1.08	263.
25.000	-2.81	7.36	.0606	.25	2.82	7.00	4.57	1.23	258.
26.000	-1.46	7.76	.2390	.74	3.09	7.11	4.65	1.63	228.
27.000	.75	8.10	.3701	.96	3.51	7.44	4.87	1.12	193.
28.000	2.98	9.64	.3573	1.20	3.96	8.81	6.40	1.14	180.
29.000	5.76	11.29	.4301	1.09	4.03	10.39	8.35	.91	118.
30.000	8.70	12.41	.4313	.52	4.39	12.57	9.52	.82	105.
32.000	7.12	13.19	.3429	-.30	4.89	13.31	8.41	.82	126.
34.000	7.63	14.40	.2056	-.25	6.22	14.94	8.98	1.04	126.
36.000	5.77	15.03	.3855	-.77	6.23	14.77	8.88	.88	126.
38.000	4.59	16.30	.4875	.03	6.65	15.28	9.80	.92	126.
40.000	2.59	16.22	.3903	1.40	7.94	15.54	9.50	1.09	126.
42.000	2.17	16.12	.3940	2.80	8.54	15.72	9.81	1.30	126.
44.000	1.50	17.09	.3416	2.75	9.52	17.73	10.17	.82	126.
46.000	1.91	21.20	.2026	4.32	13.11	22.34	11.87	.79	126.
48.000	2.91	24.45	.0453	9.57	13.74	26.54	13.35	.81	125.
50.000	5.97	25.11	.0579	7.50	10.90	25.25	14.11	.72	123.
52.000	12.17	26.06	.1031	5.08	11.24	27.11	15.48	.77	119.
54.000	21.81	27.02	.1656	4.52	13.44	32.84	17.97	.58	116.
56.000	32.21	28.84	.1653	6.80	14.90	40.65	21.92	.37	111.
58.000	43.36	29.06	.3762	8.76	16.66	49.71	25.30	.07	93.
60.000	52.01	24.89	.3074	7.77	16.00	55.46	21.19	-.51	67.
62.000	52.93	22.72	.3845	3.94	12.69	54.97	21.59	-.39	40.
64.000	62.61	19.14	.2581	1.48	14.81	64.61	17.95	-.40	23.
66.000	61.92	22.22	.1934	-4.32	16.43	64.74	20.25	-.47	23.
68.000	61.00	25.44	.1327	-10.47	15.42	64.65	22.80	-.39	23.
70.000	58.89	27.37	-.0213	-8.80	15.24	62.55	24.41	-.39	20.

TABLE I-2. WIND STATISTICAL PARAMETERS

FEBRUARY

STATION = 911620		BARKING SANDS, HI								NOBS
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS		
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	-.66	1.75	-.1134	-.23	2.44	2.22	2.15	1.47	342.	
1.000	-.92	4.21	.2134	.79	4.47	5.06	3.67	1.40	342.	
2.000	-.14	6.76	.3046	.97	4.42	6.83	4.32	1.06	342.	
3.000	2.27	7.73	.3535	.48	4.85	7.73	5.37	1.46	342.	
4.000	4.97	8.96	.2295	-.07	5.64	9.65	6.60	1.20	342.	
5.000	7.91	9.78	.1667	-1.32	6.79	11.39	7.90	1.08	342.	
6.000	10.94	10.30	.0810	-2.30	7.81	14.66	8.78	.77	342.	
7.000	13.96	11.05	.0613	-3.52	9.21	17.97	9.55	.47	340.	
8.000	17.07	12.00	.0819	-4.65	11.40	21.82	10.51	.38	337.	
9.000	20.67	13.23	.1078	-5.51	13.34	26.03	11.52	.22	336.	
10.000	24.49	13.89	.2129	-6.07	14.68	30.05	11.90	.04	329.	
11.000	27.63	14.47	.2964	-6.77	15.77	33.50	12.01	.06	324.	
12.000	29.47	15.07	.3276	-7.71	15.17	35.09	12.36	.23	324.	
13.000	29.72	14.52	.3647	-8.39	14.03	34.82	12.15	.43	323.	
14.000	27.57	13.89	.3951	-8.25	12.18	32.21	11.45	.54	322.	
15.000	24.26	12.95	.3329	-7.03	9.74	28.09	10.53	.67	320.	
16.000	19.18	10.66	.2134	-5.38	7.60	22.12	8.89	.63	317.	
17.000	13.31	8.30	.1931	-3.59	6.25	15.80	6.93	.59	314.	
18.000	7.83	7.25	.2094	-1.98	5.00	10.43	5.82	1.48	311.	
19.000	3.16	5.67	.1293	-1.39	3.69	6.42	4.05	1.29	306.	
20.000	.57	4.83	.0929	-1.37	2.62	4.94	2.80	1.14	301.	
21.000	-.80	4.64	.1456	-1.28	2.44	4.74	2.69	.69	299.	
22.000	-1.73	5.00	.0572	-1.20	2.52	5.24	2.86	.65	295.	
23.000	-2.32	4.85	.1328	-.85	2.26	5.03	3.06	.96	270.	
24.000	-2.46	5.38	.0455	-.43	2.83	5.64	3.36	.99	257.	
25.000	-1.93	6.23	.0612	.07	2.81	6.01	3.77	1.14	253.	
26.000	-.58	6.80	.0622	.30	2.65	6.23	3.84	.87	225.	
27.000	1.42	7.46	.1542	.77	2.82	6.96	4.20	.88	194.	
28.000	3.59	8.26	.2903	1.30	3.13	8.04	5.25	.91	182.	
29.000	6.76	9.04	.1548	1.40	3.42	9.64	6.90	.67	118.	
30.000	9.38	10.64	.0048	1.26	3.57	11.93	8.53	.50	100.	
32.000	11.70	10.44	.1085	-.79	4.94	14.44	7.87	.28	141.	
34.000	10.07	11.16	.0849	-.02	5.74	13.70	6.40	.82	141.	
36.000	7.25	13.32	.3778	-.80	6.38	13.39	9.54	1.30	141.	
38.000	3.28	15.64	.3963	-1.10	7.30	13.89	10.74	1.58	141.	
40.000	.84	18.08	.3034	1.72	8.32	16.43	11.31	1.44	141.	
42.000	1.13	19.40	.3309	4.89	7.85	18.34	11.85	1.33	142.	
44.000	3.41	21.50	.4608	6.11	8.53	20.18	13.68	1.49	142.	
46.000	7.55	22.59	.5966	7.25	10.56	22.44	15.00	1.17	142.	
48.000	12.37	22.81	.2995	5.88	9.64	23.73	15.32	1.06	142.	
50.000	18.30	23.78	.1524	4.74	8.99	26.77	16.86	1.00	141.	
52.000	26.12	23.22	.0921	6.18	10.94	32.81	17.32	.96	138.	
54.000	33.26	22.77	.1085	6.77	11.96	38.16	18.85	.53	133.	
56.000	38.13	22.57	.1682	8.91	11.36	42.61	18.82	.36	119.	
58.000	45.26	18.84	.1180	10.72	11.42	48.25	17.87	-.35	104.	
60.000	51.33	19.30	.1419	9.78	12.77	54.60	16.79	-.51	90.	
62.000	56.04	19.59	.1394	8.33	14.66	59.10	17.77	-.50	42.	
64.000	57.24	21.28	.2304	1.57	17.26	59.55	21.77	-.34	23.	
66.000	56.40	23.92	.4320	-9.14	19.28	61.52	20.11	-.09	27.	
68.000	52.50	23.14	.3404	-13.57	17.06	57.96	19.79	-.12	27.	
70.000	48.02	20.02	-.0031	-12.56	20.16	52.30	18.17	-.32	27.	

TABLE I-3. WIND STATISTICAL PARAMETERS

MARCH

STATION - 911620		BARKING SANDS, HI								
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS	NOBS	
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	-0.67	1.25	-.0193	-.49	2.35	1.91	2.04	1.85	387.	
1.000	-2.10	3.69	.0399	.19	3.49	4.62	2.98	1.14	397.	
2.000	-2.16	6.18	.1414	.82	3.77	6.49	3.93	.89	387.	
3.000	-.25	6.53	.2243	-.17	4.14	6.49	4.21	1.62	387.	
4.000	1.38	7.27	.2644	-.56	4.61	7.18	4.96	1.43	387.	
5.000	3.41	7.93	.2070	-1.26	5.36	8.50	5.69	1.35	397.	
6.000	5.76	8.40	.2416	-1.95	6.44	10.44	6.31	.95	386.	
7.000	8.44	9.45	.2425	-2.61	7.65	13.14	7.29	.74	386.	
8.000	11.43	10.64	.2732	-3.21	9.40	16.34	8.68	.71	386.	
9.000	15.01	12.13	.3211	-4.41	11.83	20.60	10.34	.48	377.	
10.000	19.01	13.34	.3285	-5.99	14.78	25.64	11.63	.15	370.	
11.000	23.04	14.65	.3659	-7.48	16.80	30.41	12.57	.18	363.	
12.000	26.65	15.67	.4154	-8.21	18.97	33.71	13.21	.23	363.	
13.000	26.96	15.57	.4581	-8.65	15.12	33.36	12.62	.30	361.	
14.000	24.80	13.80	.3913	-8.33	12.73	30.14	11.31	.30	357.	
15.000	21.06	11.88	.3197	-7.25	10.21	25.41	9.77	.47	350.	
16.000	16.47	9.43	.2446	-5.94	8.07	19.97	7.65	.45	346.	
17.000	11.51	7.64	.1826	-4.29	6.44	14.42	6.55	.46	352.	
18.000	6.62	6.33	.0303	-3.02	5.15	9.60	5.23	.75	349.	
19.000	2.71	4.81	.1734	-2.08	3.58	5.88	3.60	1.42	342.	
20.000	.08	4.21	.2115	-1.36	2.60	4.39	2.64	1.16	335.	
21.000	-1.20	4.13	.1254	-.99	2.34	4.22	2.66	1.65	329.	
22.000	-1.76	4.28	.0399	-1.03	2.70	4.59	2.96	1.81	323.	
23.000	-2.34	4.29	.0262	-.83	2.42	4.57	3.07	2.24	300.	
24.000	-2.93	5.15	.0204	-.56	2.89	5.44	3.76	1.78	264.	
25.000	-2.98	5.53	.1269	-.09	2.83	5.85	3.64	1.13	276.	
26.000	-2.53	6.27	.1655	.63	2.75	6.21	3.87	1.13	246.	
27.000	-1.55	7.64	.1776	1.43	2.96	7.25	4.34	1.12	205.	
28.000	-.01	9.11	.1568	1.74	3.18	8.43	4.96	.98	197.	
29.000	1.84	10.32	.2054	2.18	3.56	9.73	5.64	.59	110.	
30.000	2.99	10.96	.3136	2.22	3.38	10.35	6.10	.49	99.	
32.000	8.67	10.79	-.0250	.17	4.74	12.99	6.67	.37	126.	
34.000	6.48	10.80	-.0277	.05	5.59	12.25	6.24	.70	126.	
36.000	3.75	10.29	.0992	1.54	5.37	10.79	5.82	1.29	126.	
38.000	2.00	11.15	.0177	1.48	5.76	11.13	6.23	1.08	126.	
40.000	2.71	12.10	.0970	1.60	6.81	12.42	6.87	.93	126.	
42.000	6.21	13.31	.2230	3.94	7.41	14.80	8.11	1.06	126.	
44.000	11.88	15.09	.2410	5.34	7.93	18.86	10.17	.82	125.	
46.000	18.26	16.10	.2778	5.97	8.50	23.40	12.30	.50	124.	
48.000	24.41	17.18	.2128	5.39	8.23	28.05	14.13	.71	123.	
50.000	28.60	17.53	.1535	4.90	8.44	31.89	14.19	.76	122.	
52.000	33.18	17.10	.3383	6.10	8.74	35.77	15.05	.42	121.	
54.000	36.14	18.00	.4158	6.61	8.00	38.51	15.93	.19	117.	
56.000	38.58	19.87	.2649	7.40	8.12	41.50	16.73	.11	112.	
58.000	40.14	20.95	.0318	10.29	10.08	44.16	17.48	-.10	90.	
60.000	42.78	19.81	-.1257	9.78	9.69	46.37	16.02	-.36	65.	
62.000	49.61	17.79	-.0550	6.86	9.39	51.18	17.05	-.66	34.	
64.000	54.58	17.24	.0073	-.31	9.72	55.64	16.43	-.47	25.	
66.000	47.72	19.10	.0704	-2.68	14.18	50.68	16.38	-.39	22.	
68.000	35.30	20.36	.0279	-5.30	12.93	39.76	16.12	-.08	21.	
70.000	19.52	23.76	-.1271	-7.06	9.93	28.00	17.09	.65	21.	

TABLE I-4. WIND STATISTICAL PARAMETERS

APRIL

STATION = 911620	BARKING SANDS, MI								NOBS
Z KM	MEAN U M/S	S.D. U M/S	RIU, V1	MEAN V M/S	S.D. V M/S	MEAN WS M/S	S.D. WS M/S	SKEW WS	
.005	-1.33	1.35	-.0051	-.49	2.10	1.77	1.86	1.95	330.
1.000	-2.44	2.86	.0159	.19	2.48	3.79	2.43	1.03	388.
2.000	-3.42	4.84	.0303	.52	3.01	5.53	3.56	.98	387.
3.000	-1.96	5.03	.1155	-.24	3.16	5.37	3.21	.94	387.
4.000	-.55	5.67	.1559	-.60	3.74	5.74	3.71	1.16	387.
5.000	1.26	6.33	.0948	-.97	4.50	6.68	4.36	1.07	397.
6.000	3.21	7.19	.0978	-1.54	4.97	8.12	4.80	1.00	385.
7.000	5.21	8.20	.0227	-1.89	5.44	9.77	5.65	.70	353.
8.000	7.83	9.24	.1555	-2.18	6.40	12.12	6.74	.60	365.
9.000	11.11	10.60	.2293	-2.50	7.71	15.30	8.19	.64	384.
10.000	15.34	12.43	.2288	-2.71	9.09	19.34	10.25	.64	380.
11.000	20.61	14.64	.1366	-2.88	10.47	24.37	12.76	.50	379.
12.000	26.10	15.86	.2346	-3.07	11.02	29.38	14.15	.26	377.
13.000	29.46	15.12	.2233	-3.26	10.59	32.14	13.62	.21	373.
14.000	27.33	12.52	.2646	-3.49	8.65	29.52	11.05	.20	372.
15.000	22.81	10.33	.2438	-3.36	7.50	24.67	9.10	.18	372.
16.000	17.04	7.95	.2450	-2.83	5.93	18.64	6.90	.12	370.
17.000	11.47	6.41	.1411	-2.34	4.58	12.98	5.55	.50	368.
18.000	5.97	4.81	.1489	-1.57	3.71	7.71	4.00	.86	364.
19.000	2.12	3.93	.1754	-.85	2.90	4.69	2.65	1.10	360.
20.000	-.52	3.59	.2534	-.10	2.27	3.61	2.29	.75	353.
21.000	-2.50	3.62	.1675	-.08	1.92	4.18	2.36	.59	346.
22.000	-3.91	3.80	.0496	-.43	1.99	5.04	2.91	.74	345.
23.000	-5.07	3.92	-.0305	-.44	1.74	5.75	3.35	.65	372.
24.000	-6.03	4.55	-.0393	-.25	2.28	6.83	3.95	.55	326.
25.000	-6.42	4.81	.0029	.16	2.47	7.35	4.06	.52	316.
26.000	-6.25	5.27	.1035	.33	2.19	7.31	4.27	.57	285.
27.000	-5.71	6.27	.0682	.64	2.65	7.68	4.49	.79	221.
28.000	-5.01	7.31	.0377	.84	2.71	7.89	4.91	.77	211.
29.000	-4.07	8.26	.0903	.96	2.97	8.13	5.29	.92	126.
30.000	-3.83	8.88	.1107	.88	3.12	8.67	5.32	.82	106.
32.000	-2.13	9.76	-.1363	.28	4.62	8.92	6.00	1.21	149.
34.000	-3.60	10.06	-.2239	-.43	4.26	9.70	6.15	1.02	147.
36.000	-4.47	9.77	-.1376	.74	4.89	10.08	6.16	.81	147.
38.000	-3.73	9.63	.1082	.45	4.85	9.85	5.74	.85	147.
40.000	-3.29	11.36	.0715	.03	4.91	10.99	6.51	1.03	147.
42.000	-2.98	11.80	.1693	.89	5.32	11.64	6.40	.88	147.
44.000	-2.54	12.73	.2501	2.65	5.75	12.70	6.81	.67	147.
46.000	-.20	13.32	.2234	5.44	5.30	13.40	7.39	.89	144.
48.000	3.05	13.83	.1699	6.64	6.74	14.73	8.81	1.12	142.
50.000	6.13	14.18	.1463	5.39	6.59	14.46	10.06	1.18	140.
52.000	6.52	14.50	.1456	4.40	8.10	15.25	10.19	1.10	141.
54.000	5.57	15.21	.1418	5.85	7.90	16.14	9.85	1.03	139.
56.000	6.24	17.11	.1501	8.49	8.74	18.59	11.52	.87	122.
58.000	10.21	16.82	.0675	9.92	9.12	20.60	11.92	.98	105.
60.000	11.33	17.61	.2217	7.59	8.75	20.57	12.10	.56	77.
62.000	11.85	18.22	.0865	-.48	13.12	22.35	11.71	.43	45.
64.000	8.38	18.97	.4091	-3.90	10.04	19.79	11.97	.63	28.
66.000	-.45	19.49	-.0887	-9.02	13.14	23.04	9.22	.64	26.
68.000	-11.06	18.98	-.0149	-14.18	14.96	27.08	12.54	.59	25.
70.000	-22.46	19.53	-.2982	-11.52	14.20	33.13	10.08	.58	23.

TABLE I-5. WIND STATISTICAL PARAMETERS

MAY

STATION = 911620		BARKING SANDS, HI								
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS		
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	-1.10	1.29	-.1653	-.23	2.02	1.64	1.77	1.89	359.	
1.000	-2.29	2.43	-.1155	.47	2.27	3.28	2.40	1.15	367.	
2.000	-3.24	4.26	.1064	.50	2.69	5.09	3.19	.72	367.	
3.000	-2.01	4.71	.2570	.08	3.35	5.36	2.94	.99	367.	
4.000	-.60	5.47	.2725	-.19	3.54	5.65	3.29	.81	367.	
5.000	.80	6.20	.2778	-.57	4.06	6.40	3.85	1.07	367.	
6.000	2.07	6.86	.3365	-.87	4.80	7.37	4.56	1.06	367.	
7.000	3.57	7.88	.3386	-1.28	5.49	8.76	5.46	.92	367.	
8.000	5.34	8.95	.3763	-1.77	6.44	10.58	6.41	.83	365.	
9.000	7.64	10.61	.4089	-2.05	7.52	13.13	7.69	.82	365.	
10.000	10.28	12.72	.4017	-2.34	8.69	15.09	9.44	.85	363.	
11.000	13.63	15.35	.3958	-2.51	9.83	19.71	11.64	1.02	362.	
12.000	17.69	17.18	.4300	-2.40	10.42	23.11	13.71	.77	361.	
13.000	20.64	17.53	.4298	-2.50	10.04	25.14	14.41	.66	359.	
14.000	20.96	15.68	.3466	-2.54	8.67	24.23	13.39	.72	358.	
15.000	17.38	12.39	.3259	-2.19	7.21	19.99	10.60	.72	357.	
16.000	12.21	9.08	.3290	-1.28	5.65	14.26	7.84	.74	352.	
17.000	7.20	6.68	.2539	-.49	4.20	9.08	5.63	.87	349.	
18.000	2.65	5.08	.1579	.09	3.29	5.49	3.67	1.42	348.	
19.000	-1.37	4.10	.1444	.49	2.41	4.33	2.44	.71	345.	
20.000	-4.63	3.63	.1235	.31	1.98	5.57	2.76	.45	337.	
21.000	-7.11	3.77	.1064	.29	1.97	7.63	3.23	.28	326.	
22.000	-8.70	3.88	.0580	.27	1.84	9.02	3.57	.12	324.	
23.000	-10.10	3.88	-.0285	.10	1.73	10.31	3.71	-.16	310.	
24.000	-11.14	4.09	.0050	-.10	2.27	11.42	3.94	-.20	304.	
25.000	-11.87	4.48	.0674	.18	2.08	12.12	4.30	-.12	281.	
26.000	-12.16	4.78	-.0591	.31	2.16	12.43	4.59	-.11	252.	
27.000	-12.05	5.40	-.1250	.25	2.62	12.45	5.11	.11	203.	
28.000	-11.98	5.71	-.0131	.57	2.42	12.42	5.27	.04	194.	
29.000	-11.53	6.77	.1699	.17	3.13	12.44	5.79	.11	123.	
30.000	-11.29	7.50	.1537	.09	2.55	12.33	6.17	.17	104.	
32.000	-11.13	8.03	-.0181	.90	3.26	12.75	6.09	.72	150.	
34.000	-12.05	7.72	-.2158	.42	3.55	13.30	6.37	.56	150.	
36.000	-12.47	7.53	-.1239	.96	3.64	13.59	6.46	.41	150.	
38.000	-12.80	7.30	.0249	.54	4.31	14.01	6.31	.10	150.	
40.000	-15.06	7.85	.1793	.31	4.68	16.72	6.85	.24	150.	
42.000	-18.38	8.18	-.0465	.47	5.00	19.43	7.23	.16	153.	
44.000	-21.76	8.44	-.0500	3.63	4.97	22.82	7.85	.05	152.	
46.000	-22.89	9.16	.0287	6.29	4.92	24.59	8.16	-.07	151.	
48.000	-21.78	9.77	.0390	8.87	5.82	23.95	8.78	-.13	149.	
50.000	-21.76	10.78	.0521	7.12	5.63	24.21	9.26	.12	144.	
52.000	-23.45	11.38	-.1039	6.92	6.22	25.77	10.05	-.09	137.	
54.000	-25.65	11.72	-.0053	5.38	7.39	27.71	10.52	-.10	129.	
56.000	-26.49	13.26	.0982	7.09	8.22	29.25	11.78	.07	118.	
58.000	-25.57	14.13	.0206	8.60	8.24	29.46	11.21	.01	99.	
60.000	-24.13	14.34	-.1903	7.50	9.13	28.54	10.51	.29	74.	
62.000	-25.00	15.29	-.1335	4.27	13.01	29.73	12.53	.16	45.	
64.000	-25.70	15.04	.1140	-4.43	8.35	28.78	11.97	.03	32.	
66.000	-28.18	11.11	-.0889	-5.60	11.55	31.22	10.12	.70	32.	
68.000	-29.27	13.14	.0829	-8.27	15.40	34.59	11.36	.28	32.	
70.000	-38.25	17.24	.1674	-14.16	15.09	43.80	16.15	-.28	30.	

TABLE I-6. WIND STATISTICAL PARAMETERS

JUNE

STATION - 911620		BARKING SANDS, HI								NOBS
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS		
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	.04	1.26	-.0708	-.23	1.38	1.41	1.25	1.89	372.	
1.000	-2.36	2.37	-.0638	.21	1.42	3.08	1.94	.90	372.	
2.000	-5.01	4.23	-.0501	.01	2.43	6.15	3.34	.44	372.	
3.000	-4.16	4.46	.1113	-.48	3.01	6.04	3.15	.39	372.	
4.000	-3.09	5.13	.1147	-.39	3.61	6.16	3.31	.53	372.	
5.000	-1.87	5.61	.1029	-.17	4.23	6.43	3.40	.50	372.	
6.000	-.52	6.09	.1342	-.17	4.65	6.78	3.65	.71	372.	
7.000	.72	6.94	.1986	-.19	5.91	7.66	4.66	.71	372.	
8.000	2.07	8.24	.2503	-.10	7.04	9.60	5.41	.71	371.	
9.000	3.47	10.01	.2992	-.21	8.09	11.71	6.36	.64	370.	
10.000	5.53	12.19	.3802	-.21	9.39	14.23	8.02	.73	370.	
11.000	7.87	14.62	.3973	-.10	10.37	16.93	9.79	.69	369.	
12.000	10.17	16.43	.4040	-.12	11.06	19.10	11.40	.68	369.	
13.000	11.80	17.14	.4035	-.21	10.73	19.87	12.35	.71	369.	
14.000	11.49	15.12	.3505	-.25	9.27	17.71	11.51	.98	368.	
15.000	8.65	11.56	.3465	.19	6.85	13.35	8.77	1.04	366.	
16.000	4.62	7.97	.2156	.18	4.87	8.66	5.77	1.38	365.	
17.000	.01	5.34	.0820	.14	3.17	5.29	3.25	1.72	362.	
18.000	-4.44	4.23	-.0011	.31	2.65	5.95	3.04	.32	357.	
19.000	-8.08	3.59	.0692	.26	1.90	8.48	3.16	.02	351.	
20.000	-10.81	3.43	.1001	.31	1.59	10.95	3.37	-.13	342.	
21.000	-13.18	3.48	.0352	.09	1.94	13.33	3.45	-.15	336.	
22.000	-14.78	3.47	.0119	.18	1.93	14.93	3.36	-.12	333.	
23.000	-16.31	3.30	.0804	.08	1.88	16.42	3.23	-.19	320.	
24.000	-17.57	3.79	.0792	-.04	2.18	17.71	3.78	-.12	319.	
25.000	-18.59	3.83	-.0099	.15	2.18	18.72	3.83	-.17	298.	
26.000	-19.24	3.87	-.0249	.08	2.14	19.35	3.87	-.11	265.	
27.000	-19.64	4.06	.1044	-.05	2.78	19.83	4.05	-.15	207.	
28.000	-19.69	4.19	.0234	-.02	2.21	19.82	4.18	.12	191.	
29.000	-20.12	4.59	.0493	.19	2.80	20.32	4.56	.15	115.	
30.000	-21.13	4.87	-.0500	.18	1.90	21.22	4.85	.12	101.	
32.000	-21.28	5.54	-.0827	.95	2.72	21.48	5.51	-.04	134.	
34.000	-22.13	5.36	.1334	1.01	3.44	22.43	5.31	-.25	134.	
36.000	-23.95	5.82	.0533	.44	3.44	24.22	5.71	-.26	134.	
38.000	-27.18	5.92	-.0219	.66	3.67	27.44	5.89	-.19	133.	
40.000	-30.89	5.90	.0729	.32	4.09	31.15	5.94	-.08	133.	
42.000	-35.62	7.57	.0549	.91	4.44	35.62	7.54	-.09	131.	
44.000	-39.46	7.48	-.2330	3.22	5.34	39.94	7.54	-.07	132.	
46.000	-41.05	7.75	.0326	4.86	5.36	41.70	7.64	-.03	128.	
48.000	-41.34	8.14	.0772	5.93	5.71	42.15	8.09	.06	124.	
50.000	-42.72	9.60	.0789	5.13	5.92	43.48	9.38	.08	122.	
52.000	-44.79	9.48	-.0007	5.51	6.87	45.68	9.31	.23	121.	
54.000	-45.12	10.47	-.0141	6.80	8.13	46.39	10.24	-.24	115.	
56.000	-43.93	12.66	-.0817	8.30	9.61	45.87	12.13	-.17	104.	
58.000	-41.42	12.49	-.0719	8.63	9.67	43.54	11.93	-.18	87.	
60.000	-40.29	12.76	-.0157	8.75	9.70	42.40	12.55	-.32	60.	
62.000	-37.04	14.55	.1951	6.41	10.96	39.38	13.79	-.10	37.	
64.000	-29.45	16.36	.2530	.88	14.19	33.39	14.53	-.24	23.	
66.000	-25.87	16.13	.2731	-9.38	12.76	30.30	15.96	.00	23.	
68.000	-30.90	19.25	.4628	-18.15	13.84	38.10	19.67	-.33	22.	
70.000	-33.06	22.02	.2545	-12.35	15.68	39.32	20.55	.38	22.	

TABLE I-7. WIND STATISTICAL PARAMETERS

JULY

STATION • 911620		BARKING SANDS, HI							
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS	NOBS
KM	M/S	M/S		M/S	M/S	M/S	M/S		
.005	-.02	1.20	-.1029	-.10	1.18	1.22	1.16	1.38	340.
1.000	-2.83	2.13	.1220	-.06	1.32	3.27	1.94	.57	340.
2.000	-5.70	3.71	.1189	-.06	2.24	6.34	3.32	.45	340.
3.000	-4.69	3.83	.1718	-.27	2.94	5.88	3.27	.64	340.
4.000	-3.57	4.29	.2759	-.22	3.39	5.67	3.23	.68	338.
5.000	-1.94	5.07	.2574	.06	4.84	5.65	3.65	1.00	338.
6.000	.37	5.59	.1761	.29	4.77	6.40	3.63	.76	338.
7.000	2.35	6.33	.1593	.66	5.38	7.63	4.07	.65	337.
8.000	4.57	7.34	.1765	1.00	6.14	9.47	4.86	.63	337.
9.000	7.34	8.67	.1913	1.28	6.84	11.83	6.11	.61	335.
10.000	10.33	10.16	.2208	1.81	7.92	14.73	7.67	.49	335.
11.000	13.37	11.84	.2322	2.29	9.33	17.93	9.45	.35	332.
12.000	16.38	12.99	.2010	2.61	10.32	20.86	10.72	.19	331.
13.000	17.89	13.52	.1240	2.70	10.37	22.11	11.34	.19	327.
14.000	15.95	12.70	.1152	3.07	8.60	19.63	10.66	.34	325.
15.000	10.21	9.19	.0341	2.67	6.30	13.41	7.45	.52	325.
16.000	2.97	5.98	.0016	1.97	4.20	7.08	3.98	.75	324.
17.000	-3.58	3.84	-.0661	1.16	2.85	5.40	2.79	.64	320.
18.000	-8.84	3.08	-.0522	.73	2.30	9.18	3.03	.05	318.
19.000	-12.43	2.69	-.0176	.34	1.95	12.59	2.70	.09	315.
20.000	-15.53	2.75	.0061	.32	1.88	15.65	2.75	.11	310.
21.000	-17.39	2.76	.0305	.48	2.09	17.52	2.76	-.05	303.
22.000	-19.10	2.91	.1679	.08	1.87	19.20	2.90	.02	293.
23.000	-20.45	2.78	.1632	.11	1.84	20.53	2.75	.07	282.
24.000	-21.38	3.25	.0785	.11	2.29	21.50	3.23	-.13	282.
25.000	-22.43	3.69	-.0016	-.04	2.08	22.52	3.09	-.12	265.
26.000	-23.32	3.18	-.0028	-.26	2.22	23.43	3.17	.04	232.
27.000	-24.05	3.57	-.0502	-.21	2.45	24.18	3.55	-.03	191.
28.000	-24.72	3.18	-.0369	-.33	2.30	24.83	3.14	.01	185.
29.000	-25.15	3.31	-.0132	-.83	2.67	25.31	3.30	.12	109.
30.000	-26.44	3.34	.1130	-.52	2.17	26.53	3.34	.25	99.
32.000	-28.43	4.37	-.0328	2.63	2.92	28.09	4.35	-.23	142.
34.000	-29.60	4.33	-.0199	1.77	3.56	29.87	4.29	.05	142.
36.000	-32.74	5.36	.0423	.28	3.38	32.92	5.32	.14	142.
38.000	-36.39	5.90	.1696	.64	4.01	35.63	5.83	.00	142.
40.000	-39.53	6.15	-.0404	-.07	4.48	39.79	6.05	-.03	144.
42.000	-44.13	7.02	-.1482	.33	5.51	44.48	6.97	.06	145.
44.000	-47.27	7.36	-.1092	3.04	5.97	47.75	7.32	.03	144.
46.000	-48.09	7.56	-.0307	5.29	5.18	49.55	7.52	.15	143.
48.000	-49.93	8.46	.0203	5.12	6.00	50.61	8.35	.37	142.
50.000	-50.76	9.17	-.0594	6.02	6.23	51.47	9.17	.56	137.
52.000	-48.16	10.70	.0730	6.23	8.30	49.29	10.53	.50	130.
54.000	-43.03	12.82	.0860	5.84	9.79	44.59	12.52	.09	122.
56.000	-38.21	13.67	.1563	4.01	10.53	40.03	13.03	-.04	116.
58.000	-33.13	16.19	.2753	6.32	11.11	36.60	13.49	.00	94.
60.000	-23.98	17.25	.3221	5.06	13.87	30.33	12.71	.35	57.
62.000	-18.33	20.58	-.0137	3.85	13.22	26.50	15.37	.15	34.
64.000	-10.97	21.05	-.2537	-2.66	14.82	23.12	15.53	.43	26.
66.000	-11.37	17.63	-.1754	-2.04	13.80	20.67	13.88	1.41	24.
68.000	-14.43	16.51	-.0501	-6.10	13.63	22.91	12.83	.67	14.
70.000	-19.04	21.80	.2679	-10.58	16.57	30.57	16.15	1.13	23.

TABLE I-8. WIND STATISTICAL PARAMETERS

AUGUST

STATION = 911620		BARKING SANDS, HI							
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS	NOBS
KM	M/S	M/S		M/S	M/S	M/S	M/S		
.005	-1.31	1.16	.0167	-.01	.96	1.18	.99	1.02	394.
1.000	-2.90	2.07	-.0346	-.13	1.31	3.26	1.94	.61	393.
2.000	-4.97	3.45	.0128	-.40	2.33	5.58	3.31	.52	392.
3.000	-3.79	3.42	.1681	-.49	2.73	5.06	2.87	.51	392.
4.000	-2.47	3.74	.2492	-.47	3.01	4.68	2.74	.71	391.
5.000	-.78	3.97	.2835	-.38	3.36	4.55	2.61	.75	391.
6.000	1.01	4.58	.2453	-.16	3.95	5.28	3.12	.76	391.
7.000	3.17	5.02	.2297	.27	4.46	6.43	3.62	.68	388.
8.000	5.67	5.85	.1650	.71	5.27	8.55	4.60	.57	384.
9.000	8.34	6.78	.1312	1.24	6.23	11.11	5.67	.38	384.
10.000	11.17	7.90	.1344	1.59	7.26	13.99	6.81	.20	381.
11.000	14.44	9.37	.0934	1.75	8.38	17.32	9.30	.20	380.
12.000	17.38	10.33	.0749	2.23	9.00	20.18	9.35	.16	380.
13.000	18.67	10.92	.1023	2.85	8.94	21.29	10.11	.19	379.
14.000	16.04	10.22	.0275	3.00	7.68	18.51	9.32	.42	375.
15.000	9.84	7.56	-.0392	2.57	5.94	12.34	6.71	.81	374.
16.000	2.76	5.08	-.0517	1.55	3.93	6.16	3.64	1.04	374.
17.000	-3.89	3.56	-.0453	.63	2.62	5.27	2.70	.54	372.
18.000	-9.07	3.04	.0122	.25	2.23	9.37	2.95	.16	370.
19.000	-12.73	2.75	.0615	.03	1.84	12.87	2.73	.19	364.
20.000	-15.64	2.85	-.0054	.08	1.71	15.73	2.84	.10	362.
21.000	-17.50	2.87	-.0135	.25	2.24	17.66	2.82	.18	354.
22.000	-18.97	2.83	.0316	.04	1.91	19.06	2.83	-.10	351.
23.000	-20.06	2.60	.0404	-.07	1.92	20.15	2.61	-.28	333.
24.000	-21.19	3.01	.1929	-.08	2.32	21.31	3.01	-.20	332.
25.000	-22.10	3.21	.2155	-.02	2.03	22.20	3.19	-.22	301.
26.000	-23.09	3.12	.0598	-.05	1.99	23.18	3.10	-.04	263.
27.000	-24.02	3.17	.1108	-.08	2.62	24.16	3.18	.06	230.
28.000	-24.89	2.80	.0500	-.21	2.03	24.97	2.79	.20	221.
29.000	-25.92	3.31	-.0068	-.27	2.57	26.05	3.30	-.03	156.
30.000	-27.45	3.15	-.1623	-.07	2.36	27.56	3.13	-.03	131.
32.000	-29.59	3.58	-.0157	2.05	2.85	29.80	3.60	-.57	141.
34.000	-29.48	4.94	-.2335	2.24	3.16	29.73	4.91	.00	141.
36.000	-30.96	5.56	-.2009	1.14	3.54	31.18	5.52	-.36	141.
38.000	-32.39	7.68	.1044	.42	4.11	32.74	7.30	-.57	141.
40.000	-34.04	8.41	-.0553	-.06	4.31	34.35	8.25	.07	142.
42.000	-35.63	9.09	.0486	-.35	4.87	35.97	9.03	.28	142.
44.000	-37.13	10.08	-.0814	1.83	5.86	37.67	9.95	.15	142.
46.000	-37.03	11.55	-.0079	4.31	6.56	37.95	11.20	.33	143.
48.000	-35.04	12.75	.0104	6.09	7.17	35.49	12.11	.16	143.
50.000	-29.27	14.52	-.1535	6.54	7.46	31.27	13.70	.35	141.
52.000	-23.73	14.95	-.0559	7.12	8.55	26.77	13.92	.46	134.
54.000	-17.45	13.15	.0769	7.38	9.57	22.15	11.48	.66	131.
56.000	-13.44	12.62	.0948	5.98	10.99	19.74	10.27	.77	115.
58.000	-8.18	12.68	-.0365	5.76	11.23	17.41	9.10	.57	94.
60.000	-6.40	14.78	-.0005	4.57	10.75	17.20	9.76	.81	54.
62.000	-5.08	14.20	.1864	-.45	10.47	15.60	9.36	.84	35.
64.000	-5.62	15.05	.1329	-3.70	8.19	15.72	9.24	.72	32.
66.000	-5.49	15.17	-.1208	-3.26	12.93	17.19	11.55	1.15	30.
68.000	-8.53	11.73	-.1471	-3.81	16.38	19.67	9.77	.83	28.
70.000	-10.58	15.91	-.0075	-8.79	17.15	23.93	12.22	.61	27.

TABLE I-9. WIND STATISTICAL PARAMETERS

SEPTEMBER

STATION = 911620		BARKING SANDS, HI								NOBS
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS		
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	-1.60	1.21	.1483	.01	1.04	1.32	1.10	2.00	365.	
1.000	-2.29	2.19	.0351	.11	1.51	2.26	1.95	.82	365.	
2.000	-3.26	3.74	.2254	-.11	2.21	4.22	3.11	.22	365.	
3.000	-3.49	3.89	.2506	-.63	2.60	5.15	2.78	.61	364.	
4.000	-2.62	4.20	.3225	-.52	2.93	4.99	2.91	.53	364.	
5.000	-1.41	4.33	.3032	-.50	3.63	5.03	2.97	.93	364.	
6.000	-.17	4.69	.1999	-.39	4.37	5.03	3.09	.53	364.	
7.000	1.60	5.58	.2156	-.03	5.24	6.59	3.68	.54	363.	
8.000	3.72	6.74	.2441	.25	6.16	8.65	4.70	.56	363.	
9.000	6.13	7.96	.2739	.39	6.93	10.78	5.79	.53	362.	
10.000	8.74	8.98	.3003	.79	7.66	13.19	6.74	.34	362.	
11.000	11.83	10.16	.3131	1.05	8.87	16.01	8.15	.37	361.	
12.000	14.31	10.38	.3337	1.05	9.08	17.91	8.87	.31	360.	
13.000	15.03	10.32	.2829	.95	9.01	18.23	9.06	.23	359.	
14.000	12.45	9.60	.2491	.87	7.75	15.43	8.25	.39	359.	
15.000	7.83	7.61	.2316	.63	6.25	10.92	6.25	.72	358.	
16.000	2.79	5.50	.2135	.18	4.65	6.62	3.96	.95	357.	
17.000	-2.05	4.06	.1903	-.15	3.32	4.99	2.60	.74	357.	
18.000	-6.40	3.60	.1037	-.25	2.47	7.66	3.20	.34	357.	
19.000	-9.57	3.04	-.0219	-.11	2.04	9.61	2.99	-.04	353.	
20.000	-11.64	3.06	.1377	-.01	1.80	11.59	3.02	-.12	347.	
21.000	-13.65	3.47	-.0209	.00	1.85	13.79	3.44	-.19	341.	
22.000	-15.03	3.32	-.1176	-.13	1.95	15.16	3.28	.09	341.	
23.000	-16.40	3.21	-.0198	-.21	1.77	16.50	3.19	.12	326.	
24.000	-17.50	3.55	.0065	-.07	2.23	17.64	3.56	-.01	323.	
25.000	-18.41	3.54	.0080	.08	2.19	18.54	3.51	-.23	306.	
26.000	-19.05	3.51	-.0571	.27	2.10	19.18	3.48	-.14	263.	
27.000	-19.61	3.84	-.0475	.15	2.60	19.78	3.83	-.15	232.	
28.000	-19.94	3.60	.0461	.22	2.26	20.09	3.55	-.05	217.	
29.000	-20.18	4.14	.1272	.27	2.97	20.41	4.08	-.09	129.	
30.000	-21.01	4.48	.0620	.18	2.15	21.13	4.43	-.24	107.	
32.000	-22.36	5.68	-.0332	2.05	3.15	22.70	5.59	-.33	125.	
34.000	-19.68	7.02	.0009	2.23	3.55	20.21	6.77	-.21	125.	
36.000	-17.05	8.65	-.0323	1.29	3.78	17.74	8.14	-.02	124.	
38.000	-14.54	9.28	.1022	.33	4.60	15.70	8.50	.47	125.	
40.000	-12.72	9.83	.1658	-.01	4.54	14.78	8.66	.74	125.	
42.000	-12.19	10.76	-.0329	-.02	4.84	14.48	8.83	.72	125.	
44.000	-12.27	12.21	.0507	1.13	5.90	15.57	9.62	.58	125.	
46.000	-9.48	11.08	-.0262	3.54	6.20	13.99	8.20	.52	124.	
48.000	-5.59	10.08	-.1877	5.34	7.02	12.59	7.16	.80	122.	
50.000	-2.36	10.13	-.1233	5.63	6.29	11.88	6.13	.86	120.	
52.000	-.07	10.18	-.1115	6.33	6.41	12.42	5.43	.45	118.	
54.000	2.70	9.85	-.1090	5.52	7.37	12.07	6.51	.47	113.	
56.000	5.33	9.25	-.0976	5.08	7.79	12.44	6.67	.48	104.	
58.000	6.46	9.83	.1178	3.37	8.65	13.37	6.67	.40	95.	
60.000	5.54	11.54	.0599	1.93	10.21	14.77	7.14	.48	60.	
62.000	3.94	12.01	.1602	-1.41	10.22	14.32	7.46	.44	37.	
64.000	-1.54	14.26	.2301	-3.65	11.69	16.56	8.41	.60	25.	
66.000	.63	11.94	-.1352	-1.83	12.33	15.76	6.14	.16	21.	
68.000	-.61	13.13	-.1810	-6.03	13.97	17.95	8.20	.38	20.	
70.000	-5.22	16.58	-.1517	-12.55	13.20	22.45	10.64	.19	20.	

TABLE I-10. WIND STATISTICAL PARAMETERS

OCTOBER

STATION = 911620		BARKING SANDS, HI								NOBS
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS		
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	-.65	1.19	-.0453	-.17	1.60	1.54	1.43	1.75	376.	
1.000	-2.21	2.54	.0812	.26	2.52	3.48	2.36	1.05	376.	
2.000	-3.30	4.16	.1654	-.10	3.01	5.25	3.10	.69	376.	
3.000	-2.40	4.38	.3053	-.36	3.36	5.27	2.91	.74	376.	
4.000	-1.54	4.94	.3046	-.46	3.76	5.56	3.18	.73	375.	
5.000	-.66	5.49	.237	-.80	4.55	6.22	3.63	.83	375.	
6.000	.35	5.87	.2397	-1.02	5.54	7.00	4.16	1.04	375.	
7.000	1.45	6.60	.2388	-1.05	6.52	8.11	4.82	1.04	375.	
8.000	2.72	7.76	.3197	-1.22	7.52	9.73	5.54	.93	375.	
9.000	4.40	9.16	.4150	-1.28	8.71	11.72	6.59	.93	374.	
10.000	6.46	10.74	.4519	-1.41	9.82	13.95	7.77	.80	373.	
11.000	8.91	12.25	.4522	-1.42	10.85	16.42	8.90	.59	373.	
12.000	10.75	12.75	.4419	-1.36	11.09	17.65	9.55	.57	373.	
13.000	11.39	12.77	.4336	-1.48	10.46	17.67	9.57	.56	373.	
14.000	9.74	11.43	.3901	-1.46	8.88	15.26	8.56	.78	372.	
15.000	7.40	9.49	.3267	-1.48	7.21	12.21	7.05	.72	370.	
16.000	4.09	7.77	.2841	-1.46	5.87	9.22	5.34	.91	359.	
17.000	.86	5.89	.1430	-1.17	4.52	6.55	3.77	.86	367.	
18.000	-2.02	4.58	.0297	-.74	3.44	5.35	2.95	.82	363.	
19.000	-4.42	3.98	.0347	-.41	2.40	5.69	3.00	.47	353.	
20.000	-6.45	3.61	.0520	-.20	1.97	6.93	3.23	.08	348.	
21.000	-8.08	3.63	.1281	-.17	2.04	8.42	3.44	.03	337.	
22.000	-9.09	3.85	-.0265	-.13	1.97	9.38	3.66	.00	335.	
23.000	-9.87	3.93	-.0139	-.17	1.96	10.13	3.76	.02	317.	
24.000	-10.68	4.33	.0469	.05	2.55	11.04	4.17	.05	309.	
25.000	-11.14	4.56	-.0572	.23	2.29	11.44	4.39	-.02	287.	
26.000	-11.33	4.63	-.0588	.38	2.05	11.59	4.46	.02	256.	
27.000	-10.94	4.86	.0005	.47	2.30	11.25	4.70	.10	219.	
28.000	-10.56	5.25	.0957	.32	2.25	10.93	4.85	.17	209.	
29.000	-10.20	6.23	.2470	.23	3.00	11.16	5.22	.31	130.	
30.000	-9.58	7.07	.1156	.01	2.73	10.90	5.50	.27	113.	
32.000	-5.55	7.82	.0455	.83	3.49	9.04	4.78	.39	129.	
34.000	-.59	8.75	.0289	.89	3.55	8.19	4.78	.41	129.	
36.000	5.88	10.53	-.0382	.75	4.38	10.69	7.09	.79	130.	
38.000	11.68	11.21	-.0021	1.17	4.97	14.23	9.24	.58	130.	
40.000	15.84	11.52	.1575	.57	4.77	17.39	10.20	.29	130.	
42.000	19.53	12.26	.1826	2.00	5.94	21.10	11.20	.34	132.	
44.000	23.15	12.61	.2577	4.01	6.20	24.64	11.92	.00	132.	
46.000	27.64	13.70	.0520	4.83	5.81	29.09	12.73	-.25	132.	
48.000	31.68	14.44	-.1166	4.82	6.19	32.91	13.78	-.28	132.	
50.000	34.52	15.60	-.0911	5.05	7.27	35.91	14.95	-.23	131.	
52.000	35.58	16.21	-.0352	5.11	7.25	37.84	15.72	-.11	127.	
54.000	36.89	16.42	-.0784	6.29	7.24	38.36	15.82	-.18	122.	
56.000	37.36	16.13	-.1614	7.33	7.75	39.21	15.24	-.06	117.	
58.000	37.43	17.75	-.3011	8.19	7.64	39.80	16.12	.07	104.	
60.000	37.79	18.96	.0267	6.53	8.21	39.78	17.70	.14	69.	
62.000	38.46	18.55	-.2760	4.51	6.74	40.33	16.10	.12	42.	
64.000	33.65	19.05	-.4289	3.05	10.19	35.96	17.60	.11	28.	
66.000	28.57	19.81	-.3425	.77	10.64	31.65	17.70	-.30	26.	
68.000	22.97	20.61	.1327	-.18	13.82	30.44	14.14	.45	25.	
70.000	16.57	18.27	.0798	.06	13.84	25.96	10.45	.58	25.	

TABLE I-11. WIND STATISTICAL PARAMETERS

NOVEMBER

STATION = 911620		BARKING SANDS, HI								NOBS
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS		
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	-.81	1.23	-.0919	-.12	1.79	1.62	1.65	1.79	349.	
1.000	-2.53	3.24	-.0445	.77	3.83	4.61	3.31	1.76	346.	
2.000	-3.37	5.35	.1274	.76	4.40	6.55	4.10	.85	346.	
3.000	-2.00	5.53	.1467	.19	4.53	6.35	3.83	1.61	345.	
4.000	-.99	5.92	.1658	-.38	4.93	6.55	4.17	1.35	344.	
5.000	.43	6.69	.1175	-.68	6.02	7.53	4.97	1.16	344.	
6.000	1.96	7.66	.1551	-1.56	6.62	8.91	5.65	1.14	344.	
7.000	3.42	8.55	.1502	-2.02	7.61	10.54	5.95	1.09	344.	
8.000	5.12	9.27	.2005	-2.38	8.77	12.07	6.96	1.11	343.	
9.000	6.96	10.14	.2293	-2.62	9.78	13.85	7.85	.99	343.	
10.000	9.04	11.19	.2609	-3.20	10.68	15.97	8.89	.83	340.	
11.000	11.76	12.77	.2493	-3.40	11.83	18.69	10.14	.69	338.	
12.000	13.98	13.73	.2435	-3.83	12.25	20.56	11.20	.53	338.	
13.000	14.95	14.11	.2557	-4.47	12.03	21.30	11.54	.52	337.	
14.000	13.50	12.79	.2372	-4.48	10.39	19.17	10.30	.63	337.	
15.000	11.27	10.97	.2144	-3.62	8.60	16.17	8.52	.56	337.	
16.000	7.84	8.79	.2094	-3.31	6.69	12.48	6.19	.49	335.	
17.000	4.29	7.03	.1941	-2.72	5.26	9.06	4.65	.66	333.	
18.000	1.08	5.42	.1093	-1.76	4.24	6.28	3.48	1.03	332.	
19.000	-.89	4.38	.3051	-1.09	3.28	4.83	2.92	1.61	326.	
20.000	-2.52	3.74	.2890	-.50	2.56	4.39	2.79	1.38	319.	
21.000	-3.22	3.47	.1504	-.28	2.53	4.64	2.72	.89	312.	
22.000	-3.54	3.98	.1286	-.44	2.62	5.13	3.01	.93	310.	
23.000	-3.69	3.69	.0553	-.58	2.42	5.08	2.75	.59	301.	
24.000	-3.75	4.14	.0513	-.61	2.89	5.56	2.93	1.00	298.	
25.000	-3.25	4.75	.1144	-.05	3.15	5.64	3.34	1.03	287.	
26.000	-2.33	5.17	.1560	.42	2.91	5.35	3.47	1.42	282.	
27.000	-.88	5.74	.1843	.72	2.95	5.55	3.46	1.52	237.	
28.000	1.70	6.60	.1811	1.23	2.96	6.34	4.06	1.34	225.	
29.000	4.99	7.22	.0920	1.24	3.40	8.13	4.87	1.02	126.	
30.000	8.99	8.40	.0834	.61	3.24	11.05	6.30	.83	111.	
32.000	12.97	9.42	-.1166	.22	4.88	14.34	7.55	.62	102.	
34.000	17.93	10.32	-.0443	.84	4.80	19.33	8.82	.16	102.	
36.000	22.92	13.15	-.2683	-.15	5.04	24.09	11.95	.32	102.	
38.000	27.99	14.55	-.1050	-.60	6.52	29.21	13.56	.55	103.	
40.000	31.76	13.18	-.0197	-.11	7.55	32.79	12.78	.32	104.	
42.000	36.35	12.45	-.0495	.33	6.85	37.01	12.49	.49	104.	
44.000	42.48	12.03	-.1443		6.84	43.23	11.94	.23	104.	
46.000	48.59	12.65	-.1070	4.08	7.71	49.45	12.49	-.03	102.	
48.000	52.77	14.13	-.0153	5.13	9.64	53.97	13.75	-.23	101.	
50.000	55.58	16.09	.0651	5.91	9.41	56.73	15.90	-.09	99.	
52.000	57.20	16.77	.0516	5.50	11.04	58.65	16.22	-.18	99.	
54.000	58.44	16.71	.1876	3.58	10.11	59.53	16.27	-.32	99.	
56.000	58.72	19.34	.2430	3.71	10.09	59.82	18.93	-.43	93.	
58.000	58.35	21.48	.1365	6.23	9.99	60.04	19.97	-.45	80.	
60.000	60.74	22.93	.0920	8.30	10.83	63.05	20.52	-.42	55.	
62.000	55.66	26.42	.1116	4.42	10.68	58.50	22.28	-.24	28.	
64.000	46.70	27.77	.1193	3.76	12.90	51.53	21.26	.54	19.	
66.000	36.57	20.74	-.1849	2.84	10.75	40.95	24.33	.73	19.	
68.000	26.75	25.65	-.3034	-4.12	12.50	34.00	19.17	.62	19.	
70.000	15.81	26.83	.0304	-1.57	18.16	29.56	19.80	1.33	18.	

TABLE I-12. WIND STATISTICAL PARAMETERS

DECEMBER

STATION = 911620		BARKING SANDS, HI								NOBS
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS		
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	-.84	1.28	-.1458	-.37	2.31	1.95	2.01	1.64	319.	
1.000	-2.05	4.21	.0440	.36	4.36	5.46	3.35	1.00	317.	
2.000	-2.24	6.71	.2247	.57	4.94	7.56	4.17	.67	317.	
3.000	-.49	7.32	.3122	.25	4.98	7.71	4.36	1.22	317.	
4.000	1.02	7.95	.3339	-.43	5.69	8.48	4.96	1.10	317.	
5.000	2.67	9.15	.2976	-1.36	7.08	10.34	5.98	.76	316.	
6.000	4.72	9.84	.2599	-1.99	8.19	11.97	6.83	.75	316.	
7.000	7.11	10.74	.3061	-2.51	9.75	14.22	8.04	.80	316.	
8.000	9.26	12.18	.3532	-3.18	11.18	16.83	9.25	.89	315.	
9.000	11.56	13.62	.3950	-4.34	12.64	19.77	10.54	.78	315.	
10.000	14.07	14.79	.4377	-5.65	14.31	22.90	11.32	.59	313.	
11.000	16.92	16.44	.4947	-6.31	15.53	26.23	12.17	.46	312.	
12.000	19.46	16.99	.5604	-6.35	15.90	28.24	12.72	.53	313.	
13.000	19.69	16.69	.5493	-6.40	14.71	27.73	12.69	.67	313.	
14.000	18.60	14.84	.4639	-5.88	12.05	24.76	11.50	.78	311.	
15.000	15.76	12.02	.3714	-5.66	10.63	21.11	9.59	.45	311.	
16.000	12.20	9.89	.2549	-4.76	8.75	16.67	7.82	.41	311.	
17.000	7.75	8.48	.2515	-3.68	7.06	12.37	6.50	.82	310.	
18.000	2.83	6.48	.0970	-2.58	5.49	8.06	4.06	1.35	310.	
19.000	-.56	4.94	.0383	-1.64	3.77	5.65	3.09	1.01	306.	
20.000	-1.93	4.41	.0939	-.90	2.77	4.73	2.94	1.22	302.	
21.000	-1.78	4.48	.1110	-.40	2.64	4.55	3.10	1.68	298.	
22.000	-1.22	4.93	.1742	-.29	2.57	4.79	3.08	1.52	295.	
23.000	-.77	5.07	.2320	-.44	2.40	4.80	3.03	1.68	282.	
24.000	-.40	5.68	.1749	-.53	3.23	5.55	3.50	1.58	272.	
25.000	-.02	6.10	.2580	-.23	3.57	5.68	4.20	1.70	268.	
26.000	.64	6.49	.3448	.58	3.10	5.62	4.31	1.80	237.	
27.000	1.78	6.97	.3514	.98	3.03	6.51	4.39	1.23	208.	
28.000	3.21	7.85	.3524	1.21	3.55	7.84	4.93	.74	204.	
29.000	5.41	8.80	.3917	1.32	4.02	9.73	5.43	.58	133.	
30.000	7.29	9.68	.3258	.32	3.89	11.15	6.10	.49	126.	
32.000	8.29	11.67	.1749	-.69	4.66	13.12	7.33	.52	103.	
34.000	10.44	12.48	.3221	-.47	7.15	16.02	7.62	.61	103.	
35.000	12.94	15.23	.3980	1.16	8.36	19.16	10.10	1.03	103.	
38.000	16.81	17.24	.4100	1.01	8.23	22.37	12.07	.56	102.	
40.000	22.23	19.97	.4407	1.54	9.54	27.71	14.69	.77	103.	
42.000	26.93	22.80	.4550	4.53	11.46	32.95	17.54	.53	103.	
44.000	32.76	25.73	.3672	6.57	11.88	38.59	20.66	.68	104.	
46.000	36.05	27.42	.2841	9.06	13.48	42.60	22.27	.66	103.	
48.000	37.26	26.77	.3540	10.05	13.15	43.33	22.30	.49	102.	
50.000	36.73	26.67	.2178	9.68	14.85	43.86	21.13	.52	101.	
52.000	36.63	26.82	.1823	9.97	16.60	43.89	22.48	.51	99.	
54.000	38.93	27.98	.3142	10.05	14.75	44.65	24.52	.34	98.	
56.000	39.74	28.45	.2583	11.18	17.12	47.35	23.64	.32	89.	
58.000	42.92	28.90	.4665	11.71	16.57	49.79	24.56	.36	76.	
60.000	45.54	28.72	.5023	12.69	17.02	51.76	25.74	.02	55.	
62.000	42.63	25.14	.3119	14.00	19.67	49.07	24.78	-.29	27.	
64.000	44.68	24.81	.2729	9.81	11.01	47.75	23.16	.07	16.	
66.000	49.63	23.44	.4213	3.73	11.37	50.93	23.52	.13	14.	
68.000	50.16	27.10	.3223	-2.17	16.13	53.23	25.59	-.22	13.	
70.000	49.40	27.62	-.1825	-11.15	17.37	54.92	23.98	-.34	13.	

TABLE I-13. WIND STATISTICAL PARAMETERS

ANNUAL

STATION • 911620		BARKING SANDS, HI								
Z	MEAN U	S.D. U	R(U,V)	MEAN V	S.D. V	MEAN WS	S.D. WS	SKEW WS	NOBS	
KM	M/S	M/S		M/S	M/S	M/S	M/S			
.005	-.45	1.38	-.0730	-.22	1.95	1.63	1.75	2.00	4342.	
1.000	-2.07	3.24	.0821	.32	3.15	4.03	2.93	1.52	4330.	
2.000	-3.02	5.54	.1891	.35	3.54	6.15	3.82	.95	4320.	
3.000	-1.60	6.16	.2609	-.11	3.87	6.24	4.06	1.71	4326.	
4.000	-.17	6.97	.2276	-.40	4.39	6.74	4.76	1.76	4321.	
5.000	1.55	7.79	.1437	-.79	5.25	7.68	5.69	1.67	4320.	
6.000	3.39	8.55	.1195	-1.13	6.17	8.98	6.58	1.57	4315.	
7.000	5.36	9.50	.0979	-1.43	7.28	10.79	7.53	1.42	4303.	
8.000	7.60	10.73	.1036	-1.80	8.68	13.16	8.85	1.32	4287.	
9.000	10.23	12.22	.1306	-2.23	10.18	16.04	10.27	1.13	4276.	
10.000	13.13	13.65	.1695	-2.58	11.65	19.20	11.52	.86	4242.	
11.000	16.30	15.17	.1960	-2.87	12.90	22.55	12.75	.69	4213.	
12.000	19.17	16.13	.2148	-3.04	13.23	25.03	13.63	.60	4208.	
13.000	20.37	16.11	.2144	-3.12	12.57	25.64	13.60	.54	4190.	
14.000	18.67	14.66	.1509	-2.97	10.84	23.10	12.52	.59	4161.	
15.000	14.82	12.54	.0648	-2.58	8.92	18.02	10.80	.70	4152.	
16.000	9.85	10.48	-.0191	-2.15	6.95	13.48	8.85	.87	4137.	
17.000	4.77	9.04	-.0904	-1.66	5.30	9.59	6.58	1.15	4112.	
18.000	.00	7.95	-.1173	-1.04	4.10	7.83	4.45	1.22	4086.	
19.000	-3.50	7.05	-.0953	-.62	2.98	7.31	4.23	.57	4024.	
20.000	-6.01	6.92	-.0954	-.35	2.32	7.90	5.21	.60	3993.	
21.000	-7.59	7.22	-.1042	-.24	2.27	8.94	5.92	.52	3853.	
22.000	-8.60	7.71	-.0932	-.31	2.27	9.91	6.37	.44	3827.	
23.000	-9.44	8.07	-.0768	-.32	2.09	10.59	6.82	.37	3651.	
24.000	-10.22	8.70	-.0349	-.23	2.58	11.62	7.19	.32	3527.	
25.000	-10.39	9.36	.0362	.06	2.57	12.07	7.53	.30	3393.	
26.000	-10.26	10.14	.1377	.31	2.47	12.36	7.85	.32	3022.	
27.000	-9.69	11.28	.2026	.50	2.82	12.81	8.09	.35	2535.	
28.000	-8.91	12.58	.2777	.65	2.86	13.39	8.17	.28	2416.	
29.000	-7.98	14.31	.2853	.64	3.32	14.43	8.48	.20	1490.	
30.000	-7.06	16.14	.2137	.45	3.11	15.55	8.87	.16	1202.	
32.000	-6.85	17.63	-.1859	.73	4.04	16.94	9.37	.21	1563.	
34.000	-6.44	18.31	-.1120	.70	4.71	17.51	9.65	.27	1567.	
36.000	-6.53	19.82	.0310	.55	5.01	18.50	10.90	.43	1567.	
38.000	-6.53	21.94	.0009	.42	5.51	20.05	12.35	.52	1566.	
40.000	-6.70	24.27	.1516	.58	6.14	22.25	13.31	.50	1571.	
42.000	-6.69	27.23	.2512	1.77	6.82	24.89	14.71	.52	1576.	
44.000	-6.01	30.55	.2069	3.63	7.31	27.93	16.00	.50	1575.	
46.000	-4.05	33.10	.1342	5.46	8.16	30.35	16.96	.48	1562.	
48.000	-1.41	34.73	.0812	6.35	8.59	31.79	17.67	.45	1547.	
50.000	1.11	35.80	.0386	6.08	8.40	32.36	18.54	.49	1521.	
52.000	3.90	35.55	.0378	6.15	9.43	33.48	19.94	.50	1483.	
54.000	7.17	37.01	.0657	6.21	9.89	34.30	19.53	.43	1433.	
56.000	10.19	37.71	.0977	7.01	10.79	35.83	20.23	.50	1320.	
58.000	14.13	37.75	.1419	8.20	11.27	37.07	21.13	.51	1121.	
60.000	18.23	38.32	.1650	7.59	11.84	38.82	22.21	.44	772.	
62.000	17.64	37.90	.1460	4.27	12.76	37.79	22.46	.41	446.	
64.000	17.12	37.49	.2153	-.41	12.47	36.32	23.25	.59	306.	
66.000	14.62	36.91	.0956	-3.81	13.92	35.60	22.88	.75	287.	
68.000	10.06	36.87	.0747	-7.96	15.40	36.09	21.60	.78	277.	
70.000	3.74	37.67	.0970	-9.40	16.06	36.75	20.85	.73	757.	

TABLE II-1. THERMODYNAMIC STATISTICAL PARAMETERS

JANUARY

STATION - 911620		MARKING SANDS, HI		S.D. T		SKEW T		MEAN D		S.D. D		SKEW D		NOBS P		NOBS T		NOBS D	
Z	MEAN P	S.D. P	SKEW P	MEAN T	DEG K	DEG K	DEG K	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3						
0.000	1014.8000	3.5676	-44	293.70	2.32	2.32	.03	1195.0000	12.7400	-13	313.	313.	313.	313.	313.	313.	313.	313.	313.
0.005	1014.2000	3.7665	-47	293.64	2.38	2.38	-.03	1195.0000	13.1100	-10	344.	344.	344.	344.	344.	344.	344.	344.	344.
1.000	903.5200	3.3410	-52	288.12	1.85	1.85	-.57	1087.0000	8.3820	.14	344.	344.	344.	344.	344.	344.	344.	344.	344.
2.000	802.2500	3.1701	-47	283.71	2.57	2.57	-.49	982.1000	9.0310	.38	344.	344.	344.	344.	344.	344.	344.	344.	344.
3.000	711.1400	3.2229	-54	279.89	2.61	2.61	-.41	883.4000	7.2850	.03	344.	344.	344.	344.	344.	344.	344.	344.	344.
4.000	629.0100	3.2562	-55	274.54	2.66	2.66	-.40	797.0000	6.4320	-13	344.	344.	344.	344.	344.	344.	344.	344.	344.
5.000	555.0200	3.3030	-65	268.61	2.88	2.88	-.46	718.0000	6.0880	-.07	344.	344.	344.	344.	344.	344.	344.	344.	344.
6.000	488.2400	3.4356	-69	262.14	3.25	3.25	-.35	648.1000	6.0530	-15	344.	344.	344.	344.	344.	344.	344.	344.	344.
7.000	427.9600	3.5244	-71	255.24	3.51	3.51	-.29	533.5000	5.8420	-30	343.	343.	343.	343.	343.	343.	343.	343.	343.
8.000	373.9800	3.6178	-72	248.29	3.79	3.79	-.24	524.2000	5.9880	-43	342.	342.	342.	342.	342.	342.	342.	342.	342.
9.000	325.5100	3.6801	-66	241.66	3.92	3.92	-.09	468.8000	6.0110	-.61	342.	342.	342.	342.	342.	342.	342.	342.	342.
10.000	282.2400	3.5946	-56	235.27	3.84	3.84	-.19	417.6000	5.8590	-.58	340.	340.	340.	340.	340.	340.	340.	340.	340.
11.000	243.9200	3.4043	-42	228.83	3.52	3.52	-.36	371.3000	5.2730	-.64	337.	337.	337.	337.	337.	337.	337.	337.	337.
12.000	179.7500	2.8594	-31	222.54	3.24	3.24	-.68	328.4000	4.8820	-.81	336.	336.	336.	336.	336.	336.	336.	336.	336.
13.000	153.2800	2.5482	-20	216.10	3.03	3.03	-.73	289.8000	4.7740	-.89	335.	335.	335.	335.	335.	335.	335.	335.	335.
14.000	130.1100	2.1964	-23	204.48	2.81	2.81	-.40	254.2000	4.9170	-.96	332.	332.	332.	332.	332.	332.	332.	332.	332.
15.000	109.9800	1.8403	-28	200.21	2.69	2.69	-.10	221.7000	4.7600	-.56	331.	331.	331.	331.	331.	331.	331.	331.	331.
16.000	92.7530	1.4795	-30	197.90	3.13	3.13	.42	191.4000	4.4840	-.23	326.	326.	326.	326.	326.	326.	326.	326.	326.
17.000	78.1260	1.1330	-28	198.12	3.71	3.71	.37	163.3000	4.4000	-.25	324.	324.	324.	324.	324.	324.	324.	324.	324.
18.000	65.9470	.8414	-15	201.79	3.51	3.51	.65	137.4000	3.8640	-.45	322.	322.	322.	322.	322.	322.	322.	322.	322.
19.000	55.6530	.6535	-05	206.28	2.76	2.76	.44	113.9000	2.9480	-.34	317.	317.	317.	317.	317.	317.	317.	317.	317.
20.000	47.4530	.5345	.02	209.78	2.50	2.50	.29	94.3400	1.9190	-.23	313.	313.	313.	313.	313.	313.	313.	313.	313.
21.000	40.4140	.4647	.04	212.43	2.48	2.48	-.12	86.2800	.9768	-.11	304.	304.	304.	304.	304.	304.	304.	304.	304.
22.000	34.4950	.4062	-.01	214.61	2.40	2.40	-.17	76.0000	.7424	-.11	294.	294.	294.	294.	294.	294.	294.	294.	294.
23.000	29.4750	.3635	-.02	216.56	2.58	2.58	-.25	47.4200	.6302	-.20	279.	279.	279.	279.	279.	279.	279.	279.	279.
24.000	25.2290	.3333	-.10	218.41	2.74	2.74	-.02	40.2500	.5463	-.06	273.	273.	273.	273.	273.	273.	273.	273.	273.
25.000	21.6130	.3073	-.10	220.36	2.62	2.62	.08	34.1700	.4812	-.03	246.	246.	246.	246.	246.	246.	246.	246.	246.
26.000	18.5420	.2669	-.18	222.33	2.65	2.65	.06	29.0600	.4452	-.01	218.	218.	218.	218.	218.	218.	218.	218.	218.
27.000	15.9260	.2376	-.15	224.61	2.86	2.86	.19	24.7000	.4119	-.33	206.	206.	206.	206.	206.	206.	206.	206.	206.
28.000	13.7040	.2127	.07	226.33	2.92	2.92	.24	21.1000	.3807	-.30	168.	168.	168.	168.	168.	168.	168.	168.	168.
29.000	11.7980	.1936	.27	227.97	3.11	3.11	.09	18.0300	.35075	-.40	148.	148.	148.	148.	148.	148.	148.	148.	148.
30.000	8.8262	.1908	-.11	232.59	4.30	4.30	.43	13.2200	.3059	-.16	107.	107.	107.	107.	107.	107.	107.	107.	107.
31.000	6.6219	.1544	-.03	236.38	5.20	5.20	.12	9.7680	.2651	.14	110.	110.	110.	110.	110.	110.	110.	110.	110.
32.000	4.9934	.1190	.00	241.81	5.00	5.00	-.33	7.1930	.2651	.04	109.	109.	109.	109.	109.	109.	109.	109.	109.
33.000	3.7942	.0963	.04	247.79	4.88	4.88	-.06	5.3330	.1603	-.01	109.	109.	109.	109.	109.	109.	109.	109.	109.
34.000	2.9001	.0781	.14	254.09	6.49	6.49	-.52	3.9760	.1203	-.55	109.	109.	109.	109.	109.	109.	109.	109.	109.
35.000	2.2331	.0644	.17	260.11	6.16	6.16	-.55	2.9850	.0875	-.19	109.	109.	109.	109.	109.	109.	109.	109.	109.
36.000	1.7296	.0535	.13	265.48	6.81	6.81	-.27	2.2590	.0730	-.11	109.	109.	109.	109.	109.	109.	109.	109.	109.
37.000	1.3452	.0448	.05	268.89	6.61	6.61	.08	1.7430	.0552	.09	109.	109.	109.	109.	109.	109.	109.	109.	109.
38.000	1.0474	.0391	.05	269.38	6.35	6.35	-.84	1.3590	.0441	.20	109.	109.	109.	109.	109.	109.	109.	109.	109.
39.000	.8147	.0322	-.05	266.46	6.43	6.43	-.56	1.0630	.0333	.21	107.	107.	107.	107.	107.	107.	107.	107.	107.
40.000	.6333	.0264	.22	264.33	6.39	6.39	-.49	.8344	.0300	-.47	101.	101.	101.	101.	101.	101.	101.	101.	101.
41.000	.4908	.0222	.33	263.90	6.45	6.45	-.05	.6485	.0273	-.29	98.	98.	98.	98.	98.	98.	98.	98.	98.
42.000	.3797	.0181	.46	262.33	6.91	6.91	-.07	.5045	.0211	-.20	93.	93.	93.	93.	93.	93.	93.	93.	93.
43.000	.2926	.0144	.30	260.12	6.77	6.77	-.13	.3016	.0161	.05	78.	78.	78.	78.	78.	78.	78.	78.	78.
44.000	.2248	.0105	.26	255.01	6.13	6.13	-.87	.3060	.0125	.46	57.	57.	57.	57.	57.	57.	57.	57.	57.
45.000	.1716	.0096	.31	250.52	7.83	7.83	-.38	.2384	.0094	.41	32.	32.	32.	32.	32.	32.	32.	32.	32.
46.000	.1263	.0073	.13	241.34	7.69	7.69	-.43	.1831	.0072	-.38	17.	17.	17.	17.	17.	17.	17.	17.	17.
47.000	.0741	.0043	.29	233.44	5.67	5.67	-.37	.1478	.0041	-.20	18.	18.	18.	18.	18.	18.	18.	18.	18.
48.000	.0715	.0035	.45	222.83	5.45	5.45	.91	.1117	.0051	-.10	18.	18.	18.	18.	18.	18.	18.	18.	18.
49.000	.0528	.0026	.93	218.06	5.83	5.83	-.16	.0941	.0045	.28	16.	16.	16.	16.	16.	16.	16.	16.	16.

TABLE II-2. THERMODYNAMIC STATISTICAL PARAMETERS

FEBRUARY

STATION - 911620	BARKING SANDS, HI	S.D. T	MEAN T	S.D. K	MEAN K	S.D. P	MEAN P	S.D. D	MEAN D	S.D. O	MEAN O	S.D. S	MEAN S	S.D. T	MEAN T	S.D. P	MEAN P	S.D. D	MEAN D	S.D. O	MEAN O	S.D. S	MEAN S
2	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101
1.000	1016.3000	3.5973	-77	233.85	2.25	.29	1197.0000	11.9700	317.	317.	317.	317.	317.	317.	317.	317.	317.	317.	317.	317.	317.	317.	317.
1.001	1015.7030	3.5705	-75	233.71	2.39	.19	1197.0000	12.7700	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
1.002	994.5000	3.1352	-93	237.53	1.73	-.37	1233.0000	7.7570	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
2.000	633.4700	3.0317	-99	233.45	2.43	-.19	854.6000	7.7890	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
3.000	712.0700	3.0393	-1.03	273.56	2.34	-.09	885.6000	6.6550	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
4.000	659.7200	3.0500	-.98	274.37	2.71	-.14	798.5000	6.9040	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
5.000	555.6100	3.0541	-.93	259.50	3.07	-.04	720.0000	7.1140	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
6.000	489.7400	3.1415	-.81	252.06	3.40	-.03	649.0000	6.9780	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
7.000	428.4200	3.2541	-.73	235.23	3.66	-.01	534.2000	6.8760	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
8.000	374.3100	3.4155	-.63	218.19	4.21	-.06	454.9000	6.5450	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
9.000	325.8300	3.5883	-.62	241.33	4.44	-.11	469.9000	6.1110	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
10.000	282.4200	3.6834	-.53	234.65	4.30	-.20	418.5000	5.5090	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
11.000	243.9500	3.6677	-.41	220.59	3.69	-.57	371.7000	5.1380	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
12.000	209.7500	3.3797	-.33	222.36	3.46	-.10	328.7000	5.3170	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
13.000	179.7600	3.0570	-.28	216.26	2.78	-.73	289.6000	5.1870	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
14.000	153.3100	2.6569	-.23	210.25	2.50	-.10	254.1000	5.3710	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
15.000	130.1700	2.2119	-.16	204.78	2.61	-.31	221.5000	5.4000	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
16.000	110.0300	1.7774	-.11	200.60	3.24	-.35	191.2000	5.2400	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
17.000	92.1100	1.2377	-.10	193.29	3.71	-.29	163.2000	4.7100	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
18.000	70.2770	1.0235	-.02	198.58	4.05	-.02	137.4000	3.9550	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
19.000	56.6240	.7825	.14	202.17	3.44	-.14	113.9000	2.6550	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
20.000	55.9300	.4675	.08	205.53	2.63	-.17	94.2000	1.7030	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
21.000	47.5420	.4637	-.10	203.61	2.64	-.23	78.9000	1.2350	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
22.000	40.4910	.4178	-.01	212.70	2.35	-.18	66.3000	.5600	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
23.000	34.5730	.3636	-.03	214.08	2.28	-.07	56.0400	.7051	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
24.000	29.5600	.3333	-.03	217.07	2.48	-.14	47.4300	.5737	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
25.000	25.3040	.3159	-.05	219.16	2.59	-.09	40.2700	.4980	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
26.000	21.6570	.2952	-.05	221.30	2.59	-.06	34.1000	.4370	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
27.000	18.6300	.2667	-.03	223.35	2.61	-.01	29.0000	.3783	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
28.000	16.0160	.2432	-.05	225.51	2.69	-.06	24.7400	.3531	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
29.000	13.8020	.2302	.02	227.41	2.95	-.30	21.1400	.3339	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
30.000	11.2000	.2146	.02	229.34	2.64	-.30	18.0800	.2903	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
32.000	8.8320	.1695	.30	235.19	4.25	-.31	13.1600	.2377	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
34.000	6.6304	.1258	.20	240.50	4.97	-.02	9.6900	.2079	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
36.000	5.0653	.0958	.04	244.95	4.74	.16	7.0200	.1914	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
38.000	3.8578	.0757	-.03	250.04	5.38	-.05	5.3750	.1466	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
40.000	2.9650	.0622	.04	255.84	5.26	-.42	4.0250	.0955	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
42.000	2.2795	.0542	.12	261.34	5.47	-.62	3.0410	.0785	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
44.000	1.7650	.0452	-.01	264.89	5.58	-.63	2.3220	.0626	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
46.000	1.3709	.0382	-.08	267.39	5.94	-.87	1.7860	.0502	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
48.000	1.0666	.0327	-.27	267.56	5.97	-.35	1.3630	.0407	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
50.000	.9300	.0272	-.27	267.30	5.69	-.10	1.0400	.0335	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
52.000	.6452	.0228	-.18	263.65	5.45	-.63	.8429	.0214	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
54.000	.5005	.0190	-.04	254.21	5.81	-.25	.6703	.0216	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
56.000	.3790	.0159	-.04	251.78	5.56	-.09	.5185	.0184	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
58.000	.3004	.0124	-.03	250.52	5.17	-.28	.4675	.0141	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
60.000	.2319	.0102	-.11	255.43	5.94	-.04	.3155	.0109	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
62.000	.1771	.0037	.30	251.72	7.29	.32	.2449	.0107	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
64.000	.1328	.0090	.95	243.30	7.20	.68	.1893	.0105	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
66.000	.0742	.0040	.76	234.50	9.00	.15	.1471	.0089	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
68.000	.0734	.0040	.54	219.40	11.16	.97	.1171	.0065	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
70.000	.0744	.0040	.79	214.40	8.62	1.06	.0977	.0044	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.

MARCH

72

TABLE II-4. THERMODYNAMIC STATISTICAL PARAMETERS

APRIL

STATION - 911620 Z 101	MEAN P MB	BARKING SALES, MI S.D. P MB	MEAN T DEG K	S.D. T DEG K	SKEW T	MEAN D G/M3	S.D. D G/M3	SKEW D	NOBS P	NOBS T	NOBS D
.000	1017.0000	2.6748	288.64	1.88	.08	1187.0000	8.5440	.16	374.	374.	374.
.005	1017.3000	2.6744	288.59	1.92	.02	1186.0000	8.7950	.22	392.	392.	392.
1.000	906.5000	2.5475	288.69	1.25	-.73	1089.0000	5.5670	.39	392.	392.	392.
2.000	805.1100	2.2437	288.77	1.93	.08	995.3000	6.0150	-.02	392.	392.	392.
3.000	713.7100	2.1445	276.67	1.84	-.03	887.0000	5.3470	-.02	392.	392.	392.
4.000	631.2100	2.1157	274.55	1.87	.02	809.0000	5.0030	-.18	392.	392.	392.
5.000	549.7000	2.0240	269.64	2.02	.01	721.0000	4.8100	-.29	392.	392.	392.
6.000	469.2000	2.0423	261.50	2.11	.09	651.1000	4.3040	-.60	391.	391.	391.
7.000	429.4000	2.1332	254.74	2.19	.02	586.7000	3.8300	-.17	391.	391.	391.
8.000	375.0300	2.1314	247.26	2.33	-.01	527.0000	3.5410	-.18	391.	391.	391.
9.000	326.1000	2.2097	239.67	2.48	.03	473.7000	3.2030	-.23	391.	391.	391.
10.000	282.3300	2.2008	232.04	2.59	.08	423.7000	3.2070	-.49	391.	391.	391.
11.000	243.3000	2.2017	224.23	2.77	.31	377.1000	3.5200	-.93	391.	391.	391.
12.000	208.7700	2.1193	218.59	2.99	.22	332.0000	4.2600	-.78	393.	393.	393.
13.000	179.4300	1.9563	213.49	2.97	.10	281.0000	4.5400	-.43	395.	395.	395.
14.000	151.9500	1.7019	203.51	2.78	-.22	232.7000	4.4070	-.02	393.	393.	393.
15.000	129.0400	1.4170	208.11	2.63	-.37	219.2000	4.0010	.12	391.	391.	391.
16.000	109.3200	1.1472	203.34	2.63	-.06	187.3000	3.5530	.17	391.	391.	391.
17.000	92.4660	.9042	202.03	2.63	-.13	150.5000	3.1470	.26	391.	391.	391.
18.000	78.2090	.7074	208.37	2.59	-.30	134.3000	2.5710	.52	374.	374.	374.
19.000	66.2730	.5693	206.37	2.59	-.40	111.9000	1.8180	.39	390.	390.	390.
20.000	56.3260	.4754	209.90	2.30	-.35	93.4900	1.2840	.42	359.	359.	359.
21.000	47.5960	.4135	212.60	2.19	-.14	78.6400	.9713	-.10	350.	350.	350.
22.000	40.5320	.3532	215.05	2.12	-.11	66.3000	.7370	-.13	355.	355.	355.
23.000	35.0350	.3282	217.57	1.99	-.09	56.1000	.5930	-.23	344.	344.	344.
24.000	30.0060	.2993	220.12	2.09	-.18	47.4300	.4900	-.32	339.	339.	339.
25.000	25.7530	.2704	222.46	2.07	-.24	40.3300	.4375	-.44	328.	328.	328.
26.000	22.1450	.2448	224.70	1.97	-.09	34.3300	.3030	-.40	308.	308.	308.
27.000	19.0680	.2243	226.88	1.96	-.23	29.2900	.3422	-.21	268.	268.	268.
28.000	16.4370	.2023	220.07	2.03	-.23	25.0000	.3078	-.16	249.	249.	249.
29.000	14.1910	.1799	230.54	2.04	-.11	21.4100	.2647	-.15	198.	198.	198.
30.000	12.2670	.1559	232.77	2.05	.10	18.3000	.2280	-.46	170.	170.	170.
31.000	9.1834	.1466	238.14	3.36	.14	13.4400	.2007	-.08	123.	123.	123.
32.000	6.9304	.1231	242.33	3.43	.18	9.6000	.1748	-.07	121.	121.	121.
33.000	5.2621	.1022	246.55	4.17	.73	7.4400	.1100	-.64	120.	120.	120.
34.000	4.0135	.0840	251.04	3.70	.46	5.5000	.1163	-.35	121.	121.	121.
35.000	3.0770	.0665	256.27	3.02	.06	4.1800	.0947	-.06	120.	120.	120.
36.000	2.3718	.0539	260.97	4.05	.03	3.1000	.0748	.17	123.	123.	123.
37.000	1.8394	.0453	265.00	4.31	-.17	2.4100	.0518	-.12	119.	119.	119.
38.000	1.4265	.0373	267.13	3.18	.00	1.6300	.0472	-.18	117.	117.	117.
39.000	1.1085	.0283	268.29	3.95	-.08	1.4360	.0378	.05	114.	114.	114.
40.000	.8633	.0235	267.98	4.24	-.18	1.1210	.0280	.14	113.	113.	113.
41.000	.6718	.0194	267.00	3.93	-.17	.8758	.0229	.19	111.	111.	111.
42.000	.5218	.0157	264.31	3.99	-.13	.6875	.0173	-.08	109.	109.	109.
43.000	.4045	.0133	260.72	4.72	.14	.5404	.0131	.08	100.	100.	100.
44.000	.3120	.0114	255.92	5.05	.12	.4230	.0111	.39	85.	85.	85.
45.000	.2392	.0096	252.02	5.30	-.02	.3106	.0097	.50	62.	62.	62.
46.000	.1893	.0075	245.01	5.55	.60	.2071	.0074	.21	33.	33.	33.
47.000	.1358	.0059	235.28	5.27	1.11	.1212	.0049	.19	16.	16.	16.
48.000	.1014	.0046	229.67	5.91	1.04	.1516	.0043	.42	17.	17.	17.
49.000	.0794	.0033	219.22	9.03	1.48	.1199	.0035	.26	17.	17.	17.
50.000	.0548	.0015	213.16	4.41	-.24	.0894	.0025	-.41	16.	16.	16.

TABLE II-5. THERMODYNAMIC STATISTICAL PARAMETERS

MAY

STATION = 911620		BARKING SANDS, HI		S.D. T		MEAN T		S.D. T		SKEW T		MEAN D		S.D. D		SKEW D		NOBS P		NOBS T		NOBS D	
Z	KB	S.D. P	MEAN P	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3						
.000	1017.4000	2.0431	230.18	1.67	230.18	1.67	230.18	.61	1179.0000	7.4500	7.4500	7.4500	7.4500	7.4500	7.4500	7.4500	7.4500	356.	356.	356.	356.	356.	356.
.005	1016.8000	2.0329	238.16	1.66	238.16	1.66	238.16	.59	1179.0000	7.4100	7.4100	7.4100	7.4100	7.4100	7.4100	7.4100	7.4100	369.	369.	369.	369.	369.	369.
1.000	906.5000	1.7003	239.64	1.03	239.64	1.03	239.64	.51	1084.0000	4.8260	4.8260	4.8260	4.8260	4.8260	4.8260	4.8260	4.8260	369.	369.	369.	369.	369.	369.
2.000	805.4100	1.6269	284.68	1.89	284.68	1.89	284.68	.28	982.3000	5.9880	5.9880	5.9880	5.9880	5.9880	5.9880	5.9880	5.9880	368.	368.	368.	368.	368.	368.
3.000	714.2500	1.6363	280.95	1.93	280.95	1.93	280.95	-.07	884.1000	5.4310	5.4310	5.4310	5.4310	5.4310	5.4310	5.4310	5.4310	368.	368.	368.	368.	368.	368.
4.000	632.1500	1.7749	276.16	2.02	276.16	2.02	276.16	.19	795.5000	5.0540	5.0540	5.0540	5.0540	5.0540	5.0540	5.0540	5.0540	368.	368.	368.	368.	368.	368.
5.000	558.1700	1.8151	270.27	2.08	270.27	2.08	270.27	.00	718.7000	4.6280	4.6280	4.6280	4.6280	4.6280	4.6280	4.6280	4.6280	368.	368.	368.	368.	368.	368.
6.000	491.4200	1.9463	263.76	2.21	263.76	2.21	263.76	-.13	648.5000	4.2420	4.2420	4.2420	4.2420	4.2420	4.2420	4.2420	4.2420	368.	368.	368.	368.	368.	368.
7.000	431.1500	2.0716	256.82	2.29	256.82	2.29	256.82	-.21	584.4000	3.8350	3.8350	3.8350	3.8350	3.8350	3.8350	3.8350	3.8350	368.	368.	368.	368.	368.	368.
8.000	376.9700	2.1352	249.48	2.23	249.48	2.23	249.48	-.18	526.1000	3.2390	3.2390	3.2390	3.2390	3.2390	3.2390	3.2390	3.2390	368.	368.	368.	368.	368.	368.
9.000	328.2600	2.1973	241.79	2.29	241.79	2.29	241.79	-.15	472.7000	3.0240	3.0240	3.0240	3.0240	3.0240	3.0240	3.0240	3.0240	365.	365.	365.	365.	365.	365.
10.000	284.5000	2.2034	234.02	2.25	234.02	2.25	234.02	.01	423.4000	2.9550	2.9550	2.9550	2.9550	2.9550	2.9550	2.9550	2.9550	366.	366.	366.	366.	366.	366.
11.000	245.5400	2.1716	226.37	2.22	226.37	2.22	226.37	.00	377.9000	2.9410	2.9410	2.9410	2.9410	2.9410	2.9410	2.9410	2.9410	366.	366.	366.	366.	366.	366.
12.000	210.7200	2.0064	219.16	2.27	219.16	2.27	219.16	.06	335.0000	3.2110	3.2110	3.2110	3.2110	3.2110	3.2110	3.2110	3.2110	366.	366.	366.	366.	366.	366.
13.000	180.1300	1.8569	212.71	2.44	212.71	2.44	212.71	.45	295.0000	3.7580	3.7580	3.7580	3.7580	3.7580	3.7580	3.7580	3.7580	365.	365.	365.	365.	365.	365.
14.000	153.2800	1.6274	207.89	2.71	207.89	2.71	207.89	.51	256.9000	4.2260	4.2260	4.2260	4.2260	4.2260	4.2260	4.2260	4.2260	364.	364.	364.	364.	364.	364.
15.000	130.0100	1.3458	204.83	2.90	204.83	2.90	204.83	.21	183.6000	3.4850	3.4850	3.4850	3.4850	3.4850	3.4850	3.4850	3.4850	363.	363.	363.	363.	363.	363.
16.000	110.0300	1.0629	203.35	2.60	203.35	2.60	203.35	.09	159.7000	2.8490	2.8490	2.8490	2.8490	2.8490	2.8490	2.8490	2.8490	359.	359.	359.	359.	359.	359.
17.000	93.1870	.8598	203.34	2.63	203.34	2.63	203.34	.04	134.1000	2.2340	2.2340	2.2340	2.2340	2.2340	2.2340	2.2340	2.2340	358.	358.	358.	358.	358.	358.
18.000	78.9040	.6970	205.08	2.71	205.08	2.71	205.08	-.11	134.1000	2.2340	2.2340	2.2340	2.2340	2.2340	2.2340	2.2340	2.2340	356.	356.	356.	356.	356.	356.
19.000	66.9630	.5790	207.83	2.17	207.83	2.17	207.83	-.20	112.3000	1.6420	1.6420	1.6420	1.6420	1.6420	1.6420	1.6420	1.6420	352.	352.	352.	352.	352.	352.
20.000	56.9630	.4840	210.74	1.83	210.74	1.83	210.74	-.20	94.1700	1.2070	1.2070	1.2070	1.2070	1.2070	1.2070	1.2070	1.2070	347.	347.	347.	347.	347.	347.
21.000	48.5600	.4032	213.50	1.76	213.50	1.76	213.50	-.03	79.2400	.9233	.9233	.9233	.9233	.9233	.9233	.9233	.9233	340.	340.	340.	340.	340.	340.
22.000	41.4730	.3516	216.08	1.83	216.08	1.83	216.08	-.14	66.8700	.7559	.7559	.7559	.7559	.7559	.7559	.7559	.7559	333.	333.	333.	333.	333.	333.
23.000	35.5090	.3104	218.64	1.70	218.64	1.70	218.64	-.10	55.5800	.5500	.5500	.5500	.5500	.5500	.5500	.5500	.5500	320.	320.	320.	320.	320.	320.
24.000	30.4300	.2834	221.05	1.85	221.05	1.85	221.05	.09	47.9600	.4579	.4579	.4579	.4579	.4579	.4579	.4579	.4579	313.	313.	313.	313.	313.	313.
25.000	26.1330	.2575	223.35	1.71	223.35	1.71	223.35	.07	43.7800	.3752	.3752	.3752	.3752	.3752	.3752	.3752	.3752	300.	300.	300.	300.	300.	300.
26.000	22.4920	.2310	225.61	1.60	225.61	1.60	225.61	-.03	34.7300	.3083	.3083	.3083	.3083	.3083	.3083	.3083	.3083	270.	270.	270.	270.	270.	270.
27.000	19.3760	.2027	227.75	1.57	227.75	1.57	227.75	.07	29.6400	.2784	.2784	.2784	.2784	.2784	.2784	.2784	.2784	242.	242.	242.	242.	242.	242.
28.000	16.7120	.1824	229.63	1.54	229.63	1.54	229.63	.18	25.3500	.2518	.2518	.2518	.2518	.2518	.2518	.2518	.2518	231.	231.	231.	231.	231.	231.
29.000	14.4330	.1647	231.43	1.74	231.43	1.74	231.43	.30	21.7300	.2425	.2425	.2425	.2425	.2425	.2425	.2425	.2425	184.	184.	184.	184.	184.	184.
30.000	12.4730	.1479	233.00	1.80	233.00	1.80	233.00	.03	18.6500	.2152	.2152	.2152	.2152	.2152	.2152	.2152	.2152	160.	160.	160.	160.	160.	160.
31.000	9.3240	.1142	235.70	2.80	235.70	2.80	235.70	.10	13.7300	.1853	.1853	.1853	.1853	.1853	.1853	.1853	.1853	122.	122.	122.	122.	122.	122.
32.000	7.0375	.0530	240.90	3.40	240.90	3.40	240.90	.07	10.1700	.1720	.1720	.1720	.1720	.1720	.1720	.1720	.1720	123.	123.	123.	123.	123.	123.
33.000	5.3266	.0259	245.05	3.28	245.05	3.28	245.05	.02	7.5390	.1291	.1291	.1291	.1291	.1291	.1291	.1291	.1291	125.	125.	125.	125.	125.	125.
34.000	4.0543	.0542	249.47	3.93	249.47	3.93	249.47	-.11	5.6610	.1009	.1009	.1009	.1009	.1009	.1009	.1009	.1009	121.	121.	121.	121.	121.	121.
35.000	3.1029	.0469	255.25	3.63	255.25	3.63	255.25	.28	4.2340	.0897	.0897	.0897	.0897	.0897	.0897	.0897	.0897	120.	120.	120.	120.	120.	120.
36.000	2.3009	.0358	260.64	3.74	260.64	3.74	260.64	-.115	3.1950	.0954	.0954	.0954	.0954	.0954	.0954	.0954	.0954	121.	121.	121.	121.	121.	121.
37.000	1.8509	.0325	264.96	3.34	264.96	3.34	264.96	-.69	2.4320	.0457	.0457	.0457	.0457	.0457	.0457	.0457	.0457	120.	120.	120.	120.	120.	120.
38.000	1.4379	.0275	267.38	3.86	267.38	3.86	267.38	-.25	1.8720	.0338	.0338	.0338	.0338	.0338	.0338	.0338	.0338	119.	119.	119.	119.	119.	119.
39.000	1.1192	.0235	269.30	3.94	269.30	3.94	269.30	-.14	1.4500	.0269	.0269	.0269	.0269	.0269	.0269	.0269	.0269	109.	109.	109.	109.	109.	109.
40.000	.8716	.0200	277.60	4.26	277.60	4.26	277.60	-.48	1.1330	.0233	.0233	.0233	.0233	.0233	.0233	.0233	.0233	113.	113.	113.	113.	113.	113.
41.000	.6771	.0162	283.20	4.93	283.20	4.93	283.20	-.108	.8370	.0189	.0189	.0189	.0189	.0189	.0189	.0189	.0189	108.	108.	108.	108.	108.	108.
42.000	.5248	.0123	282.97	5.03	282.97	5.03	282.97	-.50	.6948	.0142	.0142	.0142	.0142	.0142	.0142	.0142	.0142	103.	103.	103.	103.	103.	103.
43.000	.4056	.0117	280.55	5.34	280.55	5.34	280.55	-.22	.5424	.0126	.0126	.0126	.0126	.0126	.0126	.0126	.0126	92.	92.	92.	92.	92.	92.
44.000	.3120	.0095	286.69	4.47	286.69	4.47	286.69	-.06	.4233	.0098	.0098	.0098	.0098	.0098	.0098	.0098	.0098	76.	76.	76.	76.	76.	76.
45.000	.2369	.0081	291.01	4.98	291.01	4.98	291.01	.73	.3314	.0096	.0096	.0096	.0096	.0096	.0096	.0096	.0096	59.	59.	59.	59.	59.	59.
46.000	.1828	.0062	244.02	6.93	244.02	6.93	244.02	.40	.2610	.0079	.0079	.0079	.0079	.0079	.0079	.0079	.0079	35.	35.	35.	35.	35.	35.
47.000	.1359	.0027	230.63	5.38	230.63	5.38	230.63	.32	.2013	.0046	.0046	.0046	.0046	.0046	.0046	.0046	.0046	20.	20.	20.	20.	20.	20.
48.000	.1013	.0017	230.90	4.43	230.90	4.43	230.90	.30	.1574	.0027	.0027	.0027	.0027	.0027	.0027	.0027	.0027	19.	19.	19.	19.	19.	19.
49.000	.0747	.0016	212.73																				

TABLE II-6. THERMODYNAMIC STATISTICAL PARAMETERS

JUNE

STATION - 911626	MEAN P	DATAING SAMS.HI	MEAN T	S.D. T	SKEN T	MEAN D	S.D. D	SKEN D	MOBS P	MOBS T	MOBS D
Z	MB	S.D. P	DEG K	DEG K		C/M3	C/M3				
1.000	1017.3000	1.6534	-1.45	1.51	.48	1175.0000	6.4030	-.41	343.	343.	343.
.005	1016.7000	1.6757	-1.43	1.49	.42	1175.0000	6.2120	-.39	370.	370.	370.
1.000	905.7400	1.4053	-1.48	1.52	-.07	1081.0000	4.6030	.08	370.	370.	370.
2.000	605.9700	1.5190	-1.40	2.05	.20	978.0000	6.4030	-.20	370.	370.	370.
3.000	715.1900	1.5748	-.27	2.02	-.08	879.5000	5.6140	-.20	370.	370.	370.
4.000	633.4200	1.7510	-.22	2.77	-.08	794.1000	4.9330	.02	370.	370.	370.
5.000	559.6500	1.8467	-.05	2.71	-.36	717.1000	4.7080	.39	370.	370.	370.
6.000	493.0100	1.7733	.02	2.94	-.51	647.0000	4.6950	.38	370.	370.	370.
7.000	432.7600	1.9503	.60	2.77	-.53	574.5000	4.2710	.24	370.	370.	370.
8.000	375.5000	2.0333	.60	2.50	-.33	505.1000	3.6130	-.11	369.	369.	369.
9.000	329.8600	2.0544	-.09	2.42	-.27	472.3000	2.9330	-.15	369.	369.	369.
10.000	286.1000	2.0536	-.11	2.35	-.15	423.5000	2.7900	-.21	368.	368.	368.
11.000	247.1200	2.0348	-.15	2.27	.06	378.5000	2.3740	-.23	368.	368.	368.
12.000	212.1700	1.8763	-.07	2.20	.09	336.0000	2.5390	-.71	367.	367.	367.
13.000	181.4800	1.7355	.02	2.13	.24	295.4000	3.1100	-.09	367.	367.	367.
14.000	154.4800	1.5069	.19	2.08	.32	259.3000	3.6090	-.60	365.	365.	365.
15.000	131.1000	1.2515	.28	2.05	.21	222.3000	3.9090	-.10	365.	365.	365.
16.000	111.0800	1.0149	.29	2.04	.01	189.1000	3.7130	.17	364.	364.	364.
17.000	94.0310	.8225	.26	2.04	-.18	160.4000	2.4130	.28	364.	364.	364.
18.000	79.7420	.6559	.26	2.05	.11	134.9000	1.9460	.30	360.	360.	360.
19.000	67.7140	.5534	.60	2.02	-.12	113.1000	1.3730	.30	352.	352.	352.
20.000	57.0200	.4693	-.05	2.11	-.16	94.5000	.9607	.25	345.	345.	345.
21.000	49.1320	.4001	-.11	2.14	.03	79.5000	.7130	.05	340.	340.	340.
22.000	41.7330	.3009	-.16	2.16	.09	67.5100	.6516	.19	337.	337.	337.
23.000	35.8690	.2152	-.12	2.13	-.05	57.1000	.5043	.17	321.	321.	321.
24.000	30.0300	.2770	-.13	2.21	.11	48.0000	.4005	.00	319.	319.	319.
25.000	26.4930	.2474	-.13	2.23	-.09	41.2500	.4167	.07	304.	304.	304.
26.000	22.6030	.2182	-.09	2.25	-.10	35.1800	.3351	-.04	281.	281.	281.
27.000	19.0400	.1987	.04	2.27	-.10	30.0500	.2912	.02	238.	238.	238.
28.000	16.9250	.1714	-.19	2.29	.08	25.7000	.2346	.14	221.	221.	221.
29.000	14.6310	.1531	-.08	2.30	.34	22.0700	.2241	.03	178.	178.	178.
30.000	12.5440	.1355	-.25	2.32	-.66	19.5000	.1911	.00	153.	153.	153.
32.000	9.4126	.1457	.09	2.35	.58	13.9200	.2414	.16	109.	109.	109.
34.000	7.0655	.1181	.38	2.32	-.23	10.3100	.1549	-.10	113.	113.	113.
36.000	5.3520	.1011	.56	2.44	-.64	7.0000	.1440	.24	111.	111.	111.
38.000	4.0764	.0839	.70	2.48	.05	5.7040	.1224	.23	109.	109.	109.
40.000	3.1169	.0680	.89	2.54	.33	4.2620	.1027	-.17	109.	109.	109.
42.000	2.4014	.0550	.91	2.60	-.72	3.2090	.0757	.61	107.	107.	107.
44.000	1.8590	.0446	.90	2.65	-.53	2.4430	.0555	.42	108.	108.	108.
46.000	1.4427	.0361	.92	2.65	-.71	1.8530	.0437	.50	106.	106.	106.
48.000	1.1220	.0297	.91	2.67	.01	1.4590	.0365	.75	104.	104.	104.
50.000	.8719	.0237	.94	2.65	-.18	1.1370	.0297	.69	97.	97.	97.
52.000	.6775	.0195	.69	2.65	-.50	.8905	.0232	.79	100.	100.	100.
54.000	.5357	.0153	.78	2.65	-.33	.6371	.0185	.51	97.	97.	97.
56.000	.4059	.0132	.73	2.63	-.13	.5474	.0147	.46	87.	87.	87.
58.000	.3125	.0118	.72	2.63	-.32	.4300	.0114	-.06	72.	72.	72.
60.000	.2375	.0090	1.28	2.48	.12	.3330	.0087	.47	47.	47.	47.
62.000	.1796	.0060	.29	2.44	.24	.2546	.0066	-.65	28.	28.	28.
64.000	.1318	.0021	-.02	2.33	-.33	.1659	.0052	.32	12.	12.	12.
66.000	.0936	.0018	.12	2.55	.18	.1514	.0039	-.72	13.	13.	13.
68.000	.0730	.0015	.05	2.12	.41	.1189	.0033	-.45	13.	13.	13.
70.000	.0532	.0013	-.12	2.09	-.98	.0897	.0030	-.04	13.	13.	13.

TABLE II-8. THERMODYNAMIC STATISTICAL PARAMETERS

AUGUST

STATION - 511520 Z	MEAN P HG	SATKING SAIGS.MI S.D. P HG	MEAN T C° K	S.D. T DEG K	SKREW T	MEAN D G/M3	S.D. D G/M3	SKCH D	NOBS P	NOBS T	NOBS D
.000	1016.1000	1.5374	293.40	1.18	.36	1172.0000	5.2650	-.27	385.	385.	385.
.005	1015.6000	1.6047	292.35	1.19	.34	1172.0000	5.2360	-.25	393.	393.	393.
.010	905.0700	1.4105	291.44	.94	-.52	1076.0000	4.3140	-.19	393.	393.	393.
.015	805.7100	1.2173	293.59	1.80	.34	975.7000	5.5270	-.24	392.	392.	392.
.020	715.0100	1.3331	292.45	1.67	.62	830.6000	4.7300	-.10	392.	392.	392.
.025	633.2100	1.3331	277.50	1.67	.03	773.0000	4.6100	-.12	391.	391.	391.
.030	553.5100	1.3752	271.97	1.77	.13	715.0000	4.5100	-.13	391.	391.	391.
.035	493.0500	1.4718	265.68	1.65	-.10	695.7000	3.8730	-.27	391.	391.	391.
.040	443.0000	1.5205	258.63	1.67	-.75	593.1000	3.3440	-.17	390.	390.	390.
.045	379.0100	1.6507	251.50	1.91	-.28	529.4000	2.9040	-.11	390.	390.	390.
.050	330.4200	1.7422	243.98	1.90	-.28	471.4000	2.6490	-.39	385.	385.	385.
.055	285.7800	1.7606	238.24	1.95	-.26	422.5000	2.5340	-.61	383.	383.	383.
.060	247.8000	1.7651	233.50	1.93	-.22	377.0000	2.2010	-.47	382.	382.	382.
.065	212.9500	1.6803	221.03	1.87	-.17	335.7000	2.1220	-.59	382.	382.	382.
.070	182.2800	1.5371	214.22	1.77	.03	295.4000	2.5490	-.70	382.	382.	382.
.075	155.2600	1.3594	203.91	2.03	.37	259.0000	3.4370	-.65	378.	378.	378.
.080	131.7900	1.1497	203.65	2.45	.21	223.3000	3.7940	-.28	376.	376.	376.
.085	111.6900	.9027	204.60	2.43	-.19	190.2000	3.1350	.08	376.	376.	376.
.090	94.5420	.7192	203.10	2.01	-.45	160.8000	2.1050	.20	375.	375.	375.
.095	80.2670	.6042	205.91	1.65	-.29	135.2000	1.5110	-.18	374.	374.	374.
.100	69.2110	.5092	209.16	1.46	-.15	113.6000	1.1340	-.05	369.	369.	369.
.105	58.0690	.4417	211.60	1.51	-.17	95.6100	.8977	.00	366.	366.	366.
.110	49.5210	.3630	214.07	1.47	.16	80.5900	.7232	-.06	362.	362.	362.
.115	42.3230	.3167	213.29	1.44	-.18	68.1600	.6091	.14	359.	359.	359.
.120	36.2270	.3083	218.39	1.50	-.21	57.7900	.5152	.32	345.	345.	345.
.125	31.0390	.2902	220.44	1.65	.05	49.0500	.4487	.14	339.	339.	339.
.130	26.6420	.2548	222.55	1.54	-.13	41.7100	.3788	.11	315.	315.	315.
.135	22.9020	.2272	224.47	1.55	-.07	35.5400	.3302	.07	283.	283.	283.
.140	19.7100	.2048	226.15	1.62	-.23	30.3600	.3059	.18	249.	249.	249.
.145	16.9340	.1837	227.75	1.59	-.08	25.9300	.2591	.27	240.	240.	240.
.150	14.6470	.1675	229.21	1.63	-.03	22.2500	.2261	.20	210.	210.	210.
.155	12.6450	.1533	230.61	1.50	.03	19.0400	.1967	.50	191.	191.	191.
.160	9.3914	.1430	233.64	2.06	.63	14.0100	.2009	-.58	119.	123.	117.
.165	7.0345	.1148	237.75	3.24	.22	10.5300	.1544	-.31	120.	124.	120.
.170	5.3760	.1012	242.02	3.42	.00	7.6230	.1340	-.33	121.	126.	121.
.175	4.0445	.0812	246.54	3.91	-.00	5.7130	.1127	.18	121.	126.	121.
.180	3.0081	.0701	252.14	4.20	-.10	4.4340	.0917	.73	122.	127.	122.
.185	2.3719	.0581	257.05	4.43	.38	3.7910	.0819	-.15	121.	126.	121.
.190	1.8208	.0445	263.98	4.67	-.55	2.9420	.0591	.10	120.	125.	120.
.195	1.4114	.0393	263.73	3.46	-.19	1.8700	.0470	.42	121.	125.	121.
.200	1.0394	.0318	264.07	5.16	-.03	1.4440	.0421	-.14	120.	124.	120.
.205	.8533	.0260	265.05	5.81	-.02	1.1210	.0305	.19	118.	122.	118.
.210	.6612	.0216	264.33	4.93	-.45	.8705	.0232	-.10	113.	117.	113.
.215	.5119	.0173	261.88	4.81	-.44	.6803	.0186	-.29	110.	113.	110.
.220	.3945	.0148	259.35	6.48	-.37	.5293	.0174	-.24	98.	100.	98.
.225	.3042	.0120	256.55	7.00	.59	.4130	.0144	-.67	82.	82.	78.
.230	.2319	.0097	252.95	7.24	-.55	.3154	.0121	-.22	41.	45.	41.
.235	.1748	.0069	244.53	6.00	.69	.2463	.0063	.50	28.	30.	28.
.240	.1337	.0024	238.65	7.70	1.43	.1908	.0059	-.81	24.	24.	24.
.245	.0833	.0022	229.21	6.34	-.68	.1402	.0036	-.19	22.	22.	22.
.250	.0731	.0021	217.21	7.64	.18	.1171	.0034	.06	20.	20.	20.
.255	.0535	.0019	211.21	5.89	.28	.0881	.0026	-.13	19.	19.	19.

TABLE II-9. THERMODYNAMIC STATISTICAL PARAMETERS

SEPTEMBER

STATION = 911620				BARKING SAMOS. HI				S.D. T		SKEW T		MEAN D		S.D. D		NOBS P		NOBS T		NOBS D	
Z	MEAN P	S.D. P	SKEW P	MEAN T	S.D. T	SKEW T	MEAN D	S.D. D	SKEW D	NOBS P	NOBS T	NOBS D									
MI	MI	MI		DEG K	DEG K		G/H3	G/H3													
.000	1015.5000	1.6088	-.01	298.97	1.18	.14	1173.0000	5.5860	-.09	352.	352.	352.									
.005	1014.9000	1.6049	-.01	298.93	1.19	.14	1173.0000	5.5390	-.10	361.	361.	361.									
1.000	905.5200	1.4225	-.13	291.64	.93	-.55	1075.0000	4.1110	.50	361.	361.	361.									
2.000	805.1800	1.3211	-.19	286.41	1.57	.25	975.4000	4.7480	.00	361.	361.	361.									
3.000	714.6000	1.2868	-.17	282.75	1.75	-.02	878.5000	5.0280	-.05	361.	361.	361.									
4.000	632.9500	1.4067	-.29	277.79	1.74	-.28	792.4000	4.6020	.09	351.	361.	361.									
5.000	559.3100	1.4816	-.30	272.01	1.69	-.27	715.2000	4.0750	-.08	361.	361.	361.									
6.000	492.8600	1.5752	-.35	265.50	1.79	-.39	645.6000	3.7820	.01	361.	361.	361.									
7.000	432.7700	1.6544	-.42	250.54	1.88	-.29	562.5000	3.4520	-.18	361.	361.	361.									
8.000	378.7400	1.7538	-.36	251.13	1.97	-.15	524.8000	3.2220	-.29	360.	360.	360.									
9.000	330.1100	1.8398	-.33	243.52	2.11	-.14	471.8000	2.9310	-.43	360.	360.	360.									
10.000	286.4200	1.8827	-.32	235.80	2.14	-.09	422.8000	2.6550	-.62	359.	359.	359.									
11.000	247.4900	1.9021	-.29	228.13	2.09	.00	377.9000	2.2970	-.63	358.	358.	358.									
12.000	212.6000	1.7983	-.19	220.89	1.99	.23	335.3000	2.5660	-.74	357.	357.	357.									
13.000	181.9700	1.6912	-.13	214.26	2.02	.02	295.9000	3.0360	-.59	357.	357.	357.									
14.000	154.9800	1.4973	-.05	208.87	1.95	.20	258.5000	3.3530	-.32	356.	356.	356.									
15.000	131.5400	1.2532	.02	205.31	2.24	-.09	223.2000	3.5780	-.02	355.	355.	355.									
16.000	111.4100	1.0105	.02	203.47	2.33	-.14	190.8000	3.1470	.22	354.	354.	354.									
17.000	94.3150	.8195	-.04	203.51	2.27	-.49	161.4000	2.5340	.58	354.	354.	354.									
18.000	79.8980	.6812	-.03	205.84	1.85	-.18	135.2000	1.7230	.29	354.	354.	354.									
19.000	67.8430	.5783	.02	208.35	1.64	-.08	113.4000	1.2520	.21	349.	349.	349.									
20.000	57.7240	.5060	.00	211.04	1.59	.21	95.2900	1.0130	.09	347.	347.	347.									
21.000	49.2120	.4428	-.02	213.50	1.50	.41	80.3000	.8075	.21	341.	341.	341.									
22.000	42.0360	.3960	-.05	215.90	1.51	.23	67.8300	.6573	.00	338.	338.	338.									
23.000	35.9750	.3489	-.05	218.18	1.56	.21	57.4400	.5353	.06	330.	330.	330.									
24.000	30.8230	.3119	.10	220.32	1.70	-.08	48.7400	.4573	.06	325.	325.	325.									
25.000	26.4520	.2769	.11	222.32	1.69	-.11	41.4500	.3583	-.21	306.	306.	306.									
26.000	22.7440	.2444	.48	224.20	1.68	.21	35.3400	.3421	.21	281.	281.	281.									
27.000	19.5610	.2199	.63	225.97	1.83	.39	30.1600	.3389	.20	249.	249.	249.									
28.000	16.8560	.1975	.66	227.70	1.64	.36	25.7500	.2973	.47	238.	238.	238.									
29.000	14.5430	.1810	.72	229.44	1.73	.56	22.0800	.2724	.51	186.	186.	186.									
30.000	12.4530	.1536	.65	231.12	1.93	.38	18.9200	.2272	.35	162.	162.	162.									
31.000	9.3330	.1323	.03	234.15	3.35	-.01	13.8900	.2030	-.20	98.	100.	97.									
32.000	7.0149	.1063	.41	233.34	3.40	.24	10.2500	.1427	-.05	99.	101.	99.									
33.000	5.3004	.0999	.24	242.39	3.73	-.35	7.6170	.1264	-.12	100.	102.	100.									
34.000	4.0266	.0907	.66	246.93	3.65	-.61	5.6790	.1005	-.10	100.	103.	100.									
35.000	3.0742	.0673	.71	252.08	4.12	.03	4.2450	.0901	.11	101.	104.	101.									
36.000	2.3614	.0557	.71	258.22	4.32	-.03	3.1850	.0795	.45	101.	104.	101.									
37.000	1.8248	.0459	.63	262.69	4.89	-.49	2.4170	.0623	.31	101.	104.	101.									
38.000	1.4163	.0383	.69	266.47	3.93	.29	1.8500	.0432	.55	99.	99.	99.									
39.000	1.1002	.0323	.32	267.77	4.43	-.87	1.4310	.0374	.26	97.	97.	97.									
40.000	.8555	.0259	.58	267.22	4.38	-.70	1.1150	.0272	.40	95.	93.	96.									
41.000	.6653	.0218	.53	266.14	4.54	-.75	.8711	.0225	.57	96.	95.	96.									
42.000	.5174	.0186	.48	264.23	5.11	-.52	.6818	.0183	.21	91.	94.	91.									
43.000	.4008	.0154	.20	260.92	5.30	-.44	.5349	.0151	.17	84.	87.	84.									
44.000	.3091	.0129	.26	257.48	5.20	-.28	.4179	.0141	-.32	72.	75.	72.									
45.000	.2391	.0113	.20	253.53	6.30	-.44	.3201	.0122	-.24	47.	49.	47.									
46.000	.1805	.0095	.72	245.75	8.51	-.41	.2561	.0100	.60	28.	29.	28.									
47.000	.1323	.0034	.50	237.69	4.03	-.10	.1937	.0035	.51	15.	15.	15.									
48.000	.0874	.0025	.19	230.15	3.46	.78	.1522	.0040	.40	14.	14.	14.									
49.000	.0732	.0021	-.71	214.87	4.84	-.60	.1185	.0030	.15	14.	14.	14.									
50.000	.0533	.0015	-.84	19.80	4.85	.65	.0885	.0040	-.81	14.	14.	14.									

TABLE II-10. THERMODYNAMIC STATISTICAL PARAMETERS

OCTOBER

STATION - 911620 Z KM	MEAN P MB	BARKING SANDS, HI S.D. P MB	MEAN T DEG K	S.D. T DEG K	SKIN T	MEAN D G/M3	S.D. D G/M3	SKIN D	NOBS P	NOBS T	NOBS D
.000	1015.6000	1.6339	293.21	1.66	.17	1177.0000	7.6260	-.13	370.	370.	370.
.005	1015.6000	1.9463	292.18	1.75	.15	1176.0000	7.0350	-.14	377.	377.	377.
1.000	905.4700	1.7453	291.30	1.07	.01	1075.0000	4.6270	-.33	377.	377.	377.
2.000	805.0500	1.6175	283.33	1.77	.13	975.7000	5.3120	-.02	377.	377.	377.
3.000	714.4700	1.6105	262.55	1.64	-.37	879.1000	5.1790	.21	377.	377.	377.
4.000	632.7400	1.7230	277.32	1.94	-.33	793.6000	4.9710	.19	377.	377.	377.
5.000	559.0000	1.7539	271.39	2.03	-.50	716.7000	4.5090	.38	377.	377.	377.
6.000	492.4400	1.8235	264.95	2.12	-.33	646.8000	4.0530	.06	377.	377.	377.
7.000	432.2600	2.0255	267.59	2.26	-.31	533.3000	3.7220	-.07	377.	377.	377.
8.000	378.2100	2.1031	250.64	2.32	-.30	523.3000	3.3530	-.08	377.	377.	377.
9.000	329.5800	2.1575	243.11	2.30	-.23	472.0000	3.0950	-.05	376.	376.	376.
10.000	285.6900	2.1756	235.41	2.30	-.21	422.6000	2.8960	-.32	376.	376.	376.
11.000	245.9600	2.1457	227.88	2.45	-.20	377.6000	3.1220	-.59	376.	376.	376.
12.000	212.1400	2.0179	220.69	2.47	-.26	334.9000	3.2300	-.75	375.	375.	375.
13.000	181.5400	1.9052	214.08	2.48	-.25	295.4000	3.4630	-.51	375.	375.	375.
14.000	154.6000	1.7178	206.64	2.31	-.21	259.2000	3.6110	-.36	374.	374.	374.
15.000	131.1600	1.4748	204.30	2.24	-.06	223.7000	3.6450	-.18	372.	372.	372.
16.000	110.5600	1.2010	201.59	2.50	.25	191.7000	3.6770	-.22	371.	371.	371.
17.000	93.7790	.9522	201.35	2.63	.07	162.5000	3.4130	-.03	370.	370.	370.
18.000	79.2650	.7184	203.42	2.91	-.21	135.8000	2.6110	.09	366.	366.	366.
19.000	67.2080	.5744	206.81	2.45	-.10	113.2000	1.7410	-.06	359.	359.	359.
20.000	57.1290	.4305	209.95	2.01	.13	94.8000	1.1670	-.22	354.	354.	354.
21.000	48.6580	.4310	212.79	1.85	.34	79.6100	.9073	-.20	345.	345.	345.
22.000	41.5480	.3664	215.43	1.85	.49	67.1900	.7317	-.24	341.	341.	341.
23.000	35.5480	.3453	217.74	1.79	.52	56.6800	.5318	-.12	331.	331.	331.
24.000	30.4450	.3130	219.60	1.95	.34	48.7400	.5202	-.22	324.	324.	324.
25.000	26.1210	.2775	221.75	2.09	.20	41.0400	.4445	-.33	306.	306.	306.
26.000	22.4450	.2517	223.73	2.15	.20	34.0500	.3590	-.24	274.	274.	274.
27.000	19.3090	.2293	225.67	2.28	.04	29.8100	.3052	.07	244.	244.	244.
28.000	16.6360	.2136	227.35	2.40	-.04	25.4900	.2753	-.11	236.	236.	236.
29.000	14.3540	.2033	229.29	2.74	.11	21.8100	.2517	-.22	184.	184.	184.
30.000	12.3980	.1951	231.16	2.79	-.01	18.6300	.2165	-.04	168.	168.	168.
32.000	9.2180	.1480	234.67	3.79	-.23	13.6900	.1597	-.37	100.	100.	100.
34.000	6.9368	.1294	237.49	4.23	-.58	10.1700	.1616	.44	100.	100.	100.
36.000	5.2267	.1171	241.67	4.08	-.28	7.5370	.1678	.46	101.	101.	101.
38.000	3.9698	.0931	246.46	5.33	-.44	5.6150	.1398	.19	102.	102.	102.
40.000	3.0225	.0754	252.49	4.58	-.72	4.1830	.1107	.65	102.	102.	102.
42.000	2.3593	.0611	259.27	4.89	-.51	3.1410	.0868	.75	102.	102.	102.
44.000	1.8006	.0499	263.62	5.02	-.54	2.3780	.0639	.88	102.	102.	102.
46.000	1.3978	.0408	266.60	4.38	.05	1.8240	.0506	.55	102.	102.	102.
48.000	1.0867	.0360	268.01	4.63	-.09	1.4100	.0402	.59	102.	102.	102.
50.000	.8475	.0293	267.31	4.47	-.68	1.1030	.0345	1.06	100.	100.	100.
52.000	.6632	.0253	265.16	4.71	-.01	.6670	.0321	1.19	98.	98.	98.
54.000	.5118	.0194	263.44	4.50	.74	.6765	.0211	.02	94.	94.	94.
56.000	.3560	.0162	250.35	4.83	-.27	.5300	.0198	.18	88.	88.	88.
58.000	.3059	.0132	256.01	5.89	-.66	.4162	.0159	.67	77.	77.	77.
60.000	.2340	.0096	251.05	5.87	-.51	.3234	.0103	-.07	52.	52.	52.
62.000	.1779	.0083	246.12	9.24	1.60	.2516	.0115	-.15	29.	29.	29.
64.000	.1332	.0062	237.27	6.14	-.37	.1954	.0048	.65	18.	18.	18.
66.000	.0991	.0042	227.83	4.93	-.34	.1513	.0055	.01	18.	18.	18.
68.000	.0730	.0029	214.27	6.38	.93	.1165	.0054	-.37	18.	18.	18.
70.000	.0533	.0022	203.72	7.00	-.40	.0895	.0040	-.27	18.	18.	18.

TABLE II-11. THERMODYNAMIC STATISTICAL PARAMETERS

NOVEMBER

STATION = 911620		BARKING SANDS, HI		S.D. T		SKEW T		MEAN D		S.D. D		SKEW D		NOBS P		NOBS T		NOBS D	
Z	KB	MEAN P	HB	DEG K	DEG K	DEG K	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3	G/M3
.000	1015.9000	2.5917	-1.02	1.79	256.24	.37	1185.0000	8.9160	-.56	327.	327.	327.	327.	327.	327.	327.	327.	327.	327.
.005	1015.4000	2.5795	-1.00	1.79	296.19	-.29	1185.0000	8.9450	-.45	346.	346.	346.	346.	346.	346.	346.	346.	346.	346.
1.000	905.4100	2.2396	-1.05	1.47	290.31	-.65	1080.0000	6.4330	.12	346.	346.	346.	346.	346.	346.	346.	346.	346.	346.
2.000	804.6300	2.1048	-.80	2.23	285.63	-.26	930.0000	7.2530	.10	346.	346.	346.	346.	346.	346.	346.	346.	346.	346.
3.000	713.9300	2.0953	-.80	2.24	281.94	-.09	930.0000	6.1150	-.19	346.	346.	346.	346.	346.	346.	346.	346.	346.	346.
4.000	632.0400	2.2458	-.65	2.34	276.69	-.32	794.5000	5.6430	.14	345.	345.	345.	345.	345.	345.	345.	345.	345.	345.
5.000	598.2600	2.2974	-.61	2.27	270.79	-.40	717.1000	4.9300	.01	344.	344.	344.	344.	344.	344.	344.	344.	344.	344.
6.000	491.6300	2.4142	-.56	2.35	264.27	-.37	647.1000	4.5530	-.12	344.	344.	344.	344.	344.	344.	344.	344.	344.	344.
7.000	431.4300	2.5158	-.60	2.39	257.36	-.51	593.2000	4.0400	-.22	344.	344.	344.	344.	344.	344.	344.	344.	344.	344.
8.000	377.3500	2.5065	-.58	2.42	250.05	-.44	525.1000	3.6010	-.53	344.	344.	344.	344.	344.	344.	344.	344.	344.	344.
9.000	328.7000	2.5462	-.61	2.49	242.43	-.24	471.8000	3.3370	-.62	344.	344.	344.	344.	344.	344.	344.	344.	344.	344.
10.000	285.0100	2.5253	-.62	2.54	234.76	-.10	422.5000	3.4390	-.67	343.	343.	343.	343.	343.	343.	343.	343.	343.	343.
11.000	246.1300	2.4694	-.59	2.54	227.35	-.10	377.2000	3.3950	-.77	343.	343.	343.	343.	343.	343.	343.	343.	343.	343.
12.000	211.3600	2.2834	-.49	2.59	220.32	-.01	334.2000	3.6270	-.88	343.	343.	343.	343.	343.	343.	343.	343.	343.	343.
13.000	180.8400	2.1276	-.38	2.71	213.83	-.33	294.6000	3.9670	-.81	343.	343.	343.	343.	343.	343.	343.	343.	343.	343.
14.000	153.9700	1.9102	-.28	2.72	208.37	-.45	257.4000	4.0820	-.59	341.	341.	341.	341.	341.	341.	341.	341.	341.	341.
15.000	130.5600	1.6606	-.25	2.49	203.58	.02	223.5000	3.6370	-.52	340.	340.	340.	340.	340.	340.	340.	340.	340.	340.
16.000	110.3500	1.3856	-.24	2.53	200.33	.45	191.9000	3.8320	-.34	338.	338.	338.	338.	338.	338.	338.	338.	338.	338.
17.000	93.1320	1.0950	-.27	2.72	193.12	.32	163.0000	3.4720	-.21	337.	337.	337.	337.	337.	337.	337.	337.	337.	337.
18.000	78.5770	.8521	-.36	2.97	200.65	.39	130.5000	2.9510	-.17	337.	337.	337.	337.	337.	337.	337.	337.	337.	337.
19.000	66.4820	.6764	-.50	2.05	204.67	.26	113.2000	2.0400	-.06	332.	332.	332.	332.	332.	332.	332.	332.	332.	332.
20.000	56.4340	.5653	-.73	2.05	208.62	.04	94.2500	1.3070	.08	327.	327.	327.	327.	327.	327.	327.	327.	327.	327.
21.000	48.0390	.4929	-.87	1.63	211.63	.03	79.0500	.8230	.14	320.	320.	320.	320.	320.	320.	320.	320.	320.	320.
22.000	40.9710	.4403	-.89	1.92	214.31	.07	66.6000	.7831	-.24	318.	318.	318.	318.	318.	318.	318.	318.	318.	318.
23.000	35.0330	.3908	-.87	1.93	216.77	-.08	56.3000	.6015	-.65	309.	309.	309.	309.	309.	309.	309.	309.	309.	309.
24.000	29.9820	.3548	-.77	2.17	219.01	-.09	47.6900	.5373	-.78	304.	304.	304.	304.	304.	304.	304.	304.	304.	304.
25.000	25.7070	.3255	-.67	2.20	220.92	-.23	40.5400	.5212	-.74	294.	294.	294.	294.	294.	294.	294.	294.	294.	294.
26.000	22.0770	.2951	-.61	2.29	222.63	-.05	34.5500	.4504	-.80	278.	278.	278.	278.	278.	278.	278.	278.	278.	278.
27.000	18.9720	.2540	-.51	2.46	224.45	.20	29.4500	.3678	-.60	255.	255.	255.	255.	255.	255.	255.	255.	255.	255.
28.000	16.3280	.2398	-.41	2.68	223.32	.00	25.1300	.3223	-.62	250.	250.	250.	250.	250.	250.	250.	250.	250.	250.
29.000	14.0740	.2114	-.22	2.73	227.92	.09	21.5100	.2598	-.43	197.	197.	197.	197.	197.	197.	197.	197.	197.	197.
30.000	12.1170	.1825	-.25	2.73	223.31	.04	18.4100	.2355	-.23	165.	165.	165.	165.	165.	165.	165.	165.	165.	165.
32.000	9.0482	.1604	-.61	4.17	233.32	.07	13.5500	.2223	.24	85.	85.	85.	85.	85.	85.	85.	85.	85.	85.
34.000	6.8018	.1361	-.35	4.91	230.91	.06	10.0100	.1960	-.16	83.	83.	83.	83.	83.	83.	83.	83.	83.	83.
36.000	5.1311	.1082	-.09	4.91	240.71	.13	7.4340	.1891	.01	85.	85.	85.	85.	85.	85.	85.	85.	85.	85.
38.000	3.8933	.0791	-.04	5.33	245.92	.41	5.5260	.1604	.25	83.	83.	83.	83.	83.	83.	83.	83.	83.	83.
40.000	2.9282	.0616	-.12	6.07	251.37	-.98	4.1160	.1169	.88	83.	83.	83.	83.	83.	83.	83.	83.	83.	83.
42.000	2.2755	.0495	-.05	4.85	255.23	-.40	3.0930	.0829	.24	82.	82.	82.	82.	82.	82.	82.	82.	82.	82.
44.000	1.7556	.0403	-.03	4.65	261.74	-.20	2.3350	.0559	.20	83.	83.	83.	83.	83.	83.	83.	83.	83.	83.
46.000	1.3612	.0343	-.18	5.51	265.70	-.84	1.7840	.0419	-.01	82.	82.	82.	82.	82.	82.	82.	82.	82.	82.
48.000	1.0580	.0293	-.45	4.87	267.51	-.32	1.3780	.0280	-.04	80.	80.	80.	80.	80.	80.	80.	80.	80.	80.
50.000	.8232	.0240	-.50	5.37	267.32	-.76	1.0720	.0275	-.02	79.	79.	79.	79.	79.	79.	79.	79.	79.	79.
52.000	.6405	.0204	-.52	5.11	265.67	-.55	.8390	.0228	-.28	77.	77.	77.	77.	77.	77.	77.	77.	77.	77.
54.000	.4973	.0173	-.37	5.79	261.07	-.65	.6359	.0179	-.92	76.	76.	76.	76.	76.	76.	76.	76.	76.	76.
56.000	.3959	.0147	-.24	6.29	261.65	-.65	.5135	.0173	-.13	69.	69.	69.	69.	69.	69.	69.	69.	69.	69.
58.000	.2933	.0123	-.04	6.50	250.09	-.21	.4025	.0125	-.93	61.	61.	61.	61.	61.	61.	61.	61.	61.	61.
60.000	.2292	.0109	-.09	5.82	255.29	-.66	.3128	.0119	-.46	44.	44.	44.	44.	44.	44.	44.	44.	44.	44.
62.000	.1750	.0078	-.45	5.71	249.99	-.12	.2435	.0029	-.07	22.	22.	22.	22.	22.	22.	22.	22.	22.	22.
64.000	.1293	.0041	-.31	3.15	252.78	.08	.1597	.0062	-.07	13.	13.	13.	13.	13.	13.	13.	13.	13.	13.
66.000	.0979	.0032	-.30	6.22	253.08	-.03	.1463	.0034	-.39	13.	13.	13.	13.	13.	13.	13.	13.	13.	13.
68.000	.0731	.0025	-.61	8.31	217.73	-.10	.1164	.0045	.64	14.	14.	14.	14.	14.	14.	14.	14.	14.	14.
70.000	.0533	.0021	-.35	4.34	210.33	-.21	.0862	.0029	-.55	12.	12.	12.	12.	12.	12.	12.	12.	12.	12.

TABLE II-13. THERMODYNAMIC STATISTICAL PARAMETERS

ANNUAL

STATION - 911620	MEAN P	STANDARD DEVIATION	MEAN T	S.D. T	MEAN D	S.D. D	SKEN D	NOBS P	NOBS T	NOBS D
Z	MB	PS	DEG K	DEG K	G/H3	G/H3				
.000	1016.5000	2.6578	256.96	2.79	1183.0000	12.6400	.58	4124.	4124.	4124.
.005	1015.9000	2.6928	256.87	2.84	1183.0000	12.6300	.61	4336.	4336.	4336.
1.000	965.7630	2.3850	239.83	1.87	1083.0000	7.7400	.41	4336.	4336.	4336.
2.000	894.8330	2.3441	265.14	2.40	979.9000	7.4700	.27	4334.	4334.	4334.
3.000	713.6100	2.4255	231.27	2.39	892.5000	6.4700	.08	4334.	4334.	4334.
4.000	641.0100	2.5622	275.10	2.53	765.0500	5.9700	.09	4330.	4330.	4330.
5.000	567.7100	2.7002	278.29	2.70	719.2000	5.5200	.14	4349.	4349.	4349.
6.000	491.1700	2.8432	265.74	2.68	608.1000	5.1000	.02	4348.	4348.	4348.
7.000	430.4100	3.0449	255.73	3.02	534.1000	4.5900	.13	4346.	4346.	4346.
8.000	376.7100	3.1150	249.44	3.11	505.7000	4.1500	.39	4318.	4318.	4318.
9.000	329.0500	3.1944	242.03	3.13	471.9000	4.0100	.66	4308.	4308.	4308.
10.000	284.4400	3.1646	234.63	3.08	422.1000	4.2300	-.21	4299.	4299.	4299.
11.000	245.6200	3.0597	227.42	2.99	376.5000	4.4100	-.32	4291.	4291.	4291.
12.000	210.6000	2.7714	220.60	2.87	333.2000	4.7500	-.24	4286.	4286.	4286.
13.000	180.9400	2.4589	214.57	2.73	293.4000	4.9500	-.93	4276.	4276.	4276.
14.000	153.8000	2.1523	209.16	2.66	256.2000	4.9200	-.71	4254.	4254.	4254.
15.000	130.9400	1.8003	205.12	2.76	221.7000	4.5700	-.39	4241.	4241.	4241.
16.000	110.5000	1.4968	202.53	3.17	190.1000	4.1000	-.03	4221.	4221.	4221.
17.000	93.4390	1.2646	201.69	3.83	161.4000	3.6300	.32	4209.	4209.	4209.
18.000	78.9990	1.1265	202.97	4.23	135.6000	2.9400	.44	4187.	4187.	4187.
19.000	66.9370	1.0331	206.09	3.62	113.2000	2.0200	.17	4119.	4119.	4119.
20.000	56.6030	.9460	203.47	2.85	94.5000	1.4500	-.20	4062.	4062.	4062.
21.000	48.4330	.8551	212.27	2.51	79.4500	1.1500	-.23	3970.	3970.	3970.
22.000	41.3340	.7806	214.97	2.40	66.9500	1.0400	-.21	3921.	3921.	3921.
23.000	35.3540	.7029	217.30	2.28	56.6800	.8900	-.06	3778.	3778.	3778.
24.000	30.2770	.6345	219.95	2.55	48.0400	.8051	-.05	3581.	3581.	3581.
25.000	25.9660	.5731	221.62	2.62	40.8200	.7149	-.06	3537.	3537.	3537.
26.000	22.3080	.5181	223.62	2.61	34.7500	.6280	-.06	3240.	3240.	3240.
27.000	19.1850	.4632	225.53	2.67	29.6300	.5789	-.03	2863.	2863.	2863.
28.000	16.5230	.4177	227.40	2.70	25.3100	.5304	-.13	2731.	2731.	2731.
29.000	14.2030	.3750	229.12	2.83	21.6700	.4827	-.16	2193.	2193.	2193.
30.000	12.3020	.3353	230.71	2.91	18.5800	.4359	-.21	1921.	1921.	1921.
31.000	9.1741	.2959	234.05	4.05	13.0500	.3877	-.33	1280.	1280.	1280.
32.000	6.2049	.2613	238.02	4.63	10.0700	.3019	-.48	1233.	1233.	1233.
33.000	3.2178	.1604	243.18	4.90	7.4700	.2517	-.44	1140.	1140.	1140.
34.000	3.9474	.1253	248.16	4.90	5.5200	.1604	-.50	1149.	1149.	1149.
35.000	3.0340	.0791	251.05	5.01	4.1200	.1450	-.40	1149.	1149.	1149.
36.000	2.3395	.0764	253.94	4.93	3.1100	.1104	-.38	1147.	1147.	1147.
37.000	1.8044	.0624	253.74	5.10	2.3900	.0756	-.37	1143.	1143.	1143.
38.000	1.4034	.0496	256.38	4.91	1.8300	.0634	-.30	1273.	1273.	1273.
39.000	1.0813	.0399	267.30	4.95	1.4170	.0511	-.23	1258.	1258.	1258.
40.000	.8466	.0300	269.80	5.14	1.1040	.0399	-.14	1237.	1237.	1237.
41.000	.6580	.0258	265.41	5.27	.8632	.0319	-.15	1204.	1204.	1204.
42.000	.5103	.0208	263.36	5.39	.6748	.0257	-.21	1162.	1162.	1162.
43.000	.3947	.0169	260.73	5.95	.5374	.0213	-.40	1076.	1076.	1076.
44.000	.3045	.0135	257.50	6.42	.4121	.0175	-.29	906.	906.	906.
45.000	.2338	.0108	253.49	6.84	.3213	.0139	-.24	623.	623.	623.
46.000	.1776	.0096	247.12	8.27	.2503	.0113	-.13	349.	349.	349.
47.000	.1321	.0055	230.27	7.46	.1931	.0086	-.05	208.	208.	208.
48.000	.0990	.0040	230.07	6.84	.1498	.0066	-.15	199.	199.	199.
49.000	.0734	.0031	217.08	8.19	.1173	.0055	.11	200.	200.	200.
50.000	.0537	.0023	211.95	7.45	.0882	.0045	.04	191.	191.	191.

TABLE III-1. MOISTURE RELATED STATISTICAL PARAMETERS

JANUARY

STATION = 911620		BARKING SANDS, HI		TV		TV		SKEW TV		DEWPT T		S.D. OPT		SKEW OPT		NOBS T-P		NOBS TV		
Z	VAPOR P	S.D. VP	SKEW VP	TV	TV	S.D.	SKEW TV	DEWPT T	S.D. OPT	SKEW OPT	NOBS T-P	NOBS TV	TV	TV	SKEW TV	DEWPT T	S.D. OPT	SKEW OPT	NOBS T-P	NOBS TV
MM	MEAN	MEAN	MEAN	MEAN	MEAN	DEG K	DEG K	MEAN	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K
.000	18.722	3.539	.09	295.77	2.62	.04	289.36	3.04	-.48	313.	313.									
.005	18.516	3.544	.15	295.69	2.68	-.01	289.18	3.08	-.38	344.	344.									
1.000	12.761	2.680	.00	293.67	2.05	-.50	283.42	3.35	-.83	342.	344.									
2.000	6.248	3.709	.06	284.62	2.56	-.51	270.08	11.58	-1.17	313.	344.									
3.000	2.562	2.433	1.15	280.44	2.65	-.27	255.93	13.80	-.38	291.	344.									
4.000	1.422	1.518	1.57	274.97	2.71	-.30	248.22	13.82	-.26	287.	344.									
5.000	.862	.972	1.73	269.96	2.94	-.35	242.39	13.62	-.19	231.	344.									
6.000	.530	.612	1.79	262.45	3.30	-.30	237.52	12.72	-.13	291.	344.									
7.000	.303	.326	1.65	255.53	3.59	-.14	232.66	11.53	-.21	286.	343.									
8.000	.172	.188	2.20	248.55	3.89	-.12	227.55	10.79	-.24	275.	342.									
9.000	.073	.073	2.30	241.92	4.08	.03	220.91	9.05	-.39	259.	342.									
10.000	.028	.036	4.00	235.50	4.08	-.06	213.00	8.55	-.15	80.	340.									
11.000	.013	.006	1.05	228.88	3.58	-.27	210.43	3.03	.02	27.	337.									
12.000	.006	.002	.97	222.54	3.24	-.68	204.43	2.61	.35	24.	335.									
13.000	.003	.001	.04	216.10	3.03	-.73	200.27	2.80	-.29	8.	335.									
14.000	99.999	99.999	999.99	210.09	2.96	-.40	999.99	99.99	999.99	1.	332.									
15.000	99.999	99.999	999.99	204.48	2.81	-.10	999.99	99.99	999.99	0.	331.									
16.000	99.999	99.999	999.99	200.21	2.69	.42	999.99	99.99	999.99	0.	326.									
17.000	99.999	99.999	999.99	197.90	3.13	.37	999.99	99.99	999.99	0.	324.									
18.000	99.999	99.999	999.99	198.12	3.71	.65	999.99	99.99	999.99	0.	322.									
19.000	99.999	99.999	999.99	201.79	3.51	.44	999.99	99.99	999.99	0.	317.									
20.000	99.999	99.999	999.99	206.28	2.76	.35	999.99	99.99	999.99	0.	313.									
21.000	99.999	99.999	999.99	209.78	2.50	.29	999.99	99.99	999.99	0.	304.									
22.000	99.999	99.999	999.99	212.43	2.48	-.12	999.99	99.99	999.99	0.	302.									
23.000	99.999	99.999	999.99	214.61	2.40	-.17	999.99	99.99	999.99	0.	294.									
24.000	99.999	99.999	999.99	216.56	2.58	-.25	999.99	99.99	999.99	0.	279.									
25.000	99.999	99.999	999.99	218.41	2.74	-.02	999.99	99.99	999.99	0.	273.									
26.000	99.999	99.999	999.99	220.36	2.62	.08	999.99	99.99	999.99	0.	246.									
27.000	99.999	99.999	999.99	222.33	2.65	.06	999.99	99.99	999.99	0.	218.									
28.000	99.999	99.999	999.99	224.61	2.86	.19	999.99	99.99	999.99	0.	206.									
29.000	99.999	99.999	999.99	226.33	2.92	.24	999.99	99.99	999.99	0.	168.									
30.000	99.999	99.999	999.99	227.97	3.11	.09	999.99	99.99	999.99	0.	148.									

TABLE III-2. MOISTURE RELATED STATISTICAL PARAMETERS

FEBRUARY

STATION - 911626		BARKING SANDS, HI											
Z	VAPOR P	S.D. VP	SKEW VP	TV	TV	SKEW TV	DEWPT T	S.D. DPT	SKEW DPT	NOBS T+P	NOBS TV		
	MEAN			MEAN	S.D.		MEAN						
KM	MB	MB		DEG K	DEG K		DEG K	DEG K					
.000	18.214	3.130	.26	295.86	2.49	.29	288.98	2.72	-.17	317.	317.		
.005	18.034	3.233	.25	295.70	2.64	.18	288.80	2.83	-.17	341.	341.		
1.000	12.274	2.286	-.01	289.47	1.87	-.40	282.84	2.92	-.69	341.	341.		
2.000	9.950	3.553	-.06	284.29	2.43	-.23	263.23	12.14	-1.17	317.	341.		
3.000	2.005	2.326	1.24	280.05	2.38	.19	252.94	14.00	-.12	275.	341.		
4.000	1.090	1.304	2.07	274.76	2.82	.20	245.08	13.40	-.06	269.	341.		
5.000	.656	.815	2.03	269.86	3.18	.11	240.15	12.90	-.07	269.	341.		
6.000	.475	.549	1.81	262.39	3.50	.01	235.23	12.85	-.13	266.	341.		
7.000	.274	.310	2.10	254.54	4.00	.09	231.40	11.70	-.19	264.	341.		
8.000	.151	.164	1.99	248.48	4.38	.04	226.44	10.60	-.29	252.	340.		
9.000	.074	.071	1.95	241.63	4.68	.00	221.08	9.17	-.51	202.	339.		
10.000	.034	.027	1.46	235.11	4.61	-.03	215.38	7.98	-.73	75.	339.		
11.000	.016	.006	.48	228.65	4.02	-.38	212.11	2.82	.04	27.	337.		
12.000	.007	.002	.72	222.36	3.46	-1.08	206.01	2.35	.38	26.	335.		
13.000	.004	.001	.67	216.26	2.78	-.73	201.16	2.59	.35	9.	334.		
14.000	99.999	99.999	999.99	210.25	2.50	.10	999.99	99.99	999.99	0.	332.		
15.000	99.999	99.999	999.99	204.78	2.81	.31	999.99	99.99	999.99	0.	330.		
16.000	99.999	99.999	999.99	200.66	3.24	.35	999.99	99.99	999.99	0.	328.		
17.000	99.999	99.999	999.99	198.29	3.71	.29	999.99	99.99	999.99	0.	326.		
18.000	99.999	99.999	999.99	199.58	4.05	.02	999.99	99.99	999.99	0.	324.		
19.000	99.999	99.999	999.99	202.17	3.44	-.14	999.99	99.99	999.99	0.	317.		
20.000	99.999	99.999	999.99	205.53	2.63	-.17	999.99	99.99	999.99	0.	311.		
21.000	99.999	99.999	999.99	209.81	2.24	-.28	999.99	99.99	999.99	0.	297.		
22.000	99.999	99.999	999.99	212.70	2.35	-.18	999.99	99.99	999.99	0.	293.		
23.000	99.999	99.999	999.99	214.98	2.28	-.07	999.99	99.99	999.99	0.	293.		
24.000	99.999	99.999	999.99	217.07	2.48	-.14	999.99	99.99	999.99	0.	270.		
25.000	99.999	99.999	999.99	219.16	2.59	-.09	999.99	99.99	999.99	0.	266.		
26.000	99.999	99.999	999.99	221.30	2.59	.06	999.99	99.99	999.99	0.	244.		
27.000	99.999	99.999	999.99	223.35	2.61	.01	999.99	99.99	999.99	0.	217.		
28.000	99.999	99.999	999.99	225.51	2.89	-.06	999.99	99.99	999.99	0.	207.		
29.000	99.999	99.999	999.99	227.41	2.95	.30	999.99	99.99	999.99	0.	170.		
30.000	99.999	99.999	999.99	229.34	2.64	.30	999.99	99.99	999.99	0.	145.		

TABLE III-3. MOISTURE RELATED STATISTICAL PARAMETERS

MARCH

STATION = 911620		BARKING SANDS, HI		TV		TV		SKEW TV		DEWPT 1		S.D. OPT		SKEW OPT		NOBS T-P		NOBS TV	
Z	VAPOR P	S.D. VP	SKEW VP	MEAN	S.D.	MEAN	S.D.			MEAN									
KM	MB	MB		DEG K	DEG K	DEG K	DEG K			DEG K	DEG K								
.000	18.623	3.029	.02	296.79	2.41	289.34	2.61	.30		289.34	2.61	-.32				353.		359.	
.005	18.468	3.012	.06	296.69	2.43	289.21	2.61	.34		289.21	2.61	-.27				387.		387.	
1.000	12.201	2.121	-.34	289.61	1.55	282.84	2.62	-.46		282.84	2.62	-1.28				385.		387.	
2.000	9.834	3.527	-.05	284.44	2.00	268.67	12.71	-.48		268.67	12.71	-1.23				359.		387.	
3.000	2.116	2.114	1.19	290.09	2.12	252.71	14.78	.23		252.71	14.78	-.32				318.		387.	
4.000	1.192	1.381	1.72	274.53	2.41	245.91	13.72	.13		245.91	13.72	-.06				316.		387.	
5.000	.752	.805	1.77	258.33	2.69	241.11	13.04	.10		241.11	13.04	-.07				315.		387.	
6.000	.429	.499	2.14	261.57	2.75	235.94	11.76	-.03		235.94	11.76	-.08				313.		387.	
7.000	.284	.314	1.88	254.29	2.94	232.14	11.25	-.12		232.14	11.25	-.17				327.		387.	
8.000	.149	.156	1.55	246.92	3.20	226.43	10.39	-.09		226.43	10.39	-.24				329.		387.	
9.000	.074	.072	1.54	233.71	3.44	221.01	9.16	.11		221.01	9.16	-.31				247.		395.	
10.000	.022	.026	4.35	232.94	3.91	212.33	6.53	.25		212.33	6.53	.24				76.		395.	
11.000	.010	.004	1.06	226.70	4.04	208.21	3.10	-.05		208.21	3.10	.17				33.		385.	
12.000	.005	.002	.90	221.10	3.70	204.01	2.60	-.37		204.01	2.60	.20				32.		385.	
13.000	.004	.003	3.09	215.89	3.06	201.54	3.14	-.42		201.54	3.14	1.14				21.		385.	
14.000	99.999	99.999	999.99	210.79	2.91	999.99	99.99	-.30		999.99	99.99	999.99				2.		383.	
15.000	99.999	99.999	999.99	205.87	3.00	999.99	99.99	-.02		999.99	99.99	999.99				0.		382.	
16.000	99.999	99.999	999.99	202.04	3.12	999.99	99.99	.03		999.99	99.99	999.99				0.		381.	
17.000	99.999	99.999	999.99	199.08	3.39	999.99	99.99	-.06		999.99	99.99	999.99				0.		378.	
18.000	99.999	99.999	999.99	200.57	3.41	999.99	99.99	-.08		999.99	99.99	999.99				0.		376.	
19.000	99.999	99.999	999.99	203.84	3.24	999.99	99.99	-.25		999.99	99.99	999.99				0.		367.	
20.000	99.999	99.999	999.99	207.99	2.74	999.99	99.99	-.31		999.99	99.99	999.99				0.		360.	
21.000	99.999	99.999	999.99	210.82	2.33	999.99	99.99	-.13		999.99	99.99	999.99				0.		352.	
22.000	99.999	99.999	999.99	213.74	2.49	999.99	99.99	.18		999.99	99.99	999.99				0.		344.	
23.000	99.999	99.999	999.99	216.06	2.45	999.99	99.99	.01		999.99	99.99	999.99				0.		325.	
24.000	99.999	99.999	999.99	219.27	2.57	999.99	99.99	-.07		999.99	99.99	999.99				0.		301.	
25.000	99.999	99.999	999.99	220.41	2.42	999.99	99.99	-.17		999.99	99.99	999.99				0.		289.	
26.000	99.999	99.999	999.99	222.62	2.23	999.99	99.99	.02		999.99	99.99	999.99				0.		274.	
27.000	99.999	99.999	999.99	224.96	2.28	999.99	99.99	.17		999.99	99.99	999.99				0.		243.	
28.000	99.999	99.999	999.99	227.32	2.30	999.99	99.99	.12		999.99	99.99	999.99				0.		230.	
29.000	99.999	99.999	999.99	229.21	2.47	999.99	99.99	.12		999.99	99.99	999.99				0.		177.	
30.000	99.999	99.999	999.99	230.95	2.74	999.99	99.99	-.16		999.99	99.99	999.99				0.		147.	

TABLE III-4. MOISTURE RELATED STATISTICAL PARAMETERS

APRIL

STATION • 911620		BARKING SANDS, HI		TV		TV		DEWPT T		S.D. OPT		NOBS T-P		NOBS TV	
Z	VAPOR P	S.D. VP	SKEW VP	TV	S.D.	SKEW TV	DEWPT T	S.D. OPT	SKEW OPT	NOBS T-P	NOBS TV				
MEAN	MEAN	MEAN	MEAN	MEAN	MEAN	MEAN	MEAN	MEAN	MEAN	MEAN	MEAN				
KH	MB	MB	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K	DEG K				
.000	19.696	2.626	-.17	298.83	2.00	-.03	290.29	2.17	-.58	374.	374.				
.005	19.582	2.651	-.13	298.77	2.04	-.08	290.19	2.20	-.52	392.	392.				
1.000	12.780	1.924	-.04	250.24	1.37	-.73	283.60	2.32	-.43	392.	392.				
2.000	6.555	3.129	-.27	264.68	1.85	-.11	271.79	9.90	-1.71	374.	392.				
3.000	2.361	2.090	1.02	280.31	1.81	-.05	255.11	13.93	-.58	345.	392.				
4.000	1.226	1.277	1.69	274.68	1.88	.06	246.82	13.57	-.31	332.	392.				
5.000	.711	.837	2.12	268.92	2.06	-.01	240.38	13.25	-.13	334.	392.				
6.000	.470	.498	2.05	262.14	2.14	.10	235.70	12.71	-.15	327.	391.				
7.000	.242	.275	2.11	254.96	2.24	.03	230.22	11.74	-.24	318.	391.				
8.000	.141	.156	1.93	247.48	2.40	.05	225.54	10.99	-.29	292.	391.				
9.000	.080	.075	1.39	239.88	2.54	.09	221.38	9.83	-.52	208.	391.				
10.000	.033	.029	1.72	232.12	2.72	.19	215.25	7.43	-.26	51.	391.				
11.000	.012	.009	.96	224.83	2.77	.31	208.68	5.40	.09	40.	389.				
12.000	.006	.004	1.34	218.59	2.99	.22	203.50	4.74	-.03	40.	389.				
13.000	.003	.002	1.10	213.49	2.97	.16	198.37	4.72	.08	17.	386.				
14.000	99.999	99.999	999.99	209.51	2.78	-.22	999.99	99.99	999.99	2.	383.				
15.000	99.999	99.999	999.99	206.11	2.63	-.37	999.99	99.99	999.99	0.	383.				
16.000	99.999	99.999	999.99	203.34	2.63	-.06	999.99	99.99	999.99	0.	381.				
17.000	99.999	99.999	999.99	202.03	2.83	-.13	999.99	99.99	999.99	0.	391.				
18.000	99.999	99.999	999.99	202.99	2.94	-.30	999.99	99.99	999.99	0.	380.				
19.000	99.999	99.999	999.99	206.37	2.59	-.40	999.99	99.99	999.99	0.	374.				
20.000	99.999	99.999	999.99	209.90	2.30	-.35	999.99	99.99	999.99	0.	360.				
21.000	99.999	99.999	999.99	212.60	2.19	-.14	999.99	99.99	999.99	0.	360.				
22.000	99.999	99.999	999.99	215.06	2.12	-.11	999.99	99.99	999.99	0.	355.				
23.000	99.999	99.999	999.99	217.57	1.99	-.09	999.99	99.99	999.99	0.	344.				
24.000	99.999	99.999	999.99	220.12	2.08	-.18	999.99	99.99	999.99	0.	339.				
25.000	99.999	99.999	999.99	222.46	2.07	-.24	999.99	99.99	999.99	0.	328.				
26.000	99.999	99.999	999.99	224.70	1.97	-.09	999.99	99.99	999.99	0.	308.				
27.000	99.999	99.999	999.99	226.88	1.96	-.23	999.99	99.99	999.99	0.	268.				
28.000	99.999	99.999	999.99	229.07	2.03	-.23	999.99	99.99	999.99	0.	249.				
29.000	99.999	99.999	999.99	230.94	2.04	-.11	999.99	99.99	999.99	0.	198.				
30.000	99.999	99.999	999.99	232.77	2.05	.10	999.99	99.99	999.99	0.	170.				

TABLE III-5. MOISTURE RELATED STATISTICAL PARAMETERS

MAY

STATION - 911620		BARKING SANDS, HI		TV		TV		DEWPT T		S.D. DPT		NOBS T+P		NOBS TV	
2	VAPOR P	S.D. VP	SKEW VP	TV	S.D.	SKEW TV	MEAN	S.D. DPT	SKEW DPT	NOBS T+P	NOBS TV				
KM	MEAN	MB	MB	MEAN	DEG K	DEG K	DEG K	DEG K							
.000	20.664	2.699	-.08	305.49	1.79	.59	291.05	2.13	-.55	356.	356.				
.005	20.570	2.728	-.09	303.46	1.79	.58	290.97	2.17	-.55	363.	369.				
1.000	13.537	2.127	.12	291.29	1.15	.61	284.45	2.43	-.40	369.	369.				
2.000	7.020	3.208	-.26	283.64	1.82	.26	272.91	9.45	-1.61	356.	369.				
3.000	2.653	2.231	.04	281.45	1.80	.00	256.81	13.05	-.03	311.	368.				
4.000	1.361	1.365	1.67	275.51	2.06	.38	248.72	12.72	-.30	297.	368.				
5.000	.893	.905	1.77	270.57	2.14	.14	244.66	12.34	-.30	297.	368.				
6.000	.535	.575	1.68	264.01	2.25	-.06	238.46	11.92	-.26	295.	368.				
7.000	.304	.325	1.80	257.03	2.34	-.25	232.70	11.61	-.27	299.	368.				
8.000	.173	.167	1.57	249.65	2.26	-.26	228.16	10.41	-.45	287.	368.				
9.000	.092	.091	1.43	241.92	2.34	-.17	223.36	8.79	-.47	234.	366.				
10.000	.046	.035	1.27	234.12	2.35	.09	218.85	6.12	.20	70.	366.				
11.000	.015	.008	.81	226.37	2.22	.00	211.08	4.19	-.15	52.	366.				
12.000	.007	.004	1.47	219.16	2.27	.06	205.57	3.74	.26	52.	305.				
13.000	.005	.003	.33	212.71	2.44	.45	204.69	3.55	.01	11.	365.				
14.000	99.999	99.999	999.99	207.83	2.71	.51	999.99	99.99	999.99	1.	364.				
15.000	99.999	99.999	999.99	204.88	2.90	-.07	999.99	99.99	999.99	0.	363.				
16.000	99.999	99.999	999.99	203.35	2.60	.21	999.99	99.99	999.99	0.	359.				
17.000	99.999	99.999	999.99	203.34	2.63	.04	999.99	99.99	999.99	0.	358.				
18.000	99.999	99.999	999.99	205.08	2.71	-.11	999.99	99.99	999.99	0.	356.				
19.000	99.999	99.999	999.99	207.83	2.17	-.20	999.99	99.99	999.99	0.	352.				
20.000	99.999	99.999	999.99	210.74	1.83	-.20	999.99	99.99	999.99	0.	347.				
21.000	99.999	99.999	999.99	213.50	1.76	-.03	999.99	99.99	999.99	0.	340.				
22.000	99.999	99.999	999.99	216.06	1.83	-.14	999.99	99.99	999.99	0.	333.				
23.000	99.999	99.999	999.99	218.64	1.70	-.10	999.99	99.99	999.99	0.	320.				
24.000	99.999	99.999	999.99	221.05	1.85	.09	999.99	99.99	999.99	0.	313.				
25.000	99.999	99.999	999.99	223.35	1.71	.07	999.99	99.99	999.99	0.	300.				
26.000	99.999	99.999	999.99	225.61	1.60	-.03	999.99	99.99	999.99	0.	270.				
27.000	99.999	99.999	999.99	227.75	1.67	.07	999.99	99.99	999.99	0.	242.				
28.000	99.999	99.999	999.99	229.63	1.54	.18	999.99	99.99	999.99	0.	231.				
29.000	99.999	99.999	999.99	231.43	1.74	.30	999.99	99.99	999.99	0.	184.				
30.000	99.999	99.999	999.99	233.00	1.80	.03	999.99	99.99	999.99	0.	100.				

TABLE III-6. MOISTURE RELATED STATISTICAL PARAMETERS

JUNE

STATION = 911620		BARKING SANDS, HI		TV		TV		DEWPT T		S.D. DPT		NOBS T+P	
Z	VAPOR P	S.D. VP	SKEW VP	TV	TV	SKEW TV	DEWPT T	S.D. DPT	SKEW DPT	NOBS T+P	NOBS TV		
	MEAN			MEAN	S.D.		MEAN						
MM	MM	MM		DEG K	DEG K		DEG K	DEG K					
.000	21.600	2.861	-.12	301.39	1.66	.38	291.75	2.18	-.55	343.	343.		
.005	21.453	2.831	-.04	301.37	1.64	.34	291.65	2.16	-.46	370.	370.		
1.000	14.162	1.945	-.01	292.15	1.12	-.05	295.17	2.14	-.48	370.	370.		
2.000	7.351	3.483	-.22	287.12	2.03	.25	273.00	9.22	-1.37	343.	370.		
3.000	2.801	2.118	1.14	283.17	2.09	.23	259.03	11.56	-.81	310.	370.		
4.000	1.539	1.201	1.43	277.88	2.08	.20	251.77	11.18	-.81	301.	370.		
5.000	.914	.758	1.50	271.87	2.13	-.11	245.95	11.22	-.76	302.	370.		
6.000	.531	.472	1.57	265.24	2.22	-.26	241.15	10.59	-.85	303.	370.		
7.000	.303	.293	1.48	258.04	2.30	-.27	235.99	10.41	-.85	298.	370.		
8.000	.205	.162	1.33	250.69	2.33	.01	230.80	9.49	-.85	287.	309.		
9.000	.114	.091	1.58	243.08	2.34	.15	225.06	8.23	-.73	261.	309.		
10.000	.050	.037	1.18	235.28	2.22	-.05	219.37	6.56	-.20	100.	368.		
11.000	.017	.010	.92	227.48	1.94	.06	211.71	4.71	-.05	64.	368.		
12.000	.007	.004	.74	220.00	1.80	.09	205.42	3.80	-.12	65.	368.		
13.000	.004	.001	.20	213.32	1.83	.24	201.62	2.76	-.40	17.	367.		
14.000	.002	.001	.52	209.38	2.36	.32	197.27	2.23	-.12	12.	366.		
15.000	99.999	99.999	999.99	205.50	2.70	.21	999.99	99.99	999.99	0.	365.		
16.000	99.999	99.999	999.99	204.19	2.65	.01	999.99	99.99	999.99	0.	364.		
17.000	99.999	99.999	999.99	204.33	2.31	-.18	999.99	99.99	999.99	0.	364.		
18.000	99.999	99.999	999.99	205.93	2.18	.11	999.99	99.99	999.99	0.	360.		
19.000	99.999	99.999	999.99	208.55	1.78	-.12	999.99	99.99	999.99	0.	352.		
20.000	99.999	99.999	999.99	211.39	1.51	-.16	999.99	99.99	999.99	0.	345.		
21.000	99.999	99.999	999.99	214.12	1.54	.03	999.99	99.99	999.99	0.	340.		
22.000	99.999	99.999	999.99	216.70	1.44	.09	999.99	99.99	999.99	0.	337.		
23.000	99.999	99.999	999.99	219.14	1.43	-.05	999.99	99.99	999.99	0.	321.		
24.000	99.999	99.999	999.99	221.52	1.52	.11	999.99	99.99	999.99	0.	319.		
25.000	99.999	99.999	999.99	223.68	1.48	-.09	999.99	99.99	999.99	0.	304.		
26.000	99.999	99.999	999.99	225.80	1.42	-.10	999.99	99.99	999.99	0.	281.		
27.000	99.999	99.999	999.99	227.71	1.57	-.10	999.99	99.99	999.99	0.	238.		
28.000	99.999	99.999	999.99	229.38	1.55	.08	999.99	99.99	999.99	0.	221.		
29.000	99.999	99.999	999.99	230.99	1.56	.34	999.99	99.99	999.99	0.	178.		
30.000	99.999	99.999	999.99	232.38	1.71	-.06	999.99	99.99	999.99	0.	153.		

TABLE III-7. MOISTURE RELATED STATISTICAL PARAMETERS

JULY

STATION * 911620	BARKING SANDS, HI		TV		TV		DEWPT T		S.D. DPT		NOBS T-P		NOBS TV	
Z	VAPOR P	S.D. VP	SKEW VP	TV	S.D.	SKEW TV	MEAN	S.D. DPT	SKEW DPT	NOBS T-P	NOBS TV			
KM	MB	MB		MEAN	DEG K		DEG K							
.000	22.139	2.701	.05	301.88	1.39	.49	292.17	2.00	-.48	329.	329.			
.005	22.080	2.694	.05	301.85	1.39	.49	292.13	2.00	-.47	339.	339.			
1.000	14.716	2.051	.14	292.78	1.05	.07	285.75	2.16	-.33	339.	339.			
2.000	7.580	3.490	-.16	287.52	1.78	.42	274.11	9.26	-1.80	323.	339.			
3.000	2.857	2.107	.95	282.75	1.75	.17	259.07	12.11	-.92	297.	339.			
4.000	1.408	1.143	1.56	277.43	1.98	-.41	250.67	11.04	-.67	271.	337.			
5.000	.843	.689	1.47	271.74	2.08	-.48	244.92	10.61	-.64	261.	337.			
6.000	.528	.483	2.21	265.32	2.21	-.37	239.77	10.37	-.55	269.	337.			
7.000	.322	.294	2.24	259.31	2.24	-.20	234.78	10.10	-.63	268.	337.			
8.000	.203	.170	1.59	250.90	2.26	-.17	230.61	9.42	-.68	259.	336.			
9.000	.111	.082	1.22	243.28	2.24	.04	225.69	8.31	-.91	230.	336.			
10.000	.053	.029	1.04	235.45	2.23	.08	220.70	4.99	-.51	67.	335.			
11.000	.020	.010	.25	227.63	2.01	-.03	212.70	4.92	-.63	43.	335.			
12.000	.008	.004	.10	220.27	1.77	-.20	206.70	3.76	-.62	43.	335.			
13.000	.003	.001	-.34	213.85	1.74	.02	200.74	3.10	-.67	14.	332.			
14.000	99.999	99.999	999.99	209.19	2.32	.31	999.99	99.99	999.99	1.	331.			
15.000	99.999	99.999	999.99	205.38	2.74	.42	999.99	99.99	999.99	0.	330.			
16.000	99.999	99.999	999.99	202.27	2.75	.15	999.99	99.99	999.99	0.	329.			
17.000	99.999	99.999	999.99	200.63	2.21	-.23	999.99	99.99	999.99	0.	327.			
18.000	99.999	99.999	999.99	207.05	1.73	-.11	999.99	99.99	999.99	0.	324.			
19.000	99.999	99.999	999.99	209.27	1.38	-.12	999.99	99.99	999.99	0.	320.			
20.000	99.999	99.999	999.99	211.79	1.35	.27	999.99	99.99	999.99	0.	316.			
21.000	99.999	99.999	999.99	214.48	1.38	.03	999.99	99.99	999.99	0.	306.			
22.000	99.999	99.999	999.99	216.74	1.29	-.22	999.99	99.99	999.99	0.	303.			
23.000	99.999	99.999	999.99	218.90	1.29	-.10	999.99	99.99	999.99	0.	299.			
24.000	99.999	99.999	999.99	221.07	1.50	.40	999.99	99.99	999.99	0.	296.			
25.000	99.999	99.999	999.99	223.11	1.57	.14	999.99	99.99	999.99	0.	277.			
26.000	99.999	99.999	999.99	224.91	1.58	.33	999.99	99.99	999.99	0.	261.			
27.000	99.999	99.999	999.99	226.64	1.70	.14	999.99	99.99	999.99	0.	216.			
28.000	99.999	99.999	999.99	228.30	1.65	-.05	999.99	99.99	999.99	0.	205.			
29.000	99.999	99.999	999.99	230.04	1.85	.06	999.99	99.99	999.99	0.	169.			
30.000	99.999	99.999	999.99	231.33	1.71	.16	999.99	99.99	999.99	0.	150.			

TABLE III-8. MOISTURE RELATED STATISTICAL PARAMETERS

AUGUST

STATION = 911620		BARKING SANDS, HI											
Z	VAPOR P	S.D. VP	SKW VP	TV	TV	SKW TV	DEWPT T	S.D. DPT	SKW DPT	NOBS T+P	NOBS TV		
KM	MB	MB		MEAN	S.D.		MEAN						
				DEG K	DEG K		DEG K	DEG K					
.000	22.650	2.670	.05	301.95	1.29	.34	292.54	1.92	-.31	385.	385.		
.005	22.557	2.691	.03	301.89	1.29	.32	292.47	1.95	-.33	393.	393.		
1.000	14.920	2.213	.19	293.26	1.08	-.28	285.95	2.30	-.37	393.	393.		
2.000	8.048	3.341	-.09	287.69	1.69	.22	275.54	7.48	-1.31	365.	392.		
3.000	3.299	2.368	.97	293.04	1.65	.01	261.39	11.18	-.83	341.	392.		
4.000	1.710	1.477	1.34	277.93	1.73	.18	252.27	12.07	-.55	309.	391.		
5.000	.979	.880	1.62	272.33	1.85	.05	245.94	11.48	-.51	301.	391.		
6.000	.632	.572	1.52	266.01	1.96	.02	241.24	11.04	-.46	292.	391.		
7.000	.374	.336	1.59	259.13	2.00	-.15	235.88	10.74	-.55	297.	390.		
8.000	.215	.190	1.62	251.77	2.04	-.21	230.89	9.88	-.65	297.	388.		
9.000	.118	.093	1.32	244.18	2.03	-.15	225.59	8.69	-.85	270.	385.		
10.000	.056	.044	1.30	238.47	2.11	-.04	219.68	7.93	-.74	95.	383.		
11.000	.016	.010	.96	229.50	1.98	-.22	211.39	4.61	.03	52.	382.		
12.000	.007	.004	.99	221.03	1.87	-.17	205.20	3.60	.03	52.	382.		
13.000	.002	.001	.61	214.22	1.77	.06	197.81	2.95	.30	7.	382.		
14.000	99.999	99.999	999.99	200.01	2.03	.37	999.99	99.99	999.99	0.	378.		
15.000	99.999	99.999	999.99	205.65	2.45	.21	999.99	99.99	999.99	0.	376.		
16.000	99.999	99.999	999.99	204.60	2.43	-.19	999.99	99.99	999.99	0.	376.		
17.000	99.999	99.999	999.99	205.10	2.01	-.45	999.99	99.99	999.99	0.	375.		
18.000	99.999	99.999	999.99	206.91	1.65	.29	999.99	99.99	999.99	0.	374.		
19.000	99.999	99.999	999.99	209.16	1.46	-.15	999.99	99.99	999.99	0.	369.		
20.000	99.999	99.999	999.99	211.60	1.51	-.17	999.99	99.99	999.99	0.	366.		
21.000	99.999	99.999	999.99	214.07	1.47	.16	999.99	99.99	999.99	0.	362.		
22.000	99.999	99.999	999.99	216.29	1.44	-.18	999.99	99.99	999.99	0.	359.		
23.000	99.999	99.999	999.99	218.39	1.50	-.21	999.99	99.99	999.99	0.	345.		
24.000	99.999	99.999	999.99	220.44	1.65	.05	999.99	99.99	999.99	0.	338.		
25.000	99.999	99.999	999.99	222.55	1.54	-.13	999.99	99.99	999.99	0.	315.		
26.000	99.999	99.999	999.99	224.47	1.55	-.07	999.99	99.99	999.99	0.	283.		
27.000	99.999	99.999	999.99	226.15	1.62	-.23	999.99	99.99	999.99	0.	249.		
28.000	99.999	99.999	999.99	227.75	1.59	-.09	999.99	99.99	999.99	0.	240.		
29.000	99.999	99.999	999.99	229.31	1.83	.08	999.99	99.99	999.99	0.	210.		
30.000	99.999	99.999	999.99	230.81	1.90	.26	999.99	99.99	999.99	0.	191.		

TABLE III-9. MOISTURE RELATED STATISTICAL PARAMETERS

SEPTEMBER

STATION - 911620		BARKING SANDS, HI		TV		TV		DEWPT		S.D. DPT		NOBS T+P		NOBS TV	
Z	VAPOR P	S.D. VP	SKW VP	MEAN	S.D.	SKW TV	MEAN	S.D. DPT	SKW DPT						
KH	MB	MB		DEG K	DEG K		DEG K	DEG K							
.000	22.290	2.599	.60	301.48	1.34	.10	292.29	1.85	.06	352.		352.			
.005	22.223	2.587	.61	301.43	1.34	.11	292.24	1.85	.07	361.		361.			
1.000	14.749	2.150	.00	293.45	1.04	-.58	285.77	2.28	-.48	361.		361.			
2.000	8.409	3.253	-.51	287.57	1.46	.10	276.26	7.29	-1.36	352.		361.			
3.000	3.467	2.355	.68	283.40	1.74	.11	262.20	11.01	-.89	303.		361.			
4.000	1.809	1.484	1.09	270.20	1.83	-.13	253.18	11.81	-.58	247.		361.			
5.000	1.053	.949	1.63	272.44	1.84	-.04	246.70	11.46	-.50	294.		361.			
6.000	.606	.526	1.50	275.94	1.95	-.11	241.13	10.60	-.53	240.		361.			
7.000	.391	.384	1.87	268.85	2.05	-.06	236.02	10.17	-.50	285.		361.			
8.000	.226	.195	1.73	261.42	2.15	.04	231.83	9.04	-.56	280.		360.			
9.000	.119	.094	1.50	243.76	2.27	.02	226.39	7.81	-.50	251.		360.			
10.000	.057	.048	1.65	236.02	2.30	.08	220.09	7.01	-.17	83.		359.			
11.000	.017	.009	1.00	229.13	2.09	.00	211.87	4.08	.16	49.		358.			
12.000	.007	.003	.93	220.89	1.99	.23	205.51	3.08	.28	50.		357.			
13.000	.003	.001	-.22	214.26	2.02	.02	200.49	2.00	-.44	9.		357.			
14.000	99.999	99.999	999.99	203.87	1.95	.20	999.99	99.99	999.99	0.		356.			
15.000	99.999	99.999	999.99	205.31	2.24	-.09	999.99	99.99	999.99	0.		355.			
16.000	99.999	99.999	999.99	203.47	2.33	-.14	999.99	99.99	999.99	0.		354.			
17.000	99.999	99.999	999.99	203.61	2.27	-.49	999.99	99.99	999.99	0.		354.			
18.000	99.999	99.999	999.99	205.84	1.85	-.18	999.99	99.99	999.99	0.		354.			
19.000	99.999	99.999	999.99	208.35	1.64	-.08	999.99	99.99	999.99	0.		349.			
20.000	99.999	99.999	999.99	211.04	1.59	.21	999.99	99.99	999.99	0.		347.			
21.000	99.999	99.999	999.99	213.50	1.50	.41	999.99	99.99	999.99	0.		341.			
22.000	99.999	99.999	999.99	215.90	1.51	.23	999.99	99.99	999.99	0.		338.			
23.000	99.999	99.999	999.99	213.18	1.56	.21	999.99	99.99	999.99	0.		330.			
24.000	99.999	99.999	999.99	220.32	1.70	-.08	999.99	99.99	999.99	0.		325.			
25.000	99.999	99.999	999.99	220.32	1.69	-.11	999.99	99.99	999.99	0.		306.			
26.000	99.999	99.999	999.99	224.20	1.68	.21	999.99	99.99	999.99	0.		281.			
27.000	99.999	99.999	999.99	225.97	1.83	.39	999.99	99.99	999.99	0.		249.			
28.000	99.999	99.999	999.99	227.70	1.64	.36	999.99	99.99	999.99	0.		238.			
29.000	99.999	99.999	999.99	223.44	1.73	.56	999.99	99.99	999.99	0.		186.			
30.000	99.999	99.999	999.99	231.12	1.93	.38	999.99	99.99	999.99	0.		162.			

TABLE III-10. MOISTURE RELATED STATISTICAL PARAMETERS

OCTOBER

STATION = 911620		BARKING SANDS, HI		TV		TV		DEWPT T		S.D. DPT		SKEW DPT		NOBS T+P		NOBS TV	
Z	VAPOR P	S.D. VP	SKEW VP	TV	S.D.	SKEW TV	DEWPT T	S.D. DPT	SKEW DPT	NOBS T+P	NOBS TV						
KM	MB	MB		DEG K	DEG K		DEG K	DEG K									
.000	21.969	2.925	-.01	300.66	1.83	.13	291.96	2.10	-.32	370.	370.						
.005	21.826	2.831	.01	300.63	1.83	.12	291.93	2.11	-.23	377.	377.						
1.000	14.517	2.320	-.16	297.09	1.18	.06	285.50	2.55	-.72	377.	377.						
2.000	8.199	3.508	-.30	297.45	1.66	.00	275.57	8.22	-1.44	370.	377.						
3.000	3.341	2.369	.81	292.15	1.81	-.27	261.67	10.77	-.62	331.	377.						
4.000	1.004	1.531	1.28	277.77	1.98	-.23	253.93	11.18	-.42	314.	377.						
5.000	1.004	.970	1.34	271.73	2.10	-.45	247.63	10.70	-.39	312.	377.						
6.000	.679	.077	1.71	265.24	2.20	-.30	240.34	10.47	-.42	309.	377.						
7.000	.309	.359	1.74	259.21	2.32	-.26	236.64	10.67	-.45	311.	377.						
8.000	.212	.181	1.73	250.82	2.39	-.29	231.32	8.89	-.57	301.	377.						
9.000	.111	.091	1.71	243.28	2.36	-.24	225.57	8.24	-.68	272.	376.						
10.000	.059	.053	1.23	235.57	2.39	-.22	219.46	8.74	-.52	83.	376.						
11.000	.018	.011	.92	227.88	2.45	-.20	212.01	4.63	.02	31.	376.						
12.000	.008	.004	1.11	220.69	2.47	-.26	205.91	3.92	.11	31.	375.						
13.000	99.999	99.999	999.99	214.09	2.48	-.26	999.99	99.99	999.99	0.	375.						
14.000	99.999	99.999	999.99	209.64	2.31	-.21	999.99	99.99	999.99	0.	374.						
15.000	99.999	99.999	999.99	204.30	2.24	-.06	999.99	99.99	999.99	0.	372.						
16.000	99.999	99.999	999.99	201.69	2.50	.25	999.99	99.99	999.99	0.	371.						
17.000	99.999	99.999	999.99	201.35	2.96	.07	999.99	99.99	999.99	0.	370.						
18.000	99.999	99.999	999.99	203.42	2.91	-.21	999.99	99.99	999.99	0.	366.						
19.000	99.999	99.999	999.99	203.81	2.45	-.10	999.99	99.99	999.99	0.	359.						
20.000	99.999	99.999	999.99	209.95	2.01	.15	999.99	99.99	999.99	0.	354.						
21.000	99.999	99.999	999.99	212.78	1.88	.34	999.99	99.99	999.99	0.	345.						
22.000	99.999	99.999	999.99	215.43	1.66	.49	999.99	99.99	999.99	0.	341.						
23.000	99.999	99.999	999.99	217.74	1.79	.52	999.99	99.99	999.99	0.	331.						
24.000	99.999	99.999	999.99	219.88	1.95	.34	999.99	99.99	999.99	0.	324.						
25.000	99.999	99.999	999.99	221.75	2.09	.29	999.99	99.99	999.99	0.	305.						
26.000	99.999	99.999	999.99	223.73	2.15	.20	999.99	99.99	999.99	0.	274.						
27.000	99.999	99.999	999.99	225.67	2.28	.04	999.99	99.99	999.99	0.	244.						
28.000	99.999	99.999	999.99	227.35	2.40	-.04	999.99	99.99	999.99	0.	236.						
29.000	99.999	99.999	999.99	229.29	2.74	.11	999.99	99.99	999.99	0.	184.						
30.000	99.999	99.999	999.99	231.16	2.79	-.01	999.99	99.99	999.99	0.	168.						

TABLE III-11. MOISTURE RELATED STATISTICAL PARAMETERS

NOVEMBER

STATION • 911620	BARKING SANDS, HI										
Z	VAPOR P	S.D. VP	SKLEW VP	TV	TV	SKEW TV	DEWPT T	S.D. DPT	SKEW DPT	HOUS 1+P	NOBS TV
	MEAN			MEAN	S.D.		MEAN				
KM	MB	MB		DEG K	DEG K		DEG K	DEG K			
.000	20.744	3.076	.04	233.54	2.00	.38	231.03	2.41	-.41	327.	327.
.005	20.730	3.031	.03	238.50	1.93	.31	231.07	2.38	-.41	346.	346.
1.000	14.237	2.279	-.14	242.05	1.60	-.67	235.20	2.53	-.53	345.	346.
2.000	7.061	3.729	-.30	245.72	2.19	-.25	273.92	9.90	-1.42	327.	346.
3.000	3.030	2.504	.97	232.57	2.23	.11	259.35	12.22	-.46	232.	346.
4.000	1.656	1.515	1.39	277.16	2.40	-.18	251.98	11.49	-.29	259.	345.
5.000	1.006	1.005	1.66	271.22	2.38	-.18	246.01	11.37	-.25	259.	344.
6.000	.654	.651	1.85	264.68	2.49	-.09	241.19	11.46	-.41	258.	344.
7.000	.384	.396	1.96	257.74	2.54	-.21	235.77	10.89	-.37	257.	344.
8.000	.225	.210	1.51	250.37	2.54	-.16	231.01	10.09	-.47	257.	344.
9.000	.115	.101	1.54	242.72	2.57	-.10	225.48	8.80	-.57	224.	344.
10.000	.054	.051	1.31	234.99	2.69	-.04	218.53	9.00	-.45	75.	343.
11.000	.014	.008	.74	227.35	2.54	.11	210.51	4.13	.17	22.	343.
12.000	.006	.003	1.04	220.32	2.59	-.01	204.70	3.06	.43	32.	343.
13.000	99.999	99.999	999.99	213.89	2.71	-.33	999.99	99.99	999.99	1.	343.
14.000	99.999	99.999	999.99	208.37	2.72	-.45	999.99	99.99	999.99	0.	341.
15.000	99.999	99.999	999.99	203.58	2.49	.02	999.99	99.99	999.99	0.	340.
16.000	99.999	99.999	999.99	200.33	2.53	.45	999.99	99.99	999.99	0.	338.
17.000	99.999	99.999	999.99	199.12	2.72	.32	999.99	99.99	999.99	0.	339.
18.000	99.999	99.999	999.99	200.66	2.97	.38	999.99	99.99	999.99	0.	337.
19.000	99.999	99.999	999.99	204.67	2.55	.26	999.99	99.99	999.99	0.	332.
20.000	99.999	99.999	999.99	203.62	2.05	.04	999.99	99.99	999.99	0.	327.
21.000	99.999	99.999	999.99	211.63	1.88	.03	999.99	99.99	999.99	0.	320.
22.000	99.999	99.999	999.99	214.31	1.92	.07	999.99	99.99	999.99	0.	318.
23.000	99.999	99.999	999.99	216.77	1.93	-.08	999.99	99.99	999.99	0.	309.
24.000	99.999	99.999	999.99	219.01	2.17	-.09	999.99	99.99	999.99	0.	304.
25.000	99.999	99.999	999.99	210.82	2.20	-.23	999.99	99.99	999.99	0.	294.
26.000	99.999	99.999	999.99	222.63	2.29	.05	999.99	99.99	999.99	0.	278.
27.000	99.999	99.999	999.99	224.45	2.46	.20	999.99	99.99	999.99	0.	250.
28.000	99.999	99.999	999.99	226.32	2.68	.00	999.99	99.99	999.99	0.	250.
29.000	99.999	99.999	999.99	227.92	2.73	.09	999.99	99.99	999.99	0.	197.
30.000	99.999	99.999	999.99	229.31	2.78	.08	999.99	99.99	999.99	0.	166.

TABLE III-12. MOISTURE RELATED STATISTICAL PARAMETERS

DECEMBER

STATION #	911020	BARKING SANDS, HI										
Z	VAPOR P	S.D. VP	SKWH VP	TV	TV	SKWH TV	DEWPT T	S.D. DPT	SKWH DPT	NOBS T+P	NOBS TV	
	MEAN			MEAN	S.D.		MEAN					
KH	MB	MB		DEG K	DEG K		DEG K	DEG K				
.000	19.074	3.356	.15	295.22	2.37	.00	269.53	2.82	-.25	293.	273.	
.005	18.934	3.334	.20	295.11	2.41	-.08	269.57	2.81	-.19	317.	317.	
1.000	13.258	2.527	-.15	290.70	1.66	-.23	234.04	3.07	-.91	317.	317.	
2.000	6.446	3.702	-.01	265.65	2.34	-.69	270.37	12.32	-1.41	279.	317.	
3.000	2.560	2.271	1.11	231.27	2.17	-.41	235.23	13.63	-.53	276.	317.	
4.000	1.386	1.385	1.56	275.91	2.40	-.27	248.71	13.04	-.30	257.	317.	
5.000	.777	.808	1.74	270.00	2.67	-.56	242.32	12.34	-.21	248.	317.	
6.000	.458	.497	2.23	263.51	2.89	-.71	237.10	11.44	-.23	250.	317.	
7.000	.290	.299	1.94	255.32	2.95	-.76	232.90	10.76	-.28	253.	317.	
8.000	.170	.175	1.74	249.02	2.97	-.78	227.82	10.20	-.23	245.	316.	
9.000	.089	.083	1.73	241.61	3.01	-.64	222.79	9.09	-.45	209.	315.	
10.000	.041	.037	1.67	234.19	3.03	-.30	216.57	8.41	-.52	70.	315.	
11.000	.020	.009	1.39	227.02	2.93	-.04	213.45	3.51	-.12	25.	315.	
12.000	.008	.003	.54	220.61	2.82	-.19	207.19	2.80	-.10	25.	315.	
13.000	99.999	99.999	999.99	214.64	2.69	-.13	999.99	99.99	999.99	3.	315.	
14.000	99.999	99.999	999.99	209.19	2.49	.00	999.99	99.99	999.99	0.	314.	
15.000	99.999	99.999	999.99	204.36	2.54	.20	999.99	99.99	999.99	0.	314.	
16.000	99.999	99.999	999.99	200.62	2.67	.47	999.99	99.99	999.99	0.	314.	
17.000	99.999	99.999	999.99	193.67	2.95	.38	999.99	99.99	999.99	0.	314.	
18.000	99.999	99.999	999.99	189.42	3.24	.40	999.99	99.99	999.99	0.	314.	
19.000	99.999	99.999	999.99	184.20	2.93	.16	999.99	99.99	999.99	0.	311.	
20.000	99.999	99.999	999.99	207.45	2.92	.17	999.99	99.99	999.99	0.	307.	
21.000	99.999	99.999	999.99	210.78	2.17	.18	999.99	99.99	999.99	0.	303.	
22.000	99.999	99.999	999.99	213.07	2.07	.68	999.99	99.99	999.99	0.	287.	
23.000	99.999	99.999	999.99	216.07	1.08	.17	999.99	99.99	999.99	0.	287.	
24.000	99.999	99.999	999.99	218.43	2.39	.18	999.99	99.99	999.99	0.	283.	
25.000	99.999	99.999	999.99	220.51	2.58	.17	999.99	99.99	999.99	0.	279.	
26.000	99.999	99.999	999.99	222.28	2.93	.11	999.99	99.99	999.99	0.	250.	
27.000	99.999	99.999	999.99	223.90	2.55	.29	999.99	99.99	999.99	0.	224.	
28.000	99.999	99.999	999.99	225.31	2.71	.20	999.99	99.99	999.99	0.	218.	
29.000	99.999	99.999	999.99	226.69	2.97	-.16	999.99	99.99	999.99	0.	178.	
30.000	99.999	99.999	999.99	228.08	3.36	-.11	999.99	99.99	999.99	0.	161.	

TABLE III-13. MOISTURE RELATED STATISTICAL PARAMETERS

ANNUAL

STATION = 911620		BARKING SANDS, MI											
2	VAPOR P	S.D. VP	SKW VP	TV	TV	SKW TV	DEWPT T	S.D. DPT	SKW DPT	NOBS T-D	NOBS TV		
MEAN	MEAN			MEAN	S.D.		MEAN						
MM	MM	MM		DEG K	DEG K		DEG K	DEG K					
.000	20.502	3.297	-.12	299.26	3.04	-.51	290.92	2.65	-.59	4124.	4124.		
.005	20.444	3.328	-.12	299.16	3.10	-.54	290.81	2.69	-.58	4337.	4336.		
1.000	13.678	2.423	-.08	291.50	2.05	-.58	284.55	2.82	-.78	4337.	4336.		
2.000	7.137	3.575	-.18	288.14	2.39	-.38	272.75	10.35	-1.56	4124.	4334.		
3.000	2.779	2.322	.99	281.81	2.41	-.22	257.77	13.23	-.66	3090.	4334.		
4.000	1.475	1.415	1.51	276.51	2.59	-.29	249.78	12.79	-.41	3513.	4330.		
5.000	.883	.888	1.76	270.53	2.78	-.44	243.93	12.36	-.37	3473.	4329.		
6.000	.545	.556	1.85	264.04	2.96	-.46	238.92	11.78	-.37	3472.	4328.		
7.000	.326	.330	1.89	257.00	3.11	-.48	233.55	11.15	-.40	3461.	4326.		
8.000	.187	.179	1.72	249.67	3.20	-.49	229.03	10.28	-.48	3356.	4318.		
9.000	.099	.087	1.62	242.24	3.23	-.35	223.93	9.02	-.59	2658.	4308.		
10.000	.045	.041	1.75	234.79	3.23	-.16	217.57	8.02	-.42	925.	4299.		
11.000	.016	.009	1.00	227.42	3.01	-.11	211.19	4.51	-.07	475.	4291.		
12.000	.007	.004	1.03	220.60	2.87	-.11	205.35	3.63	-.06	472.	4286.		
13.000	.004	.002	6.47	214.37	2.73	.04	200.69	3.32	.04	122.	4276.		
14.000	99.999	99.999	999.99	203.16	2.66	.06	999.99	99.99	999.99	19.	4254.		
15.000	99.999	99.999	999.99	205.12	2.76	.08	999.99	99.99	999.99	0.	4241.		
16.000	99.999	99.999	999.99	202.53	3.17	.03	999.99	99.99	999.99	0.	4221.		
17.000	99.999	99.999	999.99	201.69	3.83	-.29	999.99	99.99	999.99	0.	4209.		
18.000	99.999	99.999	999.99	202.97	4.23	-.51	999.99	99.99	999.99	0.	4187.		
19.000	99.999	99.999	999.99	200.08	3.62	-.69	999.99	99.99	999.99	0.	4119.		
20.000	99.999	99.999	999.99	209.47	2.89	-.62	999.99	99.99	999.99	0.	4067.		
21.000	99.999	99.999	999.99	212.80	2.91	-.46	999.99	99.99	999.99	0.	3978.		
22.000	99.999	99.999	999.99	214.97	2.40	-.48	999.99	99.99	999.99	0.	3941.		
23.000	99.999	99.999	999.99	217.30	2.38	-.53	999.99	99.99	999.99	0.	3776.		
24.000	99.999	99.999	999.99	219.55	2.55	-.54	999.99	99.99	999.99	0.	3681.		
25.000	99.999	99.999	999.99	221.62	2.62	-.60	999.99	99.99	999.99	0.	3537.		
26.000	99.999	99.999	999.99	223.62	2.61	-.51	999.99	99.99	999.99	0.	3240.		
27.000	99.999	99.999	999.99	225.53	2.67	-.43	999.99	99.99	999.99	0.	2463.		
28.000	99.999	99.999	999.99	227.40	2.70	-.49	999.99	99.99	999.99	0.	2731.		
29.000	99.999	99.999	999.99	229.12	2.83	-.41	999.99	99.99	999.99	0.	2199.		
30.000	99.999	99.999	999.99	230.71	2.91	-.47	999.99	99.99	999.99	0.	1921.		

TABLE IV-1. HYDROSTATIC MODEL ATMOSPHERE

JANUARY

STATION - 911620		BARKING SANDS, HI		T
Z	GEO. HT.	P	D	
KM	KM	MB	G/M ³	DEG K
.000	.000	1014.8000	1195.0000	295.77
.005	.005	1014.2000	1195.0000	295.59
1.000	.998	903.2100	1086.0000	283.87
2.000	1.995	802.1300	981.8000	274.62
3.000	2.993	711.0100	893.2000	267.44
4.000	3.990	628.9400	826.0000	274.97
5.000	4.985	554.9300	778.8000	283.55
6.000	5.983	488.2100	749.0000	292.45
7.000	6.979	428.1000	683.6000	293.53
8.000	7.974	374.0500	624.3000	298.55
9.000	8.970	325.6200	568.9000	291.92
10.000	9.965	282.4000	517.7000	275.50
11.000	10.960	243.9500	471.3000	228.60
12.000	11.954	203.8600	328.5000	222.54
13.000	12.948	179.7500	229.8000	216.10
14.000	13.942	153.2800	254.2000	210.09
15.000	14.936	130.1300	221.7000	204.48
16.000	15.929	110.0400	191.5000	200.21
17.000	16.922	92.7970	163.3000	197.00
18.000	17.914	78.1920	137.5000	198.12
19.000	18.906	65.9730	113.9000	201.79
20.000	19.899	55.8390	94.4000	205.78
21.000	20.890	47.4580	78.0000	209.78
22.000	21.881	40.4580	66.3500	212.43
23.000	22.872	34.5260	56.0500	214.61
24.000	23.863	29.5100	47.4700	216.55
25.000	24.853	25.2580	40.2900	218.41
26.000	25.844	21.6490	34.2300	220.36
27.000	26.833	18.5820	29.1200	222.33
28.000	27.823	15.9740	24.7700	224.61
29.000	28.812	13.7500	21.1600	226.33
30.000	29.801	11.8497	18.1100	227.97
32.000	31.777	8.8389	13.2200	232.59
34.000	33.752	6.6298	9.7550	235.29
36.000	35.726	4.9997	7.1020	241.81
38.000	37.699	3.7964	5.3293	247.79
40.000	39.671	2.9025	3.9740	254.09
42.000	41.641	2.2541	2.9370	260.11
44.000	43.611	1.7293	2.2660	255.43
46.000	45.579	1.3446	1.7390	255.69
48.000	47.545	1.0472	1.3570	259.38
50.000	49.511	.8146	1.0630	266.45
52.000	51.475	.6326	.8324	264.33
54.000	53.438	.4908	.6468	263.90
56.000	55.400	.3804	.5044	262.33
58.000	57.361	.2944	.3936	260.17
60.000	59.320	.2271	.3086	258.01
62.000	61.279	.1744	.2421	255.52
64.000	63.236	.1329	.1915	241.34
66.000	65.191	.1003	.1434	233.44
68.000	67.146	.0748	.1168	222.83
70.000	69.099	.0553	.0890	218.65

TABLE IV-2. HYDROSTATIC MODEL ATMOSPHERE

FEBRUARY

STATION = 911620		BARKING SANDS, HI		TV
Z	GEO. HT.	P	D	
KM	KM	MB	G/M3	DEG K
.000	.000	1016.3000	1197.0000	295.86
.005	.005	1015.8000	1197.0000	295.70
1.000	.998	904.5700	1089.0000	289.47
2.000	1.995	803.2500	934.3000	284.29
3.000	2.993	711.8900	895.5000	280.05
4.000	3.990	629.6300	798.3000	274.76
5.000	4.986	555.5000	719.8000	268.65
6.000	5.983	488.6900	648.8000	262.33
7.000	6.979	428.5200	584.2000	255.54
8.000	7.974	374.4100	524.9000	248.48
9.000	8.970	325.9000	469.9000	241.63
10.000	9.965	282.5800	418.7000	235.11
11.000	10.960	244.0500	371.8000	228.65
12.000	11.954	209.9300	328.9000	222.36
13.000	12.948	179.8100	289.6000	216.26
14.000	13.942	153.3400	254.1000	210.25
15.000	14.936	130.2100	221.5000	204.78
16.000	15.929	110.1400	191.2000	200.06
17.000	16.922	92.9160	163.2000	198.29
18.000	17.914	78.3200	137.4000	198.68
19.000	18.906	66.1300	114.0000	202.17
20.000	19.899	56.0200	94.5000	206.53
21.000	20.890	47.6110	79.0500	209.81
22.000	21.881	40.5580	66.4300	212.70
23.000	22.872	34.6200	56.1000	214.98
24.000	23.863	29.5590	47.5000	217.07
25.000	24.853	25.3460	40.2900	219.16
26.000	25.844	21.7370	34.2200	221.30
27.000	26.833	18.6700	29.1200	223.35
28.000	27.823	16.0600	24.8100	225.51
29.000	28.812	13.8340	21.1900	227.41
30.000	29.801	11.9316	18.1200	229.34
32.000	31.777	8.9223	13.1400	235.19
34.000	33.752	6.7186	9.6750	240.50
36.000	35.726	5.0823	7.1950	244.95
38.000	37.699	3.8757	5.3680	250.04
40.000	39.671	2.9695	4.0200	255.84
42.000	41.641	2.2800	3.0330	261.34
44.000	43.611	1.7724	2.3170	254.89
46.000	45.579	1.3768	1.7830	267.39
48.000	47.545	1.0710	1.3850	267.56
50.000	49.511	.8332	1.0790	267.30
52.000	51.475	.6480	.8416	268.66
54.000	53.438	.5034	.6597	264.21
56.000	55.400	.3901	.5161	261.78
58.000	57.361	.3017	.4026	259.52
60.000	59.320	.2328	.3143	256.43
62.000	61.279	.1787	.2461	251.72
64.000	63.236	.1345	.1943	243.30
66.000	65.191	.1033	.1522	234.99
68.000	67.146	.0770	.1215	219.40
70.000	69.099	.0465	.0910	215.40

TABLE IV-3. HYDROSTATIC MODEL ATMOSPHERE

MARCH

STATION - 911620		BARKING SANDS, HI		
Z	GEO. HT.	P	D	TV
KM	KM	MB	G/M3	DEG K
.000	.000	1017.6000	1195.0000	236.79
.005	.005	1017.0000	1194.0000	236.07
1.000	.938	925.6300	1090.0000	239.61
2.000	1.935	804.4700	985.3000	234.44
3.000	2.993	713.0000	886.0000	230.09
4.000	3.930	630.6000	800.0000	274.59
5.000	4.986	556.2000	722.2000	258.33
6.000	5.983	489.2000	651.5000	251.57
7.000	6.979	428.7400	587.3000	254.23
8.000	7.974	374.3200	528.1000	246.92
9.000	8.970	325.5000	473.0000	239.71
10.000	9.965	281.0970	421.6000	232.94
11.000	10.960	243.1400	373.6000	226.70
12.000	11.954	209.9100	329.2000	221.10
13.000	12.948	178.0400	289.6000	215.89
14.000	13.942	152.5200	252.1000	210.79
15.000	14.936	129.5900	219.3000	205.87
16.000	15.929	109.7300	189.2000	202.04
17.000	16.922	92.6930	161.5000	199.98
18.000	17.914	78.2560	135.9000	200.57
19.000	18.906	66.1770	113.1000	203.84
20.000	19.898	56.1260	94.1900	207.59
21.000	20.890	47.7350	78.6900	210.82
22.000	21.881	40.6960	66.3300	213.74
23.000	22.872	34.7640	55.0500	216.06
24.000	23.863	29.7470	47.4600	218.27
25.000	24.853	25.4950	40.3000	220.41
26.000	25.844	21.6850	34.2500	222.62
27.000	26.833	18.8160	29.1400	224.96
28.000	27.823	16.2030	24.8300	227.32
29.000	28.812	13.9740	21.2400	229.21
30.000	29.801	12.0655	18.2000	230.95
32.000	31.777	9.0417	13.2100	237.00
34.000	33.752	6.8201	9.7740	241.50
36.000	35.726	5.1708	7.2600	245.62
38.000	37.699	3.9402	5.4480	250.35
40.000	39.671	3.0180	4.0920	255.35
42.000	41.641	2.3243	3.0990	259.63
44.000	43.611	1.7968	2.3630	263.22
46.000	45.579	1.3930	1.8200	264.97
48.000	47.545	1.0817	1.4070	266.19
50.000	49.511	.8407	1.0910	266.72
52.000	51.475	.6535	.8505	265.96
54.000	53.438	.5075	.6642	264.46
56.000	55.400	.3935	.5190	262.43
58.000	57.361	.3044	.4065	259.17
60.000	59.320	.2347	.3176	255.76
62.000	61.279	.1802	.2483	251.22
64.000	63.236	.1374	.1968	241.69
66.000	65.191	.1037	.1540	233.05
68.000	67.146	.0772	.1218	219.45
70.000	69.093	.0567	.0918	213.92

TABLE IV-4. HYDROSTATIC MODEL ATMOSPHERE

APRIL

STATION = 911620		BARKING SANDS, HI		TV
Z	GEO. HT.	P	D	
KM	KM	MB	G/M3	CEG K
.000	.000	1017.8000	1197.0000	299.83
.005	.005	1017.2000	1186.0000	299.77
1.000	.979	905.5600	1089.0000	299.24
2.000	1.995	805.2100	985.3000	284.68
3.000	2.993	713.7300	887.0000	280.31
4.000	3.990	631.3200	800.1000	274.93
5.000	4.996	557.0100	721.6000	268.90
6.000	5.983	490.0000	651.2000	262.14
7.000	6.973	429.5700	585.9000	254.96
8.000	7.974	375.1700	528.1000	247.48
9.000	8.970	326.3100	473.9000	239.88
10.000	9.965	282.5300	424.0000	232.12
11.000	10.960	243.4600	377.3000	224.83
12.000	11.954	208.8900	332.9000	218.59
13.000	12.948	178.5000	291.3000	213.49
14.000	13.942	152.0300	252.0000	209.51
15.000	14.935	123.1200	218.2000	206.11
16.000	15.929	109.4000	197.4000	203.34
17.000	16.922	92.5420	159.6000	202.03
18.000	17.914	78.2740	134.3000	202.99
19.000	18.906	66.3270	112.0000	206.37
20.000	19.898	56.3610	93.5400	209.90
21.000	20.890	48.0100	78.6700	212.60
22.000	21.881	40.9780	66.3800	215.06
23.000	22.872	35.0410	56.1100	217.57
24.000	23.863	30.0200	47.5100	220.12
25.000	24.853	25.7040	40.3500	222.46
26.000	25.844	22.1460	34.3400	224.70
27.000	26.833	19.0660	29.2800	226.68
28.000	27.823	16.4390	25.0000	229.07
29.000	28.812	14.1930	21.4100	230.94
30.000	29.801	12.2684	18.3600	232.77
32.000	31.777	9.2104	13.4300	238.14
34.000	33.752	6.9352	9.9650	242.35
36.000	35.726	5.2724	7.4340	246.55
38.000	37.693	4.0258	5.5090	251.04
40.000	39.671	3.0868	4.1830	253.27
42.000	41.641	2.3735	3.1660	260.97
44.000	43.611	1.8423	2.4140	265.00
46.000	45.579	1.4309	1.8600	267.13
48.000	47.545	1.1134	1.4410	268.29
50.000	49.511	.8667	1.1230	267.08
52.000	51.475	.6744	.8770	267.00
54.000	53.438	.5240	.6893	264.31
56.000	55.400	.4059	.5405	260.72
58.000	57.361	.3133	.4234	256.92
60.000	59.320	.2409	.3318	252.02
62.000	61.279	.1840	.2609	245.01
64.000	63.236	.1393	.2056	235.28
66.000	65.191	.1045	.1579	229.87
68.000	67.146	.0776	.1230	219.72
70.000	69.099	.0570	.0929	213.16

TABLE IV-5. HYDROSTATIC MODEL ATMOSPHERE

MAY

STATION # 911620		BARKING SANDS, HI		TV DEG K
Z KM	GEO. HT. KM	P MB	D G/M3	
.000	.000	1017.4000	1179.0000	300.49
.005	.005	1016.8000	1179.0000	300.46
1.000	.998	906.6400	1084.0000	291.29
2.000	1.995	805.6100	992.5000	283.84
3.000	2.993	714.4000	894.3000	281.45
4.000	3.990	632.3000	796.6000	276.51
5.000	4.986	558.2900	718.8000	270.57
6.000	5.983	491.5400	648.6000	264.01
7.000	6.979	431.3600	584.6000	257.03
8.000	7.974	377.1600	526.3000	249.85
9.000	8.970	328.4200	472.9000	241.92
10.000	9.955	284.7100	423.7000	234.12
11.000	10.950	245.6400	378.0000	226.37
12.000	11.954	210.9000	335.2000	219.16
13.000	12.948	180.2000	295.1000	212.71
14.000	13.942	153.3400	257.0000	207.89
15.000	14.936	130.0800	221.2000	204.89
16.000	15.929	110.1600	188.7000	203.36
17.000	16.922	93.2370	159.7000	203.34
18.000	17.914	78.9720	134.1000	205.08
19.000	18.906	67.0140	112.3000	207.83
20.000	19.898	56.9960	94.2300	210.74
21.000	20.890	48.5830	79.2700	213.50
22.000	21.881	41.4050	66.9000	216.66
23.000	22.872	35.5100	56.5800	218.84
24.000	23.863	30.4430	47.9800	221.05
25.000	24.853	26.1430	40.7800	223.35
26.000	25.844	22.4860	34.7200	225.61
27.000	26.833	19.3700	29.6300	227.75
28.000	27.823	16.7090	25.3500	229.63
29.000	28.812	14.4310	21.7200	231.43
30.000	29.801	12.4770	18.6300	233.00
32.000	31.777	9.3600	13.7100	236.70
34.000	33.752	7.0562	10.1600	240.90
36.000	35.726	5.3461	7.5640	243.65
38.000	37.699	4.0706	5.6570	249.47
40.000	39.671	3.1169	4.2340	255.26
42.000	41.641	2.4011	3.1940	260.64
44.000	43.611	1.8587	2.4320	264.96
46.000	45.579	1.4438	1.8720	267.38
48.000	47.545	1.1236	1.4520	269.30
50.000	49.511	.8745	1.1330	267.60
52.000	51.475	.6800	.8869	265.80
54.000	53.438	.5276	.6916	262.97
56.000	55.400	.4084	.5434	260.50
58.000	57.361	.3152	.4257	256.69
60.000	59.320	.2422	.3345	251.01
62.000	61.279	.1848	.2626	244.02
64.000	63.236	.1398	.2065	234.60
66.000	65.191	.1046	.1598	226.95
68.000	67.146	.0772	.1257	218.99
70.000	69.099	.0562	.0939	207.66

TABLE IV-6. HYDROSTATIC MODEL ATMOSPHERE

JUNE

STATION - 911620		BARKING SANDS, HI		TV
Z	GEO. HT.	P	D	DEG K
KM	KM	MB	G/M3	
.000	.000	1017.3000	1176.0000	301.39
.005	.005	1016.7000	1175.0000	301.37
1.000	.998	906.8800	1081.0000	292.15
2.000	1.995	806.2100	978.2000	287.12
3.000	2.993	715.4100	870.1000	283.17
4.000	3.990	633.6100	774.4000	277.88
5.000	4.986	559.7900	717.3000	271.87
6.000	5.983	493.1600	647.7000	265.24
7.000	6.979	433.0100	594.6000	258.04
8.000	7.974	378.8100	526.4000	250.68
9.000	8.970	330.0700	473.0000	243.08
10.000	9.965	286.3400	424.0000	235.28
11.000	10.960	247.2200	379.6000	227.48
12.000	11.954	212.3900	346.3000	220.00
13.000	12.948	181.5300	305.5000	213.32
14.000	13.942	154.5700	256.4000	208.38
15.000	14.936	131.1900	222.4000	205.50
16.000	15.929	111.1600	189.7000	204.19
17.000	16.922	94.1560	160.5000	204.33
18.000	17.914	79.8100	135.0000	205.93
19.000	18.906	67.7670	113.2000	208.55
20.000	19.898	57.0660	95.0400	211.39
21.000	20.890	49.1780	80.0100	214.12
22.000	21.881	42.0230	67.5000	216.70
23.000	22.872	35.9760	57.1900	219.14
24.000	23.863	30.8530	48.5200	221.52
25.000	24.853	26.5030	41.2800	223.68
26.000	25.844	22.8000	35.1800	225.80
27.000	26.833	19.6410	30.0500	227.71
28.000	27.823	16.9410	25.7300	229.38
29.000	28.812	14.6230	22.0000	230.99
30.000	29.801	12.6431	18.9500	232.38
32.000	31.777	9.4740	13.9000	235.50
34.000	33.752	7.1305	10.3000	239.35
36.000	35.726	5.3944	7.6400	244.04
38.000	37.699	4.1035	5.7000	248.79
40.000	39.671	3.1402	4.2500	254.80
42.000	41.641	2.4184	3.2080	260.53
44.000	43.611	1.8720	2.4410	265.00
46.000	45.579	1.4535	1.8910	268.66
48.000	47.545	1.1305	1.4500	267.52
50.000	49.511	.8792	1.1390	266.76
52.000	51.475	.6832	.8999	265.29
54.000	53.438	.5299	.6971	262.67
56.000	55.400	.4097	.5482	259.26
58.000	57.361	.3153	.4304	253.13
60.000	59.320	.2414	.3359	248.37
62.000	61.279	.1810	.2598	244.04
64.000	63.236	.1391	.2063	233.03
66.000	65.191	.1040	.1586	226.70
68.000	67.145	.0768	.1242	213.70
70.000	69.099	.0540	.0946	202.08

TABLE IV-7. HYDROSTATIC MODEL ATMOSPHERE

JULY

STATION # 911620		BARKING SANDS, HI		TV
Z	GEO. HT.	P	D	DEG K
KM	KM	MB	G/M ³	
.000	.000	1016.9000	1174.0000	301.63
.005	.005	1016.4000	1173.0000	301.05
1.000	.999	996.7900	1079.0000	292.78
2.000	1.995	806.2900	970.0000	287.52
3.000	2.993	715.4000	891.5000	282.75
4.000	3.990	633.5000	795.6000	277.43
5.000	4.986	559.6000	717.5000	271.74
6.000	5.983	493.0500	647.4000	265.37
7.000	6.979	432.0000	583.0000	258.31
8.000	7.974	376.3100	520.0000	250.50
9.000	8.970	320.1000	472.7000	243.23
10.000	9.965	266.4000	423.6000	235.45
11.000	10.950	247.3000	378.5000	227.63
12.000	11.954	212.4000	336.1000	220.27
13.000	12.948	181.7200	296.0000	213.65
14.000	13.942	154.7700	257.7000	209.19
15.000	14.936	131.4400	221.0000	203.38
16.000	15.929	111.4700	183.2000	205.27
17.000	16.922	94.5030	160.1000	205.63
18.000	17.914	80.1810	134.8000	207.05
19.000	18.906	69.1310	113.4000	209.27
20.000	19.898	58.0020	95.4000	211.79
21.000	20.890	49.4780	80.3500	214.48
22.000	21.881	42.2050	67.9700	216.74
23.000	22.872	36.1900	57.6100	216.90
24.000	23.863	31.0370	48.9100	221.07
25.000	24.853	26.6310	41.6100	223.11
26.000	25.844	22.9160	35.4200	224.91
27.000	26.833	19.7280	30.3200	226.64
28.000	27.823	17.0040	25.9400	228.38
29.000	28.812	14.6740	22.2000	230.04
30.000	29.801	12.6740	19.0000	231.33
32.000	31.777	9.4806	14.6000	233.95
34.000	33.752	7.1233	10.3000	237.71
35.000	35.726	5.3787	7.6720	242.40
37.000	37.699	4.0037	5.7179	246.99
40.000	39.671	3.1181	4.2710	250.43
42.000	41.641	2.3060	3.2640	253.57
44.000	43.611	1.6700	2.4400	256.01
46.000	45.579	1.4320	1.8700	254.29
48.000	47.545	1.1121	1.4480	255.61
50.000	49.511	.6532	1.1280	254.49
52.000	51.475	.5009	.6810	251.72
54.000	53.439	.5171	.6602	253.39
56.000	55.400	.3709	.5263	257.15
58.000	57.361	.3309	.4177	254.03
60.000	59.320	.2352	.3766	248.99
62.000	61.279	.1790	.2569	240.89
64.000	63.236	.1348	.2015	231.38
66.000	65.191	.1006	.1547	224.87
68.000	67.146	.0742	.1197	214.10
70.000	69.099	.0541	.0826	208.91

TABLE IV-8. HYDROSTATIC MODEL ATMOSPHERE

AUGUST

STATION - 911620		BARKING SANDS, HI		TV
Z	GEOM. HT.	P	D	DEG K
KM	KM	MB	G/MS	
.000	.000	1016.1000	1172.0000	301.95
.005	.005	1015.5000	1172.0000	301.89
1.000	.993	906.1300	1070.0000	293.26
2.000	1.995	805.8200	975.6000	287.69
3.000	2.993	715.1300	880.2000	283.04
4.000	3.990	633.3500	793.9000	277.93
5.000	4.986	559.6400	715.9000	272.33
6.000	5.983	493.1600	645.8000	266.01
7.000	6.979	433.2200	582.4000	259.13
8.000	7.974	379.2100	524.7000	251.77
9.000	8.970	330.6100	471.7000	244.18
10.000	9.965	287.0000	422.6000	236.47
11.000	10.960	247.9700	378.1000	228.50
12.000	11.954	213.1800	336.0000	221.03
13.000	12.948	182.3300	296.6000	214.22
14.000	13.942	155.3300	259.1000	208.81
15.000	14.936	131.8700	223.4000	205.65
16.000	15.929	111.7600	190.3500	204.60
17.000	16.922	94.7000	160.9000	205.10
18.000	17.914	80.3300	135.3000	206.91
19.000	18.906	68.2550	113.7000	209.16
20.000	19.898	58.1000	95.0500	211.60
21.000	20.890	49.5500	80.6000	214.07
22.000	21.881	42.3350	69.1900	216.29
23.000	22.872	35.2280	57.7900	218.39
24.000	23.863	31.0490	49.0700	220.44
25.000	24.853	26.6510	41.7200	222.55
26.000	25.844	22.9080	35.5500	224.47
27.000	26.833	19.7160	30.3700	226.15
28.000	27.823	16.9870	25.9800	227.75
29.000	28.812	14.6520	22.2630	229.31
30.000	29.801	12.6509	19.1000	230.81
32.000	31.777	9.4596	13.9500	233.64
34.000	33.752	7.1048	10.3100	237.75
36.000	35.726	5.3637	7.6400	242.02
38.000	37.699	4.0704	5.6000	246.54
40.000	39.671	3.1067	4.2530	252.14
42.000	41.641	2.3862	3.1930	257.95
44.000	43.611	1.8410	2.4350	260.08
46.000	45.579	1.4248	1.8550	263.73
48.000	47.545	1.1052	1.4390	264.97
50.000	49.511	.8577	1.1170	265.05
52.000	51.475	.6657	.8691	264.33
54.000	53.438	.5153	.6793	261.00
56.000	55.400	.3989	.5308	257.36
58.000	57.361	.3077	.4139	253.55
60.000	59.320	.2366	.3229	252.96
62.000	61.279	.1808	.2502	244.53
64.000	63.236	.1371	.1982	238.66
66.000	65.191	.1030	.1551	229.21
68.000	67.146	.0764	.1214	217.21
70.000	69.099	.0559	.0914	211.21

TABLE IV-9. HYDROSTATIC MODEL ATMOSPHERE

SEPTEMBER

STATION = 911620		BARKING SANDS, HI		TV CEG K
Z KM	GEO. HT. KM	P MB	D G/M3	
.000	.000	1015.5000	1173.0000	301.48
.005	.005	1014.9000	1173.0000	301.43
1.000	.909	905.5000	1075.0000	293.45
2.000	1.835	805.2600	975.5000	287.57
3.000	2.633	714.6300	878.5000	283.40
4.000	3.930	633.0500	782.5000	279.28
5.000	4.835	559.4200	715.3000	272.44
6.000	5.633	492.9700	645.0000	265.94
7.000	6.979	433.0200	582.6000	259.85
8.000	7.974	378.9700	525.1000	251.42
9.000	8.970	329.3300	472.1000	243.76
10.000	9.965	285.6300	423.2000	236.02
11.000	10.960	247.6400	378.1000	229.13
12.000	11.954	212.8000	335.7000	223.83
13.000	12.948	182.1000	295.1000	219.26
14.000	13.942	155.1000	258.7000	209.87
15.000	14.935	131.0500	223.4000	205.31
16.000	15.929	111.5100	190.9000	203.47
17.000	16.922	94.3960	161.5000	203.51
18.000	17.914	79.9970	135.4000	205.34
19.000	18.910	67.9100	113.5000	209.35
20.000	19.879	57.7750	95.5700	211.34
21.000	20.830	49.2530	80.3700	213.00
22.000	21.891	42.0000	67.8700	215.90
23.000	22.872	35.9900	57.4600	218.18
24.000	23.863	30.8420	48.7700	220.32
25.000	24.853	26.4700	41.4600	222.32
26.000	25.944	22.7480	35.3500	224.20
27.000	26.833	19.5750	30.1800	225.97
28.000	27.803	16.8650	25.8000	227.70
29.000	28.812	14.5470	22.0500	229.44
30.000	29.801	12.5619	18.9400	231.12
32.000	31.777	9.3980	13.8700	234.15
34.000	33.752	7.0532	10.2400	238.34
36.000	35.726	5.3353	7.5080	242.38
39.000	37.699	4.0505	5.6590	246.93
40.000	39.671	3.0921	4.2370	252.08
42.000	41.641	2.3752	3.1790	259.22
44.000	43.611	1.8345	2.4120	268.98
46.000	45.579	1.4230	1.8460	265.47
48.000	47.545	1.1066	1.4280	267.77
50.000	49.511	.8609	1.1130	267.22
52.000	51.475	.6694	.8693	266.14
54.000	53.438	.5199	.6799	264.23
56.000	55.400	.4027	.5334	260.92
58.000	57.351	.3110	.4174	257.46
60.000	59.320	.2373	.3262	255.53
62.000	61.279	.1831	.2574	249.75
64.000	63.230	.1369	.2019	237.69
66.000	65.191	.1043	.1567	230.16
68.000	67.146	.0773	.1243	214.87
70.000	69.099	.0565	.0930	209.00

TABLE IV-10. HYDROSTATIC MODEL ATMOSPHERE

OCTOBER

STATION - 911620		BARKING SANDS, HI		TV
Z	GEO. HT.	P	D	DEG K
KM	KM	MB	G/M3	
.000	.000	1015.6000	1177.0000	300.66
.005	.005	1015.0000	1176.0000	300.63
1.000	.933	905.4000	1076.0000	297.09
2.000	1.935	805.1000	975.7000	293.45
3.000	2.933	714.4700	879.0000	289.15
4.000	3.930	632.7700	793.6000	277.77
5.000	4.996	559.0200	716.7000	271.73
6.000	5.983	492.4500	646.8000	265.24
7.000	6.979	432.4200	583.4000	258.21
8.000	7.974	378.3200	521.4000	250.82
9.000	8.970	329.6700	472.1000	243.28
10.000	9.965	286.0300	423.0000	235.57
11.000	10.960	247.0200	377.6000	227.88
12.000	11.954	212.2900	335.1000	220.69
13.000	12.948	181.5900	295.5000	214.08
14.000	13.942	154.6400	258.2000	208.64
15.000	14.936	131.2000	223.7000	204.30
16.000	15.929	111.0000	191.7000	201.69
17.000	16.922	93.8070	162.3000	201.35
18.000	17.914	79.3360	135.9000	203.42
19.000	18.906	67.2500	113.3000	206.81
20.000	19.898	57.1570	94.8400	209.95
21.000	20.890	48.6920	79.7200	212.78
22.000	21.881	41.5680	67.2200	215.43
23.000	22.872	35.5530	56.8800	217.74
24.000	23.863	30.4580	48.7500	219.88
25.000	24.853	26.1310	41.0500	221.75
26.000	25.844	22.4490	34.9600	223.73
27.000	26.833	19.3130	29.8100	225.67
28.000	27.823	16.6350	25.4900	227.35
29.000	28.812	14.3470	21.0000	229.29
30.000	29.801	12.3297	18.6700	231.16
32.000	31.777	9.2717	13.6700	234.67
34.000	33.752	6.9669	10.1500	237.49
36.000	35.726	5.2577	7.5240	241.67
38.000	37.699	3.9930	5.5970	246.46
40.000	39.671	3.0450	4.1710	252.49
42.000	41.641	2.3235	3.1330	259.27
44.000	43.611	1.8077	2.3720	263.62
46.000	45.579	1.4029	1.8200	265.60
48.000	47.545	1.0911	1.4080	268.01
50.000	49.511	.8490	1.0980	267.31
52.000	51.475	.6093	.8600	263.16
54.000	53.438	.4170	.6721	263.44
56.000	55.400	.3064	.5205	260.35
58.000	57.361	.2058	.4131	255.01
60.000	59.320	.1349	.3226	251.85
62.000	61.279	.1096	.2503	249.13
64.000	63.236	.1362	.1900	247.27
66.000	65.191	.1022	.1551	227.83
68.000	67.146	.0759	.1219	214.27
70.000	69.099	.0551	.0900	219.70

TABLE IV-11. HYDROSTATIC MODEL ATMOSPHERE

NOVEMBER

STATION - 911620		BARKING SANDS, HI		TV DEG K
Z KM	GEO. HT. KM	P MB	D G/M3	
.000	.000	1015.9000	1185.0000	293.04
.005	.005	1015.3000	1183.0000	293.50
1.000	.998	905.1200	1080.0000	282.05
2.000	1.995	804.5600	977.0000	265.72
3.000	2.993	713.8000	890.0000	262.57
4.000	3.990	632.0100	794.4000	277.16
5.000	4.985	558.2100	717.0000	271.22
6.000	5.983	491.5100	647.1000	264.68
7.000	6.979	431.5700	583.3000	257.74
8.000	7.974	377.4900	525.2000	250.37
9.000	8.970	328.5500	472.0000	242.72
10.000	9.955	285.2200	422.6000	234.99
11.000	10.950	246.2300	377.3000	227.35
12.000	11.954	211.5600	334.5000	220.32
13.000	12.948	180.3200	294.7000	213.89
14.000	13.942	154.0400	257.5000	208.37
15.000	14.936	130.6400	223.6000	203.59
16.000	15.929	110.4400	192.0000	200.33
17.000	16.922	93.1870	163.0000	199.12
18.000	17.914	78.6470	135.5000	200.66
19.000	18.906	65.5330	113.2000	204.67
20.000	19.898	56.4700	94.3000	208.62
21.000	20.890	48.0620	79.1100	211.63
22.000	21.881	40.9960	66.6400	214.31
23.000	22.872	35.0360	56.3100	216.77
24.000	23.853	29.9960	47.7100	219.01
25.000	24.853	25.7190	40.5800	220.92
26.000	25.844	22.0810	34.5500	222.63
27.000	26.833	18.9310	29.4600	224.45
28.000	27.823	16.3380	25.1500	225.32
29.000	28.812	14.0790	21.5200	227.92
30.000	29.801	12.1448	18.4500	229.31
32.000	31.777	9.0709	13.4800	233.32
34.000	33.752	6.6090	9.9630	235.91
36.000	35.726	5.1332	7.2930	240.71
38.000	37.699	3.8305	5.4910	245.62
40.000	39.671	2.9667	4.0920	251.37
42.000	41.641	2.2747	3.0790	256.28
44.000	43.611	1.7550	2.3190	261.74
46.000	45.579	1.3601	1.7750	265.70
48.000	47.545	1.0572	1.3700	267.51
50.000	49.511	.8224	1.0660	267.32
52.000	51.475	.6393	.8343	265.67
54.000	53.438	.4963	.6516	264.07
56.000	55.400	.3847	.5032	261.85
58.000	57.361	.2973	.3993	258.08
60.000	59.320	.2291	.3110	255.29
62.000	61.279	.1758	.2437	243.99
64.000	63.236	.1338	.1934	239.78
66.000	65.191	.1008	.1500	233.08
68.000	67.146	.0750	.1194	217.73
70.000	69.099	.0549	.0905	210.33

TABLE IV-12. HYDROSTATIC MODEL ATMOSPHERE

DECEMBER

STATION - 911620		BARKING SANDS, HI		TV DEG K
Z KM	GEO. HT. KM	P MB	D G/M3	
.000	.000	1016.1000	1195.0000	235.22
.005	.005	1015.5000	1195.0000	233.11
1.000	.908	904.6700	1084.5000	230.70
2.000	1.995	803.8000	979.0000	228.65
3.000	2.993	712.8000	882.9000	226.27
4.000	3.990	630.7700	795.4000	225.91
5.000	4.985	556.8000	718.4000	270.00
6.000	5.983	490.1000	647.9000	263.51
7.000	6.979	429.7500	584.4000	255.32
8.000	7.974	375.8000	525.7000	249.02
9.000	8.970	327.1600	471.7000	241.61
10.000	9.965	283.5900	421.8000	234.19
11.000	10.960	244.7300	375.5000	227.02
12.000	11.954	210.2700	332.0000	220.61
13.000	12.948	179.8300	292.0000	214.64
14.000	13.942	153.2600	255.2000	209.19
15.000	14.936	130.6800	221.7000	204.36
16.000	15.929	109.5300	191.0000	200.62
17.000	16.922	92.8040	162.7000	199.67
18.000	17.914	78.2670	136.7000	199.42
19.000	18.906	66.1370	113.4000	203.20
20.000	19.899	56.0750	94.1700	207.45
21.000	20.890	47.6880	78.8300	210.78
22.000	21.881	40.6540	66.2800	213.67
23.000	22.872	34.7270	55.9000	216.07
24.000	23.863	29.7180	47.4000	218.43
25.000	24.853	25.4720	40.2400	220.51
26.000	25.844	21.6630	34.2600	222.38
27.000	26.833	18.7880	29.2300	223.90
28.000	27.823	16.1630	24.9900	225.31
29.000	28.812	13.9180	21.3500	226.69
30.000	29.801	11.9263	18.3200	228.08
32.000	31.777	8.9480	13.4100	232.09
34.000	33.752	6.7019	9.2100	235.13
36.000	35.725	5.0437	7.3310	238.23
38.000	37.699	3.8225	5.3110	246.23
40.000	39.671	2.9893	4.0070	255.62
42.000	41.641	2.2459	3.0160	263.05
44.000	43.611	1.7372	2.2800	265.01
46.000	45.579	1.3498	1.7550	267.88
48.000	47.545	1.0506	1.3320	269.28
50.000	49.511	.8179	1.0610	269.22
52.000	51.475	.6357	.8531	267.45
54.000	53.438	.4950	.6493	263.46
56.000	55.400	.3942	.5070	257.02
58.000	57.361	.2979	.3745	248.60
60.000	59.320	.2304	.3100	238.47
62.000	61.279	.1771	.2453	228.59
64.000	63.235	.1352	.1927	214.97
66.000	65.191	.1020	.1535	231.08
68.000	67.146	.0759	.1103	220.41
70.000	69.099	.0559	.0835	217.68

TABLE IV-13. HYDROSTATIC MODEL ATMOSPHERE

ANNUAL

STATION # 911620		BARKING SANDS, HI		TV
Z	Geo. Ht.	P	D	CEG K
km	km	mb	g m ³	
.000	.000	1016.5000	1.03.0000	293.26
.005	.005	1015.5000	1.03.0000	293.16
1.000	.938	925.6500	1.02.0000	291.50
2.000	1.995	804.8500	.979.9000	286.14
3.000	2.993	713.6500	.892.4000	281.81
4.000	3.990	631.8600	.796.1000	276.51
5.000	4.986	557.9100	.718.3000	270.59
6.000	5.983	491.2100	.648.1000	264.04
7.000	6.979	431.0700	.584.3000	257.00
8.000	7.974	376.9000	.525.9000	249.67
9.000	8.970	329.2300	.472.0000	242.24
10.000	9.965	284.6300	.422.3000	234.79
11.000	10.960	245.7100	.376.4000	227.42
12.000	11.954	211.1300	.333.4000	220.60
13.000	12.948	180.6100	.293.5000	214.37
14.000	13.942	153.8500	.256.3000	209.16
15.000	14.936	130.6000	.221.8000	205.12
16.000	15.929	110.5700	.190.2000	202.53
17.000	16.922	93.4890	.161.5000	201.69
18.000	17.914	79.0640	.135.7000	202.97
19.000	18.905	66.9580	.113.2000	206.08
20.000	19.898	56.9070	.94.6400	209.47
21.000	20.890	48.4630	.79.4900	212.37
22.000	21.881	41.3600	.67.0200	214.97
23.000	22.872	35.3630	.56.6900	217.30
24.000	23.863	30.2870	.48.0000	219.55
25.000	24.853	25.9900	.40.8400	221.62
26.000	25.844	22.3160	.34.7700	223.62
27.000	26.833	19.1980	.29.6500	225.53
28.000	27.823	16.5360	.25.3300	227.40
29.000	28.812	14.2610	.21.6900	229.12
30.000	29.801	12.3120	.18.5900	230.71
32.000	31.777	9.2127	.13.6000	234.85
34.000	33.752	6.9289	.10.0600	239.82
36.000	35.726	5.2377	.7.4000	243.18
38.000	37.699	3.9810	.5.5600	248.16
40.000	39.671	3.0439	.4.1500	253.86
42.000	41.641	2.3417	.3.1200	259.38
44.000	43.611	1.8105	.2.3790	263.74
46.000	45.579	1.4049	1.8200	266.38
48.000	47.545	1.0923	1.4100	267.30
50.000	49.511	.8194	1.1030	265.80
52.000	51.475	.6601	.8619	265.41
54.000	53.439	.5122	.6740	263.36
56.000	55.400	.3906	.5271	260.73
58.000	57.361	.3063	.4121	257.50
60.000	59.320	.2357	.3222	253.49
62.000	61.279	.1804	.2530	247.12
64.000	63.235	.1370	.1902	238.27
66.000	65.191	.1030	.1551	230.07
68.000	67.146	.0754	.1219	217.08
70.000	69.099	.0560	.0915	211.95

APPENDIX A

EXAMPLES OF WIND STATISTICS FOR BARKING SANDS, HAWAII

Appendix A gives some examples of graphical displays of wind statistics that can be derived from the statistical parameters presented in table I. These illustrations should aid the user of the RRA to understand the functional relationships of the probability wind models and, thus, to develop an appreciation of the powerful properties of the bivariate normal probability distribution function.

All illustrations for this appendix are derived from the five wind component statistical parameters from table I.1 for January and table I.7 for July for eight selected altitudes. These selected altitudes are 4, 12, 20, 30, 40, 50, 60, and 70 km.

1. Frequency of Wind Direction (Figures A-1 through A-16)

The derived frequencies for wind direction shown in figures A-1 through A-16 were obtained using the five wind component parameters from tables I.1 and I.7 as input values in equation (35). The limits of integration (performed numerically) are over the 22.5-degree interval for each of the 16 compass points. These graphs give the percentage frequency that the wind will blow from the direction intervals.

2. Mean Wind Components and 80th Interpercentile Range of Wind Components (Figures A-17 through A-32)

The wind component means with respect to any orthogonal axes are obtained by using the zonal and meridional mean wind components in equations (44) and (45). These component means form the circles shown in figures A-17 through A-32. Further, the zonal and meridional wind component variances and correlation coefficients are used in equations (46) and (47) to obtain the variances with respect to any orthogonal axes. These rotated component variances and the rotated component means are used in equation (8) to obtain the 80th interpercentile range of wind components and are then illustrated in figures A-17 through A-32.

3. Probability Ellipses (Figures A-33 through A-48)

Using the five wind component parameters from tables I.1 and I.7 and $p = 0.50$, $p = 0.95$, and $p = 0.99$ as input values to equation (13), the wind probability ellipses shown in figures A-33 through A-48 were obtained by computer graphics. The statistical inferences are, for example, that 50 percent of the wind vectors lie within the smaller ellipse and 99 percent of the wind vectors lie within the outer ellipse. These probability ellipses are illustrated using the standard meteorological coordinate system explained in section I.B.1.

4. Conditional Windspeed Given the Wind Direction (Figures A-49 through A-64)

The five wind component parameters from table I.1 and table I.7 are used to evaluate the conditional probability distribution function, equation (41). Figures A-49 through A-64 show interpolations of the conditional function made to

obtain the 5th, 15th, 50th (median), 85th, 95th, and 99th conditional percentile values of windspeed, given the wind directions. The conditional mean windspeed, given the wind direction, is obtained from equation (40). The conditional mode (most probable) windspeed, given the wind direction, is obtained from equation (38). The conditional mean windspeed and the conditional windspeed modal value, given the wind direction, are also shown in these figures. For some figures, the conditional windspeed values are invalid for the given wind direction near 270° (from the west). This is caused by the lack of computational precision in evaluating equations (40) and (41) when the arguments for the Gaussian probability distribution have large negative values, i.e., when the coefficients (b/a) become less than -4 in these equations.

This appendix contains only a few of the many options in presenting wind statistics illustrations.

STATION=BARKINGSANDS MONTH=JAN ALT= 4KM




Figure A-1.

STATION=BARKINGSANDS MONTH=JAN ALT=12KM




Figure A-2.




Figure A-3.

STATION=BARKINGSANDS MONTH=JAN ALT=30KM




Figure A-4.

STATION=BARKINGSANDS MONTH=JAN ALT=40KM




Figure A-5.

STATION=BARKINOSANDS MON. JAN ALT=50KM




Figure A-6.

STATION=BARKINGSANDS MON. -JAN ALT=60KM




Figure A-7.




Figure A-8.




Figure A-9.

STATION=BARKINGSANDS MONTH=JUL ALT=120M




Figure A-10.




Figure A-11.




Figure A-12.




Figure A-13.




Figure A-14.




Figure A-15.

STATION=BARKINGSANDS MONTH=JUL ALT=70KM




Figure A-16.




Figure A-17.




Figure A-18.




Figure A-19.

XBAR= 8.70 SIGMAX= 12.41 RHO= .4313 YBAR= .52 SIGMAY= 4.39 PERCENT=****




Figure A-20.




Figure A-21.




Figure A-22.




Figure A-23.

XBAR= 58.89 SIGMAX= 27.37 RHO= -.0213 YBAR= -8.80 SIGMAY= 15.24 PERCENT=****




Figure A-24.




Figure A-25.

XBAR= 18.38 SIGMAX= 12.99 RHO= .2010 YBAR= 2.61 SIGMAY= 10.32 PERCENT=****




Figure A-26.




Figure A-27.




Figure A-28.




Figure A-29.




Figure A-30.




Figure A-31.




Figure A-32.




Figure A-33.




Figure A-34.




Figure A-35.




Figure A-36.




Figure A-37.




Figure A-38.




Figure A-39.




Figure A-40.




Figure A-41.




Figure A-42.




Figure A-43.




Figure A-44.




Figure A-45.




Figure A-46.




Figure A-47.




Figure A-48.

STATION=BARKINGSANDS MONTH=JAN ALT= 4KM




Figure A-49.

STATION=BARKINGSANDS MONTH=JAN ALT=12101




Figure A-50.

STATION=BARKINGSANDS MONTH=JAN ALT=20KM




Figure A-51.

STATION=BARKINGSANDS MONTH=JAN ALT=30KM




Figure A-52.

STATION=BARKINGSANDS MONTH=JAN ALT=401M




Figure A-53.

STATION=BARKINGSANDS MONTH=JAN ALT=50KM




Figure A-54.

STATION=BARKINGSANDS MONTH=JAN ALT=6CM




Figure A-55.

STATION-BARKINGSANDS MONTH-JAN ALT-70KM




Figure A-56.

STATION-BARKINGSANDS MONTH-JUL ALT= 4KM




Figure A-57.

STATION=BARKINGSANDS MONTH=JUL ALT=12K01




Figure A-58.

STATION-BARKINGSANDS MONTH-JUL ALT-20KM




Figure A-59.

STATION=BARKINGSANDS MONTH=JUL ALT=30KM




Figure A-60.

STATION-BARKINDSANDS MONTH-JUL ALT=40001




Figure A-61.

STATION-BARKINOSANDS MONTH-JUL ALT-50101




Figure A-62.

STATION=BARKINGSANDS MONTH=JUL ALT=60KM




Figure A-63.

STATION=BARKINOSANDS MONTH=JUL ALT=70KM




Figure A-64.

APPENDIX B

RANGE SPECIFIC INFORMATION AND THERMODYNAMIC QUANTITIES FOR BARKING SANDS, HAWAII

1. Range Specific Information

To prevent further character size reductions for tables I through IV, certain range-specific information has been omitted. This important information is given in table B-1.

TABLE B-1

<u>Header Record 0-30 Km</u>	<u>Header Record 32-70 Km</u>
Table Number-----0	Table Number-----0
Data Source (1=DATSAV, 2=WDC-A)-----1	Data Source (1=DATSAV, 2=WDC-A)-----2
Call Letters-----BKH	Call Letters-----BKH
WMO Number-----91162	WMO Number-----91162
Latitude-----22.02	Latitude-----22.02
Direction (N or S)-----N	Direction (N or S)-----N
Longitude-----159.47	Longitude-----159.47
Direction (E or W)-----W	Direction (E or W)-----W
Elevation in Meters-----5	Elevation in Meters-----5
Start Period of Record (Mo-Yr)-----863	Start Period of Record (Mo-Yr)-----169
End Period of Record (Mo-Yr)-----1282	End Period of Record (Mo-Yr)-----1179
No. of Time Windows (0, 1 or 2)-----1	No. of Time Windows (0, 1 or 2)-----1
Start Time Window No. 1 (Hr-MNZ)-1700	Start Time Window No. 1 (Hr-MNZ)-1700
End Time Window No. 1-----100	End Time Window No. 1-----100
Start Time Window No. 2-----0	Start Time Window No. 2-----0
End Time Window No. 2-----0	End Time Window No. 2-----0
Date of RRA-----683	Date of RRA-----683
Altitude Range of RRA	Altitude Range of RRA
Low Level (km)-----0	Low Level (km)-----30
Altitude Range of RRA	Altitude Range of RRA
High Level (km)-----30	High Level (km)-----70
Standard Deviation of Thermo-	Standard Deviation of Thermo-
dynamic Limits-----6.0	dynamic Limits-----6.0
Wind Limits-----6.0	Wind Limits-----6.0

2. Thermodynamic Quantities

This section presents examples of further computations and graphical displays of pressure, density, and virtual temperature statistics that can be derived from the data given in tables II, III, and IV. No attempt is made to present complete nor exhaustive illustrations that can be made to aid in visualizing the relationships that can be made from the data in tables II and IV. The choices are those that aided the committee to verify the reasonableness of the tabulations.

2.1 Monthly Mean from the Annual Mean

The hydrostatic model values in table IV are used to compute (1) the monthly mean differences relative to the annual mean values of pressure, density, and

virtual temperature expressed in percent and (2) the monthly mean difference in virtual temperature for the annual mean virtual temperature expressed in degrees Kelvin. Examples of these four statistics are given in table B-2 for January and table B-3 for July. Graphical displays of the four statistics contained in tables B-2 and B-3 are shown in figures B-1 through B-8. Also, the relative differences between the monthly mean values from table IV-1 through IV-12 for all months from the annual mean values (table IV-13) are illustrated in figure B-9 for pressure, in figure B-10 for density, and in figure B-11 for virtual temperature. The monthly mean virtual temperature differences from the annual mean virtual temperature for all months are given in figure B-12. The simple sum of the monthly mean differences from the annual mean values of these quantities is not zero. This is because the annual mean statistical parameters are computed (see section III.C.3 of text) by weighting the monthly means by the number of observations in each month.

2.2 Coefficients of Variation and Derived Correlation Coefficients

The coefficient of variation, C_V , is defined by the standard deviation with respect to the mean divided by the mean. The coefficients of variation for pressure, C_{VP} , and density, C_{VD} , were computed using the standard deviations from table II and the hydrostatic mean values from table IV. The coefficient of variation for temperature uses the standard deviations of virtual temperature from table III to the altitude where virtual temperature exists. Above this altitude, the standard deviations of temperature are from table II. The mean values for temperature (virtual temperature to the altitude where it exists) are taken from table IV. No distinction is made in the table headings in table B-4 (January) and table B-5 (July) and all related figures between virtual temperature and temperature.

From the coefficients of variation for pressure, density, and temperature (virtual temperature to the altitude where it exists), the correlation coefficients between these quantities are derived using Buell's method (see reference in text). The equations for these derived correlation coefficients are

$$r(P,T) = \frac{(C_{VT})^2 + (C_{VP})^2 - (C_{VD})^2}{2 [C_{VT} \cdot C_{VP}]} \quad , \quad (B-1)$$

$$r(P,D) = \frac{(C_{VD})^2 - (C_{VT})^2 + (C_{VP})^2}{2 [C_{VP} \cdot C_{VD}]} \quad , \quad (B-2)$$

$$r(T,D) = \frac{(C_{VP})^2 - (C_{VD})^2 - (C_{VT})^2}{2 [C_{VT} \cdot C_{VD}]} \quad . \quad (B-3)$$

The correlation coefficients in tables B-4 and B-5 are derived from the above equations.

A test for the validity of the derived correlation coefficients is that all three of the following inequalities be satisfied.

$$C_{VP} - [C_{VD} + C_{VT}] < 0$$

$$C_{VD} - [C_{VT} + C_{VP}] < 0 \quad (B-4)$$

$$C_{VT} - [C_{VP} + C_{VD}] < 0$$

In these examples (tables B-4 and B-5) the numerical values from equation (B-4) are all negative; hence, the derived correlation test is considered valid. The rare exceptions to this test for several RRAs occur at the extreme highest altitudes, where samples sizes for the statistical sample are small.

The statistical parameters from table B-4 (January) and table B-5 (July) are illustrated in figures B-13 through B-16.

For all months the C_{VP} values are shown in figure B-17, the C_{VD} values are shown in figure B-18, and C_{VT} values are shown in figure B-19. If the abscissa on the figures for the coefficient of variation were multiplied by 100, these figures would show the percentage of the random dispersion of these quantities over the month with respect to the monthly mean for these thermodynamic quantities.

The derived correlation coefficients for all months are illustrated in the following figures:

- a) Figure B-20 gives $r(P,D)$.
- b) Figure B-21 gives $r(P,T)$.
- c) Figure B-22 gives $r(T,D)$.

TABLE B-2.

STATION 911620 MONTH 1
 DELTAS IN PERCENT RELATIVE TO ANNUAL

LEVEL	PRESSURE	DENSITY	TEMP.	TMO-TA2N(CEG.K)
.000	-.17	1.01	-1.17	-3.49
.005	-.17	1.01	-1.16	-3.47
1.000	-.27	.37	-.63	-1.83
2.000	-.34	.19	-.53	-1.52
3.000	-.40	.09	-.49	-1.37
4.000	-.46	.09	-.56	-1.54
5.000	-.53	.07	-.60	-1.63
6.000	-.61	-.02	-.60	-1.79
7.000	-.69	-.12	-.57	-1.47
8.000	-.76	-.30	-.45	-1.12
9.000	-.80	-.66	-.13	-.32
10.000	-.78	-1.09	.30	.71
11.000	-.72	-1.35	.63	1.44
12.000	-.60	-1.47	.88	1.94
13.000	-.48	-1.26	.81	1.73
14.000	-.37	-.82	.44	.93
15.000	-.36	-.05	-.31	-.64
16.000	-.48	.68	-1.15	-2.32
17.000	-.74	1.11	-1.88	-3.79
18.000	-1.10	1.33	-2.39	-4.85
19.000	-1.48	.62	-2.63	-4.29
20.000	-1.77	-.25	-1.52	-3.19
21.000	-1.99	-.77	-1.22	-2.60
22.000	-2.18	-1.00	-1.18	-2.54
23.000	-2.37	-1.13	-1.24	-2.69
24.000	-2.57	-1.23	-1.36	-2.99
25.000	-2.78	-1.35	-1.45	-3.21
26.000	-3.00	-1.55	-1.46	-3.26
27.000	-3.21	-1.79	-1.42	-3.20
28.000	-3.40	-2.21	-1.23	-2.79
29.000	-3.58	-2.40	-1.22	-2.79
30.000	-3.76	-2.58	-1.19	-2.74
32.000	-4.06	-2.79	-.96	-2.26
34.000	-4.33	-3.03	-1.02	-2.44
35.000	-4.54	-3.66	-.56	-1.37
38.000	-4.64	-4.15	-.15	-.37
40.000	-4.64	-4.38	.09	.23
42.000	-4.60	-4.54	.28	.73
44.000	-4.48	-4.75	.66	1.74
46.000	-4.29	-4.87	.94	2.51
49.000	-4.13	-4.17	.40	1.68
50.000	-4.10	-3.63	-.13	-.34
52.000	-4.16	-3.42	-.41	-1.08
54.000	-4.18	-4.04	.21	.54
56.000	-4.09	-4.31	.61	1.60
58.000	-3.88	-4.49	1.02	2.62
60.000	-3.63	-4.22	.99	2.52
62.000	-3.33	-4.31	1.38	3.40
64.000	-2.98	-3.87	1.29	3.07
66.000	-2.60	-3.68	1.46	3.27
68.000	-2.02	-4.18	2.65	5.75
70.000	-1.16	-3.84	3.17	6.71

TABLE B-3.

STATION 9:1620 MONTH 7
 DELTAS IN PERCENT RELATIVE TO ANNUAL

LEVEL	PRESSURE	DENSITY	TEMP.	THO-TANN(DEG.K)
.000	.04	-.76	.88	2.62
.005	.05	-.85	.90	2.69
1.000	.12	-.28	.44	1.28
2.000	.18	-.31	.48	1.38
3.000	.23	-.10	.33	.94
4.000	.27	-.06	.33	.92
5.000	.32	-.11	.42	1.15
6.000	.37	-.11	.48	1.28
7.000	.44	-.07	.51	1.31
8.000	.51	.02	.49	1.23
9.000	.57	.15	.43	1.04
10.000	.62	.35	.28	.65
11.000	.65	.56	.09	.21
12.000	.64	.81	-.15	-.33
13.000	.61	.85	-.24	-.52
14.000	.60	.55	.01	.03
15.000	.64	.05	.61	1.26
16.000	.81	-.53	1.35	2.74
17.000	1.08	-.87	1.95	3.94
18.000	1.41	-.59	2.01	4.08
19.000	1.71	.16	1.55	3.19
20.000	1.92	.80	1.11	2.32
21.000	2.09	1.09	.99	2.10
22.000	2.24	1.42	.82	1.77
23.000	2.36	1.62	.74	1.60
24.000	2.48	1.77	.69	1.52
25.000	2.58	1.89	.67	1.49
26.000	2.68	2.07	.58	1.29
27.000	2.76	2.26	.49	1.11
28.000	2.83	2.41	.43	.98
29.000	2.90	2.49	.40	.92
30.000	2.95	2.69	.27	.62
32.000	2.93	3.09	-.38	-.89
34.000	2.80	2.98	-.46	-1.11
36.000	2.69	2.77	-.32	-.78
38.000	2.58	2.82	-.47	-1.17
40.000	2.44	2.77	-.56	-1.43
42.000	2.32	2.40	-.33	-.86
44.000	2.19	2.65	-.66	-1.73
46.000	2.00	2.57	-.78	-2.09
48.000	1.81	2.16	-.63	-1.69
50.000	1.62	2.27	-.87	-2.31
52.000	1.33	2.52	-1.39	-3.69
54.000	.93	2.26	-1.51	-3.97
56.000	.58	1.75	-1.37	-3.59
58.000	.22	1.36	-1.35	-3.47
60.000	-.20	1.37	-1.78	-4.50
62.000	-.78	1.54	-2.52	-6.23
64.000	-1.54	1.15	-2.89	-6.89
66.000	-2.28	-.26	-2.26	-5.20
68.000	-2.82	-1.64	-1.57	-2.98
70.000	-3.26	-2.02	-1.48	-3.14




Figure B-1.




Figure B-2.




Figure B-3.




Figure B-4.




Figure B-5.




Figure B-6.




Figure B-7.




Figure B-8.




Figure B-9.




Figure B-10.




Figure B-11.




Figure B-12.

TABLE B-4.

STATION 91162C LEVEL	MONTH CVP	I CVO	CVT	RIP,T	RIP,O	R:T,O	OCVP	OCVO	OCVT
.000	.0036	.0107	.0189	-.3456	.6262	-.9481	-.0159	-.0018	-.0054
.005	.0037	.0110	.0191	-.3627	.6322	-.9489	-.0163	-.0018	-.0056
1.000	.0037	.0077	.0071	.0601	.4059	-.8785	-.0111	-.0031	-.0043
2.000	.0040	.0082	.0030	.4165	.0252	-.8984	-.0132	-.0048	-.0031
3.000	.0045	.0082	.0034	.4880	-.0095	-.8774	-.0132	-.0057	-.0023
4.000	.0052	.0031	.0039	.5753	-.0618	-.8515	-.0128	-.0070	-.0034
5.000	.0050	.0055	.0109	.6390	-.1220	-.8414	-.0134	-.0064	-.0035
6.000	.0073	.0033	.0126	.6502	-.1622	-.8337	-.0149	-.0103	-.0039
7.000	.0022	.0100	.0140	.7131	-.1784	-.8170	-.0158	-.0123	-.0042
8.000	.0097	.0114	.0157	.6901	-.0992	-.7956	-.0174	-.0139	-.0054
9.000	.0112	.0128	.0169	.6500	.0217	-.7457	-.0184	-.0153	-.0072
10.000	.0127	.0141	.0173	.5999	.1637	-.6911	-.0187	-.0160	-.0094
11.000	.0140	.0142	.0156	.5446	.3628	-.5554	-.0199	-.0154	-.0125
12.000	.0149	.0149	.0146	.4239	.5202	-.4097	-.0146	-.0146	-.0152
13.000	.0159	.0165	.0140	.3935	.6255	-.4652	-.0146	-.0135	-.0184
14.000	.0166	.0193	.0141	.2150	.7028	-.5435	-.0168	-.0114	-.0219
15.000	.0169	.0215	.0137	.0275	.7685	-.6184	-.0133	-.0092	-.0146
16.000	.0167	.0234	.0134	-.1959	.8267	-.7138	-.0201	-.0067	-.0267
17.000	.0159	.0269	.0158	-.4333	.8497	-.8471	-.0202	-.0049	-.0271
18.000	.0145	.0230	.0197	-.5139	.9322	-.9033	-.0132	-.0042	-.0247
19.000	.0127	.0259	.0174	-.4618	.8029	-.8335	-.0305	-.0043	-.0212
20.000	.0117	.0203	.0134	-.3117	.7803	-.8335	-.0220	-.0047	-.0186
21.000	.0113	.0170	.0119	-.0710	.7134	-.7435	-.0176	-.0067	-.0163
22.000	.0115	.0147	.0117	.1920	.6280	-.6432	-.0149	-.0084	-.0145
23.000	.0118	.0132	.0112	.3345	.6057	-.5472	-.0127	-.0097	-.0138
24.000	.0123	.0133	.0119	.4000	.5493	-.5063	-.0129	-.0110	-.0137
25.000	.0132	.0136	.0115	.4460	.5606	-.4911	-.0129	-.0122	-.0142
26.000	.0142	.0141	.0119	.4332	.6458	-.4114	-.0118	-.0120	-.0164
27.000	.0144	.0153	.0119	.3317	.6793	-.4670	-.0129	-.0110	-.0178
28.000	.0149	.0166	.0127	.2622	.6785	-.5132	-.0145	-.0110	-.0188
29.000	.0155	.0170	.0129	.2996	.6891	-.4949	-.0145	-.0113	-.0196
30.000	.0163	.0170	.0136	.3697	.6654	-.4477	-.0143	-.0130	-.0197
32.000	.0216	.0231	.0165	.3412	.6503	-.4907	-.0200	-.0169	-.0262
34.000	.0233	.0232	.0220	.1681	.6704	-.6169	-.0279	-.0161	-.0305
36.000	.0233	.0287	.0207	.1754	.7038	-.5759	-.0215	-.0152	-.0318
38.000	.0254	.0301	.0197	.1262	.7604	-.5483	-.0144	-.0150	-.0357
40.000	.0269	.0303	.0255	.3350	.6066	-.5458	-.0299	-.0222	-.0316
42.000	.0288	.0326	.0237	.2395	.7095	-.5142	-.0275	-.0199	-.0378
44.000	.0309	.0322	.0257	.3628	.6705	-.4481	-.0270	-.0243	-.0375
46.000	.0333	.0318	.0246	.4302	.7153	-.3232	-.0230	-.0261	-.0405
48.000	.0353	.0325	.0237	.4792	.7693	-.1921	-.0198	-.0275	-.0452
50.000	.0395	.0314	.0243	.6286	.7685	-.0022	-.0152	-.0325	-.0466
52.000	.0418	.0361	.0241	.5682	.8177	-.0702	-.0184	-.0243	-.0538
54.000	.0452	.0402	.0244	.3886	.8464	-.1617	-.0214	-.0274	-.0630
56.000	.0475	.0419	.0263	.4794	.8339	-.0247	-.0207	-.0320	-.0631
58.000	.0488	.0410	.0260	.5420	.8457	.0098	-.0182	-.0328	-.0637
60.000	.0463	.0405	.0239	.4853	.8562	-.0355	-.0181	-.0398	-.0627
62.000	.0548	.0387	.0313	.7259	.8312	.2211	-.0151	-.0474	-.0622
64.000	.0402	.0376	.0327	.4832	.6498	-.3515	-.0300	-.0353	-.0452
66.000	.0430	.0406	.0386	.4127	.7691	-.2053	-.0260	-.0309	-.0561
68.000	.0465	.0441	.0247	.3766	.8275	-.2084	-.0242	-.0342	-.0639
70.000	.0467	.0510	.0267	.1196	.8545	-.4136	-.0209	-.0274	-.0710

TABLE B-5.

STATION 911828 LEVEL	MONTH CVP	7 CVD	CVT	R(P,T)	R(P,D)	R(T,D)	DCVP	DCVD	DCVT
.000	.0014	.0049	.0046	-.0822	.3598	-.9594	-.0081	-.0011	-.0017
.005	.0014	.0049	.0046	-.0702	.3491	-.9533	-.0061	-.0011	-.0017
1.000	.0013	.0023	.0036	-.0340	.3618	-.9440	-.0062	-.0010	-.0015
2.000	.0014	.0060	.0062	.2801	-.0566	-.9743	-.0107	-.0016	-.0012
3.000	.0016	.0058	.0052	.3876	-.1324	-.9050	-.0103	-.0021	-.0012
4.000	.0020	.0067	.0071	.3609	-.0856	-.9501	-.0118	-.0025	-.0015
5.000	.0024	.0056	.0077	.5588	-.2811	-.9529	-.0119	-.0035	-.0014
6.000	.0031	.0066	.0083	.6813	-.4038	-.9402	-.0118	-.0049	-.0014
7.000	.0039	.0062	.0087	.7699	-.4519	-.9172	-.0110	-.0063	-.0014
8.000	.0048	.0060	.0090	.7851	-.3781	-.8592	-.0102	-.0076	-.0018
9.000	.0059	.0058	.0092	.7917	-.2469	-.7875	-.0092	-.0093	-.0025
10.000	.0069	.0058	.0095	.7914	-.0932	-.6868	-.0084	-.0106	-.0033
11.000	.0060	.0056	.0088	.7850	.1959	-.4522	-.0064	-.0113	-.0048
12.000	.0069	.0069	.0080	.6742	.4919	-.3114	-.0061	-.0100	-.0076
13.000	.0096	.0102	.0081	.3440	.6622	-.4759	-.0098	-.0175	-.0116
14.000	.0096	.0159	.0111	-.1737	.7268	-.8026	-.0174	-.0048	-.0144
15.000	.0090	.0185	.0133	-.3498	.7403	-.8388	-.0227	-.0038	-.0143
16.000	.0082	.0184	.0134	-.4176	.7505	-.9139	-.0236	-.0032	-.0133
17.000	.0075	.0150	.0107	-.3305	.7355	-.8918	-.0183	-.0032	-.0117
18.000	.0072	.0121	.0084	-.2115	.7385	-.8152	-.0133	-.0034	-.0109
19.000	.0069	.0104	.0066	-.1904	.7812	-.7535	-.0101	-.0031	-.0108
20.000	.0068	.0093	.0064	-.1463	.7733	-.7404	-.0096	-.0032	-.0103
21.000	.0067	.0091	.0064	.0414	.7074	-.6770	-.0084	-.0040	-.0094
22.000	.0069	.0094	.0060	.1570	.7112	-.5827	-.0074	-.0045	-.0093
23.000	.0071	.0083	.0059	.1894	.7178	-.5477	-.0071	-.0047	-.0095
24.000	.0074	.0092	.0068	.1613	.6835	-.6101	-.0096	-.0050	-.0098
25.000	.0076	.0032	.0070	.2079	.6061	-.5910	-.0087	-.0054	-.0098
26.000	.0079	.0091	.0070	.2640	.6048	-.5451	-.0082	-.0058	-.0099
27.000	.0082	.0095	.0075	.2780	.6408	-.5495	-.0087	-.0063	-.0102
28.000	.0085	.0093	.0072	.3181	.6729	-.4872	-.0080	-.0065	-.0106
29.000	.0032	.0093	.0080	.4184	.6221	-.4498	-.0082	-.0079	-.0105
30.000	.0092	.0089	.0074	.4429	.6655	-.3745	-.0071	-.0077	-.0107
32.000	.0126	.0130	.0121	.4521	.5509	-.4953	-.0125	-.0118	-.0135
34.000	.0139	.0158	.0140	.3576	.5623	-.5711	-.0159	-.0121	-.0157
36.000	.0166	.0200	.0165	.2760	.6004	-.6030	-.0200	-.0132	-.0199
38.000	.0178	.0150	.0150	.5855	.5300	-.3030	-.0124	-.0176	-.0177
40.000	.0200	.0193	.0168	.4589	.6351	-.3943	-.0161	-.0175	-.0225
42.000	.0218	.0216	.0161	.3844	.7234	-.3593	-.0159	-.0164	-.0272
44.000	.0235	.0232	.0139	.3171	.8235	-.2769	-.0136	-.0142	-.0329
46.000	.0249	.0240	.0152	.3662	.8055	-.2548	-.0143	-.0162	-.0337
48.000	.0264	.0247	.0143	.3946	.8457	-.1674	-.0126	-.0160	-.0369
50.000	.0285	.0259	.0155	.3755	.8445	-.1794	-.0139	-.0172	-.0399
52.000	.0307	.0268	.0186	.4965	.7976	-.1273	-.0148	-.0225	-.0389
54.000	.0325	.0290	.0205	.4769	.7827	-.1733	-.0171	-.0240	-.0410
56.000	.0352	.0309	.0231	.5047	.7644	-.1708	-.0187	-.0274	-.0431
58.000	.0389	.0357	.0277	.4338	.7334	-.2944	-.0254	-.0299	-.0479
60.000	.0389	.0339	.0363	.5959	.5093	-.3847	-.0314	-.0413	-.0384
62.000	.0382	.0398	.0450	.5533	.3349	-.5935	-.0406	-.0434	-.0330
64.000	.0334	.0325	.0308	.4887	.5651	-.4426	-.0293	-.0317	-.0352
66.000	.0350	.0480	.0277	-.1587	.8206	-.6930	-.0407	-.0148	-.0552
68.000	.0324	.0521	.0371	-.1203	.7078	-.7864	-.0568	-.0174	-.0475
70.000	.0276	.0574	.0419	-.3365	.7267	-.8915	-.0717	-.0121	-.0432




Figure B-13.




Figure B-14.




Figure B-15.




Figure B-16.




Figure B-17.




Figure B-18.




Figure B-19.




Figure B-20.




Figure B-21.




Figure B-22.