



AD A137861

DEPARTMENT OF DEFENCE
DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION
MATERIALS RESEARCH LABORATORIES
MELBOURNE, VICTORIA

REPORT


MRL-R-892

**MANEUVERABILITY OF TORPEDOES IN THE
HORIZONTAL PLANE**

E.H. van Leeuwen

THE UNITED STATES NATIONAL
TECHNICAL INFORMATION SERVICE
IS AUTHORISED TO
REPRODUCE AND SELL THIS REPORT

Approved for Public Release



JULY, 1983

DTIC
ELECTE

FEB 14 1984

DTIC FILE COPY

84 02 14 084

E

DEPARTMENT OF DEFENCE
MATERIALS RESEARCH LABORATORIES

REPORT

MRL-R-892

MANEUVERABILITY OF TORPEDOES IN THE
HORIZONTAL PLANE

E.H. van Leeuwen

ABSTRACT

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

The equations of motion in the horizontal plane are studied for the case where the rudders of a torpedo are locked in either the port or starboard position, and secondly when held in the neutral position. For each case the equation of the resulting trajectory is found in terms of the known hydrodynamic coefficients. Effects of torpedo roll on the trajectory are also considered.

Approved for Public Release

POSTAL ADDRESS: Director, Materials Research Laboratories
P.O. Box 50, Ascot Vale, Victoria 3032, Australia

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

DOCUMENT CONTROL DATA SHEET

REPORT NO.

AR NO.

REPORT SECURITY CLASSIFICATION

MRL-R-892

AR-003-305

UNCLASSIFIED

TITLE

MANEUVERABILITY OF TORPEDOES IN THE HORIZONTAL PLANE

AUTHOR(S)

CORPORATE AUTHOR

van LEEUWEN, E.H.

Materials Research Laboratories
P.O. Box 50,
Ascot Vale, Victoria 3032

REPORT DATE

TASK NO.

SPONSOR

JULY, 1983

DST 82/193

DSTO

CLASSIFICATION/LIMITATION REVIEW DATE

CLASSIFICATION/RELEASE AUTHORITY
Superintendent, MRL
Physical Chemistry Division

SECONDARY DISTRIBUTION

Approved for Public Release

ANNOUNCEMENT

Announcement of this Report is Unlimited

KEYWORDS

Equations of Motion
Torpedoes
ManeuverabilityMathematical Models
Trajectory Equations

COSATI GROUPS

1201

1908

ABSTRACT

The equations of motion in the horizontal plane are studied for the case where the rudders of a torpedo are locked in either the port or starboard position, and secondly when held in the neutral position. For each case the equation of the resulting trajectory is found in terms of the known hydrodynamic coefficients. Effects of torpedo roll on the trajectory are also considered.

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

C O N T E N T S

	<u>Page No.</u>
1. INTRODUCTION	1
2. EQUATIONS OF MOTION IN THE HORIZONTAL PLANE	1
3. MANEUVERABILITY IN A NON-ROLLING COORDINATE FRAME	2
4. MANEUVERABILITY AND ROLL	6
5. DISCUSSION	7
6. NOMENCLATURE	8
7. REFERENCES	8

MANEUVERABILITY OF TORPEDOES IN THE HORIZONTAL PLANE

1. INTRODUCTION

The objective of this paper is to model mathematically, aspects relating to the maneuverability of a modified torpedo. Of particular interest are the analytical expressions for the trajectory of a dynamically stable torpedo executing maneuvers in the horizontal plane. It will be assumed here, that different trajectories result as a consequence of different rudder positions. For example if the rudders are set in either the port or starboard position the resulting trajectory is a circle, whereas if the rudders are set in a neutral position the trajectory is a straight line.

The equations of the trajectory can be calculated in terms of the hydrodynamic coefficients of the torpedo as will be shown in Section 3, using the equations of motion derived in [1]. In deriving the trajectory equations we are not concerned with the operation of the steering mechanism and to this end it is assumed that commands to turn the torpedo are carried out instantaneously with no lag time.

Finally in section 4 the turning circle of a torpedo which is rolled through an angle θ degrees is calculated in terms of the hydrodynamic coefficients of the torpedo.

2. EQUATIONS OF MOTION IN THE HORIZONTAL PLANE

The angular equations of motion for a torpedo moving along the x-axis in the horizontal plane through an ideal quiescent fluid can be expressed in a non-rolling coordinate frame in the ζ domain as [1]:

$$-C_{L_{\psi}} \psi + (C_{F_t} - m_L^*) \phi' + C_{L_{\delta}} \delta - A_{26}^* \phi'' = -m_T^* \psi' , \quad (2.1a)$$

and

$$C_M \psi + C_{M_d} \psi' + A_{26}^* \psi' + C_{M_\delta} \delta = \theta^* \phi'' , \quad (2.1b)$$

where nomenclature is that of a previous paper [1] and defined in section 6. In (2.1) the time coordinate t has been replaced by a non-dimensional arc length coordinate ζ , with ()' denoting differentiation with respect to ζ . The coordinate ζ is defined by:

$$\zeta := t t_c^{-1} ,$$

where $t_c := v^{-1} l$ is called the characteristic time, l is the length of the torpedo and v its velocity.

3. MANEUVERABILITY IN A NON-ROLLING COORDINATE FRAME

Aspects of maneuverability which are of interest here are (a) the turning radius of a torpedo corresponding to the path aa' in figure 3.1 when the rudders are locked in either the port or starboard position and (b) the equation of the path $a'a''$ corresponding to the case where the rudders are set in a neutral position.

When the trajectory is an arc the radius of the turn maneuver R , maybe found by solving (2.1) with δ constant (i.e., $\delta=k$). Similarly if the trajectory $a'a''$ is to be found, then solutions to (2.1) are sought with $\delta = 0$.




Figure 3.1. Torpedo trajectory in the horizontal plane.

Case (a) Calculation of R.

In order to calculate the equation of the trajectory aa' and the radius of curvature R, the angles ϕ and ψ need to be derived as a function of the independent variable ζ . ϕ can be found on decoupling (2.1a) and (2.1b) and yields an ordinary differential equation with constant coefficients:

$$\alpha_4 \phi''''(\zeta) + \alpha_3 \phi'''(\zeta) + \alpha_2 \phi''(\zeta) + \alpha_0 k = 0, \quad (3.1)$$

where

$$\begin{aligned} \alpha_4 &= m_T^* \theta^* - A_{26}^{*2}, \\ \alpha_3 &= -m_T^* C_{M_d} + A_{26}^* (C_{F_t} - m_L^*) - C_{L_\psi} \theta^* - C_M A_{26}^*, \\ \alpha_2 &= -(m_L^* - C_{F_t}) C_M + C_{L_\psi} C_{M_d}, \\ \alpha_0 &= C_M C_{L_\delta} + C_{L_\psi} C_{M_\delta}. \end{aligned} \quad (3.2)$$

Applying the Laplace transform method to (3.1) gives:

$$\bar{\phi}(s) = \frac{s^3 \phi_0 \alpha_4 + s^2 (\alpha_4 \phi_0' + \alpha_3 \phi_0) + s (\alpha_4 \phi_0'' + \alpha_3 \phi_0' + \phi_0 \alpha_2) - \alpha_0 k}{s^2 (\alpha_4 s^2 + \alpha_3 s + \alpha_2)}, \quad (3.3)$$

where $\phi(s)$ is the Laplace transform of the unknown function $\phi(t)$. The initial conditions $\phi_0(0)$, $\phi_0'(0)$ and $\phi_0''(0)$ completely determine the second term of (3.1). For a torpedo moving from a straight and level trajectory to a circular trajectory the initial conditions are $\psi = \phi_0 = \phi_0' = 0$ and from (2.1)

$$\phi_0''(0) = \frac{k(m_T^* C_{M_\delta} - C_{L_\delta} A_{26}^*)}{m_T^* \theta^* - A_{26}^{*2}}.$$

Performing a partial fraction expansion on (3.3) and then taking the inverse Laplace transform yields:

$$\begin{aligned} \phi(\zeta) &= \frac{T_3}{a_+ a_-} + \frac{T_4(a_+ + a_-)}{(a_+ a_-)^2} + \frac{T_4 \zeta}{a_+ a_-} \\ &+ \frac{(T_1 a_+^3 - T_2 a_+^2 + T_3 a_+ - T_4) e^{-a_+ \zeta}}{a_+^2 (a_+ - a_-)} \end{aligned} \quad (3.4)$$

$$+ \frac{(-T_1 a_-^3 + T_2 a_-^2 - T_3 a_- + T_4) e^{-a_- \zeta}}{a_-^2 (a_+ - a_-)},$$

where

$$T_1 := \psi_0',$$

$$T_2 := \phi_0' + \alpha_3 \phi_0 \alpha_4^{-1},$$

(3.5)

$$T_3 := \phi_0'' + (\alpha_3 \phi_0' + \phi_0 \alpha_2) \alpha_4^{-1},$$

$$T_4 := -\alpha_0 k \alpha_4^{-1},$$

and a_+ and a_- are the roots of the quadratic:

$$\alpha_4 s^2 + \alpha_3 s + \alpha_2 = 0,$$

that is

$$-a_{\pm} = \frac{-\alpha_3 \pm (\alpha_3^2 - 4\alpha_2\alpha_4)^{1/2}}{2\alpha_4}.$$

The angle ψ can be found by eliminating ψ' from (2.1a) and (2.1b) giving

$$\psi(\zeta) = T_5 \{\alpha_4 \phi'' - T_6 \phi' - T_7 \delta\}, \quad (3.6)$$

where

$$T_5 := (A_{26}^* C_{L_\psi} - m_L^* C_{M_d})^{-1},$$

$$T_6 := (m_T^* C_{M_d} - A_{26}^* (C_{F_t} - m_L^*)) , \quad (3.8)$$

$$T_7 := (-A_{26}^* C_{L_\delta} + m_T^* C_{M_\delta}).$$

Differentiating (3.4) and substituting ϕ' and ϕ'' into (3.6) yields:

$$\psi(\zeta) = \frac{(T_1 a_+^3 - T_2 a_+^2 + T_3 a_+ - T_4)(a_+ \alpha_4 + T_6) e^{-a_+ \zeta}}{a_+ (a_+ - a_-)}$$

$$\begin{aligned}
& + \frac{(-T_1 a_-^3 + T_2 a_-^2 - T_3 a_- + T_4)(a_- \alpha_4 + T_6)}{a_- (a_+ - a_-)} e^{-a_- \zeta} \\
& + \left(\frac{T_6 \alpha_0}{a_+ a_-} - T_7 \right) k T_5,
\end{aligned} \tag{3.7}$$

In figure 3.1 the angle $\xi = \psi + \phi$ is simply the sum of (3.4) and (3.7). The first two terms of (3.7) and the last two terms of (3.4) are transients and die away exponentially as ζ increases. For large values of ζ , the dominant terms are:

$$\xi \sim \frac{T_3}{a_+ a_-} + \frac{T_4 (a_+ + a_-)}{(a_+ a_-)^2} + k \left(\frac{T_6 \alpha_0}{a_+ a_-} - T_7 \right) + \frac{T_4 \zeta}{a_+ a_-}, \tag{3.9}$$

and is called the steady state solution. Under the coordinate transformation:

$$\zeta^* = \zeta + \left(\frac{T_3}{a_+ a_-} + \frac{T_4 (a_+ + a_-)}{(a_+ a_-)^2} + k \left(\frac{T_6 \alpha_0}{a_+ a_-} - T_7 \right) \right) \frac{a_+ a_-}{T_4},$$

(3.9) may be written as:

$$\xi = \frac{T_4 \zeta^*}{a_+ a_-}. \tag{3.10}$$

It follows from the above equation that the trajectory of the torpedo is a circle with radius

$$R = a_+ a_- T_4^{-1},$$

which in terms of the hydrodynamic coefficients and the rudder angle k can be expressed as:

$$R = \frac{(m_L^* - C_F) C_M - C_M C_L \psi}{(C_M C_{L_\delta} + C_L C_{M_\delta}) k}. \tag{3.11}$$

From (3.11) it follows that the radius R is inversely proportional to k if the composite change in the hydrodynamic coefficients is small, compared to changes in k .

Case (b) Equation of the Trajectory a'a''

The equation of the trajectory with neutral rudder response (ie., $k=0$) corresponding to the path a'a" in figure 3.1 can be found if ξ is small. This is achieved as follows. If $d\xi$ is a differential element of arc along the trajectory then,

$$D_{\xi} x = \cos \xi \text{ and } D_{\xi} y = \sin \xi . \quad (3.12)$$

Assuming ξ to be small and integrating (3.12) gives

$$\int_a^x du = \int_0^{\xi} dv \text{ or } x - a = \xi, \quad (3.13a)$$

and

$$y = \int_0^{\xi} \xi(\rho) \Big|_{k=0} d\rho. \quad (3.13b)$$

The asymptotic form of (3.13b) for large ξ is a straight line given by:

$$y \sim \frac{\gamma_3 x}{a_+ a_-} + \frac{1}{(a_+ a_-)^2} \{ T_3 a_+ a_- (1 + T_5 T_6) - T_3 (a_+ + a_-) + a_+^2 a_-^2 (T_1 T_5 T_6 + \alpha_4 T_2 T_5 + T_1 (a_+ + a_-)) \} + \frac{\gamma_3 a}{a_+ a_-} . \quad (3.14)$$

Thus it can be concluded if the rudder angle is set to the neutral position (ie., $k=0$) the torpedo comes out of the turn aa' and into a straight line a'a".

4. MANEUVERABILITY AND ROLL

Consider a dynamically stable torpedo moving rectilinearly along the x-axis with velocity V . If the torpedo rolls through an angle of θ degrees, when turning commences, then the equations governing the motion are similar to (2.1) but with the terms $C_{L_{\delta}} \delta$ and $C_{M_{\delta}} \delta$ replaced by:

$$C_{L_{\delta}} \delta = C_{L_{\delta r}} \delta r \cos \theta - C_{L_{\delta e}} \delta e \sin \theta ,$$

and

$$C_{M_{\delta}} \delta = -C_{M_{\delta e}} \delta e \sin \theta + C_{M_{\delta r}} \delta r \cos \theta ,$$

where δe and δr are the elevator and rudder angles respectively. Applying the procedure outlined in section 3, the decoupled equation for ϕ is similar to (3.1) but with the term αk replaced by:

$$(C_M C_{L_{\delta r}} + C_{L_{\psi}} C_{M_{\delta r}}) \delta r \cos \theta - (C_{L_{\psi}} C_{M_{\delta e}} + C_{L_{\delta e}} C_M) \delta e \sin \theta. \quad (4.1)$$

Assuming (4.1) is independent of ζ , the asymptotic form of ξ is again found to be:

$$\xi = \frac{\tau_4 \zeta^*}{a_+ a_-},$$

where radius of the trajectory aa' is now:

$$R = \frac{-C_{L_{\psi}} C_M + (m_L^* - C_{F_t}) C_{M_d}}{(C_M C_{L_{\delta r}} + C_{L_{\psi}} C_{M_{\delta r}}) \delta r \cos \phi - (C_{L_{\psi}} C_{M_{\delta e}} + C_M C_{L_{\delta e}}) \delta e \sin \phi}, \quad (4.2)$$

which reduces to (3.11) if $\theta=0$ and $\delta r=k$. If the degree of roll does not become large, we can put $\sin \theta \approx \theta$ and $\cos \theta \approx 1$ in (4.2). Assuming the ratio

$$\frac{C_{L_{\psi}} C_{M_{\delta e}} + C_M C_{L_{\delta e}}}{C_M C_{L_{\delta r}} + C_{L_{\psi}} C_{M_{\delta r}}},$$

is constant for small θ , then (4.2) takes the form:

$$R \approx R_0 \left[1 - \frac{(C_{L_{\psi}} C_{M_{\delta e}} + C_M C_{L_{\delta e}})}{(C_M C_{L_{\delta r}} + C_{L_{\psi}} C_{M_{\delta r}})} \frac{\delta e}{\delta r} \theta \right]$$

where R_0 is the radius of the turning circle in the absence of roll and is given by (3.11) with $k=\delta r$.

5. DISCUSSION

The treatment of maneuverability discussed in this paper is idealized since consideration is given only to the hydrodynamic aspects of turning. It has been assumed that when the rudder of the torpedo is locked in a particular position, a hydrodynamic pressure is created which is sufficient to enable a turn to commence immediately. The "lag" time is taken to be zero. Under these assumptions the trajectory of a torpedo in the horizontal plane with rudders fixed can be calculated and the results are presented in

section 3. In section 4 the radius of a turn has been derived with the torpedo rolled through an angle of θ degrees. Provided the hydrodynamic coefficients of the torpedo are known, the radii (3.11) or (4.2) can be explicitly found.

6. NOMENCLATURE

$C_{L\psi}$	Lift coefficient (horizontal plane) ,
C_{F_t}	Transverse force coefficient ,
$C_{L\delta}$	Rudder lift coefficient ,
$C_{M\delta}$	Rudder moment coefficient ,
C_{M_d}	Damping moment coefficient corrected for entrained water (horizontal plane) ,
C_M	Moment coefficient corrected for entrained water ,
A_{26}^*	Component of the added mass tensor ,
m_T^*	Longitudinal mass due to entrained water ,
m_L^*	Transverse mass due to entrained water ,
I^*	Moment of inertia corrected for entrained water (horizontal plane) ,
δ	Rudder angle,
R	Radius of curvature of turn maneuver,
ϕ	Orientation angle in the horizontal plane (yaw angle),
ψ	Angle of attack in yaw,

7. REFERENCES

1. Van Leeuwen, E.H., 1982 "A study of the Motion and Stability of Torpedoes in 3 Degrees of Freedom", MRL-R-891.

DISTRIBUTION LIST

MATERIALS RESEARCH LABORATORIES

DIRECTOR
Superintendent, Physical Chemistry Division
Dr G.J. Jenks
Dr B.W. Thorpe
Library (2 copies)
Dr E.H. van Leeuwen

DEPARTMENT OF DEFENCE

Chief Defence Scientist/Deputy Chief Defence Scientist/ (1 copy)
Controller, Projects and Analytical Studies/
Superintendent, Science and Technology Programme
Army Scientific Adviser
Air Force Scientific Adviser
Navy Scientific Adviser
Officer-in-Charge, Document Exchange Centre (17 copies)
Technical Reports Centre, Defence Central Library
Central Office, Directorate of Quality Assurance - Air Force
Deputy Director Scientific and Technical Intelligence, Joint
Intelligence Organisation.
Librarian, Bridges Library
Librarian, Engineering Development Establishment
Librarian, (Through Officer-in-Charge), Materials Testing
Laboratories, ALEXANDRIA, N.S.W.
Senior Librarian, Aeronautical Research Laboratories
Senior Librarian, Defence Research Centre Salisbury, S.A.
Defence Science Representative, (Summary Sheets Only)
Australia High Commission, London.
Counsellor Defence Science, Washington D.C. (Summary Sheets Only)

DEPARTMENT OF DEFENCE SUPPORT

Deputy Secretary, DDS
Head of Staff, British Defence Research & Supply Staff (Aust.)

OTHER FEDERAL AND STATE DEPARTMENTS AND INSTRUMENTALITIES

NASA Canberra Office, Woden, A.C.T.
The Chief Librarian, Central Library, C.S.I.R.O.
Library, Australian Atomic Energy Commission Research Establishment

DISTRIBUTION LIST

(Cont.)

MISCELLANEOUS - AUSTRALIA

Librarian, State Library of NSW, Sydney NSW
University of Tasmania, Morris Miller Library, Hobart, TAS.

MISCELLANEOUS - OVERSEAS

Library - Exchange Desk, National Bureau of Standards, U.S.A.
UK/USA/CAN/NZ ABCA Armies Standardisation Representative (4 copies)
The Director, Defence Scientific Information & Documentation
Centre, India
Military, Naval and Air Adviser, High Commission of India,
Canberra
Director, Defence Research Centre, Kuala Lumpur, Malaysia
Exchange Section, British Library, U.K.
Periodicals Recording Section, Science Reference Library,
British Library, U.K.
Library, Chemical Abstracts Service
INSPEC: Acquisition Section, Institute of Electrical
Engineers, U.K.
Engineering Societies Library, U.S.A.
Aeromedical Library, Brooks Air Force Base, Texas, U.S.A.
Ann Germany Documents Librarian, The Centre for Research Libraries,
Chicago I11.
Defense Attache, Australian Embassy, Bangkok, Thailand Att. D. Pender