

AD-A139 619


MEASUREMENT OF ATMOSPHERIC TRANSMISSION OVER LONG PATHS
IN THE INFRARED S. (U) TECHNION - ISRAEL INST OF TECH
HAIFA DEPT OF PHYSICS U P OPPENHEIM ET AL. 29 FEB 84
EORD-TR-84-12 AFOSR-83-0023 F/G 4/1

1/1

UNCLASSIFIED

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS - 1963 - A

Grant AFOSR-83-0023

(2)

Interim Scientific Report

MEASUREMENT OF ATMOSPHERIC TRANSMISSION OVER LONG PATHS
IN THE INFRARED SPECTRAL REGION

by

U.P. Oppenheim
S.G. Lipson

Department of Physics
Technion - Israel Institute of Technology
Haifa 32000, Israel

AD A139619

29 February, 1984.

Interim Scientific Report, 1 Oct. 1982 - 31 Dec. 1983.

This research is being conducted at Technion Research and Development Foundation Ltd. under Grant No. AFOSR-83 -0023 sponsored by the Air Force Office of Scientific Research, United States Air Force.

All rights reserved by Technion R & D Foundation.

Prepared for European Office of Aerospace Research and Development,
London, England.

DTIC
SELECTED
APR 2 1984
A

This document has been approved
for public release and sale; its
distribution is unlimited.


DTIC FILE COPY

84 03 28 070

21 March 1984


This report has been reviewed by the EOARD Information Office and is releasable to the National Technical Information Service (NTIS). At NTIS it will be releasable to the general public, including foreign nationals.

This technical report has been reviewed and is approved for publication.



JOHN D. WARBURTON
Major, USAF
Chief, Geophysics & Space

FOR THE COMMANDER



ALBERT J. ROSA
Lt Colonel, USAF
Chief Scientist

Accession For	
NTIS GRA&I	☒
ERIC TAB	☐
Unannounced	☐
Distribution	
by	
Distribution	
Availability Codes	
AVAIL AND/OR	
9-193	
A-1	

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO. AD-A139619	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) MEASUREMENT OF ATMOSPHERIC TRANSMISSION OVER LONG PATHS IN THE INFRARED SPECTRAL REGION		5. TYPE OF REPORT & PERIOD COVERED Interim Scientific 1 Oct. 82 - 31 Dec. 1983
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) U.P. OPPENHEIM S.G. LIPSON		8. CONTRACT OR GRANT NUMBER(s) AFOSR-83-0023
9. PERFORMING ORGANIZATION NAME AND ADDRESS Technion R & D Foundation Ltd. P.O. Box 4910, Haifa, ISRAEL		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Project/task: 2301/D1
11. CONTROLLING OFFICE NAME AND ADDRESS EOARD/LNI 223/231 Old Marylebone Road London NW1 5th, U.K.		12. REPORT DATE 29 Feb. 1984.
		13. NUMBER OF PAGES 5
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) AFOSR-PKZA Building 410 Bolling AFB, Wash. D.C. 20332		15. SECURITY CLASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Infrared Transmission Atmosphere Spectral Measurement Radiometry		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Instrumentation built for long path spectroradiometric measurements is described. Preliminary results for atmospheric transmission over a 7 km path are reported. A comparison is made with LOWTRAN computations.		

REPORT OF INVENTIONS AND SUBCONTRACTS (Pursuant to "Patent Rights" Contract Clause) (See Instructions on Reverse Side)					FORM APPROVED OMB NO. 22-R160	
1 NAME AND ADDRESS OF CONTRACTOR (Include Zip Code)			2 CONTRACT NUMBER			
Technion Research and Development Foundation Ltd. P.O. Box 4910 Haifa, ISRAEL			GRANT AFOSR-83-0023			
3 TYPE OF REPORT (Check One)			4. INTERIM ☐ 5. FINAL ☒			
SECTION I - INVENTIONS ("Subject Inventions")						
4. INVENTION DATA (Listed below are all inventions required to be reported) (If "None," so state)						
(i) NAME OF INVENTOR(S)	(ii) TITLE OF INVENTION	(iii) CONTRACTOR DISCLOSURE IDENTIFICATION NUMBER OR PATENT APPLICATION SERIAL NUMBER	(iv) CONTRACTOR ELECTS TO FILE U.S. PATENT APPLICATION	(v) CONFIRMATORY LICENSE OR ASSIGNMENT FORWARDED TO CONTRACTING OFFICER		
None	None		YES NO	YES NO		
SECTION II - SUBCONTRACTS (Containing a "Patent Rights" Clause)						
5. SUBCONTRACT DATA (Listed is information required but not previously reported for Subcontract(s) (If "None," so state)						
(i) NAME AND ADDRESS OF SUBCONTRACTOR (Include Zip Code)	(ii) SUBCONTRACT NUMBER	(iii) SUBCONTRACT PATENT RIGHTS CLAUSE	(iv) SUBCONTRACT WORK TO BE PERFORMED UNDER SUBCONTRACT	(v) SUBCONTRACT DATES		
None			None	AWARD COMPLETION		
SECTION III - CERTIFICATION						
CONTRACTOR CERTIFIES THAT PROMPT IDENTIFICATION AND TIMELY DISCLOSURE OF SUBJECT INVENTIONS PROCEDURES HAVE BEEN FOLLOWED						
DATE	NAME AND TITLE OF AUTHORIZED OFFICIAL (Print or Type)					
29 Feb. 1984	Mr. Y. Devir, Director for Finance, Technion, R & D Found. Ltd.					
						SIGNATURE

BACKGROUND

For the last several years we have been measuring transmittance in the 2.8-15 micron region in various parts of Israel, using a mobile spectro-radiometric laboratory. In particular, we have paid attention to the contribution of aerosols and water vapor to the absorption in this spectral region. While the LOWTRAN computer code is based mainly on laboratory measurements it was thought that a comparison with field measurements would be appropriate, with special emphasis on reliable determinations of water vapor pressure and aerosols. For this purpose we developed a filter-type radiometer and used it during our field measurements for in situ determinations of water vapor and aerosol content of the atmosphere.

Our plan was to carry out transmittance measurements in areas of high humidity and temperature during 1983 and to turn to the other extreme of low humidity and temperature during 1984. The present report summarizes the results of the first half of the plan.

THE FILTER RADIOMETER

The instrument developed and built for the present study consisted of a parabolic collimating mirror of 20 cm diameter and an f-number of 5. It had a Newtonian mirror of 4.76 cm diameter, mounted at 23.4 cm from the detector. The length of the box in which the radiometer was mounted was 120 cm and its cross section was 30x30 cm. The parabolic mirror could be moved along its

axis for focussing the image of the source on the detector.

A special filter wheel was placed in front of the detectors, containing a number of filters, centered at 0.905, 1.06, 2.235, 0.55 and 0.6328 micron, as well as an open aperture for viewing the unobstructed source. A second filter wheel was placed behind the first, with filters centered at 0.39, 1.06, 1.14, 1.243 and 1.591 micron, as well as an open aperture. Behind these two wheels was a detector wheel, containing a Si and PbSe detector (mounted together) and a Ge detector, each with its own preamplifier and power supply.

Aerosol size distribution and concentration were derived using the inversion method developed by our group (see: "Atmospheric aerosols investigated by inversion of experimental transmittance data", E. Trakhovsky, S.G. Lipson and A.D. Devir, *Applied Optics* 21, 3005-3010 (1982)). The radiometer described above was used for these measurements.

The same radiometer, used with the filters at 1.06 and 1.15 micron, allowed a measurement of the integrated water vapor density along the line of sight. This method was also developed by our group and described in a paper: "Integrated water vapor density along long atmospheric paths determined by radiometric methods", E. Trakhovsky, A.D. Devir and S.G. Lipson, *Infrared Physics* 21, 343-348 (1981).

The new radiometer was aligned in the laboratory using a $6328\text{\AA}^0$ laser for checking parallelism and focus. The field of view of the detectors was tested and found to be about 2 to 3 mrad. Uniformity of response across the detector area was found to be very good in the case of Ge and Si, but a roll

off of about 10% was found for the PbSe detector. Linearity of response as a function of irradiance was found to be good over 3 orders of magnitude in the range of intensities used in the present experiments. However, direct sunlight entering the radiometer caused saturation of all three detectors. This effect was avoided by placing special baffles and a removable shield around the detectors.

FIELD EXPERIMENTS

Early measurements of transmittance in the 2.5 to 15 micron region were carried out during 1981 in the Dead Sea area. Because of uncertainties in the attendant measurements of humidity and aerosols it was decided to repeat these experiments using the new filter radiometer. A climatic study of Israel revealed that the Dead Sea area, because of its surrounding desert, is actually somewhat drier than the coastal plain of Israel which borders on the Mediterranean Sea. The highest average values of absolute humidity in Israel (about 20 torr of H₂O vapor) are expected during the months of July-August in³ stretch of coast between Gaza and Haifa.

It was therefore decided to do a transmittance measurement in the summer of 1983, and a site near Habonim (20 km south of Haifa) was selected.

The Exotech Model 10 Spectroradiometer was placed at distances of 1.02 km and 7.35 km from a blackbody source (kept at 2100°C). The transmittance was measured using the method described by A. Ben-Shalom, D. Cabib, A.D. Devir, D. Goldschmidt, S.G. Lipson and U.P. Oppenheim ("Spectral characteristics of IR transmittance of the atmosphere in the region 2.8-14 microns - preliminary measurements", Infrared Physics 20, 165-174 (1980)).

Several expeditions to this site were undertaken during July 1983. Every time the filter radiometer was placed alongside the Exotech radiometer and the 2100°C blackbody source was viewed by both instruments. The filter radiometer was used for a determination of H₂O content as well as visual range and aerosol size distribution.

A typical example of transmittance measured in the 8-14 micron region is shown in Fig. 1. The upper curve represents the experimental results, while the lower shows the LOWTRAN-4 calculation for the parameters in the upper right hand corner of the Figure. It is seen that the experimental transmittance curve is higher than the calculated curve by a considerable amount. By assuming the LOWTRAN-4 code to be correct for all atmospheric constituents except for the H₂O continuum, it is possible to derive from Fig. 1 new values for $C_s(\lambda)$, the self-broadened attenuation coefficient (and its dependence on wavelength), as well as a new value for the constant γ . This study is now in progress.

Since the highest H₂O pressure attained was only 16.7 torr in the present experiments, another field trip is planned for the summer of 1984. In the winter (February-March 1984) an attempt will be made to measure transmittance for very low H₂O pressures, probably in the Golan Heights. Water vapor pressures of about 5 torr will hopefully be attained.




Fig. 1. Atmospheric transmittance measurements (upper curve) compared with LOWTRAN-4 calculation (lower curve) in the 7-14 micron region. Measurement was made in the Habonim area.

END

FILMED

5-84

DTIC