

AD-A141 162

INTERIM REPORT FOR GRANT AFOSR-82-0033(U) TEXAS A AND M 1/1
UNIV COLLEGE STATION DEPT OF ELECTRICAL ENGINEERING
D R HALVERSON FEB 84 AFOSR-TR-84-0364 AFOSR-82-0033

UNCLASSIFIED

F/G 9/3

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AFOSR-TR- 84 - 0364

INTERIM REPORT FOR GRANT AFOSR-82-0033

3

AD-A141 162

Submitted by

Don R. Halverson
Department of Electrical Engineering
Texas A&M University
College Station, Texas 77843

ABSTRACT

A number of results were obtained pertaining to signal detection and block truncation coding for image compression. These results led to improved performance over previous approaches, with special attention given to methods which required less statistical knowledge and which were easier to implement. In particular, use of robustness techniques was employed to allow the exploitation of whatever knowledge was available, while retaining insensitivity to the remaining inexactness in knowledge. In addition, because the presence of dependency in the underlying random processes often complicates detector design, investigations into when weak dependency could be ignored were undertaken. Finally, some results were obtained which allowed relaxing stationarity assumptions which were placed on the signal in earlier work.

DTIC FILE COPY

DTIC
S MAY 17 1984 D
A

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH
NOTICE OF TRANSMITTAL TO DTIC
This technical report has been reviewed and approved for public release IAW AFR 130-12.
Distribution is unlimited.

Research and Development Division

84 05 15 238

Approved for public release;
distribution unlimited.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited.	
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE			
4. PERFORMING ORGANIZATION REPORT NUMBER(S)		5. MONITORING ORGANIZATION REPORT NUMBER(S) AFOSR-TR- 84 - 0364	
6a. NAME OF PERFORMING ORGANIZATION Texas A&M University	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION Air Force Office of Scientific Research	
6c. ADDRESS (City, State and ZIP Code) Department of Electrical Engineering College Station TX 77843		7b. ADDRESS (City, State and ZIP Code) Directorate of Mathematical & Information Sciences, Bolling AFB DC 20332	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION AFOSR	8b. OFFICE SYMBOL (If applicable) NM	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER AFOSR-82-0033	
8c. ADDRESS (City, State and ZIP Code) Bolling AFB DC 20332		10. SOURCE OF FUNDING NOS.	
		PROGRAM ELEMENT NO. 61102F	PROJECT NO. 2304
		TASK NO. AS	WORK UNIT NO.
11. TITLE (Include Security Classification) INTERIM REPORT FOR GRANT AFOSR-82-0033			
12. PERSONAL AUTHOR(S) Don R. Halverson			
13a. TYPE OF REPORT Interim	13b. TIME COVERED FROM 1/1/83 TO 31/12/83	14. DATE OF REPORT (Yr., Mo., Day) FEB 84	15. PAGE COUNT 11
16. SUPPLEMENTARY NOTATION			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB. GR.	
19. ABSTRACT (Continue on reverse if necessary and identify by block number) A number of results were obtained pertaining to signal detection and block truncation coding for image compression. These results led to improved performance over previous approaches, with special attention given to methods which required less statistical knowledge and which were easier to implement. In particular, use of robustness techniques was employed to allow the exploitation of whatever knowledge was available, while retaining insensitivity to the remaining inexactness in knowledge. In addition, because the presence of dependency in the underlying random processes often complicates detector design, investigations into when weak dependency could be ignored were undertaken. Finally, some results were obtained which allowed relaxing stationarity assumptions which were placed on the signal in earlier work.			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT. ☐ DTIC USERS ☐		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a. NAME OF RESPONSIBLE INDIVIDUAL CPT Brian W. Woodruff		22b. TELEPHONE NUMBER (Include Area Code) (202) 767- 5027	22c. OFFICE SYMBOL NM

PERSONNEL

PRINCIPLE INVESTIGATOR: Don R. Halverson

GRADUATE RESEARCH ASSISTANTS: Julius P. Bleker
Michael W. Thompson



Accession For	
NTIS GPA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	

A-1

PUBLICATIONS SUPPORTED BY GRANT AFOSR-82-0033

1. D.R. Halverson, N.C. Griswold, and G.L. Wise, "On generalized block truncation coding quantizers for image compression", Proc. 1982 Conf. on Information Sciences and Systems, Princeton, N.J., March 17-19, 1982, pp. 47-52.
2. D.R. Halverson, "On the use of limiting in conjunction with the detection of signals in partially contaminated noise", Proc. 1982 Allerton Conf. on Communication, Control, and Computing, Monticello, Ill., October 6-8, 1982, pp. 733-738.
3. J.P. Bleker and D.R. Halverson, "Discrete time detection of time varying signals in dependent noise," Proc. 1983 Conf. on Information Sciences and Systems, Baltimore, Md., March 23-25, 1983, pp. 519-524.
4. D.R. Halverson, G.L. Wise, and M.W. Thompson, "Robust detection of a constant signal in Laplace noise," Proc. 1983 Conf. on Information Sciences and Systems, Baltimore, Md., March 23-25, 1983, pp. 228-232.
5. D.R. Halverson and G.L. Wise, "Signal detection when dependence is neglected," Proc. 1983 Annual Allerton Conf. on Communication, Control, and Computing, Monticello, Ill., October 5-7, 1983, pp. 622-630.
6. D.R. Halverson, G.L. Wise, and H.V. Poor, "On the performance of two simplified approaches to memoryless discrete time detection in dependent noise", J. Combinatorics, Information & System Sciences, vol. 7, pp. 1-9, Sept. 1982.
7. D.R. Halverson, "On the implementation of a block truncation coding algorithm", IEEE Trans. Commun., vol. COM-30, pp. 2482-2484, November 1982.
8. D.R. Halverson and G.L. Wise, "On an aspect of matched filters in continuous and discrete time", Circuits, Systems, and Signal Processing, vol. 2, pp. 269-276, Fall 1983.
9. D.R. Halverson and G.L. Wise, "Approximately optimal memoryless detection of random signals in dependent noise", IEEE Trans. Inform. Theory, March 1984.
10. D.R. Halverson, N.C. Griswold, and G.L. Wise, "A generalized block truncation coding algorithm for image compression," to appear in IEEE Trans. ASSP.
11. D.R. Halverson and G.L. Wise, "A result on neglecting dependence in signal detection," to appear in IEEE Trans. Inform. Theory.

SUMMARY OF RESEARCH

The research supported by Grant AFOSR-82-0033 was primarily concerned with signal detection, however some effort was also directed toward the area of block truncation coding for image compression. Results obtained pertaining to the latter will be summarized first.

Block truncation coding (BTC) is a technique for image compression which is easy to implement and often possesses good performance characteristics, relative to other approaches, even in the presence of many channel errors. Furthermore, the BTC algorithm does not depend on knowledge of the specific underlying statistical distributions, but rather on sample moments. The basic BTC technique employs a two level quantizer whose output levels are obtained by matching sample moments. The quantizer's threshold is either taken a priori to equal the sample mean (and thus the output levels are chosen so that the first two sample moments are preserved), or the threshold is chosen so as to preserve a third sample moment. The latter approach, while somewhat more complicated to implement, often yields improved performance since three moments are preserved instead of two.

The developers of the technique presented formulas specifying the quantizer threshold and output levels so that the first three sample moments were supposedly preserved. Unfortunately, however, the formula specifying the quantizer threshold contained an error, and one result we therefore obtained was a correction of this quantity. Moreover, the developers of the technique noted that rounding a certain quantity to an integer was at times necessary in practice; however, there existed ambiguity in precisely at what point in the algorithm the rounding should occur. We therefore investigated the perturbation of the relevant quantity, and found that it was fortunately preferable from the standpoint of all three moments for the rounding to be done consistently in one way. We furthermore investigated the effects of rounding the quantity on the performance and noted that for very many cases it should not be serious. These results were delineated in #7 of the publication list.

Noting that the BTC approach preserves sample moments (two moments with one method and three with the other), we also investigated whether

or not improved performance could be obtained by employing moments other than the first two or three. We found that the original BTC scheme could be generalized to yield a family of moment preserving quantizers using higher sample moments. In particular, we found closed form expressions for the quantizer output levels which preserved the n -th and $2n$ -th moments when a threshold equal to the L_n norm of the samples was employed; we also found closed form expressions specifying the quantizer output levels and threshold which preserved the n -th, $2n$ -th, and $3n$ -th moments. We then applied these results to various example images and found that improvement in performance was obtainable by the use of higher moments, both from the standpoint of mean absolute and mean squared error. Finally, we noted that there was a subclass of this family of moment preserving quantizers for which practical difficulties in implementation exist; we then showed that frequently this subclass could be avoided to still obtain good performance. These results were delineated in #1 and #10 of the publication list.

A number of results pertaining to the detection of signals in non-Gaussian noise were obtained. For example, a classical detector of time varying deterministic signals in dependent noise is the matched filter, which maximizes the output signal to noise power ratio; it is also Neyman-Pearson optimal in the particular case when the noise is Gaussian. In many situations it is reasonable to expect that the signal will be known at discrete instants, thus admitting the design of the discrete time matched filter. However, it is often a very different matter to assume that the signal will be known exactly as a closed form analytical expression over, for example, an interval of time, which would be necessary for the design of a matched filter in continuous time. While the signal may thus be incompletely known, it is reasonable to expect that in many cases it could be modeled as bandlimited. If we furthermore assume the signal is known at a fixed number of instants, we might hope that a continuous time filter could be designed which would be insensitive to the remaining inexactness in our knowledge of the signal. Such a filter might also have the potential for improved performance over the discrete time filter. Using a saddlepoint criterion, we obtained a result which specified the form of such a filter.

We then showed that the saddlepoint criterion did indeed impart robustness into the filter; in fact, the output signal to noise power ratio was shown to be invariant over all appropriate continuous time signals considered. Moreover, we also showed that the performance (as measured by output signal to noise power ratio) of this robust continuous time filter upper bounded that of the discrete time filter. Finally, we showed by way of example that strict improvement in performance over the discrete time filter was possible. Employment of continuous time would thus seem to be useful even in some cases which appear appropriate to discrete time. These results were delineated in #8 of the publication list.

We also investigated a situation where inexact knowledge of the statistics of the noise was present for the discrete time detection of time varying deterministic signals in i.i.d. non-Gaussian noise. In earlier work employing the canonical form of the locally optimal detector, some other authors showed how the design of the asymptotically robust detector for the Huber-Tukey mixture class of noises could be obtained. As might have been expected, the results led to censoring the factors of the test statistic to impart robustness, which led to the employment of a detector nonlinearity which limited observations of large magnitude. However, this work did not take into account the common situation where more is known about a noise density near the origin than on the tails. In fact, the noise often arises in practice from the sum of a number of "nearly" independent sources, and thus frequently the noise density resembles the Gaussian near the origin but may differ markedly on the tails. Such knowledge had the potential to be exploited for improved performance, where the robustness is imparted to account for our lack of knowledge of the tails of the noise density. We investigated this situation and obtained results which specified an asymptotically robust detector for the case where the noise density was known on an interval about the origin. We then showed by way of example that the approach led to improved performance over the previous one; in fact, the improvement was quite dramatic in certain cases. These results were delineated in #2 of the publication list.

In addition, we considered the discrete time robust detection of a known constant signal in additive independent and identically distributed nominally

Laplace noise. The heavy tailed nature of the Laplace density function makes it a popular model for such non-Gaussian noise as that encountered in atmospheric or undersea environments. We observed that applying some existing results of Huber allowed deducing the form of the test statistic as a censored version of the test statistic which is Neyman-Pearson optimal. Since the performance of robust detectors is an important subject which has been largely unexplored, we pursued such an investigation with the hope of exploiting the often tractable Laplace model for the nominal distribution. We were able to obtain closed form solutions for the distribution of the censored test statistic under both hypotheses, with the result that the performance could be measured via receiver operating characteristic curves which plotted detection probability versus false alarm rate. Such curves were then determined for various cases of interest. A comparison of these curves with those for the Neyman-Pearson optimal case was then performed, thus showing the effect of various degrees of contamination of the nominal distribution on the performance of the robust detector when compared to the Neyman-Pearson optimal one. These results were delineated in #4 of the publication list.

The area of memoryless discrete time detection of signals in ϕ -mixing noise has been studied by us in the past for both the case when the signal was constant and when it was also a random process. The detector structure employed consisted of a memoryless nonlinearity followed by an accumulator and threshold comparator, which was Neyman-Pearson optimal in the independent noise case. Using the criterion of asymptotic relative efficiency, these earlier results accounted for the dependency by specifying the detector nonlinearity which optimized performance. This nonlinearity appeared as the solution of an integral equation which unfortunately involved second order statistics of the random processes present. Since such statistical knowledge may often be incomplete, we investigated alternative approaches which required less statistical knowledge and which were easy to implement.

For example, we considered the detection of a constant signal in weakly dependent ϕ -mixing noise using two approaches. For the first, the locally optimal detector was employed, resulting in the need to know only the univariate noise density. Since this approach ignores the dependency, it is of

course important to inquire into its performance. We therefore obtained a bound on the degradation in performance which was expressed in terms of the ϕ -representation of the noise. This bound showed quantitatively how close the performance of the locally optimal detector was to optimal for various ϕ -representations. The second approach considered a more general form, consisting of the locally optimal nonlinearity plus a linear correction term. Such a structure has been shown to yield improved performance under a moving average weak dependence model. We then showed that in the much more general ϕ -mixing case, such improved performance is unfortunately not possible uniformly over the class of noise processes possessing a given ϕ -representation. In fact, for any appropriate ϕ -representation, we showed that there must exist such a process for which the locally optimal detector outperforms the one with the linear correction term. Because of this result, we might in practice simply wish to employ the locally optimal detector in the absence of the required statistical knowledge. These results were delineated in #6 of the publication list.

We also considered an alternative approach which was applied to memoryless discrete time detection of random signals in noise, where in this case both the signal and noise were random processes (not necessarily independent of each other) whose maximal correlation coefficient sequences were summable. Such processes are strong mixing, moreover this class includes as a proper subset the class of ϕ -mixing processes. In some earlier work we showed that the asymptotically optimal nonlinearity again satisfied an integral equation, which in this case involved second order statistics of both the signal and the noise. Noting that finding an exact solution was often limited in practice by the numerical techniques employed as well as the expected inexact statistical knowledge, it was concluded that the actual nonlinearity obtained was only approximately optimal. We therefore wondered whether other approximations might offer certain advantages, and thus pursued an investigation into the general problem of approximating a detector nonlinearity. This led to a result which established sufficiency conditions for the performance of a sequence of approximations to converge to the performance of a given detector. We then applied these conditions to the case where the optimal detector nonlinearity was approximated by a quantizer or by a polynomial. Our results specified the form of

the optimal M-level quantizer; moreover, it was shown that the performance of the resultant detector converged to optimal as the number of quantization levels approached infinity. Since one may be interested in quantizing to implement the detector digitally, the use of such quantizers might be attractive. We also specified the form of the optimal polynomial of a given degree, and found that it could be obtained simply by solving a set of linear equations which involved joint moments rather than densities. We then showed that for a large class of noises the resultant detector's performance converged to optimal as the degree of the polynomial approached infinity. Because of these convergence results, we therefore concluded that the employment of a quantizer or polynomial detector allowed performance arbitrarily close to optimal. These results were delineated in #9 of the publication list.

As with much work which deals with memoryless detection, the results described above were obtained in conjunction with stationarity assumptions which were imposed on the signal. Because there are many cases where a stationarity assumption regarding the signal may not be appropriate due to, for example, manmade factors affecting the signal, we then sought to investigate applications of memoryless discrete time detection to the case of a time varying deterministic signal in dependent non-Gaussian noise. Using the criterion of asymptotic relative efficiency, we first specified the form of the optimal detector for the case when the detector class considered consisted of a time invariant memoryless nonlinearity followed by an accumulator and threshold comparator, the same detector class considered by us in other contexts for various stationary signal cases. Having noted that the nonstationarity of the signal might make appropriate a different detector model, we then employed a model which included a time varying memoryless nonlinearity. We again specified the form of the optimal detector for this detector class. Several specific examples were considered, and graphs of the appropriate optimal nonlinearities were provided. We then evaluated the asymptotic performance of the optimal detectors of the two classes, and it was seen that for the examples considered the time varying nonlinearity led to superior performance. Finally, in order to reduce the amount of statistical knowledge of the noise required for the design of the detector, an approach was presented which involved employing poly-

nomial approximations of the nonlinearities of interest. Graphs were then obtained of the optimal polynomials of a given degree for various examples. These results were delineated in #3 of the publication list.

Finally, we observed that in order to obtain improved performance it might be desirable to allow the detector to possess memory. The presence of a nonstationary signal in conjunction with a dependent noise process often complicates the design of the detector; moreover, in some such cases applications of known approaches which account for the noise dependency are inhibited by lack of knowledge of the higher order noise statistics. If the noise dependency were weak the temptation to ignore it might therefore arise. We were thus led to consider the discrete time detection with memory of time varying deterministic signals in weakly dependent noise. We investigated quantitative conditions which allowed determining when the dependency could be ignored, and presented a result which allowed bounding the variation in false alarm rate and detection probability induced by ignoring the dependency. The case of stationary Gaussian noise was then considered, and we showed that our result related the bound on the variation in false alarm rate and detection probability to the rate of descent of the noise autocorrelation. These results were delineated in #5 and #11 of the publication list.

DIRECTIONS OF CURRENT RESEARCH

Current research is directed toward the areas of signal detection and block truncation coding for image compression. Most of this work has as a goal the admission of non-Gaussian processes with dependency. In addition, we are heavily interested in approaches which require only moderate amounts of statistical knowledge, thus yielding greater utility in practice. This is resulting in the attractiveness of robust or nonparametric schemes. Because in many cases we might expect the presence of dependency in the underlying random processes, we are particularly interested in studying robust or nonparametric schemes with application to dependent processes. These are areas for which few results exist in the dependent non-Gaussian case, and thus the employment of unconventional techniques might be necessary.

END

FILMED

24

DTIC