



AD-A146 517 THE HEMP (HIGH-ALTITUDE ELECTROMAGNETIC PULSE) RESPONSE 1/1
OF A LONG TRANSMI. (U) HARRY DIAMOND LABS ADELPHI MD
R P MANRIQUEZ ET AL. SEP 84 HDL-TR-2051

UNCLASSIFIED MIPR-HC1001-3-401

F/G 20/14

NL





OPY RESOLUTION TEST CHART

HDL-TR-205

September 1971

AD-A146 517

The HEMP Effects
in the Earth

by Rolando P. M...
Ronald J. Reyzer
John F. Swet...

FILE COPY



Department Command
AD-A146 517

The findings in this report are not to be construed as an official Department
of the Army position, unless so designated by other authorized documents.
Citation of manufacturers or trade names does not constitute an official
indorsement or approval of the use thereof.
Destroy this report when it is no longer needed. Do not return it to the
originator.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER HDL-TR-2051	2. GOVT ACCESSION NO. AD-A146 517	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) The HEMP Response of a Long Transmission Line Buried in the Earth	5. TYPE OF REPORT & PERIOD COVERED Technical Report	
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Rolando P. Manriquez Ronald J. Reyzer John F. Sweton	8. CONTRACT OR GRANT NUMBER(s) PRON: WS3-8301WSA9 MIPR: HC1001-3-401	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783-1197	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Ele: 33126K	
11. CONTROLLING OFFICE NAME AND ADDRESS National Communications System (DCA) Office of the Manager Washington, DC 20305	12. REPORT DATE September 1984	
		13. NUMBER OF PAGES 24
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES HDL Project No. E313E3 DRCMS Code: 33126K		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) HEMP → Transmitted E field below ground,) Distributed source, and - Conductivity, LPN model Dielectric constant, REPS Matrix tridiagonalization. ←		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) → This paper documents the calculation of the current coupled to a long, buried, insulated cable excited by a horizontally polarized plane-wave electromagnetic pulse (EMP) field. This result is compared to the current measured on a similar long, buried cable located approximately 800 ft from a radiating, horizontally polarized EMP simulator having the same driving horizontal field. Original & signed required & included.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

1 SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

FOREWORD

The National Communications System (NCS) in response to Presidential Directive/NSC-53, "National Security Telecommunications Policy," is funding a comprehensive program on the effects of nuclear weapons on selected telecommunications systems. A portion of this effort is directed at determining the high-altitude electromagnetic pulse (EMP) vulnerability of the commercial Bell Telephone T1 Carrier system, and at developing a T1 Carrier system specifically engineered to be EMP hard. The work described in this report was performed in support of these efforts.

Approved For	
RMC GRAM	
2121B	
Unannounced	☐
Classification	☐
by	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



CONTENTS

	<u>Page</u>
FOREWORD	3
1. INTRODUCTION	7
2. BURIED-CABLE RESPONSE ANALYSIS	9
3. DISCUSSION OF RESULTS	12
4. CONCLUSION	18
LITERATURE CITED	19
DISTRIBUTION	21

FIGURES

1. Cross section of shielded cable	8
2. Test configuration for HDL cable coupling studies	8
3. Incremental π section of equivalent distributed-source lumped-parameter network model of buried cable	10
4. Digitized waveforms of measured $H_x(t)$ at TP1 to TP5	13
5. Transmitted electric field at TP1 to TP5 with $\sigma = 0.001$ mho/m and $\epsilon_r = 15$	13
6. Transmitted electric field at TP1 to TP5 with $\sigma = 0.007$ mho/m and $\epsilon_r = 15$	14
7. Transmitted electric field at TP1 to TP5 with $\sigma = 0.02$ mho/m and $\epsilon_r = 15$	14
8. Soil conductivity with varying moisture content	15
9. Soil dielectric constant with varying moisture content	15
10. Transmitted electric field at TP1 to TP5 with 10-percent moisture content	16
11. Transmitted electric field at TP1 to TP5 with 25-percent moisture content	16
12. Comparison between measured and LPN data with varying moisture content	17
13. Comparison between measured and LPN short-circuit current with representative constant values of σ and ϵ_r	17
14. Late-time measured short-circuit current	18

1. INTRODUCTION

Investigators have measured the current induced by an electromagnetic pulse (EMP), as produced by the repetitive EMP simulator (REPS), on a long, terminated, insulated cable buried at a shallow depth near the air-earth interface. The measured current is compared with analytical predictions of the current induced on the same cable excited by an exoatmospheric EMP. The main objectives of this paper are to evaluate the plane-wave electromagnetic field propagation through a linear, isotropic, and homogeneous conducting medium; to represent the EMP coupling to the buried cable by the equivalent distributed-source, lumped-parameter network (LPN) model; and to compare the results to experimental measurements using an EMP simulator.

The reflection and transmission of electromagnetic waves at a plane surface between the air and earth media are familiar phenomena. It is assumed in this study that the incident wave, generated in free space, is a linearly polarized plane wave (constant amplitude and phase), and the earth boundary is treated as a semi-infinite, linear, homogeneous, isotropic, and conducting medium.

The incident electric field above the earth is computed based on the measured magnetic field above ground. Subsequently, the transmitted electric field below ground is computed through the use of Maxwell equations and Fresnel coefficients. The procedure used to calculate the transmitted fields from measured magnetic field data is reported in a companion paper.¹ The cable under study is a 1200-ft section of shielded cable that is terminated in a "short circuit" to ground at both ends of the cable. The cable is buried 18 in. below the surface of the earth. A cross section of the shielded cable is shown in figure 1. The incident field is horizontally polarized and arrives at the earth boundary at an elevation angle of 3 degrees. The earth's parameters of conductivity, σ , and dielectric permittivity, ϵ , are derived as a function of frequency based upon the universal impedance for soils, generated by Longmire and Smith,² and an assumed moisture content of 10 percent by volume.

The cable has been arranged in an arc from the center of a point-source EMP simulator, as shown in figure 2. Thus, the peak EMP signal arrives at all points along the cable at the same time. The particular simulator being used in the experiment is the Army's REPS, a horizontally polarized dipole radiator driven by a 1-MV repetitive pulse generator. The current is sensed with a Stoddard clip-on current probe (model 91550-3), and the data are recorded on a fiber-optic system and transmitted to an instrument van, where they are converted back to an electrical signal and monitored with a Tektronix 7912 oscilloscope. The data are also digitized, processed, and stored on disk for future use.

¹Rolando P. Manriquez and John F. Sweton, *An Indirect Measure of Below-Ground Electric Field, Conductivity, and Dielectric Constant*, Harry Diamond Laboratories, HDL-TR-2052 (September 1984).

²C. L. Longmire and K. S. Smith, *A Universal Impedance for Soils*, Mission Research Corp., Santa Barbara, CA, Contract No. DNAS001-75-C0094 (October 1975).




Figure 1. Cross section of shielded cable.




Figure 2. Test configuration for HDL cable coupling studies.

The electrical short circuit at the ends of the cable is achieved by the use of a calcium chloride salt solution poured into a 3 x 3 x 3 ft pit containing a 6-ft grounding rod that is attached to the cable sheath by a standard telephone press-fit connector. The electric field incident on the cable is obtained by the use of the total magnetic field measured at five points along the length of the cable. An attempt to monitor the electric field at 18 in. below the surface of the earth is documented elsewhere.¹

¹Rolando P. Manriquez and John F. Sweton, *An Indirect Measure of Below-Ground Electric Field, Conductivity, and Dielectric Constant*, Harry Diamond Laboratories, HDL-TR-2052 (September 1984).

2. BURIED-CABLE RESPONSE ANALYSIS

The analytical method used to predict the response of the buried cable is similar to the methods used in earlier work.^{3,4} The incremental section of the equivalent distributed-source LPN model is shown in figure 3. This model incorporates frequency-dependent passive elements. The voltage, V_i , is the transmitted E-field for each incremental section. The impedance for each incremental section consists of the ground impedance (Z_g), cable impedance (Z_i), and the inductive reactance (Z_L) of the insulation gap. The admittance for each incremental section consists of the capacitive susceptance (Y_d) of the insulation in series with the admittance (Y_g) of the ground. Thus, the transmission-line parameters are³

$$Z_g(\omega) = \frac{\omega\mu_o}{8} + \frac{j\omega\mu_o}{2\pi} \log \left(\frac{\sqrt{2}\delta_g}{\gamma_o b} \right) , \quad (1)$$

$$Z_i(\omega) = \frac{(1+j)T/\delta_c}{2\pi a \sigma_c T} \coth [(1+j)T/\delta_c] , \quad (2)$$

$$Z_L(\omega) = \frac{j\omega\mu_o}{2\pi} \log \left(\frac{b}{a} \right) , \quad (3)$$

$$Y_g(\omega) = \frac{2\pi\sigma_g}{\log \left(\frac{\sqrt{2}\delta_g}{\gamma_o b} \right)} + j \frac{2\pi\epsilon_g}{\log \left(\frac{\sqrt{2}\delta_g}{\gamma_o b} \right)} , \quad (4)$$

$$Y_d(\omega) = \frac{2\pi\sigma_d}{\log \left(\frac{b}{a} \right)} + j \frac{\omega 2\pi\epsilon_d}{\log \left(\frac{b}{a} \right)} , \quad (5)$$

where

$\delta_g = 1/\sqrt{\pi f \mu_o \sigma_g}$ = skin depth in the ground,

$\delta_c = 1/\sqrt{\pi f \mu_o \sigma_c}$ = skin depth in the shield,

σ_g = conductivity of the ground,

σ_c = conductivity of the shield,

σ_d = conductivity of the dielectric,

³E. F. Vance, *Coupling to Shielded Cables*, John Wiley and Sons, Inc. (1978).

⁴Michael S. Bushell, Rolando P. Manriquez, George Merkel, and William D. Scharf, *Aurora Test Cell Electron Beam Environment--Response of Large Loop*, IEEE Trans. Nucl. Sci. NS-30, No. 6 (December 1983), 4558-4563.

ϵ_g = dielectric constant of the ground,

ϵ_d = dielectric constant of the protective jacket of the cable,

$\mu_0 = 4\pi \times 10^{-7}$ H/m,

$\gamma_0 = 1.781$ = Euler's constant,

b = outer radius of the insulation,

a = outer radius of the cable shield, and

T = thickness of the shield.




Figure 3. Incremental π section of equivalent distributed-source lumped-parameter network model of buried cable.

The transmission-line response is obtained by the implicit method.⁵ At each increment along the line, the current is determined by solving the matrix equation

$$[Z][I] = [V], \quad (6)$$

where $[Z]$ is the impedance matrix, and $[I]$ and $[V]$ are the vector forms of the currents and voltages, respectively. The impedance matrix is expressed as a set of $[Z]$ coefficients and can be found by the application of Kirchoff's current and voltage law to the equivalent transmission line. The elements of the voltage matrix $[V]$ are the source terms for the transmission line, as shown in figure 3. Hence, equation (6) is expanded in the form⁵

⁵B. Carnahan, H. A. Luther, and J. O. Wilkes, *Applied Numerical Methods*, John Wiley and Sons (1969), 440-442.

$$\begin{aligned}
b_1 I_1 + c_1 I_2 &= V_1 \\
a_2 I_1 + b_2 I_2 + c_2 I_3 &= V_2 \\
a_3 I_2 + b_3 I_3 + c_3 I_4 &= V_3 \\
&\dots \\
a_i I_{i-1} + b_i I_i + c_i I_{i+1} &= V_i \\
&\dots \\
a_{n-1} I_{n-2} + b_{n-1} I_{n-1} + c_{n-1} I_n &= V_{n-1} \\
a_n I_{n-1} + b_n I_n &= V_n ,
\end{aligned} \tag{7}$$

where the $[Z]$ coefficients are

$$\begin{aligned}
b_1 &= Z_1 + Z_2 , \\
c_1 &= -Z_2 , \\
a_{n-1} &= -Z_{2n-2} , \\
b_{n-1} &= Z_{2n-1} + Z_{2n-2} + Z_{2n} , \\
c_{n-1} &= -Z_{2n} , \\
a_n &= -Z_{2n-2} , \\
b_n &= Z_{2n-1} + Z_{2n-2} + Z_{2n} .
\end{aligned}$$

Note that $Z_{\text{odd}} = Z(\omega)$, $Z_{\text{even}} = 1/Y(\omega)$, $V_i = E_i(\omega)\Delta z$, and n = total number of sections.

The set of the $[Z]$ coefficients a , b , and c alone is called the tridiagonal matrix. The system matrix (eq (7)) is readily solved by a Gaussian elimination method with a maximum of three variables per equation, and the solutions can be expressed very concisely. The recursion solutions of equation (7) for each frequency yield the currents through each branch.

The cable response obtained with the frequency-domain LPN model used in this study was then compared to two solutions based on (1) Vance's approach³ using constant or frequency-dependent σ and ϵ and (2) the time-domain LPN

³E. F. Vance, *Coupling to Shielded Cables*, John Wiley and Sons, Inc. (1978).

approach⁴ using constant σ and ϵ . The number of incremental sections was increased until good agreement between the results of the LPN models and the results of Vance's approach was achieved for constant σ and ϵ . The advantages of the frequency-domain LPN technique are that (1) σ and ϵ can be functions of frequency and moisture content and (2) different E-field values can be used for each incremental section. Finally, the solution of the short-circuit current, $I_{sc}(w)$, at the last branch is inverse Fourier transformed⁶ to yield the desired time response, $I_{sc}(t)$, at the end of the buried cable.

3. DISCUSSION OF RESULTS

The magnetic field, $H_x(t)$, was measured using an H-field sensor at a height of 1 m above ground and located on one of the faces of the Stanford Research Institute cubical sensor box.⁷ The digitized waveforms of measured $H_x(t)$ at test points TP1 to TP5 (see fig. 2) are shown in figure 4. The transmitted electric fields, $E(t)$, below ground at TP1 to TP5 are shown in figures 5 to 7 for constant values of conductivity $\sigma = 0.001, 0.007$, and 0.02 mho/m with dielectric constant $\epsilon_r = 15$. These figures show the early-time variations of $E(t)$ up to $1 \mu s$. Although the calculations were carried to $5 \mu s$, all the $E(t)$ beyond $1 \mu s$ are small. As shown in figures 5 to 7, both amplitude and waveform are significantly affected by changes in conductivity but are relatively insensitive to changes in dielectric permittivity.

In reality, the conductivity and dielectric permittivity are functions of frequency and depend upon the moisture content of the soil. Longmire and Smith's universal formula² is used to determine σ and ϵ_r for variation of moisture content. These are shown in figures 8 and 9. Figures 10 and 11 show the effects of these frequency functions for 10- and 25-percent moisture content, respectively, on $E(t)$ at TP1 and TP5.

The transmitted fields, conductivity, and dielectric permittivity are input to the frequency-domain LPN computer program used to calculate the short-circuit current response of the buried cable. The impedance and admittance parameters were increased by a factor of 2 to obtain a better correlation between the measured and calculated short-circuit current at early times.

²C. L. Longmire and K. S. Smith, A Universal Impedance for Soils, Mission Research Corp., Santa Barbara, CA, Contract No. DNAS001-75-C0094 (October 1975).

⁴Michael S. Bushell, Rolando P. Manriquez, George Merkel, and William D. Scharf, Aurora Test Cell Electron Beam Environment--Response of Large Loop, IEEE Trans. Nucl. Sci. NS-30, No. 6 (December 1983), 4558-4563.

⁶Alfred G. Brandstein and Egon Marx, Numerical Fourier Transform, Harry Diamond Laboratories, HDL-TR-1748 (September 1976).

⁷B. C. Tupper, R. H. Stehle, and R. T. Wolfram, EMP Instrumentation Development, Stanford Research Institute, report 7990, under contract to HDL, Contract DAAK02-69-C-0674 (June 1972).




Figure 4. Digitized waveforms of measured $H_x(t)$ at TP1 to TP5.




Figure 5. Transmitted electric field at TP1 to TP5 with $\sigma = 0.001$ mho/m and $\epsilon_r = 15$.




Figure 6. Transmitted electric field at TP1 to TP5 with $\sigma = 0.007$ mho/m and $\epsilon_r = 15$.




Figure 7. Transmitted electric field at TP1 to TP5 with $\sigma = 0.02$ mho/m and $\epsilon_r = 15$.




Figure 8. Soil conductivity with varying moisture content (5 to 25 percent).




Figure 9. Soil dielectric constant with varying moisture content (5 to 25 percent).




Figure 10. Transmitted electric field at TP1 to TP5 with 10-percent moisture content.




Figure 11. Transmitted electric field at TP1 to TP5 with 25-percent moisture content.

Figure 12 compares the measured and calculated $E(t)$ with σ and ϵ_r varying with frequency at 5-, 10-, and 25-percent moisture content. Values of $\sigma = 0.007$ mho/m, $\epsilon_r = 15$, and 10-percent moisture content yield close agreement between the measured and LPN data at early times. These values were also determined empirically from correlation between the measured and calculated transmitted electric fields below ground, as cited elsewhere.¹ The comparison between the measured and calculated $I_{SC}(t)$ with $\sigma = 0.001$, 0.007, and 0.02 mho/m and $\epsilon_r = 15$ are shown in figure 13. Figure 14 shows the late-time measured short-circuit current.




Figure 12. Comparison between measured and LPN data with varying moisture content (σ and ϵ_r both functions of frequency).




Figure 13. Comparison between measured and LPN short-circuit current with representative constant values of σ and ϵ_r .

¹Rolando P. Manriquez and John F. Sweton, *An Indirect Measure of Below-Ground Electric Field, Conductivity, and Dielectric Constant*, Harry Diamond Laboratories, HDL-TR-2052 (September 1984).




Figure 14. Late-time measured short-circuit current.

4. CONCLUSION

It can be seen from the data (fig. 12) that the risetime and amplitude of the calculated and measured currents are in good agreement. However, for the late-time waveshape (fig. 12 and 14), there is a significant divergence between the measured and calculated data. The reason or reasons for this disagreement are not known, but it is clear that if this discrepancy results from the (near-field) proximity of the cable to the simulator (a likely possibility), then the result to distributed system testing could be significant. On the other hand, if this discrepancy is the result of some factor not adequately accounted for in the analytic calculation, the result to distributed system analysis would be similarly significant.

LITERATURE CITED

1. Rolando P. Manriquez and John F. Sweton, An Indirect Measure of Below-Ground Electric Field, Conductivity, and Dielectric Constant, Harry Diamond Laboratories, HDL-TR-2052 (September 1984).
2. C. L. Longmire and K. S. Smith, A Universal Impedance for Soils, Mission Research Corp., Santa Barbara, CA, Contract No. DNAS001-75-C0094 (October 1975).
3. E. F. Vance, Coupling to Shielded Cables, John Wiley and Sons, Inc. (1978).
4. Michael S. Bushell, Rolando P. Manriquez, George Merkel, and William D. Scharf, Aurora Test Cell Electron Beam Environment--Response of Large Loop, IEEE Trans. Nucl. Sci. NS-30, No. 6 (December 1983), 4558-4563.
5. B. Carnahan, H. A. Luther, and J. O. Wilkes, Applied Numerical Methods, John Wiley and Sons (1969), 440-442.
6. Alfred G. Brandstein and Egon Marx, Numerical Fourier Transform, Harry Diamond Laboratories, HDL-TR-1748 (September 1976).
7. B. C. Tupper, R. H. Stehle, and R. T. Wolfram, EMP Instrumentation Development, Stanford Research Institute, report 7990, under contract to HDL, Contract DAAK02-69-C-0674 (June 1972).

DISTRIBUTION

ADMINISTRATOR
DEFENSE TECHNICAL INFORMATION CENTER
CAMERON STATION, BUILDING 5
ATTN DTIC-DDA (12 COPIES)
ALEXANDRIA, VA 22314

NATIONAL COMMUNICATIONS SYSTEM
DEPARTMENT OF DEFENSE
OFFICE OF THE MANAGER
ATTN NCS-TS, D. BODSON (150 COPIES)
WASHINGTON, DC 20305

ASSISTANT TO THE SECRETARY OF DEFENSE
ATOMIC ENERGY
ATTN EXECUTIVE ASSISTANT
WASHINGTON, DC 20301

DIRECTOR
DEFENSE COMMUNICATIONS AGENCY
ATTN CODE B410
ATTN CODE B430
ATTN CODE J300, KNAPP
WASHINGTON, DC 20305

DIRECTOR
COMMAND CONTROL ENGINEERING CENTER
ATTN C-661, DR. T. TRINKLE
ATTN G-630, R. LIPP
WASHINGTON, DC 20305

DIRECTOR
DEFENSE COMMUNICATIONS ENGINEERING CENTER
ATTN CODE R400
ATTN CODE R123, TECH LIB
ATTN CODE R111, SICA
1860 WIEHLE AVENUE
RESTON, VA 22090

ASSISTANT CHIEF OF STAFF FOR
INFORMATION MANAGEMENT
COMMAND SYSTEMS INTEGRATION OFFICE
ATTN DAMO-C4Z, COL. D. GRIGGS
THE PENTAGON
WASHINGTON, DC 20301

DIRECTOR
DEFENSE INTELLIGENCE AGENCY
ATTN DB-4C2, D. SPOHN
WASHINGTON, DC 20301

CHAIRMAN
JOINT CHIEFS OF STAFF
ATTN J-3
ATTN C3S
WASHINGTON, DC 20301

DIRECTOR DEFENSE NUCLEAR AGENCY
ATTN NATA
ATTN RAEV
ATTN DDST
ATTN RAEE
ATTN TITL
WASHINGTON, DC 20305

OFFICE OF UNDERSECRETARY OF DEFENSE
RESEARCH & ENGINEERING
DMSSO
2 SKYLINE PLACE
SUITE 1403
5203 LEESBURG PIKE
FALLS CHURCH, VA 22041

UNDER SECY OF DEF FOR RSCH & ENGRG
DEPARTMENT OF DEFENSE
ATTN STRATEGIC & SPACE SYS 9060 RM 3E129
ATTN STRAT & THEATER NUC FORCES
WASHINGTON, DC 20301

DEPUTY DIRECTOR FOR THEATRE/TACTICAL C3
SYSTEMS
JOINT STAFF
WASHINGTON, DC 20301

COMMANDER-IN-CHIEF
US FORCES, EUROPE
ATTN ECC3S
APO, NY 09128

ASSISTANT CHIEF OF STAFF FOR
AUTOMATION & COMMUNICATIONS
ATTN DAMO-C4T
ATTN DAMO-C4S
DEPARTMENT OF THE ARMY
WASHINGTON, DC 20360

US ARMY BALLISTIC RESEARCH LABORATORY
ATTN DRDAR-TSB-S (STINFO)
ABERDEEN PROVING GROUND, MD 21005

COMMANDER
US ARMY COMMUNICATIONS COMMAND
ATTN CC-OPS-WR, O. P. CONNELL
FT HUACHUCA, AZ 85613

COMMANDER
US ARMY COMM-ELEC INSTAL AGENCY
ATTN CCC-CE-TS
FT HUACHUCA, AZ 85613

CHIEF
US ARMY COMMUNICATIONS SYS AGENCY
DEPARTMENT OF THE ARMY
ATTN TECHNICAL DIRECTOR
FT MONMOUTH, NJ 07703

DISTRIBUTION (Cont'd)

COMMANDER
5TH SIGNAL COMMAND HEADQUARTERS
ATTN DCS OPS, K. MILLER
APO, NY 09056

US ARMY ELECTRONICS TECHNOLOGY
& DEVICES LABORATORY
ATTN DELET-DD
FT MONMOUTH, NJ 07703

US ARMY ENGINEER DIV HUNTSVILLE
DIVISION ENGINEER
ATTN HNDED FD, T. BOLT
PO BOX 1600
HUNTSVILLE, AL 35807

COMMANDER
US ARMY MATERIEL COMMAND
ATTN DRCRE
ATTN DRCDE
5001 EISENHOWER AVE
ALEXANDRIA, VA 22333-0001

DIRECTOR
US ARMY MATERIEL SYSTEMS ANALYSIS
ACTIVITY
ATTN DRXSY-MP, LIBRARY
ABERDEEN PROVING GROUND, MD 21005

COMMANDER
US ARMY MISSILE & MUNITIONS
CENTER & SCHOOL
ATTN ATSK-CTD-F
REDSTONE ARSENAL, AL 35809

COMMANDER
US ARMY NUCLEAR & CHEMICAL AGENCY
ATTN MONA-WE
7500 BACKLICK RD
SPRINGFIELD, VA 22150

DEP CH OF STAFF FOR RSCH DEV & ACQ
DEPARTMENT OF THE ARMY
ATTN DAMA-CSS-N
WASHINGTON, DC 20310

COMMANDER
US ARMY RSCH & STD GP (EUR)
ATTN CHIEF, PHYSICS & MATH BRANCH
FPO NEW YORK 09510

CHIEF
US ARMY SATELLITE COMMUNICATIONS
AGENCY
ATTN DRCPM-SC
FT MONMOUTH, NJ 07703

DIRECTOR
TRI/TAC
ATTN TT-E-SS, CHARNICK
FT MONMOUTH, NJ 07703

COMMANDER-IN-CHIEF
ATLANTIC
ATTN J6
NORFOLK, VA 23511

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
ATTN PME 110-241D, D. O'BRYHIM, A. LARSON
WASHINGTON, DC 20360

CHIEF OF NAVAL MATERIEL
THEATER NUCLEAR WARFARE PROJECT OFFICE
ATTN PM-23, TN-31, TATE
WASHINGTON, DC 20360

COMMANDER
NAVAL OCEAN SYSTEMS CENTER
ATTN CODE 7309, R. GREENWELL
ATTN CODE 8123, S. LICHTMAN
ATTN CODE 83, J. STAWISKI
SAN DIEGO, CA 92152

COMMANDING OFFICER
NAVAL ORDNANCE STATION
ATTN STANDARDIZATION DIVISION
INDIAN HEAD, MD 20640

COMMANDER-IN-CHIEF
PACIFIC
ATTN C3S-RP-1
CAMP H. M. SMITH, HI 96861

COMMANDING OFFICER
NAVAL RESEARCH LABORATORY
ATTN CODE 4720, J. DAVIS
WASHINGTON, DC 20375

COMMANDER
NAVAL SURFACE WEAPONS CENTER
ATTN CODE F-56
DAHLGREN, VA 22448

COMMANDER
NAVAL SURFACE WEAPONS CENTER
ATTN CODE F32, E. RATHBURN
ATTN CODE F30
WHITE OAK LABORATORY
SILVER SPRING, MD 20910

DEPARTMENT OF THE NAVY
DIRECTOR, NAVAL TELECOMMUNICATIONS
DIVISION
OFFICE OF THE CHIEF OF NAVAL OPERATIONS
ATTN OP941, HAISLMAIER

DISTRIBUTION (Cont'd)

DEPARTMENT OF THE NAVY (Cont'd)
ATTN OP943
WASHINGTON, DC 20350

HQ, USAF/SAMI
WASHINGTON, DC 20330

AIR FORCE COMMUNICATIONS COMMAND
ATTN EPPD
SCOTT AFB, IL 62225

COMMANDER US AIR FORCE SPACE COMMAND
ATTN KKO
ATTN KRQ
ATTN XPOW
PETERSON AFB, CO 80912

1842 EEG
ATTN REISG
SCOTT AFB, IL 62225

HEADQUARTERS
ELECTRONIC SYSTEMS DIVISION/YS
ATTN YSEA
HANSCOM AFB, MA 01730

HEADQUARTERS
USAFE
ATTN DCKI
RAMSTEIN AFB, GERMANY

SYSTEM INTEGRATION OFFICE
ATTN SYE
PETERSON AFB, CO 80912

AIR FORCE WEAPONS LABORATORY/DYC
ATTN NTC4, TESD, IESM
KIRTLAND AFB, NM 87117

CENTRAL INTELLIGENCE AGENCY
ATTN OWSR/NED
ATTN OWSR/STD/MTB, A. PADGETT
WASHINGTON, DC 20505

DIRECTOR
FEDERAL EMERGENCY MANAGEMENT AGENCY
OFFICE OF RESEARCH/NPP
ATTN STATE & LOCAL PROG SUPPORT
500 C STREET, SW
WASHINGTON, DC 20472

FEDERAL PREPAREDNESS AGENCY
GENERAL SERVICES ADMINISTRATION
ATTN ESTE-M MURTHA
18TH & F STREETS, NW
WASHINGTON, DC 20405

LAWRENCE LIVERMORE NATIONAL LAB
ATTN TECHNICAL INFO DEPT LIBRARY
ATTN L-156, H. CABAYAN, L. MARTIN
PO BOX 808
LIVERMORE, CA 94550

DIRECTOR
NATIONAL SECURITY AGENCY
ATTN R15
9800 SAVAGE ROAD
FT MEADE, MD 20755

AMERICAN TELEPHONE & TELEGRAPH CO
ATTN SEC OFC FOR W. EDWARDS
1120 20TH STREET, NW
WASHINGTON, DC 20036

AT&T BELL LABORATORIES
ATTN R. STEVENSON
ATTN J. MAY (3 COPIES)
1600 OSGOOD ST
N. ANDOVER, MA 01845

AT&T BELL LABORATORIES
ATTN J. SCHOLL (5 COPIES)
ATTN J. SERRI
CRAWFORDS CORNER ROAD
HOLMDEL, NJ 07733

BDM CORP
ATTN CORPORATE LIBRARY
7915 JONES BRANCH DRIVE
MCLEAN, VA 22102

BOEING CO
ATTN R. SHEPPE
PO BOX 3707
SEATTLE, WA 98124

COMPUTER SCIENCES CORPORATION
SYSTEMS DIVISION
ATTN A. SCHIFF
1400 SAN MATEO BOULEVARD, SE
ALBUQUERQUE, NM 87108

ELECTROMAGNETIC APPLICATIONS, INC
ATTN R. PERALA
PO BOX 26263
1978 SOUTH GARRISON ST
DENVER, CO 80226

ENGINEERING SOCIETIES LIBRARY
ATTN ACQUISITIONS DEPT
345 EAST 47TH STREET
NEW YORK, NY 10017

GEORGIA INSTITUTE OF TECHNOLOGY
OFFICE OF CONTRACT ADMINISTRATION
ATTN RES & SEC COORD FOR H. DENNY
ATLANTA, GA 30332

DISTRIBUTION (Cont'd)

IIT RESEARCH INSTITUTE
ATTN J. BRIDGES
ATTN I. MINDEL
10 W. 35TH STREET
CHICAGO, ILL 60616

INTERNATIONAL TEL & TELEGRAPH CORP
ATTN A. RICHARDSON
ATTN TECHNICAL LIBRARY
500 WASHINGTON AVENUE
NUTLEY, NJ 07110

MISSION RESEARCH CORP
PO BOX 7816
ATTN W. STARK
COLORADO SPRINGS, CO 80933

MISSION RESEARCH CORP
EM SYSTEM APPLICATIONS DIVISION
ATTN A. CHODOROW
1720 RANDOLF ROAD, SE
ALBUQUERQUE, NM 87106

PRI, INC
ATTN W. HAAS
6121 LINCOLNIA RD
ALEXANDRIA, VA 22312

RICHARD L. MONROE ASSOCIATES
1911 R STREET, NW
SUITE 203
WASHINGTON, DC 20009

R&D ASSOCIATES
PO BOX 9695
ATTN W. GRAHAM
MARINA DEL REY, CA 90291

R&D ASSOCIATES
ATTN DIRECTOR, DR. J. THOMPSON
1401 WILSON BLVD
SUITE 500
ARLINGTON, VA 22209

ROCKWELL INTERNATIONAL CORP
PO BOX 3105
ATTN D/243-068, 031-CA31
ATTN G. E. MORGAN
ANAHEIM, CA 92803

SCIENCE APPLICATIONS, INC
PO BOX 1303
ATTN W. CHADSEY
McLEAN, VA 22102

SCIENCE ENGINEERING ASSOC
ATTN P. FLEMING
ATTN V. JONES
MARINER SQUARE
SUITE 127

SCIENCE ENGINEERING ASSOC (Cont'd)
1900 N. NORTHLAICE WAY
PO BOX 31819
SEATTLE, WA 98103

SRI INTERNATIONAL
ATTN A. WHITSON
ATTN E. VANCE
333 RAVENSWOOD AVENUE
MENLO PARK, CA 94025

TRW DEFENSE & SPACE SYSTEMS GROUP
ATTN J. PENAR
ATTN W. GARGARO
ONE SPACE PARK
REDONDO BEACH, CA 92078

TRW DEFENSE & SPACE SYSTEMS GROUP
ATTN E. P. CHIVINGTON
2240 ALAMO, SE
SUITE 200
ALBUQUERQUE, NM 87106

TRW, INC
COMMAND & CONTROL & COMMUNICATIONS
SYSTEM DIV
ATTN N. STAMMER
5203 LEESBURG PIKE
SUITE 310
FALLS CHURCH, VA 22041

US ARMY ELECTRONICS RESEARCH &
DEVELOPMENT COMMAND
ATTN COMMANDER, DRDEL-CG
ATTN TECHNICAL DIRECTOR, DRDEL-CT
ATTN PUBLIC AFFAIRS OFFICE, DRDEL-IN

COMMANDER
HARRY DIAMOND LABORATORIES
ATTN D/TSO/DIVISION DIRECTORS
ATTN RECORD COPY, 81200
ATTN HDL LIBRARY, 81100 (3 COPIES)
ATTN HDL LIBRARY (WOODBIDGE)
ATTN TECHNICAL REPORTS BRANCH, 81300
ATTN LEGAL OFFICE, 97000
ATTN CHIEF, 21000
ATTN CHIEF, 21100
ATTN CHIEF, 21200
ATTN CHIEF, 21300
ATTN CHIEF, 21400
ATTN CHIEF, 21500
ATTN CHIEF, 22000
ATTN CHIEF, 22100
ATTN CHIEF, 22300
ATTN CHIEF, 22800
ATTN CHIEF, 22900
ATTN CHIEF, 20240
ATTN R. MANRIQUEZ, 21300 (50 COPIES)
ATTN R. REYZER, 21300
ATTN J. SWETON, 21300

END

FILMED

1-84

DTIC