

AD-A147 485

NONLINEAR WAVES IN A ROD RESULTS FOR INCOMPRESSIBLE
ELASTIC MATERIALS(U) BALLISTIC RESEARCH LABS ABERDEEN
PROVING GROUND MD T W WRIGHT OCT 84 BRL-MR-3390

//

UNCLASSIFIED

SRI AD F300 491


F/G 20/11

NL

END

DATE
FILMED

12-84
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD

**B
R
L**

MEMORANDUM REPORT BRL-MR-3390

NONLINEAR WAVES IN A ROD: RESULTS FOR
INCOMPRESSIBLE ELASTIC MATERIALS

Thomas W. Wright

October 1984

DTIC
ELECTE
NOV 15 1984
S
B

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

**US ARMY BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND**

84 11 2 016

AD-A147 485

DTIC FILE COPY

Destroy this report when it is no longer needed.
Do not return it to the originator.

Additional copies of this report may be obtained
from the National Technical Information Service,
U. S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as an official
Department of the Army position, unless so designated by other
authorized documents.

The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT BRL-MR-3390	2. GOVT ACCESSION NO. ADA147485	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Nonlinear Waves in a Rod: Results for Incompressible Elastic Materials		5. TYPE OF REPORT & PERIOD COVERED Memorandum Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Thomas W. Wright		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Ballistic Research Laboratory ATTN: AMXBR-TBD Aberdeen Proving Ground, MD 21005-5066		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L161101AH43
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Ballistic Research Laboratory ATTN: AMXBR-OD-ST Aberdeen Proving Ground, MD 21005-5066		12. REPORT DATE October 1984
		13. NUMBER OF PAGES 31
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CL. ASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution is unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) steady waves, rod, shock waves, incompressible material, nonlinear elastic		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A nonlinear intrinsic theory is used to describe the motions of a straight round elastic rod including the influence of radial shear and inertia. Consideration of steady wave motions reduces the two coupled partial differential equations to ordinary differential equations for which two integrals of the motion may be found. For incompressible elastic materials with the restriction of small strain gradients, but arbitrary finite strains, a large variety of exact solutions may be found by quadrature. These include large amplitude		

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

periodic waves (which may contain shocks), solitary waves, and in some cases waves that are transitional from one stress level to another. Such solutions may be found for uniform stress/strain curves that are concave up or down, that contain inflections, and even curves that represent phase transitions.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	<u>Page</u>
LIST OF ILLUSTRATIONS	5
I. INTRODUCTION	7
II. INCOMPRESSIBLE MATERIAL	8
III. STEADY WAVES	8
IV. SMALL SURFACE ANGLE	9
V. SHOCK WAVES	10
VI. STEADY WAVE SOLUTIONS	15
A. $T(\epsilon)$ is concave down and at ϵ_0 , $\mu(\epsilon_0) < T_\epsilon(\epsilon_0)$	15
B. $T(\epsilon)$ is concave down and at ϵ_0 , $T_\epsilon(\epsilon_0) < \mu(\epsilon_0)$	18
C. $T(\epsilon)$ has an inflection point and $T_\epsilon(\epsilon_0) < \mu(\epsilon_0)$	18
VII. UNBOUNDED SOLUTIONS	21
REFERENCES	23
DISTRIBUTION LIST	25

DTIC
ELECTE
NOV 15 1984
B



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution	
Availability Codes	
Avail and/or	
Dist	Special
A-1	.

LIST OF ILLUSTRATIONS

<u>FIG. NO.</u>		<u>Page</u>
1	Stress-strain curve and the equal area construction for bounded smooth waves where $\mu(\epsilon_0) < \rho c^2 < T_\epsilon(\epsilon_0)$	11
2	The shear modulus $\mu(\epsilon)$ is assumed to be either monotonically decreasing or monotonically increasing	13
3	Stress-strain curve and the geometry of shock waves. See text, Section 5	14
4	Typical mode shapes of steady waves. Dashed lines indicate shock waves. Roman numerals refer to cases discussed in Section 6	16
5	Stress strain curve and the equal area construction for the case $T_\epsilon(\epsilon_0) < \rho c^2 < \mu(\epsilon_0)$. Typical mode shapes are also shown. Dashed lines indicate shock waves	19
6	Stress strain curves with inflections and the equal area construction. Case a) shows a simple inflection; Case b) shows a model for a phase change. Typical mode shapes are also shown	20
7	Phase plane showing both bounded and unbounded trajectories. Typical mode shapes for some of the unbounded trajectories are also shown	22

I. INTRODUCTION

A rod may be represented intrinsically as a stretching line endowed with structure.¹ In the most elementary version of this idea one scalar internal variable can be used to simulate the effects of finite transverse dimensions in a straight cylindrical rod that undergoes only axisymmetric motions. The rod then has two kinematically independent degrees of freedom. In cylindrical coordinates R, θ, Z the motion of the rod is assumed to be

$$z = Z + w(Z, t), \quad r = R[1 + u(Z, t)], \quad \theta = \theta, \quad (1)$$

where the initial radius of the rod is a , and t is time. All field quantities depend only on the axial coordinate Z and time t .

In a previous paper² some of the consequences of the theory were worked out for an elastic material with a strain energy $W(\epsilon, u, q)$ that depends on axial strain $\epsilon = w_Z$, radial strain u , and gradient of radial strain $q = u_Z$, where the subscripts denote partial differentiation. In the terms of general continuum mechanics W is the energy density of a one-dimensional elastic continuum with one scalar internal variable, and because of invariance considerations, it is required to be an even function in q .² With a kinetic energy density $K = \frac{1}{2}\rho_1 w_t^2 + \frac{1}{2}\rho_2 u_t^2$ Hamilton's principle leads to the following Euler-Lagrange equations,

$$S_Z = \rho_1 w_{tt}, \quad Q_Z - P = \rho_2 u_{tt} \quad (2)$$

where $S = W_\epsilon$, $P = W_u$, $Q = W_q$. In Reference 2 it was shown that the forces S , P , Q may be interpreted as averages of Piola-Kirchhoff stresses, taken over a cross-section of the rod,

$$\begin{aligned} S &\leftrightarrow \frac{1}{A} \int T^{ZZ} dA, \quad P \leftrightarrow \frac{1}{A} \int (T^{rR} + T^{\theta\theta}) dA, \\ Q &\leftrightarrow \frac{1}{A} \int R T^{rZ} dA, \end{aligned} \quad (3)$$

and the appropriate kinetic energy densities are $\rho_1 = \rho$ where ρ is the density of the rod material and $\rho_2 = \frac{1}{2}pa^2$. Equation (2)₁ describes forces

¹Antman, S. S., "The Theory of Rods," *Handbuch der Physik*, Vol. VIa/2, Springer-Verlag, New York 1972.

²Wright, T. W., "Nonlinear Waves in Rods," in *Proc. IUTAM Symp. on Finite Elasticity*, D. E. Carlson and R. T. Shield, eds., Martinus-Nijhoff Publ., The Hague, 1981.

and motions in the axial direction, and equation (2)₂ describes forces and motions in the radial direction.

II. INCOMPRESSIBLE MATERIAL

If the material is incompressible, then ϵ and u are no longer kinematically independent and therefore cannot be varied independently in Hamilton's principle. The incompressibility relationship between ϵ and u , shown in equation (4),

$$(1 + \epsilon)(1 + u)^2 = 1, \quad (4)$$

must be used as a side condition in the variational principle, and the explicit dependence of the strain energy on radial strain must be suppressed,

$$W(\epsilon, u, q) = \hat{W}(\epsilon, q). \quad (5)$$

Under these conditions the Euler-Lagrange equations become

$$S_Z - [\lambda(1 + u)^2]_Z = \rho_1 w_{tt}, \quad Q_Z + 2\lambda(1 + u)(1 + \epsilon) = \rho_2 u_{tt}, \quad (6)$$

where λ is a Lagrange multiplier, and now $S = \hat{W}_\epsilon$ and $Q = \hat{W}_q$. Clearly λ may be interpreted as a superimposed hydrostatic (Cauchy) pressure. In the formulation leading to either (2) or (6) more or less equal weight is given to both radial shear, which enters through the dependence of W on q , and to radial inertia, which enters from the finite value for ρ_2 .

III. STEADY WAVES

A steady wave is a disturbance that travels down the rod at a constant speed without distortion. To examine equations (6) for the possibility of steady waves it is supposed that all field variables depend only on the combination $\xi = Z - ct$, where c is an arbitrary constant. The partial differential equations then become ordinary differential equations.

$$S' - [\lambda(1 + u)^2]' = \rho c^2 \epsilon', \quad (7)$$

$$Q' + 2\lambda(1 + u)(1 + \epsilon) = \frac{1}{2} \rho a^2 c^2 u', \quad (8)$$

where the dash signifies differentiation with respect to ξ , and ρ_1 and ρ_2 have been written in terms of ρ . As in Reference 2 there are two integrals of the motion,

$$S - \lambda(1 + \epsilon)^{-1} = \rho c^2(1 + \epsilon) + A, \quad (9)$$

$$Qu' + S(1 + \epsilon) - \lambda - \hat{W} = \quad (10)$$

$$\frac{1}{2} \rho c^2 [(1 + \epsilon)^2 + \frac{1}{2} a^2 u'^2] + B,$$

where A and B are constants of integration. The first integral is straight forward. The second integral is obtained by multiplying (7) by $(1 + \epsilon)$, (8) by u' , adding the two resulting equations, and noting that (10) is the integral of the summed expression. Equation (9) may be used to eliminate λ from (10), arriving finally at equation (11),

$$Qu' + A(1 + \epsilon) - \hat{W} = \frac{1}{2} \rho c^2 [\frac{1}{2} a^2 u'^2 - (1 + \epsilon)^2] + B. \quad (11)$$

So far the results are exact given the initial premises concerning the strain energy, the kinetic energy, and the condition of incompressibility.

IV. SMALL SURFACE ANGLE

Now, suppose that the surface angle is small in the sense that $au' \ll 1$, and express the strain energy as the first two terms of a power series in u' with coefficients that depend on ϵ in an arbitrary way,

$$\hat{W}(\epsilon, q) = \hat{W}(\epsilon, 0) + \frac{1}{2} q^2 \hat{W}_{qq}(\epsilon, 0) + \dots \quad (12)$$

Alternatively, consider the special case when $\hat{W}$ can be expressed exactly as

$$\hat{W}(\epsilon, q) = \int_0^q T(\epsilon) d\epsilon + \frac{1}{4} a^2 \mu(\epsilon) q^2. \quad (13)$$

$T(\epsilon)$ is engineering stress (force per unit original area) for uniform extension, and $\mu(\epsilon)$ is interpreted as the shear modulus. (In the linear version of the theory μ would be the bulk shear modulus as in Reference 2, so it seems fair to give it that name for finite extension as well.) From the assumed form of the energy (13) with λ eliminated by use of (8) and u eliminated by use of the incompressibility condition (4), the integral (9) may be written

$$T_0 = T(\epsilon) - \rho c^2(\epsilon - \epsilon_0) - \frac{1}{2} \gamma \epsilon'^2 - \gamma(\epsilon) \epsilon'', \quad (14)$$

where $\gamma = \frac{1}{8} a^2 (1 + \epsilon)^{-3} [\mu(\epsilon) - \rho c^2]$, and $T_0 = T(\epsilon_0)$. For convenience A has been replaced by $T_0 - \rho c^2(1 + \epsilon_0)$. Similarly the integral (11) may now be written

$$\frac{1}{4} a^2 (\mu - \rho c^2) u'^2 = \int_0^q T d\epsilon - [T_0 - \rho c^2(1 + \epsilon_0)](1 + \epsilon) - \frac{1}{2} \rho c^2(1 + \epsilon)^2 + B. \quad (15)$$

By rearranging terms and using the incompressibility condition (4), the integral may be rewritten as

$$\frac{1}{16} a^2 \frac{(\mu - \rho c^2)}{(1 + \epsilon)^3} \epsilon'^2 = \int_{\epsilon_0}^{\epsilon} [T(\epsilon) - T_0 - \rho c^2(\epsilon - \epsilon_0)] d\epsilon + C, \quad (16)$$

where C is an arbitrary constant. Equation (16) also follows from (14) directly upon noting that multiplication by ϵ' makes the terms $\frac{1}{2} \gamma \epsilon'^3 + \gamma \epsilon'' \epsilon'$ the exact derivative of $\frac{1}{2} \gamma(\epsilon) \epsilon'^2$. Solution of (16) then follows simply by quadrature.[†] The integral on the right hand side of (16) is the area between the homogeneous extension curve and a straight line through the point (T_0, ϵ_0) with slope ρc^2 . As shown in Figure 1, the cross-hatched areas both to the right and to the left of (T_0, ϵ_0) are positive. The Lagrange multiplier is given by the following expression.

$$\lambda = \frac{1}{8} \left\{ \left[\frac{\mu_{\epsilon}}{(1 + \epsilon)^2} - \frac{3}{2} \frac{\mu - \rho c^2}{(1 + \epsilon)^3} \right] \epsilon'^2 + \frac{\mu - \rho c^2}{(1 + \epsilon)^2} \epsilon' \right\}. \quad (17)$$

V. SHOCK WAVES

Although integration of (16) is straightforward, the characteristics of a particular solution depend on the parameters in the problem and the nature of the functions $T(\epsilon)$ and $\mu(\epsilon)$. In addition, it is also possible for discontinuities to occur in certain limiting cases. Therefore, before sketching out the rich variety of solutions available, it is necessary to consider the propagation of shock waves.

Since the cross sectional area of the rod cannot change discontinuously, the radial strain must be continuous according to (1), and since the material is incompressible, the axial strain must be continuous as well.

[†]Aifantis and Serrin⁵ in discussing phase transitions in the presence of surface tension and Coleman⁶ in developing a static theory of necking and drawing of fibers have encountered equations of the form

$T_0 = T(\epsilon) + \beta(\epsilon) \epsilon'^2 + \gamma(\epsilon) \epsilon''$. In fact, for static cases when $c = 0$, equation (14) coincides exactly with Coleman's result if his equilibrium equation is obtained from a variational principle (see equation (3.20) and the following discussion in Reference 6). The more general equation was solved by finding an integrating factor (e.g., see Reference 6, equation (3.3)) to obtain a first integral, followed by a quadrature to obtain a second integral.




Figure 1. Stress-strain curve and the equal area construction for bounded smooth waves where $\mu < T_\epsilon(\epsilon_0)$.

However, both u' and ϵ' may have discontinuities, and therefore, by (17) so can λ . The appropriate jump condition comes from the integral form of (2) or (6),^{3,4}

$$\frac{1}{2} \rho a^2 V^2 = \frac{[\partial \hat{W} / \partial q]}{[q]}, \quad (18)$$

where $[\cdot]$ signifies the jump in a quantity across a shock wave.[†] Substitution for W from (13) gives

$$\rho V^2 = \mu(\epsilon), \quad [q] \text{ is arbitrary}, \quad (19)$$

so that the speed V of a shock wave of any amplitude is determined solely by the instantaneous shear modulus.

If the shock is incorporated into a steady wave, then $V = c$, and if $\mu(\epsilon)$ is a monotonic function either increasing or decreasing (the only cases considered in this paper), then for a given steady wave speed c , (19) can be satisfied only at isolated values of ϵ , say $\epsilon = \epsilon^*$, unless μ is truly constant. The situation is shown in Figure 2. Since the left hand side of (16) is zero at a shock wave, no matter what the value of ϵ'^2 , two steady waves with the same speed may be joined together at the shock, but of course each wave has distinct values for T_0 , ϵ_0 , and the constant C . These values are not independent in this case, and in fact if one is known for a particular steady wave, the others may be easily computed. This is best seen by referring to Figure 3. For the case shown $\epsilon > \epsilon^*$, the point R has coordinates (T_0, ϵ_0) , and $C = -\text{Area}(PQR)$. If a second steady wave has the same speed so that $Q'R'$ is parallel to QR , then R' has coordinates (T'_0, ϵ'_0) , and $C' = -\text{Area}(PQ'R')$. The quantity $[\epsilon'^2]$ may be determined from (14), noting that $\gamma = 0$ for a steady shock wave.

$$[T_0 + \rho c^2(\epsilon^* - \epsilon_0)] = -\frac{1}{16} a^2 \frac{\mu_{\epsilon}(\epsilon^*)}{(1 + \epsilon^*)^3} [\epsilon'^2]. \quad (20)$$

The magnitude of the left hand side of (20) is just the vertical distance QQ' in Figure 3.

³Nunziato, J. W., and Walsh, E. K., "One-dimensional Shock Waves in Uniformly Distributed Granular Materials," *Int. J. Solids and Structures* 14 (1978) 681-689.

⁴Wright, T. W., "Weak Shocks and Steady Waves in a Nonlinear Rod or Granular Material," (to appear, *Int. J. Solids and Structures*).

[†]In a three-dimensional context, a discontinuity in the strain gradient would be classified as an acceleration wave, but in the present context, where the discontinuity occurs in derivatives of lower order than the highest that appear in the governing differential equation (2) and (8), it is legitimate to use the word shock.




Figure 2. The shear modulus $\mu(\epsilon)$ is assumed to be either monotonically decreasing or monotonically increasing.




Figure 3. Stress-strain curve and the geometry of shock waves.
See text, Section 5.

VI. STEADY WAVE SOLUTIONS

By a process similar to that used in References 5 and 6 it is possible to show that bounded smooth solutions in an infinite rod must be one of three kinds: periodic waves, solitary waves with either a single propagating bulge or neck, or a propagating smooth transition from one state of uniform strain to another. But in addition, solutions with discontinuities, as described in the previous section, may occur. Most of these will appear as limiting cases of the smooth solutions. At this point it is easiest to proceed by considering examples and special cases. Figure 4 shows a sketch of the rod configuration for each of the cases considered.

A. $T(\epsilon)$ is concave down and at ϵ_0 , $\mu(\epsilon_0) < T_\epsilon(\epsilon_0)$.

Refer to Figure 1 and consider the following construction. Through the point T_0, ϵ_0 draw a straight line with positive slope ρc^2 , chosen such that $\mu(\epsilon_0) < \rho c^2 < T_\epsilon(\epsilon_0)$. From Figure 2 find ϵ^* , which will lie to the left of ϵ_0 if $\mu(\epsilon)$ is a decreasing function or to the right of ϵ_0 if $\mu(\epsilon)$ is an increasing function. Finally mark off equal cross hatched areas to the right and left of ϵ_0 with ϵ^* lying outside the cross hatched interval, and set the constant C equal to minus one half the total cross hatched area. From the construction, it is clear that $\epsilon'^2 \geq 0$ over the whole interval from $\epsilon_{\min}$ to $\epsilon_{\max}$, and $\epsilon' = 0$ only at the end points. Furthermore, the construction is such that near either end point ϵ' varies as the square root of the distance from the end point. Every construction of this kind corresponds to a periodic steady wave. As the magnitude of C increases, the cross hatched areas extend farther from ϵ_0 , corresponding to a larger amplitude of the wave, until one of the following finally occurs: either i) $\epsilon_{\max} = \hat{\epsilon}$, or ii) $\epsilon_{\min} = \epsilon^*$ for the case of decreasing μ , or iii) $\epsilon_{\max} = \epsilon^*$ for the case of increasing μ . The preceding discussion shows that periodic waves form a family with three parameters, say T_0 , c , and $\epsilon_{\max}$. T_0 may be chosen arbitrarily, but c and $\epsilon_{\max}$ can only be chosen within limits.

The limiting cases require special treatment.

i) Solitary Waves, $\epsilon_{\max} = \hat{\epsilon}$. As $\epsilon_{\max}$ increases towards $\hat{\epsilon}$, the period of the wave also increases and becomes infinite when $\epsilon_{\max} = \hat{\epsilon}$. The wave in

⁵Aifantis, E. C., and Serrin, J. B., "Towards a Mechanical Theory of Phase Transformations," Tech. Rpt., Corrosion Research Center, University of Minnesota, Minneapolis, 1982.

⁶Coleman, B. D., "Necking and Drawing in Polymeric Fibers Under Tension," Arch. Rat. Mech. Anal. 83 (1983) 115-137.




Figure 4. Typical mode shapes of steady waves. Dashed lines indicate shock waves. Roman numerals refer to cases discussed in Section 6.

this case consists of a single crest, a propagating bulge in the radius of the rod for the stress/strain curve shown in Figure 1. At infinity behind and ahead of the wave the strain is $\hat{\epsilon}$, decreasing to $\epsilon_{\min}$, as determined by the equal area rule, at the crest. Since the maximum strain is determined by the choice of T_0 and c , solitary waves form a two parameter family.

ii) Shock Waves, $\epsilon_{\min} = \epsilon^*$. As $\epsilon_{\min}$ decreases towards ϵ^* , the crests of the wave become less and less rounded until finally when $\epsilon_{\min} = \epsilon^*$, the crests become sharp with ϵ' changing discontinuously. Since C in (16) has been chosen such that both sides vanish when $\epsilon = \epsilon^*$,

$$\lim_{\epsilon \rightarrow \epsilon^*} \epsilon'^2 = \frac{16(1 + \epsilon^*)^3}{a^2} \cdot \frac{T(\epsilon^*) - T_0 - \rho c^2(\epsilon^* - \epsilon_0)}{\mu_\epsilon(\epsilon^*)}, \quad (21)$$

and ϵ' jumps from one of the values that satisfies (21) to the other. The numerator in the second factor of (21) is just the negative of the vertical distance PQ in Figure 3. Choice of c determines ϵ^* , and choice of T_0 determines $\epsilon_{\max}$ from the equal area rule, so waves of this kind form a two parameter family.

iii) Shock Waves, $\epsilon_{\max} = \epsilon^*$. This case is the same as ii) except that shock waves occur at $\epsilon_{\max}$ rather than $\epsilon_{\min}$.

It may happen that two of the limiting cases occur simultaneously.

ii)' Shock Wave, $\epsilon_{\max} = \hat{\epsilon}$ and $\epsilon_{\min} = \epsilon^*$. In this case the solitary wave has a sharp crest on it. The two cross hatched areas in Figure 1 extend all the way from ϵ_0 to $\hat{\epsilon}$ and from ϵ_0 to ϵ^* . Since only one choice of T_0 will make the areas equal for a given c , these waves form a one parameter family.

iii)' $\epsilon_{\max} = \hat{\epsilon} = \epsilon^*$. By analogy with the previous case it might seem that this case would correspond to a single shock wave occurring at the maximum strain, but in fact ϵ' is zero at $\epsilon_{\max}$. This occurs because the right side of (16) now has a double zero at $\epsilon_{\max}$, but the coefficient of ϵ'^2 on the left side has only a simple zero. Thus, these waves are simply periodic waves of maximum wave length. However, since discontinuities can occur at ϵ^* , one cycle of a wave could be joined to a uniform state both behind and ahead of the wave thus creating a solitary wave of finite wavelength. Since the choice of c determines ϵ^* (and hence $\epsilon_{\max}$) and the equal area construction will determine all other parameters, these waves are a one parameter family.

iv) As stated in Section 5, a shock wave may join two steady waves together if they have the same speed. Cases ii), ii)', and iii) suggest many ways in which this could be done. Two sharp crested periodic waves with unequal wave lengths could be joined, for example, but two more interesting cases are a) a sharp crested periodic wave jointed to a sharp crested solitary wave, which resembles the familiar dispersive pattern in linear elasticity for a step load on the end of a right circular cylinder, and b) a uniform state jointed to a sharp crested solitary wave, which is really just a limiting form of iva) and might be termed a structured shock wave. With these constructions it is possible to join two arbitrary (within limits) stress states with a steady wave.

B. $T(\epsilon)$ is concave down and at ϵ_0 , $T_\epsilon(\epsilon_0) < \mu(\epsilon_0)$.

If the stress/strain curve for uniform extension turns over so far that $T_\epsilon(\epsilon_0) < \mu(\epsilon_0)$, then the previous construction for bounded solutions must be modified by choosing c such that $T_\epsilon(\epsilon_0) < \rho c^2 < \mu(\epsilon_0)$. In all other respects, however, the construction is the same. Equal areas to the right and left of ϵ_0 extend to $\epsilon_{\max}$ and $\epsilon_{\min}$. Limiting cases occur when $\epsilon_{\min}$ coincides with either $\hat{\epsilon}$ or ϵ^* (for the case of increasing μ) or when $\epsilon_{\max}$ coincides with ϵ^* (for the case of decreasing μ). Periodic waves, including periodic shock waves, look much the same as before, but the wave of infinite period (i.e., the solitary wave) is now a propagating neck rather than a bulge as previously and the limiting case is a sharp notch rather than a sharp crest. Since two different steady waves can be joined through a shock wave, many combinations are possible, but perhaps the most interesting case is the structured shock wave which joins a uniform state to half of a sharp notch. The sketches in Figure 5 should be compared with those in Figure 4.

C. $T(\epsilon)$ has an inflection point and $T_\epsilon(\epsilon_0) < \mu(\epsilon_0)$.

In this case the equal area construction can lead to a smooth transition from one uniform state to another provided that

$T_\epsilon(\epsilon_0) < \rho c^2 < \mu(\epsilon_0)$ and ϵ^* lies outside the range of strains in the transition. The constant C is equal to half the doubly cross hatched area shown in Figure 6a. The construction is valid even if the stress/strain curve for uniform extension has a maximum and a minimum as shown in Figure 6b. Such a curve has been suggested by Ericksen as a model for phase change⁷ and was used by Coleman to describe necking and drawing of polymers⁶. In the latter context the solution represented by Figure 6b shows the influence of radial inertia and radial shear on the drawing process at high speed. Note also the implication that the drawing speed is limited by the shear speed of the undrawn (drawn) material for $\mu(\epsilon)$ increasing (decreasing).

⁷Ericksen, J. L., "Equilibrium of Bars," *J. Elasticity* 5 (1975) 191-201.




Figure 5. Stress strain curve and the equal area construction for the case $T_{\epsilon_0} < \rho c^2 < \mu(\epsilon_0)$. Typical mode shapes are also shown. Dashed lines indicate shock waves.




Figure 6. Stress strain curves with inflections and the equal area construction. Case a) shows a simple inflection; Case b) shows a model for a phase change. Typical mode shapes are also shown.

It is possible for ϵ^* to lie at either the minimum or the maximum strain of the transition. In that case there will be a shock discontinuity on one side or the other of the transition, but as long as the equal area construction can be maintained, a transition solution still exists. In this case the constant C is equal to half the total cross hatched area in Figure 6b.

VII. UNBOUNDED SOLUTIONS

So far only solutions that are bounded for $-\infty < Z - ct < \infty$ have been described, but there are unbounded steady wave solutions as well. To find these, it is easiest to adopt a slightly different point of view based on the phase plane.

As an example refer to Figure 1, consider the case shown there for $\mu(\epsilon)$ decreasing and $\epsilon^* < \epsilon_0$, and suppose that ϵ_0 and c are both fixed. The construction is such that the right hand side of equation (16) has a minimum at $\epsilon = \epsilon_0$ and a maximum at $\epsilon = \hat{\epsilon}$. The constant C can be either positive or negative so the right hand side of (16) has either one or three real zeros including a possible double zero at the maximum or minimum. The coefficient of ϵ'^2 on the left hand side of (16) has only a simple zero at $\epsilon = \epsilon^*$. Bearing these facts in mind and taking account of the relative positions of the zeros on both sides, one may solve equation (16) for ϵ' as a function of ϵ and sketch a family of curves, as in Figure 7, each member of which corresponds to a different value of C . Because of the zero at ϵ^* , no curve can cross the vertical line $\epsilon = \epsilon^*$ except the case where the right hand side of (16) has a zero at ϵ^* as well, and because of incompressibility, no curve can cross the line $\epsilon = -1$. For other values of T_0 , ϵ_0 , and c the phase plane diagram can be substantially modified. For example, the location of ϵ^* obviously will have a pronounced effect, and if the straight line through T_0 , ϵ_0 has no other intersection with $T(\epsilon)$, there can be no orbits that correspond to smooth solitary waves.

The closed trajectories around ϵ_0 represent periodic waves with the curve labeled L being the limiting case of sharp crested waves. Examples of unbounded trajectories are labeled A through G. Even though these trajectories are unbounded in the phase plane, the corresponding deformation patterns are readily interpretable, and are also sketched in Figure 7, showing the rod radius as a function of ξ . Although no solution to an initial/boundary value problem could include any point with $\epsilon = -1$ or $\epsilon = \infty$ or $\epsilon' = \pm\infty$, a segment of an unbounded trajectory that does not include such singularities would be perfectly acceptable. Problems in which the material moves at constant speed with respect to fixed boundaries, where fixed boundary conditions are specified, would fall in this category.




Figure 7. Phase plane showing both bounded and unbounded trajectories. Typical mode shapes for some of the unbounded trajectories are also shown.

REFERENCES

1. Antman, S. S., "The Theory of Rods," Handbuch der Physik, Vol. VIa/2, Springer-Verlag, New York, 1972.
2. Wright, T. W., "Nonlinear Waves In Rods," in Proc. IUTAM Symp. on Finite Elasticity, D. E. Carlson and R. T. Shield, eds., Martinus Nijhoff Publ., The Hague, 1981.
3. Nunziato, J. W., and Walsh, E. K., "One-Dimensional Shock Waves in Uniformly Distributed Granular Materials," Int. J. Solids and Structures 14 (1978) 681-689.
4. Wright, T. W., "Weak Shocks and Steady Waves in a Nonlinear Rod or Granular Material" (to appear, Int. J. Solids and Structures).
5. Aifantis, E. C., and Serrin, J. B., "Towards a Mechanical Theory of Phase Transformations," Tech. Report., Corrosion Research Center, University of Minnesota, Minneapolis 1982.
6. Coleman, B. D., "Necking and Drawing in Polymeric Fibers Under Tension," Arch. Rat. Mech. Anal. 83 (1983) 115-137.
7. Ericksen, J. L., "Equilibrium of Bars," J. Elasticity 5 (1975) 191-201.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22314	5	Commander Armament Research and Development Center US Army AMCCOM ATTN: SMCAR-TSS SMCAR-LCA, T. Davidson SMCAR-SC, J. D. Corrie J. Beetle E. Bloore Dover, NJ 07801
2	Director Defense Advanced Research Projects Agency ATTN: Tech Info Dr. E. Van Reuth 1400 Wilson Boulevard Arlington, VA 22209	1	Director Benet Weapons Laboratory Armament R&D Center US Army AMCCOM ATTN: SMCAR-LCB-TL Watervliet, NY 12189
1	Deputy Assistant Secretary of the Army (R&D) Department of the Army Washington, DC 20310	1	Commander US Army Armament Munitions and Chemical Command ATTN: AMSMC-LEP-L Rock Island, IL 61299
1	HQDA (DAMA-ARP-P, Dr. Watson) Washington, DC 20310	5	Director Benet Weapons Laboratory ATTN: Dr. M. A. Hussain Dr. John Underwood Mr. D. P. Kendall Dr. J. Throup Dr. E. Schneider Watervliet, NY 12189
1	HQDA (DAMA-MS) Washington, DC 20310	1	Commander US Army Aviation Research and Development Command ATTN: AMSAV-E 4300 Goodfellow Boulevard St. Louis, MO 63120
1	Commandant Command and General Staff College ATTN: Archives Fort Leavenworth, KS 66027	1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035
1	Commander US Army War College ATTN: Lib Carlisle Barracks, PA 17013		
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333		
1	Commander Armament Research and Development Center US Army AMCCOM ATTN: SMCAR-TDC Dover, NJ 07801		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Communications Research and Development Command ATTN: AMSEL-ATDD Fort Monmouth, NJ 07703	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missile Range NM 88002
1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: AMDSD-L Fort Monmouth, NJ 07703	1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905
1	Commander US Army Harry Diamond Laboratory ATTN: DELHD-TA-L 2800 Powder Mill Road Adelphi, MD 20783	1	Commander US Army Electronics Proving Ground ATTN: Tech Lib Fort Huachuca, AZ 85613
1	Commander US Army Missile Command ATTN: AMSMI-R Redstone Arsenal, AL 35898	3	Director BMD Advanced Technology Center ATTN: ATC-T, M. Capps ATC-M, S. Brockway ATC-RN, P. Boyd P. O. Box 1500 Huntsville, AL 35807
1	Commander US Army Missile Command ATTN: AMSMI-YDL Redstone Arsenal, AL 35898	3	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-T, J. Mescall DRXMR-T, R. Shea DRXMR-H, S. C. Chou Watertown, MA 02172
2	Commander US Army Mobility Equipment Research & Development Command ATTN: DRDME-WC DRSME-RZT Fort Belvoir, VA 22060	5	Commander US Army Research Office ATTN: Dr. R. Weigle Dr. E. Saibel Dr. G. Mayer Dr. F. Smiedeshoff Dr. J. Chandra P. O. Box 12211 Research Triangle Park, NC 27709
1	Commander US Army Natick Research and Development Center ATTN: DRXRE, Dr. D. Sieling Natick, MA 01760		
1	Commander US Army Tank Automotive Command ATTN: AMSTA-TSL Warren, MI 48090		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Commander US Army Research and Standardization Group (Europe) ATTN: Dr. B. Steverding Dr. F. Rothwarf Box 65 FPO NY 09510	7	Commander Naval Research Laboratory Engineering Materials Division ATTN: E. A. Lange G. R. Yoder C. A. Griffis R. J. Goode R. W. Judy, Jr. A. M. Sullivan R. W. Crooker Washington, DC 20375
1	Office of Naval Research Department of the Navy ATTN: Code 402 Washington, DC 20360	1	AFWL/SUL Kirtland AFB, NM 87117
1	Commander US Naval Air Systems Command ATTN: AIR-604 Washington, DC 20360	4	Air Force Armament Laboratory ATTN: J. Foster John Collins Joe Smith Guy Spitale Eglin AFB, FL 32542
1	Commander Naval Ordnance Systems Command Washington, DC 20360	1	RADC (EMTLD, Lib) Griffiss AFB, NY 13441
3	Commander Naval Surface Weapons Center ATTN: Dr. W. H. Holt Dr. W. Mock Tech Lib Dahlgren, VA 22448	1	AUL (3T-AUL-60-118) Maxwell AFB, AL 36112
3	Commander Naval Surface Weapons Center ATTN: Dr. R. Crowe Code R32, Dr. S. Fishman Tech Lib Silver Spring, MD 20910	1	AFWAL/AFSC ATTN: Dr. John P. Henderson Wright-Patterson AFB, OH 45433
1	AFWAL/AFSC ATTN: Dr. Theodore Nicholas Wright-Patterson AFB, OH 45433	1	Director Environmental Science Service Administration US Department of Commerce Boulder, CO 80302
5	Commander US Naval Research Laboratory ATTN: C. Sanday R. J. Weimer Code 5270, F. MacDonald Code 2020, Tech Lib Code 7786, J. Baker Washington, DC 20375	1	Director Lawrence Livermore Laboratory ATTN: Dr. M. L. Wilkins P. O. Box 808 Livermore, CA 94550

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
6	Director Sandia National Laboratory ATTN: Dr. L. Davison Dr. P. Chen Dr. L. Bertholf Dr. W. Herrmann Dr. J. Nunziato Dr. S. Passman Albuquerque, NM 87115	7	SRI International ATTN: Dr. George R. Abrahamson Dr. Donald R. Curran Dr. Donald A. Shockey Dr. Lynn Seaman Mr. D. Erlich Dr. A. Florence Dr. R. Caligiuri 333 Ravenswood Avenue Menlo Park, CA 94025
1	Director Jet Propulsion Laboratory ATTN: Lib (TDS) 4800 Oak Grove Drive Pasadena, CA 91109	1	System Planning Corporation ATTN: Mr. T. Hafer 1500 Wilson Boulevard, Suite 1500 Arlington, VA 22209
1	Commander US Army Development & Employment Agency ATTN: MODE-TED-SAB Fort Lewis, WA 98433	1	Terra Tek, Inc. ATTN: Dr. Arfon Jones 420 Wakara Way University Research Park Salt Lake City, UT 84108
1	Aeronautical Research Associates of Princeton, Incorporated ATTN: Ray Gogolewski 1800 Old Meadow Rd., #114 McLean, VA 22102	3	California Institute of Technology Division of Engineering and Applied Science ATTN: Dr. J. Miklowitz Dr. E. Sternberg Dr. J. Knowles Pasadena, CA 91102
1	Honeywell, Inc. Defense Systems Division ATTN: Dr. Gordon Johnson 600 Second Street, NE Hopkins, MN 55343	1	Denver Research Institute University of Denver ATTN: Dr. R. Recht P. O. Box 10127 Denver, CO 80210
1	HQDA DAMA-ART-M Washington, DC 20310	3	Rensselaer Polytechnic Institute ATTN: Prof. E. H. Lee Prof. E. Krempf Prof. J. Flaherty Troy, NY 12181
2	Orlando Technology, Inc. ATTN: Dr. Daniel Matuska Dr. John J. Osborn P. O. Box 855 Shalimar, FL 32579	1	Southwest Research Institute ATTN: Dr. Charles Anderson 6220 Culebra Road P. O. Drawer 28510 San Antonio, TX 78284

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Southwest Research Institute Department of Mechanical Sciences ATTN: Dr. U. Lindholm Dr. W. Baker 8500 Culebra Road San Antonio, TX 78228	2	Forrestal Research Center Aeronautical Engineering Lab. Princeton University ATTN: Dr. S. Lam Dr. A. Eringen Princeton, NJ 08540
1	University of Dayton Research Institute ATTN: Dr. S. J. Bless Dayton, OH 45469	1	Harvard University Division of Engineering and Applied Physics ATTN: Prof. J. R. Rice Cambridge, MA 02138
6	Brown University Division of Engineering ATTN: Prof. R. Clifton Prof. H. Kolsky Prof. L. B. Freund Prof. A. Needleman Prof. R. Asaro Prof. R. James Providence, RI 02912	2	Iowa State University Engineering Research Laboratory ATTN: Dr. G. Nariboli Dr. A. Sedov Ames, IA 50010
3	Carnegie Mellon University Department of Mathematics ATTN: Dr. D. Owen Dr. M. E. Gurtin Dr. B. D. Coleman Pittsburgh, PA 15213	2	Lehigh University Center for the Application of Mathematics ATTN: Dr. E. Varley Dr. R. Rivlin Bethlehem, PA 18015
2	Catholic University of America School of Engineering and Architecture ATTN: Prof. A. Durelli Prof. J. McCoy Washington, DC 20017	1	New York University Department of Mathematics ATTN: Dr. J. Keller University Heights New York, NY 10053
6	Cornell University Department of Theoretical and Applied Mechanics ATTN: Dr. Y. H. Pao Dr. G. S. S. Ludford Dr. A. Ruoff Dr. J. Jenkins Dr. R. Lance Dr. F. Moon Ithaca, NY 14850	1	North Carolina State University Department of Civil Engineering ATTN: Prof. Y. Horie Raleigh, NC 27607
		1	Pennsylvania State University Engineering Mechanical Dept. ATTN: Prof. N. Davids University Park, PA 16802
		1	Rice University ATTN: Dr. C. C. Wang P. O. Box 1892 Houston, TX 77001

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Southern Methodist University Solid Mechanics Division ATTN: Prof. H. Watson Dallas, TX 75222	1	University of Delaware Dept. of Mechanical Engineering ATTN: Prof. J. Vinson Newark, DE 19711
1	Temple University College of Engineering Technology ATTN: Dr. R. M. Haythornthwaite Dean Philadelphia, PA 19122	1	University of Delaware Dept. of Mechanical and Aerospace Engineering ATTN: Dr. Minoru Taya Newark, DE 19711
4	The Johns Hopkins University ATTN: Prof. R. B. Pond, Sr. Prof. R. Green Prof. W. Sharpe Prof. J. Bell 34th and Charles Streets Baltimore, MD 21218	3	University of Florida Dept. of Engineering Science and Mechanics ATTN: Dr. C. A. Sciammarilla Dr. L. Malvern Dr. E. Walsh Gainesville, FL 32601
1	Tulane University Dept. of Mechanical Engineering ATTN: Dr. S. Cowin New Orleans, LA 70112	2	University of Houston Department of Mechanical Engineering ATTN: Dr. T. Wheeler Dr. R. Nachlinger Houston, TX 77004
3	University of California ATTN: Dr. M. Carroll Dr. W. Goldsmith Dr. P. Naghdi Berkeley, CA 94720	1	University of Illinois Dept. of Theoretical and Applied Mechanics ATTN: Dr. D. Carlson Urbana, IL 61801
1	University of California Dept. of Aerospace and Mechanical Engineering Science ATTN: Dr. Y. C. Fung P. O. Box 109 La Jolla, CA 92037	1	University of Illinois ATTN: Dean D. Drucker Urbana, IL 61801
1	University of California Department of Mechanics ATTN: Dr. R. Stern 504 Hilgard Avenue Los Angeles, CA 90024	1	University of Illinois at Chicago College of Engineering Dept. of Civil Engineering, Mechanics and Metallurgy ATTN: Dr. T. C. T. Ting P. O. Box 4348 Chicago, IL 60680
1	University of California at Santa Barbara Dept. of Mechanical Engineering ATTN: Prof. T. P. Mitchel Santa Barbara, CA 93106	2	University of Kentucky Dept. of Engineering Mechanics ATTN: Dr. M. Beatty Prof. O. Dillon, Jr. Lexington, KY 40506

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	University of Maryland Department of Mathematics ATTN: Prof. S. Antman College Park, MD 20740	2	Washington State University Department of Physics ATTN: Dr. R. Fowles Dr. G. Duvall Pullman, WA 99163
1	University of Minnesota Dept. of Aerospace Engineering and Mechanics ATTN: Prof. J. L. Erickson 107 Akerman Hall Minneapolis, MN 55455	2	Yale University ATTN: Dr. B.-T. Chu Dr. E. Onat 400 Temple Street New Haven, CT 06520
1	University of Pennsylvania Towne School of Civil and Mechanical Engineering ATTN: Prof. Z. Hashin Philadelphia, PA 19105	<u>Aberdeen Proving Ground</u>	
4	University of Texas Department of Engineering Mechanics ATTN: Dr. M. Stern Dr. M. Bedford Prof. Ripperger Dr. J. T. Oden Austin, TX 78712	Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen Cdr, USATECOM ATTN: AMSTE -TO-F Cdr, CRDC, AMCCOM, ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-SPS-IL	
1	University of Washington Dept. of Aeronautics and Astronautics ATTN: Dr. Ian M. Fyfe 206 Guggenheim Hall Seattle, WA 98105		

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number _____ Date of Report _____
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. How specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS	_____
	Name

	Organization

	Address

	City, State, Zip

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD ADDRESS	_____
	Name

	Organization

	Address

	City, State, Zip

(Remove this sheet along the perforation, fold as indicated, staple or tape closed, and mail.)