

**B
R
L****AD F 300 4 90****TECHNICAL REPORT BRL-TR-2591****DETAILED CHARACTERIZATION OF THE INTERIOR
BALLISTICS OF SLOTTED STICK PROPELLANT****AD-A147 499****Frederick W. Robbins
Albert W. Horst****September 1984****DTIC
ELECTE
NOV 13 1984
S D
E****APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.****US ARMY BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND****DTIC FILE COPY****84 11 01 083**

Destroy this report when it is no longer needed.
Do not return it to the originator.

Additional copies of this report may be obtained
from the National Technical Information Service,
U. S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as an official
Department of the Army position, unless so designated by other
authorized documents.

The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TECHNICAL REPORT BRL-TR-2591	2. GOVT ACCESSION NO. ADA147499	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Detailed Characterization of the Interior Ballistics of Slotted Stick Propellant		5. TYPE OF REPORT & PERIOD COVERED Technical Report Oct 82-Sep 83
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Frederick W. Robbins and Albert W. Horst		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Ballistic Research Laboratory ATTN: AMXBR-IBD Aberdeen Proving Ground, MD 21005-5066		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1L162618AH80
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Ballistic Research Laboratory ATTN: AMXBR-OD-ST Aberdeen Proving Ground, MD 21005-5066		12. REPORT DATE September 1984
		13. NUMBER OF PAGES 31
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Interior Ballistics Stick Propellant Guns Computer Codes Pressure Waves NOVA Flamespread		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) While classical, lumped-parameter modeling of granular propellant gun firings is often quite successful at reproducing experimental data, a similar treatment of stick propellant firings typically yields somewhat lower pressures and muzzle velocities than actually experienced in the gun. To identify those processes responsible for this behavior, a set of highly-instrumented gun firings has been performed in a 155-mm howitzer, using both stick and granular propellant charges. To simplify the investigation as well as to facilitate the analysis, a slotted, single-perforated stick propellant		

DD FORM 1473 EDITION OF 1 NOV 68 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

was employed, and the granular propellant was prepared simply by cutting some of the sticks to a shorter length. Firings of the two types of charges yielded the same muzzle velocities, but with the stick charges operating at a 4% lower maximum chamber pressure. Detailed analysis of pressure versus time and travel profiles, obtained using fixed and on-board pressure instrumentation, along with concurrent multiphase flow (NOVA) simulations of the event, suggest two major contributors to the unexpected performance of the stick propellant charges. The first is an "artificial progressivity" resulting from higher post-peak chamber pressures associated with the more localized burning of the stick propellant (vis that of the longitudinally distributed, fluidized bed of granular propellant). The second is a hydrodynamic effect resulting from the non-Lagrangian pressure and velocity profiles exhibited by a stick propellant charge, again ultimately associated with the grossly discontinuous distribution of the burning stick propellant as opposed to the more continuous distribution of the granular propellant throughout most of the tube.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	5
LIST OF TABLES	7
I. INTRODUCTION	9
II. EXPERIMENTAL	9
III. RESULTS	12
IV. ANALYSIS AND DISCUSSION	13
V. CONCLUSIONS	17
ACKNOWLEDGMENTS	21
REFERENCES	22
DISTRIBUTION LIST	23

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



LIST OF ILLUSTRATIONS

Figure	Page
1. Configurations of Test Charges	10
2. Locations of Pressure Gages in 155-mm, M199 Cannon	11
3. Burning Rate of M30Al Propellant, Lot RAD 472-10	11
4. Loci of Maximum Pressures	15
5. Breech Pressure Versus Travel - Experimental	16
6. Projectile Base Pressure Versus Travel - Experimental	16
7. NOVA Predictions of Gas-Velocity Profiles at Propellant Burnout	18
8. NOVA Predictions of Gas-Velocity Profiles at Projectile Exit	18
9. Breech and On-Board Projectile Base Pressures Versus Travel for a Stick Propellant (LSX) Charge	19
10. NOVA Prediction of Breech and Projectile Base Pressures Versus Travel for a Stick Propellant (LSX) Charge	19
11. Breech and On-Board Projectile Base Pressures Versus Travel for a Granular Propellant (SSX) Charge	20
12. NOVA Prediction of Breech and Projectile Base Pressures Versus Travel for a Granular Propellant (SSX) Charge	20

LIST OF TABLES

Table	Page
1. Summary of Firing Data	12
2. Maximum Pressures at Specified Gage Locations	12
3. Breech and Projectile Base Pressures as a Function of Travel	13
4. Comparison of Calculated and Experimental Results	14

I. INTRODUCTION

Numerous investigators have noted that slotted stick propellant appears to provide a higher muzzle velocity for the same charge weight than does 7-perforated, granular propellant.¹⁻³ At the same time, lumped-parameter modeling of experimental gun firings, typically quite successful in predicting the performance of granular propellant charges, has not provided similarly satisfactory simulations of stick propellant firings, even when the propellant has been slotted to minimize perforation-augmented burning processes.^{1,3} The charge weight of stick propellant for a given performance level is usually predicted to be greater than actually required, with gun firings yielding higher pressures than expected for any given charge weight. This apparent increase in thermodynamic efficiency for stick propellant suggests that some mechanism must be involved beyond that of the influence of grain geometry on the mass generation profile. The investigation reported herein was devised to identify any such mechanisms.

II. EXPERIMENTAL

A carefully designed set of gun firings was conducted in a 155-mm howitzer (M199 Cannon) to demonstrate and quantify the increase in muzzle velocity obtained using stick rather than granular propellant. Slotted stick propellant was chosen for the test to eliminate perforation-augmented burning as a major factor in the combustion process,³ and the granular propellant was obtained by simply cutting some of the stick propellant to a shorter length. Thus the compositions and form functions, as well as charge weights, were identical for both the stick and granular propellant charges tested, reducing the number of variables involved and simplifying the analysis. M30A1 propellant, Lot RAD 472-10, was employed, both as full-length, 737-mm sticks and cut into 25-mm-long grains, as shown in Figure 1. There were four charges made from the full-length stick (LS1,...,LS4) and four charges from the shortened "grains" (SS1,...,SS4); in addition, four standard (7-perforated granular) M203 charges were fired to provide baseline data. Propellant for the test charges (LSX and SSX) was weighed to 11.04 kg (either to within one SSX grain or by cutting one of the LSX sticks), a value previously determined in probe firings to give the appropriate M203 performance level. The standard M203 charges were all downloaded and brought to a weight of 11.84 kg (again, to within one grain). Further, packaging and igniter components for all three groups of charges tested were taken from one lot of M203 charges. Finally, inert-loaded M101 projectiles, adjusted to a weight of 43.08 kg and loaded to an average seating distance of 82.3 cm from the spindle face, were used for all the firings.

¹T.C. Minor, "Mitigation of Ignition-Induced Two-Phase Flow Dynamics in Guns Through the Use of Stick Propellant," ARBRL-TR-02508, Ballistic Research Laboratory, USA ARRADCOM, Aberdeen Proving Ground, MD, August 1983. ADA-133685.

²A. Grabowsky, S. Weiner, and A. Beardell, "Closed Bomb Testing of Stick Propellant Charge Assemblies," 17th JANNAF Combustion Meeting, CPIA Publication 329, Vol II, pp. 119-124, November 1980.

³F.W. Robbins and A.W. Horst, "Continued Study of Stick Propellant Combustion Processes," ARBRL-MR-03296, Ballistic Research Laboratory, USA ARRADCOM, Aberdeen Proving Ground, MD, July 1983. (AD A133004).




Figure 1. Configurations of Test Charges

The firings were performed at the Ballistic Research Laboratory's Sandy Point (R-18) Test Facility on 20 December 1982. The M199 cannon was instrumented with twelve Kistler 607C2 pressure gages (two each at three axial locations in the chamber and six at downbore locations, as shown in Figure 2). The same gages and instrumentation components were employed throughout the tests in order to best capture the relative differences among groups. A Doppler velocimeter was used to measure in-tube velocities, and induction coils were employed to determine muzzle velocities. Subsequent testing was also performed using telemetry-instrumented projectiles to provide on-board measurements of projectile base pressure and acceleration throughout the in-bore trajectory.

In support of this investigation, closed bomb firings were also conducted to determine burning rates for the RAD 472-10 propellant. Testing was done with the shortened, 25-mm-long grains and, since the propellant was slotted, the data were assumed to be applicable to the full-length sticks as well. A composite of results from four closed bomb firings, along with measured grain dimensions and calculated thermodynamic data, is provided in Figure 3.




Figure 2. Locations of Pressure Gages in 155-mm, M199 Cannon




Figure 3. Burning Rate of M30A1 Propellant, Lot RAD 472-10

III. RESULTS

Muzzle velocities and maximum breech pressures for the three configurations are tabulated in Table 1.

TABLE 1. SUMMARY OF FIRING DATA

Type	Maximum Breech Pressure (MPa)	Muzzle Velocity (m/s)	Type	Maximum Breech Pressure (MPa)	Muzzle Velocity (m/s)	Type	Maximum Breech Pressure (MPa)	Muzzle Velocity (m/s)
SS1	347.8	815.8	LS1	335.7	815.1	M203	330.1	823.8
SS2	349.5	815.0	LS2	333.3	813.5	M203	326.3	818.8
SS3	344.3	812.0	LS3	335.5	813.5	M203	324.9	817.2
SS4	346.5	812.5	LS4	330.2	814.3	M203	329.8	820.7
Average values:								
SSX	347.0	813.8	LSX	333.7	814.1	M203	327.8	820.1
Standard deviations:								
	(2.19)	(1.86)		(2.56)	(0.55)		(2.58)	(2.84)

Table 2 provides a compilation of the average maximum pressures recorded at each gage location. Values for the first four provide the loci of maximum pressures for the chamber and rear portion of the tube. The gages at positions greater than 149.6 cm are uncovered after maximum chamber pressure occurs; values reported at these locations provide data needed for construction of a downbore base pressure versus travel curve.

TABLE 2. MAXIMUM PRESSURES AT SPECIFIED GAGE LOCATIONS

DISTANCE FROM SPINDLE (cm)	PRESSURE FOR SSX (MPa)	PRESSURE FOR LSX (MPa)
0.0	347	334
41.7	332	321
83.3	322	296
149.6	302	290
256.3	189	189
332.5	142	143
408.7	109	117
484.9	90	92
576.3	65	67

A final presentation of experimental data is given in Table 3, which provides, as a function of projectile travel (determined by passage of the various downbore gages), average values of pressure recorded at the breech and at the appropriate downbore pressure gages. These data were then used to establish discrete-time, breech and projectile base pressure versus travel curves for subsequent, detailed comparison of stick and granular slotted propellant firings.

TABLE 3. BREECH AND PROJECTILE BASE PRESSURES AS A FUNCTION OF TRAVEL

PROJECTILE TRAVEL (cm)	BREECH PRESSURE (MPa)		PROJECTILE BASE PRESSURE (MPa)	
	SSX	LSX	SSX	LSX
58	333	328	302	290
165	216	231	189	189
241	160	163	142	143
318	114	111	109	117
394	92	88	90	92
485	71	71	65	67

IV. ANALYSIS AND DISCUSSION

The above firings were modeled using both a lumped-parameter interior ballistic computer code (IBHVG, a descendant of the Baer and Frankle code),⁴ and a one-dimensional, two-phase flow interior ballistic code (NOVA).⁵ All input parameters were independently determined. Values for the burning rates, the thermodynamic parameters, the barrel resistance curve, and the chamber dimensions were identical for each code. Additional inputs required for the NOVA code (e.g., friction factor, Poisson ratio, and the speed of sound in the solid aggregate) were again determined from independent measurements or taken to be the best available values. In an attempt to maintain use of the same data bases, neither code considered the presence of the salt bag or other parasitic components. The major difference in treatments thus dealt with the lumped-parameter (i.e., "well-stirred") Lagrangian picture of the gas-solid mixture provided by IBHVG versus the full multiphase flow description of NOVA (including flamespread, detailed treatment of pressure gradients, and explicit recognition of propellant motion). A comparison of calculated and experimental results is provided in Table 4.

⁴P.G. Baer and J.M. Frankle, "The Simulation of Interior Ballistic Performance of Guns by Digital Computer Program," BRL R 1183, USA Aberdeen Research and Development Center, Ballistic Research Laboratories, Aberdeen Proving Ground, MD, December 1962. AD-299980.

⁵P.S. Gough, "Extensions to NOVA Flamespreading Modeling Capacity," PGA-TR-81-2, Paul Gough Associates, Inc., Portsmouth, NH, April 1981.

TABLE 4. COMPARISON OF CALCULATED AND EXPERIMENTAL RESULTS

	GRANULAR (SSX)		STICK (LSX)	
	BREECH PRESSURE (MPa)	MUZZLE VELOCITY (m/s)	BREECH PRESSURE (MPa)	MUZZLE VELOCITY (m/s)
EXPERIMENTAL	347	814	334	814
IBHVG	348	816	327	808
NOVA	342	816	332	821

We note that IBHVG predicts that the muzzle velocity for the stick firings should be 8 m/s less than for the granular, yet the experimental values obtained were the same. The probability of the velocity difference actually being greater than 4 m/s, assuming normal populations and using the standard deviations from Table I, turns out to be less than 0.1%, suggesting this disparity to be significant. An accepted use of lumped-parameter interior ballistic codes is the design of propellant grain geometry. After matching results to an existing set of firings, calculations are then typically performed with different propellant grain geometries with the expectation that the calculated changes in the maximum pressure and velocity will be correct, both in direction and in approximate magnitude. This is not the case here, where IBHVG results indicate a need for other physics beyond that associated only with the influence of grain geometry on the mass generation profile. The NOVA calculations, while not providing quite as good a match to the granular propellant firing data as does IBHVG, do suggest the influence of some such additional physical process, since an increase in velocity at a reduced maximum pressure is indicated for the stick charge.

Some insight into this difference between granular and stick propellant charge phenomenology can be gained by a detailed comparison of the experimental data to corresponding NOVA calculations, which allow us to infer information, such as gas-velocity profiles and solid-phase motion, not easily measured in the gun. First of all, we note from these (Table 2) and earlier firings that the loci of maximum pressures in the gun chamber and rear portion of the tube are quite different for the two propellant geometries. More structure is noted with the stick charge, even though recorded maxima occur within 0.5 ms of one another. As revealed in Figure 4, NOVA simulations capture this effect quite well.

This additional structure appears to accompany the formation of a large region of ullage which opens up between the forward boundary of the bundle of stick propellant and the base of the projectile as it moves down the bore and leaves the propellant behind. This event might be compared to a sudden enlargement in the cross-sectional area of a pipe through which gas is flowing. The same effect is not predicted to occur with granular propellant because increased interphase drag forces tend to distribute the propellant throughout most of the region, both eliminating the discontinuity in area and providing mass addition (via combustion) in this forward region as well.




Figure 4. Loci of Maximum Pressures

Figure 5, constructed from the data of Table 3, also calls attention to the fact that breech pressures after the time of maximum chamber pressure are higher for the stick than for the granular propellant. Such behavior is usually attributed to a more progressive grain geometry. However, NOVA code results suggest another mechanism to be operative in this case, again finding its origin in the reduced propellant motion, more than in the different burning surface profile, associated with the stick geometry. While initial loading densities for stick and granular charges may be the same, after significant projectile motion, the "effective" loading densities might be quite different. The well-dispersed granular propellant can then deposit its combustion products throughout most of the volume between breech face and projectile base, but the stick propellant (as long as it remains intact) must burn in a far more localized region, with a finite time required to communicate information about this local accumulation of gases to distant portions of the tube (similar to a nozzleless rocket). This same effect was also observable upon comparison of experimental breech pressure versus time curves for the granular and stick firings (not shown here).

We next call attention to the fact that, if we plot the discrete data for experimental base pressure versus projectile travel (see Figure 6), the pressure at the base of the projectile for the stick firings shows an unexpected rise corresponding to the 327-cm position. The NOVA simulations again allow us to interpret this event. Since the stick firings show a slightly lower peak breech pressure but a higher breech pressure shortly thereafter (as explained above), predicted values of projectile travel at burnout turn out to be within 15 cm (262 cm for stick versus 277 cm for




Figure 5. Breech Pressure Versus Travel - Experimental




Figure 6. Projectile Base Pressure Versus Travel - Experimental

granular) of one another. Even when the projectile accelerated by the stick charge reaches the same position (277 cm), NOVA predicts it to be moving 5.5 m/s slower. (Doppler measurements performed during this program corroborated this trend.) Why then, after burnout, does the projectile continue to be accelerated faster for the stick charge than the granular charge? We recall that Figure 6 previously confirmed a higher downbore pressure for the stick propellant charge long after burnout. Again, we formulate a hypothesis associated with the discontinuous distribution of stick propellant in the gun tube, throughout its burning. We already noted its impact on pressure-distance profiles in the gun chamber (Figure 4); NOVA simulations reveal, in addition to this structure in the pressure field, a highly non-Lagrangian gas-velocity profile at burnout, shown in Figure 7, as well. Subsequent hydrodynamics can be assured to propagate this structured environment downstream, resulting in a temporarily increased acceleration relative to that encountered by the projectile experiencing the more "Lagrangian" environment provided by the granular propellant charge. Figure 8 shows the calculated gas-velocity profiles at the moment the projectile exits the muzzle.

Finally, we add that pressure- and accelerometer-instrumented projectiles were also fired using both the LSX and SSX charges. Figure 9 displays breech and on-board base pressure versus distance profiles for these firings, confirming the earlier results provided by discrete-location gages. Note particularly the excess in base pressure over that at the breech when the projectile is at about 300 cm of travel. Corresponding NOVA results are provided as Figure 10. Experimental and calculated pressure versus travel data for the granular charge, displayed in Figures 11 and 12 respectively, reveal profiles more nearly approximating the classical form.

V. CONCLUSIONS

Based on a detailed analysis of the experimental data described above, with added insight provided by concurrent NOVA code simulations of the firings, we conclude that there are two major contributors to the higher performance efficiency exhibited by stick propellant in large-caliber guns. The first is an "artificial progressivity" resulting from higher post-peak chamber pressures associated with the more localized burning of the stick propellant (as opposed to that of a longitudinally distributed, fluidized bed of granular propellant). Thus, while the initial loading densities of the two charges may be nearly identical, the "apparent" free volume associated with burning of the stick propellant after significant projectile motion may be significantly less than that for the granular propellant charge. The net results are higher local pressures and faster burning of the propellant remaining after peak pressure, allowing more time to extract "work" from the combustion gases. Interestingly enough, though this phenomenon is related to the reduced interphase drag of the stick geometry which leads to less motion of the solid phase, this behavior may still be considered a classical effect, in that its influence may be accounted for, to some extent, in a classical, lumped-parameter interior ballistic model by simply altering the pressure at which the propellant burns from the space-mean pressure to some value more representative of the local environment. (An accompanying change in the energy equation to reduce the contribution assigned to the kinetic energy of the solid phase is also recommended.)




Figure 7. NOVA Predictions of Gas-Velocity Profiles at Propellant Burnout




Figure 8. NOVA Predictions of Gas-Velocity Profiles at Projectile Exit




Figure 9. Breech and On-Board Projectile Base Pressures Versus Travel for a Stick Propellant (LSX) Charge




Figure 10. NOVA Prediction of Breech and Projectile Base Pressures Versus Travel for a Stick Propellant (LSX) Charge




Figure 11. Breech and On-Board Projectile Base Pressures Versus Travel for a Granular Propellant (SSX) Charge




Figure 12. NOVA Prediction of Breech and Projectile Base Pressures Versus Travel for a Granular Propellant (SSX) Charge.

The second effect finds its origin in this same difference in the distribution of the solid phase between stick and granular propellant during the combustion phase; however, it clearly requires a hydrodynamic treatment of the interior ballistic cycle to estimate its importance. This phenomenon might be most easily understood by considering the nature of the gas velocity and pressure profiles in the tube at the time of propellant burnout. In the case of the granular propellant, a "Lagrangian" picture prevails: a nearly linearly increasing velocity profile between breech face and projectile base, with no abrupt changes in slope, with a correspondingly smooth, monotonically decreasing pressure profile. Conditions at burnout for the stick propellant charge are, however, quite different. Data presented in the previous sections reveal significant structure in the pressure profile, with the NOVA code providing similar information about the expected gas-velocity profile as well. If one considers these two pictures (i.e, stick versus granular profiles at burnout) as differing initial conditions to an ensuing single-phase, hydrodynamic event, it is quite easy to determine that the velocity of the projectile launched by the stick propellant charge upon muzzle exit may conceptually be higher or lower than that obtained with the granular charge, depending on the length of the gun tube. In the few, large-caliber systems studied to date, however, the stick propellant charge has always provided the higher muzzle velocity.

ACKNOWLEDGMENTS

The authors wish to thank Mr. S. Bernstein of LCWSL, USA ARRADCOM, Dover, NJ, for providing the M30A1 slotted stick propellant. We also wish to thank Dr. A. Juhasz of BRL, as well as his crew, for performing the closed bomb firings. Appreciation is also expressed to Mr. J. Evans, BRL, for instrumenting the projectiles and Messrs. J. Bowen, J. Hewitt, A. Koszoru, and J. Stabile for assisting with all firing operations at Sandy Point.

REFERENCES

1. T.C. Minor, "Mitigation of Ignition-Induced Two-Phase Flow Dynamics in Guns Through the Use of Stick Propellant," ARBRL-TR-02508, Ballistic Research Laboratory, USA ARRADCOM, Aberdeen Proving Ground, MD, August 1983. ADA-133685.
2. A. Grabowsky, S. Weiner, and A. Beardell, "Closed Bomb Testing of Stick Propellant Charge Assemblies," 17th JANNAF Combustion Meeting, CPIA Publication 329, Vol II, pp. 119-124, November 1980.
3. F.W. Robbins and A.W. Horst, "Continued Study of Stick Propellant Combustion Processes," ARBRL-MR-03296, Ballistic Research Laboratory, USA ARRADCOM, Aberdeen Proving Ground, MD, July 1983. (AD A133004).
4. P.G. Baer and J.M. Frankle, "The Simulation of Interior Ballistic Performance of Guns by Digital Computer Program," BRL R 1183, USA Aberdeen Research and Development Center, Ballistic Research Laboratories, Aberdeen Proving Ground, MD, December 1962. AD-299980.
5. P.S. Gough, "Extensions to NOVA Flamespreading Modeling Capacity," PGA-TR-81-2, Paul Gough Associates, Inc., Portsmouth, NH, April 1981.

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22314	1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333
1	Commander USA Concepts Analysis Agency 8120 Woodmont Avenue ATTN: D. Hardison Bethesda, MD 20014	1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDE-DW 5001 Eisenhower Avenue Alexandria, VA 22333
1	HQDA/DAMA-ZA Washington, DC 20310	5	Project Manager Cannon Artillery Weapons System, ARDC, AMCCOM ATTN: DRCPM-CW, F. Menke DRCPM-CWW DRCPM-CWS M. Fisette DRCPM-CWA R. DeKleine H. Hassmann Dover, NJ 07801
1	HQDA, DAMA-CSM, E. Lippi Washington, DC 20310		
1	HQDA/SARDA Washington, DC 20310		
1	Commandant US Army War College ATTN: Library-FF229 Carlisle Barracks, PA 17013		
1	Director US Army BMD Advanced Tech Ctr P. O. Box 1500 Huntsville, AL 35807	2	Project Manager Munitions Production Base Modernization and Expansion ATTN: DRCPM-PBM, A. Siklosi SARPM-PBM-E, L. Laibson Dover, NJ 07801
1	Chairman DOD Explosives Safety Board Room 856-C Hoffman Bldg. 1 2461 Eisenhower Avenue Alexandria, VA 22331	3	Project Manager Tank Main Armament System ATTN: DRCPM-TMA, K. Russell DRCPM-TMA-105 DRCPM-TMA-120 Dover, NJ 07801
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCSF-E, Safety Office 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Development & Employment Agency ATTN: MODE-TED-SAB Fort Lewis, WA 98433
1	HQDA DAMA-ART-M Washington, DC 20310		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
22	Commander Armament R&D Center US Army AMCCOM ATTN: DRSMC-TSS(D) DRSMC-TDC(D) DRSMC-LC, (D) LTC N. Barron DRSMC-LCA (D) J. Lannon A. Beardell D. Downs S. Einstein S. Westley S. Bernstein P. Kemney A. Bracuti J. Rutkowski DRSMC-ICB-I.(D),D.Spring DRSMC-LCE,(D) R.Walker DRSMC-LCM-E (D) S. Kaplowitz DRSMC-LCS (D) DRSMC-LCU-CT (D) E. Barriores R. Davitt DRSMC-LCU-CV (D) C. Mandala DRSMC-LCW-A (D) M. Salsbury DRSMC-SCA (D) L. Stiefel B. Brodman Dover, NJ 07801	1	Commander US Army Watervliet Arsenal ATTN: SARWV-RD, R. Thierry Watervliet, NY 12189
		1	Director Benet Weapons Laboratory Armament R&D Ctr/ US Army AMCCOM ATTN: DRSMC-LCB-TL(D) Watervliet, NY 12189
		1	Commander US Army Aviation Research and Development Command ATTN: DRDAV-E 4300 Goodfellow Blvd. St. Louis, MO 63120
		1	Commander US Army TSARCOM 4300 Goodfellow Blvd. St. Louis, MO 63120
		1	Director US Army Air Mobility Research And Development Laboratory Ames Research Center Moffett Field, CA 94035
		1	Commander US Army Communications Research and Development Command ATTN: DRSEL-ATDD Fort Monmouth, NJ 07703
5	Commander US Army Armament Munitions and Chemical Command ATTN: DRSMC-LEP-L (R) DRSMC-LC (R) L.Ambrosini DRSMC-IRC (R) G. Cowan DRSMC-LEM (R) W. Fortune R. Zastrow Rock Island, IL 61299	1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703
		1	Commander US Army Harry Diamond Lab. ATTN: DELHD-TA-L 2800 Powder Mill Road Adelphi, MD 20783

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Commander US Army Missile Command ATTN: DRSMI-R Redstone Arsenal, AL 35898	1	President US Army Armor & Engineer Board ATTN: STEBB-AD-S Fort Knox, KY 40121
1	Commander US Army Missile Command ATTN: DRSMI-YDL Redstone Arsenal, AL 35898	1	Project Manager M-60 Tank Development ATTN: DRCPM-M60TD Warren, MI 48090
1	Commandant US Army Aviation School ATTN: Aviation Agency Fort Rucker, AL 36360	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missile Range, NM 88002
1	Commander US Army Tank Automotive Command ATTN: DRSTA-TSL Warren, MI 48090	1	Commander US Army Training & Doctrine Command ATTN: ATCD-MA/ MAJ Williams Fort Monroe, VA 23651
1	US Army Tank Automotive Command ATTN: DRSTA-CG Warren, MI 48090	2	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL Tech Library Watertown, MA 02172
1	Project Manager Improved TOW Vehicle ATTN: DRCPM-ITV US Army Tank Automotive Command Warren, MI 48090	1	Commander US Army Research Office ATTN: Tech Library P. O. Box 12211 Research Triangle Park, NC 27709
2	Program Manager M1 Abrams Tank System ATTN: DRCPM-GMC-SA, T. Dean Warren, MI 48090	1	Commander US Army Mobility Equipment Research & Development Command ATTN: DRDME-WC Fort Belvoir, VA 22060
1	Project Manager Fighting Vehicle Systems ATTN: DRCPM-FVS Warren, MI 48090		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Commander US Army Logistics Mgmt Ctr Defense Logistics Studies Fort Lee, VA 23801	1	Office of Naval Research ATTN: Code 473, R. S. Miller 800 N. Quincy Street Arlington, VA 22217
1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905	3	Commandant US Army Armor School ATTN: ATZK-CD-MS M. Falkovitch Armor Agency Fort Knox, KY 40121
1	Commandant Command and General Staff College Fort Leavenworth, KS 66027	2	Commander Naval Sea Systems Command ATTN: SEA-62R2, R. Beauregard C. Christensen National Center, Bldg. 2 Room 6E08 Washington, DC 20360
1	Commandant US Army Special Warfare School ATTN: Rev & Tng Lit Div Fort Bragg, NC 28307	1	Commander Naval Air Systems Command ATTN: NAIR-954-Tech Lib Washington, DC 20360
1	Commandant US Army Engineer School ATTN: ATSE-CD Ft. Belvoir, VA 22060	1	Director Navy Strategic Systems Project Office Dept. of the Navy Rm. 901 ATTN: J. F. Kincaid Washington, D.C. 20360
1	Commander US Army Foreign Science & Technology Center ATTN: DRXST-MC-3 220 Seventh Street, NE Charlottesville, VA 22901	1	Assistant Secretary of the Navy (R, E, and S) ATTN: R. Reichenbach Room 5E787 Pentagon Bldg. Washington, DC 20350
1	President US Army Artillery Board Ft. Sill, OK 73503	1	Naval Research Lab Tech Library Washington, DC 20375
2	Commandant US Army Field Artillery School ATTN: ATSF-CO-MW, B. Willis Ft. Sill, OK 73503		
1	Chief of Naval Materiel Department of the Navy ATTN: J. Amlie Arlington, VA 20360		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
2	Commander US Naval Surface Weapons Center ATTN: J. P. Consaga C. Gotzmer Silver Spring, MD 20910	1	Program Manager AFOSR/(SREP) Directorate of Aerospace Sciences ATTN: L. H. Caveny Bolling AFB, DC 20332
5	Commander Naval Surface Weapons Center ATTN: Code G33, J. L. East W. Burrell J. Johndrow Code G23, D. McClure Code DX-21 Tech Lib Dahlgren, VA 22448	5	Commander Naval Ordnance Station ATTN: P. L. Stang J. Birkett S. Mitchell D. Brooks Tech Library Indian Head, MD 20640
4	Commander Naval Surface Weapons Center ATTN: S. Jacobs/Code 240 Code 730 K. Kim/Code R-13 R. Bernecker Silver Spring, MD 20910	1	AFSC/SDOA Andrews AFB, MD 20334
2	Commander Naval Underwater Weapons Research and Engineering Station Energy Conversion Dept. ATTN: CODE 5B331, R. S. Lazar Tech Lib Newport, RI 02840	6	AFRPL (DYSC) ATTN: D. George J. N. Levine B. Goshgarian D. Thrasher N. Vander Hyde Tech Library Edwards AFB, CA 93523
4	Commander Naval Weapons Center ATTN: Code 388, R. L. Derr C. F. Price T. Boggs Info Sci Div China Lake, CA 93555	1	AFFTC ATTN: SSD-Tech Lib Edwards AFB, CA 93523
2	Superintendent Naval Postgraduate School Dept. of Mechanical Engineering ATTN: A. E. Fuhs Code 1424 Library Monterey, CA 93940	1	AFATL/DLYV Eglin AFB, FL 32542
		1	AFATL/DLXP ATTN: W. Dittrich Eglin AFB, FL 32542
		1	AFATL/DLXL ATTN: O. K. Heiney Eglin AFB, FL 32542
		1	AFATL/DLODL ATTN: Tech Lib Eglin AFB, FL 32542

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	AFWL/FIBC ATTN: TST-Lib Wright-Patterson AFB, OH 45433	1	General Electric Company Armament Systems Dept. ATTN: M. J. Bulman, Room 1311 Lakeside Avenue Burlington, VT 05401
1	AFWL/SUL Kirtland AFB, NM 87117	1	IITRI ATTN: M. J. Klein 10 W. 35th Street Chicago, IL 60616
1	General Applied Sciences Lab ATTN: J. Erdos Merrick & Stewart Avenues Westbury, NY 11590	1	Hercules Powder Co. Allegheny Ballistics Laboratory ATTN: R. B. Miller P. O. Box 210 Cumberland, MD 21501
1	Aerodyne Research, Inc. Bedford Research Park ATTN: V. Yousefian Bedford, MA 01730	1	Hercules, Inc Bacchus Works ATTN: K. P. McCarty P. O. Box 98 Magna, UT 84044
1	Aerojet Solid Propulsion Co. ATTN: P. Micheli Sacramento, CA 95813	1	Hercules, Inc. Eglin Operations AFATL DLDL ATTN: R. L. Simmons Eglin AFB, FL 32542
1	Atlantic Research Corporation ATTN: M. K. King 5390 Cheorokee Avenue Alexandria, VA 22314	1	Lawrence Livermore National Laboratory ATTN: M. S. L-355, A. Buckingham P. O. Box 808 Livermore, CA 94550
1	AVCO Everett Rsch Lab ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149	1	Lawrence Livermore National Laboratory ATTN: M. S. L-355 M. Finger P. O. Box 808 Livermore, CA 94550
2	Calspan Corporation ATTN: Tech Library P. O. Box 400 Buffalo, NY 14225	1	Olin Corporation Badger Army Ammunition Plant ATTN: R. J. Thiede Baraboo, WI 53913
1	Foster Miller Associates ATTN: A. Erickson 135 Second Avenue Waltham, MA 02154		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Olin Corporation Smokeless Powder Operations ATTN: R. L. Cook P.O. Box 222 St. Marks, FL 32355	2	Thiokol Corporation Wasatch Division ATTN: J. Peterson Tech Library P. O. Box 524 Brigham City, UT 84302
1	Paul Gough Associates, Inc. ATTN: P. S. Gough P. O. Box 1614, 1048 South St. Portsmouth, NH 03801	2	Thiokol Corporation Elkton Division ATTN: R. Biddle Tech Lib. P. O. Box 241 Elkton, MD 21921
1	Physics International Company 2700 Merced Street San Leandro, CA 94577	2	United Technologies Chemical Systems Division ATTN: R. Brown Tech Library P. O. Box 358 Sunnyvale, CA 94086
1	Princeton Combustion Research Lab., Inc. ATTN: M. Summerfield 475 US Highway One Monmouth Junction, NJ 08852	1	Universal Propulsion Company ATTN: H. J. McSpadden Black Canyon Stage 1 Box 1140 Phoenix, AZ 85029
2	Rockwell International Rocketdyne Division ATTN: BA08 J. E. Flanagan J. Gray 6633 Canoga Avenue Canoga Park, CA 91304	1	Veritay Technology, Inc. ATTN: E. B. Fisher P. O. Box 22 Bowmansville, NY 14026
1	Science Applications, Inc. ATTN: R. B. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364	1	Battelle Memorial Institute ATTN: Tech Library 505 King Avenue Columbus, OH 43201
3	Thiokol Corporation Huntsville Division ATTN: D. Flanigan R. Glick Tech Library Huntsville, AL 35807	1	Brigham Young University Dept. of Chemical Engineering ATTN: M. Beckstead Provo, UT 84601
1	Scientific Research Assoc., Inc. ATTN: H. McDonald P.O. Box 498 Glastonbury, CT 06033		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	California Institute of Tech 204 Karman Lab Main Stop 301-46 ATTN: F. E. C. Culick 1201 E. California Street Pasadena, CA 91109	1	Institute of Gas Technology ATTN: D. Gidaspow 3424 S. State Street Chicago, IL 60616
1	California Institute of Tech Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, CA 91103	1	Johns Hopkins University Applied Physics Laboratory Chemical Propulsion Information Agency ATTN: T. Christian Johns Hopkins Road Laurel, MD 20707
1	University of Illinois Dept of Mech Eng ATTN: H. Krier 144 MED, 1206 W. Green St Urbana, IL 61801	1	Massachusetts Institute of Technology Dept of Mechanical Engineering ATTN: T. Toong 77 Massachusetts Avenue Cambridge, MA 02139
1	University of Massachusetts Dept. of Mechanical Engineering ATTN: K. Jakus Amherst, MA 01002	1	Pennsylvania State College Applied Research Lab ATTN: G. M. Faeth P. O. Box 30 State College, PA 16801
1	University of Minnesota Dept. of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455	1	Pennsylvania State University Dept. Of Mechanical Engineering ATTN: K. Kuo University Park, PA 16802
1	Case Western Reserve University Division of Aerospace Sciences ATTN: J. Tien Cleveland, OH 44135	1	Purdue University School of Mechanical Engineering ATTN: J. R. Osborn TSPC Chaffee Hall West Lafayette, IN 47906
3	Georgia Institute of Tech School of Aerospace Eng. ATTN: B. T. Zinn E. Price W. C. Strahle Atlanta, GA 30332	1	SRI International Propulsion Sciences Division ATTN: Tech Library 333 Ravenswood Avenue Menlo Park, CA 94025

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Rensselaer Polytechnic Inst. Department of Mathematics Troy, NY 12181		<u>Aberdeen Proving Ground</u> Dir, USAMSAA ATTN: DRXSY-D DRXSY-MP, H. Cohen
1	Los Alamos National Lab ATTN: T. D. Butler MS B216 P. O. Box 1663 Los Alamos, NM 87545		Cdr, USATECOM ATTN: DRSTE-TO-F STEAP-MT, S. Walton G. Rice D. Lacey C. Herud
1	Stevens Institute of Technology Davidson Laboratory ATTN: R. McAlevy, III Castle Point Station Hoboken, NJ 07030		Dir, HEL ATTN: J. Weisz Cdr, CRDC, AMCCOM ATTN: DRSMC-CLB-PA DRSMC-CLJ-L DRSMC-CLN
1	Rutgers University Dept. of Mechanical and Aerospace Engineering ATTN: S. Temkin University Heights Campus New Brunswick, NJ 08903		
1	University of Southern California Mechanical Engineering Dept. ATTN: OHE200, M. Gerstein Los Angeles, CA 90007		
2	University of Utah Dept. of Chemical Engineering ATTN: A. Baer G. Flandro Salt Lake City, UT 84112		
1	Washington State University Dept. of Mechanical Engineering ATTN: C. T. Crowe Pullman, WA 99163		

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number _____ Date of Report _____
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. How specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS	_____
	Name

	Organization

	Address

	City, State, Zip

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD ADDRESS	_____
	Name

	Organization

	Address

	City, State, Zip

(Remove this sheet along the perforation, fold as indicated, staple or tape closed, and mail.)