

AD-A150 013

LUMBER RIVER NORTH CAROLINA & SOUTH CAROLINA SPECIAL
FLOOD HAZARD INFORMATION REPORT(U) CORPS OF ENGINEERS
(CHARLESTON SC CHARLESTON DISTRICT MAR 78

1/1


UNCLASSIFIED

F/G R/A

NL



END
DATE
FILMED
3 85
1981



AD-A150 013

NATIONAL FLOOD CONTROL

OPERATION REPORT

LOWER RIVER

NORTH CAROLINA &

SOUTH CAROLINA

OPERATION REPORT

CONTENTS

	Page
PREFACE	1
DESCRIPTION OF STUDY AREA	1
FLOOD HISTORY	1
FUTURE FLOODS	3
Flood Frequency	3
Flood Elevations	5
FLOODWAY CONCEPT	5
Floodway	5
Floodway Fringe	6
Flood Protection Elevation	6
PRESENTATION OF INFORMATION	7
Flood Boundary & Floodway Maps	7
High Water Profiles	8

TABLES

	Page
TABLE 1	
Past Flood Data on Lumber River	2
TABLE 2	
Flood Discharges - Lumber River	4

EXHIBIT

EXHIBIT 1	
Typical Floodway Plan & Cross Section	Follows Page 6

Original contains color
plates. All DTIC reproductions
will be in black and
white.

LECTE

1985


A

PLATES

PLATE

- 1 General Map
- 2 Index Map Flooded Areas
- 3 12 Flood Boundary & Floodway Maps
- 13 24 High Water Profiles

Opposite Page 1
At
End
of
Report



PREFACE


This report has been developed to fill the need for flood information at various locations along Lumber River. The study was initiated as a result of a request from the State of North Carolina for floodway mapping in the vicinities of Lumberton, Boardman and Fairbluff, North Carolina. Various other requests indicated the need for information along the entire reach of Lumber River from the mouth to the town of Lumberton. Flood information within the corporate limits of Lumberton has been developed by the Corps of Engineers under contract for the Federal Insurance Administration and will be published in a separate report. Flood information presented in this report will not conflict with data which will be presented in the Lumberton Flood Insurance Report. No other flood insurance studies have been completed or are in progress which will affect the study area covered in this report.

Although there is some urban and agricultural development in the flood plain of Lumber River in the vicinity of Lumberton, Boardman and Fairbluff, North Carolina, Nichols, South Carolina and several other small communities, most of the area subject to flooding is heavily wooded swampland. In the future, some of this land is likely to be considered for industrial sites, waste treatment facilities and other uses. Knowledge of the flooding potential is an important factor in selecting, financing and insuring various types of development.

In the past, many large floods have occurred along Lumber River, causing considerable damage at various locations. The maximum flood of record occurred during August 1928. Other notable floods occurred during September 1945, October 1964, March 1971 and April 1973. This study indicates that future floods greater than these of the past are possible.

This report was prepared by the Corps of Engineers, Charleston District, under continuing authority provided in Section 206 of the 1960 Flood Control Act, as amended

Additional copies of this report can be obtained from the Corps of Engineers, Charleston District, upon request. The Corps of Engineers will also provide technical assistance in the interpretation and use of the information presented herein



Corps of Engineers U S Army
Charleston South Carolina District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N C & S C
GENERAL MAP
MARCH 1978

DESCRIPTION OF STUDY AREA

Lumber River is an interstate stream located in the upper coastal plain of southeastern North Carolina and northeastern South Carolina. The river is formed by the junction of several creeks in Moore County and Richmond County, North Carolina. It flows southeasterly to the vicinity of Boardman, North Carolina, thence southwesterly 41 miles to its mouth at Little Pee Dee River near Nichols, South Carolina. Lumber River drains an area of 1 760 square miles of which 1616 square miles are in North Carolina and 144 square miles are in South Carolina. See Plate 1. General Map.

This report covers the 63 mile reach of Lumber River from the mouth to Lumberton, North Carolina. The flood plain along the study reach varies in width from about 1.2 mile just below Lumberton to more than 4 miles near Boardman. Most of the flood plain is wooded swampland but a considerable amount of agricultural land is subject to flooding. There are also some commercial and residential buildings located in flood plain areas in the vicinity of Lumberton, Boardman and Fairbluff, North Carolina, and Nichols, South Carolina. Some of these structures have been damaged during past floods.

FLOOD HISTORY

The greatest known flood on Lumber River occurred during September 1928. The flood resulted from a hurricane that crossed the basin a few days after the area had previously been saturated by heavy rainfall. In Nichols, South Carolina, the water rose about 11 feet above normal stage and covered some of the streets. At Lumberton, the river rose to an elevation of 117 feet above mean sea level (about four or five feet above the bank). Other significant floods on Lumber River were those of September 1945, March 1971 and April 1973. Stages and discharges for past floods are shown in Table 1.

TABLE 1
PAST FLOOD DATA ON LUMBER RIVER

Location	River Mile	September 1928		September 1945		March 1971		April 1973	
		Stage ft msl	Discharge cfs	Stage ft msl	Discharge cfs	Stage ft msl	Discharge cfs	Stage ft msl	Discharge cfs
U S Hwy 76 near Nichols S C	4 79	55 2							
N C Hwy 904 at Fairbluff N C	21 16	66 5	28 500			63 7	11 300		
U S S Gage #2 1345 U S Hwy 74 Boardman N C	40 67	83 85	25 000	82 69	13 400	82 17	9 730	81 98	9 190
Carolina Light & Power Co below Lumberton N C	61 28					109 7			
S R 1620 below Lumberton N C	61 74	117 0							

Source of Information

- 1 U S Geological Survey
- 2 S C Highway Dept
- 3 Carolina Power & Light Co

FUTURE FLOODS

The main objective of this study is to furnish information which will be useful to planners and others interested in utilizing the flood plain areas along Lumber River. In order to establish flood elevation-frequency relationships, hydrological studies based on past flood data and rainfall records were conducted. The sources of data and methods of analysis are discussed in the following paragraphs.

Flood Frequency

The frequency or recurrence frequency of a flood is an expression of its rarity. Generally, large floods occur less frequently than small floods. Using records of past floods and statistical computational methods, the chance that a given flood event will be equaled or exceeded during a specified period of time can be determined. A 10 year flood can be expected to be equaled or exceeded about ten times during a 100 year period, or it has a one chance in ten of being equaled or exceeded during any year. The 100 year flood, recognized by the Federal Government and the State of North Carolina as the regulatory flood used as basis for flood insurance and land use regulations, has one chance in one hundred of being equaled or exceeded during any year.

Flood frequency determinations are based on stream flow records collected by the U.S. Geological Survey and rainfall records collected by the National Weather Service. Other important factors which are considered during determination of flood-frequency relationships include various characteristics of the drainage basin including size and shape of the basin, type of development and its location in the basin, topography, type of soil, etc.

There are several acceptable methods that can be employed in conducting a frequency analysis. In most cases, the method or methods are selected that best utilize the basic data. If reliable stream flow records are available for a long period of record, the Log Pearson Type III Method usually produces the best results. In the absence of stream gage records, good results can often be achieved by development of a rainfall runoff model (Unit Hydrograph) which relates runoff to rainfall frequency data published by the National Weather Service. In conducting the Lumber River flood frequency analysis, both the Log Pearson Type III Method and the Unit Hydrograph Method were employed. Peak discharges for 10 year, 50 year, 100 year and 500 year frequency floods were computed at several locations throughout the study reach. Computations were based on stream flow records collected by the U.S. Geological Survey on Lumber River at Boardman, N.C., river stage records collected by the National Weather Service on Lumber River at Lumberton, N.C., and rainfall frequency data published by the National Weather Service. Table 2 lists peak discharges for computed floods at various locations.

**TABLE 2
FLOOD DISCHARGES
LUMBER RIVER**

Location	River Mile	Drainage Area sq. miles	10 Year Flood Discharge cfs	50 Year Flood Discharge cfs	100 Year Flood Discharge cfs	500 Year Flood Discharge cfs
Above Little Bear, N.C.	0.00	1,760	16,300	25,000	29,800	42,000
Above Astoria Swamp	8.40	1,565	14,500	22,500	27,000	38,100
Above S.R. 904 at Earbluff, N.C.	23.23	1,350	12,500	19,100	24,000	34,800
U.S. Hwy. 74 at Boardman, N.C.	40.67	1,220	11,300	18,000	22,000	32,000
Above Big Swamp	43.00	757	7,000	12,500	15,500	25,700
S.R. 1620, below Lumberton, N.C.	61.74	716	6,600	11,800	14,800	25,000

Flood Elevations

After establishing flood discharge frequency relationships as discussed in the preceding paragraphs, the elevations that will be reached by floods of various frequencies are determined. The elevations that will be reached during a given flood event are dependent upon several factors including peak discharge, shape, slope and area of the stream bed and adjacent flood plain, type of cover (trees, brush, etc.) and natural or man-made features which obstruct flood flow such as bridges, culverts and dams. Field surveys are conducted to obtain the data necessary to numerically describe these factors which are used as basis for hydraulic computations. The hydraulic computations incorporate various hydraulic equations for open channel flow, pressure flow and weir flow. The end result is a flow area or profile for each computed flood which shows graphically the peak elevations that would be reached throughout the study area. Computed flood elevations can also be plotted in plan view on a topographic map to show the area that would be inundated by the flood. Flood profiles and flood boundary maps were prepared for the Lumber River study area and are discussed under Presentation of Information.

FLOODWAY CONCEPT

Floodway

Encroachment on flood plains, such as artificial fill, reduces the flood carrying capacity and increases flood heights, thus increasing flood hazards in areas beyond the encroachment itself. One aspect of flood plain management involves balancing the economic gain from flood plain development against the resulting increase in flood hazard. The concept of a floodway is used as a tool to assist local communities in this aspect of flood plain management. Under this concept, the area of the 100 year flood is divided into a proposed floodway and a floodway fringe. The floodway is the channel of a stream plus any adjacent flood



plain areas that must be kept free of encroachment in order that the 100 year flood be carried without substantial increases in flood heights. Criteria adopted by the Federal Government and the State of North Carolina limit such increases in flood heights to 1.0 foot, provided that hazardous velocities are not produced. The floodways in this report are proposed to local agencies as minimum standards that can be adopted or that can be used as a basis for additional studies. The floodway proposed for Lumber River was computed on the basis of equal conveyance reduction from each side of the flood plain. Floodway boundaries were determined at surveyed cross sections. Between cross sections the boundaries were extrapolated.

Floodway Fringe

The area between the floodway and the boundary of the 100 year flood is referred to as the floodway fringe. The floodway fringe thus encompasses the portion of the flood plain that could be completely obstructed without increasing the water surface elevation of the 100 year flood more than one foot at any point.

Flood Protection Elevation

Complete filling of the floodway fringe area will cause the 100 year flood to rise about one foot higher than it would under present conditions. This possible future 100 year flood elevation is referred to as the "Flood Protection Elevation" which is designed to serve as a guide for development within the floodway fringe areas. Homes and other damageable facilities should be constructed above the flood protection elevation or provided equivalent protection by floodproofing. Exhibit 1 illustrates the terms described in the preceding paragraphs.



NOTE.

Placement of landfill in floodway fringe areas will confine 100-Year Flood to floodway and raise Natural 100-Year Flood Crest Elevation one foot to Flood Protection Elevation.

Development located in Floodway Fringe areas should be elevated above Flood Protection Elevation.

**TYPICAL FLOODWAY
PLAN & CROSS SECTION**

Not to Scale

PRESENTATION OF INFORMATION

Flood Boundary and Floodway Maps

Plate 2 is an index of Plates 3 through 12 "Flood Boundary and Floodway Maps" which show floodway boundaries and floodway fringe areas (defined by the limits of the 100 year flood) on Lumber River. Also shown on the maps are locations and numbers of surveyed cross sections and computed flood protection elevations. The floodway and floodway fringe boundaries were located on the maps by scaling the computed distances right and left of stream centerline. In order to locate the floodway and floodway fringe boundaries on land, it will be necessary to scale distances from boundary lines to identifiable reference marks (roads, fence lines, etc.) on the maps, then measure the same distances in the field. The actual limits of the 100 year flood may vary somewhat from that shown on the map because the scale and contour interval of the maps do not permit precise plotting of the flood data.


The floodway was calculated based on existing hydraulic conditions only. The method of calculating the floodway removes an equal amount of conveyance from each side of the channel. Therefore, from a hydraulic standpoint, the floodway area on either side of the stream is in proportion to the flooding potential that now exists on its respective side of the stream.


It is realized that the floodway may have to be shifted from one side to the other, depending upon political, policy or other decisions. Also, public and private plans for development and conservation may influence the desirability of the floodway location. If such policies and plans dictate a shifting of the floodway, it will be necessary to recompute the floodway based on these decisions and the hydraulic considerations.


High Water Profiles

As mentioned in the previous paragraph, the limits of the 100-year flood, which delineate the floodway fringe area, are shown on the Flood Boundary and Floodway Maps. Plates 13 through 24 "High Water Profiles", show the profiles of 10-year, 50-year, 100-year and 500-year floods along Lumber River. Other information shown on the profiles includes stream bed elevations, locations of cross sections, and locations and elevations of bridges and culverts.

When using the Flood Profiles to determine flood elevations at a property site, first find the site on one of the Flood Boundary & Floodway Maps. Using the map scale, measure the distance, along the river channel, from the site to a reference point such as a bridge, cross section, mouth of a tributary stream or a river mile indicator. Next, find the reference point on the profile and measure the distance to the site along the horizontal scale of the profile. The horizontal scale is graduated in both thousands of feet and miles above the river mouth. The vertical scale is graduated in feet above mean sea level, datum of 1929.













- **LEGEND** -

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
-  FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
-  CROSS SECTION

- **NOTES** -

- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100 YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 10 FEET




Corps of Engineers, U S Army
Charleston, South Carolina, District


FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAPS


MARCH 1978

Match Line Plate 3





Match Line Plate 6





- LEGEND -

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
- (55.4)** FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
- 5** CROSS SECTION

- NOTES -


- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT.
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF.
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100 YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 10 FEET.




Corps of Engineers, U S Army
Charleston, South Carolina, District

FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAP

MARCH 1978



Match Lin





Match Line Plate 3

2



Match Line Plate 6

— LEGEND —

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
- (55.4)** FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
- 5** CROSS SECTION

— NOTES —

- 1 BASE MAP FURNISHED BY U S
GEOLOGICAL SURVEY. WASHINGTON. D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY
FROM ACTUAL LOCATION ON GROUND AS
EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE
SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER
RIVER ONLY FLOODWAY LIMITS WERE NOT
DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH
100 YEAR FLOOD LIMITS. THE 100 YEAR
FLOOD LIMIT BECOMES THE FLOODWAY
BOUNDARY
- 6 CONTOUR INTERVAL IS 5 FEET




Corps of Engineers, U S Army
Charleston, South Carolina, District

FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAPS

MARCH 1978

Match

Match Line Plate 5



Match Line

Match Line Plate 7





Match Line Plate 4

2



Match Line Plate 8

- LEGEND -

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
- (55.4)** FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
- 5** CROSS SECTION

- NOTES -

- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100-YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 5 FEET



Corps of Engineers, U S Army
Charleston, South Carolina, District

FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAP

MARCH 1978


Match



Study Limit





Match

Match Line Plate 9



Match Line Plate 6

- LEGEND -

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
-  FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
-  CROSS SECTION

- NOTES -

- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100 YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 5 FEET

Match Line Plate 8



Corps of Engineers, U S Army
Charleston, South Carolina, District


FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAPS


MARCH 1978

PL 8





Match Line Plate 7

Match Line Plate 6





- **LEGEND** -

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
-  FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
-  CROSS SECTION

- **NOTES** -


- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100 YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 10 FEET



Corps of Engineers, U S Army
Charleston South Carolina, District





FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAPS

MARCH 1978




Match Line Plate 11

- **LEGEND** -

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
-  **55.4** FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
-  **5** CROSS SECTION

- **NOTES** -

- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100 YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 5 FEET



Corps of Engineers, U S Army
Charleston, South Carolina, District

FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAPS

MARCH 1978



F A I R M O N T

Fairmont

Hill Street


Salem Street

U.S. 421


New Hope

Leggett Crossroads

Match Line P







Match Line Plate 9



Match Line Plate 11

— LEGEND —

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
-  FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
-  CROSS SECTION

— NOTES —

- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100 YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 5 FEET




Corps of Engineers, U S Army
Charleston, South Carolina, District

**FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAPS**


MARCH 1978

Match Line Plate 12





Match Line Plate 8

1 2




- LEGEND -

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
- (55.4)** FLOOD PROTECTION ELEVATION IN FEET ABOVE MEAN SEA LEVEL
- 5** CROSS SECTION

- NOTES -

- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100 YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 10 FEET




Corps of Engineers, U S Army
 Charleston, South Carolina, District


FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAPS

MARCH 1978

Study Limit



Match Line Pl





Match Line Plate 11

e



- **LEGEND** -

-  100-YEAR FLOOD
-  FLOODWAY BOUNDARY
- M+2** RIVER MILES
- (55.4)** FLOOD PROTECTION ELEVATION
IN FEET ABOVE MEAN SEA
LEVEL
- 5** CROSS SECTION

- **NOTES** -

- 1 BASE MAP FURNISHED BY U S GEOLOGICAL SURVEY, WASHINGTON, D C
- 2 LIMITS OF OVERFLOW SHOWN MAY VARY FROM ACTUAL LOCATION ON GROUND AS EXPLAINED IN THE REPORT
- 3 AREAS OUTSIDE THE FLOOD PLAIN MAY BE SUBJECT TO FLOODING FROM LOCAL RUNOFF
- 4 FLOODWAY BOUNDARIES APPLY TO LUMBER RIVER ONLY FLOODWAY LIMITS WERE NOT DETERMINED FOR TRIBUTARIES
- 5 WHERE FLOODWAY BOUNDARIES MERGE WITH 100 YEAR FLOOD LIMITS, THE 100 YEAR FLOOD LIMIT BECOMES THE FLOODWAY BOUNDARY
- 6 CONTOUR INTERVAL IS 10 FEET




Corps of Engineers, U S Army
 Charleston, South Carolina, District

FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
FLOOD BOUNDARY & FLOODWAY MAPS

MARCH 1978

RIVER MILES




STATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES

MARCH 1978

Sheet 1 of 12 Sheets



LEGEND

- 500-YEAR FLOOD
- 100-YEAR FLOOD
- - - - - 50-YEAR FLOOD
- - - - - 10-YEAR FLOOD

RIVER MILES

8

10

CONFLUENCE OF
AIRPOLE SWAMP

EAM
BED

400+00 420+00 440+00 460+00 480+00 500+00 520+00 540+00 560+00

ATIONS IN FEET ABOVE MOUTH


Corps of Engineers, U. S. Army
Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES

MARCH 1978

Sheet 2 of 12 Sheets

PLATE 14

RIVER




LEGEND

- 500-YEAR FLOOD
- 100-YEAR FLOOD
- 50-YEAR FLOOD
- 10-YEAR FLOOD

RIVER MILES

14



STREAM BED

CROSS SECTION
9


700+00 720+00 740+00 760+00 780+00 800+00 820+00 840+00
FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES

MARCH 1978
Sheet 3 of 12 Sheets

PLATE 10

RIVER




LEGEND

- 500-YEAR FLOOD
- 100-YEAR FLOOD
- 50-YEAR FLOOD
- 10-YEAR FLOOD

RIVER MILES

18

20



N. C. HWY. 904

REAM BED

11

12


960+00 980+00 1000+00 1020+00 1040+00 1060+00 1080+00 1100+00 1120+00

STATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
 Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES
 MARCH 1978

Sheet 4 of 12 Sheets

PLATE 16




LEGEND

- 500-YEAR FLOOD
- - - - - 100-YEAR FLOOD
- · - · - 50-YEAR FLOOD
- · - - - 10-YEAR FLOOD

RIVER MILES

24

26



STREAM BED

CROSS SECTION
1340+00

1240+00 1260+00 1280+00 1300+00 1320+00 1340+00 1360+00 1380+00 1400+00
 STATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
 Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES
 MARCH 1978


Sheet 5 of 12 Sheets

PLAN

2

RIVE

28




LEGEND

- 500-YEAR FLOOD
- - - - - 100-YEAR FLOOD
- · - · - 50-YEAR FLOOD
- · - - - 10-YEAR FLOOD


RIVER MILES

30



1520+00 1540+00 1560+00 1580+00 1600+00 1620+00 1640+00 1660+00 1680+00
STATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES
MARCH 1978
Sheet 6 of 12 Sheets




LEGEND

- 500-YEAR FLOOD
- - - - - 100-YEAR FLOOD
- · - · - 50-YEAR FLOOD
- · - · - 10-YEAR FLOOD

RIVER MILES

34

36




1800+00 1820+00 1840+00 1860+00 1880+00 1900+00 1920+00 1940+00 1960+00
ELEVATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES
MARCH 1978
Sheet 7 of 12 Sheets

2

30



LEGEND

- -
 -
 -
- 500-YEAR FLOOD
50-YEAR FLOOD
100-YEAR FLOOD
10-YEAR FLOOD

STATIONS IN FEET

RIVER MILES

40

42

BRIDGE FLOOR

LOW CHORD

U.S. HWY. 76 & N.C. HWY. 130

U.S.S. GAGE
2-1348

STREAM

350

22

23

24

21

2140+00

2160+00

2180+00

2200+00

2220+00

2240+00

2080+00

2100+00

2120+00


ELEVATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S.
HIGH WATER PROFILES

MARCH 1978

Sheet 8 of 12 Sheets

PLATE




LEGEND

- 500-YEAR FLOOD
- 100-YEAR FLOOD
- - - - - 50-YEAR FLOOD
- - - - - 10-YEAR FLOOD

RIVER MILES

46



2360+00
2380+00
2400+00
2420+00
2440+00
2460+00
2480+00
2500+00
2520+00

STATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S.
HIGH WATER PROFILES


MARCH 1978
Sheet 9 of 12 Sheets

PLATE

RIVER MILES

50

52



2840+00
 2800+00
 2680+00
 2700+00
 ELEVATIONS IN FEET ABOVE MOUTH


2720+00
 2740+00
 2760+00
 2780+00
 2800+00

Corps of Engineers, U. S. Army
 Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES

MARCH 1978

Sheet 10 of 12 Sheets


PLATE 8



RIVER MILES

56

58




2920+00 2940+00 2960+00 2980+00 3000+00 3020+00 3040+00 3060+00 3080+00

STATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES

MARCH 1978
Sheet 11 of 12 Sheets

60



LEGEND

- 500-YEAR FLOOD
- 100-YEAR FLOOD
- 50-YEAR FLOOD
- 10-YEAR FLOOD

RIVER MILES

62

BRIDGE FLOOR


LOW CHORD

COUNTY ROAD 1620

LUMBERTON, N. C.
CORPORATE LIMITS

CHIPPEWA STREET

BED



ELEVATIONS IN FEET ABOVE MOUTH

Corps of Engineers, U. S. Army
 Charleston, South Carolina, District
FLOOD PLAIN INFORMATION
LUMBER RIVER, N. C. & S. C.
HIGH WATER PROFILES

MARCH 1978

Sheet 12 of 12 Sheets

PLATE

ND