

AD-A151 033 PROPERTIES OF SYSTEMS WHICH LEAD TO EFFICIENT
COMPUTATION OF RELIABILITY. (U) NORTH CAROLINA UNIV AT
CHAPEL HILL CURRICULUM IN OPERATIONS R.
UNCLASSIFIED M O BALL ET AL. AUG 84 UNC/ORSA/TR-84/16 F/G 12/1

UNCLASSIFIED M O BALL ET AL. AUG 84 UNC/ORSA/TR-84/16


F/G 12/1

NL

END

FILM

01x



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A151 033

OPERATIONS RESEARCH AND SYSTEMS ANALYSIS

Properties of Systems which Lead to
Efficient Computation of Reliability


Michael O. Ball* and J. Scott Provan**

Technical Report No. UNC/ORSA/TR-84/16

August 1984

UNIVERSITY OF NORTH CAROLINA
AT CHAPEL HILL

Copy available to DTIC users 1984
without fully legible reproduction



Approved for public release;
distribution unlimited.

MAR 8 1985

DTIC FILE COPY

DISCLAIMER NOTICE

**THIS DOCUMENT IS BEST QUALITY
PRACTICABLE. THE COPY FURNISHED
TO DTIC CONTAINED A SIGNIFICANT
NUMBER OF PAGES WHICH DO NOT
REPRODUCE LEGIBLY.**

17	23	
	24	

This research was supported in part by the Air Force Office of Scientific Research under Contract AFOSR-84-0140. Reproduction in whole or in part is permitted for any purpose of the United States government.

Properties of Systems which Lead to Efficient Computation of Reliability

Michael O. Ball
College of Business and Management
University of Maryland
College Park, MD 20742

J. Scott Provan
Curriculum in Operations Research
and Systems Analysis
The University of North Carolina
Chapel Hill, NC 27514

ABSTRACT

One of the most widely used approaches to computing system reliability is to represent the system structure in terms of a Boolean sum of all minpaths. This expression is then transformed into a sum of disjoint terms. The probability of each term is then summed to obtain the reliability of the system. A key question with respect to the difficulty of this process relates to the ability to transform the initial sum into a sum of disjoint products. In this paper, we show that for the class of shellable systems, there always exists a disjoint product expression with a number of terms equal to the number of minpaths. We provide several examples of shellable systems for which such an expression can be efficiently found.

Introduction

In this paper we consider the property of shellability of a coherent system, and show how it can be used to compute or approximate reliability for these systems. In particular, we show how one can directly evaluate the disjoint products form for reliability by writing this expression as a shelling for the system. We also indicate how the property of shellability can help to construct good approximations to reliability when even the disjoint products method is too cumbersome. We present several applications for which the underlying system is shellable, and give examples to show the shelling.

1. Definitions and Notation

Consider a set N of n components. Each component i is subject to failure with probability p_i , and all components

*The work of this author was supported in part by the Air Force Office of Scientific Research under contract AFOSR-84-0140.

fail independently. A structure function ϕ is given which maps the n -vector $x = (x_1, \dots, x_n)$ of component indicators ($x_i = 1$ if component i operates, and 0 otherwise) into the system status ($\phi(x) = 1$ if the system operates and 0 otherwise). We assume that the function ϕ is coherent, that is, $\phi(0) = 0$, $\phi(1) = 1$ and ϕ is nondecreasing in each component. In this case, the function ϕ can be described completely by giving the set $\{T_1, \dots, T_r\}$ of minpaths, that is, T_i is a minimal set of components whose operation insures system operation. It follows that $\phi(x)$ equals 1 if and only if the set $\{j: x_j = 1\}$ of operating components contains at least one of the minpaths T_i . Thus the event of system operation can be described as the union of events (denoted by plus)

$$R_\phi = (\phi = 1) = A_1 + \dots + A_r$$

where A_i represents the event that all components of T_i operate. Unfortunately, one cannot immediately write the probability for this expression because the events are not disjoint. One of the ways to proceed is to write the above expression in disjoint products form, that is, as a union of mutually exclusive events

$$R_\phi = A_1 + \bar{A}_1 A_2 + \dots + \bar{A}_1 \bar{A}_2 \dots \bar{A}_{r-1} A_r$$

where product denotes intersection and bar denotes the complementary event. The probability of system operation can now be written as the sum of probabilities of the events

$$R_{\phi,i} = \bar{A}_1 \bar{A}_2 \dots \bar{A}_{i-1} A_i$$

and the problem is reduced to computing the probabilities of each of the $R_{\phi,i}$.

Many papers have dealt with effective use of the disjoint product form to compute system reliability (see [1],[2],[3],[6],[11],[12],[13],[16],[17]).

Unfortunately, computing $P_r(R_{\phi,1})$ can also be quite complex. What we would like to investigate in this paper are systems for which we can write the disjoint product in such a way that the terms $R_{\phi,1}$ can be computed directly as intersections of component events

$$R_{\phi,1} = X_{j_1} \dots X_{j_t} \bar{X}_{j_{t+1}} \dots \bar{X}_{j_k}$$

where X_j is the event that component j operates and $\bar{X}_j$ is the event that component j fails. This leads to the following definition.

Definition: A coherent system is shellable if there is an ordering $T_1, T_2, \dots, T_r$ of minpaths such that the event $R_{\phi,1}$ can be written as a disjoint product of component events. The corresponding expression for R_{ϕ} is called a shelling for the system.

It is clear that if a shelling can be obtained for a system, then the probability of system operation can be written immediately as the sum of the probabilities of the events $R_{\phi,1}$, which can be written in turn as a product of component probabilities:

$$P_r(R_{\phi,1}) = (1p_{j_1}) \dots (1p_{j_t}) p_{j_{t+1}} \dots p_{j_k}$$

by using the independence of component events.

Example: Consider the coherent system defined on component set $N = \{1, 2, 3, 4, 5\}$ which has the set of minpaths $\{123, 14, 24, 34\}$. (For simplicity, we will use the same notation for T_i and A_i .) This is not shellable in the order given, since the event $(1\bar{2}3)(14) = X_1 \bar{X}_2 X_3 \cdot X_1 X_2 \bar{X}_3 X_4$ cannot be written as a single disjoint product of component events. The ordering $\{14, 24, 34, 123\}$, however, is a shelling, for the system operation can now be written in disjoint product form

$$\begin{aligned} R_{\phi} = & (14) + (\bar{1}4)(24) + (\bar{1}4)(\bar{2}4)(34) \\ & + (\bar{1}4)(\bar{2}4)(\bar{3}4)(123) \\ = & X_1 X_4 + \bar{X}_1 X_2 X_4 + \bar{X}_1 \bar{X}_2 X_3 X_4 \\ & + X_1 X_2 \bar{X}_3 \bar{X}_4 \end{aligned}$$

The probability of system operation can be written directly as

$$\begin{aligned} P_r(R_{\phi}) = & (1p_1)(1p_4) + p_1(1p_2)(1p_4) \\ & + p_1 p_2 (1p_3)(1p_4) \\ & + (1p_1)(1p_2)(1p_3)p_4. \end{aligned}$$

There is a second way that shellability can aid in reliability computation, and this does not depend on knowing a specific shelling at all. It turns out that shellability provides combinatorial structure to a system which restricts the number of operating configurations (x such that $\phi(x) = 1$) with a given number of operating components. This makes it possible to obtain approximations to system reliability, under the assumption of equal component failure probabilities, which are considerably more accurate than those that can be obtained without having the property of shellability. Moreover, there are very efficient methods of obtaining these approximations, and so such approximation techniques are useful when the system is too complex to allow exact computation of reliability. The details of this procedure are somewhat involved, and the reader is urged to consult [5] and [14] for details.

Shellability, therefore, is a convenient property for a system to have, in terms of facilitating reliability computation. It is not a property held by all systems. Take, for example the four component coherent system whose minpaths are $\{12, 34\}$. Neither of the

events $(\bar{1}2)(34) = \bar{X}_1 X_2 X_3 X_4 + X_1 \bar{X}_2 X_3 X_4$ nor

$(\bar{3}4)(12) = X_1 X_2 \bar{X}_3 + X_1 X_2 X_3 \bar{X}_4$ can be

written as a single product of component events, and so this system is not shellable. There are, however, a large number of classic reliability problems, with important applications, for which the underlying system is shellable. For the remainder of this paper, we give examples of these systems, along with the appropriate shellings.

2. Matroid Systems

Matroids make up a class of coherent binary systems that have been studied extensively in a variety of contexts. In particular, they have been shown to be especially powerful (see [8], [9]) in characterizing combinatorial optimization problems for which efficient solution algorithms exist. Matroids are shellable ([15], Corollary 3.2.2) and thus provide a class of systems for which the properties described in Section 1 hold. In this section, we describe two important classes of systems that are matroids and that are of interest in the study of system reliability.

A. Graph Connectedness: Much of the study of system reliability has employed network models. One measure of system reliability used in the study of computer communications networks is

Pr [operating paths exist between all node pairs].

In the case where only arcs fail, the underlying coherent binary system is what is known as a graphic matroid. For the graph illustrated in Figure 1, the





Figure 1

minpaths are {124, 125, 134, 135, 145, 234, 245, 245}, representing the spanning trees in the graph. These produce the shelling


$$\begin{aligned} R_p &= 124 + (124)(125) + (124)(125)(134) \\ &\quad + (124)(125)(134)(135) \\ &\quad + (124)(125)(134)(135)(145) \\ &\quad + (124)(125)(134)(135)(145)(234) \\ &\quad + (124)(125)(134)(135)(145)(234)(235) \\ &\quad + (124)(125)(134)(135)(145)(234)(235)(245) \\ &= x_1 x_2 x_4 + x_1 x_2 x_4 x_5 + x_1 x_2 x_3 x_4 \\ &\quad + x_1 x_2 x_3 x_4 x_5 + x_1 x_2 x_3 x_4 x_5 + x_1 x_2 x_3 x_4 \\ &\quad + x_1 x_2 x_3 x_4 x_5 + x_1 x_2 x_3 x_4 x_5 \end{aligned}$$

This class of systems has been studied extensively, not only because of its importance from an application standpoint, but also because of the rich structure it contains.

B. Personnel Assignment Systems: We now discuss a second class of systems, which we believe has important practical applications. This system relates to the reliability of a personnel system. Figure 2 illustrates the problem. The left hand set of nodes corresponds to jobs critical to the survival of an operation. The right hand set of nodes corresponds to personnel. An arc is inserted between a right hand and left



operating state:



failed state (no way to cover both jobs a and b):



Figure 2: A personnel system

hand node if the job can be filled by the corresponding person. This model is, of course, the classic assignment model. In a reliability setting the components correspond to personnel. The failure of a person corresponds to that person being unable to work, and the system operates any time the set of operating persons can cover all the required jobs. Thus, the measure of system reliability is

Pr [the operating persons can cover all required jobs].

Note that given the set of failed persons, the determination of whether the system can operate is not completely straightforward. In fact, it involves the solution of an assignment problem.

This system is what is known as a transversal matroid. If there are n jobs, then minpaths consist of sets of n persons with the property that there exists a way of assigning those n persons to the n jobs. For the system of Figure 2, the minpaths are {12346, 12347, 12356, 12357, 12467, 12567, 13456, 13457, 14567, 23456, 23457, 24567}, and these produce shelling (in the order given)

$$\begin{aligned} R_p &= x_1 x_2 x_3 x_4 x_6 + x_1 x_2 x_3 x_4 x_7 \\ &\quad + x_1 x_2 x_3 x_4 x_5 x_6 + x_1 x_2 x_3 x_4 x_5 x_7 \\ &\quad + x_1 x_2 x_3 x_4 x_6 x_7 + x_1 x_2 x_3 x_4 x_5 x_6 x_7 \\ &\quad + x_1 x_2 x_3 x_4 x_5 x_6 + x_1 x_2 x_3 x_4 x_5 x_7 \\ &\quad + x_1 x_2 x_3 x_4 x_5 x_6 x_7 + x_1 x_2 x_3 x_4 x_5 x_6 \\ &\quad + x_1 x_2 x_3 x_4 x_5 x_6 x_7 + x_1 x_2 x_3 x_4 x_5 x_6 x_7 \end{aligned}$$

1. Linear Systems

A second broad category of shellable systems includes those systems which can be represented as linear systems. Specifically, suppose the components of a system correspond to real variables which are subject to some set of linear constraints (equalities or inequalities). Component failures correspond to setting the corresponding variables to zero, and the system then operates if the remaining variables can still take values which satisfy the constraints. We need to make a further assumption that the linear system is nondegenerate (in the linear programming sense), although the two examples given here will be nondegenerate. It can be shown ([7], Lemma 2.1) that these systems are shellable, and so the results of Section 1 apply.

A. Reachability: Suppose we are given a directed network G whose arcs are subject to failure. The system operates if the operating arcs admit directed paths from a given source node s to all other nodes of G . An example is given by the network in Figure 3. The linear representation




Figure 3

of this system is

$$y_1 + y_3 + y_4 = 1$$

$$y_2 + y_3 + y_5 = 1$$

$$y_4 + y_5 = 1$$

$$y_1 \geq 0, y_2 \geq 0, y_3 \geq 0, y_4 \geq 0, y_5 \geq 0$$

Since any solution which satisfies these constraints must have the property that the arcs corresponding to nonzero components admit paths from s to u , v , and w . One can check that the minpaths for this system are {124, 125, 134, 135} and these produce the shelling

$$\begin{aligned} R_s &= (124) + (\overline{124})(125) \\ &\quad + (\overline{124})(\overline{125})(134) \\ &\quad + (\overline{124})(\overline{125})(\overline{134})(135) \\ &= x_1 x_2 x_4 + x_1 x_2 \bar{x}_4 x_5 + x_1 \bar{x}_2 x_3 x_4 \\ &\quad + x_1 \bar{x}_2 x_3 \bar{x}_4 x_5 \end{aligned}$$

B. Transportation Problems: Here we are given a set of m_1 supply points with supply a_i available at supply point i , and m_2 demand points, with demand b_j required at demand point j . We assume that total supply equals total demand, but that no proper subset of supply and demand points can have supply equal to demand. Each link (i, j) between supply point i and demand point j is subject to failure, and the system operates if the operating links are sufficient to ship from available supplies to meet the demands. As an example we take the three supply, two demand system with $a_1=2, a_2=6, a_3=7, b_1=5$, and $b_2=10$. The linear representation of this system is

Component	1	2	3	4	5	6	
Link	(1,1)	(1,2)	(2,1)	(2,2)	(3,1)	(3,2)	
	$y_1 + y_2$						= 2
		$y_3 + y_4$					= 6
				$y_5 + y_6$			= 7
	y_1		y_3		y_5		= 5
		y_2		y_4		y_6	= 10
	$y_1 \geq 0$	$y_2 \geq 0$	$y_3 \geq 0$	$y_4 \geq 0$	$y_5 \geq 0$	$y_6 \geq 0$	

and the minpaths are {1346, 1456, 2346, 2356}. These produce the shelling

$$\begin{aligned} R_\phi &= (1346) + (\overline{1346})(1456) \\ &\quad + (\overline{1346})(\overline{1456})(2346) \\ &\quad + (\overline{1346})(\overline{1456})(\overline{2346})(2456) \\ &= x_1 x_3 x_4 x_6 + x_1 \bar{x}_3 x_4 x_5 x_6 + \bar{x}_1 x_2 x_3 x_4 x_6 \\ &\quad + \bar{x}_1 x_2 \bar{x}_3 x_4 x_5 x_6 \end{aligned}$$

Conclusion

We end the paper with a word on algorithms which find shellings for these systems, since good shelling algorithms will lead naturally to good algorithms for computing system reliability. Shelling algorithms do exist for the problems given here that run in time polynomial in the number of minpaths. Those for matroid complexes can be construed from [4], and those for linear systems from [7], Lemma 2.1. Neither of these papers, however, give direct shelling algorithms, and considerably more efficient algorithms can be obtained by considering the extra structure contained in the systems presented. These algorithms will be covered in a subsequent paper.

REFERENCES

1. J.A. Abraham, "An improved method for network reliability", IEEE Trans. Reliability, vol. R428, 1977 Apr., pp. 584-591.
2. K.K. Aggarwal, K.B. Misra, J.S. Gupta, "A fast algorithm for reliability evaluation", IEEE Trans. Reliability, vol. R424, 1975 Apr., pp. 834-85.
3. K.K. Aggarwal and S. Rai, "Reliability evaluation in computer communications networks", IEEE Trans. Reliability, vol. R430, 1981 Feb., pp. 324-35.
4. M.O. Ball and G.L. Nemhauser, "Matroids and a reliability analysis problem", Mathematics of Operations Research, vol. 4, 1979, pp. 132-143.
5. M.O. Ball and J.S. Provan, "Calculating bounds on reachability and connectedness in stochastic networks," Networks, vol. 13, 1983, pp. 253-273.
6. R.G. Bennetts, "On the analysis of fault trees", IEEE Trans. Reliability, vol. R424, 1975 Aug., pp. 175-185.
7. G. Baneraj and V. Klee, "Shellings of spheres and polytopes," Duke Math. J., vol. 41, 1974, pp. 443-451.
8. J. Edmonds, "Matroid partition", Mathematics of the Decision Sciences (Lectures in Applied Mathematics), Amer. Math. Soc., vol. 11, 1968, pp. 335-346.
9. J. Edmonds, "Matroids and the greedy algorithm", Math Programming, vol. 1, 1971, pp. 127-135.
10. S. Fratta and U.G. Montanari, "A Boolean algebra method for computing the terminal reliability in a communication network", IEEE Trans. Circuit Theory, vol. CT420, 1973 May, pp. 204-211.
11. H.M. Lin, B.J. Leon, T.C. Huang, "A new algorithm for symbolic system reliability analysis", IEEE Trans. Reliability, vol. R425, 1976 Apr., pp. 24-5.
12. M.O. Locks, "Recursive disjoint products, inclusion/exclusion and minimal approximations", IEEE Trans. Reliability, vol. R429, 1980 Dec., pp. 354-371.
13. M.O. Locks, "Recursive disjoint products: a review of three algorithms", IEEE Trans. Reliability, vol. R431, 1982 Apr., pp. 334-35.
14. J.S. Provan, "Approximating reliability in networks", to appear IEEE Trans. Rel.
15. J.S. Provan and L.J. Billera, "Decompositions of simplicial complexes related to diameters of convex polyhedra", Math. Oper. Res., vol. 5, 1980, pp. 579-594.
16. S. Rai, K.K. Aggarwal, "An efficient method for reliability evaluation of a general network", IEEE Trans. Reliability, vol. R427, 1978 Aug., pp. 206-211.
17. R.K. Tiwari, M. Verma, "An algebraic technique for reliability evaluation", IEEE Trans. Reliability, vol. R429, 1980 Oct., pp. 311-313.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS													
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited.													
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE															
4. PERFORMING ORGANIZATION REPORT NUMBER(S) UNC/ORSA/TR-84-16		5. MONITORING ORGANIZATION REPORT NUMBER(S) AFOSR-TR- 85 - 0105													
6a. NAME OF PERFORMING ORGANIZATION University of North Carolina	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION Air Force Office of Scientific Research													
6c. ADDRESS (City, State and ZIP Code) Curriculum in Operations Research & Systems Analysis, Smith Bldg 128A, Chapel Hill NC 27514		7b. ADDRESS (City, State and ZIP Code) Directorate of Mathematical & Information Sciences, Bolling AFB DC 20332-6448													
8a. NAME OF FUNDING/SPONSORING ORGANIZATION AFOSR	8b. OFFICE SYMBOL (If applicable) NM	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER AFOSR-84-0140													
8c. ADDRESS (City, State and ZIP Code) Bolling AFB DC 20332-6448		10. SOURCE OF FUNDING NOS. <table border="1"><tr><td>PROGRAM ELEMENT NO. 61102F</td><td>PROJECT NO. 2304</td><td>TASK NO. A5</td><td>WORK UNIT NO.</td></tr></table>		PROGRAM ELEMENT NO. 61102F	PROJECT NO. 2304	TASK NO. A5	WORK UNIT NO.								
PROGRAM ELEMENT NO. 61102F	PROJECT NO. 2304	TASK NO. A5	WORK UNIT NO.												
11. TITLE (Include Security Classification) PROPERTIES OF SYSTEMS WHICH LEAD TO EFFICIENT COMPUTATION OF RELIABILITY															
12. PERSONAL AUTHOR(S) J. Scott Provan and Michael O. Ball															
13a. TYPE OF REPORT Technical	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Yr., Mo., Day) AUG 84	15. PAGE COUNT 10												
16. SUPPLEMENTARY NOTATION															
17. COSATI CODES <table border="1"><tr><th>FIELD</th><th>GROUP</th><th>SUB. GR.</th></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr></table>		FIELD	GROUP	SUB. GR.										18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB. GR.													
19. ABSTRACT (Continue on reverse if necessary and identify by block number) One of the most widely used approaches to computing systems reliability is to represent the system structure in terms of a Boolean sum of all minpaths. This expression is then transformed into a sum of disjoint terms. The probability of each term is then summed to obtain the reliability of the system. A key question with respect to the difficulty of this process relates to the ability to transform the initial sum into a sum of disjoint products. In this paper, the authors show that for the class of <u>shellable</u> systems, there always exists a disjoint product expression with a number of terms equal to the number of minpaths. The authors provide several examples of shellable systems for which such an expression can be efficiently found.															
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT. ☐ DTIC USERS ☐		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED													
22a. NAME OF RESPONSIBLE INDIVIDUAL MAJ Brian W. Woodruff		22b. TELEPHONE NUMBER (Include Area Code) (202) 767- 5027	22c. OFFICE SYMBOL NM												

END

FILMED

4-85

DTIC