

AD-A151 711

RAYLEIGH CRITERIA RESOLUTION OF OPTICAL CORRELATIONS
(U) ARMY MISSILE COMMAND REDSTONE ARSENAL AL RESEARCH
DIRECTORATE D A GREGORY SEP 84 AMSMI/RR-84-10-TR

1/1

UNCLASSIFIED

SBI-AD-E950 661

F/G 17/8


NL



END

FILED

DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

ADE 950 661

(2)

AD-A151 711

TECHNICAL REPORT RR-84-10

RAYLEIGH CRITERIA RESOLUTION OF OPTICAL CORRELATIONS

Don A. Gregory
Research Directorate
US Army Missile Laboratory

SEPTEMBER 1984



U.S. ARMY MISSILE COMMAND

Redstone Arsenal, Alabama 35898

Approved for public release; distribution is unlimited.

DTIC FILE COPY

DTIC
ELECTE
MAR 21 1985
S B D

85 03 15 057

DISPOSITION INSTRUCTIONS

**WHEN THIS REPORT IS NO LONGER NEEDED, DEPARTMENT OF THE
ARMY ORGANIZATIONS WILL DESTROY IT IN ACCORDANCE WITH
THE PROCEDURES GIVEN IN AR 380-5.**

DISCLAIMER

**THE FINDINGS IN THIS REPORT ARE NOT TO BE CONSTRUED AS AN
OFFICIAL DEPARTMENT OF THE ARMY POSITION UNLESS SO DESIG-
NATED BY OTHER AUTHORIZED DOCUMENTS.**

TRADE NAMES

**USE OF TRADE NAMES OR MANUFACTURERS IN THIS REPORT DOES
NOT CONSTITUTE AN OFFICIAL INDORSEMENT OR APPROVAL OF
THE USE OF SUCH COMMERCIAL HARDWARE OR SOFTWARE.**

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)


REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER RR-84-10	2. GOVT ACCESSION NO. AD A151711	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Rayleigh Criteria Resolution of Optical Correlations		5. TYPE OF REPORT & PERIOD COVERED Technical
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Don H. Gregory A		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Commander, US Army Missile Command Attn: AMSMI-RR Redstone Arsenal, AL 35898-5248		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Commander, US Army Missile Command ATTN: AMSMI-RPT Redstone Arsenal, AL 35898-524]		12. REPORT DATE
		13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; unlimited distribution.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report describes an investigation into determining the resolvability between correlations produced by Fourier transform matched filters made of very similar scenes. Knowledge of this type is needed to accurately predict the total number of matched filters needed to completely identify a scene or object regardless of its rotational position. Similar experiments may be done for scale and tilt as the variable. This report introduces the Rayleigh criteria as the standard by which distinguishability may be measured in a Vander Lugt type optical recognition system.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

1

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)



SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

ACKNOWLEDGEMENT

The author wishes to acknowledge the able assistance of James C. Thompson, currently of Auburn University, for his developoment of the plotting routines used in this report.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



TABLE OF CONTENTS

	PAGE
I. INTRODUCTION.....	1
II. THEORY.....	2
III. EXPERIMENTAL RESULTS.....	4
IV. CONCLUSIONS.....	5

I. INTRODUCTION

Considerable interest has been generated in using Fourier transform matched filters for object discrimination and tracking. In order to recognize several objects or several orientations of the same object many matched filters may be needed. Interest has been shown in storing several of these filters in a small area [1,2]. This has been done by multiply exposing the photographic plate or by using arrays produced by holographic elements or other means [3,4]. Arguments are presented here which investigate how closely packed these filters can be and still have good resolution between them. In this instance close packing refers to double-exposing a photographic plate to an input scene at two slightly different rotation positions. Classic line-shapes are used to model examples of experimental results and some conclusions are drawn using the Rayleigh criteria as a guideline.

II. THEORY

The Gaussian intensity distribution has the form

$$I_1 = I_0 e^{-2r^2/w^2} \quad (1)$$

where r is the radius from the center of the distribution and $2w$ is the full line width at $I = (1/e^2)I_0$. If another distribution of the same form is located a small distance δ_1 away

$$I_2 = I_0 e^{-2(r-\delta_1)^2/w^2} \quad (2)$$

then the sum of these distributions is

$$I = I_1 + I_2 = I_0 \left[e^{-2r^2/w^2} + e^{-2(r-\delta_1)^2/w^2} \right] \quad (3)$$

Let

$$\rho_1 = \frac{I(r=0)}{I(r=\delta_1/2)} \quad (4)$$

Substituting from the above gives

$$\rho_1 = 1/2 \left(e^{\delta_1^2/2w^2} + e^{-3\delta_1^2/2w^2} \right) \quad (5)$$

ρ_1 is thus the ratio of the peak at $r = 0$ to the height of the valley between the two distributions. Solving for δ_1 using the fact that the second term is much smaller than the first gives

$$\delta_1 = w \left[2 \ln (2\rho) \right]^{1/2} . \quad (6)$$

Using the Rayleigh criteria as a rough guideline, $\rho_1 = 1.23$ and substituting this into Eq. (6) yields

$$\delta_1 = 1.34 w \quad . \quad (7)$$

The same sort of analysis may be applied to a Lorentzian distribution having the form

$$I = \frac{A}{r^2 + (\sigma/2)^2} + \frac{A}{(r-\delta_2)^2 + (\sigma/2)^2} \quad (8)$$

where A is a constant equal to $I_0(\sigma/2)^2$, r is the radius and σ the full linewidth at half the maximum intensity. This produces a δ_2 of

$$\delta_2 = \sigma/2 \left[4\rho_2 - 3 + \sqrt{16\rho_2(\rho_2-1)+1} \right]^{1/2} \quad (9)$$

Then for $\rho_2 = 1.23$ as a value of the intensity ratio

$$\delta_2 = 1.03 \sigma \quad . \quad (10)$$

For a sinc^2 distribution

$$I = I_0 \left(\frac{\sin \alpha r}{\alpha r} \right)^2 + I_0 \left[\frac{\sin \alpha (r-\delta_3)}{\alpha(r-\delta_3)} \right]^2 \quad (11)$$

where again r is the radius from the center of the distribution and

$$\alpha = \pi/r(o) \quad (12)$$

where $r(o)$ is the value of r at the first zero of intensity. This distribution yields

$$\rho_3 = \frac{\alpha^2 \delta_3^2 + \sin^2 \delta_3}{8 \sin^2 (\alpha \delta_3 / 2)} \quad (13)$$

which must be solved graphically or by iteration using $\rho_3 = 1.23$. For small values of δ_3 , note that $\alpha^2 \delta_3^2 \gg \sin^2 \delta_3$.

III. EXPERIMENTAL RESULTS

Figure 1 shows three distributions compared with experimental data taken using visible (Helium-Neon) real-time optical correlation methods. The input scene is fed via an RCA television camera (model number TC 1005) into a Videotek Monitor (model VM-12PR) which is used as the input to a Hughes liquid crystal light valve (the same one used in Ref. 4) which produces the coherent image that is fed into a real-time Vander Lugt type correlator. Experiments of this type are described in detail elsewhere [5]. All three distributions have been arbitrarily fit to experimental data at $r = 0$ and $r = 2.94^\circ$ using $w = 2.80^\circ$, $\sigma = 2.07^\circ$, and $\alpha = .775 \text{ deg}^{-1}$. This gives $\delta_1 = 3.8^\circ$, $\delta_2 = 2.13^\circ$, and $\delta_3 = 4.0^\circ$. Note that these widths should depend upon the spatial frequency of the input scene as well as other factors and thus serve only as examples here. In this particular experiment the input scene was a low resolution black and white aerial photograph of Huntsville, Alabama. The photograph was placed on a rotatable stage and matched filters made at the desired rotation angles. Experimental data in Figure 1 is the correlation intensity for a filter made at 0° rotation of the input scene. After development of the film plate (Kodak 649F) it was replaced in the correlator and the input scene rotated slowly as the corresponding correlation intensity was measured using an RCA CCD camera fed into a television monitor then digitized by a Colorado Video Analyzer (model 321). This signal was then recorded by a Hewlett-Packard model 680 strip chart recorder. Figure 2 is representative of actual data taken as the input scene was rotated through the position (0° rotation) where the matched filter was made.

In order to investigate multiply stored filters, a single plate was exposed twice with different rotation angles of the input scene. After development using standard techniques for Kodak 649F plates, the filter was reinserted into the correlator and data taken as before. Figure 3 shows the actual data and a plot of Equation 8 using the Rayleigh criteria. The exposures were made using the same criteria for δ_2 of 2.13° of scene rotation. The agreement is reasonably good. Some variation is expected due to the difficulty in obtaining equally intense correlations for the two filters. This depends upon the exposure times used, film response, and several other variables. In the theoretical analysis the calculations could easily have been done using distributions having different peak heights but then the value of δ would depend upon these heights which can't be known with any certainty in advance of doing the experiment. In the calculations presented, it was also assumed that individual correlation intensities should be added directly rather than adding the corresponding fields then squaring for the intensity. This has been justified experimentally by storing one filter made of 0° scene rotation and another filter at 90° scene rotation then adding the resulting correlation intensities algebraically. This distribution was then compared with data similar to Figure 3. The results were found to be essentially equal. This indicates that there is little if any phase addition contribution to the sum of the two correlation intensities.

IV. CONCLUSIONS

In this brief report a method of analyzing closely spaced optical matched filters has been presented along with experimental data which tends to support the findings. The use of the Rayleigh criteria may not be strictly correct in that this criteria is for a Bessel function intensity distribution only but it serves as an initial guideline [6]. Experimental data seems to suggest that the separation criteria will become more stringent as laboratory methods improve.




Figure 1. Correlation intensity vs angle of rotation of input scene




Figure 2. Correlation intensity as input scene was rotated through 0° where matched filter was made




Figure 3. Plot of Eq. (8) compared with actual data for two filters stored
2.13° of rotation apart.

References

1. P. Meuller, Appl. Opt., Vol. 8, No. 2, 1969 (297).
2. K. Lieb and J. Mendelsohn, Proc. SPIE, Vol. 317, 1981, (148).
3. K. Lieb, R. Bondurant, S. Hsiao, R. Wohlers, and R. Herold, Appl. Opt., Vol. 17, No. 18, 1978, (2892).
4. H. K. Liu and J. H. Duthie, Appl. Opt., Vol. 21, No. 18, 1982, (3278).
5. J. Smith, B. Guenther, and C. Christensen, J. Appl. Photo. Engr., Vol. 5, No. 4, 1979, (236).
6. E. Hecht and A. Zajac, Optics, Addison-Wesley, Reading, Massachusetts, 1974, p. 352.

DISTRIBUTION

	No. of Copies	of
Commander US Army Research Office ATTN: AMXRO-PH, Dr. R. Lontz P. O. Box 12211 Research Triangle Park, NC 27709	5	
US Army Research and Standardization Group (Europe) ATTN: AMXSN-E-RX, LTC D. R. Reinhard Box 65 FPO New York 09510	1	
Commander US Army Materiel Development and Readiness Command ATTN: Dr. James Bender Dr. Gordon Bushey 5001 Eisenhower Avenue Alexandria, VA 22333	1	
Headquarters, Department of the Army Office of the DCS for Research, Development & Acquisition ATTN: DAMA-ARZ Room 3A474, The Pentagon Washington, DC 20301	1	
OUSTR&E Room 3D1079, The Pentagon Washington, DC 20301	1	
Director Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, VA 22209	1	
OUSTR&E ATTN: Dr. G. Gamota Deputy Assistant for Research (Research in Advanced Technology) Room 3D1067, The Pentagon Washington, DC 20301	1	
Director of Defense Research and Engineering Engineering Technology Washington, DC 20301	1	

DISTRIBUTION - Continued

Director Defense Advanced Research Projects Agency/STO ATTN: Commander T. F. Weiner D. W. Walsh 1400 Wilson Boulevard Arlington, VA 22209	1 1
Commander US Army Aviation Systems Command 12th and Spruce Streets St. Louis, MO 63166	1
Director US Army Air Mobility Research & Development Laboratory Ames Research Center Moffett Field, CA 94035	1
Commander US Army Electronics Research & Development Command ATTN: AMSEL-TL-T, Dr. Jacobs DELEW-R, Henry E. Sonntag Fort Monmouth, NJ 07703	1 1
Director US Army Night Vision Laboratory ATTN: John Johnson John Deline Peter VanAtta Fort Belvoir, VA 22060	1 1 1
Commander US Army Picatinny Arsenal Dover, NJ 07801	1
Commander US Army Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783	1
Commander US Army Foreign Science and Technology Center ATTN: W. S. Alcott Federal Office Building 220 7th Street, NE Charlottesville, VA 22901	1
Commander US Army Training and Doctrine Command Fort Monroe, VA 22351	1

DISTRIBUTION - Continued

Director	
Ballistic Missile Defense Advanced Technology Center	
ATTN: ATC-D	1
ATC-O	1
ATC-R	1
ATC-T	1
P.O. Box 1500	
Huntsville, Al 35808	
Commander	
US Naval Air Systems Command	
Missile Guidance and Control Branch	1
Washington, DC 20360	
Chief of Naval Research	
Department of the Navy	1
Washington, DC 20301	
Commander	
US Naval Air Development Center	1
Warminster, PA 18974	
Commander, US Naval Ocean Systems Center	
Code 6003, Dr. Harper Whitehouse	1
San Diego, Ca 92152	
Director, Naval Research Laboratory	
ATTN: Dave Ringwolt	1
Code 5570, T. Gialborinzi	1
Washington, DC 20390	
Commander, Rome Air Development Center	
US Air Force	
ATTN: James Wasielewski, IRR	1
Griffiss Air Force Base, NY 13440	
Commander, US Air Force, AFORSR/NE	
ATTN: Dr. J. A. Neff	1
Building 410, Bolling Air Force Base	
Washington, DC 20332	
Commander, US Air Force Avionics Laboratory	
ATTN: D. Rees	1
W. Schoonover	1
Dr. E. Champaign	1
Dr. J. Ryles	1
Gale Urban	1
David L. Flannery	1
Wright Patterson Air Force Base, OH 45433	

DISTRIBUTION - Continued

Director

Defense Advanced Research Projects Agency/STO

ATTN: Commander T. F. Weiner

1

D. W. Waish

1

1400 Wilson Boulevard

Arlington, VA 22209

Commander

US Army Aviation Systems Command

1

12th and Spruce Streets

St. Louis, MO 63166

Director

US Army Air Mobility Research & Development Laboratory

Ames Research Center

1

Moffett Field, CA 94035

Commander

US Army Electronics Research & Development Command

ATTN: AMSEL-TL-T, Dr. Jacobs

1

DELEW-R, Henry E. Sonntag

1

Fort Monmouth, NJ 07703

Director

US Army Night Vision Laboratory

ATTN: John Johnson

1

John Deline

1

Peter VanAtta

1

Fort Belvoir, VA 22060

Commander

US Army Picatinny Arsenal

1

Dover, NJ 07801

Commander

US Army Harry Diamond Laboratories

1

2800 Powder Mill Road

Adelphi, MD 20783

Commander

US Army Foreign Science and Technology Center

ATTN: W. S. Alcott

1

Federal Office Building

220 7th Street, NE

Charlottesville, VA 22901

Commander

US Army Training and Doctrine Command

1

Fort Monroe, VA 22351

DISTRIBUTION - Concluded

Professor Anil K. Jain
Department of Electrical Engineering 1
University of California, Davis
Davis, CA 95616

Terry Turpin
Department of Defense
9800 Savage Road
Fort George G. Meade, MD 20755 1

Dr. Stuart A. Collins
Electrical Engineering Department
Ohio State Univeristy 1
1320 Kennear Road
Columbus, OH 43212

US Army Materiel Systems Analysis Activity
ATTN: AMXSY-MP
Aberdeen Proving Ground, MD 21005 1

US Army Night Vision Laboratory
ATTN: DELNV-L, Dr. R. Buser 1
Ft. Belvoir, VA 22060

Dr. F. T. S. Yu
Penn State Univeristy
Department of Electrical Engineering 1
University Park, PA 16802

Dr. William P. Bleha
Liquid Crystal Light Valve Devices 1
Hughes Aircraft Company
6155 El Camino
Carlsbad, CA 92008

AMCPM-PE-E, John Pettitt 1
-PE 1

AMSMI-LP, Mr. Voigt 1
-O 1
-Y 1
-R, Dr. McCorkle 1
-R, Dr. Rhoades 1
-RN, Jerry Hagood 1
-RE, W. Pittman 1
-RD 1
-RG, J. A. McLean 1
-RR, Dr. R. L. Hartman 1
Dr. J. S. Bennett 1
Dr. J. G. Duthie 1
Dr. D. A. Gregory 80

-RRR 5
-RPT 1

DISTRIBUTION - Continued

Commander, AFATL/LMT ATTN: Charles Warren Eglin Air Force Base, FL 32544	1
Environmental Research Institute of Michigan Radar and Optics Division ATTN: Dr. A. Kozma Dr. C. C. Aleksoff Juris Upatnieks P. O. Box 8618 Ann Arbor, MI 41807	1 1 1
IIT Research Institute ATTN: GACIAC 10 West 35th Street Chicago, IL 60616	1
Dr. J. G. Castle 9801 San Gabriel, NE Albuquerque, NM 87111	1
Commander, Center for Naval Analyses ATTN: Document Control 1401 Wilson Boulevard Arlington, VA 22209	1
Dr. J. W. Goodman Information Systems Laboratory Department of Electrical Engineering Stanford University Stanford, CA 04305	1
Eric G. Johnson, Jr. National Bureau of Standards 325 S. Broadway Boulder, CO 80302	1
Dr. Nicholas George The Institute of Optics University of Rochester Rochester, NY 14627	1
Naval Avionics Facility Indianapolis, IN 46218	1
Dr. David Cassasent Carnegie Mellon University Hamerschage Hall, Room 106 Pittsburg, PA 15213	1

END

FILMED

4-85

DTIC