

December 1984

LIDS-P-1426

AD-A151 984

ON THE THROUGHPUT OF CHANNEL ACCESS ALGORITHMS
WITH LIMITED SENSING*

by

Pierre A. Humblet**

ABSTRACT

→ This document
We consider access protocols for Aloha type multiaccess channels.
It is
We argue, and show in an important case, that they can be modified to allow new transmitters to join the system at arbitrary times. This feature, known as "limited sensing" or "free entry", does not reduce throughput performances. In the case presented, the modified algorithm is also robust with respect to feedback errors.

Additional keywords: Naval research.

This document has been approved for public release and sale; its distribution is unlimited.

DTIC
ELECTE
MAR 26 1985
S D E

*This research was conducted at the M.I.T. Laboratory for Information and Decision Systems with partial support provided by the National Science Foundation under Grant NSF-ECS-8310698 and by the Defense Advanced Research Projects Agency under Contract ONR/N00014-84-K-0357.

**Room No. 35-203, Laboratory for Information and Decision Systems, Massachusetts Institute of Technology, 77 Massachusetts Avenue, Cambridge, MA 02139.

This paper has been submitted for possible presentation at the 1984 IEEE Symposium on Information Theory.

85 01 29 005

DTIC FILE COPY

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO. AD-A151984	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) ON THE THROUGHPUT OF CHANNEL ACCESS ALGORITHMS WITH LIMITED SENSING		5. TYPE OF REPORT & PERIOD COVERED Paper
7. AUTHOR(s) Pierre A. Humblet		6. PERFORMING ORG. REPORT NUMBER LIDS-P-1426
9. PERFORMING ORGANIZATION NAME AND ADDRESS Massachusetts Institute of Technology Laboratory for Information and Decision Systems Cambridge, Massachusetts 02139		8. CONTRACT OR GRANT NUMBER(s) DARPA Order No. 3045/2-2-84 Amendment #11 ONR/N00014-84-K-0357
11. CONTROLLING OFFICE NAME AND ADDRESS Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, Virginia 22209		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Code No. 5T10 ONR Identifying No. 049-383
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Office of Naval Research Information Systems Program Code 437 Arlington, Virginia 22217		12. REPORT DATE December 1984
		13. NUMBER OF PAGES 3
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)		
This document has been approved for public release and sale; its distribution is unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) We consider access protocols for Aloha type multiaccess channels. We argue, and show in an important case, that they can be modified to allow new transmitters to join the system at arbitrary times. This feature, known as "limited sensing" or "free entry", does not reduce throughput performances. In the case presented, the modified algorithm is also robust with respect to feedback errors.		

December 3, 1984
revised 1/16/85

ON THE THROUGHPUT OF CHANNEL ACCESS ALGORITHMS WITH LIMITED
SENSING

Pierre A. Humblet

Laboratory for Information and Decision Systems

Massachusetts Institute of Technology

ABSTRACT

We consider access protocols for Aloha type multiaccess channels. We argue, and show in an important case, that they can be modified to allow new transmitters to join the system at arbitrary times. This feature, known as "limited sensing" need not reduce throughput performances. In the case presented, the modified algorithm is also robust with respect to feedback errors.

EXTENDED ABSTRACT

We consider the classical Aloha type multiaccess channel where packets are generated at a large number of sites and are eventually transmitted on a common channel. Overlapping transmissions result in a collision and all the packets involved must be retransmitted. Transmitters monitor the activity on the channel and obtain some type of feedback information, depending on the precise model at hand.

The problem is to design protocols that exploit feedback information to schedule transmissions so as to maximize the achievable throughput and/or cause little average delay for a given throughput. The algorithms with the best performances require all transmitters to monitor the channel at all times. Some attention has also been devoted to channels with "limited sensing" where a transmitter only monitors the channel while it has a packet ready for transmission. The words "free access" are used to denote "limited sensing" algorithms where a packet MUST be transmitted immediately following its generation.

"Limited sensing" algorithms have practical advantages over algorithms that require continuous observations. The "Free access" characteristics on the other hand does not seem to be as important, except that it guarantees minimum delay in very light traffic. All the "limited sensing" algorithms described previously exhibit achievable throughputs lower than those achievable by algorithms monitoring the channel continuously [Tsybakov, Vvedenskaya], [Mathys], [Georgiadis, Papantoni-Kazakos].


This situation is rather unexpected ! As there is no requirement that delay be kept small, a transmitter can listen to the channel for a long time before transmitting a generated packet. Doing so should put it in a "state of synchronization" close to what it would have had by listening to the channel since the beginning of operations.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	<i>per</i>
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
<i>A-1</i>	



We cannot show at this time that in general limited sensing does not reduce achievable throughput. We will only illustrate our contention for the slotted channel with ternary feedback. There packets are only transmitted in predefined slots and transmitters can learn immediately whether zero, one, or more than one transmissions took place in a slot.

The best known algorithms for that channel are variations of Gallager's algorithm. For our purpose we view them as having three phases of operation, as illustrated in the figure below. There letters label the channel outcomes associated with phase transitions.



In phase I the algorithm allows transmissions from a set T of transmitters for which only a priori statistical information is available. It immediately returns to phase I (choosing another set) if no collision occurs, else it moves to phase C. In that phase set T is partitioned into subsets L and R , and only transmissions from L are allowed. An outcome of idle means that R must contain at least two active transmitters. The algorithm abandons L , partitions R and continues in phase C. A collision outcome for L implies (under Poisson statistics assumption) that only a priori information is known about transmitters in R . The algorithm partitions L and remains in phase C. After a success in phase C the algorithm moves to phase S where transmissions from R are allowed. The next phase is C or I, depending on the outcome, which cannot be "idle".

It has long been recognized that the phase of the algorithm can sometimes be determined by observing the transmission outcomes. After hearing a collision on the channel one can immediately conclude that the algorithm is in phase C. Similarly a success followed by another success or by an idle unambiguously signals a return to I. Only long strings of idles cause ambiguity as they can occur both in the I and C phases.

We suggest modifying the algorithm to force a collision after $n-1$ idles in phase C (for some $n > 1$) by allowing transmissions from the entirety of set R (a similar method has been proposed [Ryder] to recover from some feedback errors). This modification guarantees that new listeners will be "in phase" within at most n slots, while reducing the achievable throughput by occasionally wasting a slot. This throughput reduction vanishes exponentially fast with increasing n . As a side effect of the modification, the algorithm that we propose below is also robust with respect to feedback errors that can cause Gallager's algorithm to deadlock. In the case $n = 2$, no effective distinction is made between the outcomes of "idle" and "success", so that the algorithm only requires binary feedback [Mehravari, Berger].

Now that we can synchronize new listeners, it is a simple matter to make limited sensing work. We will allow "new" transmitters to transmit only when the algorithm is in the I phase and we will let transmissions be essentially Last In First Out, as in many protocols with limited sensing. Thus "old" transmitters, which have more information, defer to "new" transmitters in such a way that the properties of the original algorithm are preserved. Imagine that an observer watching the channel since the beginning of operations has iteratively produced the following picture of the time axis:

```

xxxxxxxx.....xxxxx....RRRL.....xxxxLLLLxxxxxxx...ssss      - time
0                                                                    !
                                                                    current time

```

packets generated in ssss are synchronizing (with a priori stat.)
 " " " are synchronized (still with a priori stat.)
 " " " LLLLL form the L subset (phase C)
 " " " RRRRR form the R subset (phases C and S)
 " " " xxxxx have been successfully transmitted

(The sets LL and RR appear above in keeping with the Last In First Out spirit. This feature is by no means necessary.)

As transmissions take place current time is advanced. The sss set is extended to the right, while its left part is possibly updated into The LLL set is updated into xxx (upon idle or success) or split into LL and RR (upon collision). The RRR set is returned to (upon collision) or split into TT and RR (upon idle). When the algorithm reaches the I phase a new set T is selected from the set, starting at the left boundary of the updated ssss set, in an Last In First Out fashion. For example if the LL and RR sets in the previous figure each contained one transmitter, the new figure might be

```

xxxxxxxx.....xxxxx.....xxxx.TxxxxxxxxxxxxxxxxTTTTTTTTs      - time
0                                                                    !
                                                                    current time

```

Observers that have joined the channel at some time can recreate the part of the previous picture to the right of their arrival time, so that in particular transmitters can decide to what set they belong and if they must transmit.

Conclusions about achievable throughputs and delays can readily be obtained from existing results on the original algorithms.

We believe that existing access algorithms for other types of feedback can be similarly transformed to use limited sensing only, while degrading achievable throughput by arbitrarily small amounts, at the expense of some extra delay.