

AD-A162 962	INFLUENCE OF MUZZLE BRAKES UPON THE TRAJECTORY OF FIN-STABILIZED PROJECTILES(U) ARMY BALLISTIC RESEARCH LAB ABERDEEN PROVING GROUND MD E M SCHMIDT ET AL.
UNCLASSIFIED	DEC 85 BRL-MR-3483 F/G 19/4

INFLUENCE OF MUZZLE BRAKES UPON THE TRAJECTORY OF
FIN-STABILIZED PROJECTILES(U) ARMY BALLISTIC RESEARCH
LAB ABERDEEN PROVING GROUND MD E M SCHMIDT ET AL.
DEC 85 BRL-MR-3483 F/G 19/4

141


UNCLASSIFIED

F/G 19/4

ML

END

FILMED



NATIONAL BUREAU OF STANDARDS
MICROCOPY RESOLUTION TEST CHART

12

AD-A162 962

AD



US ARMY
MATERIEL
COMMAND

MEMORANDUM REPORT BRL-MR-3483

INFLUENCE OF MUZZLE BRAKES
UPON THE TRAJECTORY OF
FIN-STABILIZED PROJECTILES

Edward M. Schmidt
Fred J. Brandon
Sharon C. Pearson

December 1985

DTIC
SELECTE
DEC 27 1985

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

US ARMY BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

COPY FILE COPY

Destroy this report when it is no longer needed.
Do not return it to the originator.

Additional copies of this report may be obtained
from the National Technical Information Service,
U. S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as an official
Department of the Army position, unless so designated by other
authorized documents.

The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Memorandum Report BRL-MR- 3483	2. GOVT ACCESSION NO. AD-A162962	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Influence of Muzzle Brakes Upon the Trajectory of Fin-Stabilized Projectiles		5. TYPE OF REPORT & PERIOD COVERED Final
7. AUTHOR(s) Edward M. Schmidt, Fred J. Brandon, Sharon C. Pearson		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Ballistic Research Laboratory ATTN: SLCBR-LF Aberdeen Proving Ground, MD 21005-5066		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD 21005-5066		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS RDT&E 1L162618AH80
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE December 1985
		13. NUMBER OF PAGES 23
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for Public Release; Distribution Unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Muzzle Brake Muzzle Blast Sabot Discard		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The dispersion of groups of fin-stabilized projectiles fired from high velocity cannon was measured for cases with and without a muzzle brake in place. The data clearly show degradation in precision due to the presence of the device. Diagnostic experiments and analyses were performed which indicate that the difficulties arise mainly due to gasdynamic loads within the muzzle device influencing both the projectile motion and sabot discard. Muzzle device design modifications are suggested to solve the problems. —		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

TABLE OF CONTENTS

	<u>Page</u>
LIST OF ILLUSTRATIONS.....	5
I. INTRODUCTION.....	7
II. GASDYNAMIC INTERACTIONS.....	8
III. MUZZLE BRAKE DESIGN FOR PRECISION.....	10
IV. SUMMARY.....	11
REFERENCES.....	17
DISTRIBUTION LIST.....	19

Accession For		
NTIS GRA&I	☒	
DTIC TAB	☐	
Unannounced	☐	
Justification		
By		
Distribution/		
Availability Codes		
Dist	Avail and/or	Special
A-1		



LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
1. Schematic of Triple Baffle Brake.	12
2. Dispersion Patterns (in arbitrary units) for Cases with Bare Muzzle and Triple Baffle Brake	12
3. Schematic of Test Round	13
4. Average Position of Sabot Components Relative to the Projectile for Cases With and Without Triple Baffle Brake in Place.	13
a. $x = 0.5$ m	13
b. $x = 2.0$ m	13
c. $x = 3.8$ m	13
d. $x = 5.6$ m	13
5. Bare Muzzle Sabot Discard	14
a. Vertical Plane Discard	14
b. Sabot Component Pitch Angle	14
6. Sabot Discard with Brake.	14
a. Vertical Plane Discard	14
b. Sabot Component Pitch Angle	14
7. Dispersion Patterns (in arbitrary units) with Bare Muzzle and Single Baffle Brake	15
8. Schematic of Typical Low Disturbance Brake.	15

I. INTRODUCTION

The use of large caliber, high velocity cannon on lightweight vehicles is currently being considered to meet the firepower and mobility needs of light forces in a number of the world's armies. To mount these cannon on the host vehicle, it is often necessary to reduce recoil loads. A classical technique to do this is through the use of a muzzle brake. These devices (Figure 1) use baffles or turning vanes to recover momentum from the propellant exhaust gases. Typically, a well-designed brake can reduce the total recoil impulse imparted to the gun by 20-30%.^{1 2} However, the incorporation of such devices on a gun tube can change the launch dynamics of the system. In the present report, the influence of a muzzle brake upon the dispersion of a cannon firing a fin-stabilized, high velocity projectile is examined. The source of disturbance is identified through a series of tests. Finally, techniques are suggested to reduce launch interactions.

The placement of a recoil brake on the muzzle of a gun tube can introduce a number of perturbations to the launch cycle. For large caliber weapons, muzzle devices are generally quite massive. This added mass changes the static flexure of the tube, alters the tube vibrations in fire-on-the-move, and influences the tube and projectile dynamics during the firing event. The presence of baffles near the projectile or sabot component flight paths can lead to mechanical interactions. One feature common to all muzzle brakes is the three-dimensional nature of their geometry. In order to attach the baffles to the gun tube, a set of cowl plates are used. For tank guns, these cowls serve an additional function. By directing the exhaust plume in the horizontal direction, scouring of ground material by the high velocity flow is limited and obscuration reduced. The geometry of the muzzle hardware produces a three-dimensional propellant gas flow within and external to the device. In turn, this flow can interact with the projectile as it passes through the muzzle region.

The magnitude of launch disturbance induced by a muzzle brake is illustrated by the dispersion patterns obtained for two series of firings of ten rounds from a high velocity cannon (Figure 2). For the bare muzzle case, the dispersion meets the specifications (nominally set to unity in arbitrary units); however, when the muzzle device is in place, the dispersion triples. In these tests, the muzzle brake was a three-baffle design (Figure 1). The projectile was fin-stabilized and launched with a single ramp sabot (Figure 3). The cannon was a heavy-walled Mann barrel; thus, it would be expected that the influence of brake mass would be minimal. To test this hypothesis, an equivalent, gasdynamically benign mass was used in place of the muzzle brake and the firings repeated. The resulting shot group returned to specifications. Apparently, the source of the launch perturbation is the enhanced gasdynamic loadings within the brake. For the remainder of the report, experimental and analytic efforts to examine the effect will be considered.

-
1. K. Oswatitsch, "Flow Research to Improve the Efficiency of Muzzle Brakes," R 6601, Kaiser Wilhelm Institute for Flow Research, Goettingen, Germany, July 1943.
 2. F. Smith, "Model Experiments on Muzzle Brakes," R 2/66, RARDE, Ft. Halstead, UK, June 1966.

II. GASDYNAMIC INTERACTIONS

The flow within the muzzle device (Figure 1) has quadrilateral symmetry about the horizontal and vertical planes. It would be expected that venting through the lateral openings would produce a rapid pressure decrease in the horizontal direction. While vertically, the confinement provided by the closed cowls would maintain high pressures on the upper and lower surfaces. For some muzzle brake configurations, the strong circumferential pressure gradients within the device have been reported³ to be sufficient to damage projectile fins. This was not observed in the present tests. When the flow impinges upon baffle surfaces, strong shock waves are generated which propagate in toward the axis. As the round moves through the brake, there are two major categories of gasdynamic interaction that may be envisioned: first, the high velocity, reverse flow may impart a transverse velocity to the round⁴ and, second, the sabot discard process may be altered in a manner which enhances interference.⁵ At present, techniques to compute the details of this type of three-dimensional, unsteady, internal flow are only just becoming available⁶ and are not capable of estimating interaction with the projectile and sabot components. To treat the present problem, a combined analytical/experimental approach is taken.

Linear theory has been used to estimate the effect of muzzle gasdynamic loads upon the trajectory of fin-stabilized projectiles.⁴ Basically, the flow is approximated to be quasi-steady and the fins are taken to be the dominant aerodynamic surfaces. The technique has been shown to correctly depict the magnitude of enhanced loads within a circular channel placed on the muzzle of a gun launching a flechette round. In the present application, an identical approach is taken to estimate the contribution to dispersion of enhanced fin loads within the muzzle brake. The pertinent gun tube exit conditions are:

$$M_e = 2.1$$

$$P_e = 58 \text{ MPa}$$

$$T_e = 1190 \text{ K}$$

The equivalent expansion ratio into the muzzle device (accounting for venting) is $A_c/A_e = 3.5$, which yields for the channel flow:

-
3. L. MacAllister, Private Communication, BRL, APG, MD, April 1984.
 4. E.M. Schmidt, K.S. Fansler, and D.D. Shear, "Dispersion of Fin-Stabilized Projectiles: Launch Gasdynamics," 2d International Symposium on Ballistics, ADPA, Alexandria, VA, March 1976.
 5. E.M. Schmidt and D.D. Shear, "Aerodynamic Interference during Sabot Discard," *Journal of Spacecraft and Rockets*, Vol. 15, No. 3, AIAA, New York, NY, May-June 1978, pp. 162-167.
 6. J.C. Buell and G.F. Widhopf, "Three-Dimensional Simulation of Muzzle Brake Flowfields," Paper No. 84-1641, AIAA, New York, NY, June 1984.

$$M_c = 3.15$$

$$P_c = 9.5 \text{ MPa}$$

$$T_c = 810 \text{ K}$$

and the relative Mach number over the projectile is

$$M_r = 0.6$$

Using the distribution in projectile angle of attack at separation from the gun,⁷ the increase in dispersion may be estimated. Based upon the units of Figure 2, this increase is 0.4, a number significantly lower than actually observed.

To examine the influence of internal gasdynamics upon the subsequent sabot discard, an experiment was conducted using a set-up similar to that described previously.⁵ Six orthogonal x-ray stations were positioned over the first 9.0 m of the trajectory to observe the discard process and initial projectile dynamics. The projectile then enters the BRL Transonic Range⁸ where free flight motion is measured for a distance of 206 m. Six full data rounds were fired: three with the triple baffle brake in place and three with a bare muzzle.

A comparison of the mean sabot discard trajectories is presented in Figure 4. The figures in this sequence present the relative locations of the sabot and projectile averaged over all sabot components and data rounds for each muzzle configuration. It is apparent that the presence of the brake acts to retard sabot discard. At the first x-ray station, the sabot for the bare muzzle case has pitched cleanly up and off the projectile. While at the same location, the sabot for the muzzle brake case still remains essentially in the assembled position. By the second station, both cases show the sabot clearing the projectile with the brake case being closer. This behavior is maintained throughout the discard. While the discard is obviously retarded by the presence of the brake, there does not appear to be a sufficiently drastic alteration in the dynamics to explain the observed dispersion growth. Examination of the details of individual discard sequences produces a more valuable correlation.

Data for the discard process with the bare muzzle are presented in Figure 5. The sequence (Figure 5a) is similar to the mean data. In this case, the trajectories of two opposing components are plotted for each x-ray station. The discard is clean and reasonably symmetric. Once a sabot component clears the projectile, it does not reimpinge. Comparison of the pitch angles relative to the projectile for all four sabot components reinforces the symmetry

7. P. Plostins, "Launch Dynamics of APFSDS Ammunition," 8th International Symposium on Ballistics, ADPA, Alexandria, VA, October 1984.

8. W.K. Rogers, "The Transonic Free Flight Range," U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, BRL Report 849, February 1953 (AD 13358).

argument (Figure 5b).

With the muzzle brake in place, there is a change in the discard (Figure 6). The sequence (Figure 6a) shows the position of the sabot components in the vertical plane at stations 2, 3, and 4. After first moving laterally, the bottom component rotates and reimpinges on the projectile. The impact is asymmetric in that the upper component does not touch. This type of mechanical impact is a significant source of perturbation⁹ which can lead to subsequent aerodynamic asymmetries in discard. The rear ramp of the sabot is configured in a manner that the reverse flow within the muzzle brake will tend to hold the components in the assembled position. This neutralizes any initial lateral motion imparted to the sabot components due to elastic decompression upon release from the gun tube and changes the overall discard process. The distribution in pitch angles of the sabot components for a discard with the muzzle brake (Figure 6b) shows that there are significant differences between the various components. Such geometric asymmetries produce aerodynamic asymmetry which can further perturb the flight path. The combination of impact of the sabot components with the projectile and subsequent aerodynamic interference may be sufficient to explain the observed growth in the dispersion of the system when the muzzle device is in place. To minimize the influence of the muzzle brake, it is necessary to consider the gasdynamic as well as the mechanical interactions that may occur.

III. MUZZLE BRAKE DESIGN FOR PRECISION

Reduction of muzzle brake induced gasdynamic interactions requires designs which minimize asymmetry, thus decreasing the magnitude of interactions. Further, the overall length of the device should be constrained, thereby, reducing the duration of interactions. For the existing brake, the latter concept was easily tested. The length of the brake (and its efficiency) was decreased by cutting off the outer two baffles producing the dispersion pattern (for a ten round group) illustrated in Figure 7. Obviously, the dispersion is closer to the specified value; however, the efficiency of the brake has decreased from a value of 14% for the triple baffle design to 7% for the single baffle case.

In order to restore efficiency, a larger single baffle brake has been designed (Figure 8) with an estimated efficiency of 23%. The design attempts to minimize any gasdynamic interactions along the axis by providing a "quasi-symmetric" initial expansion. Horizontally, the propellant gas exhausts through the vents. Vertically, the device provides an initial turning angle which is 90° , or the same as in the horizontal direction. The cowl is shaped in a fashion which prevents the shock generated off the surface from reaching the axis. The baffle is flat (although a chamfered baffle could provide higher efficiency and perhaps enhanced strength). The projectile hole is cut with an angle of the core flow from an undisturbed exhaust jet. While it is recognized that a normal shock will form on the baffle, the turning angle through the projectile hole will develop an expansion which should weaken the

9. E.M. Schmidt, "Disturbance to the Launch of Fin-Stabilized Projectiles," *Journal of Spacecraft and Rockets*, Vol 19, No. 1, AIAA, New York, NY, Jan-Feb 82, pp. 30-35.

shock. The resulting brake is similar to devices which may be observed on vehicles parked in a number of ordnance museums around the world; however, in this case, it has been designed with the sabot projectile as the prime motivator. At present, the device has not been fabricated or tested.

IV. SUMMARY

Data are presented which demonstrate that the use of muzzle brake on high velocity cannon can interfere with the launch of fin-stabilized ammunition. In particular, it appears that the interaction is associated with enhancement of muzzle gasdynamic loads within the brake. Analysis tends to support the alteration of sabot discard dynamics as the major source of perturbation. Techniques are presented for the design of muzzle brakes with acceptable level of efficiency which do not significantly degrade precision.




Figure 1. Schematic of Triple Baffle Brake




Figure 2. Dispersion Patterns (in arbitrary units) for Cases with Bare Muzzle and Triple Baffle Brake

4 SEGMENT, SINGLE RAMP




Figure 3. Schematic of Test Round






Figure 4. Average Position of Sabot Components Relative to the Projectile for Cases With and Without Triple Baffle Brake in Place




a. Vertical Plane Discard




b. Sabot Component Pitch Angle

Figure 5. Bare Muzzle Sabot Discard



a. Vertical Plane Discard



b. Sabot Component Pitch Angle

Figure 6. Sabot Discard with Brake




Figure 7. Dispersion Patterns (in arbitrary units) with Bare Muzzle and Single Baffle Brake




Figure 8. Schematic of Typical Low Disturbance Brake

REFERENCES

1. K. Oswatitsch, "Flow Research to Improve the Efficiency of Muzzle Brakes," R 6601, Kaiser Wilhelm Institute for Flow Research, Goettingen, Germany, July 1943.
2. F. Smith, "Model Experiments on Muzzle Brakes," R 2/66, RARDE, Ft. Halstead, UK, June 1966.
3. L. MacAllister, Private Communication, BRL, APG, MD, April 1984.
4. E.M. Schmidt, K.S. Fansler, and D.D. Shear, "Dispersion of Fin-Stabilized Projectiles: Launch Gasdynamics," 2d International Symposium on Ballistics, ADPA, Alexandria, VA, March 1976.
5. E.M. Schmidt, and D.D. Shear, "Aerodynamic Interference during Sabot Discard," Journal of Spacecraft and Rockets, Vol. 15, No. 3, AIAA, New York, NY, May-June 1978, pp. 162-167.
6. J.C. Buell, and G.F. Widhopf, "Three-Dimensional Simulation of Muzzle Brake Flowfields," Paper No. 84-1641, AIAA, New York, NY, June 1984.
7. P. Plostins, "Launch Dynamics of APFSDS Ammunition," 8th International Symposium on Ballistics, ADPA, Alexandria, VA, October 1984.
8. W.K. Rogers, "The Transonic Free Flight Range," US Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, Report 849, February 1953 (AD 13358).
9. E.M. Schmidt, "Disturbance to the Launch of Fin-Stabilized Projectiles," Journal of Spacecraft and Rockets, Vol. 19, No. 1, AIAA, New York, NY, Jan-Feb 1982, pp. 30-35.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	1	Commander US Army Communications - Electronics Command ATTN: AMSEL-ED Fort Monmouth, NJ 07703
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001	1	Commander, U.S. Army Missile Command Research, Development & Engineering Center, ATTN: AMSMI-RD Redstone Arsenal, AL 35898
1	Commander US Army Materiel Command ATTN: AMCLDC 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Missile Command ATTN: AMSMI-RBL Redstone Arsenal, AL 35898
1	HQDA DAMA-ART-M Washington, DC 20310	1	Commander US Army Missile Command ATTN: AMSMI-TLH Redstone Arsenal, AL 35898
2	Commander US Army Aviation Research and Development Command ATTN: Tech Dir AMSAV-E 4300 Goodfellow Boulevard St. Louis, MO 63120	1	Commander US Army Missile Command ATTN: AMSMI-RDK Redstone Arsenal, AL 35898
1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035	1	Director, U.S. Army Missile & Space Intelligence Center ATTN: AIAMS-YDL Redstone Arsenal, AL 35898-5500
1	Commander ERADCOM Technical Library ATTN: DELSD-L (Reports Section) Fort Monmouth, NJ 07703-5301	1	Commander US Army Tank Automotive Command ATTN: AMSTA-TSL Warren, MI 48090
1	President US Army Aviation Test Board ATTN: ATZQ-OP-AA Ft. Rucker, AL 36360	1	Commander US Army Operational Test and Evaluation Agency ATTN: CSTE-ZS 5600 Columbia Pike Falls Church, VA 22041
		1	Commander US Army Armament Munitions & Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299

DISTRIBUTION LIST (continued)

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
8	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-TSS SMCAR-TDS, Mr. Lindner SMCAR-LC-F, Mr. Loeb SMCAR-LCW, Mr. Salsbury SMCAR-LCW, Mr. R. Wrenn SMCAR-SCA, Mr. Gehbauer SMCAR-LCU, Mr. Barrieres Dover, NJ 07801-5001	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missile Range, NM 88002
		2	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Ft. Benning, GA 31905
1	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-TDC Dover, NJ 07801	1	Commander US Army Development and Employment Agency ATTN: MODE-TED-SAB Fort Lewis, WA 98433
1	ODCSI, USAREUR / 7A ATTN: AEAGB-PDN(S&E) APO, NY 09403	1	Commander US Army Research Office Durham ATTN: CRD-AA-EH P.O. Box 12211 Research Triangle Park, NC 27709-2211
4	Director Benet Weapons Laboratory Armament R&D Center US Army AMCCOM ATTN: SMCAR-LCB-TL Dr. T. Simkins Dr. G. Carofano Dr. C. Andrade Watervliet, NY 12189	1	Commander US Army Ballistic Missile Defense Systems Command P.O. Box 1500 Huntsville, AL 35807
1	Commander US Army Jefferson Proving Ground Madison, IN 47251	1	President US Army Armor and Engineer Board ATTN: ATZK-AE-PD, Mr. W. Wells Ft. Knox, KY 40121
1	Commander US Army Materials and Mechanics Research Center ATTN: AMXRE-ATL Watertown, MA 02172	3	Commander Naval Air Systems Command ATTN: AIR-604 Washington, DC 20360
1	Commander US Army Natick Research and Development Laboratory ATTN: AMDNA, Dr. D. Sieling Natick, MA 01760	1	Commander Naval Sea Systems Cmd ATTN: 003 Washington, DC 20362

DISTRIBUTION LIST (continued)

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Commander David W. Taylor Naval Ship Research & Development Ctr ATTN: Lib Div, Code 522 Aerodynamic Lab Bethesda, MD 20084	1	Director National Aeronautics and Space Administration George C. Marshall Space Flight Center ATTN: MS-I, Lib Huntsville, AL 38512
2	Commander Naval Surface Weapons Center ATTN: 6X Dr. J. Yagla Dr. G. Moore Dahlgren, VA 22448	1	Director Jet Propulsion Laboratory ATTN: Tech Lib 4800 Oak Grove Drive Pasadena, CA 91109
1	Commander Naval Surface Weapons Center ATTN: Code 730 Silver Spring, MD 20910	1	Director NASA Scientific & Technical Information Facility ATTN: SAK/DL P.O. Box 8757 Baltimore/Washington International Airport, MD 21240
1	Commander Naval Weapons Center ATTN: Technical Services Branch China Lake, CA 93555	1	AAI Corporation ATTN: Dr. T. Stastny P.O. Box 126 Cockeysville, MD 21030
1	Commander Naval Weapons Center ATTN: Tech Info Div Washington, DC 20375	1	Advanced Technology Labs ATTN: Mr. J. Erdos Merrick & Steward Avenues Westbury, NY 11590
1	Commander Naval Ordnance Station ATTN: Code FS13A, P. Sewell Indian Head, MD 20640	1	Aerospace Corporation ATTN: Dr. G. Widhopf Bldg. D8 M4/965 P.O. Box 92957 Los Angeles, CA 90009
2	AFATL (DLRA) ATTN: F. Burgess Tech Lib Eglin AFB, FL 32542	1	AVCO Systems Division ATTN: Dr. D. Siegelman 201 Lowell Street Wilmington, MA 01887
1	AFWL/SUL Kirtland AFB, NM 87117	1	Technical Director Colt Firearms Corporation 150 Huyshope Avenue Hartford, CT 14061
1	Air Force Armament Laboratory ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000		
1	ASD/XRA (Stinfo) Wright-Patterson AFB, OH 45433		

DISTRIBUTION LIST (continued)

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	General Electric Armament & Electric Systems ATTN: Mr. R. Whyte Lakeside Avenue Burlington, VT 05401	1	Director Applied Physics Laboratory The Johns Hopkins University Johns Hopkins Road Laurel, MD 20707
2	Honeywell, Inc. ATTN: Mail Station MN 112190, G. Stille MN 50-2060, Mr. T. Melander 600 Second Street, North East Hopkins, MN 55343	1	Massachusetts Institute of Technology Dept of Aeronautics and Astronautics ATTN: Tech Lib 77 Massachusetts Avenue Cambridge, MA 02139
1	Hughes Helicopter Company Bldg. 2, MST22B ATTN: Mr. R. Forker Centinella and Teale Streets Culver City, CA 90230	1	Ohio State University Dept of Aeronautics and Astronautical Engineering ATTN: Tech Lib Columbus, OH 43210
1	Martin Marietta Aerospace ATTN: Mr. A. J. Culotta P.O. Box 5837 Orlando, FL 32805	1	Polytechnic Institute of New York Graduate Center ATTN: Tech Lib Route 110 Farmingdale, NY 11735
1	AEROJET Ordnance Company ATTN: Mr. A. Flatau 2521 Michelle Drive Tustin, CA 92680	2	Loral Corporation ATTN: S. Schmotolocha Ben Axley 300 N. Halstead St. P.O. Box 7101 Pasadena, CA 91109
1	Olin Corporation 275 Winchester Avenue New Haven, CT 06504	1	Director Forrestal Research Center Princeton University Princeton, NJ 08540
1	Director Sandia National Laboratory ATTN: Aerodynamics Dept Org 5620, R. Maydew Albuquerque, NM 87115	1	Kaman Tempo ATTN: Mr. J. Hindes 816 State Street P.O. Drawer QQ Santa Barbara, CA 93102
1	Guggenheim Aeronautical Lab California Institute of Tech ATTN: Tech Lib Pasadena, CA 91104	1	Southwest Research Institute ATTN: Mr. Peter S. Westine P.O. Drawer 28510 8500 Culebra Road San Antonio, TX 78228
1	Franklin Institute ATTN: Tech Lib Race & 20th Streets Philadelphia, PA 19103	22	

DISTRIBUTION LIST (continued)

<u>No. of Copies</u>	<u>Organization</u>
1	Boeing Company ATTN: C. R. Pond MS 8C-64 PO Box 3999 Seattle, WA 98124
1	FMC Corporation Northern Ordnance Division ATTN: Scott Langlie, Advanced Techniques 4800 East River Road Minneapolis MN 55421

Aberdeen Proving Ground

Dir, USAMSAA
ATTN: AMXSY-D
AMXSY-MP, H. Cohen

Cdr, USATECOM
ATTN: AMSTE-TO-F

Cdr, CRDC, AMCCOM
ATTN: SMCCR-RSP-A
SMCCR-MU
SMCCR-SPS-IL

Dir, Wpns Sys Concepts Team
ATTN: AMSMC-ACW

Dir, USAHEL
ATTN: Dr. Weisz
Dr. Cummings
Mr. Garinther

Dir, USACSTA
ATTN: Mr. S. Walton

10 Central Intelligence Agency
Office of Central Reference
Dissemination Branch
Room GE-47 HQS
Washington, D.C. 20502

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number _____ Date of Report _____
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. How specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Name

Organization

Address

City, State, Zip

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD
ADDRESS

Name

Organization

Address

City, State, Zip

(Remove this sheet along the perforation, fold as indicated, staple or tape closed, and mail.)

FOLD HERE

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-9989



FOLD HERE

END

FILMED

2-86

DTIC