

AD-A168 986

DESIGN ANALYSIS OF U-SHAPED DRY DOCK AND LOCK
STRUCTURES: A SURVEY(U) DELAWARE UNIV NEWARK A D KERR
MAY 86 WES/MP/ATC-86-1 DACW39-84-M-1509


1/1

UNCLASSIFIED

F/G 13/2

NL

[illegible]







MICROSCOPE

1000X



US Army Corps
of Engineers

AD-A168 986



MISCELLANEOUS PAPER ATC-86-1

12

DESIGN ANALYSES OF U-SHAPED DRY DOCK AND LOCK STRUCTURES: A SURVEY

by


Arnold D. Kerr
University of Delaware
Newark, Delaware 19716



May 1986
Final Report

Approved for Release by NSA on 09-11-2013 pursuant to E.O. 13526

DTIC FILE COPY



FOR THE DIRECTOR, ARMY
ENGINEER WATERWAYS
EXPERIMENT STATION
WASHINGTON, D.C.
1986

211

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Miscellaneous Paper ATC-86-1	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) DESIGN ANALYSES OF U-SHAPED DRY DOCK AND LOCK STRUCTURES: A SURVEY		5. TYPE OF REPORT & PERIOD COVERED Final report
7. AUTHOR(s) Arnold D. Kerr		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Dr. Arnold D. Kerr University of Delaware Newark, Delaware 19716		8. CONTRACT OR GRANT NUMBER(s) DACW 39-84-M-1509-0002
11. CONTROLLING OFFICE NAME AND ADDRESS DEPARTMENT OF THE ARMY US Army Corps of Engineers Washington, DC 20314-1000		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBER
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) US Army Engineer Waterways Experiment Station Automation Technology Center PO Box 631, Vicksburg, Mississippi 39180-0631		12. REPORT DATE May 1986
		13. NUMBER OF PAGES 20
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES Available from National Technical Information Service, 5285 Port Royal Road, Springfield, Virginia 22161.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Dry-docks (LC) Locks (Hydraulic engineering) (LC) U-frame locks (WES)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Various methods for analyzing U-shaped dry dock and lock structures are covered by this paper. Included are reports of approaches evolving over the last century as were performed in the United States of America (USA), West Germany, and the Union of Soviet Socialist Republics (USSR). These reported investigations deal with the use of analytical models and how they are related to the measurements obtained from actual structures. (Continued)		

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

20. ABSTRACT (Continued).

A major problem is the determination of the lateral pressure on lock walls. This is so because the pressure depends on the lock wall movements which are caused by such varied factors as fluctuating water levels and temperatures within the chamber, and densification of the backfill.

The USA publications are more readily available to WES; therefore, the emphasis in this paper is placed on those of Germany and the USSR.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

SUMMARY

This paper gives details of a survey of the various methods for analyzing U-shaped dry dock and lock structures as they evolved over the last century. Special emphasis is given to the analytical models used and their relationship to the extensive measurements performed on actual structures in the United States of America (USA), West Germany, and the Union of Soviet Socialist Republics (USSR) during recent decades. It was found that currently there are no generally accepted methods for analyzing the structures under consideration. The main difficulty is the determination of the lateral pressure on the lock walls and how this pressure is affected by the lock wall movements. Such movements are caused by the fluctuating water levels and temperatures within the chamber, which in turn are influenced by the densification of the backfill, among other factors.

AI

TY
110

PREFACE

This report presents a review of the engineering literature on methods for analyzing U-shaped dry dock and lock structures. The objective of the review was to determine which analytical models are presently being used for analysis of these complex structures. Preparation of the review for this report was accomplished with funds provided to the US Army Engineer Waterways Experiment Station (WES), Vicksburg, Miss., under the Civil Works Research and Development program of the Office, Chief of Engineers, US Army (OCE), as part of the Structural Engineering Research Program work unit of the Soil-Structure Interaction (SSI) Studies project.

The report was written by Dr. Arnold D. Kerr of the University of Delaware, under contract DACW 39-84-M-1509-0002 with WES.

Dr. N. Radhakrishnan, Chief of the Automation Technology Center (ATC), WES, and SSI Studies Project Manager, and Dr. Robert L. Hall, Research Civil Engineer, ATC, WES, coordinated and monitored the work. Ms. Gilda Shurden, Publications and Graphic Arts Division, WES, edited the material before publication. Mr. Donald R. Dressler, Structures Division, Civil Works Directorate, was the OCE point of contact.

Director of WES was COL Allen F. Grum, USA. Technical Director was Dr. Robert W. Whalin.

CONTENTS

	<u>Page</u>
SUMMARY	1
PREFACE	2
PART I: INTRODUCTION	4
Background	4
Need for Investigation	4
PART II: SURVEY OF ANALYSES	5
Early Analyses	5
State-of-the-Art Summary	7
Analyses by Ohde	8
Analyses Used for the Port Allen and Old River Locks	9
Recent West German Structures and Their Analyses	10
Lock Analyses in the USSR	12
PART III: SURVEY OF TESTS	14
Field Tests in Germany, USA, and USSR	14
Reports Translated and Published	14
REFERENCES	15
BIBLIOGRAPHY	20

DESIGN ANALYSES OF U-SHAPED DRY DOCK AND
LOCK STRUCTURES: A SURVEY

PART I: INTRODUCTION

1. This miscellaneous paper represents the steps involved in the study entitled "Survey of Analyses for Navigational Lock Structures." Much detail was required for the location and acquisition of relevant papers and reports, as well as the study and write-up of this material. It gives an account of publications that have appeared in the United States of America (USA), West Germany, and Union of Soviet Socialist Republics (USSR). Since the USA publications are known to the Waterways Experiment Station (WES), emphasis is placed on those from Germany and the USSR.

Background

2. The recent approach in West Germany assumes that the base slab rests on an elastic base and the walls are subjected to prescribed earth and water pressure distributions. A thesis by Hilmer (1976) describes this approach.

3. The USSR assumptions are that the walls are attached to a linear Winkler base with a variable coefficient or a nonlinear Winkler base. Gol'tsman discusses some of these problems in his recent contributions to the journal, Hydrotechnical Construction.

Need for Investigation

4. Much concern was created among design engineers in Germany and the USSR because some measurements on completed U-shaped structures revealed earth pressures on the walls that were three times larger than those pressures assumed in the respective analyses. The possible reasons given were the horizontal movements of the walls due to temperature changes, water level changes inside the lock, and the ground-water-level fluctuations outside the structure, as well as the nonuniform compaction of the backfill material. On the other hand, no such pressure increases were recorded on some of the locks studied. This problem should be clarified, since it has a strong effect on the assumptions guiding the choice of an analytical model for locks.

PART II: SURVEY OF ANALYSES

5. The early analyses of lock-type structures are based on simple assumptions regarding the anticipated contact pressures, with no consideration for the stiffness properties of the soil and structures.

Early Analyses

6. An example of an early analysis is the presentation by Gromsch (1891). In 1906, Brennecke suggested that, depending on the anticipated conditions, the contact pressure at the base slab may be assumed as uniformly distributed or a linearly varying distribution with the vertex at the center. The pressure against the wall, due to water and/or soil, was assumed to be triangular. Based on this approach, Franzius (1908b, 1916, 1927) presented dry-dock analyses for a large variety of cases, which occur during dock construction and its operation upon completion. The analyses proposed by Engels (1921) were based on a similar concept. The pressure distributions used are shown in Figure 1.

7. In these analyses the choice of a pressure distribution is intuitive and it must satisfy only the vertical equilibrium, without regard to the properties of the soil and structure. Joppen (1952) attempted to prove that the




Figure 1. Assumed pressure distributions in early analyses

uniform contact pressure distribution is the critical one for design purposes. However, because of various misconceptions, his proof is not correct.

8. Analyses based on variations of the approach described above were suggested by Ellerbeck, as described by Pietrkowski (1929), and by Odenkirchen, as reported by Mugge (1940). For critical comments on the Ellerbeck method, refer to Ohde (1942).

9. More than a century ago Winkler (1867) published the differential equations for the continuously supported beam

$$D \frac{d^4 w}{dx^4} + kw = q(x) \quad (1)$$

Solutions for specific cases related to railroad tracks were presented by Schwedler (1882) and Zimmerman (1888). These results suggested their use for the analysis of locks. Freund (1918) applied this approach for the analysis of a U-shaped lock structure by assuming that the vertical walls are "rigid" and subjected to water and earth pressure and the base slab is attached to a Winkler foundation, as shown in Figure 2. The first part of the paper (pp 84-104) covers the analytical approach, whereas the second part (pp 188-202) introduces an approximate graphical method.





Figure 2. Analytical model used by Freund (1918)

10. Hayashi (1921) discussed the analysis of a U-shaped dry dock and presented a numerical example using the model shown in Figure 3. He also discussed a case when the center of the base slab may lift-off the ground (pp 154-158). The lock analysis by Zhemochkin (1927) was not available for review.

Figure 3. Analytical
model used by
Hayashi (1921)



11. Freund (1927), in a follow-up paper, first discussed the justification of the assumption that the soil responds elastically, and the methods for determining the coefficient of subgrade reaction k .^{*} In this connection, he cited the test results by Muhlhofer (1922, 1923), Wolterbeck (1925), Moller (1921), and Franzius (1980a). A simplified analysis is then introduced, and the structure under consideration is classified as "short" (rigid), "finite," and "long" on a Winkler base.

12. The remainder of this paper is dedicated to an extensive analysis of the effect of vertical ground movements on the response of the U-shaped lock structure. The three types of ground movements discussed are:
(1) settlements on one side only, (2) settlements on both sides, and
(3) settlement at the center, as shown in Figure 4.

13. Another numerical example for analyzing a U-shaped dry dock, with the base slab modeled as a beam on a Winkler foundation, was presented by Beyer (1948).

State-of-the-Art Summary

14. In a treatise entitled "Analysis and design of dry docks and navigational locks," Agatz (1950) summarized the state-of-the-art in this area. The paper covers a large range of important topics and describes the

* Of interest is the comment by Freund (1927, pp 76): "It is a pity that it is still not possible to establish the modulus of subgrade reaction k from Young's modulus E of the soil determined in a laboratory. This shortcoming should be taken into consideration in future soil and foundation investigations." For related results, refer to the recent paper "On the Determination of Foundation Model Parameters" by A. D. Kerr, Journal of Geotechnical Engineering, 1985.




Figure 4. Ground movements discussed by Freund (1927)

experience gained from the many existing dry docks and navigation locks. Although no new method of analysis was proposed, the paper includes a discussion of various aspects that should be considered when analyzing dry docks and navigation locks.

15. The book by Press (1956) contains a description of various lock structures (with details of blueprints) and general guidelines regarding lock analyses (pp 293-298).

Analyses by Ohde

16. Still another method for the analysis of the base slab of a lock was presented by Ohde (1953). It is based on a number of assumptions, regarding the contact pressure distribution and the shape of the deformed slab (1942). It is a rather involved analysis which, because of the availability of the FEM and boundary integral methods, this method may not be very useful. The same comment applies to the base slab analysis presented by Kany (1959).

17. After World War II a number of lock-type structures were designed and built in the USA, West Germany, and the USSR. Since the planned structures were much larger than those built earlier, they revived questions regarding the sufficiency of the available analyses and codes. This, in turn, led to the initiation of a number of research projects with the aim of establishing the proper analyses for design purposes.

Analyses Used for the Port Allen and Old River Locks

18. In the USA the structures in question were the U-shaped Port Allen Lock, with a wall height of 21 meters, completed in 1961, and the Old River Lock, with a wall height of 24 meters, completed in 1963. The procedure followed was described by Clough and Duncan (1969) as follows:

"In connection with the design of Port Allen Lock, the US Army Engineers conducted a review, described by Sherman and Trahan (1968), of existing procedures to determine the earth pressures acting on U-frame structures. All the methods reviewed had certain common features: (1) a plane section was analyzed; (2) wall pressures were assumed according to conventional earth pressure concepts; and (3) downdrag on the walls was neglected. Only in determining the base pressures were the methods different. A number of approaches involved the use of base pressure distributions determined by experience, but none of these approaches considered the required compatibility between the deflected base slab shape and the subsoil settlement profile. Analyses based on subgrade modulus concepts had been suggested as a means of satisfying the compatibility requirement, but this approach was not considered reliable in view of the difficulty in accounting for the effects of the backfill and the uncertainty in choosing an appropriate value of subgrade modulus.

The method chosen for use in determining the base pressures for design of Port Allen Lock, and later Old River Lock, was a trial procedure in which soil deformations and base slab structural deflections were calculated for various assumed base pressure distributions. The correct pressure distribution was taken as that which yielded compatible structural deflections and soil deformations. This method thus satisfied the compatibility requirement and accounted for the soil compressibility, including time effects."

19. Because of the uncertainty of the used analyses, the docks were instrumented in order to record the earth pressures on the walls and base plate, the displacements, temperature distributions, etc. The instrumentation and results of the initial measurements were reported by Kaufman and Sherman (1964). They found that the distribution of the recorded base pressures differed substantially from the distribution assumed in the design analysis and that the observed wall pressures were generally lower than those used. It was also found that the downdrag mobilized at the lock walls produced moments at the centerline of base slab which were about 50 percent larger than those used in design.

20. An extensive report of the measurements on the Port Allen Lock was presented by Sherman and Trahan (1968) and on the Old River Lock by Sherman and Trahan (1972).

21. Because of the found discrepancies between the recorded data and the design analyses, the lock structures were again analyzed by using FEM modeling the surrounding soil as an elastic continuum. These results were reported by Clough and Duncan (1969), Duncan and Clough (1971), Clough and Duncan (1972), and Gould (1970). Since the initial calculations using linear constitutive equations were not satisfactory, the nonlinear equations proposed by Duncan and Chang (1970) were utilized. For the *chosen material parameters* the agreement of the calculations and measurement was good.

Recent West German Structures and Their Analyses

22. In West Germany the structures in question were the 16 locks needed for the Main-Danube-Canal, which were designed and built for three decades since the midfifties, as reported by Kuhn (1962, 1971). The lock wall heights vary. The ones of the Nurnberg-Sud Lock are 25 meters high, thus, slightly higher than the walls of the Old River Lock.

23. The designers of these locks also encountered the lack of reliable methods for estimating the expected earth pressures on the base slab as well as on the walls. The earth pressure on the walls was assumed, until then, as linearly increasing with increasing distance from the top. However, this assumption appeared questionable because of the flexibility of the tall walls. This was especially so, since the results of measurements on locks on the Volga River, reported by Tsarev and Feldman (1965), showed that the recorded

earth pressures might be three times higher than the calculated values.

24. This situation led to a number of research projects, as reported by Franke and Bernhard (1972), Sadgorski (1974), and Hilmer (1976). Hilmer, in his Dr.-Ing. dissertation, after briefly reviewing the earth-pressure assumptions used in Germany, presents results of an analysis with modified earth-pressure distributions, as shown in Figure 5.




Figure 5. Modified earth-pressure distributions

25. The report by Hilmer (1976) contains a description of the test program on the Nurnberg-Sud lock and model tests conducted at the engineering schools in Nurnberg and Darmstadt. He utilized the Clough and Duncan (1969, 1972) FEM programs for an extensive parametric study of the Nurnberg-Sud Lock, using modified nonlinear constitutive equations by Duncan and Chang (1970) for the soil and linear response expressions for the concrete and steel rods.

26. According to Hilmer, the analyses pointed out the importance of taking into consideration the construction sequences when estimating the earth pressures and the displacement of the lock structure. It also showed that the temperature variations between winter and summer have a large effect on the earth pressures on lock walls that are over 15 meters high.

27. Hilmer did not observe the "stiffening" of the backfill material in the model tests and in some of the lock measurements. This was considered the reason for the substantial increase of earth pressures on some of the Volga locks as reported by Tsarev and Feldman (1965). This "stiffening" was

considered to have been caused by the cyclic horizontal movements of the lock walls due to the fluctuations of the water level and the annual temperatures in the chamber and the ground-water movements outside of the lock wall. This was suggested by Sinyavskaya and Pavlova (1971). However, on the basis of his findings, Hilmer accepts the explanation by Shcherbina (1974) that these earth-pressure increases were caused, instead, by a nonuniform compaction of the backfill. Note that a "stiffening" effect was also observed in the tests of the Luneburg ship-lifting facility, as reported by Schuppener (1975), and much earlier by Ohde (1948). This problem requires clarification.

28. In his concluding suggestions, Hilmer points out two essential loading cases for lock analyses: (1) due to earth pressure, when chamber is empty, and temperature increases inside of chamber; this case should yield the largest tensile stresses on the outer surface of lock wall, and (2) due to earth pressure, when chamber is filled, and temperature inside chamber drops; this case should yield the largest tensile stresses on the chamber side of the lock walls.

Lock Analyses in the USSR

29. In the USSR the intensification of research on the analyses of lock-type structures was apparently caused by planned revisions of the corresponding codes (SNiP II-I.10-65, SN 303-65, and SN 349-66) in the 1970's. A main problem with the old codes was the lack of reliable methods for the analysis of the earth pressure on vertical walls. This, according to the Editor's Note to the paper by Gol'tsman (1975), led to an "...increase in the consumption of reinforcement steel in structures being designed, in comparison with the consumption in older structures which are operating successfully." Thus, the lack of generally accepted methods for estimating earth pressures is similar to the situation encountered in the USA and West Germany.

30. According to the USSR code SNiP II-I.10-65 entitled "Retaining Walls of Hydraulic Structures" (in Russian) published by Stroizdat in Moscow during 1966, when the wall displaces toward the backfill, caused by external loads or temperature effects, the determination of the resulting (passive) earth pressure is to be calculated using the model of a beam on a Winkler foundation with a constant modulus along the wall height. It is also

mentioned that the foundation modulus, when justified, may be assumed as varying. Also of interest are the relevant sections in the book by Dubrova (1963).

31. A major effort then followed to establish the variation of the foundation modulus with wall height. The results of various research activities were reported by Gol'tsman (1975), Gol'tsman and Sheinman (1976), Gol'tsman (1977), and Bugrov (1978). Of special interest is the paper by Gol'tsman (1977) entitled "Strength Analysis of Dock-Type Lock Chambers and Retaining Walls" where the various methods of analysis used in the USSR are discussed.

32. When analyzing lock-type structures, the problem of uplift pressure must also be considered. In this connection, the publications by Sokolov and Logunova (1977), Marchuk (1979), Petrashen (1981), and Fishman (1982) should be noted.

PART III: SURVEY OF TESTS

Field Tests in Germany, USA, and USSR

33. Results of early tests on two dry docks were described by Franzius (1908a) while more recent studies on a lock-type structure conducted in Germany were reported by Schuppener (1975). Of special interest is the observed increase of the lateral earth pressure on the walls caused apparently by the horizontal movements of the walls. Other test results were described by Hilmer (1976).

34. Test results in the USA on the Port Allen Lock and Old River Lock were reported by Kaufman and Sherman (1964), Sherman and Trahan (1968), and Sherman and Trahan (1972).

35. Extensive field test programs on constructed structures were also conducted in the USSR. They were reported by Tsarev and Feldman (1965), Burmistrov and Kotenkov (1967), Sinyavskaya and Pavlova (1971, 1972), Mikhailov and Avdeeva (1973, 1974), and Nefedova and Kotenkov (1973).

36. As discussed in paragraph 23, the measurements of Tsarev and Feldman (1965) caused special concern among the design engineers, since some of the recorded earth pressures on the lock walls were three times higher than the values assumed in the analyses.

Reports Translated and Published

37. Four of these Russian papers were translated into German and were published by Smolczyk, Pertschi, and Hilmer (1976). This publication also includes the German translation of the USSR Code SN 303-65 "Guidelines for the Planning of Navigational Locks" published by Stroizdat in Moscow in 1966.

REFERENCES

- Agatz, A. 1950. "Berechnung und Konstruktive Gestaltung von Trockendocks und Seeschleusen" ("Analysis and Design of Dry Docks and Navigation Locks," In German), Jahrbuch der Hafenbautechn. Gesellschaft, Vol 19, pp 1941-1949, Springer Verlag, Berlin/Gottingen/Heidelberg.
- Beyer, K. 1948. "Die Berechnung der Sohle eines Trockendocks" ("The Analysis of the Base Slab of a Dry Dock," In German), Die Statik im Stahlbetonbau, 2nd ed., Springer Verlag, Berlin, pp 147-149.
- Bugrov, A. K. 1978. "Calculation of the Resistance of Backfill to Displacements of Retaining Walls," Hydrotechnical Construction,* No. 7, pp 699-704.
- Burmistrov, M. A., and Kotenkov, Yu, K. 1967. "Field Investigations of the Static Behavior of a Navigation Lock Chamber," Hydrotechnical Construction, No. 3, pp 248-254.
- Clough, G. W., and Duncan, J. W. 1969. "Finite Element Analyses of Port Allen and Old River Locks," Contract Report S-69-6, US Army Engineer Waterways Experiment Station, Vicksburg, Miss.
- _____. 1972. "Temperature Effects on Behavior of Port Allen Lock," American Society of Civil Engineers Specialty Conference, Purdue University, West Lafayette, Ind.
- Dubrova, G. A. 1963. "Vzaimodeistvie Grunta i Sooruzhenii" ("Soil Structure Interaction," In Russian), Izd. Rechnoi Transport, Moscow, pp 40-45.
- Duncan, J. M., and Chang, Chin Yung. 1970. "Nonlinear Analysis of Stress and Strain in Soil," Journal, Soil Mechanics and Foundation Division, American Society of Civil Engineers, No. SM5, pp 1629-1653.
- Duncan, J. W., and Clough, G. W. 1971. "Finite Element Analyses of Port Allen Lock," Journal, Soil Mechanics and Foundation Division, American Society of Civil Engineers, No. SM8, pp 1053-1068.
- Engels. 1921. In "Taschenbuch fur Bauingenieure," Forster, Editor, 4th ed., Springer Verlag, Berlin.
- Fishman, Yu. A. 1982. "Consideration of the Uplift Pressure of Water in Calculations of Concrete Dams on Rock Foundations," Hydrotechnical Construction, No. 9, pp 502-507.
- Franke, E., and Bernhard, K. 1972. "Erddruckansatz bei trogformigen Bauwerken und Wechselwirkung zwischen Erd- und Sohldruck am Beispiel des Schiffshebewerks Luneburg" ("Assumption of Earth Pressure Distribution for U-shaped Structures and Interaction Between the Earth Pressure and Bottom Pressure on the Example of the Ship-lifting Facility in Luneburg," In German), Mitteilungsblatt der Bundesanstalt fur Wasserbau, No. 32, Karlsruhe, West Germany.

* Hydrotechnical Construction is the title of the English translation of the journal Gidrotekhnicheskoe Stroitelstvo, Plenum Publishing Corp.

Franzius, O. 1908a. "Messungen von Bewegungen der Trockendocks V and VI der Keiserlichen Werft Kiel" ("Measurement of Movement of the Drydocks V and VI of the Imperial Shipbuilding Facility Kiel," In German), Zeitschrift fur Bauwesen, Vol LVIII, pp 84-98.

_____. 1908b. "Uber die Berechnung von Trockendocks" ("On the Analysis of Dry Docks," In German), Zeitschrift fur Bauwesen, pp 476-506.

_____. 1916. "Vereinfachte Berechnung von trogformigen Betonkorpern, wie Docks, Schleusen, usw," Beton und Eisen, pp 85.

_____. 1927. Der Verkehrswasserbau (Navigational Hydrotechnical Engineering, In German), Springer Verlag, Berlin, pp 406-414.

Freund, A. 1918. "Die Berechnung von Schleusenboden nach der Elastizitatslehre" ("The Analysis of Lock Base Slabs as an Elastic Problem," In German), Zeitschrift fur Bauwesen, pp 84-202.

_____. 1927. "Erweiterte Theorie fur die Berechnung von Schleusenboden und ahnlichen Grundungskorpern" ("Extended Theory for the Analysis of Lock Base Slabs and Similar Foundation Bodies," In German), Zeitschrift fur Bauwesen, Part I, pp 73-88; Part II, pp 108-120.

Gol'tsman, V. Kh. 1975. "Values and Law of the Depth Distribution of the Coefficient of Resistance of Backfill to Displacement of Vertical Walls," Hydrotechnical Construction, No. 11, pp 1060-1071.

_____. 1977. "Strength Analysis of Dock-Type Lock Chambers and Retaining Walls," Hydrotechnical Construction, No. 3, pp 282-295.

Gol'tsman, V. Kh., and Sheinman, L. B. 1976. "Calculation of Dock Structures of Lock Chambers Utilizing the Data from Full-Scale Observations; Construction Specifications," Hydrotechnical Construction, No. 5, pp 996-1003.

Gould, J. P. 1970. "Lateral Pressure on Rigid Permanent Structures," American Society of Civil Engineers Specialty Conference, Cornell University, Ithaca, New York, pp 219-270.

Gromsch. 1891. "Uber die Berechnung gemauerter Schleusen und Trockendocks" ("On the Analysis of Locks and Dry Docks," In German), Zeitschrift fur Bauwesen, p 538.

Hayashi, K. 1921. "Uber die Berechnung von Trockendocks" ("On the Analysis of Dry Docks," In German), Theorie des Tragers auf Elastischer Unterlage, Part IX, Verlag von J. Springer, Berlin, pp 245-256.

Hilmer, K. 1976. Erddruck auf Schleusenkammerwande (Earth Pressure on Lock Chamber Walls, In German), Dr.-Ing. Dissertation, published as Report No. 6 of the Institut fur Grundbau und Bodenmechanik, Universitat Stuttgart, West Germany.

Joppen, F. 1952. "Sohlendruckverteilung unter Schiffartsschleusen mit durchgehender biegungsfester Sohlenplatte" ("Contact Pressure Distribution Under Navigation Locks with a Continuous Lock Base Slab," In German), Die Bautechnik, Vol 29, No. 2, pp 46-51.

Kany, M. 1959. "Berechnung einer Schleusensohle" ("Analysis of a Lock Base Slab," In German), Berechnung von Flachengrundungen, Verlag Ernst and Sohn, Berlin, pp 49-53.

Kaufman, R. I., and Sherman, W. C. 1964. "Engineering Measurements for Port Allen Lock," Journal, Soil Mechanics and Foundation Division, American Society of Civil Engineers, Vol 90, No. SM5.

Kuhn, R. 1962. "Die Sparschleusen der Strecke Bamberg-Nurnberg" ("The Locks of the Section Bamberg-Nurnberg," In German), Construction Report of the Rhein-Main-Donau AG, Munich, West Germany.

_____. 1971. "Die Schleusen des Main-Donau-Kanals" ("The Locks of the Main-Donau Canal," In German), Der Bauingenieur, pp 163-184.

Marchuk, A. N. 1979. "Uplift Pressure of Water on Base of Concrete Dams on Rock Foundations," Hydrotechnical Construction, No. 12.

Mikhailov, A. V., and Avdeeva, V. I. 1973. "Nekotoryie Rezultaty Issledovaniy Staticheskoi Raboty Kamer Sudokhodnykh Shlyuzov" ("Some Results of Investigations on the Static Response of Chambers of Ship Locks," In Russian), Trudy Gidroproekta, Vol 32, pp 179-183.

_____. 1974. "Effect of a Change in the Reactive Pressure of Backfills on Stresses in Lock Chambers with Solid Bottoms," Hydrotechnical Construction, pp 20-26.

Mugge. 1940. "Bau des Schleusenkanals der Staustufe einer Flusskanalisierung" (Construction of a Channel Lock," In German), Die Bautechnik, Vol 18, Heft 40/41.

Moller, B. 1921. "Die neue Erzwäsche in Broistedt," Der Bauingenieur.

Muhlhofer, L. 1922. "Neuerungen auf dem Gebiete des Druckstollenbaues," Der Bauingenieur, p 545.

_____. 1923. "Über die Inanspruchnahme von Druckstollenauskleidungen," Der Bauingenieur, p 509.

Nefedova, G. N., and Kotenkov, Yu. K. 1973. "Naturnyie Issledovaniya Staticheskoi Raboty Tipovoi Sektsii Kamery Sudokhodnogo Slyuza" ("In-situ Investigations of the Static Response of a Typical Section of a Navigation Lock Chamber," In Russian), Trudy Gidroproekta, Vol 32, pp 183-193.

Ohde, J. 1942. "Die Berechnung der Druckverteilung unter Grundungskörpern" ("The Analysis of Contact Pressures Under Footings," In German), Der Bauingenieur, Vol 23, Heft 14/16 and 17/18.

_____. 1948. "Zur Erddrucklehre" ("To the Theories of Earth-Pressure," In German), Die Bautechnik, pp 121-126.

_____. 1953. "Einfache Berechnung bigefester Schleusensohlen" ("Simple Analysis of Lock Base Slabs," In German), Die Bautechnik, Vol 30, No. 5, pp 140-146.

Petrashen, R. N. 1981. "Uplift Pressure of Water on the Base of Hydraulic Structures in Limit Design States; Discussion of Design Specifications," Hydrotechnical Construction, No. 7, pp 427-431.

Pietrkowski. 1929. "Berechnungsformeln für die Bodenpressungen an Schleusenbauwerken" ("Formulas for Calculating the Base Pressures of Lock Type Structures," In German), Der Bauingenieur, No. 8, pp 139, 140.

Press, H. 1956. "Berechnungsgrundlagen für Wasserbauten, besonders für Schleusenkorper" ("Foundations of Analysis for Hydrotechnical Structures, Especially for Locks," In German). Binnenwasserstrassen und Binnenhafen, Verlag Ernst and Sohn, Berlin, pp 293-298.

Sadgorski, W. 1974. "Berechnung durchgehender Sohlplatten im Wasserbau nach dem Steifezahlverfahren," (In Berechnung von Flachengrundungen by M. Kany), Verlag Wilhelm Ernst and Sohn, Berlin, West Germany.

Schuppener, B. 1975. "Erddruckmessungen am Schiffshebewerk Lüneburg" ("Earth Pressure Measurements at the Ship-Lifting Facility in Lüneburg," In German), Mitteilungsblatt der Bundesanstalt für Wasserbau, No. 37, Karlsruhe, West Germany.

Schwedler, J. W. 1882. "Wood on Iron Permanent Way," Proceedings, Institution of Civil Engineers, London, pp 95-118.

Shcherbina, V. I. 1974. "Earth Pressure on Lock Chamber Walls During Construction," Hydrotechnical Construction, pp 128-132.

Sherman, W. C., and Trahan, C. C. 1968. "Analysis of Data from Instrumentation Program, Port Allen Lock," Technical Report S-68-7, US Army Engineer Waterways Experiment Station, Vicksburg, Miss.

_____. 1972. "Analysis of Data from Instrumentation Program, Old River Lock," Technical Report S-72-10, US Army Engineer Waterways Experiment Station, Vicksburg, Miss.

Sinyavskaya, V. M., and Pavlova, A. E. 1971. "Effect of Periodic Displacements of a Lock Wall on the Earth Pressure and Reinforcement Stresses," Hydrotechnical Construction, No. 3, pp 247-254.

_____. 1972. "Rezultaty Prirodnikh Issledovaniy Raboty Stenki Kamery Volgogradskogo Shlyuza" ("Results of In-Situ Investigations on the Response of the Chamber Walls of the Volgograd Lock," In Russian), Trudy Gidroproekta, Vol 24, pp 214-225.

Smolczyk, U., Pertschi, O., and Hilmer, K. 1976. "Messungen an Schleusen in der UdSSR-Schleusennorm der UdSSR [SN 303-65]" ("Measurements on Locks in the USSR-Codes for Locks in the USSR [SN 303-65]"), Baugrundinstitut, Universität Stuttgart, Mitteilung 5, West Germany.

Sokolov, I. B., and Logunova, V. A. 1977. Seepage and Uplift Pressure of Water in Concrete of Hydraulic Structures (In Russian), Energiya Publishing House, Moscow.

Tsarev, A. I., and Feldman, A. I. 1965. "Davlenie Peschanykh Zasypok na Stenki Dokovykh Konstruktsii Kamern Sudokhodnykh Shlyuzov" ("Pressure of Sand Backfill on the Walls of the Chamber Walls of Navigation Locks," In Russian), Gidrotekhnicheskoe Stroitelstvo (Hydrotechnical Construction), Vol 35, No. 9, pp 22-26.

Union of Soviet Socialist Republics Code SNiP II-I.10-65. 1966a. "Retaining Walls of Hydraulic Structures," Stroizdat, Moscow.

_____. Code SN 303-65. 1966b. "Guidelines for the Planning of Navigational Locks" (In Russian), Izd. Lit po Stroitelstvo, Moscow.

Winkler, E. 1867. On Elasticity and Strength, H. Dominicus, Prague, Czechoslovakia.

Wolterbeck, C. 1925. "Belastungsproblem zur Klärung des Einflusses der Elastizität des Bodens auf die Berechnung eines Schleusenbodens" ("Loading Tests for Clarifying the Influence of Soil Elasticity on the Analysis of a Lock Base Slab," In German), Die Bautechnik, p 411.

Zhemochkin, V. N. 1927. "K Voprosu o Rashcete Sukhikh Dokov" ("To the Analysis of Dry Docks," In Russian), Trudy MIIT, Vypusk VI, Gostransizdat, Moscow.

Zimmerman, H. 1888. Die Berechnung des Eisenbahnoberbaues (The Analysis of Railroad Tracks, In German), Verlag W. Ernst and Sohn, Berlin.

BIBLIOGRAPHY

Mikhailov, A. V. 1955. "Sudokhodnyie Shlyuzy" ("Navigation Locks," In Russian), Gos. Izd. Lit. po Stroitelstvo i Arkhitekture, Moscow.

END

DTIC

7-86