

PA 571984 ⁷⁸

UNCLASSIFIED
Technical
Report
distributed by

TACTEC



DEFENSE

TECHNICAL

INFORMATION

CENTER

A187 175-



DEFENSE LOGISTICS AGENCY
Cameron Station
Alexandria, Virginia 22304-6145

UNCLASSIFIED

MAR 06 1989

UNCLASSIFIED

NOTICE

We are pleased to supply this document in response to your request.

The acquisition of technical reports, notes, memorandums, etc., is an active, ongoing program at the **Defense Technical Information Center (DTIC)** that depends, in part, on the efforts and interest of users and contributors.

Therefore, if you know of the existence of any significant reports, etc., that are not in the **DTIC** collection, we would appreciate receiving copies or information related to their sources and availability.

The appropriate regulations are Department of Defense Directive 3200.12, DoD Scientific and Technical Information Program; Department of Defense Directive 5200.20, Distribution Statements on Technical Documents (*amended by Secretary of Defense Memorandum, 18 Oct 1983, subject: Control of Unclassified Technology with Military Application*); Military Standard (*MIL-STD*) 847-B, Format Requirements for Scientific and Technical Reports Prepared by or for the Department of Defense; Department of Defense 5200.1R, Information Security Program Regulation.

Our Acquisition Section, **DTIC-FDAB**, will assist in resolving any questions you may have. Telephone numbers of that office are: (202) 274-6847, (202) 274-6874 or Autovon 284-6847, 284-6874.

DO NOT RETURN THIS DOCUMENT TO DTIC


**EACH ACTIVITY IS RESPONSIBLE FOR DESTRUCTION OF THIS
DOCUMENT ACCORDING TO APPLICABLE REGULATIONS.**

UNCLASSIFIED

DTIC FILE COPY

ADF300991

AD



AD-A187 175

TECHNICAL REPORT BRL-TR-2842

DTIC
ELECTE
DEC 04 1987
S
C&D
D

A PROPULSION SYSTEM COMPARISON
STUDY FOR THE 120-mm
ANTI-ARMOR CANNON

PAUL G. BAER
CATHERINE F. BANZ
INGO W. MAY
WALTER F. MORRISON

AUGUST 1987

APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED

US ARMY BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

87 11 30 114

DESTRUCTION NOTICE

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE

AD-A187175


REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188
Exp. Date: Jun 30, 1986

1a. REPORT SECURITY CLASSIFICATION <u>Unclassified</u>			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) <u>BRL-TR-2842</u>			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION <u>US Army Ballistic Research Laboratory</u>		6b. OFFICE SYMBOL (if applicable) <u>SLCBR-IB</u>		7a. NAME OF MONITORING ORGANIZATION	
6c. ADDRESS (City, State, and ZIP Code) <u>Aberdeen Proving Ground, MD 21005-5066</u>		7b. ADDRESS (City, State, and ZIP Code)			
8a. NAME OF FUNDING / SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (if applicable)		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO.		PROJECT NO.	TASK NO.
					WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) <u>A PROPULSION SYSTEM COMPARISON STUDY FOR THE 120-mm ANTI-ARMOR CANNON</u>					
12. PERSONAL AUTHOR(S) <u>Baer, Paul G., Banz, Catherine F., May, Ingo W., and Morrison, Walter F.</u>					
13a. TYPE OF REPORT <u>TR (Technical Report)</u>		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day) <u>August 1987</u>	
15. PAGE COUNT <u>17</u>					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	170 - cannon; gun; propulsion; antiarmor; propellant; travelling charge gun; liquid propellant		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
We explore the effect of advanced propulsion technologies on the performance potential of a 120-mm high performance cannon. The current 120-mm gun using conventional granular propellant operates at a peak pressure of 505 MPa and accelerates a 7.1 kg sabot projectile with a kinetic energy penetrator to a velocity of 1650 m/s. We predict that performance increases on the order of 25% are possible in theory for the best of the advanced propulsion concepts. In practice a 10 to 15% increase is a more realistic upper limit. The use of a 30% longer gun tube operating at a 15% higher peak breech pressure results in an almost 10% increase in muzzle velocity. Relatively small increases in muzzle velocity such as these can result in significant improvements in overall gun system effectiveness. ← 2180 - (see p. 1)					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION <u>Unclassified</u>		
22a. NAME OF RESPONSIBLE INDIVIDUAL <u>Paul G. Baer</u>			22b. TELEPHONE (Include Area Code) <u>(301) 278-6187</u>		22c. OFFICE SYMBOL <u>SLCBR-IB-B</u>

TABLE OF CONTENTS

	Page
LIST OF FIGURES	v
I. INTRODUCTION	1
II. GROUND RULES AND PROCEDURES	1
1. IMPROVED CONVENTIONAL GUN	2
2. CONSTANT PRESSURE GUN	3
3. SOLID PROPELLANT TRAVELING CHARGE GUN	3
4. REGENERATIVE LIQUID PROPELLANT GUN	4
III. DISCUSSION	13
1. IMPROVED CONVENTIONAL GUN	13
2. CONSTANT PRESSURE GUN	14
3. SOLID PROPELLANT TRAVELING CHARGE GUN	14
4. REGENERATIVE LIQUID PROPELLANT GUN	15
IV. SUMMARY	16
REFERENCES	19
DISTRIBUTION LIST	21



Accession For	
NTIS CNA21	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Traveling Charge Gun Concept	3
2	RLP Gun Concept	4
3	Interior Ballistic Trajectory for Conventional 120-mm Gun Propulsion Using 19-Perforated JA2 Propellant.	6
4	Interior Ballistic Trajectory for an Ideal 120-mm Constant Pressure Gun Using JA2 Propellant.	7
5	Interior Ballistic Trajectory for an Idealized 120-mm Traveling Charge Gun	8
6	Interior Ballistic Trajectory for a 120-mm RLP Gun Using LGP 1845 Propellant.	9
7	Effect of Increased Loading Density on Performance of Standard 120-mm Gun Using Four Propulsion Options.	10
8	Effect of Increased Loading Density on Performance of Enhanced 120-mm Gun with Four Propulsion Options.	11
9	Effect of Propellant Thermochemistry on Performance of a 120-mm RLP Gun.	12

I. INTRODUCTION

2180/ It is the purpose of this study to examine the potential of advanced gun propulsion technologies for improving the performance of a 120-mm cannon. We examine briefly the improvements possible by optimizing conventional granular propellant technology. We also examine the limiting performance potential of conventional gun propulsion as represented by the idealized constant pressure (CP) gun requiring perfect surface area control. We re-examine the improvements possible with the solid propellant traveling charge (SPTC) effect. Finally, in the same context, we analyze the performance of a regenerative liquid propellant gun (RLPG). While none of these advanced technologies are mature enough at this point in time for fielding, they do represent the performance potential for future gun systems.

For anti-armor gun systems, kinetic energy (KE) penetrators have become the ammunition of choice. Basic armor penetration mechanics reveals that KE penetrators, which impact targets at velocities near the 50% perforation probability (v_{50}) limit, benefit greatly by small increases in muzzle velocity. Five to ten percent increases in striking velocity are important enough to justify substantial developmental efforts to realize them in practice.

We begin this study by defining some pertinent interior ballistic parameters of the current baseline 120-mm gun system and its standard round. We then present the ground rules for the parametric comparison of the advanced propulsion options. We first show representative interior ballistic trajectories for all of the propulsion options at the performance level of current standard ammunition. This provides insight into some of the important physical aspects involved. We then review the performance increases possible by varying the loading density. Each of these comparisons also examines the combined effect of operating at a higher pressure with a longer gun tube. We finally discuss the results and assess their implications.

II. GROUND RULES AND PROCEDURES

The pertinent interior ballistic parameters for a standard 120-mm gun system are shown in Table 1. These parameters were used to calibrate the interior ballistic codes. The calibration factors include heat loss, burning rate adjustments, and bore friction profiles. These were then frozen for the rest of the parametric study as appropriate. Three different computer codes were used for this study each requiring a somewhat different calibration approach.

TABLE 1. 120-mm Gun and Projectile Characteristics

In-Bore Projectile Weight (kg)	7.1
Bore Diameter (mm)	120
Maximum Projectile Travel (m)	4.75
Chamber Volume (l)	9.75
Peak Breech Pressure (MPa)	505
Muzzle Velocity (m/s)	1650

PROPELLANT CHARACTERISTICS

Types	JA2	FNC	KC	BEN
Weights (kg)	7.40	0.66	0.11	0.03
Impetus (J/g)	1140.	547.	286.	635.
Flame Temperature (K)	3410.	1610.	1054.	2000.
Specific Heat Ratio	1.225	1.258	1.273	1.250
Covolume (cc/g)	0.996	1.009	0.357	1.084
Density (g/cc)	1.578	0.941	0.941	1.661
Web (cm)	0.178	0.32	0.32	0.20
Number of perforations	7	1	1	0
Burn Rate Coef. (cm/(sec-MPa)	0.150	0.100	0.004	9947.
Burn Rate Exponent	0.95	1.00	1.00	0.0

Notes on Propellants:

- JA2 - Granular high energy propellant
- FNC - Felted Nitrocellulose Combustible Cartridge Case
- KC - Kraft Paper Liner for Cartridge Case
- BEN - Benite Igniter

The parametric calculations performed for the four propulsion options described below were done for two pairs of peak pressure and gun tube lengths. One is the standard case shown above; the other is an enhanced 120-mm gun postulated to operate at a nominal peak pressure of 579 MPa with a projectile travel of 6.274 meters. This may represent a practical upper bound for the growth potential of the current 120-mm gun.

1. IMPROVED CONVENTIONAL GUN

For the parametric analyses of the conventional gun, the complexities of the combustible case and ignition components were neglected and a solution using conventional, hexagonal, 19-perforated granular grains with JA2 propellant is shown. A revised version of the Baer-Frankle code,¹ called IBHVG2,² was used. IBHVG2 is a thermodynamic or lumped parameter interior ballistic code in which mass and energy conservation are explicitly treated, while the hydrodynamics of the two-phase gas flow are approximated by the Lagrange assumption of constant gas density. This propulsion option constitutes the baseline against which all others are to be compared.

2. CONSTANT PRESSURE GUN

The constant pressure gun represents the thermodynamic limiting performance of conventional gun propulsion. A special option of the IBHVG2 code allows either surface area or burning rate to be computed so that a specified pressure is maintained. It is the goal of consolidated and deterred propellant efforts to approach constant pressure operation. The thermodynamic parameters of the propellant were those for JA2 propellant, currently used in 120-mm ammunition.

3. SOLID PROPELLANT TRAVELING CHARGE GUN

The details of the traveling charge effect, its advantages and disadvantages, have been previously described.³ For this concept to work as desired, a propellant with very high burning rate characteristics is attached to the projectile as shown schematically in Figure 1. The rapidly burning propellant produces thrust which, combined with the base pressure, accelerates the projectile. Typically, effective burning rates on the order of 100 to 200 m/s are required. The developmental efforts to obtain such propellants have been described by Juhasz.⁴

SEQUENCE OF OPERATION-TRAVELING CHARGE GUN




Figure 1. Traveling Charge Gun Concept

The parametric calculations for this propulsion concept were performed by a computer model called BRTC.⁵ It is a one-dimensional, single phase flow model which assumes a thin reaction zone and planar surface regression. It assumes a linear elastic solid propellant response and includes a simple treatment of wall friction and heat loss. A special feature called the constant stress option was exercised. In this option the combined thrust plus projectile base pressure were kept constant. The propellant thermodynamic parameters of JA2 were used for all BRTC calculations.

4. REGENERATIVE LIQUID PROPELLANT GUN

Details of the RLPG concept and experimental progress have been described by Morrison et al.⁶ In the RLPG, a liquid propellant behind a piston is injected through orifices in the piston into a hot, high pressure combustion chamber. A schematic of the RLPG is shown in Figure 2. The high pressure LP spray is ignited in the hot chamber producing pressure which accelerates a projectile downbore. The piston area difference between the chamber and the reservoir maintains a positive pressure difference required for injecting the LP without external pressurization.




Figure 2. RLPG Gun Concept

For the RLPG performance calculations a computer model, RLPTC, developed by Gough⁷ was used. In this model the LP reservoir and the combustion chamber are treated as lumped parameter regions, while the barrel is modeled as a two-phase, one-dimensional flow region. Calculations were made for two propellants, a hypothetical "liquid JA2" and LGP 1845, a hydroxylammonium nitrate based liquid monopropellant of somewhat lower energy than JA2; see Table 2. The parameters adjusted in the calculations were total LP injection area, initial gas pressurization during the ignition phase, and shot start pressure. Piston mass was scaled from 105-mm experimental data. Parameters were adjusted to give nearly constant chamber pressure operation until propellant burnout. For this study, combustion of the injected liquid propellant was assumed to be instantaneous.

TABLE 2. Propulsion Systems Summary Baseline Cases

GUN AND PROJECTILE CHARACTERISTICS				
Projectile Weight (kg)	7.1			
Bore Diameter (mm)	120			
Maximum Projectile Travel (m)	4.75			
Chamber Volume (l)	9.75			
Propulsion System	Conv.	CP	SPTC	RLPG
Propellant	JA2	JA2	JA2	LGP 1845
Weight (kg)	7.51	6.92	7.21	8.78
Impetus (J/g)	1140.	1140.	1140.	973.
Flame Temperature (K)	3410.	3410.	3410.	2695.
Specific Heat Ratio	1.225	1.225	1.225	1.215
Covolume (cc/g)	0.996	0.996	0.996	0.609
Density (g/cc)	1.578	1.578	1.578	1.462
PERFORMANCE				
Muzzle Velocity (m/s)	1650	1650	1650	1650
Max. Chamber Pressure (MPa)	505	505	505	505
Max. Gun Pressure (MPa)	505	505	505	705
Max. Proj. Base Pressure (MPa)	337	505	505	505

Figure 3 illustrates the interior ballistic trajectory for the 120-mm gun using conventional granular gun propellant. This is a typical plot for a high performance gun. The upper pressure-travel curve shows the breech pressure with a peak value of 505 MPa. The lower curve shows the projectile base pressure. It is the area under this second curve which represents the work done on the projectile, hence its kinetic energy. The pressure difference between the two curves is due to the finite speed of sound in this hot, high pressure medium. The magnitude of the pressure difference is determined by the choice of the Pidduck-Kent approximation in IBHVG2.




Figure 3. Interior Ballistic Trajectory for Conventional 120-mm Gun Propulsion Using 19-Perforated JA2 Propellant.

Figure 4 illustrates the ideal interior ballistic trajectory for the 120-mm gun assuming constant pressure operation. For a given set of interior ballistic parameters using conventional propellant and propulsion technology, one cannot obtain better results in terms of efficiency. The burning rate is calculated to give the necessary gas generation rate required to keep the breech pressure constant in the face of the ever expanding volume as the projectile moves downbore. At propellant burnout the problem is reduced to adiabatic expansion. The pressure gradient between the breech and the projectile base is, of course, very similar to the standard conventional propellant case.




Figure 4. Interior Ballistic Trajectory for an Ideal 120-mm Constant Pressure Gun Using JA2 Propellant.

The interior ballistic trajectory of a 120-mm gun driven by the traveling charge effect is illustrated in Figure 5. As mentioned earlier, in this concept a cylinder of very high burning rate propellant (VHBR) attached to the projectile, provides the propulsion necessary to accelerate the projectile. In this plot we show the stress, breech, and projectile base pressures as a function of projectile travel. In this simulation the gun chamber is pressurized to its peak value before motion of the projectile is permitted. Thereafter, the burning rate is calculated to keep the total stress at the propellant surface constant until burnout. This stress pressure is the sum of the impulse, or thrust, due to the rapidly regressing propellant surface and the gas pressure near the same surface. While the stress pressure remains constant, the breech and projectile base pressures decrease with increasing projectile travel.




Figure 5. Interior Ballistic Trajectory for an Idealized 120-mm Traveling Charge Gun

Figure 6 illustrates the interior ballistic trajectory of a 120-mm gun using the regenerative liquid propellant gun (RLPG). Shown in this plot are: (1) the liquid propellant reservoir pressure; (2) the combustion chamber pressure; (3) the projectile base pressure; and (4) projectile velocity; all are shown as a function of projectile travel. The maximum chamber pressure is kept at the same peak value of 505 MPa as in the previous three cases. However, the peak LP reservoir pressure is 36% higher due to the piston area ratio between the chamber and the LP reservoir side of the piston. There is also a pressure gradient between the chamber and the base of the moving projectile. This pressure gradient is analogous to that exhibited in a conventional gun and is due to the momentum loss in moving the combustion gases down the bore. A major assumption in this simulation is that the liquid propellant burns instantaneously and completely upon injection from the LP reservoir into the combustion chamber.




Figure 6. Interior Ballistic Trajectory for a 120-mm RLP Gun Using LGP 1845 Propellant.

The effect of loading density on the muzzle velocities for the four propulsion systems is illustrated in Figures 7 and 8. The constraints are fixed peak chamber pressure, projectile travel, JA2 propellant thermodynamics, projectile weight, and chamber volume. Figure 7 shows the results for the current 120-mm gun, and Figure 8 shows the results for the enhanced 120-mm gun with its longer barrel and higher operating pressure. The chamber volume is kept the same for both the current and enhanced systems. We also present a comparison of the RLPG performance potential for a current liquid propellant in Figure 9. The two curves are for the hypothetical "liquid JA2" propellant and LGP 1845.




Figure 7. Effect of Increased Loading Density on Performance of Standard 120-mm Gun Using Four Propulsion Options.




Figure 8. Effect of Increased Loading Density on Performance of Enhanced 120-mm Gun with Four Propulsion Options.




Figure 9. Effect of Propellant Thermochemistry on Performance of a 120-mm RLP Gun.

III. DISCUSSION

The results in this study indicate that for loading densities above about 0.9 g/cc, the best performance in the 120-mm gun is obtained by using the traveling charge gun, followed by the constant pressure gun, the RLPG and the conventional gun.

The constant breech pressure for the solid and regenerative gun simulations, and the constant stress solid traveling charge gun simulation represent an estimate of the upper limits on the performance one can achieve with these concepts. Given that different levels of physical approximations are made in the computer simulations used in this study, the magnitude of the resulting velocity differences at a given loading density may not be exact. However, the rank ordering of the results agrees with our intuitive understanding of the ballistic processes for the three advanced propulsion concepts. At high muzzle velocities, the available propellant is burned most effectively at the projectile base (SPTC), least effectively at the breech (RLPG), and with moderate effectiveness in the lumped parameter interior ballistic codes for the conventional and CP gun where it is assumed to be distributed between the breech and the base of the projectile.

It is also intuitively obvious that all propulsion options must collapse at low loading densities to the same muzzle velocity. When burnout of the propellant occurs before projectile motion begins, all expansion work is done on the projectile alone, and, therefore, the same muzzle velocity is obtained for all concepts.

The physical differences in the four propulsion techniques considered in this study are apparent in both Figures 7 and 8. However, these differences are more pronounced in the latter. At low loading densities, 0.7-0.9 g/cc, the traveling charge results in velocities comparable to the conventional charge. Above 0.9 g/cc, the benefit of the traveling charge at very high velocities becomes increasingly apparent. In contrast, the conventional result reaches a maximum and begins to decrease above 0.9 g/cc. The two constant pressure concepts give almost identical results below 0.9 g/cc, and both provide higher predicted velocities than either the conventional or SPTC cases. Above 0.9 g/cc, the RLPG curve flattens out rapidly while the constant pressure solid propellant curve continues to rise. In the constant pressure case, the imposition of the Pidduck-Kent pressure gradient implies that propellant combustion is distributed along the tube in such a way as to maintain the imposed gradient.

1. IMPROVED CONVENTIONAL GUN

The relatively flat pressure vs. travel curve shown in Figure 3 is the direct result of the progressive, 19-perforated grain geometry. In fact, the similarity to the CP gun curves of Figure 4 are striking. Except for the initial pressurization region, the curves are virtually the same. The ballistic efficiency of the optimized conventional gun is about 92% that of the constant pressure gun, or, in terms of velocity, the muzzle velocity of

the optimized conventional gun is 96% that of the CP gun for the baseline case.

Figure 8 shows that the optimum loading density for the standard conventional gun is about .9 g/cc. Putting more propellant in the chamber actually results in a lower velocity because unburned propellant is being ejected. For the enhanced 120-mm gun shown in Figure 9, the optimum loading density increases to 1.0 g/cc, and the conventional gun curve stays closer to the CP gun limiting curve. As the peak operating pressure and the expansion ratio increase, the two curves will eventually collapse into one.

In a separate calculation, the muzzle velocity increase due to a longer gun tube alone is computed to be 5%, while the combined effect of a longer gun and higher pressure at the same loading density results in a 9% increase in velocity. This is a very desirable level of improvement.

In all of these calculations, we assume that the sabot mass is insensitive to changes in peak acceleration. In reality, increased peak base pressures require increased sabot mass which results in a reduced muzzle velocity. Fortunately, the trade-off is usually a net gain for modest changes.

2. CONSTANT PRESSURE GUN

As previously mentioned, the CP gun represents the performance limit for conventional gun propulsion for any given set of gun parameters. The CP muzzle velocity vs. loading density curves of Figures 7 and 8 show that large increases in velocity are possible at the high loading densities if one can find a way to burn the propellant in the required, highly progressive fashion. From a practical standpoint, the upper limit in loading density is about 1.25 g/cc for compacted or consolidated propellant. Indeed, experimental results suggest that for such propellants, the required surface area progressivity can be obtained through mechanical fracture and chemical deterrents.⁸ Increases in loading density beyond 1.25 g/cc do not result in any significant velocity increases in any case.

While perfect constant pressure operation may be desirable, little performance will be sacrificed by slight deviations from the ideal. If one assumes that the overall efficiency for a high loading density "CP" charge is comparable to that of a conventional charge, a 6% velocity gain over an optimized granular round is possible. In fact, 10% velocity increases have been experimentally demonstrated for consolidated charge rounds in several different calibers.⁸

3. SOLID PROPELLANT TRAVELING CHARGE GUN

Figures 8 and 9 show quite clearly that the traveling charge propulsion concept offers the greatest performance increase, if the required propellants were available. Research efforts to date, while showing progress, have not yet yielded a safe and practical solution to this problem.

The traveling charge effect becomes more efficient than the other propulsion options at the high velocities because less energy is wasted in accelerating gases. In the SPTC, gases exit the propellant surface at high velocities with respect to the surface but at nearly zero velocity with respect to the barrel. For the other propulsion options considered, the gases at the projectile base must move at the same velocity as the projectile. At propellant burnout, the energy acquired in accelerating the mass of solid propellant attached to the projectile is, of course, redistributed among internal energy of the gases, kinetic energy of the bullet and, to a more limited extent, kinetic energy of the gases, heat loss, and other small irreversible energy losses.

Figure 5 shows the rather intriguing drop in base pressure at propellant burnout. A common misconception of the traveling charge propulsion concept is that muzzle pressures must be exceedingly high. This is not necessarily the case. At burnout the gases near the projectile are virtually at rest with respect to the barrel, hence after burnout they must suddenly accelerate. This causes the substantial pressure drop. Of course, the expansion work done on the projectile also suffers. It therefore pays to delay burnout to within a few calibers of the muzzle by reducing the peak operating stress.

It is also clear that the traveling charge concept is of little value at moderate performance levels. Only when muzzle velocities on the order of 2000 m/s are required, does it make sense to consider this propulsion concept.

4. REGENERATIVE LIQUID PROPELLANT GUN

The loading density results for the RLPG show trends very similar to the CP gun. This is not surprising since the injection area for the RLPG is adjusted to maintain virtually constant chamber pressure as shown in Figure 6. Oscillations in the reservoir pressure are due to the response of the spring-mass system, formed by the reservoir and piston, to the imposed start-up conditions.⁹ In practice, low frequency spring-mass oscillations, similar to those in Figure 6 but much lower in amplitude, are observed in RLPG test firings.¹⁰ Much higher frequency oscillations related to the liquid jet breakup and combustion processes are also observed in RLPG firings in most calibers.¹⁰ It appears difficult to eliminate these oscillations completely. Due to the very high frequencies involved, breechblow hazards have not been associated with these oscillations as in solid propellant and bulk loaded liquid propellant guns.

The divergence of the RLPG curve from the CP curve in Figures 8 and 9 results from an interesting physical consideration. In the RLPG, gas generation takes place entirely in the chamber, and the pressure gradient in the barrel is defined by the acceleration of the combustion gases behind the projectile. Since a finite amount of time is required for communication between the combustion chamber and the projectile base, fluctuations in chamber pressure are not immediately sensed at the projectile base. In the case of the RLPG, it was observed that upon burnout a rarefaction wave moves from the breech toward the muzzle. If muzzle exit occurs before this wave

reaches the base of the projectile, the addition of more propellant to the system is superfluous. In fact, beyond a given travel, the projectile is no longer influenced by the conditions in the combustion chamber, i.e. pressure waves from the chamber cannot traverse the bore and overtake the projectile before it exits the muzzle. Therefore, any propellant burned after this critical projectile travel is reached, cannot contribute to an increase in muzzle velocity. This explains the flattening of the velocity vs. loading density curve for the RLPG. For the specific gun conditions used here, no increase in velocity is observed beyond a loading density of 1.05 g/cc.

It is important to note that, in the case of the RLPG, it is possible to obtain the desired propellant injection rate, and thus the gas generation rate required for constant pressure operation, purely by mechanical means. In fact, near-constant pressure operation has been demonstrated in experimental gun firings.¹¹

Figure 9 shows loading density results for both a real (LGP 1845) and the hypothetical liquid (JA2) propellant. In the high loading density region, a 4% velocity difference is noted between the high energy JA2 and the moderate energy, lower flame temperature and low vulnerability LGP 1845. This implies that an increase in propellant energy may be desirable for anti-armor applications of the RLPG. However, such increases in propellant energy are usually accompanied by a degradation in vulnerability characteristics. To some extent the velocity difference can be compensated for by increasing the chamber volume, a degree of freedom not explored in this study.

Finally, we recognize that the intrinsic self-pumping aspect of the RLPG is achieved at the expense of a liquid propellant reservoir pressure higher than the peak chamber pressure. This consideration will increase the overall weight of an RLPG cannon. This increase may indeed be minimal in a system if total ammunition and gun weight are considered, due to the packing efficiency of LP.

IV. SUMMARY

Finally, Table 3 summarizes the best performance levels achieved for the different propulsion options. It appears that the current standard 120-mm round is quite well designed. Little margin for growth is possible by conventional means without changing some of the ground rules such as peak pressure and travel. Using unconventional propulsion techniques, muzzle velocity increases up to 25% over a well designed conventional round appear possible in principle. In practice, a 10 to 15% increase is likely to be the upper limit. It should be noted that the relative increases are by no means universal. They are very much system and ground rule dependent and must, therefore, be used in proper context.

TABLE 3. Best Performance of Each Propulsion Option

Propulsion Option	STANDARD 120-mm				ENHANCED 120-mm			
	CONV	CP	SPTC	RLPG	CONV	CP	SPTC	RLPG
Max. Missile Velocity (m/s)	1700.	1874.	2084.	1778.	1864.	2080.	2283.	1814
Loading Density (g/cc)	0.80	1.30	1.20	1.05	1.00	1.30	1.30	1.05
% Increase	base	10.2	22.6	~~0.5~~ 4.6	0.6	21.2	34.3	12.6

REFERENCES

1. Baer, P. and Frankle, J., "The Simulation of Interior Ballistic Performance of Guns By Digital Computer Program," Ballistic Research Laboratory Report R 1183, December 1962.
2. Anderson, R. and Fickie, K., "IBHVC2 - A User's Guide," BRL Report in preparation.
3. May, I.W., Baran, A., Baer, P., and Gough, P., "The Traveling Charge Effect," Ballistic Research Laboratory Memorandum Report ARBRL-MR-03034, July 1980.
4. Juhasz, A., May, I., Aungst, W., and Lynn, F., "Combustion Studies of Very High Burning Rate Propellants," Ballistic Research Laboratory Memorandum Report ARBRL-MR-03152, February 1982.
5. Gough, P., "A Model of the Traveling Charge," Ballistic Research Laboratory Contract Report ARBRL-CR-00432, July 1980.
6. Morrison, W.F., Knapton, J.D., and Klingenberg, G., "Liquid Propellants for Gun Applications," Proceedings of the Seventh International Symposium on Ballistics, 1983.
7. Gough, P., "A Model of the Interior Ballistics of Hybrid Liquid Propellant Guns," Paul Gough Associates Report PGA-TR-83-4, September 1983.
8. Scott, L., private communication.
9. Baer, P.G. and Morrison, W.F., "Modeling of High Frequency Oscillations in the 105-mm Regenerative Liquid Propellant Gun," Twentieth JANNAF Combustion Meeting, CPIA Publication 383 (1983).
10. Mandzy, J., Magoon, I., Morrison, W.F., and Knapton, J.D., "Preliminary Report on Test Firings of a 105-mm Regenerative Fixture," Twentieth JANNAF Combustion Meeting, CPIA Publication 383 (1983).
11. Morrison, W.F., Bulman, M. J., Baer, P.G., and Banz, C.F., "The Interior Ballistics of Regenerative Liquid Propellant Guns," Proceedings of the 1984 JANNAF Propulsion Meeting.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	3	Director Benet Weapons Laboratory Armament R&D Center US Army AMCCOM ATTN: SMCAR-LCB-TL E. Conroy A. Graham Watervliet, NY 12189
1	Director Defense Advanced Research Projects Agency ATTN: H. Fair 1400 Wilson Boulevard Arlington, VA 22209	1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-7300
1	HQDA DAMA-ART-M Washington, DC 20310	1	Commander US Army Aviation Research and Development Command ATTN: AMSAV-E 4300 Goodfellow Blvd. St. Louis, MO 63120
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001	1	Commander Materials Technology Lab US Army Laboratory Cmd ATTN: SLCMT-MCM-SB M. Levy Watertown, MA 02172-0001
13	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-TSS SMCAR-TDC SMCAR-SCA, B. Brodman R. Yalamanchili SMCAR-AEE-B, D. Downs A. Beardell SMCAR-LCE, N. Slagg SMCAR-LCS, W. Quine A. Bracuti J. Lannon SMCAR-PSS-A, R. Price L. Frauen SMCAR-PSA-S, H. Liberman Picatinny Arsenal, NJ 07806-5000	1	Director US Army Air Mobility Rsch. and Development Lab. Ames Research Center Moffett Field, CA 94035
		1	Commander US Army Communications Electronics Command ATTN: AMSEL-ED Fort Monmouth, NJ 07703
		1	Commander ERADCOM Technical Library ATTN: STST-L Ft. Monmouth, NJ 07703-5301

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Harry Diamond Labs ATTN: DELHD-TA-L 2800 Powder Mill Rd Adelphi, MD 20783	1	Commander Armament Rsch & Dev Ctr US Army Armament, Munitions and Chemical Command ATTN: SMCAR-CCS-C, T Hung Picatinny Arsenal, NJ 07806-5000
1	Commander US Army Missile Command Rsch, Dev, & Engr Ctr ATTN: AMSMI-RD Redstone Arsenal, AL 35898	1	Commandant US Army Field Artillery School ATTN: ATSP-CMW Ft Sill, OK 73503
1	Commander US Army Missile & Space Intelligence Center ATTN: AIAMS-YDL Redstone Arsenal, AL 35898-5500	1	Commandant US Army Armor Center ATTN: ATSB-CD-MLD Ft Knox, KY 40121
1	Commander US Army Belvoir R&D Ctr ATTN: STR3E-WC Tech Library (Vault) 8-315 Fort Belvoir, VA 22060-5606	1	Commander US Army Development and Employment Agency ATTN: MODE-TED-SAB Fort Lewis, WA 98433
1	Commander US Army Tank Automotive Cnd ATTN: AMSTA-TSL Warren, MI 48397-5000	1	Commander Naval Surface Weapons Center ATTN: D.A. Wilson, Code G31 Dahlgren, VA 22448-5000
1	Commander US Army Research Office ATTN: Tech Library P.O. Box 12211 Research Triangle Park,NC 27709-2211	1	Commander Naval Surface Weapons Center ATTN: Code G33, J. East Dahlgren, VA 22448-5000
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missile Range NM 88002	2	Commander US Naval Surface Weapons Ctr. ATTN: O. Dangel K. Thorsted Silver Spring, MD 20902-5000
1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905	1	Commander Naval Weapons Center China Lake, CA 93555-6001
		1	Commander Naval Ordnance Station ATTN: C. Dale Code 5251 Indian Head, MD 20640

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Superintendent Naval Postgraduate School Dept of Mechanical Eng. ATTN: Code 1424, Library Monterey, CA 93943	10	Central Intelligence Agency Office of Central Reference Dissemination Branch Room GE-47 HQS Washington, DC 20502
1	APWL/SUL Kirtland AFB, NW 87117	1	Central Intelligence Agency ATTN: Joseph E. Backofen HQ Room 5F22 Washington, DC 20505
1	Air Force Armament Lab ATTN: APATL/DLODL Eglin, AFB, FL 32542-5000	4	Bell Aerospace Textron ATTN: P. Boorady K. Berman A.J. Friona J. Rockenfeller Post Office Box One Buffalo, NY 14240
1	APOSR/NA (L. Caveny) Bldg. 410 Bolling AFB, DC 20332	1	Calspan Corporation ATTN: Tech Library P.O. Box 400 Buffalo, NY 14225
1	Commandant USAFAS ATTN: ATSF-TSM-CN Ft Sill, OK 73503-5600	7	General Electric Ord. Sys Dpt ATTN: J. Mandzy, OP43-220 R.E. Mayer H. West M. Bulman R. Pate I. Magoon J. Scudiere 100 Plastics Avenue Pittsfield, MA 01201-3698
1	US Bureau of Mines ATTN: R.A. Watson 4800 Forbes Street Pittsburgh, PA 15213	1	General Electric Company Armament Systems Department ATTN: D. Maher Burlington, VT 05401
1	Director Jet Propulsion Lab ATTN: Tech Libr 4800 Oak Grove Drive Pasadena, CA 91109	1	IITRI ATTN: Library 10 W. 35th St. Chicago, IL 60616
2	Director National Aeronautics and Space Administration ATTN: MS-603, Tech Lib MS-86, Dr. Povinelli 21000 Brookpark Road Lewis Research Center Cleveland, OH 44135	1	Olin Chemicals Research ATTN: David Gavin P.O. Box 586 Cheshire, CT 06410-0586
1	Director National Aeronautics and Space Administration Manned Spacecraft Center Houston, TX 77058		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Olin Corporation ATTN: Victor A. Corso Dr. Ronald L. Dotson P.O. Box 30-9644 New Haven, CT 06536	2	University of Delaware Department of Chemistry ATTN: Mr. James Cronin Professor Thomas Brill Newark, DE 19711
1	Paul Gough Associates ATTN: Paul Gough PO Box 1614 Portsmouth, NH 03801	1	U. of ILLinois at Chicago ATTN: Professor Sohail Murad Dept of Chemical Eng Box 4348 Chicago, IL 60680
1	Safety Consulting Engr ATTN: Mr. C. James Dahn 5240 Pearl St. Rosemont, IL 60018	1	U. of Maryland at College Park ATTN: Professor Franz Kasler Department of Chemistry College Park, MD 20742
1	Science Applications, Inc. ATTN: R. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364	1	U. of Missouri at Columbia ATTN: Professor R. Thompson Department of Chemistry Columbia, MO 65211
1	Sunstrand Aviation Operations ATTN: Dr. Owen Briles P.O. Box 7002 Rockford, IL 61125	1	U. of Michigan ATTN: Prof. Gerard M. Faeth Department of Aerospace Engineering Ann Arbor, MI 48109-3796
1	Veritay Technology, Inc. ATTN: E. B. Fisher 4845 Millersport Highway, P.O. Box 305 East Amherst, NY 14051-0305	1	U. of Missouri at Columbia ATTN: Professor F. K. Ross Research Reactor Columbia, MO 65211
1	Director Applied Physics Laboratory The Johns Hopkins Univ. Johns Hopkins Road Laurel, Md 20707	1	U. of Missouri at Kansas City Department of Physics ATTN: Prof. R.D. Murphy 1110 East 48th Street Kansas City, MO 64110-2499
2	Director Chemical Propulsion Info Agency The Johns Hopkins Univ. ATTN: T. Christian Tech Lib Johns Hopkins Road Laurel, MD 20707	1	Pennsylvania State University Dept. of Mechanical Eng ATTN: K. Kuo University Park, PA 16802

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Princeton Combustion Rsch Laboratories, Inc. ATTN: N.A. Messina M. Summerfield 475 US Highway One North Monmouth Junction, NJ 08852		
1	University of Arkansas Department of Chemical Engineering ATTN: J. Havens 227 Engineering Building Fayetteville, AR 72701		

Aberdeen Proving Ground

Dir, USAMSAA
ATTN: AMXSY-D
AMXSY-MP, H. Cohen

Cdr, USATECOM
ATTN: AMSTE-TO-F

CDR, CRDEC, AMCCOM
ATTN: SMCCR-RSP-A
SMCCR-MU
SMCCR-SPS-IL

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number _____ Date of Report _____

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. How specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS Name _____
 Organization _____
 Address _____
 City, State, Zip _____

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD ADDRESS Name _____
 Organization _____
 Address _____
 City, State, Zip _____

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

FOLD HERE

Director
US Army Ballistic Research Laboratory
ATTN: DRXBR-OD-ST
Aberdeen Proving Ground, MD 21005-5066




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
US Army Ballistic Research Laboratory
ATTN: DRXBR-OD-ST
Aberdeen Proving Ground, MD 21005-9989



FOLD HERE

END

Feb.

1988

DTIC

UNCLASSIFIED
Technical
Report
distributed by



DEFENSE

TECHNICAL

INFORMATION

CENTER



DEFENSE LOGISTICS AGENCY
Cameron Station
Alexandria, Virginia 22304-6145

UNCLASSIFIED

UNCLASSIFIED

NOTICE

We are pleased to supply this document in response to your request.

The acquisition of technical reports, notes, memorandums, etc., is an active, ongoing program at the **Defense Technical Information Center (DTIC)** that depends, in part, on the efforts and interest of users and contributors.

Therefore, if you know of the existence of any significant reports, etc., that are not in the **DTIC** collection, we would appreciate receiving copies or information related to their sources and availability.

The appropriate regulations are Department of Defense Directive 3200.12, DoD Scientific and Technical Information Program; Department of Defense Directive 5200.20, Distribution Statements on Technical Documents (*amended by Secretary of Defense Memorandum, 18 Oct 1983, subject: Control of Unclassified Technology with Military Application*); Military Standard (*MIL-STD*) 847-B, Format Requirements for Scientific and Technical Reports Prepared by or for the Department of Defense; Department of Defense 5200.1R, Information Security Program Regulation.

Our Acquisition Section, **DTIC-FDAB**, will assist in resolving any questions you may have. Telephone numbers of that office are: (202) 274-6847, (202) 274-6874 or Autovon 284-6847, 284-6874.

DO NOT RETURN THIS DOCUMENT TO DTIC

**EACH ACTIVITY IS RESPONSIBLE FOR DESTRUCTION OF THIS
DOCUMENT ACCORDING TO APPLICABLE REGULATIONS.**

UNCLASSIFIED