

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited	
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE				
4. PERFORMING ORGANIZATION REPORT NUMBER(S) ONR 1987			5. MONITORING ORGANIZATION REPORT NUMBER(S)	
6a. NAME OF PERFORMING ORGANIZATION National Bureau of Standards		6b. OFFICE SYMBOL (If applicable)		7a. NAME OF MONITORING ORGANIZATION Office of Naval Research
6c. ADDRESS (City, State, and ZIP Code) Ultrasonic Standards Group Sound, Al47 Gaithersburg, MD 20899		7b. ADDRESS (City, State, and ZIP Code) Physics Division - Code 1112 Arlington, VA 22217 - 5000		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER N00014-87-F-0006
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS		
		PROGRAM ELEMENT NO. 61153N11	PROJECT NO.	TASK NO. 4126303
		WORK UNIT ACCESSION NO.		
11. TITLE (Include Security Classification) Ultrasonic Measurements Research: Progress in 1987 (Unclassified)				
12. PERSONAL AUTHOR(S) Breckenridge, F.R.; Proctor, T.M.; Hsu, N.N.; Greenspan, M. and Eitzen, D.G. (NBS)				
13a. TYPE OF REPORT Annual Summary		13b. TIME COVERED FROM Sep 86 TO Aug 87		14. DATE OF REPORT (Year, Month, Day) 87-07-31
15. PAGE COUNT 10				
16. SUPPLEMENTARY NOTATION F.R. Breckenridge: Tel. (301) 975-6628. This is a summary. References give more complete reporting				
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP		
20	01		Acoustic emission, calibration, physical acoustics, transducers, ultrasonics.	
17	01			
19. ABSTRACT (Continue on reverse if necessary and identify by block number)				
The purpose of this work is to make accurate measurements in acoustic emission (AE) and ultrasonics and to relate all measurements to national standards. The problems presently under study are: (1) the characterization of AE transducers, (2) the determination of the transfer characteristics (Green's functions) of media and structures, (3) the development of well defined sources, (4) the development of high fidelity transducers, and (5) the development of improved ultrasonic and acoustic emission techniques. Progress in FY 87 is described. The AE transducer calibration facility has been improved to maintain it as a world-class facility. The effect of test specimen characteristics have been determined both by analysis and by experiment. The feasibility of experimentally determining mechanical Green's functions has been demonstrated. A high fidelity transducer has been developed to measure dynamic, in-plane motion; its response agrees well with theoretical predictions.				
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a. NAME OF RESPONSIBLE INDIVIDUAL L.E. Hargrove			22b. TELEPHONE (Include Area Code) (202) 696-4221	
			22c. OFFICE SYMBOL ONR Code 1112	

July 31, 1987

Ultrasonic Measurements Research: Progress in 1987 (Unclassified)

F.R. Breckenridge, T.M. Proctor, N.N. Hsu,
M. Greenspan, and D.G. Eitzen
Automated Production Technology
Center for Manufacturing Engineering
National Bureau of Standards

ABSTRACT

The purpose of this work is to make accurate measurements in acoustic emission (AE) and ultrasonics and to relate all measurements to national standards. The problems presently under study are: (1) the characterization of AE transducers, (2) the determination of the transfer characteristics (Green's functions) of media and structures, (3) the development of well defined sources, (4) the development of high fidelity transducers, and (5) the development of improved ultrasonic and acoustic emission techniques.

Progress in FY 87 is described. The AE transducer calibration facility has been improved to maintain it as a world-class facility. The effect of test specimen characteristics have been determined both by analysis and by experiment. The feasibility of experimentally determining mechanical Green's functions has been demonstrated. A high fidelity transducer has been developed to measure dynamic, in-plane motion; its response agrees well with theoretical predictions.

CALIBRATION AND RELATED ACTIVITIES

The AE transducer calibration facility continues to be an indispensable tool for the development of special transducers as well as for analyzing the performance parameters of AE transducers. For this reason, considerable effort has been expended to upgrade the system.

The transient recorders that were originally used in the calibration system were nominal eight bit devices, which have an inherent accuracy limitation of about 1 % and could be expected to introduce quantization noise of a significant amount into the calibration signal. Further problems existed because at high slew rates (typical of the calibration signals) the original recorder's performance degraded to that of a four bit recorder. These transient recorders have been replaced by devices having nominal ten bit accuracy, better linearity, and much superior slewing performance.

Originally the calibration data analysis and storage were carried out on a mainframe computer at another location. This mainframe computer became obsolete and, for the purposes of the AE calibration, has been replaced by an IBM compatible computer, dedicated to the purpose. The new computer is advantageous because it is more convenient and the data are now readily transferable to other IBM compatible computers.

Replacement of the transient recorders and computer necessitated complete rewriting of the software associated with the calibration. The rewriting has now been accomplished, and the calibration process has been speeded up by this.

Further improvements involving replacement of the original unity-gain front-end amplifier/guard ring driver by a low noise charge amplifier are being considered. The charge amplifier has been obtained, and a second stage quiet voltage amplifier to follow the charge amplifier has been designed and built.

The prototype secondary calibration scheme which we are constructing involves the use of an NBS conical transducer as the source and another NBS conical transducer as the transfer standard. The process is viewed as being a comparison calibration. We are attempting to design the system to avoid the use of any very expensive or esoteric equipment. Hence, an inexpensive steel plate serves as the transfer medium. By using a tone-burst source and some simple gating circuitry, it is hoped to obviate using expensive transient recorders. Part of the circuitry has now been constructed, and the steel plate has been tested. Results of one such test of the steel plate are shown in Fig. 1.

TRANSDUCER LOADING EFFECT

When a transducer is attached to a structure, it becomes part of the structure. Motion of the structure in the vicinity of the transducer is modified by the transducer's presence. In calibrating a transducer, we consider the acoustical input signal to the transducer to be the motion of the surface of the structure that would have occurred if the transducer had not been present. The actual motion of the face of the transducer depends upon the interaction of the mechanical impedance of the structure with that of the transducer. The conditions of the calibration are such that the acoustical signal travels through the calibration block as in a semi-infinite medium. A calibration performed using a given structure will be valid on another structure only if the mechanical impedances of the structures as seen by the transducer are the same.

For a structure that is large enough to act like a semi-infinite medium, the mechanical impedance seen by the transducer depends on the elastic properties and density of the structure material. We have attempted to answer the question of how much the properties of the material affect the calibration results. In other words, for example, if a transducer is calibrated on a steel block, how badly in error would the calibration be if the transducer were used on a glass block?

To determine how serious this effect is, transducers were calibrated on our steel block and also subjected to surface-pulse waveforms in aluminum, glass, and methyl methacrylate plastic. The surface-pulse waveforms were generated by a pencil-break apparatus having provision for measuring the force. For each material, the surface pulse waveform was calculated at the transducer location. This calculated waveform convolved with the waveform measured for a typical pencil break event was considered to be the input to the transducer under test in each case. These tests were performed on two transducers: a commercial AE/UT unit and an NBS conical transducer. The results are shown in Figs 2 and 3. Analysis of the NBS conical transducer has been carried out by M. Greenspan [1], and the theoretical results for a transducer of this type on

the same media are shown in Fig 4.

The experimental results are very approximate because the sizes of the blocks were not as large as would be desirable, and because no capacitance transducer was used as a check on the calculated waveforms. However, it is clear that the effect of loading is significant for glass and aluminum, and more than an order of magnitude for the plastic (all relative to steel). A summary of the results is given in Table I.

Table I. Reduction of transducer sensitivity owing to the material to which it is coupled. Values for the transducers are rms sensitivities for the range 0.1 MHz to 1 MHz relative to the value obtained on steel. Values of ρc and E are relative to those for steel.

	ALUMINUM	GLASS	PMMA
AE/UT transducer	0.379	0.425	0.015
NBS conical (experiment)	0.595	0.447	0.039
NBS conical (theory)	0.580	0.523	0.068
ρc	0.370	0.304	0.069
E	0.331	0.308	0.028

It appears that, for work on media having relatively low elastic moduli, it would be desirable to have transducers with relatively higher internal compliance than those now available. It would also be desirable to have a calibration system designed around a block of a compliant medium, such as PMMA.

TRANSDUCER DEVELOPMENT

The development of transducers for accurate measurement of both in-plane and out-of-plane displacement on high modulus solids has progressed well [2,3,4,5]. The theory will be useful in the design of transducers similar to the NBS conical transducers, but optimized for other applications. For example, transducers might be optimized for better high frequency response or for use on materials having low acoustic impedance (plastic).

The transducers have become useful tools for the purposes of secondary calibration, determination of the characteristics of sources, or as sources themselves. The conical transducer has also been used as the basis for development of a new impact/echo technique for detecting defects in lossy materials. Feasibility was demonstrated for concrete as part of another program at NBS[6].

One model of a transducer for detecting in-plane displacement has been completed and demonstrated. Its output has been compared with theoretically predicted waveforms (Fig. 5). The agreement is satisfying.

ADDITIONAL INFORMATION

Additional information is detailed in references 7 through 9.

SUMMARY

The AE calibration facility has been improved by the replacement of the two transient recorders by new ones having superior performance. The facility also now has a dedicated IBM compatible computer, and faster calibration processing programs.


A study was made of one aspect of transducer performance: the interactive effect between the transducer and the medium on which it is placed. The study shows that the sensitivity of the the transducer, as defined by the AE calibration, is altered significantly by the elastic properties of the medium. In some cases the effect is more than an order of magnitude.


The design of basic in-plane and out-of-plane high fidelity displacement transducers has been satisfactorily completed. The basic theory for the out-of-plane transducer is also complete. Further extensions of the design principles are contemplated.


REFERENCES


- [1] M. Greenspan, "The NBS Conical Transducer: Analysis", J. Acoust. Soc. Am., 81(1), 173-183, Jan. 1987.
- [2] T. M. Proctor, "An improved Piezoelectric Acoustic Emission Transducer", J. Acoust. Soc. Am., 71(5), 1163-1168, May 1982.
- [3] T. M. Proctor, "Some Details on the NBS Conical Transducer", J. Acoust. Emission, 1(3), 173-178, July 1982.
- [4] T. M. Proctor, "More Recent Improvements on the NBS Conical Transducer", J. Acoust. Emission, 5(4), 134-142, Oct-Dec 1986.
- [5] T. M. Proctor, "An Improved Piezoelectric Horizontal Displacement Transducer for Acoustic Emission", for publication in J. Acoust. Emission.
- [6] M. Sansalone, N. J. Carino, and N. N. Hsu, "A Finite Element Study of the Interaction of Transient Stress Waves with Planar Flaws", NBS Journal of Research, 92(4), 279-290, July-Aug. 1987.
- [7] F. R. Breckenridge, T. M. Proctor, N. N. Hsu, and D. G. Eitzen, "Some Notions Concerning the Behavior of Transducers", Proceedings of the 8th International Acoustic Emission Symposium, Tokyo, Japan, 675-684, Oct, 1986.
- [8] N. N. Hsu, "Dynamic Green's Functions of an Infinite Plate - A Computer Program", NBS Internal Report, NBSIR 85-3234, Aug. 1985.
- [9] A. S. Carasso and N. N. Hsu, "Probe Waveforms and Deconvolution in the Experimental Determination of Elastic Green's Functions", SIAM J. Appl. Math. 45(3) 369-382, June 1985.

- Fig. 1 Comparison of experimental waveform (lower trace) and calculated waveform for a steel plate. Conditions: source, capillary break; receiver, NBS conical transducer; plate thickness, 33 mm; source and receiver on same side, separated by 3 plate thicknesses. Calculations are performed using the program of reference 8.
- Fig. 2 Approximate calibration of an AE/UT transducer done on blocks of four different materials. A pencil break was the source for all except the steel block calibration. The results were compensated for the pencil-break waveform.
- Fig. 3 Approximate calibration of an NBS conical transducer. Conditions are the same as in Fig. 2.
- Fig. 4 Calculated sensitivity of the NBS conical transducer of Fig. 3 on four different materials. Calculations are based on the theory of reference 1.
- Fig. 5 Comparison of measured tangential displacement (lower trace) and theoretical waveform for a large steel block.










5

REFERECE DISPLACEMENT. HORIZONTAL. PIEZO. 585



VOLTAGE RESPONSE - NBS "202 FINAL VERSION

