

2

**AD-A194 222**

AFWAL-TR-87-4114

DTIC FILE COPY



**FEASIBILITY STUDY FOR THE APPLICATION  
OF AN EASY-FIX METHOD FOR REDEPLOYING  
DAMAGED ISO TACTICAL SHELTERS**

Daniel R. Bowman  
University of Dayton Research Institute  
300 College Park Avenue  
Dayton, OH 45469

January 1988

Interim Report for Period January 1986 to February 1987

Approved for Public Release; Distribution Unlimited.

**DTIC**  
**ELECTE**  
**APR 26 1988**  
**S D**  
**E**

MATERIALS LABORATORY  
AIR FORCE WRIGHT AERONAUTICAL LABORATORIES  
AIR FORCE SYSTEMS COMMAND  
WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433-6533

88 4 25 161


NOTICE


When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely Government-related procurement, the United States Government incurs no responsibility or any obligation whatsoever. The fact that the Government may have formulated or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication, or otherwise in any manner construed, as licensing the holder, or any other person or corporation; or as conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This report has been reviewed by the Office of Public Affairs (ASD/PA) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nationals.

This technical report has been reviewed and is approved for publication.

FOR THE COMMANDER

  
ROBERT B. URZI  
Air Force Project Engineer

  
THEODORE REINHART, Chief  
Materials Engineering Branch  
Systems Support Division  
Materials Laboratory

"If your address has changed, if you wish to be removed from our mailing list, or if the addressee is no longer employed by your organization, please notify AFWAL/MLSE, Wright-Patterson AFB, OH 45433-6533 to help us maintain a current mailing list."

Copies of this report should not be returned unless return is required by security considerations, contractual obligations, or notice on a specific document.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

## REPORT DOCUMENTATION PAGE

1a REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS			
2a SECURITY CLASSIFICATION AUTHORITY			3 DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.			
2b DECLASSIFICATION/DOWNGRADING SCHEDULE						
4 PERFORMING ORGANIZATION REPORT NUMBER(S) UDR-TR-87-25			5. MONITORING ORGANIZATION REPORT NUMBER(S) AFWAL-TR-87-4114			
6a NAME OF PERFORMING ORGANIZATION University of Dayton Research Institute		6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION Air Force Wright Aeronautical Laboratories Materials Laboratory (AFWAL/MLSE)			
6c ADDRESS (City, State and ZIP Code) 300 College Park Avenue Dayton, OH 45469			7b. ADDRESS (City, State and ZIP Code) Wright-Patterson Air Force Base, OH 45433-6533			
8a NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER F33615-85-C-5094			
8c ADDRESS (City, State and ZIP Code)			10 SOURCE OF FUNDING NOS.			
			PROGRAM ELEMENT NO	PROJECT NO.	TASK NO.	WORK UNIT NO.
11 TITLE (Include Security Classification) SEE OTHER SIDE			62102F	2418	04	41
12 PERSONAL AUTHOR(S) Daniel R. Bowman						
13a TYPE OF REPORT Interim		13b. TIME COVERED FROM 1/86 TO 2/87		14. DATE OF REPORT (Yr., Mo., Day) January 1988		15. PAGE COUNT 21
16 SUPPLEMENTARY NOTATION						
17 COSATI CODES			18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)			
FIELD	GROUP	SUB GR	Damage	Design Loads	ISO Shelter	
1A	06		Easy-Fix	Materials		
1B	13		Tactical Shelters	Airlift		
19 ABSTRACT (Continue on reverse if necessary and identify by block number)  This report documents a program which was conducted to study the feasibility of using an "Easy-Fix" system to redeploy structurally damaged ISO tactical shelters. This system could be used to evacuate structurally damaged non-operational tactical shelters using external helicopter airlift capabilities. Various concepts and material systems were evaluated with respect to size, weight, and cost.						
20 DISTRIBUTION AVAILABILITY OF ABSTRACT UNCLASSIFIED UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS <input type="checkbox"/>			21 ABSTRACT SECURITY CLASSIFICATION Unclassified			
22a NAME OF RESPONSIBLE INDIVIDUAL Robert Urzi			22b TELEPHONE NUMBER (Include Area Code) (513) 255-7483		22c OFFICE SYMBOL AFWAL/MLSE	

DD FORM 1473, 83 APR

EDITION OF 1 JAN 73 IS OBSOLETE.

UNCLASSIFIED  
SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

11. TITLE OF REPORT (Continued)

FEASIBILITY STUDY FOR THE APPLICATION OF AN EASY-FIX METHOD FOR REDEPLOYING  
DAMAGED ISO TACTICAL SHELTERS

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

PREFACE

The effort documented in this report was performed by the University of Dayton Research Institute (UDRI), Dayton, Ohio, under Contract F33615-85-C-5094, "Technical Support for Tactical Shelters," for the Materials Laboratory, Air Force Wright Aeronautical Laboratories, Wright-Patterson Air Force Base, Ohio. Air Force administrative and technical direction was provided by Mr. Robert Urzi, AFWAL/MLSE.

The work described herein was conducted during the period January 1986 to February 1987. Project supervision was provided through the Materials Engineering Division of the University of Dayton Research Institute, with Mr. Dennis Gerdeman as supervisor and Mr. D. Robert Askins as Project Engineer during the overall activities. Technical effort was accomplished by Mr. D. R. Bowman, Applied Mechanics Group, Aerospace Mechanics Division.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



## TABLE OF CONTENTS

SECTION		PAGE
1.0	BACKGROUND/INTRODUCTION	1
2.0	GROUND RULES AND GUIDELINES	1
3.0	STRUCTURAL CONCEPTS	3
4.0	MATERIAL SYSTEMS	7
5.0	STRUCTURAL EVALUATION	10
6.0	SYSTEM WEIGHT	10
7.0	CONCLUSIONS	12

## 1.0 BACKGROUND/INTRODUCTION

Tactical shelters are susceptible to a variety of types of in-service damage. This can result from battle damage, handling/transport damage, and environmental damage, and can be of a structural or functional nature. Structural damage consists of damage of sufficient extent to walls, roof, floor, or frame that transportability of the shelter is jeopardized. EASY-FIX is a method for providing the means to evacuate structurally damaged, non-operational tactical shelters using external airlift capabilities.

The results of the feasibility study reported herein consist of a preliminary investigation to define structural concepts, material systems, and assembly procedures relative to the stated objectives. The concepts were evaluated with respect to size, weight, and cost. The results are summarized and conclusions and recommendations made.

## 2.0 PREMISES AND GUIDELINES

Guidelines used for the ISO EASY-FIX feasibility study are listed below.

- EASY-FIX shelter evacuation will be effected using helicopter airlift with Class 1 slinging provisions per MIL-STD-209F.
- The ISO shelter will not be transported in the expanded mode.
- Shelter air conditioning units will be discarded or pulled into the shelter prior to implementation of EASY-FIX.
- Shelter armor will be removed before effecting EASY-FIX, and will not be in place during the EASY-FIX evacuation.
- Any damaged shelter to which EASY-FIX is applied is no longer a functionally operational shelter, and upon

application there will be no entry into or egress from the shelter.

- No modification to existing shelters for attachment of EASY-FIX structural components will be made.
- Available field personnel will be assumed to possess no specialized mechanical skills or knowledge for evaluating structural integrity.
- There will be no electrical power at the shelter site.
- No special or exotic tools will be required to effect EASY-FIX.
- EASY-FIX concept will be capable of being effected by two persons in one eight-hour period.
- Materials, tools, and capability for making localized structural repairs is not a part of the EASY-FIX concept.
- The weight of the shelter and its contents are assumed to be uniformly distributed over the floor area of the shelter.
- The weight of the individual EASY-FIX structural components shall not exceed 120 pounds to facilitate two-person handling.
- The weight of all EASY-FIX structural members, fittings, and hardware shall not exceed ten percent of the shelter maximum shipping weight.
- The ISO shelter maximum shipping weight is taken as 20,000 pounds.
- EASY-FIX will be designed to be stored with the shelter or with a shelter support group.

### 3.0 STRUCTURAL CONCEPTS

A number of structural concepts were considered, some of which made use of the existing shelter structural members and lifting "eye" bolts. These approaches, however, had inherent disadvantages that are not compatible with the stated premises in Paragraph 2.0. The most important of these disadvantages are:

(1) A detailed assessment of the structural integrity of individual shelter components by on-site personnel is required,

(2) EASY-FIX structural members must be integrated into the undamaged shelter structure through special fittings and attachments,

(3) Bending stresses could be introduced into the EASY-FIX members where attach points, lifting eye, and truss-element force vectors could not be constrained to intersect at a common point, and

(4) System complexity becomes excessive.

Based on these considerations the concept depicted in Figure 1 was selected as being the most simple, versatile, and easy to effect. Structurally, the system reacts the applied loads as a truss. The tubular members form an independent framework at the top of the shelter and react the compressive loads. Tension cables (or rods) are used to transfer the loads resulting from the shelter weight into the tubular framework corner fittings. These cables will attach to corner fittings at the shelter base frame structure. The number of cables and the attach point location along the base frame structure could be varied in accordance with the severity and location of damage to the shelter; however, the kit should be kept as simple as possible to avoid confusion.

If the shelter base frame structure and floor system are severely damaged, additional tubular members and/or cables could be passed through the fork lift tine openings or under the shelter base. Thus, this concept consists of a basket with a stiff rim




Figure 1. EASY-FIX Concept.

at the top that can be used to transport a shelter with varying degrees of damage.

Provisions for helicopter airlift will be similar to those used for the basic shelter. The only difference will be the use of lift rings on the tubular framework corner fittings instead of the shelter lift rings. For stability in the plane of the tubular frame, tension cables or rods connecting the diagonal corners will be installed. Vertical pins will be used to connect the tubular framework corner elbows to the straight tubular frame members. This will prevent out-of-plane warping due to rotation of the tubular frame corner members.

The EASY-FIX concepts provided herein are dependent on access underneath the shelter for placement of support cables or straps to complete the bottom of the basket. If corner jacks are not standard equipment with the ISO shelters, EASY-FIX kits would need to include them, or an alternative would be to include toe jacks for lifting at the forklift hole locations.

#### Design Loads

The design loads for helicopter airlift are defined in Paragraph 5.1.1.1 of MIL-STD-209F. For equipment weighing less than 20,000 pounds, the working load is equal to the maximum shipping weight multiplied by 3.2.\* All slinging components, including the connection and structural members, are required to withstand their proportionate share of this working load without permanent deformation. In addition, they are required to have an ultimate strength not less than 1.5 times the working load.

The loads for an assumed worst case loading condition are depicted in Figure 2. The sling apex is over the center of gravity (assumed to be the geometric center of the shelter). The

---

\*Applies to equipment with a maximum shipping weight to maximum projected frontal area  $>60 \text{ lbs/ft}^2$ . For the shelter under consideration, this ratio equals  $20,000/(20 \times 8) = 125 \text{ lbs/ft}^2$ .




Figure 2. EASY-FIX Loads Diagram.

true angle of each sling leg is taken as 45 degrees from the vertical (the maximum angle permitted by MIL-STD-209F). The total shelter weight is conservatively assumed to be supported by cables attached to the center of the long side of the shelter.

This arrangement results in the most critical buckling load for the 20 foot long tubular compression members. The equivalent static limit design load (working load) for the EASY-FIX system is

$$P_{\text{limit}} = 3.2 \times 20,000 = 64,000 \text{ lb}$$

The corresponding equivalent static ultimate design load is

$$P_{\text{ult}} = 3.2 \times 1.5 \times 20,000 = 96,000 \text{ lb}$$

The working loads are shown in Figure 3. The working and ultimate design loads for the EASY-FIX components are summarized in Table 1.

#### 4.0 MATERIAL SYSTEMS

Four representative material systems for the tubular compression members have been selected for evaluating the feasibility of the EASY-FIX concept. They are A-36 steel, 6061-T6 aluminum alloy, DWAL 20 (a SIC/6061-T6 metal matrix composite produced by DWA Composite Specialties, Inc.), and a high modulus GR/EP system. These systems are not exhaustive of material system possibilities. However, they cover a broad range with respect to weight and cost and provide a good basis for evaluating feasibility.

The EASY-FIX system tension members could be steel, Kevlar, nylon, or fiberglass cable or rod.




Figure 3. Working Loads Summary.

TABLE 1  
DESIGN LOADS

Member	Working Load* (lbs)	Minimum Safety Factor Required	Ultimate Load (lbs)
AB, AC, AD, AE	22,600	5	113,100
BC, DE	-13,900	1.5	-20,900
BE, CD	-30,900	1.5	-46,300
BF, CF, DH, EH	17,900	5	89,400
CG, DG, BI, EI	25,600	5	128,100

\*Working load is equal to maximum shipping weight multiplied by 3.2.

## 5.0 STRUCTURAL EVALUATION

Since the 20 foot long tubular compression members will fail catastrophically when the buckling load is reached, they will be designed using the Euler buckling formula for long columns:

$$P_{cr} = \frac{\pi^2 EI}{l^2}$$

From the loads analysis,  $P_{cr} = 46,300$  lbs for the 20 foot long tubular compression members. Solving Euler's equation for the required stiffness gives

$$(EI)_{req'd} = \frac{P_{cr} l^2}{\pi^2}$$

Using this equation and assuming the members to be thin walled cylindrical tubes yields the results summarized in Table 2. Although for this study the compression tubes are designed strictly as columns, it is possible that eccentricity of the connections at the corner fittings would cause the tubes to carry some bending moment. Therefore, for a production design, the stiffness of the tubes should be increased to provide a safety factor against bending in addition to compression.

## 6.0 SYSTEM WEIGHT

Some perturbation about the cylindrical tube sizes listed in Table 2 would be required for weight optimization of a given material system. However, the weights shown are representative for each material system, and reflects the weight differences to be expected as a function of material system.

Table 2  
ISO Tactical Shelter Easy-Fix Compression Tube Evaluation

Material System	$E_x$ (ksi)	$\sigma_y$ (ksi)	$I_{req}$ (in. <sup>4</sup> )	Dia. (in.)	$t_{wall}$ (in.)	A (in. <sup>2</sup> )	$I_{act}$ (in. <sup>4</sup> )	L/R	$\sigma_{act}$ (ksi)	$\rho$ (lb/in. <sup>3</sup> )	Weight (lb/ft)	Weight Total (pounds)	Cost (\$/lb)	Total Cost (\$)
A-36 Steel	$30 \times 10^3$	36	9.00	6.0	0.188	3.42	14.47	117.	13.53	0.283	11.61	232.	0.45	104.
				7.0	0.094	2.03	12.29	97.5	22.8	0.283	6.89	138.		62.
6061-T6 Al	$10 \times 10^3$	38	27.01	6.0	0.5	8.64	33.20	122.	5.36	0.100	10.37	207.	1.30-1.80	320.
				7.0	0.25	5.3	30.23	100.	8.73	0.1	6.36	127.2		200.
				8.0	0.156	3.85	29.62	86.5	12.02	0.1	4.62	92.4		145.
E-30 GR/EP	$22 \times 10^3$	72	12.28	5.0	0.375	5.45	14.66	146.	8.49	0.06	3.92	78.5		4320.
70% 0°				6.0	0.188	3.42	14.47	117.	13.53	0.06	2.46	49.3	35.75	2710.
30% +45°				7.0	0.125	2.70	15.96	98.7	17.14	0.06	1.94	38.9		2140.
DWAL 20	$18.5 \times 10^3$	65.2	14.6	5.0	0.438	6.27	16.47	148.	7.38	0.09	6.77	135.		5060.
(30 V/O SIC/				6.0	0.25	4.52	18.7	118.	10.25	0.09	4.88	97.6	30-45	3660.
6061-T6 Al)				7.0	0.125	2.70	15.96	98.7	17.14	0.09	2.92	58.3		2190.

Note:  $P_{critical}$  (ultimate) = -46,300 pounds

$L_e$  = 240 in.

Note that to meet the guideline of 120 pound maximum tube weight, wall thickness for a steel tube would have to be less than 0.10 inch. This would not be acceptable because the tube could be easily dented and structurally compromised. Therefore, steel compression tubes cannot be used without exceeding the individual tube weight limitation.

Minimal production cost projection data is available for the DWAL 20 and graphite/epoxy material systems. Best estimates were used to establish a cost range and the median cost was used to project the cost of a fabricated 20 foot long tubular member.

The tension cables (or rods) will be of steel, nylon, fiberglass, or Kevlar. They will be round or flat in cross-section. Based on the maximum ultimate cable loads shown in Table 1 it is anticipated that 1-1/8 to 1-3/8 inch diameter steel cable would be required. Nylon straps would probably be more weight efficient, however, detailed design/analysis of fittings and cables (size and material) was considered beyond the scope of this study.

A cursory analysis of the system weight was made to evaluate feasibility with respect to the study guideline of being less than ten percent of the shelter weight. The assumptions made and the results of the weight analysis are summarized in Table 3. The estimated total system weight for all materials is well within the guidelines for feasibility.

## 7.0 CONCLUSIONS

This investigation resulted in the definition of a structural concept that provides the potential for meeting the EASY-FIX evacuation objective within the constraints established by the study ground rules and guidelines.

Several material systems were evaluated and all, except steel, provide acceptable individual member and total system

TABLE 3  
ISO EASY-FIX SYSTEM WEIGHT

Material System	Compression Tubes	Aluminum Corner Fittings	Nylon Tension Members	Cable Fittings & Miscellaneous	Total Weight
A-36 Steel* 7" tube	367	80	150	490	1087 lbs.
6061-T6 Aluminum 8" tube	259	80	150	490	979 lbs.
DWAL 20 (30 V/O SIC/ 6061-T6 Aluminum) 6-7" tube	207	80	150	490	927 lbs.
E-30 GR/EP 70% 00, 30% ± 450 6" tube	182	80	150	490	902 lbs.

\*Note that the individual tube weight (see Table 2) exceeds the 120 pound guideline.

weights for the shelter under consideration. Consideration of longer and/or heavier shelters could alter this result.

The proposed concept is characterized by simplicity and versatility. Assembly is capable of being accomplished by two persons with no special training or tools required; however, the use of a third person would make erection of the compression tubes much easier.

No major problem areas with respect to implementing this system are expected. Details regarding fitting design, tension member location and attachment, and the optimum number of components for maximizing flexibility require further study. However, these considerations are not expected to affect the conclusion regarding feasibility.