

AD-A194 688


STRUCTURE LIMITS FOR A 30MM ANNULAR PISTON(U) ARMY
BALLISTIC RESEARCH LAB ABERDEEN PROVING GROUND MD
C WATSON MAY 88 BRL-TR-2913


1/1

UNCLASSIFIED

F/G 19/1

NL





AD-A194 688

TECHNICAL REPORT BRL-TR-2913

BRL

1938 - Serving the Army for Fifty Years - 1988

STRUCTURE LIMITS FOR A 30-MM ANNULAR PISTON

CRIS WATSON

MAY 1988

DTIC
ELECTE
JUN 14 1988
CH

APPROVED FOR PUBLIC RELEASE. DISTRIBUTION UNLIMITED.

U.S. ARMY LABORATORY COMMAND

**BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND**

DESTRUCTION NOTICE

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

ADA194688

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) BRL-TR-2913			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION US Army Ballistic Rsch Lab		6b. OFFICE SYMBOL (If applicable) SLCBB-IB		7a. NAME OF MONITORING ORGANIZATION	
6c. ADDRESS (City, State, and ZIP Code) Aberdeen Proving Ground, MD 21005-5066				7b. ADDRESS (City, State, and ZIP Code)	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State, and ZIP Code)				10. SOURCE OF FUNDING NUMBERS	
				PROGRAM ELEMENT NO.	PROJECT NO.
				TASK NO.	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) Structure Limits for a 30-mm Annular Piston					
12. PERSONAL AUTHOR(S) Watson, Cris					
13a. TYPE OF REPORT TR		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day)	
15. PAGE COUNT					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP			
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
The annular injection piston of the 30-mm regenerative liquid propellant gun was subjected to a stress analysis to determine if the existing design could be used in high performance firings. The piston was shown to fail under 558 MPa chamber pressure using finite-element stress analysis. This study concluded that the piston must be redesigned to reduce the unbalanced forces which exist across the thin shell portion of the piston wall before high performance firings with this fixture could be attempted.					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT ☐ UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Cris Watson			22b. TELEPHONE (Include Area Code) (301) 278-6103		22c. OFFICE SYMBOL SLCBB-IB-B

TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES	v
I. INTRODUCTION	1
II. REGENERATIVE LIQUID PROPELLANT GUN	1
III. STRESS ANALYSIS PROCEDURE	3
IV. RESULTS	4
V. CONCLUSION	8
REFERENCES	9
DISTRIBUTION LIST	11



Accession For	
NO. A&I	☒
Distribution/	
Availability	
A-1	

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Basic Regenerative Liquid Propellant Gun (RLPG)	2
2	Annular Piston RLPG	2
3	Static Pressure Loads and Boundary Conditions	4
4	Maximum Effective Stress vs. Chamber Pressure.	5
5	Effective Stress Contours at 558 MPa Chamber Pressure	5
6	Radial Tension Stress Contours at 558 MPa Chamber Pressure	5
7	Radial Compression Stress Contours at 558 MPa Chamber Pressure	6
8	Axial Tension Stress Contours at 558 MPa Chamber Pressure	6
9	Axial Compression Stress Contours at 558 MPa Chamber Pressure	6
10	Hoop Tension Stress Contours at 558 MPa Chamber Pressure	7
11	Hoop Compression Stress Contours at 558 MPa Chamber Pressure	7
12	Undeformed Grid	7
13	Deformed Grid (Enlarged)	8

I. INTRODUCTION

General Electric Ordnance Systems Division (GEOSD) at Pittsfield, MA, under contract to the BRL, has designed and fabricated a 30-mm regenerative liquid propellant gun (RLPG) system. The fixture was installed at the BRL in July, 1984. The fixture is now being used to evaluate liquid propellants and study various features of the RLPG cycle.

To obtain a set of structural and performance limits for the 30-mm RLPG, a finite element analysis was undertaken on the most highly stressed component of the fixture, the annular injection piston. Initial and boundary conditions for the analysis were obtained from both pressure and piston travel records taken from actual firings and interior ballistic simulations.

The information obtained from the analysis will be used to determine if this 30-mm RLPG can be used in the high pressure liquid propellant gun firings. Chamber pressure may be as high as 700 MPa which, because of the differential area piston, may produce up to 1000 MPa in the liquid propellant reservoir.

II. REGENERATIVE LIQUID PROPELLANT GUN

Most studies of the liquid gun propulsion technology have been directed toward the bulk-loaded approach. While the bulk-loaded approach is simpler mechanically, the regenerative technique offers greater control over the ballistic cycle.

The regenerative liquid propellant gun cycle uses a differential area piston to pump liquid propellants into a combustion chamber. Figure 1 illustrates a simple regenerative piston concept that was studied extensively by GEOSD and others.^{1 2} The propellant burns in the combustion chamber, sustaining the pressure which drives the piston. While the simple system shown in Figure 1 is adequate for performing various parametric studies, it is not acceptable for practical systems.

For practical systems, methods must be provided for rapid projectile, propellant, and igniter loading; confinement of the liquid propellant to the reservoir prior to ignition; possibly prepressurization of the liquid propellant to reduce the ignition risk from adiabatic compression of bubbles in the liquid propellant; and a capability for variable charge loading in the case of artillery applications. One approach for satisfying these requirements is a configuration which uses an annular piston similar to that shown in Figure 2.

The 30-mm RLPG at the BRL test facility uses an annular piston to inject a monopropellant into the chamber. The propellant enters the combustion chamber as an annular sheet, where it breaks up into droplets and combusts. The injection is controlled by tapers on the central control rod.

The constant diameter portion of the rod controls the maximum pressure. The charge length may be varied by changing the length of the constant diameter section.




Figure 1. Basic Regenerative Liquid Propellant Gun (RLPG)




Figure 2. Annular Piston RLPG

The RLPG cycle starts with the transducer block forward, resting against the rear of the piston. The piston is supported by a spacer in the forward part of the combustion chamber. As the fill cycle begins, propellant is forced through a check valve in the rod and enters the liquid propellant reservoir. Ullage is removed through a port in the transducer block. Pressure in the reservoir forces the transducer block rearward until it encounters a stopping cone on the central rod. The system is then prepressurized to 7 MPa to reduce the chance of ignition due to adiabatic heating of the remaining ullage. The fixture is then ready to fire. A solid propellant igniter is used to initiate the cycle. As the pressure rises in the combustion chamber due to the igniter, the piston is forced back generating a gap between the piston and the rod. Propellant enters the combustion chamber through this gap where it breaks up and burns. The forward taper of the rod controls the start-up of the cycle. The system approaches a steady state condition as the pressure generated by the burning liquid propellant forces the piston over the constant diameter portion of the central rod. As the piston encounters the rear taper, the injection area decreases causing the liquid propellant pressure to increase, which in turn decelerates the piston. The piston stops when it contacts the face of the transducer block at the rear, ending the cycle.

III. STRESS ANALYSIS PROCEDURE

Stress data was generated using the SAAS-II finite element computer code.³ Applied loads were taken from 30-mm RLPG firing data and appropriately scaled for this analysis. The loads are listed in Table 1. The scaled firing data represents pressures which would be encountered in the higher pressure operating regimes. A quasi-static, steady-state linear analysis was adequate for this problem because the period of mechanical vibration of the piston is an order of magnitude higher than the pressure pulse. Figure 3 shows the location of the static load placement and boundary conditions.

The piston was manufactured of PH13-8MO precipitation-hardened stainless steel hardened to a Rockwell C-scale of 38-42. A summary of the properties of the PH13-8MO stainless steel are given in Table 2.

TABLE 1. Loads Used in the Stress Analysis Calculations

Stress Analysis #	Combustion Chamber Pressure (MPa)	Liquid Reservoir Pressure (MPa)	Grease Pressure (MPa)
1	413	578	462
2	482	675	539
3	551	771	617
4	620	868	694
5	689	964	771
6	558	781	624




Figure 3. Static Pressure Loads and Boundary Conditions

TABLE 2. Material Properties of PH13-8MO Stainless Steel (4)

Modulus of Elasticity	=	205.8 GPa
Poisson's Ratio	=	0.28
Shear Modulus	=	79.9 GPa
Yield Stress (0.2%)	=	1240 MPa

IV. RESULTS

The maximum effective stresses (von Mises criterion) in the piston are plotted in Figure 4. This plot represents the computed maximum effective stresses for six analyses using the scaled pressure data from Table 1. Figure 4 shows that the maximum effective stress exceeds the yield stress, 1240 MPa, when the chamber pressure exceeds 558 MPa.

Figures 5-11 shows effective, radial, axial, and hoop stress contours plotted graphically along the length of the piston. Figures 12 and 13 show the undeformed and deformed grid under 558 MPa chamber pressure. The piston fails at the thin walled section between the piston head and the seal location. Failure in this location results in increased clearance between the seal and piston and promotes leakage.




Figure 4. Maximum Effective Stress vs. Chamber Pressure.




Figure 5. Effective Stress Contours at 558 MPa Chamber Pressure




Figure 6. Radial Tension Stress Contours at 558 MPa Chamber Pressure




Figure 7. Radial Compression Stress Contours
at 558 MPa Chamber Pressure




Figure 8. Axial Tension Stress Contours at 558 MPa Chamber Pressure




Figure 9. Axial Compression Stress Contours at 558 MPa Chamber Pressure




Figure 10. Hoop Tension Stress Contours at 558 MPa Chamber Pressure




Figure 11. Hoop Compression Stress Contours at 558 MPa Chamber Pressure



Figure 12. Undeformed Grid




Figure 13. Deformed Grid (Enlarged 1.6x)

V. CONCLUSION

Results from the stress analysis show that the thin-walled section of the piston will undergo a permanent deformation when the chamber pressure is 558 MPa. The present piston, which was designed for lower operating pressures (350 MPa), is not suitable for a gun system where the chamber pressure exceeds 558 MPa and where unbalanced forces exist across the thin-walled section of the piston. A piston designed for higher operating pressures must reduce these unbalanced forces across the thin-walled section to work.

REFERENCES

1. Mandzy, J., Cushman, P.G., and Magoon, I., "Liquid Propellant Technology Final Report," GEOSD Final Report, Aug 1984.
2. Graham, A.R., "The Regenerative Liquid Propellant Gun," US Army Armament Research and Development Command, Benet Weapons Laboratory, Watervliet, NY, Special Report ARLCB-SP-82022, Nov 82.
3. Sawyer, S.G., "BRLESC Finite Element program for Axisymmetric Plane Strain, and Plane Stress, Orthotropic Solids with Temperature-Dependent Material Properties," BRL Report #1359, Mar 1971.
4. Republic Steel Corp., "Precipitation Hardenable Stainless Steel, PH13-8MO, 15-5 PH, PH15-7MO, 17-4 PH, 17-7 PH," 1975.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	3	Director Benet Weapons Laboratory Armament R&D Center US Army AMCCOM ATTN: SMCAR-LCB-TL E. Conroy A. Graham Watervliet, NY 12189
1	Director Defense Advanced Research Projects Agency ATTN: H. Fair 1400 Wilson Boulevard Arlington, VA 22209	1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-7300
1	HQDA DAMA-ART-M Washington, DC 20310	1	Commander US Army Aviation Research and Development Command ATTN: AMSAV-E 4300 Goodfellow Blvd St. Louis, MO 63120
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001	1	Commander Materials Technology Lab US Army Laboratory Cmd ATTN: SLCMT-MCM-SB M. Levy Watertown, MA 02172-0001
13	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-TSS SMCAR-TDC SMCAR-SCA, B. Brodman R. Yalamanchili SMCAR-AEE-B, D. Downs A. Beardell SMCAR-LCE, N. Slagg SMCAR-AEE-B, W. Quine A. Bracuti J. Lannon SMCAR-CCH, R. Price SMCAR-FSS-A, L. Frauen SMCAR-FSA-S, H. Liberman Picatinny Arsenal, NJ 07806-5000	1	Director US Army Air Mobility Rsch and Development Lab Ames Research Center Moffett Field, CA 94035
		1	Commander US Army Communications Electronics Command ATTN: AMSEL-ED Fort Monmouth, NJ 07703

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander ERADCOM Technical Library ATTN: STET-L Ft. Monmouth, NJ 07703-5301	1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missile Range NM 88002
1	Commander US Army Harry Diamond Labs ATTN: SLCHD-TA-L 2800 Powder Mill Rd Adelphi, MD 20783	1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905
1	Commander US Army Missile Command Rsch, Dev, & Engr Ctr ATTN: AMSMI-RD Redstone Arsenal, AL 35898	1	Commander Armament Rsch & Dev Ctr US Army Armament, Munitions and Chemical Command ATTN: SMCAR-CCS-C, T Hung Picatinny Arsenal, NJ 07806-5000
1	Commander US Army Missile & Space Intelligence Center ATTN: AIAMS-YDL Redstone Arsenal, AL 35898-5500	1	Commandant US Army Field Artillery School ATTN: ATSF-CMW Ft Sill, OK 73503
1	Commander US Army Belvoir R&D Ctr ATTN: STRBE-WC Tech Library (Vault) B-315 Fort Belvoir, VA 22060-5606	1	Commandant US Army Armor Center ATTN: ATSB-CD-MLD Ft Knox, KY 40121
1	Commander US Army Tank Automotive Cmd ATTN: AMSTA-TSL Warren, MI 48397-5000	1	Commander US Army Development and Employment Agency ATTN: MODE-TED-SAB Fort Lewis, WA 98433
1	Commander US Army Research Office ATTN: Tech Library PO Box 12211 Research Triangle Park, NC 27709-2211	1	Commander Naval Surface Weapons Center ATTN: D.A. Wilson, Code G31 Dahlgren, VA 22448-5000
		1	Commander Naval Surface Weapons Center ATTN: Code G33, J. East Dahlgren, VA 22448-5000

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Commander US Naval Surface Weapons Ctr ATTN: O. Dengel K. Thorsted Silver Spring, MD 20902-5000	1	Director Jet Propulsion Lab ATTN: Tech Library 4800 Oak Grove Drive Pasadena, CA 91109
1	Commander Naval Weapons Center China Lake, CA 93555-6001	2	Director National Aeronautics and Space Administration ATTN: MS-603, Tech Lib MS-86, Dr. Povinelli 21000 Brookpark Road Lewis Research Center Cleveland, OH 44135
1	Commander Naval Ordnance Station ATTN: C. Dale Code 5251 Indian Head, MD 20640	1	Director National Aeronautics and Space Administration Manned Spacecraft Center Houston, TX 77058
1	Superintendent Naval Postgraduate School Dept of Mechanical Engr ATTN: Code 1424, Library Monterey, CA 93943	10	Central Intelligence Agency Office of Central Reference Dissemination Branch Room GE-47 HQS Washington, DC 20502
1	AFWL/SUL Kirtland AFB, NM 87117	1	Central Intelligence Agency ATTN: Joseph E. Backofen HQ Room 5F22 Washington, DC 20505
1	Air Force Armament Lab ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000	3	Bell Aerospace Textron ATTN: F. Boorady F. Picirillo A.J. Friona PO Box One Buffalo, NY 14240
1	AFOSR/NA (L. Caveny) Bldg 410 Bolling AFB, DC 20332	1	Calspan Corporation ATTN: Tech Library PO Box 400 Buffalo, NY 14225
1	Commandant USAFAS ATTN: ATSF-TSM-CN Ft Sill, OK 73503-5600		
1	US Bureau of Mines ATTN: R.A. Watson 4800 Forbes Street Pittsburgh, PA 15213		

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
7	General Electric Ord Sys Div ATTN: J. Mandzy, OP43-220 R.E. Mayer H. West M. Bulman R. Pate I. Magoon J. Scudiere 100 Plastics Avenue Pittsfield, MA 01201-3698	1	Science Applications, Inc. ATTN: R. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364
1	General Electric Company Armament Systems Department ATTN: D. Maher Burlington, VT 05401	1	Sundstrand Aviation Operations ATTN: Mr. Owen Briles PO Box 7202 Rockford, IL 61125
1	IITRI ATTN: Library 10 W. 35th St Chicago, IL 60616	1	Veritay Technology, Inc. ATTN: E.B. Fisher 4845 Millersport Highway PO Box 305 East Amherst, NY 14051-0305
1	Olin Chemicals Research ATTN: David Gavin PO Box 586 Cheshire, CT 06410-0586	1	Director Applied Physics Laboratory The Johns Hopkins Univ. Johns Hopkins Road Laurel, MD 20707
2	Olin Corporation ATTN: Victor A. Corso Dr. Ronald L. Dotson PO Box 30-9644 New Haven, CT 06536	2	Director CPIA The Johns Hopkins Univ. ATTN: T. Christian Tech Library Johns Hopkins Road Laurel, MD 20707
1	Paul Gough Associates ATTN: Paul Gough PO Box 1614 Portsmouth, NH 03801	1	U. of Illinois at Chicago ATTN: Professor Sohail Murad Dept of Chemical Engr Box 4348 Chicago, IL 60680
1	Safety Consulting Engr ATTN: Mr. C. James Dahn 5240 Pearl St Rosemont, IL 60018	1	U. of MD at College Park ATTN: Professor Franz Kasler Department of Chemistry College Park, MD 20742

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	U. of Missouri at Columbia ATTN: Professor R. Thompson Department of Chemistry Columbia, MO 65211	3	University of Delaware Department of Chemistry ATTN: Mr. James Cronin Professor Thomas Brill Mr. Peter Spohn Newark, DE 19711
1	U. of Michigan ATTN: Prof. Gerard M. Faeth Dept of Aerospace Engr Ann Arbor, MI 48109-3796		<u>Aberdeen Proving Ground</u> Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen
1	U. of Missouri at Columbia ATTN: Professor F.K. Ross Research Reactor Columbia, MO 65211		Cdr, USATECOM ATTN: AMSTE-TO-F
1	U. of Missouri at Kansas City Department of Physics ATTN: Prof. R.D. Murphy 1110 East 48th Street Kansas City, MO 64110-2499		Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-SPS-IL
1	Pennsylvania State University Dept of Mechanical Engr ATTN: Prof. K. Kuo University Park, PA 16802		
2	Princeton Combustion Rsch Laboratories, Inc. ATTN: N.A. Messina M. Summerfield 475 US Highway One North Monmouth Junction, NJ 08852		
1	University of Arkansas Dept of Chemical Engr ATTN: J. Havens 227 Engineering Building Fayetteville, AR 72701		

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number _____ Date of Report _____
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. How specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Name

Organization

Address

City, State, Zip

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD
ADDRESS

Name

Organization

Address

City, State, Zip

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

----- FOLD HERE -----

Director
US Army Ballistic Research Laboratory
ATTN: DRXBR-OD-ST
Aberdeen Proving Ground, MD 21005-5066




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE: \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
US Army Ballistic Research Laboratory
ATTN: DRXBR-OD-ST
Aberdeen Proving Ground, MD 21005-9989



----- FOLD HERE -----

END

DATED

FILM

8-88

DTIC